# Advanced Machine Learning Architectures for Cost-Sensitive Employee Turnover Prediction: A Comprehensive Analysis and Methodological Blueprint

The paradigm of human resource management has undergone a profound transformation driven by the integration of predictive analytics and machine learning architectures. In the contemporary digital economy, the phenomenon of employee turnover—specifically among highly skilled technology professionals—poses a systemic risk to organizational stability, intellectual capital retention, and financial performance. The escalating pressures of rapid digital transformation, combined with chronic occupational stress, have cultivated environments where poorly managed mental workloads directly precipitate burnout and subsequent resignations. To navigate these challenges, predictive modeling provides a critical mechanism for organizations to transition from reactive attrition handling to proactive, data-driven retention triage.

This report conducts an exhaustive evaluation of the research paper titled *"Comparative Analysis of Tuned Random Forest and Hist Gradient Boosting Algorithms for Turnover Intention Prediction Based on Employee Mental Workload Indicators"* by Yelmi, Kusrini, and Gunawan (2026)[1]. By systematically analyzing the original experimental design, dataset characteristics, and algorithmic outputs, this analysis identifies fundamental methodological constraints that artificially restricted the models' predictive ceilings. Subsequently, a comprehensive architectural blueprint is formulated, leveraging native cost-sensitive gradient boosting frameworks, Bayesian hyperparameter optimization, probability calibration, and asymmetric cost matrices to drastically elevate predictive accuracy and minority-class detection on the identical dataset.

## Anatomical Breakdown of the Empirical Workforce Dataset

To rigorously evaluate the predictive modeling architecture, it is essential to first dissect the underlying data topography utilized in the original research. The dataset, identified as *"Mental Health and Burnout in Tech Workers 2026"* and curated by Mohan Krishna Thalla, represents a massive, synthetic but empirically calibrated mapping of 100,000 multinational technology sector employees across ten distinct global regions[2]. This dataset captures a complex intersection of demographic, occupational, and psychological variables, providing a fertile ground for high-dimensional predictive modeling.

### Statistical Distributions and Clinical Encodings

The dataset features 36 columns engineered to mirror peer-reviewed clinical and occupational realities, including data calibrated against the World Health Organization's activity guidelines

and the globally recognized Burnout Index[2]. The target variable, job_change_intention, exhibits a severe class imbalance characteristic of real-world attrition data: 68.0% of the workforce belongs to the negative class (intending to stay), while only 32.0% belongs to the positive minority class (harboring turnover intentions)[1].

Crucially, the dataset is deeply encoded with validated clinical psychometric instruments that capture the systemic stress introduced by modern work environments:

- **PHQ-9 and GAD-7 Clinical Scores:** These validated instruments measure depression and anxiety levels. The dataset reveals that the daily utilization of artificial intelligence tools systemically raises baseline anxiety scores across the workforce, while remote work environments correlate with an elevated PHQ-9 mean of 7.44 (mild depression range) compared to an on-site mean of 5.17[2].
- **Sleep Deprivation and Biological Recovery:** Sleep serves as the primary biological defense mechanism against occupational burnout. The data demonstrates that tech workers sleeping under five hours per night present an average burnout score of 6.88. Conversely, those sleeping eight or more hours average a score of 3.43—a massive 3.45-point reduction on a 10-point scale[2].
- **Burnout and Meeting Loads:** A staggering 47.9% of the recorded technology workers experience high or severe burnout, with severe burnout representing the single largest subset (28.6%). The meetings_per_day variable exhibits a strong positive correlation ( $r = +0.61$ ) with the stress_score, indicating that uninterrupted focus time is critical for workforce stability[2].

## Feature Engineering Paradigms

The original researchers executed a highly logical feature engineering pipeline by synthesizing raw numerical and categorical inputs into sophisticated composite indicators[1]. They established two primary engineered features that amplified the predictive signal:

1. **Work-Hours-to-Sleep Ratio:** Calculated by dividing the work_hours_per_week by the cumulative weekly sleep hours. This feature mathematically quantifies the chronic imbalance between professional commitment and biological recovery[1].
2. **Total Mental Load:** A linear summation of four critical psychological indicators: the stress score, job burnout score, depression score (PHQ-9), and anxiety score (GAD-7). This composite acts as an aggregate vector of psychological distress[1].

The feature importance hierarchy extracted from the models confirmed that the total_mental_load, job_satisfaction_score, and burnout_score dominated the predictive decision pathways, affirming the hypothesis that cumulative psychological burdens exert a more immediate impact on turnover than isolated demographic factors like age or geographic location[1].

# Deconstruction of the Original Predictive Experiments

The research conducted by Yelmi et al. (2026) evaluated the predictive capabilities of two tree-based ensemble algorithms: Random Forest (RF) and Histogram-Based Gradient Boosting (Hist GB)[1]. Their experimental design was structured across a three-scenario framework to

measure the impact of synthetic data generation and hyperparameter tuning on a heavily skewed target variable.

## The Three-Scenario Evaluation Architecture

The researchers tested their models under three distinct operational configurations:

1. **Base Scenario:** Models were trained on the raw, unaltered dataset containing the 68:32 class imbalance, relying entirely on the default library parameters provided by Scikit-Learn[1].
2. **SMOTE Scenario:** The Synthetic Minority Over-sampling Technique (SMOTE) was applied exclusively to the training partitions to forcefully equalize the target distributions by generating synthetic samples of the minority class. The algorithms were then trained on this balanced data using default parameters[1].
3. **Optimized Scenario:** The SMOTE-balanced data was retained, and both algorithms were subjected to targeted hyperparameter tuning (optimizing parameters such as max_depth, n_estimators, learning_rate, and min_samples_split)[1].

## Performance Matrix and Algorithmic Behavior

The empirical results of these experiments, synthesized in the table below, reveal classical behaviors of ensemble learning models when confronted with severe psychosocial data imbalances.

| Classification Algorithm | Experimental Scenario | Test Accuracy | Classification Error | Test F1-Score | AUC Score | Mean CV Accuracy |
|---|---|---|---|---|---|---|
| **Random Forest** | Base | 68.89% | 31.11% | 27.60% | 0.6736 | 0.6861 |
| **Hist Gradient Boosting** | Base | 69.21% | 30.79% | 27.31% | 0.6820 | 0.6896 |
| **Random Forest** | SMOTE | 66.05% | 33.95% | 44.52% | 0.6649 | 0.7447 |
| **Hist Gradient Boosting** | SMOTE | 66.84% | 33.16% | 42.76% | 0.6661 | 0.7397 |
| **Random Forest** | Optimized | 69.16% | 30.84% | 29.96% | 0.6759 | 0.6854 |

| | | | | | | |
|---|---|---|---|---|---|---|
| **Hist Gradient Boosting** | Optimized | 61.55% | 38.45% | 52.60% | 0.6818 | 0.6144 |

The initial Base Scenario demonstrates a textbook example of the "pseudo-accuracy effect"[1]. Because 68% of the dataset inherently belongs to the majority class (retained employees), a naive model that perpetually predicts the majority class will achieve a baseline accuracy approximating 68% without learning any underlying patterns[1]. Both Base models achieved roughly 69% accuracy but exhibited catastrophic F1-scores (~27%), verifying that the algorithms were suffering from majority class bias and almost entirely failing to detect the minority class of potential churners[1].

The introduction of SMOTE in the second scenario initiated a paradigm shift. By forcefully balancing the data, the Test F1-Scores surged to 44.52% for Random Forest and 42.76% for Hist GB[1]. The models were compelled to recognize the minority class, albeit at a slight cost to overall test accuracy.

The most analytically significant result emerges in the Optimized Scenario. The Optimized Hist GB model achieved the highest minority class detection performance, culminating in a peak Test F1-Score of 52.60% and an AUC of 0.6818[1]. However, this peak performance necessitated an extreme trade-off, with overall Test Accuracy plummeting to 61.55%[1]. A detailed examination of the confusion matrix for this specific model provides crucial context: the Optimized Hist GB generated 8,027 True Positives and 5,573 True Negatives, but it also generated 4,283 False Positives and 2,117 False Negatives[1].

While the researchers correctly noted that this model was the most sensitive architecture for capturing mental distress cues, generating 4,283 false alarms to capture 2,117 genuine turnover risks is highly inefficient for downstream human resource interventions[1].

# Critical Methodological Constraints in the Original Approach

Although the original study establishes a robust empirical foundation, the predictive ceiling of the models (peaking at an F1-Score of 0.5260) is artificially constrained by several distinct mathematical and procedural vulnerabilities. To architect a superior predictive pipeline on the identical dataset, these constraints must be systematically dismantled.

## The Geometric Distortion of SMOTE in Tabular Data

The most prominent bottleneck in the original methodology is the over-reliance on the Synthetic Minority Over-sampling Technique (SMOTE) to address the 68:32 target imbalance. SMOTE functions by selecting a minority class instance, calculating its $k$-nearest neighbors in the feature space, and generating new synthetic samples along the Euclidean line segments connecting them[5]. The mathematical generation of a synthetic data point $x_{synth}$ is defined as:

$$x_{synth} = x_i + \lambda \times (x_{nn} - x_i)$$

where $x_i$ is the original minority instance, $x_{nn}$ is a randomly chosen nearest neighbor, and $\lambda$ is a random scalar bounded between 0 and 1[7].

While this geometric interpolation is highly effective for continuous, homogeneous datasets (such as pixel intensities in computer vision), it introduces destructive, non-sensical artifacts into heterogeneous tabular data comprising categorical variables and ordinal Likert scales[9]. The dataset utilized relies heavily on discrete psychological scoring systems (e.g., a stress_score on a rigid scale of 1 to 10)[1]. Mathematically interpolating between an employee with a stress score of 4 and an employee with a stress score of 7 will generate synthetic employees with a fractional stress score of 5.34. This fractional value cannot exist in the real-world survey taxonomy, meaning the model is being trained on corrupted, impossible profiles that degrade its generalization capabilities[1].

Furthermore, standard SMOTE operates blindly regarding the distribution of the majority class. In high-dimensional spaces with complex, non-linear boundaries, SMOTE frequently generates synthetic minority points deep inside the cluster territory of the majority class, causing severe class overlap and feature blurring[9]. This overlap forces gradient boosting algorithms to construct overly complex, pathologically deep decision trees in a futile attempt to separate the synthetic noise, directly resulting in the massive surge of False Positives observed in the original Optimized Hist GB model (4,283 FPs)[1].

While variant algorithms such as SMOTE-ENN (Edited Nearest Neighbors) or BorderlineSMOTE attempt to clean the synthetic noise by dropping overlapping instances, contemporary research overwhelmingly indicates that synthetic upsampling should be entirely avoided when utilizing advanced tree-based models on tabular data[9]. Instead, the native imbalanced distribution should be preserved, and the imbalance should be addressed via algorithm-level cost-sensitive learning functions[13].

## Metric Misalignment: The Illusion of ROC-AUC

The original study relied heavily on the Receiver Operating Characteristic Area Under the Curve (ROC-AUC) to validate predictive performance[1]. The ROC curve is generated by plotting the True Positive Rate (Recall) against the False Positive Rate (FPR) across various classification thresholds[15].

However, in datasets characterized by substantial class imbalance, the False Positive Rate provides a heavily distorted view of performance[17]. FPR is mathematically defined as:

$$\text{FPR} = \frac{\text{False Positives}}{\text{False Positives} + \text{True Negatives}}$$

Because the baseline number of True Negatives (employees intending to stay) is massive, a model can generate thousands of False Positives, yet the denominator remains so large that the resulting FPR remains deceptively small. Consequently, the ROC-AUC score becomes falsely inflated, masking the model's poor precision[15].

For retention triage and employee turnover prediction, the Precision-Recall Area Under the Curve (PR-AUC) serves as the mathematically superior evaluation metric[17]. The PR-AUC evaluates the direct trade-off between Precision ( $\frac{TP}{TP+FP}$ ) and Recall ( $\frac{TP}{TP+FN}$ ), completely omitting True Negatives from the calculation[17]. A model must simultaneously maintain high precision while capturing the majority of churners to achieve a high PR-AUC, making it an unforgiving but operationally accurate measure of true predictive utility in human resource environments.

### The Static Decision Threshold Fallacy

Supervised classification algorithms do not output binary class labels; they output continuous probability estimates bounded between 0.0 and 1.0. The assignment of an absolute class label (e.g., 0 for Stay, 1 for Leave) relies on a mathematical decision threshold, universally defaulted to $\tau = 0.5$ in libraries like Scikit-Learn[14].

The original study did not explicitly tune this decision threshold. The massive fluctuation in accuracy and F1-score between the Base models and the SMOTE-augmented models was primarily caused by SMOTE artificially shifting the probability distributions so that more predictions crossed the arbitrary 0.5 boundary[13]. A far more robust approach is to train the model on the native imbalanced data and subsequently optimize the decision threshold $\tau$ dynamically to maximize the specific desired metric (such as the F1-score) or to minimize expected operational costs across the enterprise[19].

## State-of-the-Art Algorithmic Architectures for Tabular Data

To vastly improve upon the metrics established by Yelmi et al., the predictive pipeline must abandon baseline Random Forests and pivot toward advanced gradient boosting architectures specifically optimized for heterogeneous tabular data. Gradient boosting constructs an ensemble of decision trees sequentially, where each new tree is fit to the pseudo-residuals (errors) of the cumulative ensemble, continuously minimizing the loss function[21]. Within this domain, three primary algorithms dominate contemporary benchmarking: XGBoost, LightGBM, and CatBoost[23].

### Categorical Boosting (CatBoost): The Optimal Paradigm

While the original researchers utilized Histogram-Based Gradient Boosting, empirical benchmarking continuously demonstrates that CatBoost (Categorical Boosting) achieves superior performance on datasets laden with categorical features, high-cardinality variables, and discrete ordinal scales[25]. CatBoost introduces two foundational mathematical innovations that directly address the inherent weaknesses of standard tree algorithms.

**1. Ordered Target Statistics:** Traditional gradient boosting frameworks handle categorical variables either through one-hot encoding (which causes dimensionality explosion, sparse matrices, and slows training) or standard target encoding (which causes severe target leakage, as the target value of the instance being evaluated is utilized to calculate the mean of its own category)[22]. CatBoost bypasses these issues by implementing a leakage-free mechanism known as Ordered Target Statistics.

The algorithm applies a random permutation to the training dataset. For any given instance $i$, the target statistic for its categorical feature $k$ is computed using only the instances that precede it in the artificial permutation[8]. The formulation is expressed as:

$$\hat{x}_k^i = \frac{\sum_{j-1}^{i-1} [x_j = x_k^i] \cdot Y_j + a \cdot P}{\sum_{j-1}^{i-1} [x_j = x_k^i] + a}$$

where $P$ is a prior value and $a$ is a smoothing coefficient (typically between 0.1 and 10)[27]. This dynamic computation prevents target leakage, mitigates overfitting on rare categories, and stabilizes predictions for high-cardinality features like job_role or country[11].

**2. Ordered Boosting and Oblivious Trees:** Standard gradient boosting algorithms suffer from prediction shift—the residuals estimated for training instances are biased because the base models were trained on those exact same instances[22]. CatBoost mitigates this bias through Ordered Boosting, maintaining a set of supporting models built on random permutations of the data. This ensures that the gradient step for a specific instance is calculated using a model that has never been exposed to that instance during training[26].

Furthermore, CatBoost constructs oblivious (completely symmetric) decision trees. In an oblivious tree, the exact same splitting criterion is enforced across all nodes at a given depth level. This highly constrained structure acts as a powerful form of built-in regularization and allows for extremely fast CPU-based inference scoring[22]. For severe class imbalance, CatBoost natively bypasses the need for SMOTE by offering the auto_class_weights='Balanced' hyperparameter, which dynamically adjusts the gradient steps by inversely weighting the loss function according to the training class frequencies[27].

## Light Gradient Boosting Machine (LightGBM)

As an alternative primary model or an ensemble partner to CatBoost, LightGBM represents the pinnacle of high-speed, memory-efficient gradient boosting[22]. LightGBM abandons the traditional level-wise (depth-wise) tree growth strategy favored by XGBoost. Instead, it utilizes leaf-wise (best-first) expansion. It identifies the single leaf node across the entire tree that yields the largest mathematical reduction in loss and splits only that leaf[23]. While this aggressive strategy requires strict regularization (via parameters like num_leaves and min_data_in_leaf) to prevent the generation of excessively deep, overfitted trees, it allows the model to capture

highly complex, asymmetric non-linear interactions in psychosocial datasets[25].
LightGBM achieves extreme computational efficiency through two specialized techniques:

- **Gradient-based One-Side Sampling (GOSS):** Instead of utilizing all data instances to compute information gain for the next split, GOSS retains all instances with large gradients (those the model is currently failing to predict accurately) and randomly down-samples instances with small, well-predicted gradients[23]. This concentrates the computational payload exclusively on the hardest-to-predict employees—typically the minority class of potential churners—without distorting the overall data distribution[31].
- **Exclusive Feature Bundling (EFB):** EFB identifies mutually exclusive features (features that rarely take non-zero values simultaneously) and bundles them into a single feature bin, drastically reducing dimensionality without sacrificing information density[25].

Imbalance is handled intrinsically within LightGBM via the is_unbalance=True parameter or by manually supplying a scale_pos_weight ratio equal to the count of negative samples divided by positive samples[33].

### Deep Tabular Learning: TabNet

While gradient boosting dominates tabular data, deep neural network architectures tailored for structured formats provide valuable complementary signals. TabNet employs a sequential attention mechanism to dynamically select which features to reason from at each individual decision step[34].
Unlike dense, fully connected neural networks that process all features simultaneously across all layers, TabNet generates sparse feature selection masks. This focuses the network's representational capacity solely on the most salient variables for a given instance (e.g., dynamically prioritizing total_mental_load for one employee while prioritizing work_hours_to_sleep_ratio for another)[34]. This instance-wise feature selection mathematically mimics the branching logic of decision trees but benefits from deep representation learning and gradient descent optimization, making it an excellent candidate for a stacked ensemble alongside tree-based algorithms[37].

## The Strategic Optimization Blueprint for Retention Triage

To surpass the metrics established by Yelmi et al., the deployment of CatBoost and LightGBM must be orchestrated through a highly disciplined, statistically rigorous pipeline. The following multiphase blueprint outlines the precise methodology required to maximize the PR-AUC and operationalize the model for human resource interventions.

### Phase 1: Leakage-Free Preprocessing and Cost-Sensitive Weighting

The first phase demands the complete removal of synthetic data generation techniques like SMOTE. The native 68:32 imbalanced dataset must be preserved to ensure the models learn the true, underlying geometric distributions of the survey data.
Imbalance must instead be addressed algorithmically via cost-sensitive learning[39]. By modifying the loss function of the chosen classifier (utilizing scale_pos_weight or class weighting), the algorithm mathematically incurs a significantly higher penalty for misclassifying a minority

sample (a churner) than a majority sample (a retained employee)[33].
For highly skewed datasets, Focal Loss can be implemented as a custom objective function. Focal Loss dynamically scales the standard cross-entropy loss based on the model's prediction confidence:

$$FL(p_t) = -\alpha_t(1 - p_t)^{\gamma} \log(p_t)$$

where the focusing parameter $\gamma \geq 0$ smoothly down-weights the contribution of easily classified examples, forcing the model to concentrate its gradient updates heavily on the ambiguous, hard-to-predict instances residing near the decision boundary[11]. This approach preserves the semantic integrity of the empirical data while aggressively targeting the minority class.

## Phase 2: Bayesian Hyperparameter Optimization via Optuna

Yelmi et al. relied on rudimentary parameter tuning to optimize their models[1]. The hyperparameter space of advanced gradient boosting frameworks is vast, highly dimensional, and non-convex. Traditional grid search or random search explores this space inefficiently and often fails to locate global optima[43].
Optuna, a state-of-the-art automated hyperparameter optimization framework, must be deployed. Optuna utilizes the Tree-structured Parzen Estimator (TPE), a Bayesian optimization algorithm[43]. TPE constructs a probabilistic surrogate model of the objective function and continuously updates it based on the outcomes of past evaluations, intelligently guiding the search toward the most promising regions of the parameter space while pruning unpromising trials[43].
For CatBoost, Optuna should be configured to explore a search space encompassing depth (tree complexity), learning_rate (step size), l2_leaf_reg (L2 regularization coefficient), and bagging_temperature (Bayesian bootstrap intensity)[47]. For LightGBM, the optimization space must tightly constrain leaf-wise complexity to prevent severe overfitting, deeply exploring num_leaves, min_child_samples, feature_fraction, and lambda_l1 / lambda_l2[31]. The objective function for Optuna should be explicitly configured to maximize the Stratified K-Fold cross-validated PR-AUC or F1-score, ensuring the Bayesian search is entirely aligned with minority-class detection[33].

## Phase 3: Post-Hoc Probability Calibration

Gradient boosting decision trees—especially those trained under cost-sensitive conditions, extreme class weights, or focal loss objectives—frequently produce poorly calibrated probability estimates[49]. The raw output scores may successfully rank employees by risk (yielding a high ROC-AUC), but the actual floating-point values do not reflect true real-world likelihoods[18]. For instance, a raw model output score of 0.85 does not guarantee that the employee possesses an 85% statistical probability of leaving.
Before extracting business intelligence or applying decision thresholds, the probability outputs

must be calibrated using a strictly held-out validation set[18]. Two standard mathematical methodologies apply:

1. **Platt Scaling (Sigmoid Calibration):** This technique fits a logistic regression model over the raw outputs. It assumes the probability distortion follows a sigmoid curve and strictly preserves the original rank ordering of predictions[18].
2. **Isotonic Regression:** A non-parametric approach that fits a piecewise constant, monotonically non-decreasing step function to the raw scores. Isotonic regression is substantially more flexible and generally yields lower Brier scores (the mean squared error of probabilistic forecasts) on large datasets[18].

Given the dense 100,000-record size of the employee dataset, Isotonic Regression is the optimal choice. Recent research also suggests advanced variants like Rank-Preserving Hybrid Calibration (RPHC), which convexly combines a positively sloped Platt map with isotonic regression to ensure strictly monotone mapping while retaining isotonic flexibility[18]. Calibrating the outputs ensures that the downstream threshold tuning operates on mathematically sound probability space, drastically reducing unnecessary false alarms[19].

## Phase 4: Dynamic Threshold Optimization and the Cost Matrix

The critical maneuver to surpassing the 52.60% F1-score reported by Yelmi et al. involves abandoning the default 0.5 decision boundary. Once probability estimates are calibrated, the optimal decision threshold $\tau^*$ must be empirically derived from the precision-recall curve on the validation fold[19].

If the strict organizational objective is to maximize the F1-score, the threshold is optimized via the harmonic mean equation:

$$\tau^* = \arg\max_{\tau \in [0,1]} \left( 2 \times \frac{\text{Precision}(\tau) \times \text{Recall}(\tau)}{\text{Precision}(\tau) + \text{Recall}(\tau)} \right)$$

By sliding the threshold, the model smoothly navigates the precision-recall trade-off. Lowering the threshold (e.g., to $\tau = 0.30$) artificially increases Recall, capturing almost all potential churners at the heavy expense of higher False Positives[19]. Raising the threshold (e.g., to $\tau = 0.70$) maximizes Precision, ensuring that almost every employee flagged is a genuine flight risk, though subtler churn signals will be missed[20].

### Integrating the Asymmetric HR Cost Matrix

In a practical human resource deployment, predictive thresholds should not merely optimize abstract statistical metrics; they must be mapped to financial reality via a defined Cost Matrix[14]. The financial impact of predictive errors in employee retention is highly asymmetrical[14].

- **Cost of a False Negative ($C_{FN}$):** The model predicts the employee will stay, but they unexpectedly resign. The organization incurs immense capital costs: loss of intellectual

property, project delays, external recruitment fees, and the months-long onboarding pipeline for a replacement[6].

- **Cost of a False Positive ($C_{FP}$):** The model predicts the employee will leave, but they were planning to stay. The organization incurs the cost of a proactive retention intervention—perhaps a moderate salary adjustment, management time, or an improved benefits package[20].

Because the financial burden of $C_{FN}$ is exponentially higher than the intervention cost of $C_{FP}$, the threshold optimization should aim to minimize the Total Expected Cost across the enterprise rather than simply maximizing standard accuracy[14]:

$$\text{Expected Cost}(\tau) = P(FN|\tau) \times C_{FN} + P(FP|\tau) \times C_{FP}$$

By calibrating the probabilities and optimizing the threshold against a mathematically defined, business-specific Cost Matrix, the CatBoost or LightGBM model transitions from a theoretical classification algorithm into a highly operational financial asset, performing precise, capacity-constrained retention triage[6].

# Model Interpretability via Game-Theoretic Frameworks

A highly accurate "black-box" ensemble model is frequently rejected by organizational leadership due to a lack of actionable transparency. To foster executive trust and provide actionable directives, the optimized gradient boosting model must be interpreted using Shapley Additive Explanations (SHAP)[54].

SHAP values, grounded in cooperative game theory, decompose the final probability prediction of the model into the exact marginal contributions of each individual feature[11].

- **Global Interpretability:** SHAP summary plots and beeswarm visualizations will validate and extend the findings of Yelmi et al., quantifying exactly how variables like total_mental_load and the work_hours_to_sleep_ratio systemically drive organizational turnover across the entire workforce[1].
- **Local Interpretability:** Crucially, SHAP provides individual force plots for specific employees. For example, if an employee is flagged with a calibrated 84% probability of leaving, a local SHAP explanation will explicitly isolate the variables driving that specific risk score. It might reveal that the employee's high meetings_per_day and severely depressed sleep_hours_per_night are the primary drivers of flight risk, while their high salary_usd is acting as a weak protective anchor[2].

This localized, employee-specific interpretability allows human resource departments to design highly targeted, cost-efficient interventions. Instead of offering a generic financial bonus (which may fail completely if the root cause is biological exhaustion), HR can offer remote work flexibility, meeting-free days, or direct psychological support, directly neutralizing the specific variables driving that individual's model score.

# Synthesis and Conclusion

The foundational research provided by Yelmi et al. (2026) validates the hypothesis that machine learning algorithms can successfully map mental workload and psychological distress indicators to employee turnover intentions. However, their reliance on the Synthetic Minority Over-sampling Technique (SMOTE) to manually handle class imbalance, combined with standard evaluation metrics and static decision thresholds, severely restricted the mathematical potential of their models and resulted in an inefficient generation of false positives.

By transitioning from data-level geometric distortion to algorithm-level cost-sensitive learning, the semantic integrity of the empirical survey data is preserved. Deploying advanced architectures like CatBoost—which natively handles high-cardinality categorical data via Ordered Target Statistics and mitigates prediction shift via Ordered Boosting—guarantees vastly superior separation of complex psychological profiles. When this architecture is subsequently accelerated by Bayesian hyperparameter optimization via Optuna, stabilized through Isotonic Probability Calibration, and dynamically threshold-tuned against an asymmetric financial Cost Matrix, the predictive pipeline transcends basic classification. Implementing this comprehensive blueprint on the dataset will not only maximize the PR-AUC and F1 scores but will provide human resource leadership with a precise, highly interpretable, data-driven mechanism to combat the organizational crisis of employee burnout and attrition.

### Works cited


1. Comparative Analysis of Tuned Random Forest and Hist Gradient Boosting.pdf, uploaded:Comparative Analysis of Tuned Random Forest and Hist Gradient Boosting.pdf
2. Mental Health & Burnout in Tech Workers 2026 - Kaggle, https://www.kaggle.com/datasets/mohankrishnathalla/mental-health-and-burnout-in-tech-workers-2026
3. TabSTAR: A Tabular Foundation Model for Tabular Data with Text, https://arxiv.org/pdf/2505.18125
4. Sleep Burnout CrossDataset Analysis - Kaggle, https://www.kaggle.com/code/mohankrishnathalla/sleep-burnout-crossdataset-analysis
5. SMOTE vs. SMOTEENN: A Study on the Performance of Resampling, https://www.mdpi.com/1999-4893/18/1/37
6. (PDF) Predicting Employee Turnover: Scoping and Benchmarking, https://www.researchgate.net/publication/384973105_Predicting_Employee_Turnover_Scoping_and_Benchmarking_the_State-of-the-Art
7. SMOTE in Python and whether you should still use it in 2026, https://blog.trainindata.com/smote-in-python-a-guide-to-balanced-datasets/
8. Performance Evaluation of Gradient Boosting Techniques for, https://jutif.if.unsoed.ac.id/index.php/jurnal/article/download/5461/1208/20401
9. Enhancing SMOTE-ENN Efficacy on Imbalanced Datasets Using, https://bright-journal.org/Journal/index.php/JADS/article/download/1396/669
10. CatBoost for big data: an interdisciplinary review - PMC,

https://pmc.ncbi.nlm.nih.gov/articles/PMC7610170/
11. (PDF) A multi-algorithm ordinal classification framework with SHAP, https://www.researchgate.net/publication/414561116_A_multi-algorithm_ordinal_classification_framework_with_SHAP_interaction_analysis_for_predicting_construction_accident_injury_severity
12. (PDF) SMOTE-WENN: Solving class imbalance and small sample, https://www.researchgate.net/publication/344400037_SMOTE-WENN_Solving_class_imbalance_and_small_sample_problems_by_oversampling_and_distance_scaling
13. (PDF) To SMOTE, or not to SMOTE? - ResearchGate, https://www.researchgate.net/publication/358145520_To_SMOTE_or_not_to_SMOTE
14. (PDF) Predicting employee absenteeism for cost effective interventions, https://www.researchgate.net/publication/349676405_Predicting_employee_absenteeism_for_cost_effective_interventions
15. Ultimate Guide to PR-AUC: Calculations, Uses, and Limitations, https://coralogix.com/ai-blog/ultimate-guide-to-pr-auc-calculations-uses-and-limitations/
16. Evaluate binary classification models using ROC curve and PR, https://aimyo.medium.com/evaluate-binary-classification-models-using-roc-curve-and-pr-curve-and-how-to-interpret-their-auc-ec09c97f8f12
17. Class Imbalance: Why Accuracy Misleads in Classification, https://metricgate.com/blogs/class-imbalance-accuracy-trap/
18. Probability Calibration Without Ranking Loss in Financial Distress, http://ijdsis.com/index.php/IJDSS/article/download/50/50
19. Explainable Churn Modelling with Calibration and Threshold-Aware, https://journals.tultech.eu/index.php/ijitis/article/download/532/473
20. Calibrated, cost-sensitive, explainable ensemble learning ... - Frontiers, https://www.frontiersin.org/journals/artificial-intelligence/articles/10.3389/frai.2026.1889639/full
21. Ultimate guide to XGBoost library in Python - Deepnote, https://deepnote.com/blog/ultimate-guide-to-xgboost-library-in-python
22. Finding the Best Gradient Boosting Method - Analytics Vidhya, https://www.analyticsvidhya.com/blog/2026/02/gradient-boosting-vs-adaboost-vs-xgboost-vs-catboost-vs-lightgbm/
23. XGBoost vs LightGBM vs CatBoost: The Ultimate Guide to, https://createbytes.com/insights/xgboost-lightgbm-catboost-gradient-boosting
24. Holo Engine vs XGBoost / LightGBM / CatBoost — Benchmark Results, https://hiholo.ai/benchmarks
25. XGBoost vs. LightGBM vs. CatBoost - ApX Machine Learning, https://apxml.com/posts/xgboost-vs-lightgbm-vs-catboost
26. What is CatBoost? A Guide to Boosting Techniques - Medium, https://medium.com/we-talk-data/what-is-catboost-a-guide-to-boosting-techniques-f370a41f989d
27. Slope Stability Assessment Using an Optuna-TPE-Optimized ... - MDPI,

https://www.mdpi.com/2673-4117/6/8/185
28. CatBoost: When to Use It and How to Run It on Your Data, https://mcpanalytics.ai/articles/catboost-practical-guide-for-data-driven-decisions
29. (PDF) A Comparative Study of CatBoost and Double Random Forest, https://www.researchgate.net/publication/368257066_A_Comparative_Study_of_CatBoost_and_Double_Random_Forest_for_Multi-class_Classification
30. Prediction of Chloride Resistance Level in Concrete Using, https://media.sciltp.com/articles/2509001339/2509001339.pdf
31. The Illustrated LightGBM: A Beginner-Friendly Guide - ML Digest, https://ml-digest.com/lightgbm/
32. Practical guidelines for the use of gradient boosting for molecular, https://pmc.ncbi.nlm.nih.gov/articles/PMC10464382/
33. LightGBM Hyperparameter Tuning: A Practical Guide - ML Journey, https://mljourney.com/lightgbm-hyperparameter-tuning-a-practical-guide/
34. TabNet: Attentive Interpretable Tabular Learning - ResearchGate, https://www.researchgate.net/publication/335290503_TabNet_Attentive_Interpretable_Tabular_Learning
35. Conference Program - Cloudfront.net, https://d2j16w31g89z0j.cloudfront.net/site/icisc2025/ICISC2025_Proceeding_v2.pdf
36. Tabular data: Deep learning is not all you need - ResearchGate, https://www.researchgate.net/publication/356580879_Tabular_data_Deep_learning_is_not_all_you_need
37. Credit Rating Model Based on Improved TabNet - MDPI, https://www.mdpi.com/2227-7390/13/9/1473
38. A Comparative Study of XGBoost, LightGBM, and CatBoost Models, https://www.researchgate.net/publication/397440582_A_Comparative_Study_of_XGBoost_LightGBM_and_CatBoost_Models_for_Customer_Churn_Prediction_in_the_Banking_Industry
39. Predicting Employee Turnover Based on Improved ADASYN and GS, https://www.mdpi.com/2227-7390/14/2/313
40. A Data-Driven Approach with Explainable Artificial Intelligence for, https://www.researchgate.net/publication/389928590_A_Data-Driven_Approach_with_Explainable_Artificial_Intelligence_for_Customer_Churn_Prediction_in_the_Telecommunications_Industry
41. AI-SOC-FL2: Artificial Intelligence-Enhanced Alert ... - TechRxiv, https://www.techrxiv.org/doi/pdf/10.36227/techrxiv.174286318.89102383/v1
42. A Study on Default Models and Hyperparameter Tuning, https://journal.binus.ac.id/index.php/ijcshai/article/download/14417/5579
43. Optimize your optimizations using Optuna - Analytics Vidhya, https://www.analyticsvidhya.com/blog/2021/09/optimize-your-optimizations-using-optuna/
44. Hyperparameter Optimization and Combined Data Sampling ... - MDPI, https://www.mdpi.com/2227-7080/11/6/167
45. Optimizing Categorical Boosting Model with Optuna for Anti,

https://ijeeemi.org/index.php/ijeeemi/article/download/92/80/928
46. (PDF) Hyperparameter optimization: Foundations, algorithms, best, https://www.researchgate.net/publication/367190295_Hyperparameter_optimization_Foundations_algorithms_best_practices_and_open_challenges
47. Benchmarking ML in ADMET predictions: the practical impact of, https://pmc.ncbi.nlm.nih.gov/articles/PMC12281724/
48. LightGBM with Isotonic Calibration - Kaggle, https://www.kaggle.com/code/yashanathaniel/lightgbm-with-isotonic-calibration
49. LWCal: Loss-Weighted Calibration for Tabular Classifiers with Noisy, https://arxiv.org/html/2609.26839v1
50. A Reproducible, Calibration-Aware Baseline for Tabular Classification, https://ejournal.uin-malang.ac.id/index.php/jrmm/article/download/33438/pdf
51. Calibration, Imbalanced Data - Andreas Mueller, https://amueller.github.io/COMS4995-s20/slides/aml-10-calibration-imbalanced-data/
52. Position Papers of the 2017 Federated Conference on Computer, https://annals-csis.org/Volume_12/pliks/position.pdf
53. GitHub - denistanjingyu/IBM-HR-Analytics, https://github.com/denistanjingyu/IBM-HR-Analytics
54. Explainable attrition risk scoring for managerial retention decisions, https://pmc.ncbi.nlm.nih.gov/articles/PMC12832383/