



National University of Computer & Emerging Sciences, Karachi
Computer Science Department
Fall 2022, Lab Manual - 04



Course Code: CL-2005	Course : Database Systems Lab
Instructor(s) :	Erum Shaheen,Mafaza Mohi,Ulya Seerat,Amin

Contents:

1. Groups of Data(Group by, Having)
2. Sub Queries(Single Row, Multiple and correlated)
3. Sub Queries and DML
4. Tasks

Group By Statement:

The GROUP BY statement group's rows that have the same values into summary rows, like "find the number of customers in each country".

The GROUP BY statement is often used with aggregate functions (COUNT, MAX, MIN, SUM, AVG) to group the result-set by one or more columns.

Group by Syntax

```
SELECT column_name(s)
FROM table_name
GROUP BY column_name(s)
```

Group By:

```
SELECT
    AVG(salary) as "average_salary"
FROM
    employees
GROUP BY Department_id
```

Sample Output:

[illegible]

Group by (Having)

HAVING Clause is used with GROUP BY Clause to restrict the groups of returned rows where condition is TRUE.

Syntax:

```
SELECT expression1, expression2, ... expression_n,  
    aggregate_function (aggregate_expression)  
FROM tables  
WHERE conditions  
GROUP BY expression1, expression2, ... expression_n  
HAVING having_condition;
```

HAVING Example: (with GROUP BY SUM function)

```
SELECT Department_ID,  
    SUM(salary) AS "TOTAL SALARY"  
FROM employees  
GROUP BY Department_ID  
HAVING SUM(salary) < 15000;
```

HAVING Example: (with GROUP BY MIN function)

```
SELECT Department_ID,  
    MIN(salary) AS "Lowest salary"  
FROM employees  
GROUP BY Department_ID  
HAVING MIN(salary) < 15000;
```

Sample Output:

	DEPARTMENT_ID	Lowest salary
1	100	6900
2	30	2500
3	(null)	7000
4	20	6000
5	70	10000
6	110	8300
7	50	2100
8	80	6100
9	40	6500
10	60	4200
11	10	4400

HAVING Example: (with GROUP BY MAX function)

```
SELECT Department_ID,
MAX(salary) AS "Highest salary"
FROM employees
GROUP BY Department_ID
HAVING MAX(salary) > 3000;
```

Sample Output:

	DEPARTMENT_ID	Highest salary
1	100	12008
2	30	11000
3	(null)	7000
4	90	24000
5	20	13000
6	70	10000
7	110	12008
8	50	8200
9	80	14000
10	40	6500
11	60	9000
12	10	4400

Sub Queries:

A Subquery is a query within another SQL query and embedded within the WHERE clause.

Important Rule:

- A subquery can be placed in a number of SQL clauses like WHERE clause, FROM clause, HAVING clause.
- You can use Subquery with SELECT, UPDATE, INSERT, DELETE statements along with the operators like =, <, >, >=, <=, IN, BETWEEN, etc.

- A subquery is a query within another query. The outer query is known as the main query, and the inner query is known as a subquery.
- Subqueries are on the right side of the comparison operator.
- A subquery is enclosed in parentheses.
- In the Subquery, **ORDER BY** command cannot be used. But **GROUP BY** command can be used to perform the same function as **ORDER BY** command.

NOTE:

Subqueries are useful when a query is based on unknown values.

Sub Queries with SELECT Statement:**Syntax:**

```
SELECT column_name
FROM table_name
WHERE column_name expression operator
( SELECT column_name from table_name WHERE ... );
```

Types of Subqueries:

Single Row Sub Query: Sub query which returns single row output. They mark the usage of single row comparison operators, when used in WHERE conditions.

Multiple row sub query: Sub query returning multiple row output. They make use of multiple row comparison operators like IN, ANY, ALL. There can be sub queries returning multiple columns also.

Single Row Sub Queries:

- Return only one row
- Use single-row comparison operators

Operator	Meaning
=	Equal to
>	Greater than
>=	Greater than or equal to
<	Less than
<=	Less than or equal to
<> , !=	Not equal to

```
SELECT First_Name, Job_ID FROM Employees WHERE job_ID = ( SELECT
job_ID FROM JOBS WHERE JOB_ID='PU_CLERK' );
```

Sample Output:

	FIRST_NAME	JOB_ID
1	Alexander	PU_CLERK
2	Shelli	PU_CLERK
3	Sigal	PU_CLERK
4	Guy	PU_CLERK
5	Karen	PU_CLERK

Single Row Functions:

Finds the employees who have the highest salary:

```
SELECT
    employee_id, first_name, last_name, salary
FROM
    employees
WHERE
    salary = (SELECT
        MAX(salary)
    FROM
        employees)
```

Sample Output:

	EMPLOYEE_ID	FIRST_NAME	LAST_NAME	SALARY
1	100	Steven	King	24000

Finds all employees who salaries are greater than the average salary of all employees:

```
SELECT
    employee_id, first_name, last_name, salary
FROM
    employees
WHERE
    salary > (SELECT
        AVG(salary)
    FROM
        employees)
```

Sample Output:

	EMPLOYEE_ID	FIRST_NAME	LAST_NAME	SALARY
1	100	Steven	King	24000
2	101	Neena	Kochhar	17000
3	102	Lex	De Haan	17000
4	103	Alexander	Hunold	9000
5	108	Nancy	Greenberg	12008
6	109	Daniel	Faviet	9000
7	110	John	Chen	8200
8	111	Ismael	Sciarra	7700
9	112	Jose Manuel	Urman	7800
10	113	Luis	Popp	6900

Multiple row sub query:

Return more than one row

- Use multiple-row comparison operators
 - [$>$ ALL] More than the highest value returned by the subquery
 - [$<$ ALL] Less than the lowest value returned by the subquery
 - [$<$ ANY] Less than the highest value returned by the subquery
 - [$>$ ANY] More than the lowest value returned by the subquery
 - [$=$ ANY] Equal to any value returned by the subquery (same as IN)

IN: Show the name and dept_ID of all employees having location_ID=1700

```
SELECT first_name, department_id
FROM employees
WHERE department_id IN (SELECT Department_id
                        FROM departments
                        WHERE LOCATION_ID = 1700)
```

Sample Output:

	FIRST_NAME	DEPARTMENT_ID
1	Shelli	30
2	John	100
3	Karen	30
4	Lex	90
5	Daniel	100
6	William	110
7	Nancy	100
8	Shelley	110
9	Guy	30
10	Alexander	30

ANY:

```
SELECT employee_ID, First_Name, job_ID FROM EMPLOYEES WHERE
SALARY < ANY
( SELECT salary FROM EMPLOYEES WHERE JOB_ID = 'PU_CLERK' );
```

Sample Output:

	EMPLOYEE_ID	FIRST_NAME	JOB_ID
1	132 TJ		ST_CLERK
2	128 Steven		ST_CLERK
3	136 Hazel		ST_CLERK
4	127 James		ST_CLERK
5	135 Ki		ST_CLERK
6	119 Karen		PU_CLERK
7	131 James		ST_CLERK
8	140 Joshua		ST_CLERK
9	144 Peter		ST_CLERK
10	182 Martha		SH_CLERK

ALL:

```
SELECT employee_ID, First_Name, job_ID FROM EMPLOYEES WHERE
SALARY > All
( SELECT salary FROM EMPLOYEES WHERE JOB_ID = 'PU_CLERK' )
AND job_ID <> 'PU_CLERK' ;
```

Sample Output:

	EMPLOYEE_ID	FIRST_NAME	JOB_ID
1	180 Winston		SH_CLERK
2	125 Julia		ST_CLERK
3	194 Samuel		SH_CLERK
4	138 Stephen		ST_CLERK
5	133 Jason		ST_CLERK
6	129 Laura		ST_CLERK
7	186 Julia		SH_CLERK
8	141 Trena		ST_CLERK
9	189 Jennifer		SH_CLERK
10	137 Renske		ST_CLERK

Group By and HAVING IN SUB QUERIES: select department_Name, avg (salary) from EMP_Details_VIEWS where average salary is greater then the average salary of employees in employee table.

```
SELECT department_name, avg(salary)
FROM EMP_DETAILS_VIEW
GROUP BY department_name
HAVING avg(salary) > (
    SELECT avg(salary)
    FROM EMPLOYEES
);
```

Sample Output:

[illegible]

SUBQUERIES AND DML:

Subqueries with the INSERT Statement

- SQL subquery can also be used with the Insert statement. In the insert statement, data returned from the subquery is used to insert into another table.
- In the subquery, the selected data can be modified with any of the character, date functions.

Syntax:

```
INSERT INTO table_name (column1, column2, column3. ...)
SELECT *
FROM table_name
WHERE VALUE OPERATOR
```

You may login from a new user for DML sub Queries.

Example: Let's assume we have an EMPLOYEE_BKP table available which is backup of EMPLOYEE table having all the attributes of Employees table

```
INSERT INTO EMPLOYEE_BKP
SELECT * FROM EMPLOYEES
WHERE job_ID IN (SELECT job_id
FROM jobs WHERE job_title='Accountant');
```

Subqueries with the UPDATE Statement

The subquery of SQL can be used in conjunction with the Update statement. When a subquery is used with the Update statement, then either single or multiple columns in a table can be updated.

Syntax

```
UPDATE table
SET column_name = new_value
WHERE VALUE OPERATOR
      (SELECT COLUMN_NAME
       FROM TABLE NAME
```



```
WHERE condition);
```

Example:

The given example updates the SALARY by 10 times in the EMPLOYEE table for all employee whose minimum salary is 3000.

```
Update employees  
set salary= salary+(0.1*salary)  
WHERE job_ID IN (SELECT job_ID  
FROM jobs WHERE min_salary=3000);
```

Subqueries with the DELETE Statement

The subquery of SQL can be used in conjunction with the Delete statement just like any other statements mentioned above.

Syntax

```
DELETE FROM TABLE_NAME  
WHERE VALUE OPERATOR  
(SELECT COLUMN_NAME  
FROM TABLE_NAME  
WHERE condition);
```

Example:

Let's assume we have an EMPLOYEE_BKP table available which is backup of EMPLOYEE table. The given example deletes the records from the EMPLOYEE_BKP table for all EMPLOYEE whose end date is '31-DEC-06'.

```
Delete from employee_BKP  
WHERE job_ID IN (SELECT job_ID  
FROM job_History WHERE end_Date='31-Dec-06');
```

Tasks:

1. For each department, retrieve the department no, the number of employees in the department and their average salary.
2. Write a Query to display the number of employees with the same job.
3. Write a Query to select Firstname and Hiredate of Employees Hired right after the joining of employee_ID no 110.
4. Write a SQL query to select those departments where maximum salary is at least 15000.
5. Write a query to display the employee number, name (first name and last name) and job title for all employees whose salary is smaller than any salary of those employees whose job title is IT_PROG.
6. Write a query in SQL to display all the information of those employees who did not have any job in the past.
7. Display the manager number and the salary of the lowest paid employee of that manager. Exclude anyone whose manager is not known. Exclude any

groups where the minimum salary is 2000. Sort the output in descending order of the salary.

8. Insert into employees_BKP as it should copy the record of the employee whose start date is '13-JAN-01' from job_History table.
9. Update salary of employees by 20% increment having minimum salary of 6000.
10. Delete the record of employees from employees_BKP who are manager and belongs to the department 'Finance'.
11. For each department that has more than five employees, retrieve the department number and the number of its employees who are making more than \$20,000.