

Lecture 8

DYNAMIC SAFE ARRAYS LAST THOUGHTS & INTRODUCTION TO RECURSION

September 21, 2021
Tuesday

2D Vs 1D ARRAY

- We generally visualize a 2D array as a Matrix or Table.
- We refer to 2D arrays as composition of rows and columns.
- However, **Memory is Linear** and there is no such thing as row and column

	Col 0	Col 1	Col 2	Col 3
Row 0	11	22	33	44
Row 1	55	66	77	88
Row 2	11	66	77	44

2D Vs 1D ARRAY

- Statically defined 2D arrays are stored in **row-major order** as 1D array in memory.
- The order dictates that all elements of row 0 should be stored first, followed by all the elements of row 1 and so on.



2D Vs 1D ARRAY

- We can still utilize the 2D indexing conventions to read/write on this 1D array.
- The order dictates that all elements of row 0 should be stored first, followed by all the elements of row 1 and so on.



FLATTENED 2D ARRAY | CONSTRUCTOR

```
DynamicArrayFlat (int r, int c) : n_rows ( r ), n_cols ( c ), size (r * c), p2fa (NULL) {  
    p2fa = new (nothrow) int [n_rows * n_cols] {};  
    if (!p2fa) {  
        // Memory allocation and initialization successful.  
    } else {  
        // Memory allocation failed, throw exception  
        exit(EXIT_FAILURE);  
    }  
}  
  
~DynamicArrayFlat ( ) {  
    delete [] p2fa;  
}
```

FLATTENED 2D ARRAY | ACCESS OPERATOR

```
int& operator ( ) (int row_index, int col_index) {  
    if ( row_index < row_lower_bound || row_index >= row_upper_bound ||  
        col_index < col_lower_bound || col_index >= col_upper_bound ) {  
        // throw Index Out Of Bound Exception  
    }  
  
    return p2fa [ row_index * n_cols + col_index];  
}
```

FLATTENED 2D ARRAY | GET

ONLY FUNCTION DEFINITION HAS CHANGED BODY IS SAME AS ACCESS OPERATOR

```
int get ( ) (int row_index, int col_index) {  
    if ( row_index < row_lower_bound || row_index >= row_upper_bound ||  
        col_index < col_lower_bound || col_index >= col_upper_bound ) {  
        // throw Index Out Of Bound Exception  
    }  
  
    return p2fa [ row_index * n_cols + col_index];  
}
```

FLATTENED 2D ARRAY | SET

```
void set ( ) (int row_index, int col_index, int value) {  
    if ( row_index < row_lower_bound || row_index >= row_upper_bound ||  
        col_index < col_lower_bound || col_index >= col_upper_bound ) {  
        // throw Index Out Of Bound Exception  
    }  
  
    p2fa [ row_index * n_cols + col_index ] = value;  
}
```



FLATTENED 2D ARRAY | PUSHBACK ROW

```
void pushback_row ( int row [ ], int row_cols ) {  
    if (row_cols != n_cols){  
        // row size mismatch throw an exception  
    }  
    int* newArray = new(nothrow) int [ size+ n_cols + growth_factor ] {};  
    for (int i = 0; i < size; i++)  
        newArray [ i ] = p2fa [ i ];  
    for (int j = size; j < size + n_cols; j++)  
        newArray [ j ] = row [ j - size];  
    delete [ ] p2fa;  
    p2fa = newArray;  
    n_rows++;  
    size = n_rows * n_cols;  
}
```

FLATTENED 2D ARRAY | PUSHBACK COLUMN

```
void pushback_row ( int col [ ], int col_rows ) {  
    int* newArray = new(nothrow) int [ size+ n_rows ] {};  
    for (int i = 0; i < size + n_rows; i++) {  
        if ( ( ( i + 1 ) % ( n_cols + 1 ) ) == 0 ) {  
            newArray [ i ] = col [ i ];  
        } else {  
            newArray [ i ] = p2fa [ i ];  
        }  
    }  
    delete [ ] p2fa;  
    p2fa = newArray;  
    n_rows++;  
    size = n_rows * n_cols;  
}
```

MAZE WITH A UNIQUE SOLUTION



MAZE WITH A UNIQUE SOLUTION

0	1	1	1
0	0	1	0
1	0	1	1
0	0	0	0

MAZE WITH A UNIQUE SOLUTION

1. Given
 - a. Start is (0, 0) Index.
 - b. Destination is (n_rows, n_cols)
2. Algorithm
 - a. Check if start is blocked (return false); // hint: if (maze [row] [col] == 1)
 - b. Check if destination is reached (return true);
 - i. // hint if (row == n_rows && col == n_cols)
 - c. Check if right path is open (move right);
 - i. //hint if(maze [row] [col+1] == 0)
 - ii. Check if down path is open (move down);
 1. return false;

SOME INTERESTING PROBLEMS TO THINK ABOUT

- Finding common elements in 2 Arrays.
- Finding repeating elements in 2 or 3 Dynamic Safe Arrays.
- Finding Lower and Upper Bound of a Given Value.
- Merging 2 Dynamic Safe Arrays with only unique items (INTERSECTION).
- Merging 2 Dynamic Safe Arrays with all items (UNION).
- Find more problems on internet, books exercises etc and practice to strengthen your concepts.

RECURSION

WHAT IS RECURSION

A function call in which function being called is the same as the one making the call.



RECURSION

- In C++ any function can invoke another function.
 - A function can even invoke itself.
 - When a function invokes itself, it makes a recursive call.
- Recursive by definition means
 - Having the characteristics of coming up again or repeating.
- When a function directly calls itself, we refer to it as **Direct Recursion**.
- When a chain of two or more function returns to the same function that originated the chain, we refer to it as **Indirect Recursion**.

RECURSION

- Recursion offers simple and elegant solutions to the problems which require iteration.
- However, these solutions can be less efficient than iterative solutions to the same problem.
- Some programming languages does not offer recursion
 - FORTRAN, BASIC and COBOL
- C++ is more generous and offers both
 - Iterative
 - Recursive


CLASSIC EXAMPLE OF RECURSION

$$n! = \begin{cases} 1, & \text{if } n = 0 \\ n * (n - 1) * (n - 2) * \dots * 1, & \text{if } n > 0 \end{cases}$$

- Recursive Definition
 - A definition in which something is defined in terms of a smaller version of itself.
 - $4! = 4 * 3 * 2 * 1 = 24$


RECURSION | THE FACTORIAL

- What is 4!
 - $4! = 4 * (4 - 1)! = 4 * 3!$




RECURSION | THE FACTORIAL

- What is 4!
 - $3! = 3 * (3 - 1)! = 3 * 2!$




RECURSION | THE FACTORIAL

- What is 4!
 - $2! = 2 * (2 - 1)! = 2 * 1!$




RECURSION | THE FACTORIAL

- What is 4!
 - $1! = 1 * (1 - 1)! = 1 * 0!$



RECURSION | THE FACTORIAL



RECURSION | COMPONENTS

- Base Case
 - The case for which the solution can be stated non recursively.
 - Terminating condition.
- Recursive Case
 - The case for which the solution is expressed in terms of smaller version of itself.
- Recursive Algorithm
 - A solution that is expressed in terms of
 - smaller instances of itself
 - has a base case

RECURSION | FACTORIAL

// Precondition: number is non-negative.
// Post: function value = factorial of number.

```
int Factorial (int number) {  
    if (number == 0)  
        return 1;  
    else  
        return number * Factorial (number - 1);  
}
```

RECURSION | VERIFYING

- Base Case Question
 - Will the recursion end?
 - Will the control reach base case?
- Smaller Case Question
 - Does each recursive call leads to the smaller case of the original problem?
 - Will this lead to base case?
- General Case Question
 - Assuming first two conditions are met.
 - Does the function as a whole works correctly?

RECURSION | WRITING RECURSION

- Get an exact definition of the problem to be solved.
 - This is the first step in solving any programming problem.
- Determine the size of the problem to be solved on this call to the function.
- Identify and solve the base case.
 - This ensures the yes answer to the base case question.
- Identify and solve the general case.
 - This ensures the yes answer to the smaller instance and general case question.

RECURSION | VALUE IN THE LIST

- Get an exact definition of the problem to be solved.
 - This is the first step in solving any programming problem.
- Determine the size of the problem to be solved on this call to the function.
- Identify and solve the base case.
 - This ensures the yes answer to the base case question.
- Identify and solve the general case.
 - This ensures the yes answer to the smaller instance and general case question.

RECURSION | VALUE IN THE LIST

- Get an exact definition of the problem to be solved.
 - This is the first step in solving any programming problem.
- Determine the size of the problem to be solved on this call to the function.
- Identify and solve the base case.
 - This ensures the yes answer to the base case question.
- Identify and solve the general case.
 - This ensures the yes answer to the smaller instance and general case question.

RECURSION | COMBINATIONS

```
int Combinations ( int group, int members) {  
    if (members == 1)  
        return group;  
    else if (members == group)  
        return 1;  
    else  
        (Combinations (group - 1, members - 1) + Combinations (group - 1, members) );  
}
```