


# Practice Questions: Congestion Control and Queuing

COS 461: Computer Networks

<http://www.cs.princeton.edu/courses/archive/spr14/cos461/>




1. Name the event at B which occurs that causes the sender to decrease its window

**(a) Triple Duplicate Ack**

(b) Slow Start

(c) Packet loss

(d) Time out




2. Does the event at B necessitate that the network discarded a packet ?

(a) Yes

**(b) No**


(c) Don't know

No. It could be due to either reordering or queuing or asymmetric paths.



3. Name the event at D which occurs that causes the sender to decrease its window.

- (a) Triple Duplicate Ack
- (b) Slow Start
- (c) Packet loss
- (d) Time out**




4. Does the event at D necessitate that the network discarded a packet

(a) Yes

**(b) No**

(c) Don't know

No. Congestion in either direction could cause  $RTT > RTO$  (retrans. timeout).




5. For a lightly-loaded network, is the event at D MORE likely or LESS likely to occur when the sender has multiple TCP segments outstanding

(a) MORE

**(b) LESS**

(c) ALMOST SAME



6. Consider the curved slope labeled by point A. Why does the TCP window behave in such a manner, rather than have a linear slope? (Put another way, why would it be bad if region A had a linear slope?)

This “slow-start” period quickly discovers the maximum acceptable throughput that the path supports – otherwise, AI (additive increase) could take too long (each a full RTT).

**1** In slow start, a sender doubles its window size every RTT if all sent packets were acknowledged

**T/F**



**1** In slow start, a sender doubles its window size every RTT if all sent packets were acknowledged

**T/F**

**2** In steady state, a sender increases its window size by one packet for each acknowledgement

**T/F** – increases by one MSS for every RTT

**1** In slow start, a sender doubles its window size every RTT if all sent packets were acknowledged

**T/F**

**2** In steady state, a sender increases its window size by one packet for each acknowledgement

**T/F** – increases by one MSS for every RTT

**3** A sender that underestimates the round-trip time of a connection may unnecessarily induce a TCP timeout

**T/F**

**1** In slow start, a sender doubles its window size every RTT if all sent packets were acknowledged

**T/F**

**2** In steady state, a sender increases its window size by one packet for each acknowledgement

**T/F** – increases by one MSS for every RTT

**3** A sender that underestimates the round-trip time of a connection may unnecessarily induce a TCP timeout

**T/F**

**4** After detecting packet loss through a timeout, TCP halves its window size as a response to the path congestion

**T/F** – TCP resets its window size to one MSS