AIAC ASSIGNMENT – 16.1

Syed Abdul Mateen

2303A51921

BATCH – 12

Task1: Design a database schema for a Student Information System and generate queries using AI.

```sql
-- Task: Design a database schema for a Student Information System and generate queries using AI.
-- Drop tables if already exist (to avoid errors)
DROP TABLE IF EXISTS Enrollments;
DROP TABLE IF EXISTS Students;
DROP TABLE IF EXISTS Courses;

-- Students Table
CREATE TABLE Students (
    student_id INTEGER PRIMARY KEY AUTOINCREMENT,
    first_name TEXT NOT NULL,
    last_name TEXT NOT NULL,
    date_of_birth TEXT NOT NULL,
    email TEXT UNIQUE NOT NULL
);

-- Courses Table
CREATE TABLE Courses (
    course_id INTEGER PRIMARY KEY AUTOINCREMENT,
    course_name TEXT NOT NULL,
    course_code TEXT UNIQUE NOT NULL,
    credits INTEGER NOT NULL
);

-- Enrollments Table
CREATE TABLE Enrollments (
    enrollment_id INTEGER PRIMARY KEY AUTOINCREMENT,
    student_id INTEGER NOT NULL,
    course_id INTEGER NOT NULL,
    enrollment_date TEXT NOT NULL,
    FOREIGN KEY (student_id) REFERENCES Students(student_id),
    FOREIGN KEY (course_id) REFERENCES Courses(course_id)
);
```

1. Query : Insert a new student record

```sql
-- Enrollments Table
CREATE TABLE Enrollments (
    enrollment_id INTEGER PRIMARY KEY AUTOINCREMENT,
    student_id INTEGER NOT NULL,
    course_id INTEGER NOT NULL,
    enrollment_date TEXT NOT NULL,
    FOREIGN KEY (student_id) REFERENCES Students(student_id),
    FOREIGN KEY (course_id) REFERENCES Courses(course_id)
);

-- Insert Students
INSERT INTO Students (first_name, last_name, date_of_birth, email)
VALUES
('John', 'Doe', '2000-01-15', 'john@example.com'),
('Jane', 'Smith', '1999-05-20', 'jane@example.com');

-- Insert Courses
INSERT INTO Courses (course_name, course_code, credits)
VALUES
('Introduction to Computer Science', 'CS101', 3),
('Database Systems', 'CS102', 4);

-- Enrollments
INSERT INTO Enrollments (student_id, course_id, enrollment_date)
VALUES
(1, 1, '2024-01-10'),
(1, 2, '2024-01-12'),
(2, 1, '2024-01-11');
```

2. Query : Fetch all courses enrolled by a student.

```sql
-- Insert Students
INSERT INTO Students (first_name, last_name, date_of_bi
VALUES
('John', 'Doe', '2000-01-15', 'john@example.com'),
('Jane', 'Smith', '1999-05-20', 'jane@example.com');

-- Insert Courses
INSERT INTO Courses (course_name, course_code, credits)
VALUES
('Introduction to Computer Science', 'CS101', 3),
('Database Systems', 'CS102', 4);

-- Enrollments
INSERT INTO Enrollments (student_id, course_id, enroll
VALUES
(1, 1, '2024-01-10'),
(1, 2, '2024-01-12'),
(2, 1, '2024-01-11');

-- Query
SELECT s.first_name, s.last_name, c.course_name
FROM Students s
JOIN Enrollments e ON s.student_id = e.student_id
JOIN Courses c ON e.course_id = c.course_id
WHERE c.course_code = 'CS101';
```

SQL ▾ < 1 / 1 > 1 - 0 of 0

SQL ▾ < 1 / 1 > 1 - 0 of 0

SQL ▾ < 1 / 1 > 1 - 0 of 0

SQL ▾ < 1 / 1 > 1 - 0 of 0

SQL ▾ < 1 / 1 > 1 - 0 of 0

SQL ▾ < 1 / 1 > 1 - 0 of 0

SQL ▾ < 1 / 1 > 1 - 0 of 0

SQL ▾ < 1 / 1 > 1 - 0 of 0

SQL ▾ < 1 / 1 > 1 - 0 of 0

SQL ▾ < 1 / 1 > 1 - 2 of 2

first_name	last_name	course_name
John	Doe	Introduction to Computer Science
Jane	Smith	Introduction to Computer Science

3. Query : Count number of students in each course.

```sql
--  Count number of students in each course.
SELECT c.course_name, COUNT(e.student_id) AS student_co
FROM Courses c
LEFT JOIN Enrollments e ON c.course_id = e.course_id
GROUP BY c.course_id;
```

SQL ▾ < 1 / 1 > 1 - 2 of 2

course_name	student_count
Introduction to Computer Science	2
Database Systems	1

TASK 2 : Create schema and queries for a Hospital Management System.

```sql
-- Create schema and queries for a Hospital Management System
-- Drop tables if already exist (to avoid errors)
DROP TABLE IF EXISTS Appointments;
DROP TABLE IF EXISTS Patients;
DROP TABLE IF EXISTS Doctors;
-- Patients Table
CREATE TABLE Patients (
    patient_id INTEGER PRIMARY KEY AUTOINCREMENT,
    first_name TEXT NOT NULL,
    last_name TEXT NOT NULL,
    date_of_birth TEXT NOT NULL,
    email TEXT UNIQUE NOT NULL
);
-- Doctors Table
CREATE TABLE Doctors (
    doctor_id INTEGER PRIMARY KEY AUTOINCREMENT,
    first_name TEXT NOT NULL,
    last_name TEXT NOT NULL,
    specialty TEXT NOT NULL,
    email TEXT UNIQUE NOT NULL
);
-- Appointments Table
CREATE TABLE Appointments (
    appointment_id INTEGER PRIMARY KEY AUTOINCREMENT,
    patient_id INTEGER NOT NULL,
    doctor_id INTEGER NOT NULL,
    appointment_date TEXT NOT NULL,
    FOREIGN KEY (patient_id) REFERENCES Patients(patient_id),
    FOREIGN KEY (doctor_id) REFERENCES Doctors(doctor_id)
);
```

```sql
-- Appointments Table
CREATE TABLE Appointments (
    appointment_id INTEGER PRIMARY KEY AUTOINCREMENT,
    patient_id INTEGER NOT NULL,
    doctor_id INTEGER NOT NULL,
    appointment_date TEXT NOT NULL,
    FOREIGN KEY (patient_id) REFERENCES Patients(patient_id),
    FOREIGN KEY (doctor_id) REFERENCES Doctors(doctor_id)
);
```

```sql
-- Insert Patients
INSERT INTO Patients (first_name, last_name, date_of_birth, email)
VALUES
('Emily', 'Clark', '1985-07-12', 'emily@example.com'),
('Michael', 'Brown', '1990-11-05', 'michael@example.com');
-- Insert Doctors
INSERT INTO Doctors (first_name, last_name, specialty, email)
VALUES
('Dr. Sarah', 'Johnson', 'Cardiology', 'sarah.johnson@example.com'),
('Dr. David', 'Smith', 'Neurology', 'david.smith@example.com');
-- Insert Appointments
INSERT INTO Appointments (patient_id, doctor_id, appointment_date)
VALUES
(1, 1, '2024-07-01'),
(1, 2, '2024-07-15'),
(2, 1, '2024-07-10');
```

Query 1: List all appointments for a specific doctor.

```sql
-- Insert Patients
INSERT INTO Patients (first_name, last_name, date_of_birth, email)
VALUES
('Emily', 'Clark', '1985-07-12', 'emily@example.com'),
('Michael', 'Brown', '1990-11-05', 'michael@example.com');
-- Insert Doctors
INSERT INTO Doctors (first_name, last_name, specialty, email)
VALUES
('Dr. Sarah', 'Johnson', 'Cardiology', 'sarah.johnson@example.com'),
('Dr. David', 'Smith', 'Neurology', 'david.smith@example.com');
-- Insert Appointments
INSERT INTO Appointments (patient_id, doctor_id, appointment_date)
VALUES
(1, 1, '2024-07-01'),
(1, 2, '2024-07-15'),
(2, 1, '2024-07-10');
```

Ask for Edits Ctrl+I

```sql
-- List all appointments for a specific doctor.
SELECT p.first_name, p.last_name, a.appointment_date
FROM Patients p
JOIN Appointments a ON p.patient_id = a.patient_id
JOIN Doctors d ON a.doctor_id = d.doctor_id
WHERE d.email = 'sarah.johnson@example.com';
```

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	appointment_date
Emily	Clark	2024-07-01
Michael	Brown	2024-07-10

Query 2 : Retrieve patient history by patient ID.

```sql
-- List all appointments for a specific doctor.
SELECT p.first_name, p.last_name, a.appointment_date
FROM Patients p
JOIN Appointments a ON p.patient_id = a.patient_id
JOIN Doctors d ON a.doctor_id = d.doctor_id
WHERE d.email = 'sarah.johnson@example.com';

-- Retrieve patient history by patient ID.
SELECT d.first_name, d.last_name, a.appointment_date
FROM Doctors d
JOIN Appointments a ON d.doctor_id = a.doctor_id
JOIN Patients p ON a.patient_id = p.patient_id
WHERE p.patient_id = 1;
```

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	appointment_date
Emily	Clark	2024-07-01
Michael	Brown	2024-07-10

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	appointment_date
Dr. Sarah	Johnson	2024-07-01
Dr. David	Smith	2024-07-15

Query 3 : Count total patients treated by each doctor.

Ask for Edits Ctrl+I

```sql
-- Count total patients treated by each doctor.
SELECT d.first_name, d.last_name, COUNT(a.patient_id) AS patient_cour
FROM Doctors d
LEFT JOIN Appointments a ON d.doctor_id = a.doctor_id
GROUP BY d.doctor_id;
```

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	patient_count
Dr. Sarah	Johnson	2
Dr. David	Smith	1

TASK 3 : Design schema for a Library Management System

```sql
-- Design schema for a Library Management System
-- Drop tables if already exist (to avoid errors)
DROP TABLE IF EXISTS Borrowings;
DROP TABLE IF EXISTS Books;
DROP TABLE IF EXISTS Members;
-- Members Table
CREATE TABLE Members (
    member_id INTEGER PRIMARY KEY AUTOINCREMENT,
    first_name TEXT NOT NULL,
    last_name TEXT NOT NULL,
    email TEXT UNIQUE NOT NULL
);
-- Books Table
CREATE TABLE Books (
    book_id INTEGER PRIMARY KEY AUTOINCREMENT,
    title TEXT NOT NULL,
    author TEXT NOT NULL,
    isbn TEXT UNIQUE NOT NULL
);
-- Borrowings Table
CREATE TABLE Borrowings (
    borrowing_id INTEGER PRIMARY KEY AUTOINCREMENT,
    member_id INTEGER NOT NULL,
    book_id INTEGER NOT NULL,
    borrow_date TEXT NOT NULL,
    return_date TEXT,
    FOREIGN KEY (member_id) REFERENCES Members(member_id),
    FOREIGN KEY (book_id) REFERENCES Books(book_id)
);
```

```sql
-- Insert Members
INSERT INTO Members (first_name, last_name, email)
VALUES
('Alice', 'Johnson', 'alice@example.com'),
('Bob', 'Smith', 'bob@example.com');
-- Insert Books
INSERT INTO Books (title, author, isbn)
VALUES
('The Great Gatsby', 'F. Scott Fitzgerald', '978-0-7432-7356-5'),
('To Kill a Mockingbird', 'Harper Lee', '978-0-06-114803-6');
-- Insert Borrowings
INSERT INTO Borrowings (member_id, book_id, borrow_date, return_date)
VALUES
(1, 1, '2024-08-01', '2024-08-15'),
(1, 2, '2024-08-16', NULL),
(2, 1, '2024-08-05', '2024-08-20');
```

Query 1 : Retrieve all books currently issued.

```sql
-- Retrieve all books currently issued.
SELECT b.title, m.first_name, m.last_name, br.borrow_date
FROM Books b
JOIN Borrowings br ON b.book_id = br.book_id
JOIN Members m ON br.member_id = m.member_id
WHERE br.return_date IS NULL;
```

SQL ▾ < 1 / 1 > 1 - 1 of 1

title	first_name	last_name	borrow_date
To Kill a Mockingbird	Alice	Johnson	2024-08-16

Query 2 : Find the most purchased product.

```sql
-- Retrieve all books currently issued.
SELECT b.title, m.first_name, m.last_name, br.borrow_date
FROM Books b
JOIN Borrowings br ON b.book_id = br.book_id
JOIN Members m ON br.member_id = m.member_id
WHERE br.return_date IS NULL;

-- Find the most purchased product.
SELECT b.title, COUNT(br.borrowing_id) AS borrow_count
FROM Books b
JOIN Borrowings br ON b.book_id = br.book_id
GROUP BY b.book_id
ORDER BY borrow_count DESC
LIMIT 1;
```

SQL ▾ < 1 / 1 > 1 - 0 of 0

SQL ▾ < 1 / 1 > 1 - 1 of 1

title	first_name	last_name	borrow_date
To Kill a Mockingbird	Alice	Johnson	2024-08-16

SQL ▾ < 1 / 1 > 1 - 1 of 1

title	borrow_count
The Great Gatsby	2

Query 3 : Count number of books loaned by each member.

```
-- Find the most purchased product.
SELECT b.title, COUNT(br.borrowing_id) AS borrow_count
FROM Books b
JOIN Borrowings br ON b.book_id = br.book_id
GROUP BY b.book_id
ORDER BY borrow_count DESC
LIMIT 1;
```

Ask for Edits Ctrl+I

```
-- Count number of books loaned by each member.
SELECT m.first_name, m.last_name, COUNT(br.borrowing_id) AS borrow_count
FROM Members m
LEFT JOIN Borrowings br ON m.member_id = br.member_id
GROUP BY m.member_id;
```

To Kill a Mockingbird	Alice	Johnson	2024-08-16

SQL ▾ 1 / 1 1 - 1 of 1

title	borrow_count
The Great Gatsby	2

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	borrow_count
Alice	Johnson	2
Bob	Smith	1

TASK 4 : Design a database for an E-commerce platform.

```
-- Design a database for an E-commerce platform.
-- Drop tables if already exist (to avoid errors)
DROP TABLE IF EXISTS Orders;
DROP TABLE IF EXISTS Products;
DROP TABLE IF EXISTS Customers;
-- Customers Table
CREATE TABLE Customers (
    customer_id INTEGER PRIMARY KEY AUTOINCREMENT,
    first_name TEXT NOT NULL,
    last_name TEXT NOT NULL,
    email TEXT UNIQUE NOT NULL
);
-- Products Table
CREATE TABLE Products (
    product_id INTEGER PRIMARY KEY AUTOINCREMENT,
    product_name TEXT NOT NULL,
    price REAL NOT NULL,
    stock INTEGER NOT NULL
);
-- Orders Table
CREATE TABLE Orders (
    order_id INTEGER PRIMARY KEY AUTOINCREMENT,
    customer_id INTEGER NOT NULL,
    product_id INTEGER NOT NULL,
    order_date TEXT NOT NULL,
    quantity INTEGER NOT NULL,
    FOREIGN KEY (customer_id) REFERENCES Customers(customer_id),
    FOREIGN KEY (product_id) REFERENCES Products(product_id)
);
```

```
-- Insert Customers
INSERT INTO Customers (first_name, last_name, email)
VALUES
('John', 'Doe', 'john@example.com'),
('Jane', 'Smith', 'jane@example.com');
-- Insert Products
INSERT INTO Products (product_name, price, stock)
VALUES
('Laptop', 999.99, 10),
('Mouse', 29.99, 50);
-- Insert Orders
INSERT INTO Orders (customer_id, product_id, order_date, quantity)
VALUES
(1, 1, '2024-08-01', 1),
(1, 2, '2024-08-01', 2),
(2, 1, '2024-08-02', 1);
```

Query 1 : Retrieve all orders by a user.

```sql
-- Retrieve all orders by a user.
SELECT c.first_name, c.last_name, p.product_name, o.order_date, o
FROM Customers c
JOIN Orders o ON c.customer_id = o.customer_id
JOIN Products p ON o.product_id = p.product_id
WHERE c.email = 'john@example.com';
```

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	product_name	order_date	quantity
John	Doe	Laptop	2024-08-01	1
John	Doe	Mouse	2024-08-01	2

2 : Find the most purchased product. Query

```sql
-- Retrieve all orders by a user.
SELECT c.first_name, c.last_name, p.product_name, o.order_date, o
FROM Customers c
JOIN Orders o ON c.customer_id = o.customer_id
JOIN Products p ON o.product_id = p.product_id
WHERE c.email = 'john@example.com';

-- Find the most purchased product.
SELECT p.product_name, SUM(o.quantity) AS total_quantity
FROM Products p
JOIN Orders o ON p.product_id = o.product_id
GROUP BY p.product_id
ORDER BY total_quantity DESC
LIMIT 1;
```

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	product_name	order_date	quantity
John	Doe	Laptop	2024-08-01	1
John	Doe	Mouse	2024-08-01	2

SQL ▾ 1 / 1 1 - 1 of 1

product_name	total_quantity
Laptop	2

Query 3 : Calculate total revenue in a given month

```sql
-- Find the most purchased product.
SELECT p.product_name, SUM(o.quantity) AS total_quantity
FROM Products p
JOIN Orders o ON p.product_id = o.product_id
GROUP BY p.product_id
ORDER BY total_quantity DESC
Ask for Edits Ctrl+I
-- Calculate total revenue in a given month
SELECT strftime('%Y-%m', o.order_date) AS month, SUM(p.price * o.
FROM Orders o
JOIN Products p ON o.product_id = p.product_id
GROUP BY month
ORDER BY month;
```

John	Doe	Mouse	2024-08-01	2

SQL ▾ 1 / 1 1 - 1 of 1

product_name	total_quantity
Laptop	2

SQL ▾ 1 / 1 1 - 1 of 1

month	total_revenue
2024-08	2059.96

TASK 5 : Design a database schema for a University Examination System and generate SQL queries using AI.

```sql
-- Design a database schema for a University Examination System and generate SQL queries using AI.
-- Drop tables if already exist (to avoid errors)
DROP TABLE IF EXISTS ExamResults;
DROP TABLE IF EXISTS Students;
DROP TABLE IF EXISTS Exams;
-- Students Table
CREATE TABLE Students (
    student_id INTEGER PRIMARY KEY AUTOINCREMENT,
    first_name TEXT NOT NULL,
    last_name TEXT NOT NULL,
    date_of_birth TEXT NOT NULL,
    email TEXT UNIQUE NOT NULL
);
-- Exams Table
CREATE TABLE Exams (
    exam_id INTEGER PRIMARY KEY AUTOINCREMENT,
    course_name TEXT NOT NULL,
    exam_date TEXT NOT NULL
);
-- ExamResults Table
CREATE TABLE ExamResults (
    result_id INTEGER PRIMARY KEY AUTOINCREMENT,
    student_id INTEGER NOT NULL,
    exam_id INTEGER NOT NULL,
    score REAL NOT NULL,
    FOREIGN KEY (student_id) REFERENCES Students(student_id),
    FOREIGN KEY (exam_id) REFERENCES Exams(exam_id)
);
```

```sql
-- Exams Table
CREATE TABLE Exams (
    exam_id INTEGER PRIMARY KEY AUTOINCREMENT,
    course_name TEXT NOT NULL,
    exam_date TEXT NOT NULL
);
-- ExamResults Table
CREATE TABLE ExamResults (
    result_id INTEGER PRIMARY KEY AUTOINCREMENT,
    student_id INTEGER NOT NULL,
    exam_id INTEGER NOT NULL,
    score REAL NOT NULL,
    FOREIGN KEY (student_id) REFERENCES Students(student_id),
    FOREIGN KEY (exam_id) REFERENCES Exams(exam_id)
);
-- Insert Students
INSERT INTO Students (first_name, last_name, date_of_birth, email)
VALUES
('Alice', 'Johnson', '2001-03-22', 'alice@example.com'),
('Bob', 'Smith', '2000-07-15', 'bob@example.com');
-- Insert Exams
INSERT INTO Exams (course_name, exam_date)
VALUES
('Mathematics', '2024-08-15'),
('Physics', '2024-08-20');
-- Insert Exam Results
INSERT INTO ExamResults (student_id, exam_id, score)
VALUES
(1, 1, 85.5),
(1, 2, 92.0),
(2, 1, 78.0),
(2, 2, 88.5);
```

Query 1 : Insert examination results for a student.

```sql
-- Query 1 : Insert examination results for a student.
INSERT INTO ExamResults (student_id, exam_id, score)
VALUES (1, 1, 85.5);
```

Query 2: Retrieve subject-wise marks for a student.

```sql
-- Query 2: Retrieve subject-wise marks for a student.
SELECT e.course_name, er.score
FROM ExamResults er
JOIN Exams e ON er.exam_id = e.exam_id
WHERE er.student_id = 1;
```

course_name	score
Mathematics	85.5
Physics	92.0
Mathematics	85.5

Query 3 : Calculate average marks for each subject.

```sql
-- Query 3: Calculate the average score for a specific exam.
SELECT e.course_name, AVG(er.score) AS average_score
FROM ExamResults er
JOIN Exams e ON er.exam_id = e.exam_id
WHERE e.course_name = 'Mathematics'
GROUP BY e.exam_id;
```

course_name	average_score
Mathematics	83.0

LAB OBSERVATIONS

Objective

To design and implement database schemas for various real-world systems and perform SQL operations such as table creation, data insertion, and query execution using SQL.

Observation 1: Student Information System

- Createdthreetables: **Students, Courses, Enrollments.**
- Established **many-to-many relationship** usingabridge table (Enrollments).
- Used **primary keys** and **foreign keys** to maintaindata integrity.
- Inserted sample student and course data successfully.
- Performed queries to:
  - Retrieve students enrolled in a specific course.
  - Count number of students in each course.
- Observedthat **JOIN operations** help combinedatafrom multiple tables.

Observation 2: Hospital Management System

- Designedtables: **Patients, Doctors, Appointments.**
- Implemented relationships using foreign keys.
- Inserted patient, doctor, and appointment data.
- Executed queries to:
  - List appointments for a specific doctor.
  - Retrieve patient history.
  - Count total patients handled by each doctor.
- Observedthat **LEFT JOIN** helpsincludedoctors with no appointments.

Observation 3: Library Management System

- Createdtables: **Members, Books, Borrowings.**
- Maintained relationships using foreign keys.
- Inserted borrowing records with return status.
- Executed queries to:
  - Find currently issued books (using NULL condition).
  - Identify most borrowed book.

- o Count books borrowed by each member.

- Observed that **NULL values** are useful for tracking incomplete actions (e.g., not returned books).

◆ **Observation 4: E-Commerce System**

- Designed tables: **Customers, Products, Orders.**
- Established relationships using foreign keys.
- Inserted sample order and product data.
- Executed queries to:
  - o Retrieve all orders by a specific customer.
  - o Find most purchased product.
  - o Calculate total revenue per month.
- Observed that **aggregate functions (SUM, COUNT)** are useful for business analysis.

◆ **Observation 5: University Examination System**

- Created tables: **Students, Exams,ExamResults** .
- Linked students and exams using a result table.
- Inserted exam and result data.
- Executed queries to:
  - o Retrieve subject-wise marks.
  - o Calculate average scores for exams.
- Observed that **GROUP BY and AVG functions**help in performance evaluation.