

1.1/2"SQUARE DRIVE



IMPACT SOCKET 6 POINT STANDARD

PART NO.	mm	A/F	D1	D2	S	T	Weight
		Inch	mm	mm	mm	mm	gm
TI627F		1.1/16"	54 :	86	80	23	1841
TI629F	į	1.1/8"	58	86	80	23	1841
TI635F	:	1.3/8"	64 :	86	80	23	1841
TI636	36		64	86	80	28	2249
TI637F		1.7/16"	64	86	80	28	2249
TI638	: 38		69 :	86	80	28	2249
T1638F	i	1.1/2"	69	86	80	28	2249
TI640F	:	1.9/16"	69 :	86	80	30	2249
TI641	41		69	86	83	32	2249
TI641F		1.5/8"	69 :	86	83	36	2249
TI643F		1.11/16	69	86	83	36	2249
TI644F	:	1.3/4"	69	86	83	36	2249
T1646	: 46		76	86	86	36	2249
TI646F		1.13/16	76	86	86	36	2249
TI648F	:	1.7/8"	76 :	86	86	36	2351
T1650	: : 50		81	86	90	39	2351
TI651F	:	2"	81	86	90	39	2351
TI652		2.1/16"	81	86	90	39	2351
TI655	55		88	86	95	41	2555
T1655F	:	2.3/16"	88	86	95	41	2555
TI657F	1	2.1/4"	88	86	95	41	2861
T1660	60	,	96	86	98	45	2861
TI660F	. 00	2.3/8"	96	86	98	45	3269
TI661F	:	2.7/16"	96	86	98	45	3269
TI665	65	,10	102	86	102	46	3421
TI665F	: 03	2.9/16"	102	86	102	46	3421
TI666F		2.5/8"	102	86	102	46	3421
TI670	70	2.5/0	108	86	102	50	3677
TI670F	: 70	2.3/4"	108	86	102	50	* 1.000 D.Y.L.
TI671F	1	2.13/16		86	102	50	3677
TI675	: 75	2.13/10		86	•	57	3677
	75	2.15/16	116		108	57	3983
T1675F	:	3"		86	108		3983
TI676F	:		112	86	108	57	4595
TI680	: 80	2 1 /0"	120:	86	110	62	4595
T1680F		3.1/8"	120	86	110	62	4595
TI685	85	2 2 (0"	130	86	115	62	6126
TI685F		3.3/8"	130	86	115	62	6126
TI690	90	0 4 (0)	135	125	118	65	6726
T1690F	:	3.1/2"	135:	125	118	65	6726
TI695	95		140	125	123	70	9486
TI695F	1	3.3/4"	140	125	123	70	9486
TI6100	100		148	125	128	75	10206
TI6100F		3.7/8"	148	125	128	75	10206
TI6105	105	. To the second	155	125	133	80	11406
TI6105F	:	4.1/8"	155	125	133	80	11406
TI6106F		4.1/4"	155	125	133	80	12246
TI6110	110	1	161	150	138	85	12486
TI6115	115		161	150	143	94	12606
TI6115F	<u> </u>	-					-





TI6120 TI6120F


Note: All the above sizes are available in 12 point (Bi-Hex) Sockets. To order Bi-Hex suffix above part numbers with "BH"


1.1/2"SQUARE DRIVE



IMPACT SOCKET 6 POINT LONG

ART NO.	mm	A/F Inch	D1 mm	D2 mm	L mm	T mm	Weight gm
TIL627F		1.1/16"	54	86	130	23	5406
TIL629F		1.1/8"	58	86	130	23	5406
TIL635F	:	1.3/8"	64	86	130	23	5406
TIL636	36		64	86	130	28	5406
TIL637F		1.7/16"	64	86	130	28	5406
TIL638	38		69	86	130	28	5406
TIL638F		1.1/2"	69	86	130	28	5406
TIL640F		1.9/16"	69	86	130	30	5406
TIL641	41		69	86	130	32	5406
TIL641F		1.5/8"	69	86	130	36	5406
TIL643F	:	1.11/16"	69	86	130	36	5406
TIL644F		1.3/4"	69	86	130	36	5406
TIL646	46	: :	76	86	130	36	5406
TIL646F		1.13/16	76	86	130	36	5406
TIL648F	i —	1.7/8"	76	86	130	36	5406
TIL650	50		81	86	130	39	5406
TIL651F	:	2"	81	86	130	39	5406
TIL652F	:	2.1/16"	81	86	140	39	5406
TIL655	55	: :	88	: 86	140	41	5406
TIL655F	:	2.3/16"	88	86	140	41	5406
TIL657F	:	2.1/4"	88	86	140	41	5406
TIL660	60		96	86	140	45	5526
TIL660F	:	2.3/8"	96	86	140	45	5526
TIL661F		2.7/16"	96	86	140	45	5526
TIL665	65	1	102	86	140	46	5886
TIL665F	. 03	: 2.9/16"	102	86	140	46	5886
TIL666F	:	2.5/8"	102	86	140	46	5886
TIL670	70		108	86	150	50	6006
TIL670F	: 70	2.3/4"	108	86	150	50	6006
TIL670F		2.13/16	108	86	150	50	6006
TIL675	: : 75	2.13/10		86	150	57	
	: /5	2.15/16"	116				6726
TIL675F TIL676F		3"	116	86	150	57	6726 7086
	: 00	f :	112	86	150	57	
TIL680 TIL680F	80	3.1/8"	120	86	150	62	7086
TIL680F	. or	/0	120 130	86	150	62 62	7086 7446
	85	3.3/8"					
TIL685F		5.570	130	86	170	62	7446
TIL690	90	3.1/2"	135	125	170	65	8166
TIL690F		3.1/2	135	125	170	65	8166
TIL695	95	3.3/4"	140	125	170	70	11886
TIL695F	:		140	125	170	70	11886
TIL6100	100	3.7/8"	148	125	190	75	12846
TIL6100F		3.7/8	148	125	: 190	75	12846
TIL6105	105	41/0"	155	125	190	80	14286
TIL6105F		4.1/8"	155	125	190	80	14286
TIL6106F		4.1/4"	155	125	190	80	14286
TIL6110	110		161	150	200	85	15006
TIL6115	115		161	150	200	94	15006





TIL6120 TIL6120F


Note: All the above sizes are available in 12 point (Bi-Hex) Sockets. To order Bi-Hex suffix above part numbers with "BH"

1.1/2"SQUARE DRIVE




ADAPTER (MALE-MALE)

Part No.	Type	Mail	D mm	L mm	Wt (gm)
TA601		1.1/2"	49	101	1205
TA602	1.1/2"D	1.1/2"	49	127	1545
TA603		1.1/2"	49	254	3425
TA604		1.1/2"	49	504	6555




ADAPTER (FEMALE- MALE)

Part No.	Туре	D1	D2	D mm	L mm	Wt (gm)
TA605		1.1/2"	1"	86	95	2305
TA606	1.1/2D	1.1/2"	2.1/2"	86	93	2305
TA606		1.1/2"	SPLINE NO.5	86	138	2305




ADAPTER (FEMALE-FEMALE)

Part No.	Туре	D1	D2	D mm	L mm	Wt (gm)
TA607		1.1/2"	1"	86	83	2055
TA608	1.1/2"D	1.1/2"	2.1/2"	86	85	2695
TA609		1.1/2"	SPLINE NO.5	127	115	6505



EXTENSION BAR

Part No.	Type	Male	Female	D mm	L mm	Wt (gm)
TAE610		1.1/2"	1.1/2"	86	150	3985
TAE611	1.1/2"D	1.1/2"	1.1/2"	86	225	4545
TAE612		1.1/2"	1.1/2"	86	300	5005
TAE613		1.1/2"	1.1/2"		i .	



UNIVERSAL JOINT

Part No.	Square Size	Type	D mm	L mm	Wt (gm)
TAU614	1.1/2"	1/2"D	86	125	4075



RETAINING PINS AND RINGS

Part No.			For S	ocket	Pi	n	Ring
Ret Pin	ainig Ring	Туре	Square Size	Dia. of sq end		L (mm)	D (mm)
TAP6015	TAR617	1.1/2"D	1.1/2"	86	6	75	75
TAP616	: TAR618	1 1	1.1/2"	127	6	116	116

