

Task Status API

TaskViewSet contains a custom action `change_status` decorated with `@action(detail=True, methods=['patch'])`. It fetches the selected task using `self.get_object()`, updates `task.status` from `request.data`, saves it, and returns a success response.

Signup Endpoint

SignupView receives POST data, validates it using `SignupSerializer`, creates the user with `create_user()` so the password is hashed, and returns HTTP 201.

Login Endpoint

Initially LoginView used `authenticate(username, password)` to verify credentials. If valid, it returned a success response.

JWT Authentication

Simple JWT was installed and `TokenObtainPairView` and `TokenRefreshView` were added. `/login/` returns access and refresh tokens. `/token/refresh/` returns a new access token using a valid refresh token.

Accounts URLs

`accounts/urls.py` contains `signup`, `login`, and `token/refresh` endpoints. The project `urls.py` includes `Accounts.urls` so these endpoints become available.

IsAuthenticated

`permission_classes = [IsAuthenticated]` ensures only authenticated users can access the endpoint. If no valid authentication is supplied, DRF returns HTTP 401 `Unauthorized`.

Protecting Project Endpoints

`ProjectViewSet` was updated with `permission_classes = [IsAuthenticated]`. Every CRUD endpoint generated by `ModelViewSet` is now protected.

Why Browser Shows 401

JWT does not automatically authenticate browser requests. The browser address bar cannot send an `Authorization: Bearer` header, so opening `/projects/` directly returns `Authentication credentials were not provided`.

SessionAuthentication

If browser-based login is required, `SessionAuthentication` can be enabled and `rest_framework.urls` included. After logging in through the browser, the session cookie is automatically sent with future requests.