Tyep POS

Firebase setup for delivery

Beginner-friendly steps for connecting the POS, rider app, and free in-app order alert.

Before you begin

- Have a Google account and access to the project folder on your Mac.
- Keep rider passwords private. Each person uses an individual account.
- Never put a Firebase service-account file or private key in either app.
- Create only the manager account in Firebase Console. You can add riders later from the POS.

Part 1 - Create the Firebase project

1. Open Firebase Console and sign in with Google. Choose **Create a project** and give it a name, such as Tyep Delivery. Google Analytics is optional.

2. When the project is ready, open the gear next to Project Overview, then **Project settings**. Write down the **Project ID**; it is different from the display name.

Part 2 - Register a web app

1. In Project settings, scroll to **Your apps** and click the web icon **</>**. Name it Tyep Delivery Web and register it.

2. Copy these four settings from its configuration: **apiKey, authDomain, projectId, appId**. They are browser-app settings, not service-account credentials.

Part 3 - Turn on sign-in and create the manager

1. Open **Authentication** > Sign-in method. Turn on **Email/Password** and save.

2. In Authentication > Users, choose Add user. Create the POS delivery manager account and copy its UID. Rider accounts are created later from the POS.

Create the database and manager profile

Part 4 - Create Firestore

1. Open **Firestore Database** and choose Create database.

2. Choose **Production mode**, not test mode.

3. For a new database, use the configured Firebase region **northamerica-northeast1**. If your database already exists in another region, pause and ask for help before deploying.

Part 5 - Add the manager profile

1. In Firestore's Data tab, choose Start collection and name it exactly **deliveryRiders**.

2. Create one document. Set its document ID to the manager's exact Authentication UID, not their email.

3. Add these fields using the listed types:

Field	Value	Type
role	manager	string
name	POS Manager or your name	string
email	Manager's email	string
enabled	true	boolean

Only the manager document must be created manually. The POS creates each rider's Authentication account and profile together.

Part 6 - Add riders from the POS

- Sign in to Delivery in the POS with the manager account. Fill in Rider name, Email, Initial password (at least 6 characters), and optional phone/area, then choose Create rider account.
- The email must be new to this Firebase project. The POS does not email the password; share it privately with the rider. Note the password before submitting.
- Remove access disables the rider's delivery profile but keeps their Firebase login and delivery history. It can be restored later. A rider must have no active deliveries before access can be removed.

Permanent deletion of the Firebase login requires Firebase Console or a trusted Admin SDK service. The POS does not contain a private service-account key.

Add settings and understand alerts

Part 7 - Add Firebase settings

There are two .env files: one in the main project folder and one inside DAPP. Keep unrelated settings already in the POS .env file. Do not send .env files to riders.

In both .env files, add the four values from your Firebase web app:

```
VITE_FIREBASE_API_KEY=your-api-key
VITE_FIREBASE_AUTH_DOMAIN=your-project.firebaseapp.com
VITE_FIREBASE_PROJECT_ID=your-project-id
VITE_FIREBASE_APP_ID=your-app-id
```

Replace the example words with the real values. Never use a service-account JSON file or private key.

Free in-app order alert

The rider app shows its custom alert when a new order arrives while the rider is signed in, the app is open, and the phone is connected. It uses the Firestore subscription already loading available orders. It does not use a Cloud Function, notification permission, or background push. No extra billing setup is needed for this alert, but Firestore quotas still apply.

If the rider closes or suspends the app, no alert is sent.

Build, deploy, and test

Part 8 - Publish the app and rules

Open VS Code's Terminal > New Terminal. These commands assume the project is still in its current folder on this Mac:

```
cd "/Users/d87/Downloads/Projects/POS(mern)/WindowsPOSV2/DAPP"
```

1. Install app packages and build after saving DAPP/.env:

```
npm install
npm run build
```

2. Sign in to Firebase using the Google account that owns the project:

```
npx firebase-tools login
```

3. Replace your-project-id with the Project ID from Part 1, then deploy:

```
npx firebase-tools deploy --only hosting,firestore:rules --project your-project-id
```

Wait for a success message. Firebase will show a website address such as https://your-project-id.web.app. Stop and ask for help if Firebase asks to overwrite or delete something unexpected.

Part 9 - Connect and test

- Restart the POS, open Delivery, and sign in with the manager account.
- Add a rider using the form. Open the Firebase website address on their phone and sign in using the email and initial password you provided.
- Keep the rider app open and connected. Create a test delivery in the POS and confirm it appears in the rider app with the custom in-app alert.
- Claim the order, advance it to On the way, and mark it Delivered. Check the POS status and payment totals.

Troubleshooting

Setup needed: check the four Firebase settings in DAPP/.env, then rebuild and deploy. POS cannot connect: check the top-level .env and restart the POS. Rider cannot sign in: check the email and initial password. Rider sees no orders: check their profile shows Enabled and the app is open and connected. Permission denied: check that current Firestore rules are deployed to the same Project ID.