LAB 01 COMPUTER ORGANIZATION AND ASSEMBLY LANG(COAL)



Sarim Latif Khan		20K-1644	3E
STUDENT NAME	•	ROLL NO	$\overline{ ext{SEC}}$
		SIGNATU	RE & DATE
MARKS A	WARDED:		

Version: 1.0

Date:

NATIONAL UNIVERSITY OF COMPUTER AND EMERGING SCIENCES (NUCES), KARACHI

Prepared by:

Amin Sadiq

Lab Session 01 CONFIGURATION OF VS 2019

Lab Session 01: CONFIGURATION OF VS 2019

Objectives:


- Introduction to Visual Studio 2019
- An introduction to Assembly Language
- Understanding the Visual Studio 2019
- Configuring Visual Studio 2019 to activate MASM assembler
- Running a test program

Section 1: Introduction to visual studio 2019


Visual Studio (for all its versions) is an integrated development environment (IDE) from Microsoft. It is a leading tool to develop computer programs, as well as web sites, web applications and web services. For this course, we will use Visual Studio version 2019 to develop programs in Assembly Language. We could, however, use a stand-alone assembler like NASM or MASM to code in Assembly Language.

Installation Process

Go to this link https://visualstudio.microsoft.com/downloads/ and select VS 2019 Download for community version



Run that downloaded setup on your system and when it's complete, you have to download and install **Desktop Development with C++**. When it's done you are ready to go.




Configuration vs2019 for assembly language


Click here to download Irvine library from this link: www.asmirvine.com/gettingStartedVS2019/Irvine.zip

Once you have downloaded the required Irvine library, install it in your computer and verify that a folder named Irvine has been created in your C:\ drive. Now, follow these steps to configure Visual Studio 2019:

1. Start Microsoft Visual Studio 2019. If you are running it for the first time then this would be the screen you may see




2. From languages select C++, and then create an empty project




3. Once your new project is created, press **Ctrl+Alt+L** to open **Solution Explorer**. In the solution explorer window, you would see your project's file hierarchy.

Select

Create a new project.




Tick the **masm** checkbox & select **OK**.




4. Right-click on **Source Files** in solution explorer & select **Add > New Item**.


Now go to **Utility > Text File** to add a new file, but we do not want to add .txt file, instead we want to add a .asm file. So, rename your new text file as Test.asm (we can choose any other name e.g. xyz.asm but for this tutorial we will use the name Test.asm).



 Now right-click your project again and click **Properties**. Now click the tiny arrow marker besides **Configuration Properties** to expand it. Now click **Microsoft Macro Assembler** and expand it.




- 6. Now click **General** entry under Microsoft Macro Assembler and then set the value of **Include Paths** as **C:\Irvine**. The menu should now like this.
- 7. Click Linker tab to expand it. Select General and set the value of Additional Library Directories to C:\Irvine



Our Visual Studio 2019 configuration for Assembly Language is complete. We can now write a sample program and run it to test our project. Open Test.asm from the solution explorer by doubleclicking it. The Test.asm file will contain all the code that we write in our program. Go on and copy the following code onto your Test.asm file.

TITLE My First Program (Test.asm)
INCLUDE Irvine32.inc

8. Click **Input**, select **Additional Dependencies**. You will see a list of different .lib file names written there, do not alter any of those. Write **irvine32.lib**; at the start of the list like this.



```
Microsoft Visual Studio Debug Console

EAX=00000010 EBX=00000025 ECX=005910AA EDX=005910AA EDX=005910AA EDX=005910AA EDI=005910AA EDX=005910AA EDX=0
```

.code main



PROC mov eax, 10h mov ebx, 25h call DumpRegs exit main ENDP END main

Press **Ctrl+F5** to see the output in console window.

As we can see in the output window, the program has affected two registers eax & ebx. Let us dissect our code line by line to see what it does.

The first line TITLE MyFirstProgram (Test.asm) gives an optional title to our program. The second line INCLUDE irvine32.inc adds a reference to the include file that links your program to the Irvine library. The third line .code defines the beginning of the code segment (to be covered in detail later). The code segment is the segment of memory where all your code resides. In the fourth line, a main procedure is defined. The fifth and sixth lines show a mnemonic mov (to be covered in detail later) that 'moves' values 10h and 25h to eax and ebx, respectively. The radix h defines a hexadecimal constant.

The lines seven and eight calls the procedure DumpRegs that outputs the current values of the registers followed by a call to windows procedure named exit that halts the program. The lines nine and ten mark the end of the main procedure.

SECTION 2: DEBUGGING OUR PROGRAM

We have seen how to configure Visual Studio 2019 for Assembly Language and tested it with a sample program. The output of our sample program was displayed using a console window but it is usually more desirable to watch the step by step execution of our program with each line of code using breakpoints.

Let us briefly define the keywords relevant to debugging in Visual Studio and then we will cover an example for understanding.

Debugger

The (Visual Studio) debugger helps us observe the run-time behavior of our program and find problems. With the debugger, we can break execution of our program to examine our code, examine and edit variables, view registers, see the instructions created from our source code, and view the memory space used by our application.

BREAKPOINT

A breakpoint is a signal that tells the debugger to temporarily suspend execution of your program at a certain point. When execution is suspended at a breakpoint, your program is said to be in break mode.

CODE STEPPING


One of the most common debugging procedures is stepping: executing code one line at a time. The Debug menu provides three commands for stepping through code:

- Step Into (By pressing F11)
- Step Over (By pressing F10) Step Out (Shift+F11)


SINGLE STEPPING

To see the values of internal registers and memory variables during execution, let us use an example. Copy the following code onto your Test.asm file.k


1. Right-click on line 6 to insert a breakpoint.



2. Click on **Debug** tab from the toolbar, select **Start Debugging** OR press **F10** to start stepping over the code.




3. Click on **Debug** tab than select Windows after that open menu and select **Registers** option.



4. Breakpoint set on 1st instruction






Press **F10** again to execute next line.

```
;EAX=10000h
mov eax, 10000h
add eax,40000h
                  ;EAX=50000h
sub eax,20000h
                   ;EAX=30000h
call DumpRegs
```

```
▼ 🗖 X
EAX = 00010000 EBX = 7E97F000 ECX = 003E1005 EDX = 000E1005 EDX =
```

National University of Computer & Emerging Sciences, Karachi

Again press **F10** key for next instruction execution.



Press **F10** again, the program will not terminate after executing the current instruction and as soon as it reaches the line with a call to **DumpRegs**

SECTION 2: EXERCISE

- 1. Install Visual Studio 2019 & create a new Visual C++ project for Assembly Language.
- 2. Configure the project using the steps show in this lab.
- 3. Run a test program in console window by changing the value of EAX in line 6 to 8500h.
- 4. Debug the below program and note down the values of all the registers after the execution of each line.


TITLE My First Program (Test.asm) INCLUDE Irvine32.inc

```
.code
main PROC
mov eax, 47h
mov ebx, 39h
mov ecx, 60h
add eax, ebx add
eax, ecx mov
ebx, 85h mov
ecx, 64h add
eax, ebx add
eax, ecx
call DumpRegs
```

exit


main ENDP END main

Task 1:



Task 2:


Task 2 includes Run a test program in console window by changing the value of EAX in line 6 to 8500h.



Task 3:




```
Task 3.asm
          INCLUDE Irvine32.inc
          .code
         main PROC
         mov eax, 47h
         mov ebx, 39h
         mov ecx, 60h
          add eax, ebx
          add eax, ecx
          mov ebx, 85h
         mov ecx, 64h
     11
         add eax, ebx
     12
         add eax, ecx
     13
         call DumpRegs
     14
         exit
     15
         main ENDP
         END main
     16
```




DEBUGGING TASK Code:





Output:



Debugging now:

