

BIEK LECTURE-WISE STUDY GUIDES

BIEK Computer Science XI

One PDF per lecture — plus a full chapter pack for each unit.

Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — گیارہویں جماعت

XI

Lecture index

Chapter packs are named **Lecture 01–06**. Individual topics are **ChNN-LNN**. ★ marks Golden (high-yield) exam topics.

Code	File	Title
Lecture 01	CS-XI-Lecture-01-Computer-Systems.pdf	Computer Systems
Ch01-L01	CS-XI-Ch01-L01-1.1.1-1.1.2-Discrete-vs-Continuous-Digital-Systems.pdf	1.1.1 & 1.1.2 Discrete vs Continuous & Digital Systems
Ch01-L02	CS-XI-Ch01-L02-1.1.3-Analog-and-Digital-Signals.pdf	1.1.3 Analog and Digital Signals ★
Ch01-L03	CS-XI-Ch01-L03-1.1.4-1.1.6-Boolean-Algebra-Operations-Truth-Tables.pdf	1.1.4 – 1.1.6 Boolean Algebra, Operations & Truth Tables
Ch01-L04	CS-XI-Ch01-L04-1.1.7-Basic-Logic-Gates-AND-OR-NOT.pdf	1.1.7 Basic Logic Gates (AND, OR, NOT) ★
Ch01-L05	CS-XI-Ch01-L05-1.1.7-Universal-Advanced-Logic-Gates.pdf	1.1.7 Universal & Advanced Logic Gates
Ch01-L06	CS-XI-Ch01-L06-1.1.8-1.1.11-Logic-Expressions-Minterms-Diagrams.pdf	1.1.8 – 1.1.11 Logic Expressions, Minterms & Diagrams ★
Ch01-L07	CS-XI-Ch01-L07-1.1.13-Karnaugh-Maps-K-Maps-Simplification.pdf	1.1.13 Karnaugh Maps (K-Maps) Simplification ★
Ch01-L08	CS-XI-Ch01-L08-LogiSim-Simulation-Tool-Guide.pdf	LogiSim Simulation Tool Guide
Ch01-L09	CS-XI-Ch01-L09-1.2.1-1.2.3-Software-Development-Life-Cycle-SDLC.pdf	1.2.1 – 1.2.3 Software Development Life Cycle (SDLC) ★
Ch01-L10	CS-XI-Ch01-L10-1.2.4-1.2.7-Waterfall-vs-Agile-Models-Case-Studies.pdf	1.2.4 – 1.2.7 Waterfall vs Agile Models & Case Studies ★
Ch01-L11	CS-XI-Ch01-L11-1.3.1-1.3.4-Communication-Models-OSI-7-Layer-Model.pdf	1.3.1 – 1.3.4 Communication Models & OSI 7-Layer Model ★
Ch01-L12	CS-XI-Ch01-L12-1.3.5-1.3.6-TCP/IP-Model-vs-OSI-Model.pdf	1.3.5 – 1.3.6 TCP/IP Model vs OSI Model
Lecture 02	CS-XI-Lecture-02-Computational-Thinking-Algorithm.pdf	Computational Thinking & Algorithm
Ch02-L01	CS-XI-Ch02-L01-2.1-2.2-Introduction-to-CT-Algorithms.pdf	2.1 & 2.2 Introduction to CT & Algorithms ★

Code	File	Title
Ch02-L02	CS-XI-Ch02-L02-2.2.2-Algorithm-vs-Pseudocode.pdf	2.2.2 Algorithm vs Pseudocode ★
Ch02-L03	CS-XI-Ch02-L03-2.3.1-Algorithmic-Strategy-Decomposition.pdf	2.3.1 Algorithmic Strategy: Decomposition ★
Ch02-L04	CS-XI-Ch02-L04-2.3.2-Algorithmic-Strategy-Pattern-Recognition.pdf	2.3.2 Algorithmic Strategy: Pattern Recognition
Ch02-L05	CS-XI-Ch02-L05-2.3.3-Algorithmic-Strategy-Abstraction.pdf	2.3.3 Algorithmic Strategy: Abstraction
Ch02-L06	CS-XI-Ch02-L06-2.4.1-Sorting-Algorithms-Bubble-Sort.pdf	2.4.1 Sorting Algorithms: Bubble Sort ★
Ch02-L07	CS-XI-Ch02-L07-2.4.1-Sorting-Algorithms-Selection-Sort.pdf	2.4.1 Sorting Algorithms: Selection Sort ★
Ch02-L08	CS-XI-Ch02-L08-2.4.2-Searching-Algorithms-Linear-Search.pdf	2.4.2 Searching Algorithms: Linear Search
Ch02-L09	CS-XI-Ch02-L09-2.4.2-Searching-Algorithms-Binary-Search.pdf	2.4.2 Searching Algorithms: Binary Search ★
Ch02-L10	CS-XI-Ch02-L10-2.5-Evaluation-Criteria-of-Algorithm.pdf	2.5 Evaluation Criteria of Algorithm
Ch02-L11	CS-XI-Ch02-L11-2.6-How-to-Decide-Which-Algorithm-to-Use.pdf	2.6 How to Decide Which Algorithm to Use
Lecture 03	CS-XI-Lecture-03-Programming-Fundamentals.pdf	Programming Fundamentals
Ch03-L01	CS-XI-Ch03-L01-3.1-Programming-Language-Types.pdf	3.1 Programming & Language Types
Ch03-L02	CS-XI-Ch03-L02-3.2-Career-Growth-with-Python.pdf	3.2 Career Growth with Python
Ch03-L03	CS-XI-Ch03-L03-3.3-Integrated-Development-Environment-IDE-VS-Code.pdf	3.3 Integrated Development Environment (IDE) & VS Code
Ch03-L04	CS-XI-Ch03-L04-3.4-Fundamentals-of-Python-Programming.pdf	3.4 Fundamentals of Python Programming ★
Ch03-L05	CS-XI-Ch03-L05-3.4.1-Variables-and-Data-Types.pdf	3.4.1 Variables and Data Types ★
Ch03-L06	CS-XI-Ch03-L06-3.4.2-Input-Output-Handling.pdf	3.4.2 Input Output Handling

Code	File	Title
Ch03-L07	CS-XI-Ch03-L07-3.4.3-Operators-and-Operands-Arithmetic-Relational-Bitwise.pdf	3.4.3 Operators and Operands (Arithmetic, Relational, Bitwise) ★
Ch03-L08	CS-XI-Ch03-L08-3.5-Control-Structures-Overview.pdf	3.5 Control Structures Overview ★
Ch03-L09	CS-XI-Ch03-L09-3.5.1-Sequence.pdf	3.5.1 Sequence
Ch03-L10	CS-XI-Ch03-L10-3.5.2-Selection-Statements-if-if-else-if-elif-else-nested.pdf	3.5.2 Selection Statements (if, if-else, if-elif-else, nested) ★
Ch03-L11	CS-XI-Ch03-L11-3.5.3-Repetition-Statements-for-loop-while-loop.pdf	3.5.3 Repetition Statements (for loop, while loop) ★
Ch03-L12	CS-XI-Ch03-L12-3.6-Libraries-in-Python-Built-in-Third-Party.pdf	3.6 Libraries in Python (Built-in & Third-Party)
Ch03-L13	CS-XI-Ch03-L13-3.7-Debugging-Code-in-Python.pdf	3.7 Debugging Code in Python
Lecture 04	CS-XI-Lecture-04-Data-and-Analysis.pdf	Data and Analysis
Ch04-L01	CS-XI-Ch04-L01-4.1.1-Data-Information-and-Database.pdf	4.1.1 Data, Information and Database
Ch04-L02	CS-XI-Ch04-L02-4.1.2-Database-Management-System-DBMS.pdf	4.1.2 Database Management System (DBMS)
Ch04-L03	CS-XI-Ch04-L03-4.2-Database-Components-Tables-Records-Fields.pdf	4.2 Database Components (Tables, Records, Fields)
Ch04-L04	CS-XI-Ch04-L04-4.3.1-Keys-and-Integrity-Constraints.pdf	4.3.1 Keys and Integrity Constraints ★
Ch04-L05	CS-XI-Ch04-L05-4.3-Relational-Database-Management-System-RDBMS.pdf	4.3 Relational Database Management System (RDBMS)
Ch04-L06	CS-XI-Ch04-L06-4.4-Entity-Relationship-Model-ER-Model.pdf	4.4 Entity Relationship Model (ER-Model) ★
Ch04-L07	CS-XI-Ch04-L07-4.5-Referential-Integrity-Cascade-Update-Delete.pdf	4.5 Referential Integrity (Cascade Update & Delete) ★
Ch04-L08	CS-XI-Ch04-L08-4.6-Relational-Schema-Development.pdf	4.6 Relational Schema Development
Ch04-L09	CS-XI-Ch04-L09-4.7-Case-Study-Library-Management-System.pdf	4.7 Case Study — Library Management System

Code	File	Title
Ch04-L10	CS-XI-Ch04-L10-4.8-Different-Database-Objects-Tables-Forms-Queries-Reports.pdf	4.8 Different Database Objects (Tables, Forms, Queries, Reports)
Ch04-L11	CS-XI-Ch04-L11-4.9-Creation-of-Tables-in-Microsoft-Access.pdf	4.9 Creation of Tables in Microsoft Access
Ch04-L12	CS-XI-Ch04-L12-4.10-Designing-Forms-for-Data-Manipulation.pdf	4.10 Designing Forms for Data Manipulation
Ch04-L13	CS-XI-Ch04-L13-4.11-Creating-Queries-in-MS-Access.pdf	4.11 Creating Queries in MS Access ★
Ch04-L14	CS-XI-Ch04-L14-4.11.4-Data-Summarization-Statistical-Analysis.pdf	4.11.4 Data Summarization & Statistical Analysis
Ch04-L15	CS-XI-Ch04-L15-4.11.6-Data-Visualization-in-MS-Access-Charts.pdf	4.11.6 Data Visualization in MS Access (Charts)
Lecture 05	CS-XI-Lecture-05-Application-and-Impacts-of-Computing.pdf	Application and Impacts of Computing
Ch05-L01	CS-XI-Ch05-L01-5.1-Introduction-to-Computing-Impacts.pdf	5.1 Introduction to Computing Impacts
Ch05-L02	CS-XI-Ch05-L02-5.1.1-Artificial-Intelligence-AI.pdf	5.1.1 Artificial Intelligence (AI) ★
Ch05-L03	CS-XI-Ch05-L03-5.1.2-Internet-of-Things-IoT-Components.pdf	5.1.2 Internet of Things (IoT) & Components ★
Ch05-L04	CS-XI-Ch05-L04-5.1.3-Data-Analytics-Components.pdf	5.1.3 Data Analytics & Components
Ch05-L05	CS-XI-Ch05-L05-Table-IoT-vs-AI-vs-Data-Analytics-Comparison.pdf	Table: IoT vs AI vs Data Analytics Comparison
Ch05-L06	CS-XI-Ch05-L06-5.2-Uses-of-IoT-in-Different-Areas.pdf	5.2 Uses of IoT in Different Areas
Ch05-L07	CS-XI-Ch05-L07-5.2.1-Scope-of-AI-in-Education-in-Pakistan.pdf	5.2.1 Scope of AI in Education in Pakistan
Ch05-L08	CS-XI-Ch05-L08-5.3-Information-Sources-Primary-Secondary-Tertiary.pdf	5.3 Information Sources (Primary, Secondary, Tertiary) ★
Ch05-L09	CS-XI-Ch05-L09-5.4-Impacts-of-Computing-in-Various-Fields.pdf	5.4 Impacts of Computing in Various Fields
Ch05-L10	CS-XI-Ch05-L10-5.5-Assistive-Technologies.pdf	5.5 Assistive Technologies ★
Ch05-L11	CS-XI-Ch05-L11-5.5.1-Importance-of-Assistive-Technologies.pdf	5.5.1 Importance of Assistive Technologies

Code	File	Title
Ch05-L12	CS-XI-Ch05-L12-5.5.2-Career-Connection-in-Assistive-Tech.pdf	5.5.2 Career Connection in Assistive Tech
Lecture 06	CS-XI-Lecture-06-Digital-Literacy.pdf	Digital Literacy
Ch06-L01	CS-XI-Ch06-L01-6.1-6.2-Introduction-to-Digital-Literacy.pdf	6.1 & 6.2 Introduction to Digital Literacy
Ch06-L02	CS-XI-Ch06-L02-6.3-Types-of-Data-Qualitative-vs-Quantitative.pdf	6.3 Types of Data (Qualitative vs Quantitative) ★
Ch06-L03	CS-XI-Ch06-L03-6.4-Data-Collection-Strategies.pdf	6.4 Data-Collection Strategies ★
Ch06-L04	CS-XI-Ch06-L04-6.4.1-6.4.2-Interviews-and-Surveys.pdf	6.4.1 – 6.4.2 Interviews and Surveys ★
Ch06-L05	CS-XI-Ch06-L05-6.4.3-6.4.5-Prototypes-Observation-and-Simulations.pdf	6.4.3 – 6.4.5 Prototypes, Observation, and Simulations ★
Ch06-L06	CS-XI-Ch06-L06-6.5-Primary-and-Secondary-Data.pdf	6.5 Primary and Secondary Data ★
Ch06-L07	CS-XI-Ch06-L07-6.6-Designing-a-Data-Collection-Approach.pdf	6.6 Designing a Data-Collection Approach
Ch06-L08	CS-XI-Ch06-L08-6.7-Presenting-Data-Using-Digital-Tools.pdf	6.7 Presenting Data Using Digital Tools
Ch06-L09	CS-XI-Ch06-L09-6.7.1-6.7.4-Spreadsheets-Presentations-Infographics-Reports.pdf	6.7.1 – 6.7.4 Spreadsheets, Presentations, Infographics, Reports
Ch06-L10	CS-XI-Ch06-L10-6.8-Case-Study-Digital-Inquiry-Project.pdf	6.8 Case Study: Digital Inquiry Project ★
Ch06-L11	CS-XI-Ch06-L11-Step-1-3-Advanced-Search-Methodology.pdf	Step 1 – 3: Advanced Search & Methodology ★
Ch06-L12	CS-XI-Ch06-L12-Step-4-6-Survey-Prep-Primary-Data-Collection.pdf	Step 4 – 6: Survey Prep & Primary Data Collection ★
Ch06-L13	CS-XI-Ch06-L13-Step-7-9-Secondary-Data-Spreadsheet-Organization.pdf	Step 7 – 9: Secondary Data & Spreadsheet Organization ★
Ch06-L14	CS-XI-Ch06-L14-Step-10-12-Data-Analysis-Conclusion-Artefact.pdf	Step 10 – 12: Data Analysis, Conclusion & Artefact ★
Lecture 07	CS-XI-Lecture-07-Final-Revision-and-Mock-Paper.pdf	Final Revision and Mock Paper

Lecture 01

Computer Systems

Chapter lecture — 12 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XI · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — گیارہویں جماعت

12 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XI

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیئریر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

Lectures in this pack

Chapter 1: Computer Systems. Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 1.1.1 & 1.1.2 Discrete vs Continuous & Digital Systems

L02. 1.1.3 Analog and Digital Signals

L03. 1.1.4 – 1.1.6 Boolean Algebra, Operations & Truth Tables

L04. 1.1.7 Basic Logic Gates (AND, OR, NOT)

L05. 1.1.7 Universal & Advanced Logic Gates

L06. 1.1.8 – 1.1.11 Logic Expressions, Minterms & Diagrams

L07. 1.1.13 Karnaugh Maps (K-Maps) Simplification

L08. LogiSim Simulation Tool Guide

L09. 1.2.1 – 1.2.3 Software Development Life Cycle (SDLC)

L10. 1.2.4 – 1.2.7 Waterfall vs Agile Models & Case Studies

L11. 1.3.1 – 1.3.4 Communication Models & OSI 7-Layer Model

L12. 1.3.5 – 1.3.6 TCP/IP Model vs OSI Model

Computer Systems

This chapter shows you how a computer thinks in 0s and 1s, how logic gates turn those bits into decisions, how software is planned and built step by step, and how data travels across a network. These three ideas — digital logic, software development and communication models — are the foundation of everything else in Computer Science.

اس باب میں آپ سیکھیں گے کہ کمپیوٹر صفر اور ایک کی زبان میں کیسے کام کرتا ہے، لاجک گیٹس فیصلے کیسے کرتے ہیں، سافٹ ویئر مرحلہ وار کیسے بنایا جاتا ہے، اور نیٹ ورک پر ڈیٹا ایک جگہ سے دوسری جگہ کیسے پہنچتا ہے۔

What you will learn

- Tell the difference between discrete and continuous quantities, and between analog and digital signals, with examples.
- Use the Boolean operations AND, OR and NOT, and apply the order of precedence.
- Draw the symbol, write the expression and give the truth table of AND, OR, NOT, NAND, NOR, XOR and XNOR gates.
- Simplify Boolean expressions using 2-variable and 3-variable Karnaugh maps.
- Describe the six phases of the SDLC and compare the Waterfall and Agile models using case studies.
- State the advantages of digital systems.
- Build a complete truth table for any expression with 2 or 3 inputs.
- Write minterms (SOP) and maxterms (POS) from a truth table, and draw a logic diagram from an expression.
- Build and test a simple circuit in LogiSim Evolution.
- Explain the seven layers of the OSI model and map them to the four layers of the TCP/IP model.

1.1.1 & 1.1.2 Discrete vs Continuous & Digital Systems

LEARN IT

Everything around you that can be measured or counted is a **quantity**. Quantities come in two kinds.
Discrete quantities are separate, countable items with specific values. You can count them one by one: 1, 2, 3 ... There is nothing "in between". You cannot have 2.5 students in a classroom.
Continuous quantities can take any value within a range. They flow smoothly without breaks. Water can be 30 °C, 30.5 °C, 30.51 °C, and so on — there is always another value in between.

Discrete (counted)	Continuous (measured)
Number of students in a classroom	Temperature of water
Number of cars in a parking lot	Speed of a moving car
Has fixed, separate values	Has any value in a range



Stairs have fixed steps (discrete). A ramp lets you stand at any point (continuous).

REMEMBER IT

Stairs vs Ramp. On stairs you can only stand on step 1, 2 or 3 — that is discrete data. On a ramp you can stand at any height — that is continuous data. Ask yourself: "Do I count it or measure it?" Count → discrete. Measure → continuous.

COMMON MISTAKE

Students sometimes say "money is continuous because amounts are large". No — rupees and paise are counted in fixed units, so money is discrete. Size does not matter; what matters is whether values in between are possible.

اُردو میں سمجھیں

منفصل (Discrete) مقداریں وہ ہیں جنہیں ایک ایک کرکے گنا جا سکتے، جیسے کلاس میں طلبہ کی تعداد۔ مسلسل (Continuous) مقداریں کسی حد تک اندر کوئی بھی قیمت لے سکتی ہیں، جیسے پانی کا درجہ حرارت۔ سبزہاں منفصل ڈینڈا کی مثال ہیں اور لہلہاں (ریڑی) مسلسل ڈینڈا کی۔

CHECK YOURSELF

1. Is the number of pages in a book discrete or continuous?
2. Is your height discrete or continuous?
3. In the stairs/ramp analogy, which one shows continuous data?

Answers: 1. Discrete (you count pages). 2. Continuous (height is measured and can be any value). 3. The ramp.

LEARN IT

A **digital system** is an electronic system that uses only two values: 0 and 1. These two values are called **binary digits**, or **bits** for short.

- 0 represents OFF, LOW, or FALSE.
- 1 represents ON, HIGH, or TRUE.

Why only two values? Because it is easy for an electronic circuit to tell "voltage present" from "no voltage". Every number, letter, photo and song in a computer is finally stored as a long pattern of these bits.

Advantages of digital systems

Advantage	Detail
Reliable	Less affected by noise and interference.
Accurate	No loss of quality when copying data.
Easy to design	Only two states (0 and 1) to handle.
Programmable	Can be easily controlled by software.

Examples of digital systems

- Computers:** process data as 0s and 1s.
- Smartphones:** store photos and music as binary data.
- Digital cameras:** capture images as binary code.

WORKED EXAMPLE

Why is copying digital data "accurate"?

- Step 1: A song is stored as bits, for example 10110010...
- Step 2: When you copy it to a USB, the computer copies each bit exactly: 1 stays 1, 0 stays 0.
- Step 3: Even after 100 copies the bits are identical, so the song sounds the same. An old cassette tape (analog) loses a little quality every time it is copied.

REMEMBER IT

Think of a bit as a light switch: it is either ON (1) or OFF (0). A digital system is a huge panel of such switches.

اُردو میں سمجھیں

ڈیجیٹل نظام صرف دو قیمتیں استعمال کرتا ہے: 0 اور 1، جنہیں بیت (Bit) کہتے ہیں۔ 0 کا مطلب بند، کم یا غلط ہے اور 1 کا مطلب چالو، زیادہ یا درست ہے۔ ڈیجیٹل نظام قابلِ پھروسا، درست، بنانے میں آسان اور سافٹ ویئر سے قابو میں رہنے والے ہوتے ہیں۔

CHECK YOURSELF

1. What does a 1 represent in a digital system?
2. Give two advantages of digital systems.

Answers: 1. ON, HIGH or TRUE. 2. Any two of: reliable (less affected by noise), accurate (no loss when copying), easy to design (two states), programmable (controlled by software).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A discrete quantity is: a. Counted in separate steps b. Any value on a smooth range c. Always analog d. A sine wave	MCQ 2. Temperature of tea is: a. Continuous b. Discrete c. Only Boolean d. A gate	MCQ 3. Number of students in a class is: a. Discrete b. Continuous c. Analog voltage d. A ramp	MCQ 4. The stairs vs ramp analogy: stairs are: a. Discrete b. Continuous c. TCP d. Agile	MCQ 5. Digital systems use: a. 0 and 1 b. Every real number c. Only sine waves d. Paper only	MCQ 6. A bit is: a. A binary digit, 0 or 1 b. Eight bytes c. A logic gate d. A database
---	--	---	---	---	--

Extra short questions

1. Differentiate discrete and continuous with one example each.
2. Why do computers prefer digital values?
3. What is a digital system?
4. Give two advantages of digital systems.

Extra long question

1. With a labelled stairs/ramp sketch, explain discrete vs continuous and link both to analog vs digital signals.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Discrete: countable steps (cars in a park). Continuous: any value in a range (speed of a car).
2. Bits 0/1 can be restored after noise; analog waves are bent by interference.
3. An electronic system that stores and processes only two values, 0 and 1.
4. Reliable (noise resistant), accurate copies, easy to design (two states), programmable.


Long

1. Stairs = discrete/digital (fixed levels). Ramp = continuous/analog (smooth). Computers convert analog measurements into bits, process bits, then convert back if a human must see the result.

1.1.3 Analog and Digital Signals ★ Golden

LEARN IT

A **signal** is a changing voltage (or other quantity) that carries information.
Analog signals are continuous signals that change smoothly over time, like a **sine wave**. Examples: the human voice, a traditional mercury thermometer.
Digital signals have only two levels: **HIGH (1)** and **LOW (0)**. They jump instantly between these values, which creates a **square wave**. Example: computer data.



An analog signal changes smoothly; a digital signal jumps between only two levels.

Feature	Analog data	Digital data
Nature	Continuous flow.	Discrete, separate values (bits).
Wave shape	Sine wave (smooth curve).	Square wave (sudden jumps).
Reliability	Low (affected by noise).	High (resistant to noise).
Examples	Human voice, traditional thermometer.	Computer data.

WORKED EXAMPLE

Why is digital more resistant to noise?

Step 1: Suppose a wire carries 5 V for HIGH and 0 V for LOW.
Step 2: Noise adds a small error, so 5 V arrives as 4.6 V and 0 V arrives as 0.3 V.
Step 3: The receiver only asks "Is it closer to HIGH or LOW?" 4.6 V is still read as 1 and 0.3 V is still read as 0. The data is perfect.
Step 4: In an analog signal, every exact value carries meaning, so 4.6 V instead of 5 V really changes the sound or reading. The noise cannot be removed.

REMEMBER IT

Analog = A smooth curve. Digital = Doorsteps. Analog looks like ocean waves; digital looks like a castle wall (square teeth).

COMMON MISTAKE

Do not draw a digital signal with sloping sides. A digital signal jumps *instantly*, so its edges are straight vertical lines. Also do not confuse "digital" with "electronic": an analog signal can also be electronic.

اردو میں سمجھیں

اینا لگ سگنل وقت کے ساتھ ہموار انداز میں بدلتا ہے، جیسے سائن ویو (Sine Wave)؛ انسانی آواز اس کی مثال ہے۔ ڈیجیٹل سگنل کی صرف دو سطحیں ہوتی ہیں، HIGH (1) اور LOW (0)، اور یہ اچانک ایک سے دوسری پر جاتا ہے، اس لیے مربع لہر (Square Wave) بنتی ہے۔ ڈیجیٹل سگنل شور سے کم متاثر ہوتا ہے، اس لیے زیادہ قابلِ بھروسہ ہے۔

EXAM TIP

Common questions: "Differentiate between analog and digital signals" (3–4 marks) and "Draw an analog and a digital signal." Write the comparison as a table with at least three features (nature, wave shape, reliability, example). Always label your diagrams: axes V and t, and HIGH(1)/LOW(0) on the square wave.

CHECK YOURSELF

- What shape of wave does a digital signal make?
- Which type of signal is more affected by noise?
- Give one example of an analog signal.

Answers: 1. A square wave. 2. Analog. 3. Human voice (or a traditional thermometer reading).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An analog signal:

- a. Changes smoothly, like a sine wave
- b. Jumps only 0/1
- c. Is a truth table
- d. Is TCP

MCQ 2. A digital signal looks like:

- a. A square wave of HIGH and LOW
- b. A smooth sine
- c. A pie chart
- d. A stack

MCQ 3. Noise harms analog more because:

- a. Many in-between levels can be bent
- b. Bits cannot exist
- c. OSI has 7 layers
- d. Python is analog

MCQ 4. Human voice on a microphone is first:

- a. Analog
- b. A Boolean 1 only
- c. A K-map
- d. SQL

MCQ 5. HIGH in digital means:

- a. 1 / ON / TRUE
- b. 0 / OFF
- c. A continuous ramp
- d. Gray code

MCQ 6. Copying analog tape many times:

- a. Loses quality
- b. Stays perfect
- c. Creates bits
- d. Builds NAND

Extra short questions

- Define analog signal and digital signal.
- Give one example of each.
- Why is digital more reliable?
- What does a computer do with analog sound?

Extra long question

- Draw analogue (sine) and digital (square) waves. Tabulate nature and reliability. This is a ★ Golden 10-mark.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Analog: continuous, smooth change. Digital: only two levels, HIGH(1) and LOW(0), a square wave.
- Analog: traditional thermometer / voice. Digital: computer data / logic pulse.
- A bent 0 or 1 can be restored to a clean 0 or 1; analog distortion stays in the wave.
- Sample and quantise it into bits, process the bits, then convert back to analog for a speaker.

Long

- Sine labelled V against t; square labelled HIGH/LOW. Table: analog = continuous, low reliability; digital = discrete bits, high reliability. Close with the noise argument.

1.1.4 – 1.1.6 Boolean Algebra, Operations & Truth Tables

Concept	Description	Example
Variables	Letters that hold the value 0 or 1.	A, B, C, X, Y
Operations	Actions performed on variables.	AND, OR, NOT
Expressions	Combinations of variables and operations.	A AND B, Y = A + B

Some simple rules (laws) follow directly from the meaning of AND, OR and NOT. They are useful when you check or simplify answers:

OR rules	AND rules	NOT rules
$A + 0 = A$	$A \cdot 1 = A$	$(\overline{\overline{A}}) = A$
$A + 1 = 1$	$A \cdot 0 = 0$	$A + \overline{A} = 1$
$A + \overline{A} = 1$	$A \cdot \overline{A} = 0$	$A \cdot \overline{A} = 0$

WORKED EXAMPLE

Using law: Simplify $Y = AB + AB$.
Step 1 Both terms contain B, so take B out: $Y = B(A + A)$.
Step 2 $A + A = 1$ (a variable OR its opposite is always 1).
Step 3 $Y = B \cdot 1 = B$.

COMMON MISTAKE

In Boolean algebra “+” means OR, not addition. So $1 + 1 = 1$ (TRUE OR TRUE is TRUE), not 2. There is no value bigger than 1.

آردو میں سمجھیں

جارج بول (George Boole) نے بنایا۔ اس میں صرف دو فیصلے ہوتے ہیں: درست (1) اور غلط (0)۔ متغیرات (Variables) جیسے A اور B صرف 0 یا 1 رکھتے ہیں۔ آپریٹرز AND، OR اور NOT ہیں اور ان کی مکالمے سے ایکسپریشن (Expressions) بنتا ہے۔

CHECK YOURSELF

1. Who developed Boolean algebra?

2. In Boolean algebra, what is $1 + 0$?

Answers: 1. George Boole. 2. 1 (Because + means OR).

LEARN IT

There are three basic Boolean operations. Every other operation can be made from them.

1. AND operation ($\cdot$) — gives output 1 only when ALL inputs are 1. Expression: $\overline{Y} = \overline{A \cdot B}$ (often written just AB).

2. OR operation ($+$) — gives output 1 when ANY input is 1. Expression: $Y = A + B$.

3. NOT operation ($\overline{}$) — inverts (flips) the input. If the input is 1 the output is 0, and if the input is 0 the output is 1. It is a unary operation, meaning it works on only one operand. Expression: $Y = \overline{A}$ (also written as A with a bar on top, $\overline{A}$).

Operation	Real life analogy
AND	A door with two locks. The door opens only when both locks are unlocked.
OR	A room with two doors. You can enter if either door is open.
NOT	A room light switch. When the switch is ON the room is lit; when it is OFF the room is dark — the state is the opposite of “dark”.

WORKED EXAMPLE

Evaluate each expression for $A = 1$, $B = 0$.

(a) $A \cdot B + 1 \cdot 0 = 0$ (not all inputs are 1).

(b) $A + B + 1 + 0 = 1$ (at least one input is 1).

(c) $\overline{B} + \overline{A} = 1$ (NOT flips 0 to 1).

(d) $A \cdot \overline{B} = 1 \cdot 1 = 1$

REMEMBER IT

AND is “strict” — everyone must agree (all 1s). OR is “easy-going” — one 1 is enough. NOT is “the rebel” — it always says the opposite.

آردو میں سمجھیں

AND آپریٹرز میں 1 بننا ہے جب تمام ان پٹ 1 ہیں (دونوں والے دروازے) OR آپریٹرز میں 1 بننا ہے جب کوئی ایک ان پٹ بھی 1 ہو (دونوں والے کمرے) NOT آپریٹرز ان پٹ کو الٹ دیتا ہے اور صرف ایک ان پٹ پر کام کرتا ہے اس لیے اسے یونیری (Unary) کہتے ہیں۔

CHECK YOURSELF

1. What symbol is used for the OR operation?

2. Why is NOT called a unary operation?

3. Find $A + \overline{B}$ when $A = 0$, $B = 1$.

Answers: 1. +. 2. Because it works on only one operand (one input). 3. $\overline{B} = 0$, so $0 + 0 = 0$.

LEARN IT

A truth table shows all possible input combinations and the output for each one, for a logic gate or circuit. It is the “complete record” of how the circuit behaves.

How to create a truth table:

- Count the number of inputs (n).
- Calculate total rows = 2^n .
- List all input combinations in binary counting order (0, 1, 2, 3 ... in binary).
- Calculate the output for each combination.

2-input example ($n = 2$, rows = 4)

A	B	Combination
0	0	Row 1
0	1	Row 2
1	0	Row 3
1	1	Row 4

3-input example ($n = 3$, rows = 8)

A	B	C	Decimal
0	0	0	0
0	0	1	1
0	1	0	2
0	1	1	3
1	0	0	4
1	0	1	5
1	1	0	6
1	1	1	7

REMEMBER IT

Quick fill trick for 3 inputs: In column C write 0,0,1,1... (change every row). In column B write 0,0,1,1,1,1 (change every 2 rows). In column A write 0,0,0,0,1,1,1,1 (change every 4 rows). For n inputs the leftmost column changes every 2^{n-1} rows.

WORKED EXAMPLE

Make the truth table of a 3-input AND $\overline{Y} = \overline{A \cdot B \cdot C}$.

Step 1: $n = 3$, so rows = $2^3 = 8$.

Step 2: List the 8 combinations in binary order.

Step 3: AND gives 1 only when all inputs are 1, so only row 7 (111) gives 1.

A	B	C	$Y = A \cdot B \cdot C$
0	0	0	0
0	0	1	0
0	1	0	0
0	1	1	0
1	0	0	0
1	0	1	0
1	1	0	0
1	1	1	1

COMMON MISTAKE

Do not fill rows in a random order — you may miss or repeat a combination. Always count in binary from 000 to 111. Also remember rows = 2^n , not $2 + n$. 3 inputs give 8 rows, not 6.

آردو میں سمجھیں

جوتابہ قبل (Truth Table) کسی گیت یا سرکٹ کی تمام ممکنہ ان پٹ اور ان کی آؤٹ پٹ دکھاتا ہے۔ اگر ان پٹ 4 ہیں تو قطاریں (Rows) 2 کی طاقت 4 ہیں گی۔ دو ان پٹ کی لیے 4 اور تین ان پٹ کی لیے 8 قطاریں۔ ان پٹ بعینہ پانچویں ترتیب میں لکھیں۔

CHECK YOURSELF

1. How many rows does a truth table with 4 inputs have?

2. In a 3-input table, what is the 8th row (counting from row 1 = 000)?

Answers: 1. $2^4 = 16$. 2. 101.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Boolean algebra uses: a. TRUE/F and FALSE/0 only b. All real numbers c. ASCII letters d. IPv4	MCQ 2. AND is 1 only when: a. Every input is 1 b. Any input is 1 c. Inputs differ d. There is no input	MCQ 3. OR is 1 when: a. Any input is 1 b. All inputs are 0 c. Inputs are equal d. NOT is applied twice	MCQ 4. NOT of 1 is: a. 0 b. 1 c. 2 d. A	MCQ 5. Rows in an n-input truth table: a. 2^n b. n c. n^2 d. $n+1$	MCQ 6. Two-input truth table has: a. 4 rows b. 2 rows c. 8 rows d. 16 rows
---	---	---	--	---	---

Extra short questions

- Who developed Boolean algebra and what two values does it use?
- With $\overline{Y} = \overline{A \cdot B}$ and $Y = A + B$ in words.
- Why is NOT called unary?
- List the four steps to build a truth table.

Extra long question

- Write complete truth tables for 2-input AND, OR and 1-input NOT. Add one real-life lock/door/switch example each.

Extra answer key

MCQs: 1. A, 2. A, 3. A, 4. A, 5. A, 6. A

Short

- George Boole, TRUE/F and FALSE/0.
- AND: output 1 only if all inputs are 1. OR: output 1 if any input is 1.
- It has only one operand: it inverts a single input.
- Count inputs n; rows = 2^n ; list combinations in binary order; compute each output.


Long

- AND: 0001 on AB=11 (two locks), OR: 0111 (two doors), NOT: 10 / 01 (light switch). Show all four-two rows.

1.1.7 Basic Logic Gates (AND, OR, NOT) ★ Golden

LEARN IT

Logic gates are electronic circuits that perform Boolean operations. They take one or more input bits and produce one output bit. They are the **building blocks of all digital systems** — a processor contains billions of them. The three basic gates match the three basic operations: the **AND gate**, the **OR gate** and the **NOT gate** (also called an **inverter**).



Symbols of the basic gates. AND has a flat back and round front ("D" shape); OR has a curved back and pointed front; NOT is a triangle with a small circle (bubble).

AND gate — $Y = A \cdot B$

A	B	Y
0	0	0
0	1	0
1	0	0
1	1	1

OR gate — $Y = A + B$

A	B	Y
0	0	0
0	1	1
1	0	1
1	1	1

NOT gate — $Y = A'$

A	Y
0	1
1	0

WORKED EXAMPLE

A school bell circuit. The bell (Y) should ring when the timer says "period over" ($A = 1$) **and** the school is open ($B = 1$).

Step 1: The bell needs both conditions, so use an AND gate: $Y = A \cdot B$.

Step 2: Sunday, timer fires: $A = 1$, $B = 0 \rightarrow Y = 1 \cdot 0 = 0$. No bell.

Step 3: Monday, timer fires: $A = 1$, $B = 1 \rightarrow Y = 1$. The bell rings.

If instead the bell should ring when *either* the timer fires or the principal presses a button, you would use an OR gate.

REMEMBER IT

Shortcut: AND output is 0 if any input is 0. OR output is 1 if any input is 1. Learn just the "special row": AND is 1 only at 11; OR is 0 only at 00.

COMMON MISTAKE

Do not mix up the AND and OR symbols. AND has a **flat** input side (like the letter D). OR has a **curved** input side and a **pointed** output, like a shield or arrowhead.

اردو میں سمجھیں

لاچک گیٹس الیکٹرانک سرکٹ میں جو پولین آپریشن انجام دیتے ہیں اور تمام ڈیجیٹل نظاموں کی بنیادی اینٹیں ہیں۔ AND گیٹ صرف تب 1 دیتا ہے جب دونوں ان پٹ 1 ہوں، OR گیٹ صرف تب 0 دیتا ہے جب دونوں ان پٹ 0 ہوں، اور NOT گیٹ ان پٹ کو الٹ دیتا ہے۔

EXAM TIP

You are often asked to "draw the symbol, write the expression and truth table" of a gate (2–3 marks each). Draw neat symbols with labelled inputs A, B and output Y. Write the full truth table in binary order. A frequent MCQ: "Which gate gives 1 only when all inputs are 1?" (AND).

CHECK YOURSELF

- What is the output of an OR gate when $A = 0$ and $B = 0$?
- What is another name for the NOT gate?
- For which input does a 2-input AND gate output 1?

Answers: 1. 0. 2. Inverter. 3. Only $A = 1$, $B = 1$.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Logic gates implement:

- Boolean operations in hardware
- SQL joins
- HTTP only
- Pie charts

MCQ 2. AND output is 1 for inputs 1,1:

- 1
- 0
- Z
- X

MCQ 3. OR of 1 and 0 is:

- 1
- 0
- NAND
- XOR

MCQ 4. The inverter is the:

- NOT gate
- AND gate
- Bus
- Router

MCQ 5. Building blocks of digital systems are:

- Logic gates
- Spreadsheets
- MVPs
- Fonts

MCQ 6. $Y = A \cdot B$ is the:

- AND expression
- OR expression
- XOR
- NOR

Extra short questions

- Define a logic gate.
- State the AND, OR, NOT expressions.
- Draw the truth table of 2-input AND from memory.
- Why is NOT drawn with a bubble?

Extra long question

- For AND, OR and NOT: symbol, expression, full truth table, and one daily-life model. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short


- An electronic circuit that performs a Boolean operation; the building block of digital systems.
- $Y = A \cdot B$; $Y = A + B$; $Y = A'$ (or $\bar{A}$).
- 00→0, 01→0, 10→0, 11→1.
- The bubble marks inversion of the input.

Long

- Standard IEC/US symbols. AND two locks, OR two doors, NOT a switch. Tables must have every row.

1.1.7 Universal & Advanced Logic Gates

LEARN IT
NAND means "NOT AND": it is an AND gate followed by a **NOT**. **NOR** means "NOT OR": an OR gate followed by a **NOT**. On the symbol, the NOT is shown as a small bubble at the output.
NAND and NOR are called **universal gates** because **any logic circuit in the world can be built using only NAND gates (or only NOR gates)**. Factories like this: they can mass-produce one type of chip and build everything from it.



NAND (NOT AND) — $Y = (A \cdot B)'$

A	B	AB	Y
0	0	0	1
0	1	0	1
1	0	0	1
1	1	1	0

NOR (NOT OR) — $Y = (A + B)'$

A	B	A+B	Y
0	0	0	1
0	1	1	0
1	0	1	0
1	1	1	0

WORKED EXAMPLE
Show that a **NAND gate can work as a NOT gate**.
Step 1: Connect the same input A to both inputs of the NAND gate. Then $Y = (A \cdot A)'$.
Step 2: Since $A \cdot A = A$, we get $Y = A'$.
Step 3: Check: $A = 0 \rightarrow (0 \cdot 0)' = 0' = 1$, $A = 1 \rightarrow (1 \cdot 1)' = 1' = 0$. This is exactly the NOT truth table.
In the same way, a **NOR gate** with both inputs tied together gives $(A + A)' = A'$. And a **NAND** followed by a **NAND-as-NOT** gives $((A \cdot B)')' = A \cdot B$, an **AND gate**. This is why they are "universal".

REMEMBER IT
NAND is the exact **opposite** of AND (0 only at 11). NOR is the exact opposite of OR (1 only at 00). Just flip the AND/OR output column.

COMMON MISTAKE
Do not forget the bubble. Without the small circle, a NAND symbol becomes an AND symbol and your answer is wrong. Also, $(A \cdot B)'$ is **not** the same as $A' \cdot B'$: for $A = 1, B = 0$, $(1 \cdot 0)' = 1$ but $0 \cdot 1 = 0$.

آردو میں سمجھیں

NAND کا مطلب ہے NOT AND اور NOR کا مطلب ہے NOT OR۔ انہیں یونیورسل (عامگیر) گیت کہتے ہیں کیونکہ صرف NAND یا صرف NOR گیتوں سے دنیا کا کوئی بھی لایک سرکٹ بنایا جا سکتا ہے۔ NAND صرف تب 0 دیتا ہے جب دونوں ان پٹ 1 ہوں، اور NOR صرف تب 1 دیتا ہے جب دونوں ان پٹ 0 ہوں۔

CHECK YOURSELF
1. Why are NAND and NOR called universal gates?
2. What is the NOR output for $A = 0, B = 1$?
3. How do you make a NOT gate from a NAND gate?
Answers: 1. Any logic circuit can be built using only NAND gates or only NOR gates. 2. 0. 3. Join both inputs together and feed A into them: $(A \cdot A)' = A'$.

LEARN IT
XOR (Exclusive OR) gives output 1 when the inputs are **different**. Expression: $Y = A \oplus B$. In terms of basic operations, $A \oplus B = A'B + AB'$.
XNOR (Exclusive NOR) is XOR followed by NOT. It gives output 1 when the inputs are the **same**. Expression: $Y = (A \oplus B)' = A'B' + AB$.
The XOR symbol is an OR symbol with an extra curved line at the input side. XNOR adds a bubble at the output.



XOR — $Y = A \oplus B$

A	B	Y
0	0	0
0	1	1
1	0	1
1	1	0

XNOR — $Y = (A \oplus B)'$

A	B	Y
0	0	1
0	1	0
1	0	0
1	1	1

All seven gates at a glance

A	B	AND	OR	NAND	NOR	XOR	XNOR
0	0	0	0	1	1	0	1
0	1	0	1	1	0	1	0
1	0	0	1	1	0	1	0
1	1	1	1	0	0	0	1

NOT has one input: $A \cdot 0 = 0$, $A \cdot 1 = 0$.

WORKED EXAMPLE
A staircase light. A light has one switch at the bottom (A) and one at the top (B) of a staircase. Flipping either switch should change the light.
Step 1: Start with both switches down: $A = 0, B = 0$, light off ($Y = 0$).
Step 2: Flip the bottom switch: $A = 1, B = 0 \rightarrow$ light on ($Y = 1$).
Step 3: Walk up and flip the top switch: $A = 1, B = 1 \rightarrow$ light off ($Y = 0$).
Step 4: The pattern 0, 1, 1, 0 is the XOR truth table. So the light is $Y = A \oplus B$.

REMEMBER IT
Memory trick: XOR outputs 1 when inputs are "exclusively" different. XNOR outputs 1 when inputs are the **same**. XNOR is sometimes called the "equality gate".

COMMON MISTAKE
XOR is not the same as OR. They differ only in the last row: for $A = 1, B = 1$, OR gives 1 but XOR gives 0.

آردو میں سمجھیں

XOR گیت تب 1 دیتا ہے جب دونوں ان پٹ مختلف ہوں، اور XNOR گیت تب 1 دیتا ہے جب دونوں ان پٹ ایک جیسے ہوں۔ XNOR براہِ راست XOR کے بعد NOT ہے۔ OR اور XOR میں فرق صرف آخری قطار میں ہے جہاں دونوں ان پٹ 1 ہوں۔

CHECK YOURSELF
1. What is $1 \oplus 1$?
2. Which gate outputs 1 when both inputs are the same?
3. Write XOR using AND, OR and NOT.
Answers: 1. 0. 2. XNOR. 3. $A \oplus B = A'B + AB'$.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. NAND and NOR are universal because:

- Any circuit can be built from only that gate
- They are analog
- They store files
- They sort arrays

MCQ 2. NAND is:

- NOT of AND
- AND of NOT
- OR of XOR
- Only OR

MCQ 3. NAND of 1,1 is:

- 0
- 1
- Z
- 2

MCQ 4. NOR of 0,0 is:

- 1
- 0
- A
- B

MCQ 5. XOR is 1 when inputs are:

- Different
- Both 1 only
- Both 0 only
- Always 1

MCQ 6. XNOR is 1 when inputs are:

- The same
- Different
- Only 1,0
- Flipping

Extra short questions
1. Why are NAND and NOR called universal gates?
2. Write NAND and NOR expressions.
3. Memory trick for XOR vs XNOR.
4. Truth table of XOR.

Extra long question
1. Show how a NOT, AND and OR can each be built from NAND only. Include truth-table checks.

Extra answer key
MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short
1. Any Boolean function (AND, OR, NOT, XOR...) can be built using only NAND, or only NOR.
2. $Y = (A \cdot B)'$ and $Y = (A + B)'$.
3. XOR: exclusively different $\rightarrow$ 1. XNOR: same $\rightarrow$ 1 (equivalence).
4. 00→0, 01→1, 10→1, 11→0.

Long
1. NOT: NAND with inputs tied. AND: NAND then NAND-NOT. OR: invert inputs with NAND-NOTs then NAND (De Morgan). Tables must match the target gate.

11.8 – 11.11 Logic Expressions, Minterms & Diagrams

LEARN IT

A **logic expression** (Boolean expression) combines variables with operations, for example $Y = A + B \cdot C$. To evaluate it correctly you must follow the **order of precedence**, just like the BODMAS in maths.

Parenttheses ()

2. NOT ()

3. AND ()

4. OR (+)

WORKED EXAMPLE

Worked example 1: truth table of $Y = A + B \cdot C$

Step 1: Inputs, six rows.

Step 2: Precedence: first find $B \cdot C$ (NOT), then $B \cdot C$ (AND), then $A + B \cdot C$ (OR). Make a column for each step.

A	B	C	B · C	Y = A + B · C
0	0	0	0	0
0	0	1	0	0
0	1	0	0	0
0	1	1	1	1
1	0	0	0	1
1	0	1	0	1
1	1	0	0	1
1	1	1	1	1

Step 3: $Y = 1$ in rows 1, 4, 5, 6, 7 (decimal). Check one row by hand: $A=0$, $B=0$, $C=1$, $B \cdot C = 0$, $Y = 0 + 0 = 0$.

WORKED EXAMPLE

Worked example 2: truth table of $Y = (A + B) \cdot C$

Step 1: Parentheses first: find $A + B$. Then NOT C . Then AND the two.

A	B	C	A + B	C'	Y
0	0	0	0	1	0
0	0	1	0	0	0
0	1	0	1	1	0
0	1	1	1	0	0
1	0	0	1	1	0
1	0	1	1	0	0
1	1	0	1	1	0
1	1	1	1	0	0

Step 2: $Y = 1$ in rows 2, 4 and 6 (decimal).

Minterms (SOP) and Maxterms (POS)

LEARN IT

Sometimes you are given a truth table and must find the expression. There are two standard ways.

Minterms based on SOP – Sum of Products – product (AND) of all the variables, written for a row whose output is 1. A variable is complemented (A') if its value is 0, and uncomplemented (A) if its value is 1. OR-ing all the minterms gives the SOP expression.

Maxterms based on POS – Product of Sums – sum (OR) of all the variables, written for a row whose output is 0. A variable is complemented (A') if its value is 1, and uncomplemented (A) if its value is 0. AND-ing all the maxterms gives the POS expression.

A	B	C	Output (Y)	Minterm (SOP)	Maxterm (POS)
0	0	0	0	–	$A + B$
0	0	1	1	AB	–
0	1	0	0	–	$A + B$
0	1	1	1	AB	–
1	0	0	1	AB	–
1	0	1	1	AB	–
1	1	0	1	AB	–
1	1	1	1	AB	–

Your SOP expression: $Y = AB + AB + AB + AB + AB + AB$ (that POS expression: $Y = (A + B)(A + B)$ both describe the same table. (Both simplify to $Y = B$ – look at the table: Y always equals B. You will confirm this with a K-map later.)

WORKED EXAMPLE

Worked example 3: write the SOP for a 3-input "majority" circuit. $Y = 1$ when at least two of A, B, C are 1.

Row	A	B	C	Y	Minterm
0	0	0	0	0	–
1	0	0	1	0	–
2	0	1	0	0	–
3	0	1	1	1	ABC
4	1	0	0	0	–
5	1	0	1	1	ABC
6	1	1	0	1	ABC
7	1	1	1	1	ABC

Step 1: Pick the rows with $Y = 1$: rows 3, 5, 6, 7.

Step 2: Row 3 is $A=0$, $B=1$, $C=1$ so A is 0 so write A' ; B and C are 1 so write B, C: ABC .

Step 3: Do the same for the other rows and OR them: $Y = ABC + ABC + ABC + ABC$ (in short form: $Y = \Sigma m(3,5,6,7)$) this will simplify this with a K-map to 1111.

$Y = ABC + ABC + ABC + ABC = \Sigma m(3,5,6,7)$

WORKED EXAMPLE

SOP – Sum of Products. Or, Minterms: 0 → low, 1 → high. Minterms: the inverse (1 → low, 0 → high). Think "Min Does No, Max Does On".

COMMON MISTAKES

The classic errors (1) writing minterms for the 0-rows – minterms come only from rows where $Y = 1$ (2) forgetting precedence → $AB + B \cdot C$ is not $(A + B) \cdot C$ for $A=1$, $B=0$, $C=0$ the first gives 1 and the second gives 0.

از این متن استفاده کنید

در این متن، ما به شما یاد می‌دهیم که چگونه می‌توانید یک عبارت منطقی را به یک جدول حقیقت تبدیل کنید. این کار با استفاده از قوانین اولویت عملیاتی (BODMAS) انجام می‌گیرد. در این مثال، ما یک عبارت منطقی داریم که می‌گوید: اگر A و B هر دو 1 باشند، یا اگر A و C هر دو 1 باشند، یا اگر B و C هر دو 1 باشند، آنگاه خروجی Y برابر با 1 خواهد بود. ما این عبارت را به یک جدول حقیقت تبدیل می‌کنیم و سپس می‌توانیم آن را به یک عبارت منطقی دیگر تبدیل کنیم.

CHECK YOURSELF

1. Which comes first: AND or OR?
2. Write the minterms for $A + B \cdot C$ and $A \cdot B + C$.
3. Write the maxterms for $A + B \cdot C$ and $A \cdot B + C$.

LEARN IT

A **logic diagram** shows how logic gates are connected to create a circuit. It is a "picture" of a Boolean expression. To draw one, use the order of precedence: the operation with the **highest priority** is drawn first (nearest the inputs), and the last operation is the gate that gives the final output.

WORKED EXAMPLE

Example 1: Draw the logic diagram for $Y = A \cdot B + C$.

Step 1: Find the operations: AND (·) and OR (+).

Step 2: AND has higher precedence than OR, so draw the AND gate first, with inputs A and B. Its output is $A \cdot B$.

Step 3: Draw an OR gate. Feed $A \cdot B$ and C into the AND gate to get Y.

$Y = (A \cdot B) + C$ OR first, then OR.

COMMON MISTAKES

Read the expression and ask "What is done last?" That gate goes on the far right, next to Y. Work backwards to the inputs. Count gates: $Y = AB + C$ needs 2 gates; $Y = (AB + C) \cdot D$ needs 3.

از این متن استفاده کنید

در این متن، ما به شما یاد می‌دهیم که چگونه می‌توانید یک عبارت منطقی را به یک مدار منطقی تبدیل کنید. این کار با استفاده از قوانین اولویت عملیاتی (BODMAS) انجام می‌گیرد. در این مثال، ما یک عبارت منطقی داریم که می‌گوید: اگر A و B هر دو 1 باشند، یا اگر A و C هر دو 1 باشند، یا اگر B و C هر دو 1 باشند، آنگاه خروجی Y برابر با 1 خواهد بود. ما این عبارت را به یک مدار منطقی تبدیل می‌کنیم و سپس می‌توانیم آن را به یک عبارت منطقی دیگر تبدیل کنیم.

CHECK YOURSELF

1. In $Y = A + B \cdot C$, which gate is drawn first?
2. How many gates are needed for $Y = A \cdot B + C$?
3. Write the minterms for $A + B \cdot C$ and $A \cdot B + C$.

از این متن استفاده کنید

در این متن، ما به شما یاد می‌دهیم که چگونه می‌توانید یک عبارت منطقی را به یک مدار منطقی تبدیل کنید. این کار با استفاده از قوانین اولویت عملیاتی (BODMAS) انجام می‌گیرد. در این مثال، ما یک عبارت منطقی داریم که می‌گوید: اگر A و B هر دو 1 باشند، یا اگر A و C هر دو 1 باشند، یا اگر B و C هر دو 1 باشند، آنگاه خروجی Y برابر با 1 خواهد بود. ما این عبارت را به یک مدار منطقی تبدیل می‌کنیم و سپس می‌توانیم آن را به یک عبارت منطقی دیگر تبدیل کنیم.

از این متن استفاده کنید

در این متن، ما به شما یاد می‌دهیم که چگونه می‌توانید یک عبارت منطقی را به یک مدار منطقی تبدیل کنید. این کار با استفاده از قوانین اولویت عملیاتی (BODMAS) انجام می‌گیرد. در این مثال، ما یک عبارت منطقی داریم که می‌گوید: اگر A و B هر دو 1 باشند، یا اگر A و C هر دو 1 باشند، یا اگر B و C هر دو 1 باشند، آنگاه خروجی Y برابر با 1 خواهد بود. ما این عبارت را به یک مدار منطقی تبدیل می‌کنیم و سپس می‌توانیم آن را به یک عبارت منطقی دیگر تبدیل کنیم.

Extra board practice

Three MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1: Precedence (highest first) is:

- 1) then NOT then AND then OR
- 2) OR then AND then NOT
- 3) AND then () then OR
- 4) NOT first always

MCQ 2: A minterm is used when Y is:

- 1) SOP
- 2) POS
- 3) Always 0
- 4) A check

MCQ 3: For $AB + C$ if $Y=1$ the minterms is:

- 1) AB
- 2) AB
- 3) AB
- 4) AB

MCQ 4: A minterm is a:

- 1) Sum (OR) for a 0 output
- 2) Product for a 1
- 3) K-map only
- 4) Gate delay

MCQ 5: SOP means:

- 1) Sum of products
- 2) Sum of people
- 3) Stack of printers
- 4) Set of pins

MCQ 6: In a logic diagram you draw first the operation with:

- 1) Highest precedence
- 2) Lowest precedence
- 3) Most inputs
- 4) Green ink

Extra short questions

- State operator precedence in Boolean algebra.
- Define minterms and maxterms.
- From Y rows 01 and 11 write SOP.
- For $Y = AB + C$, which gate is drawn first?

Extra long question

- Given a 2-input truth table with $Y = 0,0,1,1$, write minterms, SOP, maxterms that apply, and draw the logic diagram.

Extra answer key

MCQs: 1. A, 2. A, 3. A, 4. A, 5. A, 6. A

Short

- 1) Parentheses, NOT, AND, OR.
- 2) Minterms: AND of all variables (complemented if 0) for rows where $Y=1$. Maxterms: OR of all variables (complemented if 1) for rows where $Y=0$.
- 3) $Y = AB + C$.
- 4) AND (A, B), then OR with C, because AND beats OR.

Long

- 1) $Y=1$ on 01 and 11 = $AB + AB$ which simplifies to B. Diagram: if unsimplified, two ANDs into an OR; simplified, $Y=B$ (wire). Show both and say examiners accept the simplified form if working is shown.


9

LogiSim Simulation Tool Guide

LEARN IT

LogiSim Evolution is a free graphical tool for designing and simulating logic circuits. "Simulating" means the computer pretends to be the real circuit: you can switch inputs on and off and watch the output change. It lets you see the truth tables and Boolean expressions you learn in theory.

1. The Interface areas



The main areas of the LogiSim Evolution window.

Area	What it does
Menu Bar (top)	File, Edit, Project, Simulate menus — open/save files and control the simulation.
Toolbar	Quick access to standard tools: Wiring, Poke, and AND, OR, NOT gates.
Explorer Panel (left)	Contains the component libraries: Gates, I/O, Wiring.
Attribute Table (bottom left)	Adjust the properties of the selected gate, e.g. Number of inputs or Facing direction.
Drawing Canvas (right)	The dotted grid where you place and wire the gates.

Wiring colours during simulation

Colour	Meaning
Bright green	Logic 1 (HIGH)
Dark green	Logic 0 (LOW)
Blue	Unknown / unconnected pin
Red	Error / short circuit

REMEMBER IT

Colours like a traffic light: Green means "working" (bright = 1, dark = 0). Blue means "the wire is lonely — not connected". Red means "stop, something is wrong".

COMMON MISTAKE

If your output wire is blue, the circuit is not wrong in logic — a wire is simply not touching a pin. Zoom in and make sure every wire end sits exactly on a connection point.

اردو میں سمجھیں

لاچی بیم ایپولیفون (LogiSim Evolution) لاجیک سرکٹ بنانی اور چلا کر دیکھنے کا سافٹ ویئر ہے۔ اس میں میٹو ہاں ٹول ہاں ایکسیلوور ہیل، اینڈری بیوت ٹیل اور ڈرائنگ کیبوس بوتی ہیں۔ چھکدار سیر تار 1، گہری سیر 0، نیلی تار غیر منسلک اور سرخ تار غلطی کو ظاہر کرتی ہے۔

CHECK YOURSELF

1. Where do you change the number of inputs of a gate?


2. What does a red wire mean?

Answers: 1. In the Attribute Table (bottom left). 2. An error or short circuit.

WORKED EXAMPLE

Step by step: building $Y = A \cdot B$

1. Select the **AND** gate from the Toolbar (or from the Gates library) and place it on the canvas.
2. Select the **Input Pin** (square icon with a 0) and place two pins to the left of the gate. Label them A and B.
3. Select the **Output Pin** (circle icon with a 0) and place it to the right. Label it Y.
4. Use the **Wiring Tool** to click and drag wires from the input pins to the AND gate's input ports. Wires must be horizontal or vertical.
5. Wire the gate's output to the output pin Y.
6. Select the **Poke Tool** (pointing finger) and click inputs A and B to toggle them between 0 and 1. Test the circuit!



Bright green = 1, dark green = 0

Testing with the Poke Tool: A = 1 (bright green wire), B = 0 (dark green), so $Y = 1 \cdot 0 = 0$.

WORKED EXAMPLE

Testing the circuit = making its truth table. Poke the inputs through all four combinations and write what Y shows:

Poke A	Poke B	Y shows	Output wire colour
0	0	0	Dark green
0	1	0	Dark green
1	0	0	Dark green
1	1	1	Bright green

This matches the AND truth table, so the circuit is correct. Try the same with $Y = A \cdot B + C$ from 1.1.1 (add a second gate and a third input pin).

REMEMBER IT

Input pin = square (you push it). Output pin = circle (it shows a light). Poke = finger — you "poke" inputs to change them.

COMMON MISTAKE

Students often try to poke inputs while the Wiring or Select tool is active — then clicking moves the pin instead of changing it. Switch to the Poke Tool first.

اردو میں سمجھیں

لاچی بیم میں $A \cdot B = Y$ بنانے کے لیے AND گیٹ رکھیں، ہالیں جاب دو ان پٹ بن (جوگور) اور دالیں جاب ایک آؤٹ پٹ بن (گول) رکھیں، پھر وائرنگ ٹول سے تاریں جوڑیں۔ آخر میں پوک ٹول (انگری) سے ان پٹ کو 0 اور 1 کرکے سرکٹ کو جانچیں۔

CHECK YOURSELF

1. Which icon is the input pin: square or circle?

2. Which tool do you use to change an input between 0 and 1?

Answers: 1. Square (output pin is the circle). 2. The Poke Tool (pointing finger).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. LogiSim Evolution is used to: a. Draw and simulate logic circuits b. Edit videos c. Send email d. Compile Java only	MCQ 2. The canvas is where you: a. Place and wire gates b. Install Python c. Write SQL d. Draw pie charts	MCQ 3. Poke tool is for: a. Toggling inputs while simulating b. Deleting the OS c. Printing Urdu d. Sorting	MCQ 4. Attribute table sets: a. Inputs, facing, labels b. Big O c. IP addresses d. Passwords	MCQ 5. To build $Y=A \cdot B$ you need: a. AND gate plus two inputs and an output b. Only XOR c. A stack d. Pandas	MCQ 6. Simulation lets you check: a. The truth table live b. HTTP status c. File modes d. HCI wireframes only
---	--	--	---	---	--

Extra short questions

1. Name four areas of the LogiSim window.
2. Steps to build $Y=A \cdot B$.
3. Where do you change the number of inputs on a gate?
4. Why simulate at all if the truth table is already on paper?

Extra long question

1. Describe, with a canvas sketch, how you would build and test $Y = A \cdot B + C$ in LogiSim.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Menu bar, toolbar, explorer (libraries), attribute table, drawing canvas.
2. Place AND; add two input pins; add output pin; wire; label; simulate with Poke.
3. Attribute table (bottom left).
4. Catches wiring mistakes and shows students the table "come alive".

Long

1. AND for A,B; OR with C; three inputs, one output; wiring; poke all 8 combinations; tick the truth table. Mention facing and labels.

1.2.1 – 1.2.3 Software Development Life Cycle (SDLC) ★ Golden

LEARN IT

The **Software Development Life Cycle (SDLC)** is a structured process that guides software development from beginning to end. It ensures **clear goals, better planning, risk reduction and high quality**. Without it, teams forget features, go over budget and deliver buggy software. SDLC has **6 phases**:



Phases 1-3 in detail

Phase	Activities and details	Deliverable (what it produces)
1. Requirement Analysis	Meet clients, understand their needs, list the features. This is the most important phase — mistakes here spread to every later phase.	SRS Document (Software Requirements Specification)
2. System Design	Create the High-Level Design (overall architecture), the Low-Level Design (database, UI screens) and flowcharts.	Design Document
3. Implementation	Write the actual code in programming languages (Python, Java, etc.) based on the design documents.	Working Source Code

Phases 4-6 in detail

Phase	Activities and details	Deliverable
4. Testing	Find and fix bugs (errors), using Black Box and White Box testing.	Test Reports, bug-free software
5. Deployment	Release the software to end-users: Direct, Phased, or Pilot release.	Live Software
6. Maintenance	Provide support and updates, and fix post-release issues.	Patches, Updated Versions

Deployment methods: In a **direct** release the old system is switched off and the new one switched on at once. In a **phased** release the new system is introduced part by part. In a **pilot** release one small group (for example one branch or one class) uses it first before everyone else.

Testing methods

Black Box Testing

- The tester does **not** see the code.
- Tests functionality: give inputs, check outputs.
- Done by dedicated testers.

White Box Testing

- The tester **can** see the code.
- Tests the internal logic and structure.
- Done by developers.

WORKED EXAMPLE

Building a house = SDLC.

- Phase 1 (Requirements): you ask the family what rooms they need — 3 bedrooms, a kitchen, a garage.
- Phase 2 (Design): the architect draws the blueprints.
- Phase 3 (Implementation): the builders lay the bricks.
- Phase 4 (Testing): an inspector checks the wiring and the plumbing.
- Phase 5 (Deployment): the family moves in.
- Phase 6 (Maintenance): repairs, painting and a new room added later.

WORKED EXAMPLE

Black box vs white box on a login screen. A black-box tester types a correct password and a wrong password and checks that the first is accepted and the second rejected — without looking at the code. A white-box tester (the developer) reads the code and checks that every `if` branch, for example the “account locked after 3 tries” branch, actually runs correctly.

REMEMBER IT

Remember the order with “Real Developers Implement, Test, Deploy, Maintain” (R-D-I-T-D-M). Black box = a closed box (you can’t see inside). White box = a glass box (you can see inside).

COMMON MISTAKE

Do not say the SDLC ends at deployment. Maintenance is a full phase and often lasts the longest. Also, the SRS is the deliverable of Requirement Analysis, not of Design.

آرڈو میں سمجھیں

ایس ڈی ایل سی (SDLC) سافٹ ویئر بنانے کا منظم طریقہ ہے جس کے چھ مراحل ہیں: ضروریات کا تجزیہ، سسٹم ڈیزائن، کوڈنگ (Implementation)، ٹیسٹنگ، تنصیب (Deployment) اور دیکھ بھال (Maintenance)۔ پہلا مرحلہ سب سے اہم ہے اور اس سے SRS دستاویز بنتی ہے۔ ہلکے ہلکے ٹیسٹنگ میں کوڈ نظر نہیں آتا جبکہ وائٹ باکس ٹیسٹنگ میں کوڈ دیکھ کر اندرونی منطقی جانچی جاتی ہے۔

EXAM TIP

“Explain the phases of SDLC” is a very common long question (5-8 marks). Name all 6 phases in order, write 1-2 lines of activities for each, and state the deliverable of each (SRS, Design Document, Source Code, Test Reports, Live Software, Patches). A short question often asks you to differentiate black box and white box testing — answer in a 3-row table (see code?, what is tested?, who does it?).

CHECK YOURSELF

- Which phase produces the SRS document?
- Who usually performs white box testing?
- Name the three ways to deploy software.

Answers: 1. Requirement Analysis. 2. Developers. 3. Direct, Phased and Pilot release.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. SDLC is: a. A structured process from idea to retired software b. A logic gate c. A search algorithm d. A chart type	MCQ 2. The first SDLC phase is usually: a. Requirement analysis b. Maintenance c. Coding only d. Retirement	MCQ 3. A deliverable is: a. The document or product of a phase b. A Boolean 1 c. A pie slice d. An IP port	MCQ 4. Testing comes: a. After implementation, before deployment b. Before requirements c. Instead of design d. Never	MCQ 5. Maintenance is: a. Fixing and updating after release b. The first interview c. NAND d. Big O	MCQ 6. SDLC exists to: a. Control quality, cost and time b. Replace Boolean algebra c. Draw K-maps d. Sort arrays
--	--	---	--	--	--

Extra short questions

- Define SDLC.
- List the six phases in order.
- Name one deliverable of requirements and of design.
- Why not jump straight to coding?

Extra long question

- Tabulate the six SDLC phases with activities and one deliverable each. ★ Golden 10-mark.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Software Development Life Cycle: a structured process that guides software from beginning to end.
- Requirements, design, implementation/coding, testing, deployment, maintenance.
- SRS / requirements document; design diagrams or architecture document.
- Wrong requirements become expensive bugs; SDLC catches them on paper first.

Long

- Phase | activities | deliverable. Stress that testing uses the requirements as the oracle, and maintenance is the longest phase in real life.

1.3.1 – 1.3.4 Communication Models & OSI 7-Layer Model ★ Golden

LEARN IT

A **communication model** explains how data travels from one device to another through a network. Because sending data is complicated, the job is split into **layers**; each layer does one part of the job and passes the data to the next layer.

The **OSI (Open Systems Interconnection) model** was developed by **ISO** (International Organization for Standardization) in **1984**. It divides communication into **7 layers**. When you send data, it goes **down** the layers on your device (7 → 1), travels as bits over the cable or air, and goes **up** the layers on the receiving device (1 → 7).



The 7 layers of the OSI model with the mnemonic "Please Do Not Throw Sausage Pizza Away".

REMEMBER IT

Mnemonic (bottom to top, 1 → 7): "Please Do Not Throw Sausage Pizza Away" = Physical, Data Link, Network, Transport, Session, Presentation, Application. (Top to bottom you can use "All People Seem To Need Data Processing".)

OSI layers — top layers (7 to 4)

Layer	Function	Protocols / examples
7. Application	Provides network services directly to user applications (browser, email program).	HTTP, HTTPS, FTP, SMTP, DNS
6. Presentation	Data translation, encryption (security) and compression.	SSL/TLS, JPEG, MP3, ASCII
5. Session	Opens, maintains and closes communication sessions.	NetBIOS, RPC
4. Transport	Reliable end-to-end delivery, error checking, port numbering.	TCP (reliable), UDP (fast)

OSI layers — bottom layers (3 to 1)

Layer	Function	Protocols / hardware
3. Network	Logical addressing (IP addresses) and routing packets across networks.	IP, ICMP (Ping), Routers
2. Data Link	Physical addressing (MAC addresses) and error detection in frames.	Ethernet, MAC, Switches
1. Physical	Transmits raw bits (0, 1) over cables or wireless media.	Cables, Hubs, Wi-Fi radio

TCP vs UDP at the Transport layer

	TCP	UDP
Main feature	Reliable — checks that all data arrives correctly and in order.	Fast — sends data without waiting for checks.
Use when	Accuracy matters.	Speed matters more than perfection.
Examples	Web browsing, emails	Video streaming, online gaming

WORKED EXAMPLE

Tracing an email through the OSI layers (sender side).

Layer 7 (Application): you press Send; your email program uses **SMTP**.

Layer 6 (Presentation): the text is encoded (ASCII) and may be encrypted with TLS.

Layer 5 (Session): a session is opened with the mail server.

Layer 4 (Transport): **TCP** breaks the data into segments and numbers them, so nothing is lost (email needs accuracy).

Layer 3 (Network): each packet gets the **IP address** of the destination; **routers** choose the path.

Layer 2 (Data Link): packets are put in **frames** with **MAC addresses**; a **switch** forwards them on the local network.

Layer 1 (Physical): the frames are sent as raw **bits** over the cable or Wi-Fi radio.

At the receiver, the same steps happen in reverse order (1 → 7).

COMMON MISTAKE

Do not mix up the two addresses: **IP address** = logical address = **Network layer (3)**; **MAC address** = physical address = **Data Link layer (2)**. Also, routers work at layer 3, switches at layer 2 and hubs at layer 1.

اردو میں سمجھیں

کیونیکیشن ماڈل بتاتا ہے کہ ڈیٹا نیٹ ورک کے ذریعے ایک ڈیوائس سے دوسری لک کیسے پہنچتا ہے۔ او ایس آئی (OSI) ماڈل 1984 میں آئی ایس او (ISO) نے بنایا اور اس کی سات ہی (Layers) ہیں: فزیکل، ڈیٹا لنک، نیٹ ورک، ٹرانسپورٹ، سیشن، پریزنٹیشن اور اپلی کیشن۔ ہر تپ کا الگ کام ہے، جیسے نیٹ ورک تپ IP ایڈریس اور روٹنگ سنبھالتی ہے۔ TCP درستگی کے لیے اور UDP رفتار کے لیے استعمال ہوتا ہے۔

EXAM TIP

A guaranteed long question: "Explain the seven layers of the OSI model." Draw the 7-layer stack (numbered, layer 7 on top), then write one function and one or two protocols/devices for each layer. MCQs often ask: "Which layer handles routing?" (Network), "Which layer does encryption?" (Presentation), "Who developed OSI and when?" (ISO, 1984), "Which protocol is used for video streaming?" (UDP).

CHECK YOURSELF

- Which OSI layer is responsible for encryption and compression?
- At which layer do switches and MAC addresses work?
- Should online gaming use TCP or UDP? Why?

Answers: 1. Presentation layer (6). 2. Data Link layer (2). 3. UDP, because speed matters more than perfect accuracy.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. OSI has: a. 7 layers b. 4 layers c. 2 layers d. 12 layers	MCQ 2. Layer 7 is: a. Application b. Physical c. Network d. Data link	MCQ 3. IP addressing lives at: a. Network (layer 3) b. Physical c. Application d. Session	MCQ 4. Cables and bits are: a. Physical b. Presentation c. Session d. Application	MCQ 5. End-to-end ports (TCP/UDP) are: a. Transport b. Network c. Physical d. Data link	MCQ 6. The model that explains "how data travels" is a: a. Communication model b. Sort algorithm c. K-map d. MVP
---	--	--	--	--	---

Extra short questions

- Write the 7 OSI layers from top to bottom.
- One job of Transport and of Network.
- Why layer models?
- Mnemonic: you will actually write in the exam.

Extra long question

- Name all 7 OSI layers with one job and one protocol/hardware example each. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short


- Application, Presentation, Session, Transport, Network, Data Link, Physical.
- Transport: reliability/ports (TCP/UDP). Network: routing and logical addressing (IP).
- Each layer has a small job; vendors can change one layer without rewriting the rest.
- Please Do Not Throw Sausage Pizza Away (bottom-up) or All People Seem To Need Data Processing (top-down).

Long

- 7 App HTTP/DNS; 6 Pres encryption/JPEG; 5 Sess dialogs; 4 Trans TCP/UDP; 3 Net IP/routers; 2 DL frames/MAC/switches; 1Phy cables/bits/hubs. Draw the stack.

1.3.5 – 1.3.6 TCP/IP Model vs OSI Model

LEARN IT The OSI model is mainly a reference model used for teaching and design. The TCP/IP model is the practical model used on the real Internet . It condenses the 7 OSI layers into just 4 layers .	
TCP/IP model (4 layers)	Corresponds to OSI layers
1. Application	Application, Presentation, Session (7, 6, 5)
2. Transport	Transport (4)
3. Internet	Network (3)
4. Network Access	Data Link, Physical (2, 1)



How the 7 OSI layers map onto the 4 TCP/IP layers.

Point	OSI model	TCP/IP model
Number of layers	7	4
Use	Reference / teaching model	Practical model used on the real Internet
Top layers	Separate Application, Presentation and Session layers	All three combined into one Application layer
Bottom layers	Separate Data Link and Physical layers	Combined into one Network Access layer

WORKED EXAMPLE

Where does each protocol/device go in TCP/IP?

HTTP (OSI layer 7) → TCP/IP **Application**.

SSL/TLS (OSI layer 6) → TCP/IP **Application** (layers 7, 6, 5 are merged).

UDP (OSI layer 4) → TCP/IP **Transport**.

IP and routers (OSI layer 3) → TCP/IP **Internet**.

Ethernet, switches, cables (OSI layers 2 and 1) → TCP/IP **Network Access**.

REMEMBER IT

Count it as **3-1-1-2**: the TCP/IP Application layer takes 3 OSI layers, Transport takes 1, Internet takes 1, Network Access takes 2. Total 3+1+1+2 = 7.

COMMON MISTAKE

The OSI "Network" layer (3) matches the TCP/IP "**Internet**" layer, not the TCP/IP "Network Access" layer. The similar names confuse many students.

آردو میں سمجھیں

ٹی سی پی/آئی پی (TCP/IP) ماڈل حقیقی انٹرنیٹ پر استعمال ہونے والا عملی ماڈل ہے اور اس کی صرف چار تہیں ہیں۔ اس کی ایپلی کیشن تہ OSI کی 7، 6 اور 5 تہوں کے برابر ہے، ٹرانسپورٹ تہ 4 کے، انٹرنیٹ تہ 3 کے، اور نیٹ ورک ایکسیس تہ 2 اور 1 کے برابر ہے۔

CHECK YOURSELF

1. How many layers does the TCP/IP model have?

2. Which TCP/IP layer corresponds to OSI layers 2 and 1?

3. Which TCP/IP layer contains the OSI Session layer?

Answers: 1. Four. 2. Network Access. 3. Application.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. OSI has:

a. 7 layers

b. 4 layers

c. 2 layers

d. 12 layers

MCQ 2. Layer 7 is:

a. Application

b. Physical

c. Network

d. Data link

MCQ 3. IP addressing lives at:

a. Network (layer 3)

b. Application

c. Physical

d. Session

MCQ 4. Cables and bits are:

a. Physical

b. Presentation

c. Session

d. Application

MCQ 5. End-to-end ports (TCP/UDP) are:

a. Transport

b. Network

c. Physical

d. Data link

MCQ 6. The model that explains "how data travels" is a:

a. Communication model

b. Sort algorithm

c. K-map

d. MVP

Extra short questions

1. Write the 7 OSI layers from top to bottom.

2. One job of Transport and of Network.

3. Why layer models?

4. Mnemonic you will actually write in the exam.

Extra long question

1. Name all 7 OSI layers with one job and one protocol/hardware example each. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Application, Presentation, Session, Transport, Network, Data Link, Physical.

2. Transport: reliability/ports (TCP/UDP). Network: routing and logical addressing (IP).

3. Each layer has a small job; vendors can change one layer without rewriting the rest.

4. Please Do Not Throw Sausage Pizza Away (bottom-up) or All People Seem To Need Data Processing (top-down).

Long

1. 7 App HTTP/DNS; 6 Pres encryption/JPEG; 5 Sess dialogs; 4 Trans TCP/UDP; 3 Net IP/routers; 2 DL frames/MAC/switches; 1 Phy cables/bits/hubs. Draw the stack.

Computer Systems

12 single-page lessons · 7 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- Discrete quantities are counted (students, cars); continuous quantities are measured and can take any value (temperature, speed). Stairs vs ramp.
- A digital system uses only two values, 0 (OFF/LOW/FALSE) and 1 (ON/HIGH/TRUE), called bits. It is reliable, accurate, easy to design and programmable.
- Analog signals change smoothly (sine wave) and are affected by noise; digital signals jump between HIGH and LOW (square wave) and resist noise.
- Boolean algebra, by George Boole, works with only TRUE (1) and FALSE (0) using variables, operations and expressions.
- AND (·) gives 1 only when all inputs are 1; OR (+) gives 1 when any input is 1; NOT (') inverts its single input (unary).
- A truth table lists all 2^n input combinations in binary order with their outputs.
- Logic gates are the building blocks of digital systems: AND, OR, NOT (basic); NAND, NOR (universal); XOR, XNOR (advanced).
- NAND and NOR are universal: any circuit can be built using only one of them.
- XOR gives 1 when inputs are different; XNOR gives 1 when inputs are the same.
- Order of precedence: Parentheses → NOT → AND → OR. A logic diagram is drawn in the same order.
- Minterms (SOP) come from rows with output 1; maxterms (POS) come from rows with output 0.
- K-maps use Gray code (00, 01, 11, 10); group 1s in sizes 1, 2, 4, 8, as large as possible; overlap and wrap-around are allowed; changing variables are eliminated.
- LogiSim Evolution simulates circuits: input pins are squares, output pins circles; the Poke Tool toggles inputs; bright green = 1, dark green = 0, blue = unconnected, red = error.
- SDLC has 6 phases: Requirement Analysis (SRS), Design, Implementation, Testing (black box/white box), Deployment (direct/phased/pilot), Maintenance.
- Waterfall is linear and suits fixed requirements (AI-Noor Library); Agile is iterative with 2–4 week sprints and suits changing requirements (AI-Noor Student App).
- The OSI model (ISO, 1984) has 7 layers — "Please Do Not Throw Sausage Pizza Away"; the practical TCP/IP model has 4 layers: Application, Transport, Internet, Network Access.

Key terms

Term	Meaning	اردو
Discrete quantity	A countable quantity with separate, fixed values.	منفصل مقدار
Continuous quantity	A quantity that can take any value within a range.	مسلسل مقدار
Bit	A binary digit, 0 or 1.	بائنری ہندسہ
Digital system	An electronic system that uses only the values 0 and 1.	ڈیجیٹل نظام
Analog signal	A continuous signal that changes smoothly, like a sine wave.	اینالوگ سگنل (مسلسل اشارہ)
Digital signal	A signal with only two levels, HIGH and LOW (square wave).	ڈیجیٹل سگنل
Noise	Unwanted interference that disturbs a signal.	شور (مداخلت)
Boolean algebra	Algebra of two values, TRUE (1) and FALSE (0), developed by George Boole.	بولین الجبرا
Truth table	A table of all input combinations and their outputs.	تروٹھ ٹیبل (صداقت جدول)
Logic gate	An electronic circuit that performs a Boolean operation.	منطقی گیٹ
Universal gate	A gate (NAND or NOR) from which any circuit can be built.	عالمگیر گیٹ
Unary operation	An operation with only one operand, e.g. NOT.	یک عددی عمل

Computer Systems

75 marks · 1 hour 15 minutes · no notes · no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 12 and the recap. **Section A** — all 15 MCQs (1 mark). **Section B** — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define · Explain · Example · Diagram · Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. Which of the following is a continuous quantity?
 - a. Number of students in a class
 - b. Number of cars in a parking lot
 - c. Temperature of water
 - d. Number of books on a shelf
2. In a digital system, the value 1 represents:
 - a. OFF
 - b. LOW
 - c. FALSE
 - d. ON / HIGH / TRUE
3. A square wave represents a:
 - a. Digital signal
 - b. Analog signal
 - c. Sine wave
 - d. Noise signal
4. Boolean algebra was developed by:
 - a. Charles Babbage
 - b. George Boole
 - c. Alan Turing
 - d. Maurice Karnaugh
5. How many rows does a truth table with 4 inputs have?
 - a. 4
 - b. 8
 - c. 16
 - d. 32
6. Which gate gives output 1 only when all inputs are 1?
 - a. OR
 - b. AND
 - c. NOR
 - d. XOR
7. Which pair of gates are called universal gates?
 - a. AND and OR
 - b. XOR and XNOR
 - c. NOT and AND
 - d. NAND and NOR
8. What is the output of a NOR gate when A = 0 and B = 0?
 - a. 1
 - b. 0
 - c. Unknown
 - d. Depends on the gate size
9. An XOR gate gives output 1 when:
 - a. Both inputs are 1
 - b. Both inputs are 0
 - c. The inputs are different
 - d. The inputs are the same
10. After parentheses, which operation has the highest precedence?
 - a. OR
 - b. NOT
 - c. AND
 - d. XOR
11. The minterm for the row A = 1, B = 0 is:
 - a. AB'
 - b. A'B
 - c. A + B'
 - d. A' + B
12. The columns of a 3-variable K-map (BC) are written in the order:
 - a. 00, 01, 10, 11
 - b. 00, 10, 01, 11
 - c. 11, 10, 01, 00
 - d. 00, 01, 11, 10
13. In black box testing, the tester:
 - a. Reads the source code line by line
 - b. Does not see the code and tests inputs/outputs
 - c. Is always the developer
 - d. Tests only the internal structure
14. Which OSI layer handles logical (IP) addressing and routing?
 - a. Data Link
 - b. Transport
 - c. Network
 - d. Session
15. The TCP/IP Network Access layer corresponds to which OSI layers?
 - a. 7, 6 and 5
 - b. 4
 - c. 3
 - d. 2 and 1

Section B — Short questions (10 × 3 = 30)

1. Define discrete and continuous quantities. Give two examples of each.
2. State four advantages of digital systems.
3. Differentiate between analog and digital signals (any three points).
4. Why is NOT called a unary operation? Write its truth table.
5. How many rows are needed in a truth table for 3 inputs? List all the input combinations.
6. Why are NAND and NOR called universal gates? Show how a NAND gate can be used as a NOT gate.
7. A 2-input truth table has $Y = 1$ only for rows $A=0, B=1$ and $A=1, B=0$. Write the SOP expression and name the gate.
8. Name the deliverable of each SDLC phase.
9. Differentiate between black box testing and white box testing.
10. When should TCP be used and when should UDP be used? Give one example of each.

Section C — Long questions (attempt any 3 × 10 = 30)

1. Draw the symbol, write the Boolean expression and give the truth table for each of these gates: AND, OR, NOT, NAND, NOR, XOR and XNOR.
2. A function is given as $F(A, B, C) = \sum m(1, 3, 5, 6, 7)$. (a) Make its truth table. (b) Simplify it using a 3-variable K-map, explaining each group. (c) Draw the logic diagram of the simplified expression.
3. For $Y = A \cdot B' + C$: (a) state the order in which the operations are done; (b) make the complete truth table; (c) draw the logic diagram.
4. Explain the six phases of the Software Development Life Cycle with the activities and deliverable of each phase. Use the house-building analogy.
5. Compare the Waterfall and Agile models under five headings. Explain why the AI-Noor Library Management System used Waterfall and the AI-Noor Student Mobile Application used Agile.
6. Explain the seven layers of the OSI model with the function and one protocol/device for each layer. Then show how they map onto the four layers of the TCP/IP model.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

1. **1.1.1 & 1.1.2 Discrete vs Continuous & Digital Systems.** Answers: 1. Discrete (you count pages). 2. Continuous (height is measured and can be any value). 3. The ramp.
2. **1.1.3 Analog and Digital Signals.** Answers: 1. A square wave. 2. Analog. 3. Human voice (or a traditional thermometer reading).
3. **1.1.4 – 1.1.6 Boolean Algebra, Operations & Truth Tables.** Answers: 1. George Boole. 2. 1 (because + means OR).
4. **1.1.7 Basic Logic Gates (AND, OR, NOT).** Answers: 1. 0. 2. Inverter. 3. Only $A = 1, B = 1$.
5. **1.1.7 Universal & Advanced Logic Gates.** Answers: 1. Any logic circuit can be built using only NAND gates or only NOR gates. 2. 0. 3. Join both inputs together and feed A into them: $(A \cdot A)' = A'$.
6. **1.1.8 – 1.1.11 Logic Expressions, Minterms & Diagrams.** Answers: 1. AND. 2. $AB'C$. 3. $A + B'$.
7. **1.1.13 Karnaugh Maps (K-Maps) Simplification.** Answers: 1. $BC = 11$. 2. Cells 2 and 3 are the row $A = 1$; B changes $\rightarrow Y = A$. 3. The whole row $A = 1$ is a group of 4 $\rightarrow Y = A$.
8. **LogiSim Simulation Tool Guide.** Answers: 1. In the Attribute Table (bottom left). 2. An error or short circuit.
9. **1.2.1 – 1.2.3 Software Development Life Cycle (SDLC).** Answers: 1. Requirement Analysis. 2. Developers. 3. Direct, Phased and Pilot release.
10. **1.2.4 – 1.2.7 Waterfall vs Agile Models & Case Studies.** Answers: 1. Because each phase must be completed before the next begins, in a fixed order. 2. Because its requirements were 100% fixed before coding began.
11. **1.3.1 – 1.3.4 Communication Models & OSI 7-Layer Model.** Answers: 1. Presentation layer (6). 2. Data Link layer (2). 3. UDP, because speed matters more than perfect accuracy.
12. **1.3.5 – 1.3.6 TCP/IP Model vs OSI Model.** Answers: 1. Four. 2. Network Access. 3. Application.

Answer key

Multiple choice

1. c
2. d
3. a
4. b
5. c
6. b
7. d
8. a
9. c
10. b
11. a
12. d
13. b
14. c
15. d

Short questions — model answers

1. Discrete quantities are separate, countable items with specific values (number of students in a classroom, number of cars in a parking lot). Continuous quantities can take any value within a range and flow without breaks (temperature of water, speed of a moving car).
2. Reliable (less affected by noise and interference); accurate (no loss of quality when copying); easy to design (only two states, 0 and 1); programmable (easily controlled by software).
3. Nature: analog is a continuous flow; digital has discrete values (bits, HIGH/LOW). Shape: analog is a sine wave; digital is a square wave. Reliability: analog is low (affected by noise); digital is high (resistant to noise). Examples: human voice vs computer data.
4. NOT works on only one operand (one input), so it is unary. Truth table: $A = 0 \rightarrow Y = 1$; $A = 1 \rightarrow Y = 0$.
5. $2^3 = 8$ rows: 000, 001, 010, 011, 100, 101, 110, 111.
6. Any logic circuit can be built using only NAND gates, or only NOR gates. NAND as NOT: join both inputs and feed A: $Y = (A \cdot A)' = A'$. Check: $A = 0 \rightarrow 1$, $A = 1 \rightarrow 0$.
7. Minterms: $A'B$ (row 01) and AB' (row 10). $Y = A'B + AB'$. This is the XOR gate, $Y = A \oplus B$.
8. Requirement Analysis $\rightarrow$ SRS document; System Design $\rightarrow$ Design Document; Implementation $\rightarrow$ Working Source Code; Testing $\rightarrow$ Test Reports / bug-free software; Deployment $\rightarrow$ Live Software; Maintenance $\rightarrow$ Patches / Updated Versions.
9. Black box: tester does not see the code, tests functionality (inputs/outputs), done by dedicated testers. White box: tester can see the code, tests internal logic/structure, done by developers.
10. Use TCP when accuracy matters, e.g. web browsing or email. Use UDP when speed matters more than perfection, e.g. video streaming or online gaming.

Long questions — model answers

- Symbols as drawn in 1.1.7 (AND = D shape; OR = curved back, pointed front; NOT = triangle + bubble; NAND = AND + bubble; NOR = OR + bubble; XOR = OR with extra back curve; XNOR = XOR + bubble). Expressions: AND $Y = A \cdot B$; OR $Y = A + B$; NOT $Y = A'$; NAND $Y = (A \cdot B)'$; NOR $Y = (A + B)'$; XOR $Y = A \oplus B$; XNOR $Y = (A \oplus B)'$. Outputs for inputs 00, 01, 10, 11: AND 0,0,0,1; OR 0,1,1,1; NAND 1,1,1,0; NOR 1,0,0,0; XOR 0,1,1,0; XNOR 1,0,0,1. NOT: 0 $\rightarrow$ 1, 1 $\rightarrow$ 0.
- (a) Truth table ($ABC \rightarrow F$): 000 $\rightarrow$ 0, 001 $\rightarrow$ 1, 010 $\rightarrow$ 0, 011 $\rightarrow$ 1, 100 $\rightarrow$ 0, 101 $\rightarrow$ 1, 110 $\rightarrow$ 1, 111 $\rightarrow$ 1.

(b) K-map:

	BC = 00	BC = 01	BC = 11	BC = 10
A = 0	0	1	1	0
A = 1	0	1	1	1

Group 1 (size 4): the two middle columns, m_1, m_3, m_5, m_7 . A changes and B changes; C = 1 stays $\rightarrow$ **C**. Group 2 (size 2): m_7 and m_6 in row A = 1. C changes; A = 1, B = 1 stay $\rightarrow$ **AB** (m_7 is shared — overlapping is allowed). **F = C + AB**. Check: C + AB is 1 for rows 1, 3, 5, 7 (C = 1) and 6, 7 (AB = 1) = {1, 3, 5, 6, 7}. ✓

(c) Logic diagram: an AND gate with inputs A and B gives AB; an OR gate takes AB and C and gives F.

- (a) First NOT (B'), then AND ($A \cdot B'$), then OR ($+ C$).

(b) Truth table:

A	B	C	B'	A·B'	Y
0	0	0	1	0	0
0	0	1	1	0	1
0	1	0	0	0	0
0	1	1	0	0	1
1	0	0	1	1	1
1	0	1	1	1	1
1	1	0	0	0	0
1	1	1	0	0	1

(c) Logic diagram: input B goes through a NOT gate to give B' . A and B' go into an AND gate to give $A \cdot B'$. $A \cdot B'$ and C go into an OR gate to give Y. (3 gates.)

- Requirement Analysis: meet clients, understand needs, list features; most important phase; deliverable SRS (house: asking the family what rooms they need). System Design: high-level design (architecture), low-level design (database, UI screens), flowcharts; deliverable Design Document (architect draws blueprints). Implementation: write code in Python, Java etc. from the design; deliverable Working Source Code (builders lay bricks). Testing: find and fix bugs using black box and white box testing; deliverable Test Reports / bug-free software (inspector checks the house). Deployment: release to end-users by direct, phased or pilot release; deliverable Live Software (family moves in). Maintenance: support, updates, fixing post-release issues; deliverable Patches / Updated Versions (repairs and extensions).
- Comparison: Flexibility — Waterfall rigid, Agile very flexible. Customer involvement — Waterfall only at start and end, Agile continuous after every sprint. Delivery — Waterfall single delivery at the end, Agile frequent partial deliveries. Testing — Waterfall late in a dedicated phase, Agile continuous in every sprint. Documentation — Waterfall heavy, Agile light. The Al-Noor Library system used Waterfall because its requirements were 100% fixed before coding began, so a simple, well-documented linear process fitted. The Al-Noor Student App used Agile because teachers, parents and students kept requesting new features, so short sprints with continuous feedback were needed.
- OSI (ISO, 1984), top to bottom: 7 Application — network services to user applications (HTTP, HTTPS, FTP, SMTP, DNS); 6 Presentation — translation, encryption, compression (SSL/TLS, JPEG, MP3, ASCII); 5 Session — opens, maintains, closes sessions (NetBIOS, RPC); 4 Transport — reliable end-to-end delivery, error checking, port numbers (TCP, UDP); 3 Network — logical IP addressing and routing (IP, ICMP, routers); 2 Data Link — physical MAC addressing and error detection in frames (Ethernet, switches); 1 Physical — raw bits over cables/wireless (cables, hubs, Wi-Fi radio). Mnemonic bottom to top: "Please Do Not Throw Sausage Pizza Away". TCP/IP mapping: Application = OSI 7, 6, 5; Transport = 4; Internet = 3; Network Access = 2, 1.

Self-assessment: I can...

- ☐ ...tell discrete from continuous quantities and analog from digital signals, and draw both waves.
- ☐ ...evaluate AND, OR and NOT expressions and follow the order of precedence.
- ☐ ...draw all seven gate symbols and write their truth tables from memory.
- ☐ ...write the SOP (minterms) and POS (maxterms) from a truth table.
- ☐ ...simplify expressions with 2- and 3-variable K-maps, including overlap and wrap-around groups.
- ☐ ...explain the six SDLC phases and choose between Waterfall and Agile for a project.
- ☐ ...list four advantages of digital systems.
- ☐ ...build a complete truth table for 2 or 3 inputs without missing a row.
- ☐ ...explain why NAND and NOR are universal gates.
- ☐ ...draw a logic diagram from an expression.
- ☐ ...build and test a simple circuit in LogiSim and read the wire colours.
- ☐ ...name the 7 OSI layers in order, state their functions, and map them to the 4 TCP/IP layers.

Lecture 02

Computational Thinking & Algorithm

Chapter lecture — 11 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XI · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — گیارہویں جماعت

11 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XI

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیریئر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

Lectures in this pack

Chapter 2: Computational Thinking & Algorithm. Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 2.1 & 2.2 Introduction to CT & Algorithms

L03. 2.3.1 Algorithmic Strategy: Decomposition

L05. 2.3.3 Algorithmic Strategy: Abstraction

L07. 2.4.1 Sorting Algorithms: Selection Sort

L09. 2.4.2 Searching Algorithms: Binary Search

L11. 2.6 How to Decide Which Algorithm to Use

L02. 2.2.2 Algorithm vs Pseudocode

L04. 2.3.2 Algorithmic Strategy: Pattern Recognition

L06. 2.4.1 Sorting Algorithms: Bubble Sort

L08. 2.4.2 Searching Algorithms: Linear Search

L10. 2.5 Evaluation Criteria of Algorithm

Computational Thinking & Algorithm

This chapter teaches you how to think like a computer scientist: break a problem into parts, spot patterns, ignore what does not matter, and write clear step-by-step algorithms. You will then learn four famous algorithms — Bubble Sort, Selection Sort, Linear Search and Binary Search — and how to judge and choose between them.

اس باب میں آپ سیکھیں گے کہ کسی مسئلے کو کمپیوٹر سائنس دان کی طرح کیسے سوچ کر حل کیا جاتا ہے: مسئلے کو چھوٹے حصوں میں توڑنا، پیٹرن پہچاننا، غیر ضروری باتوں کو نظر انداز کرنا اور مرحلہ وار الگورتھم لکھنا۔ اس کے بعد آپ ترتیب دینے (Sorting) اور تلاش کرنے (Searching) کے چار اہم الگورتھم سیکھیں گے۔

What you will learn

- Define computational thinking and name its four parts: decomposition, pattern recognition, abstraction and algorithms.
- Compare an algorithm with pseudocode on at least five points.
- Dry-run Bubble Sort and Selection Sort pass by pass on a given list, and write them in pseudocode and Python.
- List the advantages and disadvantages of each sorting and searching algorithm.
- Evaluate an algorithm for correctness (using a trace table), efficiency and clarity.
- Define an algorithm and state five reasons why algorithms are important.
- Apply decomposition, pattern recognition and abstraction to real-life problems.
- Trace Linear Search step by step and Binary Search using a low / mid / high table.
- State the best-case and worst-case time complexity of the four algorithms.
- Choose the right algorithm for a situation and justify your choice.

LEARN IT

Computational Thinking (CT) is a systematic approach to solving problems. "Systematic" means you follow a fixed, organised method instead of guessing. CT involves four activities:

- Decomposition** — breaking a big problem down into smaller parts.
- Pattern recognition** — identifying things that repeat or follow a rule.
- Abstraction** — hiding (ignoring) details that do not matter.
- Algorithms** — developing clear step-by-step instructions to solve the problem.

CT is not "thinking like a computer". It is thinking in a way that lets you describe a solution so clearly that a computer (or another person) could carry it out.

Problem → Decomposition → Pattern recognition → Abstraction → Algorithm → Program

You already use computational thinking in daily life. When you plan your exam preparation, you split the syllabus into chapters (decomposition), notice that every chapter needs the same routine of reading, making notes and practising (pattern recognition), ignore things that are not in the syllabus (abstraction), and make a day-by-day timetable (algorithm).

LEARN IT

Did you know? Pseudocode is a human-readable representation of an algorithm using plain English and structured programming keywords. It is the bridge between human logic and machine code. You will study it in detail in section 2.2.2.

REMEMBER IT

Remember the four parts of CT with the phrase **"Don't Pick Any Apple"**: Decomposition, Pattern recognition, Abstraction, Algorithm.

COMMON MISTAKE

Students sometimes think computational thinking means "writing code". It does not. CT happens before coding. You can do all four steps with pen and paper, without a computer.

آرڈو میں سمجھیں

کمپیوٹیشنل ٹھنکگ (Computational Thinking) مسائل حل کرنے کا ایک منظم طریقہ ہے۔ اس کے چار حصے ہیں: مسئلے کو چھوٹے حصوں میں توڑنا (Decomposition)، دہرائی جانے والی باتوں کو پہچانتا (Pattern Recognition)، غیر ضروری تفصیلات کو چھپانا (Abstraction) اور مرحلہ وار حل لکھا (Algorithm)۔ یہ سوچنے کا طریقہ ہے، کوڈ لکھنا نہیں۔

CHECK YOURSELF

1. Name the four parts of computational thinking.

2. Is computational thinking done before or after writing code?

3. What is pseudocode called a "bridge" between?

Answers: 1. Decomposition, pattern recognition, abstraction, algorithms. 2. Before coding (it is planning the solution). 3. Between human logic and machine code.

LEARN IT

An **algorithm** is a step-by-step logical procedure used to solve a problem. It is **conceptual** in nature (it is an idea, a plan) and completely **independent of any programming language**. The same algorithm can be written later in Python, C++ or Java.

A good algorithm has:

- Input** — the data it starts with.
- Clear steps** — each step has only one meaning.
- A definite end** — it must finish after a limited number of steps.
- Output** — the result it produces.

WORKED EXAMPLE

Algorithm to find the larger of two numbers

Step 1: Start

Step 2: Read A and B

Step 3: If A > B, print "A is larger"

Step 4: Else print "B is larger or equal"

Step 5: End

Notice: there is no Python or C++ here. Anyone — even a non-programmer — can follow these steps. That is what "language-independent" means.

2.2.1 Importance of Algorithms

Reason	What it means for you
Structured approach	Algorithms provide a structured approach to problem-solving, making complex tasks manageable.
Optimization	They optimise time and memory usage, which is crucial for large-scale applications (for example, searching millions of records).
Reusability	They can be reused for similar problems, saving time and effort. A sorting algorithm for marks can also sort prices.
Accuracy and consistency	They ensure accuracy and consistency, reducing human error. The same steps always give the same result.
Blueprint	They act as a blueprint (a plan) before actual code implementation, just like an architect's map before building a house.

REMEMBER IT

Remember the five reasons as **S-O-R-A-B**: Structured, Optimised, Reusable, Accurate, Blueprint.

COMMON MISTAKE

Do not write "an algorithm is a program". A program is the algorithm written in a programming language so that a computer can run it. The algorithm itself is only the logic.

آرڈو میں سمجھیں

الگورتھم (Algorithm) کسی مسئلے کو حل کرنے کا مرحلہ وار منطقی طریقہ ہے۔ یہ ایک تصور ہے اور کسی بھی پروگرامنگ زبان پر منحصر نہیں۔ الگورتھم کام کو منظم بناتے ہیں، وقت اور میموری بچاتے ہیں، دوبارہ استعمال ہو سکتے ہیں، غلطیاں کم کرتے ہیں اور کوڈ لکھنے سے پہلے نقشے کا کام دیتے ہیں۔

EXAM TIP

Very common short question: "Define algorithm and write its importance." Write the definition word for word — a *step-by-step logical procedure used to solve a problem; conceptual and independent of any programming language* — then list at least four of the five importance points. If asked to "write an algorithm", always begin with **Step 1: Start** and finish with **End**, and number every step.

CHECK YOURSELF

1. Why is an algorithm called "language-independent"?

2. Give two reasons why algorithms are important.

3. Write a 5-step algorithm to find the sum of two numbers.

Answers: 1. Because it describes only the logic; it is not tied to Python, C++ or any other language. 2. Any two: structured approach, optimise time/memory, reusable, accurate and consistent, blueprint before coding. 3. Step 1: Start; Step 2: Read A and B; Step 3: SUM = A + B; Step 4: Print SUM; Step 5: End.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Computational thinking is:

a. A systematic way to solve problems

b. Only typing Python

c. Only drawing gates

d. A database key

MCQ 2. An algorithm is:

a. A step-by-step finite method to solve a problem

b. A random guess

c. A picture of a PC

d. An IP address

MCQ 3. CT pillars include:

a. Decomposition, pattern, abstraction, algorithm

b. Only encryption

c. Only HTML

d. Only Agile sprints

MCQ 4. Algorithms must halt:

a. After finitely many steps

b. Never

c. Only on Fridays

d. After OSI layer 1

MCQ 5. Cooking a recipe is like:

a. An algorithm

b. A K-map group of 3

c. A XOR of pies

d. Big O of clouds

MCQ 6. CT is useful even:

a. Without a computer

b. Only inside NAND

c. Only in Figma

d. Only in SQLite

Extra short questions

1. Define computational thinking.

2. Define algorithm with two properties.

3. Give a non-computer algorithm.

4. How is CT different from "just coding"?

Extra long question

1. Take "assign 200 students to exam rooms". Apply the four CT pillars and then write a 8-step algorithm.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Solving problems by breaking them down, spotting patterns, hiding detail (abstraction) and writing algorithms.

2. Ordered, finite, unambiguous steps that produce a result. Precision + finiteness.

3. Making tea / finding a roll number in a sorted list.

4. CT is the thinking; coding is one way to write the algorithm down.

Long

1. Decompose: rooms, students, constraints. Pattern: groups of 30. Abstract: ignore bag colours. Algorithm: numbered steps with a stop condition. Mention input/output.

2.2.2 Algorithm vs Pseudocode ★ Golden

LEARN IT

Both algorithms and pseudocode are used in problem-solving, but they serve different purposes in the design phase. The **algorithm** says what must be done. The **pseudocode** shows how it could be implemented, using programming-like keywords such as IF , FOR and WHILE , but it still cannot be run on a computer.

Point	Algorithm	Pseudocode
Definition	A step-by-step logical procedure to solve a problem.	A human-readable representation of an algorithm using plain English & keywords.
Nature	Conceptual and language-independent.	Semi-formal and structured, but not executable code.
Purpose	To define what needs to be done logically.	To present how it can be implemented in a readable format.
Form	Usually described in plain steps, bullets or numbered points.	Written using structured constructs (IF, FOR, WHILE) like programming.
Focus	Focuses on the logic and steps of the problem.	Focuses on representing steps clearly before coding.
Audience	For anyone trying to understand the logic (including non-programmers).	Mainly for programmers or students preparing for coding.
Format rules	No fixed format; can be informal.	Follows standard pseudocode conventions for clarity.

WORKED EXAMPLE

The same problem written both ways: print whether a number is even or odd.

Algorithm

Step 1: Start
Step 2: Read a number N
Step 3: Divide N by 2 and find the remainder
Step 4: If the remainder is 0, print "Even", otherwise print "Odd"
Step 5: End

Pseudocode

```
START
INPUT N
SET R TO N MOD 2
IF R = 0 THEN
  PRINT "Even"
ELSE
  PRINT "Odd"
END IF
END
```

The equivalent Python program (real, executable code):

```
n = 7
if n % 2 == 0:
    print("Even")
else:
    print("Odd")
```

OUTPUT
Odd

Problem → Algorithm (what) → Pseudocode (how) → Program (code) → Output

REMEMBER IT

Teacher's analogy: an **algorithm** is like a recipe ("Bake a cake at 350 degrees"). **Pseudocode** is like a structured kitchen manual using standard verbs (SET temperature TO 350; WHILE cake is not baked, WAIT). The program is the oven actually doing it.

COMMON MISTAKE

Pseudocode is **not** executable. If you type pseudocode into Python, it will give errors. Also, do not mix exact Python syntax (colons, brackets) into pseudocode answers unless asked — use keywords like IF ... THEN ... END IF .

آرڈو میں سمجھیں

الگورتھم بتاتا ہے کہ کیا کرنا ہے، جبکہ سڈو کوڈ (Pseudocode) بتاتا ہے کہ اسے کیسے کیا جا سکتا ہے۔ الگورتھم سادہ مرحلوں میں لکھا جاتا ہے اور ہر کوئی اسے سمجھ سکتا ہے۔ سڈو کوڈ میں IF, FOR اور WHILE جیسے الفاظ استعمال ہوتے ہیں اور یہ زیادہ تر پروگرامرز کے لیے ہوتا ہے، لیکن اسے کمپیوٹر پر چلایا نہیں جا سکتا۔

EXAM TIP

"Differentiate between algorithm and pseudocode" is a favourite 4–5 mark question. Draw a two-column table and give at least **five** points (definition, nature, purpose, form, audience). Adding the recipe vs kitchen-manual analogy and one small example of each earns full marks.

CHECK YOURSELF

- Which one — algorithm or pseudocode — uses keywords like FOR and WHILE?
- Which one is meant for non-programmers too?
- Can pseudocode be executed by a computer?

Answers: 1. Pseudocode. 2. Algorithm. 3. No; it is semi-formal and not executable.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Pseudocode is:

- a. English-like steps for an algorithm, not a real language
- b. Runnable C++
- c. A logic gate
- d. A pie chart

MCQ 2. An algorithm vs pseudocode: algorithm is:

- a. The idea/method
- b. Always Python
- c. Always a table
- d. Always OSI

MCQ 3. Pseudocode should be:

- a. Clear enough to code from
- b. Encrypted
- c. Drawn as NAND only
- d. A CSV file

MCQ 4. Keywords like IF, WHILE in pseudocode are:

- a. Control, written in capitals by convention
- b. Python-only
- c. SQL-only
- d. Illegal

MCQ 5. You write pseudocode:

- a. Before coding
- b. After the program crashes only
- c. Instead of requirements
- d. On OSI layer 1

MCQ 6. A flowchart is:

- a. A diagram of the algorithm
- b. A database index
- c. A stack pop
- d. A sprint

Extra short questions

- Differentiate algorithm and pseudocode.
- Give two pseudocode conventions.
- Why not write Python immediately?
- Write 5 lines of pseudocode to add two numbers.

Extra long question

- Write an algorithm AND pseudocode to find the largest of three numbers. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Algorithm: the method. Pseudocode: a structured English write-up of that method that a programmer can translate.
- Capital keywords (IF, WHILE); one step per line; indent blocks; START/END.
- Pseudocode is language-independent and easier to correct on paper.
- START; READ a,b; SET s ← a+b; PRINT s; END.

Long


- Algorithm numbered 1..n. Pseudocode with IF/ELSE. Same logic. Show a dry-run with 4, 9, 7 → 9.

2.3.1 Algorithmic Strategy: Decomposition ★ Golden

2.3 Algorithmic Strategies for Problem Solving. An algorithmic strategy is a general method that helps you design an algorithm. The three strategies in your syllabus are decomposition, pattern recognition and abstraction.

LEARN IT

Decomposition is a problem-solving technique in which a complex task or system is broken down into smaller, manageable parts. By dividing a big problem into simpler steps, it becomes easier to understand, develop and solve. Each small part is called a **sub-task** (or sub-problem). You solve each sub-task separately, then join the solutions to solve the whole problem.



Decomposition: one complex problem is split into smaller sub-tasks.

WORKED EXAMPLE

Real-life example: Learning a new language

"Learn English" (or any language) is too big to do in one go. Decompose it:

Sub-task	Description
Learn vocabulary	Learn the words for people, actions and things (e.g., "I", "eat", "apple").
Grammar rules	Learn the sentence structure: Subject → Verb → Object.
Learn tenses	Present, past, future (e.g., "I eat" vs. "I ate").
Sentence building	Combine words using the rules to create valid sentences: "I ate an apple."



WORKED EXAMPLE

Computing example: a "Student Result" program

Problem: read the marks of a student in 5 subjects and print the total, percentage and grade.

- Sub-task 1: Input marks of 5 subjects.
- Sub-task 2: Calculate total = sum of the 5 marks.
- Sub-task 3: Calculate percentage = total ÷ 500 × 100.
- Sub-task 4: Decide the grade from the percentage.
- Sub-task 5: Print the result card.

Each sub-task is now so small that you can write it in two or three lines of code.

Why is decomposition useful?

Reduces complexity: you focus on one piece at a time.

Helps in debugging: you can find exactly where the mistake is (e.g., in the language example, is the error in the verb tense or the word order?).

Promotes reusability: once you learn or build a small part, you can apply it elsewhere (the "calculate percentage" part can be reused in an attendance program).

REMEMBER IT

Think of eating a big roti: you cannot eat it in one bite, so you break it into small pieces. Decomposition = "break the roti".

COMMON MISTAKE

Do not break a problem into random pieces. Each sub-task must be a meaningful, clear job, and all sub-tasks together must solve the whole problem. If one part is missing (e.g., "print result!"), the solution is incomplete.

آدو میں سنجھیں

ڈیکمپوزیشن (Decomposition) کا مطلب یہ کسی بڑے اور پیچیدہ مسئلے کو چھوٹے اور آسان حصوں میں تقسیم کرنا۔ مثلاً نئی زبان سیکھنے کو الفاظ، گرامر، زمانے (Tenses) اور جملہ سازی میں تقسیم کیا جا سکتا ہے۔ اس سے پیچیدگی کم ہوتی ہے، غلطی ڈھونڈنا آسان ہوتا ہے اور حصے دوبارہ استعمال ہو سکتے ہیں۔

EXAM TIP

Expect "Define decomposition with a real-life example" or "Explain the benefits of decomposition". Give the definition, draw the small tree (Complex Problem → Sub-task 1, 2, 3), show the language-learning table, and list the three benefits: reduces complexity, helps debugging, promotes reusability.

CHECK YOURSELF

- What is each smaller part of a decomposed problem called?
- Decompose "Making a school timetable" into three sub-tasks.
- State the three benefits of decomposition.

Answers: 1. A sub-task (sub-problem). 2. Example: list subjects and teachers; decide periods per subject per week; place periods in days so no teacher has two classes at once. 3. Reduces complexity, helps in debugging, promotes reusability.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. OSI has:

- a. 7 layers
- b. 4 layers
- c. 2 layers
- d. 12 layers

MCQ 2. Layer 7 is:

- a. Application
- b. Physical
- c. Network
- d. Data link

MCQ 3. IP addressing lives at:

- a. Network (layer 3)
- b. Application
- c. Physical
- d. Session

MCQ 4. Cables and bits are:

- a. Physical
- b. Presentation
- c. Session
- d. Application

MCQ 5. End-to-end ports (TCP/UDP) are:

- a. Transport
- b. Network
- c. Physical
- d. Data link

MCQ 6. The model that explains "how data travels" is a:

- a. Communication model
- b. Sort algorithm
- c. K-map
- d. MVP

Extra short questions

- Write the 7 OSI layers from top to bottom.
- One job of Transport and of Network.
- Why layer models?
- Mnemonic you will actually write in the exam.

Extra long question

- Name all 7 OSI layers with one job and one protocol/hardware example each. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Application, Presentation, Session, Transport, Network, Data Link, Physical.
- Transport: reliability/ports (TCP/UDP). Network: routing and logical addressing (IP).
- Each layer has a small job; vendors can change one layer without rewriting the rest.
- Please Do Not Throw Sausage Pizza Away (bottom-up) or All People Seem To Need Data Processing (top-down).

Long

- 7 App HTTP/DNS; 6 Pres encryption/JPEG; 5 Sess dialogs; 4 Trans TCP/UDP; 3 Net IP/routers; 2 DL frames/MAC/switches; 1Phy cables/bits/hubs. Draw the stack.

2.3.2 Algorithmic Strategy: Pattern Recognition

LEARN IT

Pattern recognition is the process of identifying regularities, repetitions or rules in data. It helps in reducing the overall complexity of an algorithm and forms the foundation of concepts such as loops.

How it works — ask yourself three questions:

- What is repeating?
- What changes in a predictable way?
- Can I generalise this (write one rule that works for every case)?

WORKED EXAMPLE

Example: Triangle of stars

OUTPUT

```
*
**
***
****
*****
```

Step 1 — What repeats? Every row prints stars.

Step 2 — What changes predictably? Each row adds 1 star to the previous row's count.

Row	Stars
1	1
2	2
3	3
...	...
N	N

Step 3 — Generalise: Row N = N stars. Recognising this pattern lets us write one generic loop instead of 5 separate print statements.

Without the pattern (5 statements)

```
print("*")
print("**")
print("***")
print("****")
print("*****")
```

With the pattern (one loop)

```
n = 5
for row in range(1, n + 1):
    print("*" * row)
```

Both programs print exactly the same triangle. But if you want 100 rows, the loop version needs only one change (n = 100), while the first version needs 100 lines.

REMEMBER IT

Whenever you see "the same thing again and again, with a small change each time", think **loop**. Pattern recognition is the habit of spotting that.

COMMON MISTAKE

Do not generalise from too few cases. Check your rule on several rows (or items) before trusting it. "Row N = N stars" is correct here; a different triangle (1, 3, 5, 7 stars) follows the rule "Row N = 2N - 1 stars".

اردو میں سمجھیں

پيٽرن ريڪگنيشن (Pattern Recognition) کا مطلب ہے ڈیٹا میں دہرائی جانے والی چیزوں یا اصولوں کو پہچاننا۔ ستاروں کی نگوں میں ہر قطار میں پچھلی قطار سے ایک ستارہ زیادہ ہے، یعنی قطار N میں N ستارے۔ یہ پيٽرن پہچان کر ہم پانچ الگ پرنٹ کے بجائے ایک لوپ (Loop) لکھ سکتے ہیں۔

CHECK YOURSELF

1. Which programming concept is based on pattern recognition?

2. How many stars will row 8 of the triangle have?

3. Find the rule: 2, 4, 6, 8, ...

Answers: 1. Loops. 2. 8 stars (Row N = N stars). 3. Term N = 2 × N (each term adds 2).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Pattern recognition is:

a. Spotting repeats and rules in data

b. Hiding details

c. Breaking into parts

d. A TCP flag

MCQ 2. If every student card has name+photo+id, that is a:

a. Pattern

b. Virus

c. K-map wrap

d. Sprint

MCQ 3. Patterns let you:

a. Reuse a solution

b. Delete the algorithm

c. Avoid abstraction

d. Skip testing

MCQ 4. Spam filters look for:

a. Patterns in text

b. OSI layer 1 copper

c. NAND only

d. Beachhead markets

MCQ 5. No pattern means:

a. Treat the case as unique

b. Always bubble sort

c. Always pie charts

d. Always Agile

MCQ 6. CT pillar closest to "I've seen this shape of problem" is:

a. Pattern recognition

b. Physical layer

c. Variance

d. Figma

Extra short questions

1. Define pattern recognition.

2. Give a school example.

3. How do patterns shrink an algorithm?

4. What if you force a pattern that is not there?

Extra long question

1. Show pattern recognition on: (a) attendance lists, (b) weather by month, (c) login screens. For each, name the repeating structure and the algorithm you reuse.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Finding regularities, repetitions or rules so you can reuse a method.

2. Every paper has roll, name, marks — same record shape, same processing loop.

3. One loop or one function handles every similar case.

4. Wrong reuse — the solution fails on the odd case.

Long

1. (a) row per student → linear scan/count. (b) month+value → line graph / average. (c) username+password+submit → same validation function.

7

2.3.3 Algorithmic Strategy: Abstraction

LEARN IT

Abstraction means hiding unnecessary features and focusing only on the essential ones needed to solve a problem. It reduces complexity by ignoring what is not important (the **noise**).

When you apply abstraction you sort details into three groups:

- Necessary steps** — the core logic that never changes.
- Changes based on the situation** — these become **variables** (inputs) in the algorithm.
- Abstraction items (noise)** — details you can ignore completely.

WORKED EXAMPLE

Example: applying abstraction to "Making Tea"

To make an algorithm for tea, we separate the necessary steps from the situational changes and the noise.

1. Necessary steps (core logic)	2. Changes based on situation (variables)	3. Abstraction items (ignore / noise)
1. Boil water 2. Add tea leaves/bag 3. Steep for a few minutes 4. Pour into cup 5. Serve	Ingredients (black, green, milk) Additions (sugar, lemon) Tools (stove vs kettle)	Brand of kettle Cup colour or design Where tea is made (kitchen, office)

The core abstracted logic, independent of cup colour or kettle brand:

Boil water → Add tea → Steep → Pour → Serve

This one algorithm now works for green tea in an office kettle and for milk tea on a kitchen stove. The middle column simply becomes inputs: `tea_type`, `addition`, `tool`.

Computers use abstraction everywhere. When you call `print("Hello")` in Python, you do not think about how the screen lights up each pixel — those details are hidden from you. A map of Karachi shows roads and landmarks but hides every tree and car: it is an abstraction of the city.

REMEMBER IT

Abstraction = "**Keep the skeleton, drop the decoration.**" Ask: "If I remove this detail, does the solution still work?" If yes, it is noise.

COMMON MISTAKE

Do not confuse abstraction with decomposition. Decomposition *splits* a problem into parts. Abstraction *removes* unimportant details. Also, do not throw away details that really matter — "boil water" can never be ignored, but kettle brand can.

اردو میں سمجھیں

ایبسٹریکشن (Abstraction) کا مطلب ہے غیر ضروری تفصیلات کو چھپا کر صرف ضروری باتوں پر توجہ دینا۔ چائے بنانے کی مثال میں پانی ابلانا، پتی ڈالنا، دم دینا، کپ میں ڈالنا اور پیش کرنا ضروری مراحل ہیں؛ چائے کی قسم یا چینی متغیرات (Variables) ہیں؛ جبکہ کیتلی کا برانڈ یا کپ کا رنگ فالتو باتیں (Noise) ہیں جنہیں نظر انداز کیا جاتا ہے۔

CHECK YOURSELF

1. What is "noise" in abstraction?
2. In the tea example, is "sugar or lemon" a necessary step, a variable, or noise?
3. How is abstraction different from decomposition?

Answers: 1. Unnecessary details that do not affect the solution. 2. A variable (it changes with the situation). 3. Decomposition breaks a problem into parts; abstraction hides details that are not important.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Abstraction means:

a. Hiding extra detail, keeping what matters
b. Adding every detail
c. Sorting slowly
d. Drawing 7 OSI layers always

MCQ 2. A metro map that is not to scale is:

a. Abstraction
b. A truth table
c. A histogram
d. A key

MCQ 3. In coding, a function header without inner code is:

a. Abstraction of how
b. Decomposition only
c. A race condition
d. NAND

MCQ 4. Too little abstraction:

a. Overwhelms you with noise
b. Always speeds Big O
c. Creates XOR
d. Fixes phishing

MCQ 5. Too much abstraction:

a. Hides a detail you actually need
b. Prints SQL
c. Draws K-maps
d. Creates sprints

MCQ 6. A data type (list, stack) is an abstraction of:

a. How items are stored/accessed
b. TCP ports
c. Screen DPI
d. Figma frames

Extra short questions

1. Define abstraction.
2. Give a transport example.
3. Give a programming example.
4. How is abstraction different from decomposition?

Extra long question

1. For a college library app, list five details to keep and five to hide. Justify each as abstraction.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Hide unnecessary features; keep the essential ones needed to solve the problem.
2. Bus timetable shows stops and times, not engine temperature.
3. You call `sort(list)` without writing the swap loop.
4. Decomposition splits; abstraction hides. You often do both.

Long

1. Keep: ISBN, availability, due date, member id, fine. Hide: shelf paint colour, server fan speed, librarian's tea break, exact disk blocks, CSS pixels. Link to a simple interface of search/issue/return.

8

2.4.1 Sorting Algorithms: Selection Sort

Selection Sort is a simple sorting algorithm that works by repeatedly **selecting the smallest element** from the unsorted portion of the list and moving it to its correct position at the front. Think of it as filling seats from the front: first find who belongs in position 1, then position 2, and so on. In the textbook version, the element at position K is compared with every element after it; whenever a smaller one is found, the two are swapped. So at the end of pass K , the K th smallest value sits in position K .



Algorithm (Textbook)

```
1. Sort:
2. Step 1: Set DATA → [A, 1, 1, 1, 3]
3. Step 2: Set n ← 5
4. Step 3: Repeat Step 5 and 6 for
    K = 1 to n
5. Step 5: Set PTR ← K
6. Step 6: Repeat while PTR < n:
    a. If DATA[K] > DATA[PTR]:
       1. Set Temp ← DATA[K]
       2. Set DATA[K] ← DATA[PTR]
       3. Set DATA[PTR] ← Temp
    7. Set PTR ← PTR + 1
8. Step 7: End
```

Pseudocode

```
1. Sort:
2. DATA ← [A, 1, 1, 1, 3]
3. n ← 5
4. For outer ← 0 to n-1
   For inner ← outer+1 to n-1
     If DATA[outer] > DATA[inner]
       Temp ← DATA[outer]
       DATA[outer] ← DATA[inner]
       DATA[inner] ← Temp
   End If
6. End For
7. End For
```

Teacher's tip – spot the difference: In Selection Sort the inner loop starts at 'outer' + 1 and compares with the fixed position DATA[outer]. In Bubble Sort the inner loop always starts at 0 and compares neighbours DATA[inner] and DATA[inner+1]. Bubble pushes the largest to the end; Selection brings the smallest to the front.

WORKED EXAMPLE

Worked example: sort 8, 4, 1, 9, 3 in ascending order (textbook method). The two positions in brackets are being compared.

Pass 1 – find the smallest for Position 1

Compare	List	Post2 > Post3?	Action	List after
Post2 vs Post3	[8], [4], [1], 9, 3	8 > 4 Yes	Swap	4, 8, 1, 9, 3
Post2 vs Post3	[4], 8, [1], 9, 3	4 > 1 Yes	Swap	1, 8, 4, 9, 3
Post2 vs Post3	[1], 8, 4, [9], 3	1 > 9 No	No change	1, 8, 4, 9, 3
Post2 vs Post3	[1], 8, 4, 9, [3]	1 > 3 No	No change	1, 8, 4, 9, 3

1 is now permanently in Position 1.

Pass 2 – find the smallest for Position 2

Compare	List	Post2 > Post3?	Action	List after
Post2 vs Post3	1, [8], [4], 9, 3	8 > 4 Yes	Swap	1, 4, 8, 9, 3
Post2 vs Post3	1, [4], 8, [9], 3	4 > 9 No	No change	1, 4, 8, 9, 3
Post2 vs Post3	1, [4], 8, 9, [3]	4 > 3 Yes	Swap	1, 3, 4, 8, 9

Pass 3 – find the smallest for Position 3

Compare	List	Post3 > Post4?	Action	List after
Post3 vs Post4	1, 3, [8], [9], 4	8 > 9 No	No change	1, 3, 8, 9, 4
Post3 vs Post4	1, 3, [8], 9, [4]	8 > 4 Yes	Swap	1, 3, 4, 8, 9

Pass 4 – find the smallest for Position 4

Compare	List	Post4 > Post5?	Action	List after
Post4 vs Post5	1, 3, 4, [8], [9]	8 > 9 Yes	Swap	1, 3, 4, 9, 8

Sorted list: 1, 3, 4, 8, 9. Totals: 4 + 3 + 2 + 1 = 10 comparisons, 6 swaps in this textbook method.

Pass		Last after pass	Fixed at the front
Start		8, 4, 1, 9, 3	—
1		1, 8, 4, 9, 3	1
2		1, 3, 4, 8, 9	1, 3
3		1, 3, 4, 8, 9	1, 3, 4
4		1, 3, 4, 8, 9	all

WORKED EXAMPLE

Selection Sort in Python (follows the textbook pseudocode):

```
data = [8, 4, 1, 9, 3]
n = len(data)
for outer in range(n - 1):
    for inner in range(outer + 1, n):
        if data[outer] > data[inner]:
            temp = data[outer]
            data[outer] = data[inner]
            data[inner] = temp
    print("After pass", outer + 1, ":", data)
print("Sorted list:", data)
```

Output:

```
After pass 1: [1, 8, 4, 9, 3]
After pass 2: [1, 3, 4, 9, 8]
After pass 3: [1, 3, 4, 8, 9]
After pass 4: [1, 3, 4, 8, 9]
Sorted list: [1, 3, 4, 8, 9]
```

WORKED EXAMPLE

The "classic" Selection Sort (one swapper pass). Many books first find the position of the smallest value in the unsorted part, and swap only once at the end of each pass. The result is the same; only the swaps are fewer.

```
data = [8, 4, 1, 9, 3]
n = len(data)
for outer in range(n - 1):
    minIndex = outer
    for inner in range(outer + 1, n):
        if data[inner] < data[minIndex]:
            minIndex = inner
    data[outer], data[minIndex] = data[minIndex], data[outer]
    print("After pass", outer + 1, ":", data)
```

Output:

```
After pass 1: [1, 8, 4, 9, 3]
After pass 2: [1, 3, 4, 9, 8]
After pass 3: [1, 3, 4, 8, 9]
After pass 4: [1, 3, 4, 8, 9]
```

Here only 4 swaps are made (at most $N - 1$). This is why Selection Sort is said to perform fewer swaps than Bubble Sort. In exams, use the textbook method unless the question asks otherwise.

Advantages	Disadvantages
Very easy to code.	Time grows very fast with list size (nested loops, about n^2 comparisons).
Requires fewer swaps overall compared to Bubble Sort.	Must track every single loop — it's "stupid" to be already sorted list.
Does not need extra memory.	Not stable (it might change the relative positions of equal items).

WORKED EXAMPLE

Why "yes stable"? Take two equal marks, S_1 (Ali) and S_2 (Bilal). In the list S_1, S_2 , Pass 1 compares S_1 with S_2 (no swap), then S_1 with 2 → swap → $2, S_1, S_2$. Now Bilal is before Ali, although Ali came first originally. Bubble Sort never does this, because it swaps only neighbours that are strictly out of order.

COMMON MISTAKE

In the textbook method, the comparison is always with the **fixed position** DATA[K] (Post in pass 1, Post2 in pass 2), not with the neighbour. Students often mix this up with Bubble Sort and compare neighbours. Also, after a swap, the new value at Pos K is used for the next comparison.

آدم من مستحقين
سليمن مبارك (Selection Sort) من فيروست كي غير ترتيب شده حلقه مي مي سب مي بهرود عدد دن كر امني سامني ابي كر دروست بگ بر كجا بگذاي، بر ابي من ايك طرزه بگ (Prohibit) كا موازك ابي كي بعد وائي تمام عناصر مي بولاي، اس كا كراش امان بر اور بيل سارز مي كم ترابي (Swap) بوتاي بين ليكن به مستحسك (Stable) ابي اور ترتيب شده فيروست پر وهي بولم كواب جاتا اي.

EXAM TIP

Typical questions: "Sort ... using Selection Sort, showing all steps", "Differentiate between Bubble Sort and Selection Sort" and "Why is Selection Sort not stable?". In the difference question mention: what is compared (neighbours vs fixed position), where the inner loop starts (0 vs outer-1), where items settle (end vs front), stability, and number of swaps.

CHECK YOURSELF

- In Selection Sort, where does the inner loop start?
- Using the textbook method, show 2, 7, 5 after pass 1.
- Which of the two sorts is stable?

Answers: 1. At outer + 1 (PTR = K + 1). 2. Post vs Post2? 7 > 2 swap → 2, 7, 5. Post vs Post2? 5 > 5 no → 2, 7, 5. 3. Bubble Sort.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Selection sort each pass:

- Selects the minimum from the unsorted part and swaps it into place
- Swaps only adjacent
- Needs a sorted list first
- Uses a stack

MCQ 2. After k passes, the first k items are:

- The k smallest in order
- Random
- The k largest
- Deleted

MCQ 3. Comparisons are about:

- $O(n^2)$ even if nearly sorted
- $O(n)$
- $O(n^2)$
- Zero always

MCQ 4. Swaps per pass: at most:

- One
- 0
- n^2
- Zero always

MCQ 5. Selection vs bubble: selection usually has:

- Fewer swaps
- Fewer comparisons
- Better Big O
- A hash table

MCQ 6. On [8,4,1] min of whole list is:

- 1, swapped to front
- 8
- 4
- 9

Extra short questions

- Define selection sort.
- One pass on 8,4,0,3.
- Why isn't $O(n^2)$ if data is sorted?
- Stable?

Extra long question

- Full trace of selection sort on 8,4,0,3. Count swaps. Compare swap count with bubble on the same list.

Extra answer key

MCQs: 1. A, 2. A, 3. A, 4. A, 5. A, 6. A

Short

- Repeatedly select the smallest remaining item and swap it into the next position.
- Min-1, swap with 8 → 1,8,0,3.
- You still scan the unsorted suffix every pass; there is no early exit like Tagged bubble.
- Classic selection is not stable (equal keys can swap order).


Long

- Passes put 1, then 3, then 4, then 8,9. Swaps: 8+1, 4+3, 6+4, maybe 8+6 skip, 9 in place. Bubble does more adjacent swaps. Both $O(n^2)$ comparisons.

2.4.2 Searching Algorithms: Linear Search

LEARN IT

Linear Search, also known as **sequential search**, works by examining each element in the list one by one, from the start, until the target is found (or the list ends). It works on both **sorted** and **unsorted** data. A **flag** variable (here `ValueFound`) starts at 0 and becomes 1 when the item is found. After the loop, the flag tells us whether to print the item or "Not Found".



Algorithm (textbook)

```
Step 1: Start
Step 2: DATA := {8,3,6,1,7,2,4,5}
Step 3: N := 8
Step 4: FindValue := 7
Step 5: ValueFound := 0
Step 6: Repeat for PTR = 1 to N
Step 7: If DATA[PTR] = FindValue:
    a. ValueFound = 1
    b. Goto Step 8
Step 8: If ValueFound = 1:
    Print DATA[PTR]
Else:
    Print "Not Found"
Step 9: End
```

Pseudocode

```
Start
data = {8, 3, 6, 1, 7, 2, 4, 5}
n = 8
FindValue = 7
valueFound = 0
for PTR = 0 to N-1
    If DATA[PTR] == FindValue then
        ValueFound = 1
    Exit Loop
End If
See Ron
If ValueFound == 1 then
    Print DATA[PTR]
Else
    Print "Data Not Found"
End If
End
```

WORKED EXAMPLE

Worked example. Data list: 8, 3, 6, 1, 7, 2, 4, 5. Searching item: 7.

Step	Element checked	Condition (i==7)	Result
1	8	8 == 7?	Not found
2	3	3 == 7?	Not found
3	6	6 == 7?	Not found
4	1	1 == 7?	Not found
5	7	7 == 7?	Found! (Exit loop)

7 is found at position 5 (index 4) after 5 comparisons. The remaining items 2, 4, 5 are never checked.

If the item is missing — e.g., search for 9 — all 8 elements are checked, the flag stays 0, and "Data Not Found" is printed. This is the **worst case**: N comparisons.

WORKED EXAMPLE

Linear Search in Python

```
data = [8, 3, 6, 1, 7, 2, 4, 5]
find_value = 7
value_found = 0
for ptr in range(len(data)):
    print("Step", ptr + 1, ": checking", data[ptr])
    if data[ptr] == find_value:
        value_found = 1
        break
if value_found == 1:
    print("Found", data[ptr], "at position", ptr + 1)
else:
    print("Data Not Found")
```

OUTPUT

```
Step 1 : checking 8
Step 2 : checking 3
Step 3 : checking 6
Step 4 : checking 1
Step 5 : checking 7
Found 7 at position 5

break is Python's "Exit Loop".
```

Advantages and disadvantages

Advantages	Disadvantages
Does not care whether data is scrambled or sorted.	If the target is at the end of 1 million items, it does 1 million checks.
Extremely simple code (one loop, one if statement).	Time grows linearly (double the list = double the time).
Faster for very small lists (no setup time, such as sorting).	Inefficient if you need to search the same list thousands of times.
Does not require any extra space.	

REMEMBER IT

Linear Search is like looking for your friend in a queue by checking every face from the front. Best case: 1 check (first person). Worst case: N checks (last person or not there).

COMMON MISTAKE

Do not print "Not Found" inside the loop after every mismatch — that would print it many times. Decide only **after** the loop ends, using the flag. And remember to **exit** the loop once the item is found, or you waste comparisons.

آرڈو میں سمجھیں

لینیئر سرچ (Linear Search) کو ترتیب وار تلاش (Sequential Search) بھی کہتے ہیں۔ اس میں فہرست کے ہر عنصر کو شروع سے ایک ایک کر کے چیک کیا جاتا ہے جب تک مطلوب چیز نہ مل جائے۔ یہ ترتیب شدہ اور غیر ترتیب شدہ دونوں قسم کے ڈیٹا پر کام کرتی ہے اور بہت سادہ ہے، لیکن بڑی فہرست میں بہت وقت لیتی ہے۔

CHECK YOURSELF

- What is another name for Linear Search?
- In 8, 3, 6, 1, 7, 2, 4, 5, how many comparisons are needed to find 2?
- What is the purpose of the variable ValueFound?

Answers: 1. Sequential search. 2. 6 comparisons (2 is in position 6). 3. It is a flag: 0 means not found yet, 1 means found; it decides what to print after the loop.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Linear search checks: a. Each item in order until found or the list ends b. Only the middle c. Only the last d. A binary tree	MCQ 2. It works on: a. Sorted or unsorted lists b. Sorted lists only c. Graphs only d. Empty files only	MCQ 3. Worst comparisons for n items: a. n b. log n c. 1 d. n ²	MCQ 4. Best case is: a. Target is first: 1 comparison b. Always n c. Always log n d. 0	MCQ 5. If the item is absent: a. You scan the whole list b. You halt at mid c. You pop a stack d. You draw a pile	MCQ 6. Linear search is also called: a. Sequential search b. Binary search c. Hash search d. Interpolation always
---	--	---	---	--	--

Extra short questions

- Define linear search.
- Advantage vs binary.
- Disadvantage.
- Trace search for 7 in 8,3,6,1,7.

Extra long question

- Write pseudocode for linear search that returns the index or -1. Dry-run a hit and a miss.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Examine each element from the start until the target is found or the list ends.
- No need to sort first; works on any list.
- O(n)** — slow for huge lists.
- 8, 3, 6, 1, 7 = found at index 4 (0-based) / position 5.

Long

- FOR i ← 0 TO n-1: IF a[i]=t RETURN i; RETURN -1. Hit example and miss example with counts.

2.4.2 Searching Algorithms: Binary Search

Linear Search

Binary Search is a highly efficient search algorithm that works by repeatedly dividing the search interval in half. **Crucial limitation: it only works on a SORTED list.**

Three variables mark the part of the list still being searched:

- BEG (low)** — first position of the current part.
- END (high)** — last position of the current part.
- MID** = $(\text{BEG} + \text{END}) / 2$ — the middle position. INT means "drop the decimal part".

At each step compare the item with $\text{DATA}[\text{MID}]$:

- Equal = found, stop.
- Item < $\text{DATA}[\text{MID}]$ => the item can only be in the left half: set $\text{END} = \text{MID} - 1$.
- Item > $\text{DATA}[\text{MID}]$ => the item can only be in the right half: set $\text{BEG} = \text{MID} + 1$.

If BEG becomes greater than END , the part is empty and the item is **not in the list**.



Algorithm (textbook summary)

```
Step 1: Start
Step 2: data = [1, 2, 3, 4, 5, 6, 7, 8, 9]
(sorted)
Step 3: beg = 1, end = 9
Step 4: mid = int((beg+end)/2)
Step 5: item = 7
Step 6: loc = 0
Step 7: Repeat while beg <= end and mid <= len(data):
Step 8: If item < data[mid]:
    end = mid - 1
Else:
    beg = mid + 1
Step 9: mid = int((beg+end)/2)
Step 10: [End loop]
Step 11: If data[mid] == item:
    loc = mid
Else:
    loc = 0
Step 12: Print result based on loc
Step 13: End
```

Pseudocode

```
Algorithm
data = [1, 2, 3, 4, 5, 6, 7, 8, 9]
beg = 1, end = 9
mid = int((beg+end)/2)
loc = NULL
Repeat while beg <= end and data[mid] != item:
    If item < data[mid] then
        end = mid - 1
    Else
        beg = mid + 1
    mid = int((beg+end)/2)
Print mid
If data[mid] == item then
    loc = mid
Else
    loc = NULL
Print loc
If loc = NULL then
    Print "Not Found"
Else
    Print "Found"
```

COMMON MISTAKE

The slide's pseudocode writes the loop condition as $\text{BEG} < \text{END}$ OR $\text{DATA}[\text{MID}] == \text{item}$. That is a slip with OR the loop would never stop once the item is found while $\text{BEG} < \text{END}$. The textbook algorithm (Step 7) correctly uses **AND** — keep going only while the part is not empty and the item is not yet found. Likewise, the slide sets $\text{LOC} = \text{NULL}$ but then tests $\text{LOC} > 0$; the check should simply be " LOC is not NULL " [ie, with $\text{LOC} = 0$ meaning not found, " $\text{LOC} > 0$ ". The pseudocode above shows the corrected form.

WORKED EXAMPLE

Worked example 1 (textbook algorithm). DATA = 1, 2, 3, 4, 5, 6, 7, 8, 9, item = 7, Positions 1 to 9.

Step	BEG (low)	END (high)	MID	DATA[MID]	Compare	Action
1	1	9	$(1+9)/2 = 5$	5	$7 > 5$	$\text{BEG} = 6$ (go right)
2	6	9	$(6+9)/2 = 7$	7	$7 = 7$	Found, LOC = 7

Only 2 comparisons. Linear Search would need 7.

WORKED EXAMPLE

Worked example 2 (slide example). Sorted list: 1, 2, 3, 4, 5, 6, 7, 8. Searching item: 3.

Step	BEG (low)	END (high)	MID	DATA[MID]	Compare	Action
1	1	8	$(1+8)/2 = 4$	4	$3 < 4$	$\text{END} = 3$ (go left)
2	1	3	$(1+3)/2 = 2$	2	$3 > 2$	$\text{BEG} = 3$ (go right)
3	3	3	$(3+3)/2 = 3$	3	$3 = 3$	FOUND at position 3

Picture the list shrinking (the highlighted cell is MID):

Step	1	2	3	4	5	6	7	8
1	1	2	3	4	5	6	7	8
2	1	2	3	4	5	6	7	8
3	1	2	3	4	5	6	7	8

The slide describes the same steps using the size of each sub-list: Step 1 $\text{MID} = 4$ (value 4), $3 < 4$, go left; Step 2 sub-list [1, 2, 3], middle = $(1+3)/2 = 2$ (value 2), $3 > 2$, go right; Step 3 sub-list [3], middle = 1st item (value 3), FOUND. Both ways land on the same values $4 + 2 = 3$.

WORKED EXAMPLE

Binary Search in Python (index starts at 0, so positions 1-8 become indexes 0-7):

```
def binary_search(data, item):
    low = 0
    high = len(data) - 1
    while low <= high:
        mid = (low + high) // 2
        if data[mid] == item:
            return mid
        elif data[mid] < item:
            low = mid + 1
        else:
            high = mid - 1
    return None

# Example usage
data = [1, 2, 3, 4, 5, 6, 7, 8]
item = 3
result = binary_search(data, item)
if result is not None:
    print(f"Item found at index {result}")
else:
    print("Item not found")
```

// is integer division, the same as INT(). Index 2 is position 3. Here $\text{low} = -1$ means "not found", so the test $\text{low} > \text{high}$ is correct.

Why is it so fast?
Every comparison throws away half of the remaining list. $1,000,000 \rightarrow 500,000 \rightarrow 250,000 \rightarrow \dots \rightarrow 1$ takes about 20 halvings, because $2^{20} \approx 1,048,576$. So Binary Search finds an item among 1 million elements in at most about 20 steps, while Linear Search may need 1,000,000.

Advantages and disadvantages

Advantages	Disadvantages
Extremely fast for "Big Data": finds an item in 1M elements in just ~20 steps.	The list must be sorted first; it fails on scrambled data.
Massive time savings for static lists that are searched repeatedly.	Requires random access to elements (works on arrays, not really on linked lists).
	More complex code, prone to logic errors (off-by-one).

REMEMBER IT

Binary Search is how you find a word in a dictionary: open the middle, decide "before or after?", and throw away half the book each time. **"Sorted first, then split."**

COMMON MISTAKE

Common errors (5) using Binary Search on an unsorted list — the answer will be wrong: (2) setting $\text{END} = \text{MID}$ instead of $\text{MID} - 1$ (or $\text{BEG} = \text{MID}$ instead of $\text{MID} + 1$), which can cause an infinite loop — this is the "off-by-one" error; (3) forgetting INT, so MID becomes a decimal like 4.5.

اردو میں سمجھیں

بائیوری سرچ (Binary Search) ایک تیز رفتار طریقہ ہے جو ہر قدم پر تلاش کی جاتی ہے کہ آیا وہ موجود ہے یا نہیں۔ صرف ایک بار دہرائے (sorted) ڈیٹا پر کام کرنا ہے۔ درجہ اول (MID) سے موازنہ کیا جاتا ہے اگر مطلوب چیز پھولوں کو تو پائی آتی ہے جسے میں تلاش جاری رکھتی ہوں، میں اس کا نصف دائرہ میں کھینچ کر ایک نیا نصف دائرہ بناتی ہوں۔

EXAM TIP

You will usually be given a sorted list and an item and asked to "search using Binary Search, showing all steps". Always draw a table with **BEG, END, MID, DATA[MID], comparison, action**. Show the INT calculation for MID. If the item is absent, continue until $\text{BEG} > \text{END}$ and write "Not Found". Also learn: "Why must the list be sorted?" and "Compare Linear and Binary Search".

CRUCIAL REMINDER

CRUCIAL REMINDER: Binary Search only works on a sorted list. If the list is unsorted, the results will be incorrect.

CRUCIAL REMINDER

CRUCIAL REMINDER: Binary Search only works on a sorted list. If the list is unsorted, the results will be incorrect.

Answers: 1. The list must be sorted. 2. $\text{INT}((1+9)/2) = 5$. 3. $\text{MID} = 4$ (value 4, go right, $\text{BEG} = 6$) → $\text{MID} = \text{INT}((6+9)/2) = 7$ (value 7, go right, $\text{BEG} = 8$) → $\text{MID} = 8$ (value 8, found). Four comparisons.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Binary search requires: a. A sorted list b. An unsorted list c. A graph d. A pie chart	MCQ 2. Each step discards: a. About half the remaining items b. One item only c. The whole list d. Only when numbers	MCQ 3. Complexity is: a. $O(n^2)$ b. $O(n)$ c. $O(\log n)$ d. $O(1)$ always	MCQ 4. If mid value is too big you go: a. Left half b. Right half c. To a stack d. To OS layer 7	MCQ 5. On sorted [1..8] searching 3, first mid is: a. 4 (value 4), then go left b. 1 c. 8 d. 7	MCQ 6. Binary search on unsorted data is: a. Wrong / may miss b. Always faster c. A sort d. A pile
--	---	--	---	---	---

Extra short questions

- Define binary search and its precondition.
- Why **$O(\log n)$** ?
- What if the list is unsorted?
- Trace 3 in [1,2,3,4,5,6,7,8].

Extra long question

5. Write binary search pseudocode with low, high, mid. Trace two targets (present and absent) on an 8-item sorted list. ★ Golden.

Extra answer key

MCQs: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100.

Short

- Repeatedly test the middle of a sorted list; go left or right. List must already be sorted.
- $n = n/2 \rightarrow n/4 \rightarrow \dots \rightarrow 1$. About $\log_2 n$ steps.
- Sort first (extra cost) or use linear search.
- mid 4, 3-4 left [2,3,4], mid 2, 3-2 right [3,4], mid 3 found.

Long

- WHILE low/high: mid=(low+high)/2; equal return; less → high=mid-1; greater → low=mid+1. Absent: low-high → not found. Show the shrinking intervals.

2.5 Evaluation Criteria of Algorithm

LEARN IT
Many algorithms can solve the same problem. To judge which is better, we evaluate them on three criteria: **correctness**, **efficiency** and **clarity**.

2.5.1 Correctness

An algorithm is **correct** if:

- Its output matches the expected outcomes;
- It handles **edge cases** gracefully (unusual inputs such as an empty list, 0, a negative number, or an item that is not present);
- It is guaranteed to finish — no infinite loops.

We test correctness with a **trace table** (dry run): we feed sample inputs and record every value by hand, then compare the result with what we expect.

WORKED EXAMPLE

Trace table example: Even/Odd checker. Rule: divide the number by 2; if the remainder is 0 it is Even, otherwise Odd.

Input	Operation (divide by 2, find remainder)	Remainder == 0?	Result
3	3 / 2 (Quotient = 1, Remainder = 1)	No	Odd
6	6 / 2 (Quotient = 3, Remainder = 0)	Yes	Even
15	15 / 2 (Quotient = 7, Remainder = 1)	No	Odd

All three results match what we expect, so the algorithm is correct for these inputs. The same check in Python:

```
for number in [3, 6, 15]:
    remainder = number % 2
    if remainder == 0:
        print(number, "remainder", remainder, "→ Even")
    else:
        print(number, "remainder", remainder, "→ Odd")
```

```
OUTPUT
3 remainder 1 → Odd
6 remainder 0 → Even
15 remainder 1 → Odd
```

A good tester would also try the edge case 0 (remainder 0 → Even, which is correct).

2.5.2 Efficiency

We measure algorithm efficiency through **time** (speed) and **space** (memory). The key question is: how fast does it run as the input size grows — does it **scale** well?

Computer scientists describe growth with **Big O notation**. It counts roughly how many steps are needed for N items:

- O(1)** — constant: same time, whatever N is.
- O(log N)** — logarithmic: grows very slowly (Binary Search).
- O(N)** — linear: double N, double the time (Linear Search).
- O(N²)** — quadratic: double N, four times the time (Bubble and Selection Sort).

WORKED EXAMPLE

How the worst-case number of comparisons grows

N (Items)	Linear Search (N)	Binary Search (about log ₂ N)	Bubble/Selection Sort (N(N-1)/2)
10	10	4	45
100	100	7	4,950
1,000	1,000	10	499,500
1,000,000	1,000,000	20	499,999,500,000

This is why Binary Search is called excellent for Big Data and the simple sorts are called useless for it.

2.5.3 Clarity (Readability)

An algorithm must be easy to read, understand and modify. It should use **clear steps**, **meaningful variable names** and **good indentation**.

Unclear

```
s=[3,6,15]
for x in s:
    if x%2==0:print(x,"E")
    else:print(x,"O")
```

Clear

```
numbers = [3, 6, 15]
for number in numbers:
    if number % 2 == 0:
        print(number, "Even")
    else:
        print(number, "Odd")
```

Both work, but the second is far easier for another person (or you, a month later) to understand and change.

REMEMBER IT

Remember **C-E-C**: **C**orrect (right answer, always finishes), **E**fficient (fast and light), **C**lear (easy to read).

COMMON MISTAKE

Testing only "normal" inputs is not enough to prove correctness. Always include edge cases in your trace table, e.g., the first item, the last item, a missing item, or an empty list in a search.

آزمو میں سمجھیں
کسی الگورتھم کو تین معیارات پر پرکھا جاتا ہے: درستگی (Correctness) یعنی درست نتیجہ دے، غیر معمولی صورتوں کو سنبھالے اور بعینہ ختم ہوا کارکردگی (Efficiency) یعنی کم وقت اور کم میموری استعمال کرے؛ اور وضاحت (Clarity) یعنی پڑھنے، سمجھنے اور تبدیل کرنے میں آسان ہو۔ درستگی جانچنے کے لیے ٹریس ٹیبل (Trace Table) بنایا جاتا ہے۔

CHECK YOURSELF

- Name the three evaluation criteria of an algorithm.
- Give one example of an edge case for a search algorithm.
- Efficiency is measured in terms of which two resources?

Answers: 1. Correctness, efficiency, clarity. 2. The item is not in the list (or the list is empty, or the item is the last element). 3. Time (speed) and space (memory).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Correctness means:

- a. Output matches the spec, including edges
- b. The code is short
- c. It uses XOR
- d. It prints Urdu

MCQ 2. Time efficiency is:

- a. How fast it grows with n
- b. Font size
- c. Cable length
- d. Number of comments

MCQ 3. Space efficiency is:

- a. Extra memory used
- b. Screen brightness
- c. TCP window only
- d. Pie slices

MCQ 4. An edge case for divide is:

- a. Divisor 0
- b. n=100 always
- c. Color of GUI
- d. Sprint length

MCQ 5. Readability is part of:

- a. Quality / clarity, not Big O itself
- b. Physical layer
- c. NAND grouping
- d. Variance

MCQ 6. You evaluate an algorithm before coding so you can:

- a. Pick a good one
- b. Skip tests
- c. Avoid variables
- d. Draw Figma only

Extra short questions

- List four evaluation criteria.
- What is an edge case?
- Correct but slow — is it acceptable?
- How do you show correctness in Xi/Xiif?

Extra long question

- Compare linear vs binary search using correctness, time, space, preconditions and a 10,000-name example.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Correctness, time, space, clarity/simplicity (and sometimes completeness).
- An extreme input: empty list, n=1, already sorted, not found, 0.
- For tiny n yes; for huge n you need a better Big O.
- Trace table or stepwise reasoning plus test cases.

Long

- Both can be correct. Linear **O(n)** any order; binary **O(log n)** needs sort. Space **O(1)**. 10k names: ~10k vs ~14 comparisons. Mention the cost of keeping the list sorted.

2.6 How to Decide Which Algorithm to Use

LEARN IT

Before choosing an algorithm, ask three questions:

- What is the input size? (10 items or 10 million?)
- Is the data sorted?
- Do we need speed or memory efficiency?

Simple decision guide:

- If searching on **unsorted** data → use **Linear Search**.
- If searching on **sorted** data → use **Binary Search**.
- If data needs **ordering** → use a **sorting** algorithm.



Comparison of the four algorithms

Algorithm	Type	Best case	Worst case	Extra memory	Needs sorted data?	Stable?
Bubble Sort	Sorting	$O(N^2)$ as written; $O(N)$ with an early-stop check	$O(N^2)$	None — $O(1)$	—	Yes
Selection Sort	Sorting	$O(N^2)$	$O(N^2)$	None — $O(1)$	—	No
Linear Search	Searching	$O(1)$ (first item)	$O(N)$ (last item / absent)	None — $O(1)$	No	—
Binary Search	Searching	$O(1)$ (item at first MID)	$O(\log N)$	None — $O(1)$	Yes	—

Point	Bubble Sort	Selection Sort
What is compared	Adjacent elements (j and j+1)	Fixed position K with every later element
Inner loop starts at	0	outer + 1
After each pass	Largest moves to the end	Smallest moves to the front
Swaps	Many	Fewer
Stable	Yes	No

Point	Linear Search	Binary Search
Method	Checks one by one	Splits the list in half each step
Data required	Sorted or unsorted	Sorted only
Worst case (1M items)	1,000,000 checks	About 20 checks
Code	Very simple	More complex, off-by-one risk
Best for	Small or unsorted lists, one-off searches	Large, sorted lists searched many times

WORKED EXAMPLE

Choosing in practice

- A shopkeeper's list of 15 items, written in random order, searched once: Linear Search — the list is unsorted and tiny; sorting first would waste time.
- NADRA looking up a CNIC number among millions of sorted records, thousands of times a day: Binary Search — data is sorted, huge, and searched repeatedly.
- A teacher arranging 40 students' marks into a merit list: a sorting algorithm; for 40 items even Bubble or Selection Sort is acceptable.
- An unsorted list of 1 million records that will be searched thousands of times: sort it once, then use Binary Search for every search.

REMEMBER IT

Two keywords decide most exam answers: "sorted?" and "how big?". Unsorted or small → Linear. Sorted and big → Binary.

COMMON MISTAKE

"Binary Search is always better" is wrong. On unsorted data it does not work at all, and for a single search on a small unsorted list, sorting first costs more than a simple Linear Search.

آردو میں سمجھیں

الگورتھم چننے سے پہلے دیکھیں کہ ڈیٹا کتنا بڑا ہے، ترتیب شدہ ہے یا نہیں، اور ہمیں رفتار چاہیے یا میموری کی بچت۔ غیر ترتیب شدہ ڈیٹا میں تلاش کے لیے لینیئر سرچ، اور ڈیٹا کو ترتیب دینے کے لیے سارٹنگ الگورتھم استعمال کریں۔

CHECK YOURSELF

1. Which search would you use on an unsorted list of phone contacts?
2. What is the worst-case time complexity of Binary Search?
3. Which sort has the same time complexity in its best and worst case?

Answers: 1. Linear Search. 2. $O(\log N)$. 3. Selection Sort ($O(N^2)$ in both).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. If the list is unsorted and n is small, search with: a. Linear search b. Binary search immediately c. Dijkstra d. Quicksort only	MCQ 2. If the list is sorted and n is huge, search with: a. Binary search b. Linear only c. Bubble d. OSI	MCQ 3. If you must sort a class of 20 names by hand: a. Simple $O(n^2)$ is fine b. You must use $O(n \log n)$ hardware c. K-maps d. HCI	MCQ 4. Memory is tiny: prefer: a. In-place algorithms b. Huge extra arrays c. Storing every trace forever d. Videos	MCQ 5. Need a stable sort of equal keys: a. Do not pick unstable selection without care b. Always XOR c. Always pie d. Always Agile	MCQ 6. The first questions are: a. n? sorted? time vs memory? b. Font? Colour? OS? c. NAND count only d. Figma frames
--	--	--	--	--	--

Extra short questions

1. List four questions before choosing an algorithm.
2. When is $O(n^2)$ OK?
3. When must you use binary search?
4. Give a wrong choice and why.

Extra long question

1. A college has 30 students (daily) and 50,000 archived papers (yearly search). Recommend sort/search for each situation with reasons.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Input size? Sorted? Need speed or memory? Stable? Worst vs average?
2. Small n, or the inner work is tiny, or you run it rarely.
3. Large sorted collection, many queries.
4. Binary search on unsorted roll numbers — may miss the target.

Long

1. Daily: selection/bubble or even by-hand; linear search. Archive: keep sorted, binary search (or a database index). State Big O and a precondition.

Computational Thinking & Algorithm

11 single-page lessons · 6 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- **Computational thinking** is systematic problem solving using decomposition, pattern recognition, abstraction and algorithms.
- An **algorithm** is a step-by-step logical procedure to solve a problem; it is conceptual and language-independent.
- Algorithms give structure, optimise time and memory, are reusable, ensure accuracy and act as a blueprint for code.
- **Pseudocode** is a human-readable, structured representation of an algorithm using keywords like IF, FOR and WHILE; it is not executable.
- An algorithm defines *what* to do; pseudocode shows *how* to implement it.
- **Decomposition** breaks a big problem into smaller sub-tasks; it reduces complexity, helps debugging and promotes reusability.
- **Pattern recognition** finds repetitions and rules (Row N = N stars) and is the foundation of loops.
- **Abstraction** hides noise and keeps only essential steps; situational details become variables.
- Sorting arranges data (ascending or descending); searching locates an element's position or existence.
- **Bubble Sort** compares and swaps adjacent elements; the largest value moves to the end each pass; N – 1 passes; stable; $O(N^2)$.
- **Selection Sort** brings the smallest remaining value to the front each pass; inner loop starts at outer + 1; fewer swaps; not stable; $O(N^2)$.
- **Linear Search** checks items one by one; works on unsorted data; $O(N)$ worst case.
- **Binary Search** halves the search range using BEG, MID and END; needs sorted data; $O(\log N)$ — about 20 steps for 1 million items.
- Algorithms are evaluated on **correctness** (checked with trace tables and edge cases), **efficiency** (time and space) and **clarity**.
- Choose by asking: input size, sorted or not, speed or memory? Unsorted → Linear; sorted → Binary; needs order → sort.

Key terms

Term	Meaning	اردو
Computational thinking	A systematic approach to solving problems using decomposition, patterns, abstraction and algorithms.	کمپیوٹیشنل سوچ
Algorithm	A step-by-step logical procedure to solve a problem, independent of any language.	الگورتھم، مرحلہ وار طریقہ حل
Pseudocode	A human-readable, structured but non-executable representation of an algorithm.	سوڈو کوڈ، فرضی کوڈ
Decomposition	Breaking a complex problem into smaller, manageable parts.	تقسیم کاری
Sub-task	One small part of a decomposed problem.	ذیلی کام
Pattern recognition	Identifying regularities, repetitions or rules in data.	نمونے کی پہچان
Abstraction	Hiding unnecessary details and focusing on essentials.	تجريد، غير ضروری تفصیل چھپانا
Noise	Details that do not affect the solution and can be ignored.	فالتو تفصیلات
Sorting	Arranging items in ascending or descending order.	ترتیب دینا
Searching	Locating an element in a list to find its position or existence.	تلاش کرنا
Ascending order	Smallest to largest (0–9, A–Z).	صعودی ترتیب
Descending order	Largest to smallest (9–0, Z–A).	نزولی ترتیب

Computational Thinking & Algorithm

75 marks · 1 hour 15 minutes · no notes · no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 11 and the recap. **Section A** — all 15 MCQs (1 mark). **Section B** — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define · Explain · Example · Diagram · Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. An algorithm is best defined as:
 - a. a programming language
 - b. a step-by-step logical procedure to solve a problem
 - c. a type of computer hardware
 - d. compiled machine code
2. Pseudocode is:
 - a. executable machine code
 - b. a symbol used in flowcharts
 - c. a Python library
 - d. a human-readable representation of an algorithm using plain English and keywords
3. Breaking a complex problem into smaller, manageable parts is called:
 - a. decomposition
 - b. abstraction
 - c. pattern recognition
 - d. compilation
4. In the "making tea" example, ignoring the brand of the kettle is an example of:
 - a. decomposition
 - b. sorting
 - c. abstraction
 - d. searching
5. Pattern recognition forms the foundation of:
 - a. variables
 - b. loops
 - c. comments
 - d. input devices
6. Bubble Sort works by comparing:
 - a. the first and last elements
 - b. every element with the middle element
 - c. adjacent elements
 - d. random pairs of elements
7. After the first pass of Bubble Sort (ascending) on 8, 4, 1, 9, 3, the list is:
 - a. 1, 3, 4, 8, 9
 - b. 4, 8, 1, 9, 3
 - c. 1, 8, 4, 9, 3
 - d. 4, 1, 8, 3, 9
8. Binary Search works only on a list that is:
 - a. sorted
 - b. unsorted
 - c. stored in a linked list
 - d. of strings only
9. Linear Search is also known as:
 - a. binary search
 - b. sequential search
 - c. bubble search
 - d. random search
10. How many passes does Bubble Sort need to sort N elements?
 - a. N
 - b. N + 1
 - c. N - 1
 - d. 2N
11. In Selection Sort pseudocode, the inner loop starts at:
 - a. 0
 - b. N - 1
 - c. outer - 1
 - d. outer + 1
12. The worst-case time complexity of Binary Search is:
 - a. $O(\log N)$
 - b. $O(N)$
 - c. $O(N^2)$
 - d. $O(1)$
13. About how many steps does Binary Search need, at most, to find an item among 1 million sorted elements?
 - a. 2
 - b. 20
 - c. 1,000
 - d. 1,000,000
14. Which sorting algorithm is NOT stable?
 - a. Bubble Sort
 - b. Both are stable
 - c. Selection Sort
 - d. Neither sorts data
15. Which of the following is NOT an evaluation criterion of an algorithm?
 - a. Correctness
 - b. Efficiency
 - c. Clarity
 - d. Popularity

Section B — Short questions (10 × 3 = 30)

1. Define computational thinking and name its four components.
2. Write any four points on the importance of algorithms.
3. Give three differences between an algorithm and pseudocode.
4. What is decomposition? Explain it with the example of learning a new language.
5. What three questions should you ask during pattern recognition? Apply them to the triangle of stars.
6. Define abstraction. In the "making tea" example, name two variables and two noise items.
7. Differentiate between sorting and searching.
8. Why does Binary Search require a sorted list? State two disadvantages of Binary Search.
9. Give two differences between Bubble Sort and Selection Sort.
10. Name the three evaluation criteria of an algorithm. What is a trace table used for?

Section C — Long questions (attempt any 3 × 10 = 30)

1. Sort the list **5, 2, 7, 1, 6** in ascending order using Bubble Sort. Show every comparison of every pass in a table, and state the total number of comparisons and swaps. Then write the Python code for Bubble Sort.
2. Sort the list **6, 2, 9, 5, 1** in ascending order using Selection Sort (textbook method). Show every comparison of every pass and count the swaps. Also state why Selection Sort is called "blind" to an already sorted list.
3. The sorted list is **3, 8, 12, 17, 23, 31, 40, 52, 66** (Python indexes 0–8). Using Binary Search, show a low / mid / high table to search for (a) 40 and (b) 20. For each, state how many comparisons Linear Search would need.
4. Write the algorithm and pseudocode for Linear Search. Dry-run it on **8, 3, 6, 1, 7, 2, 4, 5** for FindValue = 2 and for FindValue = 9, and give two advantages and two disadvantages of Linear Search.
5. A school wants a program that reads the marks of 5 subjects for every student and prints each student's total, percentage and grade. Apply decomposition, pattern recognition and abstraction to this problem, and write a short algorithm.
6. A library has 50,000 book IDs stored in sorted order, and the librarian searches it hundreds of times a day. (a) Which search algorithm should be used and why? (b) What is the maximum number of comparisons for Linear and for Binary Search? (c) Explain the three evaluation criteria you would use to judge the chosen program.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

1. **2.1 & 2.2 Introduction to CT & Algorithms.** Answers: 1. Decomposition, pattern recognition, abstraction, algorithms. 2. Before coding (it is planning the solution). 3. Between human logic and machine code.
2. **2.2.2 Algorithm vs Pseudocode.** Answers: 1. Pseudocode. 2. Algorithm. 3. No; it is semi-formal and not executable.
3. **2.3.1 Algorithmic Strategy: Decomposition.** Answers: 1. A sub-task (sub-problem). 2. Example: list subjects and teachers; decide periods per subject per week; place periods in days so no teacher has two classes at once. 3. Reduces complexity, helps in debugging, promotes reusability.
4. **2.3.2 Algorithmic Strategy: Pattern Recognition.** Answers: 1. Loops. 2. 8 stars (Row N = N stars). 3. Term N = $2 \times N$ (each term adds 2).
5. **2.3.3 Algorithmic Strategy: Abstraction.** Answers: 1. Unnecessary details that do not affect the solution. 2. A variable (it changes with the situation). 3. Decomposition breaks a problem into parts; abstraction hides details that are not important.
6. **2.4.1 Sorting Algorithms: Bubble Sort.** Answers: 1. D, C, B, A. 2. It temporarily holds one value so that two values can be swapped without losing either.
7. **2.4.1 Sorting Algorithms: Selection Sort.** Answers: 1. At outer + 1 (PTR = K + 1). 2. Pos1 vs Pos2: $7 > 2$ swap $\rightarrow 2, 7, 5$; Pos1 vs Pos3: $2 > 5$ no $\rightarrow 2, 7, 5$. 3. Bubble Sort.
8. **2.4.2 Searching Algorithms: Linear Search.** Answers: 1. Sequential search. 2. 6 comparisons (2 is in position 6). 3. It is a flag: 0 means not found yet, 1 means found; it decides what to print after the loop.
9. **2.4.2 Searching Algorithms: Binary Search.** Answers: 1. The list must be sorted. 2. $\text{INT}(15/2) = 7$. 3. MID = 4 (value 4, go right, BEG = 5) $\rightarrow$ MID = $\text{INT}(13/2) = 6$ (value 6, go right, BEG = 7) $\rightarrow$ MID = $\text{INT}(15/2) = 7$ (value 7, go right, BEG = 8) $\rightarrow$ MID = 8 (value 8, found). Four comparisons.
10. **2.5 Evaluation Criteria of Algorithm.** Answers: 1. Correctness, efficiency, clarity. 2. The item is not in the list (or the list is empty, or the item is the last element). 3. Time (speed) and space (memory).
11. **2.6 How to Decide Which Algorithm to Use.** Answers: 1. Linear Search. 2. $O(\log N)$. 3. Selection Sort ($O(N^2)$ in both).

Answer key

Multiple choice

1. b
2. d
3. a
4. c
5. b
6. c
7. d
8. a
9. b
10. c
11. d
12. a
13. b
14. c
15. d

Short questions — model answers

1. Computational thinking is a systematic approach to solving problems. Its four components are decomposition (breaking down), pattern recognition (finding repetitions), abstraction (hiding unnecessary details) and algorithms (writing step-by-step solutions).
2. Algorithms (1) provide a structured approach that makes complex tasks manageable; (2) optimise time and memory usage, crucial for large applications; (3) can be reused for similar problems; (4) ensure accuracy and consistency, reducing human error; (5) act as a blueprint before coding. (Any four.)
3. (1) An algorithm is a step-by-step logical procedure; pseudocode is a human-readable representation of it using English and keywords. (2) An algorithm is conceptual and language-independent; pseudocode is semi-formal and structured but not executable. (3) An algorithm has no fixed format and is for anyone; pseudocode uses IF/FOR/WHILE, follows conventions and is mainly for programmers.
4. Decomposition is breaking a complex task into smaller, manageable parts. Learning a language is decomposed into: vocabulary (words like "I", "eat", "apple"), grammar rules (Subject → Verb → Object), tenses ("I eat" vs "I ate") and sentence building (combining words with rules).
5. Ask: What is repeating? What changes in a predictable way? Can I generalise this? For the star triangle: stars repeat in every row; each row has one more star than the previous; generalisation: Row $N = N$ stars, so one loop can print it.
6. Abstraction means hiding unnecessary features and focusing on the essential ones. Variables: type of tea (black, green, milk), additions (sugar, lemon), tool (stove or kettle) — any two. Noise: brand of kettle, cup colour or design, where tea is made — any two.
7. Sorting arranges a collection of items in ascending or descending order to organise data (e.g., Bubble Sort, Selection Sort). Searching locates a specific element in a list to find its position or whether it exists (e.g., Linear Search, Binary Search).
8. Binary Search decides to go left or right by comparing with the middle value; this decision is only valid if all smaller values are on the left and larger on the right, i.e., the list is sorted. Disadvantages: needs sorted data; needs random access (arrays, not linked lists); code is more complex and prone to off-by-one errors. (Any two.)
9. (1) Bubble Sort compares adjacent elements; Selection Sort compares a fixed position with all later elements. (2) Bubble Sort moves the largest to the end each pass; Selection Sort moves the smallest to the front. Also: Bubble Sort is stable, Selection Sort is not; Selection Sort makes fewer swaps.
10. Correctness, efficiency (time and space) and clarity (readability). A trace table records the values of variables step by step during a dry run, so we can check that the output matches the expected result and so prove correctness.

Long questions — model answers

1. Bubble Sort on 5, 2, 7, 1, 6

Pass	Pair	Left > Right?	List after
1	[5, 2]	Yes, swap	2, 5, 7, 1, 6
1	[5, 7]	No	2, 5, 7, 1, 6
1	[7, 1]	Yes, swap	2, 5, 1, 7, 6
1	[7, 6]	Yes, swap	2, 5, 1, 6, 7
2	[2, 5]	No	2, 5, 1, 6, 7
2	[5, 1]	Yes, swap	2, 1, 5, 6, 7
2	[5, 6]	No	2, 1, 5, 6, 7
3	[2, 1]	Yes, swap	1, 2, 5, 6, 7
3	[2, 5]	No	1, 2, 5, 6, 7
4	[1, 2]	No	1, 2, 5, 6, 7

Total comparisons = 4 + 3 + 2 + 1 = 10; total swaps = 3 + 1 + 1 + 0 = 5. Sorted list: 1, 2, 5, 6, 7.

```
data = [5, 2, 7, 1, 6]
n = len(data)
for outer in range(n - 1):
    for inner in range(n - 1 - outer):
        if data[inner] > data[inner + 1]:
            temp = data[inner]
            data[inner] = data[inner + 1]
            data[inner + 1] = temp
print(data)
```

OUTPUT

```
[1, 2, 5, 6, 7]
```

2. Selection Sort (textbook method) on 6, 2, 9, 5, 1

Pass	Compare	Values	Action	List after
1	Pos1 vs Pos2	6 > 2	Swap	2, 6, 9, 5, 1
1	Pos1 vs Pos3	2 > 9	No	2, 6, 9, 5, 1
1	Pos1 vs Pos4	2 > 5	No	2, 6, 9, 5, 1
1	Pos1 vs Pos5	2 > 1	Swap	1, 6, 9, 5, 2
2	Pos2 vs Pos3	6 > 9	No	1, 6, 9, 5, 2
2	Pos2 vs Pos4	6 > 5	Swap	1, 5, 9, 6, 2
2	Pos2 vs Pos5	5 > 2	Swap	1, 2, 9, 6, 5
3	Pos3 vs Pos4	9 > 6	Swap	1, 2, 6, 9, 5
3	Pos3 vs Pos5	6 > 5	Swap	1, 2, 5, 9, 6
4	Pos4 vs Pos5	9 > 6	Swap	1, 2, 5, 6, 9

10 comparisons, 7 swaps. Sorted list: 1, 2, 5, 6, 9. (With the classic one-swap-per-pass method the passes give 1, 2, 9, 5, 6 → 1, 2, 9, 5, 6 → 1, 2, 5, 9, 6 → 1, 2, 5, 6, 9.)

Selection Sort is "blind" to a sorted list because its loops have fixed limits: it always makes all $N(N-1)/2$ comparisons, even if the list is already in order. It has no way to notice that no swaps were needed and stop early.

3. (a) Search for 40

Step	low	high	mid	data[mid]	Compare	Action
1	0	8	$(0+8)//2 = 4$	23	$40 > 23$	low = 5
2	5	8	$(5+8)//2 = 6$	40	$40 = 40$	Found at index 6

Binary: 2 comparisons. Linear Search: 40 is the 7th item, so 7 comparisons.

(b) Search for 20

Step	low	high	mid	data[mid]	Compare	Action
1	0	8	4	23	$20 < 23$	high = 3
2	0	3	$(0+3)//2 = 1$	8	$20 > 8$	low = 2
3	2	3	$(2+3)//2 = 2$	12	$20 > 12$	low = 3
4	3	3	3	17	$20 > 17$	low = 4
—	4	3	low > high, so the loop stops: Not Found			

Binary: 4 comparisons. Linear Search must check all 9 items before saying "Not Found".

4. Algorithm and pseudocode: as in section 2.4.2 (Start; DATA, N, FindValue, ValueFound := 0; repeat for PTR = 1 to N: if DATA[PTR] = FindValue then ValueFound = 1 and exit; after the loop print DATA[PTR] if ValueFound = 1, else "Not Found"; End).

FindValue = 2:

Step	1	2	3	4	5	6
Element	8	3	6	1	7	2
= 2?	No	No	No	No	No	Yes — exit

Found at position 6 after 6 comparisons; ValueFound = 1; prints 2.

FindValue = 9: 8, 3, 6, 1, 7, 2, 4, 5 are all checked (8 comparisons), none equals 9, ValueFound stays 0, so "Data Not Found" is printed.

Advantages: works on sorted and unsorted data; very simple code; fast for small lists; no extra space. Disadvantages: up to N checks (1 million for 1 million items); time grows linearly; inefficient if the same list is searched thousands of times. (Any two of each.)

5. **Decomposition:** (1) input a student's 5 marks; (2) calculate total; (3) calculate percentage = total ÷ 500 × 100; (4) decide grade; (5) print result; (6) repeat for the next student.

Pattern recognition: the same steps repeat for every student, and the same "add a mark" step repeats for every subject — so use a loop over students and a loop over subjects.

Abstraction: keep only roll number, marks, total, percentage and grade; ignore noise such as the student's address, uniform or the colour of the result card. The number of students can be a variable.

Algorithm: Step 1: Start. Step 2: Read number of students S. Step 3: Repeat Steps 4–8 for each student. Step 4: TOTAL = 0. Step 5: Repeat 5 times: read MARK, TOTAL = TOTAL + MARK. Step 6: PER = TOTAL / 500 × 100. Step 7: If PER ≥ 80 grade "A1", else if PER ≥ 70 "A", else if PER ≥ 60 "B", else if PER ≥ 50 "C", else "Fail" (school's own grading scale). Step 8: Print TOTAL, PER, GRADE. Step 9: End.

6. (a) **Binary Search**, because the data is already sorted, it is large (50,000 items) and it is searched many times a day, so the time saved per search adds up; Linear Search would be far slower.

(b) Linear Search worst case: 50,000 comparisons. Binary Search worst case: 16 comparisons, because $2^{15} = 32,768 < 50,000 \leq 2^{16} = 65,536$, so 16 halvings are enough to reduce 50,000 items to one.

(c) **Correctness:** it must return the right position for IDs that exist, say "Not Found" for missing IDs (edge cases: first ID, last ID, missing ID), and always stop. **Efficiency:** time $O(\log N)$ and no extra memory ($O(1)$). **Clarity:** meaningful names like low, mid, high, clear steps and good indentation so another programmer can maintain it.

Self-assessment: I can...

- ☐ define computational thinking and name its four parts.
- ☐ draw a table comparing algorithm and pseudocode on at least five points.
- ☐ find a pattern in data and turn it into a loop.
- ☐ dry-run Bubble Sort pass by pass and count comparisons and swaps.
- ☐ trace Linear Search with a step table, including the "not found" case.
- ☐ state best and worst time complexity for all four algorithms.
- ☐ define an algorithm and give five reasons it is important.
- ☐ decompose a real-life problem into sub-tasks and explain three benefits.
- ☐ separate necessary steps, variables and noise using abstraction.
- ☐ dry-run Selection Sort pass by pass and explain why it is not stable.
- ☐ trace Binary Search with a BEG / MID / END table and explain why it needs sorted data.
- ☐ evaluate an algorithm for correctness, efficiency and clarity, and choose the right algorithm for a situation.

Lecture 03

Programming Fundamentals

Chapter lecture — 13 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XI · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — گیارہویں جماعت

13 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XI

How to use this BLEK study-guide lecture

Each PDF follows one textbook lecture from the BLEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیئریر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

Lectures in this pack

Chapter 3: Programming Fundamentals. Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 3.1 Programming & Language Types

L02. 3.2 Career Growth with Python

L03. 3.3 Integrated Development Environment (IDE) & VS Code

L04. 3.4 Fundamentals of Python Programming

L05. 3.4.1 Variables and Data Types

L06. 3.4.2 Input Output Handling

L07. 3.4.3 Operators and Operands (Arithmetic, Relational, Bitwise)

L08. 3.5 Control Structures Overview

L09. 3.5.1 Sequence

L10. 3.5.2 Selection Statements (if, if-else, if-elif-else, nested)

L11. 3.5.3 Repetition Statements (for loop, while loop)

L12. 3.6 Libraries in Python (Built-in & Third-Party)

L13. 3.7 Debugging Code in Python

Programming Fundamentals

In this chapter you start writing real programs in Python. You will learn how programs store data, take input, make decisions, repeat work, use ready-made libraries, and how to find and fix your own mistakes.

اس باب میں آپ پائتھن (Python) میں حقیقی پروگرام لکھنا سیکھیں گے۔ آپ جانیں گے کہ پروگرام ڈیٹا کیسے محفوظ کرتا ہے، فیصلے کیسے کرتا ہے، کام کو کیسے دہراتا ہے، اور غلطیاں کیسے تلاش کی جاتی ہیں۔

What you will learn

- Define a program and a programming language, and compare low-, mid- and high-level languages.
- Describe the features of an IDE and the main parts of the VS Code window.
- Take input with `input()`, convert it with `int()` / `float()`, and display output with `print()` and f-strings.
- Use sequence, selection (`if`, `if-else`, `if-elif-else`, nested `if`) and repetition (`for`, `while`, `range()`, `break`, `continue`, nested loops).
- Identify syntax, runtime and logical errors and read a traceback to fix a bug.
- Name career areas where Python is used.
- Write Python programs that use comments, correct indentation, valid variable names and the main data types.
- Evaluate expressions with arithmetic, assignment, relational, logical, membership and bitwise operators, including binary working.
- Import and use built-in libraries (`math`, `random`, `datetime`) and install third-party libraries with `pip`.

3.1 Programming & Language Types

LEARN IT

Computers are "dumb" machines. They are very fast, but they cannot think or do anything on their own. They need exact, step-by-step **instructions**.

- A set of instructions given to a computer is called a **program**.
- The language used to write these instructions is called a **programming language**.
- Writing programs is called **programming**, and the person who writes them is a **programmer**.

Think of a recipe. A cook follows the recipe line by line: "boil water, add rice, wait 15 minutes". A computer follows a program in the same way, one instruction at a time, without guessing what you meant.

WORKED EXAMPLE

A tiny program. Here is a complete Python program with one instruction. It tells the computer to show a message on the screen.

```
print("Hello")
```

OUTPUT
Hello

The word `print` is the instruction; `"Hello"` is the data it works on.

REMEMBER IT

Program = recipe, programmer = recipe writer, computer = cook who follows every line exactly. If the recipe is wrong, the food is wrong. The cook does not fix it for you.

COMMON MISTAKE

Students often think the computer "understands" what they want. It does not. If you type `Print("Hello")` with a capital P, Python stops with an error, because it only knows `print`. Be exact.

اردو میں سمجھیں

کمپیوٹر خود سے کچھ نہیں سوچ سکتا۔ اسے کام کرنے کے لیے ہدایات چاہئیں۔ ہدایات کے مجموعے کو پروگرام (Program) کہتے ہیں، اور جس زبان میں یہ ہدایات لکھی جاتی ہیں اسے پروگرامنگ لینگویج (Programming Language) کہتے ہیں۔

CHECK YOURSELF

1. What is a program?
2. Why do we say computers are "dumb" machines?


Answers: 1. A set of instructions given to a computer to perform a task. 2. Because they cannot think or do anything without instructions; they only follow exactly what they are told.

LEARN IT

Programming languages are classified into **three main types**, depending on how close they are to the computer's own language (binary 0s and 1s) or to human language.

Type	Description	Examples
Low level	Closest to the native language of the computer (binary 0s and 1s). Very difficult for humans to read and write.	Machine language (binary)

Mid level	Bridges the gap. It can access hardware but is easier to read than binary because it uses short words called mnemonics (e.g. <code>MOV</code> , <code>ADD</code>).	Assembly language
High level	Designed to be easy for humans to read and write. Uses English-like words.	C++, Java, Python



The three levels of programming languages, with a sample line from each.

Common high-level languages

Language	Key idea	Used for
C++	Powerful and closer to hardware.	System software, operating systems, high-performance computer games.
Java	"Write once, run anywhere."	Large enterprise applications, Android mobile apps, server programming.
Python	Simple, readable syntax.	Data Science, Artificial Intelligence, Web Development, and learning to program.

WORKED EXAMPLE

Same task, three levels. Suppose you want to copy a value.

- Machine language: a pattern like `01010101` — you would need a chart to know what it means.
- Assembly: `MOV AX, BX` — "move the value in register BX into register AX". Shorter words, but you still need to know the hardware.
- Python: `a = b` — you simply say "a gets the value of b".

The higher the level, the less you need to know about the hardware and the faster you can write the program.

REMEMBER IT

"Low = Like the machine, High = Human." Mid level sits in the Middle and uses Mnemonics (both start with M).

COMMON MISTAKE

"Low level" does not mean "bad" or "weak". Low-level code runs very fast and controls hardware directly. It is just harder for humans to write.

اردو میں سمجھیں

پروگرامنگ زبانوں کی تین اقسام ہیں: لو لیول (Low Level) جو بائری 0 اور 1 میں ہوتی ہے، مڈ لیول (Mid Level) یعنی اسمبلی جو مختصر الفاظ (Mnemonics) استعمال کرتی ہے، اور ہائی لیول (High Level) جیسے پائتھن، جاوا اور سی پلس پلس جو انگریزی جیسے الفاظ استعمال کرتی ہیں اور انسانوں کے لیے آسان ہیں۔

CHECK YOURSELF

1. Which level is MOV AX, BX ?
2. Which high-level language is famous for "write once, run anywhere"?
3. Give one use of C++.

Answers: 1. Mid level (assembly language). 2. Java. 3. Any one: system software, operating systems, high-performance games.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A program is:

- a. A set of instructions
- b. A mouse
- c. A cable
- d. A pie

MCQ 2. High-level languages are:

- a. Closer to English (Python, C++)
- b. Only 0 and 1
- c. Only analog
- d. Only SQL

MCQ 3. Machine language is:

- a. Binary codes for the CPU
- b. Python
- c. Urdu
- d. HTML always

MCQ 4. C++ is typically:

- a. High-level, closer to hardware than Python
- b. A DBMS
- c. A chart
- d. An OSI layer

MCQ 5. Python is popular in XI because:

- a. Simple syntax, huge libraries
- b. It is binary only
- c. It cannot print
- d. It is analog

MCQ 6. The translator of Python is a:

- a. Interpreter (also compiles to bytecode)
- b. Router
- c. Switch
- d. K-map

Extra short questions

1. Define program and programming language.
2. Differentiate high-level and low-level.
3. Name three high-level languages and one use each.
4. Why are computers "dumb" without programs?

Extra long question

1. Compare machine, assembly and high-level languages in a table (readability, speed, portability, example). Link why this course uses Python.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Program: instructions for a computer. Language: the notation used to write them.

2. High-level: English-like, portable. Low-level: close to hardware, faster but harder.
3. Python data/scripts; C++ systems/games; Java apps — (accept similar).
4. They only follow instructions; they do not understand the problem.

Long

1. Machine 0/1 fastest least portable; assembly mnemonics; high-level portable. Python: readable, batteries included, matches the Sindh practicals.

3.2 Career Growth with Python

LEARN IT

Python is one of the most in-demand languages in the world. Learning it opens many career paths:

- **Software Development:** build desktop and web applications.
- **Data Science and Data Analysis:** analyse data, create reports and make predictions.
- **Artificial Intelligence and Machine Learning:** develop intelligent systems, chatbots and recommendation algorithms (like "videos you may like").
- **Web Development:** use frameworks such as **Django** and **Flask** to build websites.
- **Automation and Scripting:** automate repetitive office or lab tasks (renaming 500 files, filling spreadsheets).
- **Cybersecurity and Networking:** write security tools and analyse network data.

Why Python? Python lets you focus on **problem-solving and logic** instead of memorising complex syntax rules.

Compare printing a message in Python with C++:

```
# Python
print("Hello")
```

```
// C++
#include <iostream>
int main() {
    std::cout << "Hello";
    return 0;
}
```

WORKED EXAMPLE

Automation example. A school clerk must write "Roll No. 1" to "Roll No. 5" on a list. Python does it in two lines:

```
for n in range(1, 6):
    print("Roll No.", n)
```

OUTPUT

```
Roll No. 1
Roll No. 2
Roll No. 3
Roll No. 4
Roll No. 5
```

Change 6 to 501 and it writes 500 lines just as fast. (You will learn loops in 3.5.3.)

REMEMBER IT

Six careers — remember **"S-D-A-W-A-C"**: **S**oftware, **D**ata, **A**I, **W**eb, **A**utomation, **C**ybersecurity.

COMMON MISTAKE

Django and Flask are **web frameworks** (for websites), not AI tools. AI/ML uses libraries such as TensorFlow and PyTorch (see 3.6.2).

اردو میں سمجھیں

پائتھن سیکھ کر آپ سافٹ ویئر ڈیولپمنٹ، ڈیٹا سائنس، مصنوعی ذہانت (AI)، ویب ڈیولپمنٹ، آٹومیشن اور سائبر سیکیورٹی جیسے شعبوں میں کیریئر بنا سکتے ہیں۔ پائتھن کا آسان انداز آپ کو مشکل اصول یاد کرنے کے بجائے مسئلہ حل کرنے پر توجہ دینے دیتا ہے۔

CHECK YOURSELF

1. Name two Python web frameworks.
2. Which career area builds chatbots and recommendation systems?

Answers: 1. Django and Flask. 2. Artificial Intelligence and Machine Learning.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Python careers include:

- a. Data analyst, web, automation, AI
- b. Only plumber
- c. Only analog technician
- d. Only OS kernel in 1950

MCQ 2. Python is used in AI because:

- a. Libraries like TensorFlow/Pandas exist
- b. It is binary only
- c. It cannot loop
- d. It has no syntax

MCQ 3. A scripting job often means:

- a. Automating repetitive tasks with Python
- b. Soldering NAND
- c. Drawing OSI only
- d. Figma only

MCQ 4. Learning Python in XI helps later with:

- a. XII data analysis and file handling
- b. Cooking only
- c. Cabling only
- d. Waterfall contracts only

MCQ 5. Syntax of Python is:

- a. Clear and beginner-friendly
- b. Harder than machine code
- c. Only umlauts
- d. Mandatory semicolons always

MCQ 6. Open-source means:

- a. The language/tools are free to use and inspect
- b. You must pay per loop
- c. Closed NAND
- d. Secret OSI

Extra short questions

1. Give four career paths that use Python.
2. Why do employers like Python?
3. What should an XI student build as proof?
4. Is Python the only language you will ever need?

Extra long question

1. Write a 10-mark "career connection" answer: three jobs, the Python skill each needs from this chapter, and one ethical warning.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Developer, data analyst, automation/scripting, AI/ML, teaching, testing.
2. Fast to write, huge ecosystem, readable by teams.
3. Small projects: bill calculator, file grader, attendance list.

4. No — but it is a strong first language and used in this syllabus.

Long

1. Analyst: data types+libraries. Developer: control structures. Automation: files later in XII. Ethics: do not scrape private student data without permission.

3.3 Integrated Development Environment (IDE) & VS Code

LEARN IT

An **IDE (Integrated Development Environment)** is a software tool that helps programmers **write, run and manage code in one place**. It is a complete workspace for programming. "Integrated" means many tools are joined together in one window.

Key features of an IDE:

- **Code Editor:** where you write and edit code.
- **Syntax Highlighting:** colours different parts of the code (keywords, strings, numbers) to make it easier to read.
- **Auto-completion:** suggests code while you type (type `pri` and it offers `print`).
- **Run/Execute Tool:** runs the program with one click.
- **Debugger:** helps you find and fix errors, for example by pausing the program at a chosen line.

WORKED EXAMPLE

Without vs with an IDE. Without an IDE you would write code in Notepad, save it, open a terminal and type `python file.py`, then go back to Notepad to fix mistakes. With an IDE you write, run (press the ► Run button) and debug in the same window, and errors are underlined while you type.

REMEMBER IT

IDE features — **"E-S-A-R-D"**: Editor, Syntax highlighting, Auto-completion, Run, Debugger.

COMMON MISTAKE

An IDE does not write the program for you and does not catch logical mistakes. It only makes writing, running and debugging easier.

اردو میں سمجھیں

آئی ڈی ای (IDE) ایک ایسا سافٹ ویئر ہے جس میں کوڈ لکھنا، چلانا اور غلطیاں درست کرنا ایک ہی جگہ ممکن ہوتا ہے۔ اس کی اہم خصوصیات میں کوڈ ایڈیٹر، رنگین کوڈ (Syntax Highlighting)، خودکار تجاویز (Auto completion)، رن بٹن اور ڈیبیگر شامل ہیں۔

CHECK YOURSELF

1. What does "integrated" mean in IDE?
2. Which IDE feature suggests code while you type?

Answers: 1. Many programming tools (editor, runner, debugger) are combined in one program. 2. Auto-completion.

LEARN IT

VS Code is a **free, lightweight and powerful code editor** made by Microsoft and widely used for Python. By default it is **not a full IDE**, but it becomes one when you install **extensions** (add-ons), such as the **Python extension by Microsoft**.

VS Code interface elements

Element	Description
1. Top Menu Bar	Control over files, editing, navigation and workspace (File, Edit, Selection, View, Go, Run).
2. Side Bar	Contains the core tools: Explorer, Search, Source Control, Run & Debug and Extensions.

3. Explorer	Shows project files and folders. Helps you create, open and manage your Python files.
4. Search	Finds and replaces text in the open file or across the whole project.
5. Source Control	Connects with Git (a version control system) to track changes, undo mistakes and collaborate.
6. Run & Debug	Runs code, finds errors, pauses at specific lines and lets you inspect variables.
7. Extensions	Like an App Store for VS Code. Add features such as the Python extension, Prettier or Python Debugger.



A simplified VS Code window: menu bar, side bar, Explorer and the code editor.

WORKED EXAMPLE

Setting up and running your first program in VS Code:



```
print("Hello, World!")
```

OUTPUT

```
Hello, World!
```

The output appears in the **Terminal** panel at the bottom of the window.

REMEMBER IT

Extensions are the **"App Store"** of VS Code: just as apps give your phone new abilities, extensions give VS Code new abilities.

COMMON MISTAKE

Always save Python files with the `.py` extension (e.g. `hello.py`). Without it, VS Code does not know the file is Python, so there is no syntax highlighting and no Run button.

اردو میں سمجھیں

وی ایس کوڈ (VS Code) ایک مفت اور ہلکا پھلکا کوڈ ایڈیٹر ہے۔ یہ اپنے آپ میں مکمل آئی ڈی ای نہیں، لیکن ایکسٹینشنز (Extensions) لگانے سے آئی ڈی ای بن جاتا ہے۔ اس کے اہم حصے مینو بار، سائیڈ بار، ایکسپلورر، سرچ، سورس کنٹرول، رن اینڈ ڈیبگ اور ایکسٹینشنز ہیں۔

CHECK YOURSELF

1. Which VS Code element connects to Git?
2. Is VS Code a full IDE by default? How does it become one?
3. Where do you see and manage your project's files?

Answers: 1. Source Control. 2. No; it becomes an IDE by installing extensions (e.g. the Python extension). 3. Explorer.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An IDE is:

- a. One app to write, run and debug code
- b. A printer
- c. A sort
- d. A cable

MCQ 2. VS Code is:

- a. A popular editor/IDE
- b. A DBMS
- c. An OSI layer
- d. A gate

MCQ 3. The terminal/run button is for:

- a. Executing the program
- b. Drawing pie charts only
- c. Sending TCP SYN only
- d. K-maps

MCQ 4. Syntax highlighting helps you:

- a. See keywords and mistakes
- b. Sort faster
- c. Encrypt disks
- d. Route packets

MCQ 5. A file explorer in VS Code shows:

- a. Project files
- b. OSI layer 1
- c. NAND groups
- d. Beachhead users

MCQ 6. Debugging in an IDE uses:

- a. Breakpoints and variable watch
- b. Only bubble sort
- c. Only pie charts
- d. Only Agile stickers

Extra short questions

1. Define IDE.
2. Name four VS Code areas.
3. Why not use Notepad only?
4. What is an extension?

Extra long question

1. Describe how you would create, run and debug a first Python file in VS Code. Include two interface elements from the notes.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Integrated Development Environment: editor + run + debug + files in one place.

2. Activity bar/sidebar (files), editor, terminal, status bar (and extensions).
3. No easy run, no highlighting, no debugger.
4. An add-on (Python plugin) that teaches VS Code a language.

Long

1. New file .py, type print, Run Python, read terminal. Mention top menu, explorer, terminal panel.
Breakpoint on a wrong variable.

3.4 Fundamentals of Python Programming ★ Golden

LEARN IT

The basic structure of a Python program is simple and clear. A program takes data, **processes it using statements**, and finally **shows output**. Python runs the statements **top to bottom, one after another** (sequentially).

A **statement** is one complete instruction, usually written on one line, such as `print("Hi")` or `x = 5`.

- 1. Comments (#)** — Comments are notes written in the code **for humans**. They start with the `#` symbol. The Python interpreter completely **ignores** them. Use them to explain what your code does.
- 2. Indentation (spaces)** — C++ and Java use curly brackets `{ }` to mark a **block** of code (a group of statements that belong together). Python instead uses **indentation**: spaces at the beginning of a line. Indentation is **mandatory** in Python. The standard is **4 spaces** (or 1 tab).

```
# This is a comment. It explains the code below.
print("Hello, World!")
if 5 > 2:
    # The space before 'print' is the indentation
    print("Five is greater than two!")
```

OUTPUT

```
Hello, World!
Five is greater than two!
```

WORKED EXAMPLE

Reading the program line by line:

1. Line 1 starts with `#`, so Python skips it.
2. Line 2 prints `Hello, World!`.
3. Line 3 asks a question: is 5 greater than 2? The colon `:` says "a block follows".
4. Line 4 is a comment inside the block (ignored).
5. Line 5 is indented by 4 spaces, so it belongs to the `if` block. Because `5 > 2` is true, it runs.

What happens if you forget the indentation?

```
if 5 > 2:
print("Five is greater than two!")
```

OUTPUT

```
File "indent.py", line 2
    print("Five is greater than two!")
    ^
IndentationError: expected an indented block after 'if' statement on line 1
```

Python refuses to run the program and points to line 2. Add 4 spaces before `print` to fix it.

REMEMBER IT

Think of indentation like the points and sub-points in your notebook. Sub-points are written a little to the right to show they "belong" to the main point. A colon `:` at the end of a line always means "**indent the next line**".

COMMON MISTAKE

IndentationError? Check your spaces. **Mixing tabs and spaces** can break a Python program even when the code looks lined up. Choose 4 spaces and use them everywhere (VS Code inserts 4 spaces when you press Tab in a `.py` file).

پائتھن پروگرام اوپر سے نیچے ترتیب سے چلتا ہے۔ # سے شروع ہونے والی لائن تبصرہ (Comment) ہوتی ہے جسے پائتھن نظر انداز کر دیتا ہے۔ پائتھن میں کوڈ کے بلاک کو بریکٹ کے بجائے انڈینٹیشن (Indentation) یعنی لائن کے شروع میں چار خالی جگہوں سے ظاہر کیا جاتا ہے، اور یہ لازمی ہے۔

EXAM TIP

Common questions: "What is the purpose of comments?", "Why is indentation important in Python?", "How is Python different from C++/Java in defining blocks?" Write: comments start with # and are ignored by the interpreter; Python uses indentation (4 spaces) instead of { } ; wrong indentation gives an IndentationError . Always give a 3-4 line code example.

CHECK YOURSELF

1. Predict the output:

```
# print("A")
print("B")
if 3 > 7:
    print("C")
print("D")
```

2. What is the standard amount of indentation in Python?

Answers: 1. B then D on separate lines (line 1 is a comment; 3 > 7 is false so C is skipped). 2. 4 spaces (or 1 tab).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Python runs statements:

- a. From top to bottom (unless control changes that)
- b. Randomly
- c. Only backwards
- d. Only on even lines

MCQ 2. A statement is:

- a. One instruction
- b. A mouse
- c. A layer
- d. A sprint

MCQ 3. Comments start with:

- a. #
- b. // always only
- c.

Lecture 04

Data and Analysis

Chapter lecture — 15 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XI · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — گیارہویں جماعت

15 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XI

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیئریر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

Lectures in this pack

Chapter 4: Data and Analysis. Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 4.1.1 Data, Information and Database

L02. 4.1.2 Database Management System (DBMS)

L03. 4.2 Database Components (Tables, Records, Fields)

L04. 4.3.1 Keys and Integrity Constraints

L05. 4.3 Relational Database Management System (RDBMS)

L06. 4.4 Entity Relationship Model (ER-Model)

L07. 4.5 Referential Integrity (Cascade Update & Delete)

L08. 4.6 Relational Schema Development

L09. 4.7 Case Study — Library Management System

L10. 4.8 Different Database Objects (Tables, Forms, Queries, Reports)

L11. 4.9 Creation of Tables in Microsoft Access

L12. 4.10 Designing Forms for Data Manipulation

L13. 4.11 Creating Queries in MS Access

L14. 4.11.4 Data Summarization & Statistical Analysis

L15. 4.11.6 Data Visualization in MS Access (Charts)

Data and Analysis

This chapter teaches you how raw facts become organised information in a database, how tables are linked with keys, how to draw an ER diagram, and how to build tables, forms, queries and charts in Microsoft Access. Banks, NADRA, college libraries and fee offices all run on these ideas.

اس باب میں آپ سیکھیں گے کہ خام حقائق کو ڈیٹا بیس میں کیسے منظم کیا جاتا ہے، ٹیبلز کو کیز سے کیسے جوڑا جاتا ہے، ای آر خاکہ کیسے بنتا ہے، اور مائیکروسافٹ ایکسیس میں ٹیبل، فارم، کوئری اور چارٹ کیسے بنائے جاتے ہیں۔

What you will learn

- Distinguish data, information and a database, and explain what a DBMS does.
- Choose candidate, primary, alternate and foreign keys and state integrity rules.
- Explain referential integrity, Cascade Update and Cascade Delete with before/after tables.
- Develop the college-library case study from requirements to the final ER schema.
- Create tables in Access (Datasheet and Design view) and pick data types.
- Identify tables, records and fields in a given example.
- Draw ER diagrams (entities, attributes, relationships) and give cardinality 1:1, 1:M, M:N.
- Write a relational schema and resolve an M:N relationship with a junction table.
- State the job of tables, forms, queries and reports.
- Build a form with the Form Wizard and a SELECT query with criteria, AND/OR, totals and charts.

4.1.1 Data, Information and Database

LEARN IT

Data are unprocessed facts, figures or observations. They can be **quantitative** (numbers: 80, 75, 90) or **qualitative** (descriptions: the colours of cars in a parking lot). Data on its own is not very useful — a list of marks does not yet tell you whether the class is strong.

When you organise, process and interpret data, it becomes **information**. Information has meaning and supports a decision. Example: "The class average is 80%, so we can move to the next chapter."

A **database** is an organised collection of **related** data, stored in a structured way so it can be accessed, managed and updated easily. Paper registers and loose files make searching painful; a database is built for search, update and sharing.



Aspect	Data	Information
Definition	Raw facts and figures	Processed, meaningful data
Example	85, 90, 75	Average marks = 83.3%
Usefulness	Little, on its own	Useful for decisions

WORKED EXAMPLE

Five CS XI marks: 80, 75, 90, 70, 85. Sum = 400. Average = $400 \div 5 = 80\%$. The numbers are data; "the class average is 80%" is information; a **Student** table holding every student's marks is a database.

REMEMBER IT

Exam line: *Data is raw; information is processed data used for decision-making.* Always add one pair of examples.

COMMON MISTAKE

Do not call a jumble of WhatsApp numbers a database. Related + structured + easy to update is what makes it a database.

اردو میں سمجھیں

ڈیٹا خام حقائق ہیں، معلومات وہی حقائق ہیں جب انہیں ترتیب دے کر معنی دے دیا جائے۔ ڈیٹا بیس متعلقہ ڈیٹا کا منظم ذخیرہ ہے جسے آسانی سے تلاش اور تبدیل کیا جا سکتا ہے۔

CHECK YOURSELF

1. Is "Nadia, Class 11, 72 marks" data or information?

2. Why is a stack of unmarked answer sheets not a database?

Answers: 1. Data (raw facts about one student). 2. It is not organised in a structured, searchable, updatable collection of related records.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Data is:

- a. Raw unprocessed facts
- b. Always information
- c. Always a graph
- d. A program

MCQ 2. Information is:

- a. Processed, meaningful data
- b. Noise only
- c. A cable
- d. A gate

MCQ 3. A database is:

- a. An organised collection of related data
- b. A single unsorted scrap
- c. A CPU fan
- d. A pie chart

MCQ 4. Marks 45, 67, 12 are:

- a. Data
- b. Information already
- c. A query
- d. A report

MCQ 5. "Ali failed" after processing marks is:

- a. Information
- b. Raw data only
- c. A primary key
- d. A form

MCQ 6. Storing related tables together is the job of a:

- a. Database
- b. Compiler
- c. Router
- d. K-map

Extra short questions

- Differentiate data and information with a school example.
- Define database.
- Give two problems of storing data only in paper lists.
- Is a phone contacts app a database?

Extra long question

- A college keeps loose pages of marks. Argue, with definitions, why they should move to a database, and what information a principal could then get.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Data: 45, 67. Information: class average is 56 so we need extra classes.
- Organised related data stored so it can be retrieved quickly.
- Slow search, duplication, hard updates, errors.
- Yes — organised related records (name, number).

Long

- Define data/information/database. Benefits: search, consistency, reports (fail list, subject averages). One risk: need backup/access control.

4.1.2 Database Management System (DBMS)

LEARN IT

A **DBMS** is software that lets you create, manage and interact with databases. It sits between the user and the stored files. You never edit raw data files by hand — you talk to the DBMS (Access, MySQL, Oracle, SQLite) and it handles storage, security and consistency.

Advantages you must be able to list:

- **Less redundancy.** The department name is stored once, not in every student row.
- **Consistency.** Change a phone number once; every screen that uses it shows the new number.
- **Security.** Only authorised users see sensitive fields (an admin sees marks; office staff see names).
- **Integrity.** Rules stop duplicate roll numbers and empty primary keys.

WORKED EXAMPLE

In a paper register, Ali's address is written on the admission page, the fee page and the sports page. If he moves house, two of the three pages stay wrong. In a DBMS, Address lives in one **Student** table. Every form and report reads that single field.

اردو میں سمجھیں

ڈی بی ایم ایس وہ سافٹ ویئر ہے جو صارف اور ڈیٹا بیس کے درمیان پل کا کام کرتا ہے۔ اس سے تکرار کم ہوتی ہے، ڈیٹا ایک جیسا رہتا ہے، صرف مجاز افراد دیکھ سکتے ہیں، اور غلط اندراج رک جاتی ہے۔

CHECK YOURSELF

1. Name two DBMS programs.
2. Which advantage stops two students sharing the same roll number?

Answers: 1. MS Access, MySQL (Oracle, SQLite also). 2. Integrity (unique / primary-key constraint).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A DBMS is software that:

- a. Creates and manages databases
- b. Draws only pie charts
- c. Routes IP
- d. Sorts using bubble only

MCQ 2. Examples of DBMS:

- a. MS Access, MySQL, SQLite, Oracle
- b. Python only
- c. Figma only
- d. Chrome only

MCQ 3. DBMS handles:

- a. Storage, retrieval, security, multi-user access
- b. Only fonts
- c. Only OSI layer 1
- d. Only NAND

MCQ 4. Without a DBMS, programs would:

- a. Each invent their own file format
- b. Run faster always
- c. Need no keys
- d. Need no SQL

MCQ 5. Access is used in XI because:

- a. It is a GUI DBMS for tables/forms/queries/reports
- b. It is a programming language
- c. It is Agile
- d. It is analog

MCQ 6. SQLite in XII is a:

- a. Lightweight DBMS/library
- b. Chart
- c. Gate
- d. Sprint

Extra short questions

1. Define DBMS.
2. Four DBMS functions.
3. DBMS vs database.
4. Name two desktop and two server DBMS.

Extra long question

1. Compare managing 500 students in Excel vs a DBMS (Access). Use data integrity, search, multi-user and reports.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Database Management System: software to define, store, query, protect and share a database.
2. Create tables, insert/update/delete, query, enforce keys/security, backup.
3. Database is the data; DBMS is the software that manages it.
4. Desktop: Access, SQLite. Server: MySQL, Oracle, PostgreSQL.

Long

1. Excel: easy but duplicates, weak keys, clash when two people edit. DBMS: primary keys, queries, forms, reports, controlled access.

4.2 Database Components (Tables, Records, Fields)

LEARN IT

The basic structure is a **table** (also called a relation): rows and columns, like a spreadsheet, holding facts about one kind of thing (Students, Teachers, Books).

A **record** (row, tuple) is one complete instance — everything about Ali. A **field** (column, attribute) is one kind of fact — the whole Name column, or the whole Grade column.

Roll No	Name	Course	Grade
101	Ali	CS	A
102	Sara	IT	B+
103	Ahmed	CS	A

The row 101 | Ali | CS | A is one **record**. The Name column is one **field**.

REMEMBER IT

Memory: **row = record = one person. column = field = one question on the admission form.**

COMMON MISTAKE

Do not mix two entities in one table (students and library books together). Each entity gets its own table; keys will link them later.

اردو میں سمجھیں

ٹیبل قطاروں اور کالموں میں ڈیٹا رکھتا ہے۔ ایک قطار ایک ریکارڈ (مثلاً علی کی پوری معلومات) ہے، ایک کالم ایک فیلڈ (مثلاً صرف نام) ہے۔

CHECK YOURSELF

- How many records and how many fields are in the table above?
- Is "CS" a record or a field value?

Answers: 1. 3 records, 4 fields. 2. A value stored in the Course field.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A table is:

- Rows and columns of one entity type
- A Python for-loop
- A cable
- A sprint

MCQ 2. A record is:

- One row
- One column
- The DBMS name
- A query

MCQ 3. A field/attribute is:

- One column
- The whole database
- A report
- A form

MCQ 4. A value in one cell is:

- A data item
- A relationship
- A schema
- A view

MCQ 5. Students table columns might be:

- id, name, class
- AND, OR, NOT
- HTTP, TCP
- Mean, π

MCQ 6. Many records share the same:

- Fields (structure)
- Primary key value
- OSI layer
- Random NAND

Extra short questions

- Define table, record, field.
- Give a 3-field student record example.
- What is a data type of a field?
- Why not put two entities in one messy table?

Extra long question

- Design a Marks table: fields, types, one sample record, and which field will likely become the primary key.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Table: entity set. Record: one instance. Field: one property.
- 101 | Ali | 85
- The kind of value: Number, Text, Date, Yes/No.
- Duplication and update anomalies — later ER/normalisation.

Long

- roll (Number, PK), name (Text), subject (Text), marks (Number). Sample 12, Ali, CS, 85. Justify uniqueness of roll or roll+subject.

4.3.1 Keys and Integrity Constraints ★ Golden

LEARN IT

A **key** is a field (or a set of fields) that uniquely identifies records and links tables. Integrity constraints are the rules that keep those keys honest.

Candidate key. Any field (or combination) that *could* uniquely identify a row. A table may have several. In an Employee table: EmpID, EmpLicense# and EmpPassport are all candidate keys.

Primary key (PK). The one candidate you actually choose. Rules: unique, never NULL, only one PK per table (it may be a **composite** of two columns). Example: EmpID.

Alternate key. The leftover candidate keys. After EmpID is chosen, EmpLicense# and EmpPassport become alternate keys — still unique, just not "the" identifier.

Foreign key (FK). A field in this table that refers to the PK of another table. It *may* contain duplicates (many employees in one department) and, in some designs, NULL.

WORKED EXAMPLE

Classroom analogy. Roll Number, B-Form number and phone number can all identify a student (candidate keys). The school picks Roll Number as the primary key. B-Form and phone become alternate keys. In a **Result** table, RollNo is a foreign key pointing back to Student.

Table	Field	Role
Student	RollNo	Primary key
Student	BFormNo	Alternate key
Result	RollNo	Foreign key → Student.RollNo
Result	ExamID + RollNo	Could be a composite primary key

EXAM TIP

Board questions: "Differentiate primary and foreign key" (table of 4 points) and "Why can a PK not be NULL?" Because a NULL would mean "this row has no identity", so the DBMS could not tell rows apart.

COMMON MISTAKE

A phone number is a bad PK: people change numbers, two siblings may share one, and some students have none (NULL). Roll numbers are issued by the school and stay unique.

اردو میں سمجھیں

کینڈیڈٹ کی وہ فیلڈ ہے جو ریکارڈ کی شناخت کر سکے۔ پرائمری کی منتخب شدہ شناخت ہے — منفرد اور خالی نہیں۔ جو بچ جائیں وہ آئرنٹیٹ کیڑ ہیں۔ فارن کی دوسرے ٹیبل کی پرائمری کی طرف اشارہ کرتی ہے اور ٹیبلز کو جوڑتی ہے۔

CHECK YOURSELF

1. Can a table have two primary keys?

2. Can a foreign key have duplicate values?

Answers: 1. No — only one PK (it may be composite). 2. Yes — many child rows may point to the same parent.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A primary key:

- a. Uniquely identifies each record
- b. May freely repeat
- c. Is always a name
- d. Is a chart

MCQ 2. A candidate key is:

- a. Any field set that could be the PK
- b. A foreign key
- c. A report
- d. A form

MCQ 3. An alternate key is:

- a. A candidate not chosen as PK
- b. A duplicate PK
- c. A null PK
- d. A pie

MCQ 4. A foreign key:

- a. Refers to a PK in another table
- b. Is always unique in its table
- c. Sorts the table
- d. Encrypts the DB

MCQ 5. NULL in a primary key is:

- a. Not allowed
- b. Required
- c. A default
- d. A relationship type

MCQ 6. Integrity constraints exist to:

- a. Stop invalid data
- b. Draw graphs
- c. Route packets
- d. Compile Python

Extra short questions

- Define PK, FK, candidate, alternate.
- Give a two-table example with an FK.
- Entity integrity rule.
- Why not use student name as PK?

Extra long question

- For Members and Borrow in a library, choose keys and write two integrity rules. Show one invalid insert the DBMS should reject. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- PK: chosen unique identifier. Candidate: any unique identifier. Alternate: unused candidate. FK: copy of another table's PK.
- Students(roll PK); Marks(roll FK, subject, score).
- PK unique and not NULL.
- Names duplicate and change.

Long

- MemberID PK; Borrow(BorrowID PK, MemberID FK). Reject Borrow with unknown MemberID or NULL MemberID. Mention cascade later.

4.3 Relational Database Management System (RDBMS)

LEARN IT

An **RDBMS** stores data in several tables and uses primary and foreign keys to keep relationships. Banks, universities and NADRA use RDBMS software. Extra strengths on top of a plain DBMS:

- Reduces redundancy by splitting data into related tables.
- Supports many users at once, with permissions.
- Is queried with **SQL** (Structured Query Language) — a standard language of SELECT, INSERT, UPDATE, DELETE.

WORKED EXAMPLE

Instead of one giant spreadsheet of students-and-departments, an RDBMS has Department(DeptID, DeptName) and Student(RollNo, Name, DeptID FK). CS is stored once. SQL: SELECT Name FROM Student WHERE DeptID = 1;

اردو میں سمجھیں

آر ڈی بی ایم ایس کئی ٹیبلز میں ڈیٹا رکھتا ہے اور کیڑ سے ان کے تعلقات برقرار رکھتا ہے۔ ایس کیو ایل سے سوال پوچھے جاتے ہیں۔ اس سے تکرار کم اور کئی صارفین محفوظ طریقے سے کام کر سکتے ہیں۔

CHECK YOURSELF

1. What language do you use to query an RDBMS?
2. Why split Department out of the Student table?

Answers: 1. SQL. 2. To store the department name once (less redundancy) and update it in one place.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A DBMS is software that:

- a. Creates and manages databases
- b. Draws only pie charts
- c. Routes IP
- d. Sorts using bubble only

MCQ 2. Examples of DBMS:

- a. MS Access, MySQL, SQLite, Oracle
- b. Python only
- c. Figma only
- d. Chrome only

MCQ 3. DBMS handles:

- a. Storage, retrieval, security, multi-user access
- b. Only fonts
- c. Only OSI layer 1
- d. Only NAND

MCQ 4. Without a DBMS, programs would:

- a. Each invent their own file format
- b. Run faster always
- c. Need no keys
- d. Need no SQL

MCQ 5. Access is used in XI because:

- a. It is a GUI DBMS for tables/forms/queries/reports
- b. It is a programming language
- c. It is Agile
- d. It is analog

MCQ 6. SQLite in XII is a:

- a. Lightweight DBMS/library
- b. Chart
- c. Gate
- d. Sprint

Extra short questions

1. Define DBMS.
2. Four DBMS functions.
3. DBMS vs database.
4. Name two desktop and two server DBMS.

Extra long question

1. Compare managing 500 students in Excel vs a DBMS (Access). Use data integrity, search, multi-user and reports.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Database Management System: software to define, store, query, protect and share a database.
2. Create tables, insert/update/delete, query, enforce keys/security, backup.
3. Database is the data; DBMS is the software that manages it.
4. Desktop: Access, SQLite. Server: MySQL, Oracle, PostgreSQL.

Long


1. Excel: easy but duplicates, weak keys, clash when two people edit. DBMS: primary keys, queries, forms, reports, controlled access.

4.4 Entity Relationship Model (ER-Model) ★ Golden

LEARN IT

The **ER model** is the architect's blueprint: you draw what will be stored and how it connects *before* you create tables in Access. Three building blocks:

Component	Meaning	Symbol	Example
Entity	A real-world object we store data about	Rectangle	STUDENT, TEACHER, COURSE
Attribute	A property of an entity. PK is underlined	Oval	StudentID, Name, Class
Relationship	How two entities are connected	Diamond	Enrolls, Teaches, Has



Rectangle = entity, diamond = relationship, oval = attribute. Underline the primary-key attribute.

Cardinality (types of relationship)

Type	Meaning	Example
One-to-One (1:1)	One record ↔ exactly one record. Rare; often for security.	One student has one ID card.
One-to-Many (1:M)	One record in A ↔ many in B. The most common type.	One teacher teaches many students.
Many-to-Many (M:N)	Many in A ↔ many in B.	Many students enrol in many classes.

COMMON MISTAKE

The M:N rule. A relational database cannot store M:N directly — it duplicates data. Break it into two 1:M relationships with a **junction table** (also called a bridge or associative table). Example: Enrollment(StudentID, ClassID, Date).

EXAM TIP

Always state cardinality on the diagram (1 and M at the ends of the line). For M:N, the long question is “how do you resolve it?” — draw the junction entity with two foreign keys.

آردو میں سمجھیں

ای آر ماڈل ڈیٹا بیس کا خاکہ ہے۔ مستطیل بستی، بیضوی صفت، لوزی تعلق، تعلقات 1:1، M:1 یا M:N ہوتے ہیں۔ M:N کو دو M:1 میں توڑنے کے لیے جنکشن ٹیبل بنانا پڑتا ہے۔

CHECK YOURSELF

- What symbol is used for a relationship?
- A hospital: one patient, many appointments. Cardinality?

Answers: 1. Diamond. 2. 1:M (Patient 1 — has — M Appointment).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An ER model is drawn:

- Before building tables
- After deleting the DB
- Only in Python
- Only in OSI

MCQ 2. An entity is:

- A real-world thing we store
- A Python keyword
- A cable
- A sprint

MCQ 3. A relationship 1:M means:

- One A, many B
- Many A, many B only
- One to one only
- No link

MCQ 4. M:N in an RDBMS needs:

- A bridge/associative table
- A pie chart
- A stack
- A NAND

MCQ 5. A diamond in ER often shows:

- A relationship
- An attribute oval only
- A PK square
- A report

MCQ 6. Cardinality is:

- 1:1, 1:M, M:N
- Big O
- TCP window
- Variance

Extra short questions

- Define ER model.
- Three relationship types with examples.
- How do you convert 1:M to tables?
- Why ER first?

Extra long question

- Draw ER for Library: Member, Book, Borrow. Mark keys, cardinality, and how you resolve M:N. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Entity-Relationship: conceptual design of entities, attributes, relationships.
- 1:1 person-NIC; 1:M mother-children / member-borrows; M:N students-courses.
- PK of the 1 side copied as FK on the M side.
- Cheaper to fix a diagram than a populated database.

Long

- Member 1—M Borrow M—1 Book (Borrow as relationship-entity with date). If Book-Member M:N, Borrow is the bridge with composite/surrogate key.

4.5 Referential Integrity (Cascade Update & Delete) ★ Golden

LEARN IT

Referential integrity means every foreign-key value in a child table must match an existing primary-key value in the parent — or be NULL if the design allows it. It stops orphan records.

If Result.StudentID is a FK to Student.StudentID, you cannot type Result for student 999 if 999 is not in Student. You also cannot delete student 101 while results for 101 still exist — unless you first handle those child rows.

Parent — STUDENT		Child — RESULT	
ID	Name	ID	Grade
101	Ali	101	A
102	Sara	999	F — rejected

Cascade operations

Cascade Update. Change the PK in the parent, and every matching FK in the child changes automatically. Ali's ID 101 → 201 updates Enrollments too. Nothing is left pointing at a vanished 101.

Cascade Delete. Delete the parent, and related child rows are deleted too. If Sara (102) leaves school, her Enrolment and Result rows disappear. That prevents "ghost" marks for a student who is gone.

WORKED EXAMPLE

Before Cascade Update

Student.ID	Enrol.StudentID
101	101

After changing 101 → 201 with Cascade Update ON

Student.ID	Enrol.StudentID
201	201

If Cascade Update were OFF, Access would refuse the change, or (in a sloppy file) leave Enrol stuck on 101 — an orphan.

COMMON MISTAKE

Cascade Delete is powerful and dangerous. Deleting one parent can wipe years of child history. In a real school, you more often **archive** a student (a Status field) than delete them.

EXAM TIP

Write: definition, why it matters (no orphans), then one numbered example of Cascade Update and one of Cascade Delete. Mention parent vs child.

اردو میں سمجھیں

ریفرنشل انٹیگریٹی کا مطلب ہے بچہ ٹیبل کی فارن کی ہمیشہ والدین کی موجود پرائمری کی طرف اشارہ کرے۔ کیسکیڈ اپ ڈیٹ والدین کی بدلتے پر بچوں کو خود بدل دیتی ہے؛ کیسکیڈ ڈیلیٹ والدین مٹانے پر متعلقہ بچے ریکارڈ بھی مٹا دیتی ہے۔

CHECK YOURSELF

1. What is an orphan record?

2. Cascade Delete: parent Teacher is removed. What happens to that teacher's Class rows?

Answers: 1. A child row whose FK value does not exist in the parent. 2. They are deleted automatically (if Cascade Delete is on).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Referential integrity means:

a. Every FK matches an existing PK (or is NULL if allowed)

b. Names are unique

c. Files are encrypted

d. Charts are labelled

MCQ 2. Cascade update:

a. Changes child FKs when the parent PK changes

b. Deletes the DBMS

c. Sorts tables

d. Draws ER

MCQ 3. Cascade delete:

a. Deletes child rows when the parent is deleted

b. Inserts a parent

c. Creates a view

d. Opens a form

MCQ 4. Inserting an FK that does not exist should:

a. Be rejected

b. Be auto-sorted

c. Draw a pie

d. Start Agile

MCQ 5. Orphan records are:

a. Child rows whose parent is gone

b. Primary keys

c. Reports

d. Queries

MCQ 6. Referential integrity is enforced by the:

a. DBMS

b. Monitor

c. Mouse

d. Compiler of Python only

Extra short questions

1. Define referential integrity.

2. What does cascade update solve?

3. When is cascade delete dangerous?

4. Give an invalid operation.

Extra long question

1. In Members-Borrow, specify restrict vs cascade for UPDATE and DELETE with a Sindh-college story. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. FK values must exist in the parent PK (unless NULL is allowed).

2. If roll number 12 becomes 112, all Marks.roll 12 become 112 automatically.

3. Deleting a member could wipe years of borrow history — sometimes restrict instead.

4. INSERT borrow for MemberID 999 when no such member.

Long

1. UPDATE MemberID: cascade so old cards still match. DELETE member who still has books: restrict (cannot delete). DELETE member with no books: allow. Show one rejected SQL/Access action.

4.6 Relational Schema Development

LEARN IT

A **relational schema** is the formal written design of the database: table names, fields, primary keys, foreign keys and how tables relate. You write it *before* clicking around in Access. It defines (1) how data is split into tables, (2) which columns each table has, (3) which fields are PK/FK, (4) the relationships. Benefits: less redundancy, integrity planned in advance, easier to grow later.

WORKED EXAMPLE

Written schema for a tiny college:

```
Department (DeptID PK, DeptName)
Student (RollNo PK, Name, Class, DeptID FK → Department)
Course (CourseID PK, Title, Credit, DeptID FK → Department)
```

REMEMBER IT

Skipping the schema is like building a house without a drawing. You get messy, broken structures that are painful to repair.

اردو میں سمجھیں

ریشنل اسکیم ڈیٹا بیس کا لکھا ہوا نقشہ ہے: کون سے ٹیبل، کون سے فیلڈ، کون سی کیز، کون سے تعلقات۔ سافٹ ویئر کھولنے سے پہلے یہ بنانا چاہیے۔

CHECK YOURSELF

1. Name two things a schema must show.
2. Give one reason to write a schema before opening Access.

Answers: 1. Tables/fields and keys/relationships. 2. It reduces redundancy and mistakes (any valid benefit).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A relational schema is:

- a. The blueprint of tables, keys, types
- b. A running query result
- c. A pie chart
- d. A Python list

MCQ 2. Student(roll PK, name, class) is a:

- a. Schema notation
- b. Python call
- c. OSI frame
- d. MVP

MCQ 3. Schema is designed:

- a. Before stuffing thousands of rows
- b. After losing the backup
- c. Instead of ER
- d. By the compiler

MCQ 4. Data types in schema stop:

- a. Wrong values (text in marks)
- b. TCP errors
- c. NAND delay
- d. Figma overflow

MCQ 5. Foreign keys in schema implement:

- a. Relationships
- b. Sorts
- c. Charts
- d. Sprints

MCQ 6. Changing schema later is:

- a. Painful once data exists
- b. Free always
- c. Impossible in Access
- d. A gate

Extra short questions

1. Define relational schema.
2. Write schema for Book.
3. How does schema differ from ER?
4. Name two things schema documents besides columns.

Extra long question

1. Turn your library ER into a schema listing: three tables, keys, two constraints. Justify one data type.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Formal structure: relation names, attributes, types, keys.
2. Book(ISBN PK, title, author, copies: Number).
3. ER is conceptual diagram; schema is the relational implementation.
4. PKs, FKs, unique, not null, relationships.

Long

1. Member(MemberID PK, name Text, phone Text unique). Book(ISBN PK, title Text, copies Number). Borrow(BorrowID PK, MemberID FK, ISBN FK, date Date). Copies is Number because you count them.

4.7 Case Study — Library Management System

LEARN IT

A college library needs a database. Walk the seven steps examiners expect.

Step 1 — Requirements. A book has ID, title, author, publisher. A member (student/teacher) has ID, name, contact. A member can borrow many books; a book can be borrowed by different members over time. Record Issue Date and Return Date.

Step 2 — Entities. Book, Member. (Borrowing will need a third entity in step 6.)

Step 3 — Attributes. Book: BookID (PK), Title, Author, Publisher. Member: MemberID (PK), Name, ContactInfo.

Step 4 — Relationship. Member borrows Book.

Step 5 — Cardinality. One member borrows many books over time; one book is borrowed by many members over time → **M:N**.

Step 6 — Resolve M:N. Add junction entity **BorrowRecord**: BorrowID (PK), MemberID (FK), BookID (FK), IssueDate, ReturnDate. Now Member 1—M BorrowRecord M—1 Book (two 1:M links).

Step 7 — Final schema.

Member (MemberID PK, Name, ContactInfo)

Book (BookID PK, Title, Author, Publisher)

BorrowRecord (BorrowID PK, MemberID FK, BookID FK, IssueDate, ReturnDate)



Final library ER: two 1:M relationships through the BorrowRecord junction table.

WORKED EXAMPLE

Sample rows after Sara borrows “Khushwant” on 5 Oct 2026:

BorrowID	MemberID	BookID	IssueDate	ReturnDate
5001	102	B-17	2026-10-05	

The same book can later be borrowed by Ali as BorrowID 5002 — no duplicated book title, no duplicated member address.

اردو میں سمجھیں

لائبریری میں ممبر اور کتاب کا تعلق بہت-بہت سے ہے، اس لیے پورو ریکارڈ نامی پل ٹیبل بنائے ہیں جس میں دونوں کی فارن کیڈ اور اجراء/واپسی کی تاریخ ہوتی ہے۔

CHECK YOURSELF

1. Why is BorrowRecord needed?

2. Where do IssueDate and ReturnDate belong, and why not on Book?

Answers: 1. To break M:N into two 1:M links. 2. On BorrowRecord — they belong to a *transaction*, not to the book itself (a book is issued many times).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The library case study starts from:

a. Requirements

b. Random tables

c. Pie charts

d. Sprints only

MCQ 2. Member to Borrow is typically:

a. 1:M

b. Always 1:1

c. No relation

d. M:1 the other way only if reversed

MCQ 3. Book to Borrow is typically:

a. 1:M (one book title/copy can be borrowed many times)

b. Always M:N without a bridge

c. 1:1 mandatory

d. A stack

MCQ 4. M:N Member–Book is resolved by:

a. Borrow record table

b. A pie

c. A NAND

d. OSI

MCQ 5. A good case-study answer shows:

a. ER then schema then sample rows

b. Only careers

c. Only Python turtle

d. Only Figma

MCQ 6. Fine calculation would be stored in:

a. Borrow (or computed in a query)

b. The OSI header

c. A K-map

d. A histogram bin

Extra short questions

1. List four requirements of a college library system.

2. Name the entities.

3. Why a Borrow entity?

4. One report the librarian wants.

Extra long question

1. Walk the seven case-study steps from the notes: requirements → entities → attributes → relationships → keys → resolve M:N → final ER. Draw the final diagram.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Register members; catalogue books; issue/return; calculate fines; search.

2. Member, Book, Borrow (and maybe Copy if multiple copies).

3. The issue event has its own date/fine — and it breaks M:N.

4. Overdue list: member, book, days late.

Long

1. Follow the textbook library walk-through. Final: Member 1–M Borrow M–1 Book. Keys labelled. One sentence on cascade.

4.8 Different Database Objects (Tables, Forms, Queries, Reports)

LEARN IT

Four objects you will meet in Access. Learn the one-line jobs cold:

Object	Job	You ...
Table	Stores the data (foundation; every other object depends on it)	keep the actual records here
Form	Friendly screen for enter / edit / view (text boxes, drop-downs)	type data in; fewer mistakes than a raw grid
Query	Ask a question: filter, sort, calculate	e.g. "students above 80%"
Report	Formatted output for printing or sharing	read only — never type into a report

REMEMBER IT

Store → Enter → Search → Print. Tables, Forms, Queries, Reports.

COMMON MISTAKE

A query does not copy the table into a second storage place. It is a saved question. Change the table, re-run the query, and the answer updates.

اردو میں سمجھیں

ٹیبل ڈیٹا رکھتی ہے، فارم سے اندراج ہوتا ہے، کوئری سوال پوچھ کر چھاننتی ہے، رپورٹ چھپائی کے لیے سنواری ہوئی پیشکش ہے — اس میں ڈیٹا بھرا نہیں جاتا۔

CHECK YOURSELF

1. Which object would you use for a printed fee slip?
2. Which object actually holds the fee amount?

Answers: 1. Report. 2. Table.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The four Access objects are:

- a. Tables, forms, queries, reports
- b. Lists, tuples, sets, dicts
- c. AND OR NOT XOR
- d. HTTP TCP IP ETH

MCQ 2. Tables store:

- a. The actual data
- b. Only print layout
- c. Only VBA
- d. Only charts

MCQ 3. Forms are for:

- a. Friendly data entry
- b. Physical cabling
- c. Big O proofs
- d. Sorting theories

MCQ 4. Queries:

- a. Ask questions / filter / calculate without changing stored rows (select)
- b. Always delete tables
- c. Draw OSI
- d. Compile C

MCQ 5. Reports are for:

- a. Printable summaries
- b. Capturing packets
- c. NAND grouping
- d. Figma prototypes

MCQ 6. You should enter daily data in a:

- a. Form (not raw datasheet if avoidable)
- b. Report
- c. Macro only
- d. Relationship window only

Extra short questions

1. Role of each object in one line.
2. Why not type into reports?
3. A select query does not:
4. Give one example object for a library.

Extra long question

1. Design the four objects for an attendance database. Say what each contains and how a teacher uses them in one period.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Table: store. Form: enter. Query: ask. Report: print/share.
2. Reports are output; they do not store new rows.
3. By itself permanently delete table data (unless you run a delete-query).
4. Query: books overdue; Report: overdue letters; Form: issue desk.

Long

1. Table Students+Attendance. Form mark present. Query absentees today. Report monthly letter. Flow: form → table → query → report.

4.9 Creation of Tables in Microsoft Access

LEARN IT

Plan first (4.9.1): purpose, field list, data type of each field, which field is the PK.

Datasheet View (4.9.2) — fast, spreadsheet-like, good for beginners, weak on rules.

- Create tab → Table.
- A blank grid appears.
- Double-click Field1, Field2, ... to rename.
- Type data; Access guesses the data type.

Limitation: you cannot easily say "Marks cannot exceed 100". Professionals use Design View.

Design View (4.9.3) — full control before any data is typed.

- Create tab → Table Design.
- Type each Field Name (StudentID, Name, ...).
- Pick the Data Type from the dropdown.
- Right-click the unique field → Primary Key (key icon).
- Save the table.

Data type	Use it for
Short Text	Names, addresses, phone numbers (you do not add phone numbers). Up to 255 characters.
Number	Values you calculate with: Age, Marks, Quantity.
Date/Time	Date of birth, admission date, appointment time.
Currency	Fees, salary.
AutoNumber	Access fills a unique sequential number — excellent PK.

COMMON MISTAKE

Phone numbers look numeric but are Short Text. Leading zeros (0333...) would vanish in a Number field, and you never sum two phone numbers.

اردو میں سمجھیں

پہلے ٹیبل کا منصوبہ بنائیں۔ ڈیٹا شیٹ ویو تیز لیکن کمزور ہے؛ ڈیزائن ویو میں فیلڈ، ڈیٹا ٹائپ اور پرائمری کی خود منتخب کرتے ہیں۔ فون نمبر ہارٹ ٹیکسٹ رکھیں۔

CHECK YOURSELF

1. Best data type for StudentID if you want Access to generate it?

2. Best data type for FeeAmount?

Answers: 1. AutoNumber. 2. Currency.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Design View is best when you:

- Need full control of names, types, keys before data
- Want a random spreadsheet
- Draw Figma
- Ping a router

MCQ 2. Datasheet View is for:

- Typing rows after the structure exists
- Defining PK only
- Writing Python
- OSI captures

MCQ 3. A Number field should not store:

- Phone numbers that need leading zeros (use Text)
- Marks
- Counts
- IDs that are truly numeric

MCQ 4. Primary key is set in:

- Design View (key icon)
- A report footer
- A pie
- Agile sticky

MCQ 5. Yes/No fields store:

- Boolean-like presence
- Paragraphs
- Images only
- OSI layers

MCQ 6. Creating tables is step one because:

- Everything else hangs on the structure
- Reports can store data
- Queries invent columns from nothing always
- Forms replace keys

Extra short questions

- Steps to create a table in Design View.
- When Datasheet create is OK?
- Why set field size/validation?
- Name three data types you used in class.

Extra long question

- Create (on paper) Design View for Students: four fields, PK, one validation rule, and say what error Access shows if the rule fails.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Create → Table Design; field name; data type; PK; save name.
- Quick throwaway; still go back to Design to set PK/types.
- Stop 999 marks out of 100; stop 40-character roll numbers.
- Short Text, Number, Date/Time, Yes/No, Currency, AutoNumber.

Long

- Roll AutoNumber/Number PK; Name Short Text required; Marks Number 0–100 validation; Passed Yes/No. Invalid marks: validation text "0 to 100".

4.10 Designing Forms for Data Manipulation

LEARN IT

A form is the screen people actually type into. It cuts errors and can show validation messages. Every form **must** have a data source — a table or a query. A form with no source has nowhere to save.

Form Wizard (the exam method):

1. Create tab → Form Wizard.
2. Select the table (e.g. Student).
3. Move fields with > (one) or >> (all).
4. Choose layout. **Columnar** = one record at a time, best for data entry.
5. Name it ("Student Registration") → Finish.

WORKED EXAMPLE

A Student Registration form shows Student ID (AutoNumber, locked), Full Name, Class, Department as labelled boxes, plus Save. The clerk never sees the raw datasheet and cannot accidentally overwrite the next row.

اردو میں سمجھیں

فارم اندراج کی سادہ اسکرین ہے۔ ہر فارم کسی ٹیبل یا کوئری سے جڑا ہوتا ہے۔ فارم وزرڈ سے ٹیبل چنائیں، فیلڈز منتخب کریں، کالم نما لے آؤت بہتر ہے، نام دے کر ختم کریں۔

CHECK YOURSELF

1. Can a form exist without a table or query?
2. Which layout is best for entering one student at a time?

Answers: 1. No — it needs a data source. 2. Columnar.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A form is:

- a. A screen for entering/editing records
- b. A printed summary only
- c. A TCP socket
- d. A sort

MCQ 2. Bound controls show:

- a. Fields from a table/query
- b. Random clipart only
- c. OSI headers
- d. NAND

MCQ 3. Validation on a form:

- a. Stops bad keystrokes before they hit the table
- b. Sorts binary search
- c. Encrypts OSI
- d. Draws histograms

MCQ 4. A combo box is for:

- a. Picking from a list (e.g. class names)
- b. Drawing ER
- c. Pinging
- d. Compiling

MCQ 5. Why forms vs datasheet?

- a. Fewer mistakes, one-record focus, hidden dangerous fields
- b. Forms store more rows than tables
- c. Datasheets cannot show data
- d. Forms replace primary keys

MCQ 6. Navigation buttons on a form:

- a. Move among records
- b. Create queries
- c. Set PK
- d. Start sprints

Extra short questions

1. Define form.
2. Two controls and their use.
3. How does a form enforce a rule visually?
4. Wizard vs Design View?

Extra long question

1. Design an Issue-Book form: record source, four controls, one validation, and how it prevents an orphan borrow.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Interface to enter, edit, view records, with validation.
2. Text box: name. Combo: class list. Button: save/new.
3. Required star, dropdown instead of free text, cannot tab off an empty PK.
4. Wizard fast; Design for layout and extra controls.

Long

1. Source Borrow+combo of MemberID and ISBN from parent tables (combo bound to FK). Date default today. Validation: due>issue. Combo prevents typing a non-existent member.

4.11 Creating Queries in MS Access ★ Golden

LEARN IT

A query retrieves, filters and analyses data **without changing the original tables**. A simple SELECT query:

1. Create tab → Query Design.

2. Show Table → add Student → Close.

3. Double-click the fields you want; they drop into the grid.

4. Red Run (!) button executes it.

Criteria restrict rows. Type a value in the Criteria row under a field.

Goal	Where to type	Example
Single criterion	Criteria row, one column	Department → "Computer Science"
AND (both must match)	Same Criteria row, two columns	Name "Ali" and Department "Computer Science"
OR (either may match)	Criteria row and the or: row	Department "IT" or "Computer Science"

Wildcards in Access: * = any characters, ? = one character. Like "A*" finds Ali, Ahmed, Ayesha.

WORKED EXAMPLE

Equivalent SQL (what Access writes behind the grid):

```
SELECT StudentName, Department
FROM Student
WHERE Department = "Computer Science";

SELECT StudentName, Department
FROM Student
WHERE StudentName = "Ali" AND Department = "Computer Science";

SELECT StudentName, Department
FROM Student
WHERE Department = "IT" OR Department = "Computer Science";
```

EXAM TIP

Remember: AND = same row in the grid; OR = different rows. Examiners draw a blank grid and ask you to fill Criteria and or:.

COMMON MISTAKE

Text criteria need quotes: "IT" . Numbers do not: ≥ 80 . Mixing these is a common cause of empty results.

اردو میں سمجھیں

کوئی ٹیبل کو بدلے بغیر سوال پوچھتی ہے۔ ایک شرط Criteria قطار میں، AND ایک ہی قطار کی دو کالموں میں، OR الگ قطار (or) میں۔ والٹڈ کارڈ * کئی حروف، ? ایک حرف۔

CHECK YOURSELF

1. Criteria for marks at least 80?

2. You want CS or IT. Same row or two rows?

Answers: 1. ≥ 80 under Marks. 2. Two rows (OR).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A query is:

a. A request to retrieve/filter/calculate data

b. A printed letter

c. A cable

d. A gate

MCQ 2. Criteria in a query:

a. Filter rows (e.g. Marks>=40)

b. Change field types

c. Draw ER

d. Set the OS

MCQ 3. A parameter query asks:

a. The user for a value at run time

b. The CPU voltage

c. TCP window

d. Figma frames

MCQ 4. Select queries by default:

a. Do not delete stored rows

b. Always wipe the table

c. Always cascade

d. Always print

MCQ 5. Sorting in a query:

a. Orders the result (Asc/Dsc)

b. Changes PK

c. Encrypts

d. Creates a form

MCQ 6. This topic is ★ because board papers love:

a. Writing criteria and showing results

b. Cabling

c. NAND only

d. Sprints

Extra short questions

1. Define query.

2. Write criteria: CS students with marks < 40.

3. Difference between filter on a datasheet and a query.

4. What is a calculated field in a query?

Extra long question

1. Design a query: join Students and Marks, show Fail list (marks<40) sorted by name, with a calculated column 40-Marks as Needed. Write QBE grid/SQL-like criteria. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. A saved question that selects, filters, sorts, calculates from tables.

2. Class = "CS" AND Marks < 40 (field names as in the table).

3. Query is reusable, can join tables, calculate, feed reports.

4. Total:[Math]+[Eng] — not stored, computed.

Long

1. Tables joined on roll. Fields Name, Subject, Marks, Needed: 40-[Marks]. Criteria Marks<40. Sort Name. Result sample two rows.

16

4.11.4 Data Summarization & Statistical Analysis

LEARN IT

Grouping combines rows that share a value (all CS students together) and then an **aggregate** calculates a number for the group. In Access click Totals (Σ) to reveal the Total row in the grid.

Function	What it calculates
COUNT()	How many records (students in IT)
SUM()	Total of a number field (fees collected)
AVG()	Mean
MAX() / MIN()	Highest / lowest in the group

WORKED EXAMPLE

Average marks per department: add Department and Marks; Totals Σ; Department → Group By; Marks → Avg; Run.

Department	Avg of Marks
Computer Science	82.5
IT	76.0

Check: CS marks 80, 85 → average $(80+85)/2 = 82.5$. IT 70, 82 → 76.0.

```
SELECT Department, AVG(Marks) AS AvgOfMarks
FROM Student
GROUP BY Department;
```

اردو میں سمجھیں

گروپ بائی ایک جیسے ریکارڈ جوڑتا ہے، پھر COUNT, SUM, AVG, MAX, MIN سے خلاصہ نکلتا ہے۔ ایکسیس میں Σ بنن Total قطار کھولتا ہے۔

CHECK YOURSELF

- Which Total setting goes under Department?
- Which function counts how many books each member has borrowed?

Answers: 1. Group By. 2. COUNT (of BorrowID or BookID) grouped by MemberID.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Grouping in a query:

- Collapses rows that share a value (e.g. by class)
- Deletes the table
- Draws OSI
- Opens Figma

MCQ 2. Count(*) with group by class gives:

- How many students per class
- The PK
- A pie automatically
- A stack

MCQ 3. Avg(Marks) is:

- An aggregate
- A primary key
- A form control always
- A foreign key

MCQ 4. Sum is for:

- Totals (fees, marks)
- Sorting names alphabetically
- Encryption
- Routing

MCQ 5. Min/Max in a totals query:

- Smallest/largest in the group
- The table name
- The form wizard
- TCP ports

MCQ 6. You summarise when:

- n is large and you need a picture of each group
- You have one row
- You draw NAND
- You write sprints

Extra short questions

- Name four aggregate functions.
- What must you set in Access Totals query?
- Example: average marks per subject.
- Why not list 2000 rows to the principal?

Extra long question

- From a Marks table, design two totals queries: (1) count of fails per class (2) average marks per subject. Show the Group By row.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Count, Sum, Avg, Min, Max.
- Group By on the category; Count/Avg on the measure.
- Group by Subject; Avg(Marks).
- A 5-row summary is decidable; a dump is not.

Long


- (1) Class Group By; Marks Count with criteria <40 or a Fail Yes/No Count. (2) Subject Group By; Marks Avg. Sample output.

4.11.6 Data Visualization in MS Access (Charts)

LEARN IT

Charts turn numbers into a picture so a pattern jumps out. Pick the chart that matches the question:

Chart	Shape	Best for
Bar (horizontal)	Bars sideways	Categories with long names (English, Mathematics, ...)
Column (vertical)	Bars standing	Side-by-side comparison (2024 / 2025 / 2026 admissions)
Pie	Slices of a circle	Parts of one whole (percent of CS vs IT vs Eng). Few slices.
Line	Dots joined	A trend over time (visitors per month)



Column = compare categories. Pie = share of a total. Line = change over time.

EXAM TIP

"Which chart?" — line for time, pie for composition, bar/column for comparing categories. Mention one reason.

اردو میں سمجھیں

بار لمبے ناموں والی اقسام، کالم سادہ موازنہ، پائی حصوں کا تناسب، لائن وقت کے ساتھ رجحان۔ چارٹ کوئی یا ٹیبل کے اعداد کو تصویر بناتا ہے۔

CHECK YOURSELF

1. Website visitors each month — which chart?
2. Share of boys vs girls in one class — which chart?

Answers: 1. Line. 2. Pie (two parts of a whole).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A column chart in Access is for:
a. Comparing categories
b. Parts of a whole only
c. Time only
d. OSI only

MCQ 2. A pie chart shows:
a. Share of a total
b. A trend of 60 months well
c. Binary search
d. Foreign keys

MCQ 3. A line chart shows:
a. Change over time
b. Unrelated categories best
c. ER diamonds
d. NAND

MCQ 4. Charts should be based on:
a. A summarised query, not 10,000 raw rows if possible
b. The relationship window
c. Python turtle
d. Figma

MCQ 5. Unlabelled axes in an exam chart score:
a. Near zero
b. Full marks
c. Bonus NAND
d. An extra sprint

MCQ 6. Choose the chart that matches the question, same rule as:
a. Matplotlib in Xil
b. Bubble sort
c. TCP handshake
d. K-maps

Extra short questions

1. When pie vs column?
2. When line?
3. Why chart a totals query not the raw table?
4. Three labels every chart needs.

Extra long question

1. For library data pick a chart: (a) books per genre (b) issues per month (c) share of lost vs on-shelf vs borrowed. Justify and sketch.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Pie: composition of one whole (few slices). Column: compare separate categories.
2. Enrolment 2019–2026 — time.
3. The chart needs one number per category, not every student.
4. Title, axis titles / legend, units.

Long

1. (a) column (b) line (c) pie. Each sketch labelled. One sentence why the others are worse.

Data and Analysis

15 single-page lessons · 4 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- Data = raw facts; information = processed data used for decisions; a database stores related data in a structured, updatable way.
- A DBMS is the software layer that provides less redundancy, consistency, security and integrity.
- Table = rows (records) and columns (fields). One table, one entity.
- Candidate keys could identify a row; the primary key is the one you choose (unique, not NULL); leftover candidates are alternate keys; a foreign key points at another table's PK.
- An RDBMS keeps several related tables and is queried with SQL.
- ER symbols: rectangle entity, oval attribute, diamond relationship. Cardinality 1:1, 1:M, M:N. M:N needs a junction table.
- Referential integrity forbids orphan FKs. Cascade Update copies a changed PK into children; Cascade Delete removes children with the parent.
- Write a relational schema before building. Library case: Member and Book are M:N, resolved by BorrowRecord.
- Objects: tables store, forms enter, queries search, reports print.
- Access Design View sets field names, data types and the PK. Phone numbers are Short Text; money is Currency; auto IDs are AutoNumber.
- Forms need a table/query source; Wizard + columnar layout for data entry.
- Query criteria: one value; AND on the same row; OR on two rows. Totals Σ for Group By / Count / Sum / Avg / Max / Min.
- Bar/column compare categories, pie shows parts of a whole, line shows a trend over time.

Key terms

Term	Meaning	اردو
Data	Raw facts and figures.	ڈیٹا / خام حقائق
Information	Processed data that supports a decision.	معلومات
Database	Organised collection of related data.	ڈیٹا بیس
DBMS	Software that creates and manages databases.	ڈیٹا بیس مینجمنٹ سسٹم
Table	Rows and columns about one entity.	ٹیبل
Record	One row — one instance.	ریکارڈ
Field	One column — one attribute.	فیلڈ
Primary key	Chosen unique, non-empty identifier.	پرائمری کی
Foreign key	Field that refers to another table's PK.	فارن کی
Candidate key	Any field(s) that could be the PK.	کینڈیڈیٹ کی
Alternate key	A candidate not chosen as PK.	آلٹرنیٹ کی
RDBMS	DBMS that stores related tables linked by keys.	ریلیشنل ڈی بی ایم ایس

Data and Analysis

75 marks · 1 hour 15 minutes · no notes · no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 15 and the recap. **Section A** — all 15 MCQs (1 mark). **Section B** — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define · Explain · Example · Diagram · Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. Processed data used for a decision is called:
 - a. a field
 - b. information
 - c. a query
 - d. redundancy
2. A complete row about one student is a:
 - a. field
 - b. report
 - c. record
 - d. schema
3. A primary key cannot contain:
 - a. numbers
 - b. text
 - c. NULL
 - d. an AutoNumber
4. EmpLicense# after EmpID is chosen as PK is an:
 - a. foreign key
 - b. alternate key
 - c. orphan
 - d. report
5. A foreign key:
 - a. must be unique in the child table
 - b. may contain duplicates
 - c. cannot exist in an RDBMS
 - d. is always AutoNumber
6. The ER symbol for a relationship is a:
 - a. rectangle
 - b. oval
 - c. diamond
 - d. circle
7. The most common cardinality is:
 - a. 1:1
 - b. 1:M
 - c. M:N stored as-is
 - d. 0:0
8. M:N is stored in an RDBMS by:
 - a. duplicating both tables
 - b. a junction table
 - c. deleting one entity
 - d. using a pie chart
9. A child row whose StudentID is not in Student is:
 - a. a candidate key
 - b. an orphan record
 - c. a form
 - d. a primary key
10. Changing parent ID 101 → 201 and seeing the child follow is:
 - a. Cascade Delete
 - b. Cascade Update
 - c. a SELECT query
 - d. a pie chart
11. Which Access object is for printing a report card?
 - a. Table
 - b. Form
 - c. Query
 - d. Report
12. Phone numbers should be stored as:
 - a. Number
 - b. Currency
 - c. Short Text
 - d. Date/Time
13. AND criteria go:
 - a. on two different rows of the grid
 - b. on the same Criteria row
 - c. in a report header
 - d. only in SQL Server
14. To average marks per department you set Department to:
 - a. Sum
 - b. Where
 - c. Group By
 - d. Expression
15. The best chart for admissions in 2024, 2025, 2026 is a:
 - a. pie chart
 - b. column chart
 - c. junction table
 - d. foreign key

Section B — Short questions (10 × 3 = 30)

1. Differentiate data and information with one example each.
2. List four advantages of a DBMS.
3. Define record and field with reference to a Student table.
4. Differentiate primary key and foreign key (four points).
5. Why can a relational database not store M:N directly?
6. What is referential integrity? Give one rejected-insert example.
7. Differentiate Cascade Update and Cascade Delete.
8. State the four Access objects and the job of each in one line.
9. Why are phone numbers Short Text, not Number?
10. How do you express OR in Query Design?

Section C — Long questions (attempt any 3 × 10 = 30)

1. Draw a complete ER diagram for Student–Course enrolment (M:N). Resolve it with a junction entity. Write the relational schema with keys marked.
2. A Result table uses StudentID as a foreign key. Explain referential integrity, then show before/after tables for (a) Cascade Update of ID 101 → 201 and (b) Cascade Delete of student 102.
3. Work through the library case study: requirements, entities, attributes, relationship, cardinality, junction table, final schema. Include two sample BorrowRecord rows.
4. Write step-by-step how to create a Student table in Access Design View (fields RollNo Number PK, Name Short Text, Marks Number, Fee Currency, AdmDate Date/Time) and then a columnar form with the Wizard.
5. Write the Query Design settings and the SQL to list CS students with Marks ≥ 80 , sorted by Name. Then write a totals query that shows COUNT of students and AVG(Marks) for each Department.
6. A principal wants to see (i) fee collected per class, (ii) the share of each class in total enrolment, (iii) enrolment over five years. Which chart for each, and why?

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

1. **4.1.1 Data, Information and Database.** Answers: 1. Data (raw facts about one student). 2. It is not organised in a structured, searchable, updatable collection of related records.
2. **4.1.2 Database Management System (DBMS).** Answers: 1. MS Access, MySQL (Oracle, SQLite also). 2. Integrity (unique / primary-key constraint).
3. **4.2 Database Components (Tables, Records, Fields).** Answers: 1. 3 records, 4 fields. 2. A value stored in the Course field.
4. **4.3.1 Keys and Integrity Constraints.** Answers: 1. No — only one PK (it may be composite). 2. Yes — many child rows may point to the same parent.
5. **4.3 Relational Database Management System (RDBMS).** Answers: 1. SQL. 2. To store the department name once (less redundancy) and update it in one place.
6. **4.4 Entity Relationship Model (ER-Model).** Answers: 1. Diamond. 2. 1:M (Patient 1 — has — M Appointment).
7. **4.5 Referential Integrity (Cascade Update & Delete).** Answers: 1. A child row whose FK value does not exist in the parent. 2. They are deleted automatically (if Cascade Delete is on).
8. **4.6 Relational Schema Development.** Answers: 1. Tables/fields and keys/relationships. 2. It reduces redundancy and mistakes (any valid benefit).
9. **4.7 Case Study — Library Management System.** Answers: 1. To break M:N into two 1:M links. 2. On BorrowRecord — they belong to a *transaction*, not to the book itself (a book is issued many times).
10. **4.8 Different Database Objects (Tables, Forms, Queries, Reports).** Answers: 1. Report. 2. Table.
11. **4.9 Creation of Tables in Microsoft Access.** Answers: 1. AutoNumber. 2. Currency.
12. **4.10 Designing Forms for Data Manipulation.** Answers: 1. No — it needs a data source. 2. Columnar.
13. **4.11 Creating Queries in MS Access.** Answers: 1. ≥ 80 under Marks. 2. Two rows (OR).
14. **4.11.4 Data Summarization & Statistical Analysis.** Answers: 1. Group By. 2. COUNT (of BorrowID or BookID) grouped by MemberID.
15. **4.11.6 Data Visualization in MS Access (Charts).** Answers: 1. Line. 2. Pie (two parts of a whole).

Answer key

Multiple choice

1. b
2. c
3. c
4. b
5. b
6. c
7. b
8. b
9. b
10. b
11. d
12. c
13. b
14. c
15. b

Short questions — model answers

1. Data = raw facts (80, 75, 90). Information = processed meaning ("average is 81.7%, the class is ready").
2. Less redundancy, consistency, security (authorised access), integrity (valid, unique keys). (Sharing / backup also accepted.)
3. Record = one student's full row (101, Ali, CS, A). Field = one column such as Name.
4. PK uniquely identifies a row, cannot be NULL, one per table, lives in the parent. FK refers to a PK, may duplicate, may be NULL, lives in the child, creates the relationship.
5. It would duplicate attributes of both entities. Split into two 1:M links with a junction table that holds both FKs plus extra attributes (dates).
6. Every FK must match an existing parent PK. Inserting Result.StudentID = 999 is rejected if 999 is not in Student — that would have been an orphan.
7. Cascade Update copies a changed parent PK into child FKs. Cascade Delete removes child rows when the parent is deleted.
8. Table stores; form enters; query searches/filters; report prints.
9. They are identifiers, not quantities; leading zeros would vanish; you never add two numbers of a phone.
10. Put one value on the Criteria row and the other on the or: row of the same field (or of different fields if that is the question).

Long questions — model answers

1. Entities STUDENT and COURSE, relationship Enrolls (M:N). Junction ENROLLMENT(EnrollID PK, StudentID FK, CourseID FK, Date). Schema: Student(StudentID PK, Name, Class); Course(CourseID PK, Title); Enrollment as above. Diagram: 1 — M — M — 1 through the junction.
2. (a) Parent 101 Ali → 201 Ali; child Result rows that said 101 now say 201. (b) Delete parent 102 Sara; all Result and Enrolment rows with 102 disappear. Integrity definition: FK must match a live PK; this stops orphans and keeps reports true.
3. Follow steps 1–7 in the chapter. Sample: (5001, 102, B-17, 2026-10-05, NULL); (5002, 101, B-17, 2026-10-12, 2026-10-20) — same book, two members, no duplicated titles.
4. Create → Table Design; enter the five fields and types; right-click RollNo → Primary Key; Save as Student. Create → Form Wizard → Student → >> all fields → Columnar → name Student Registration → Finish.
5. Grid: Name, Department, Marks. Criteria under Department: "CS" (or "Computer Science"); Criteria under Marks: ≥ 80 (same row = AND); Sort under Name: Ascending. SQL: `SELECT Name, Department, Marks FROM Student WHERE Department="CS" AND Marks  $\geq 80$  ORDER BY Name`; Totals query: Department Group By, StudentID Count, Marks Avg.
6. (i) Column or bar — compare categories (classes). (ii) Pie — each class is a part of one whole enrolment. (iii) Line — a trend over years.

Self-assessment: I can...

- | | |
|--|---|
| ☐ explain data vs information vs database vs DBMS. | ☐ point at records and fields in a table. |
| ☐ choose PK / FK / candidate / alternate keys correctly. | ☐ draw ER symbols and label 1:1, 1:M, M:N. |
| ☐ resolve M:N with a junction table. | ☐ explain referential integrity and both cascade operations with examples. |
| ☐ write a relational schema including the library case study. | ☐ match tables, forms, queries and reports to a task. |
| ☐ create a table in Design View and pick data types. | ☐ build a Wizard form and a criteria query (AND, OR, totals). |
| ☐ choose bar, column, pie or line for a given question. | |

Lecture 05

Application and Impacts of Computing

Chapter lecture — 12 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XI · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — گیارہویں جماعت

12 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XI

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیئریر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

Lectures in this pack

Chapter 5: Application and Impacts of Computing. Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 5.1 Introduction to Computing Impacts

L03. 5.1.2 Internet of Things (IoT) & Components

L05. Table: IoT vs AI vs Data Analytics Comparison

L07. 5.2.1 Scope of AI in Education in Pakistan

L09. 5.4 Impacts of Computing in Various Fields

L11. 5.5.1 Importance of Assistive Technologies

L02. 5.1.1 Artificial Intelligence (AI)

L04. 5.1.3 Data Analytics & Components

L06. 5.2 Uses of IoT in Different Areas

L08. 5.3 Information Sources (Primary, Secondary, Tertiary)

L10. 5.5 Assistive Technologies

L12. 5.5.2 Career Connection in Assistive Tech

Application and Impacts of Computing

This chapter shows you how computing technologies such as Artificial Intelligence, the Internet of Things and Data Analytics are changing life in Pakistan — in cities, hospitals, farms and classrooms. You will also learn how to judge information sources, weigh the good and bad effects of computing, and see how assistive technologies give everyone an equal chance.

اس باب میں آپ سیکھیں گے کہ مصنوعی ذہانت (AI)، انٹرنیٹ آف تھنگز (IoT) اور ڈیٹا اینالیٹکس ہماری روزمرہ زندگی کو کیسے بدل رہے ہیں۔ آپ معلومات کے ذرائع کو پرکھنا، کمپیوٹنگ کے مثبت اور منفی اثرات سمجھنا، اور معذور افراد کی مدد کرنے والی ٹیکنالوجی کے بارے میں بھی جانیں گے۔

What you will learn

- Explain what Artificial Intelligence (AI) is and give everyday examples of it.
- Name and explain the six components of an IoT system, with examples of each.
- Compare IoT, AI and Data Analytics by definition, purpose, type of work and output.
- Discuss the uses, benefits and challenges of AI in education in Pakistan.
- Analyse positive and negative impacts of computing in five fields, and practise responsible use.
- Describe how IoT, Data Analytics and AI work together in a smart system.
- List the five components of Data Analytics in the correct order.
- Describe uses of IoT in smart cities, industry, healthcare, education, homes and farming.
- Classify information sources as primary, secondary or tertiary, and judge when a source is unreliable.
- Explain the four categories of assistive technologies, their importance, and related careers.

5.1 Introduction to Computing Impacts

LEARN IT

Computing means using computers and computer-based devices to store, process and share information. Today computing is an important part of your daily life. You use computers, mobile phones, the internet and smart devices almost everywhere — at home, in college and on the road.

In Pakistan, computing is becoming **vital** (very necessary) in:

- **Schools and colleges** — online admissions, e-books, online results of the Sindh boards.
- **Hospitals** — computerised patient records, digital X-rays, online appointment systems.
- **Banks** — ATMs, mobile banking apps, Raast instant payments, JazzCash and Easypaisa wallets.
- **Farms** — weather forecasts on mobile phones, soil sensors, tube-well control.
- **Industries** — automatic machines in textile mills in Karachi, Hyderabad and Faisalabad.

An **impact** is the effect something has on people and society. Computing has **positive impacts** (speed, convenience, new jobs) and **negative impacts** (privacy risks, addiction, job loss). In this chapter you will study three key technologies first — AI, IoT and Data Analytics — and then their uses and impacts.

WORKED EXAMPLE

A day in Sara's life in Karachi — spot the computing:

Step 1. 7:00 am — Her phone unlocks by recognising her face (AI).

Step 2. 7:30 am — She books a ride on a ride-hailing app; GPS shows the car's location (internet + location data).

Step 3. 9:00 am — College attendance is marked by a biometric (fingerprint) machine (IoT).

Step 4. 2:00 pm — She pays her fee through a mobile banking app (computing in business).

Step 5. 8:00 pm — YouTube suggests a physics lecture based on what she watched yesterday (AI).

Conclusion: in a single day, Sara uses computing in at least five different fields without even thinking about it.

اردو میں سمجھیں

کمپیوٹنگ آج ہماری روزمرہ زندگی کا اہم حصہ بن چکی ہے۔ پاکستان میں اسکول، اسپتال، بینک، کھیت اور صنعتیں سب کمپیوٹر اور انٹرنیٹ پر انحصار کرنے لگے ہیں۔ کمپیوٹنگ کے فائدے بھی ہیں اور نقصانات بھی، جنہیں ہم اس باب میں سمجھیں گے۔

CHECK YOURSELF

1. Name four places in Pakistan where computing has become vital.
2. What is meant by the "impact" of computing?

Answers: 1. Any four of: schools, hospitals, banks, farms, industries. 2. The effect computing has on people and society — it can be positive or negative.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Computing is now part of:

- a. Daily life — phones, banks, schools
- b. Only museums
- c. Only NAND labs
- d. Only OSI textbooks

MCQ 2. An impact can be:

- a. Positive or negative
- b. Only positive
- c. Only hardware heat
- d. Only Big O

MCQ 3. This unit's three big technologies are:

- a. AI, IoT, Data analytics
- b. Only bubble sort
- c. Only Access forms
- d. Only Figma

MCQ 4. A smart meter is closest to:

- a. IoT
- b. A primary key
- c. A K-map
- d. A sprint

MCQ 5. Predicting fail risk from marks is:

- a. Data analytics / AI
- b. Physical cabling
- c. A pie only
- d. Waterfall always

MCQ 6. Students must also learn:

- a. Limits and ethics, not only hype
- b. That computers never fail
- c. That data is always true
- d. That IoT needs no internet

Extra short questions

1. Give two daily computing uses in Pakistan.
2. Why study impacts, not only coding?
3. Name the three tools this chapter compares.
4. One negative impact.

Extra long question

1. Write a balanced 10-mark intro: three benefits of computing in a Sindh college and three harms, with one mitigation each.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. JazzCash/Easypaisa; NADRA records; online boards; WhatsApp classrooms — any two.
2. Technology changes jobs, privacy, inequality — exams ask both sides.
3. AI, IoT, data analytics.
4. Job displacement, addiction, surveillance, e-waste.

Long

1. Benefits: attendance systems, online notes, analytics of results. Harms: distraction, data leaks, unfair access. Mitigations: phone policy, passwords/backups, lab hours for students without devices.

5.1.1 Artificial Intelligence (AI) ★ Golden

LEARN IT

Artificial Intelligence (AI) is the ability of a computer system to perform tasks that normally need human thinking, such as recognising faces, understanding language and making decisions.

Understand the name in two parts:

- **Artificial** — It is *created by humans*; it is not natural.
- **Intelligence** — It can perform tasks that *require thinking*.

AI systems **use data to make decisions**. The more good data an AI system sees, the better it becomes at recognising patterns (repeating features) and predicting what to do.

Examples from the source:

1. **Face recognition** on a mobile phone to unlock the screen.
2. **YouTube suggesting videos** based on your interests.
3. **Chatbots** answering questions on a website (for example, a bank's help chat).

More Pakistani examples: Google Maps predicting traffic on Shahrāh-e-Faisal, Urdu voice typing on your phone, banks flagging a suspicious card transaction, and AI tools that translate English into Urdu.

AI in smart systems

AI rarely works alone. It often acts as the **"brain"** of a system, working together with the **Internet of Things (IoT)** and **Data Analytics**:

- **IoT devices gather data** — they are the "eyes" (sensors).
- **Analytics sorts the data** — it organises and studies it.
- **AI makes the final decision** — it is the "brain".
- **An action follows** — something happens in the real world.



WORKED EXAMPLE

Smart air-conditioner in a hot Hyderabad room — trace the system:

Step 1 (IoT – eyes). A temperature sensor reads the room temperature: 36 °C.

Step 2 (Analytics). The readings of the last 10 minutes are organised: 34, 35, 35, 36 °C — the room is getting hotter.

Step 3 (AI – brain). The AI compares this with the comfortable limit (say 26 °C) and with the fact that a person is in the room (motion sensor). Decision: "Turn the AC on."

Step 4 (Action). A switch turns the AC on automatically.

No human pressed a button — the system sensed, thought and acted.

REMEMBER IT

Eyes – Sort – Brain – Do. IoT is the eyes, Analytics sorts, AI is the *brain*, and the actuator *does* the action. Think of a cricket fielder: his eyes see the ball (IoT), he judges speed and direction (analytics), decides to dive (AI), and his body moves (action).

COMMON MISTAKE

Mistake: "AI means robots." **Fix:** Most AI is just *software* — YouTube suggestions, spam filters and face unlock have no robot body. A robot may use AI, but AI itself is the *thinking software*.

اردو میں سمجھیں

مصنوعی ذہانت (AI) کو "مصنوعی" اس لیے کہتے ہیں کہ اسے انسانوں نے بنایا ہے، اور "ذہانت" اس لیے کہ یہ ایسے کام کر سکتی ہے جن کے لیے سوچنا پڑتا ہے۔ AI دینا کی مدد سے فیصلے کرتی ہے، جیسے چہرہ پہچان کر فون کھولنا یا یوٹیوب پر ویڈیوز تجویز کرنا۔ ایک اسمارٹ سسٹم میں IoT آٹکھوں کا کام کرتا ہے اور AI دماغ کا۔

EXAM TIP

Common questions: "Define AI and give two examples" (2–3 marks), and "Explain how AI, IoT and Data Analytics work together" (4–5 marks).

To score full marks: (1) write the two-part meaning of the name — *artificial = made by humans, intelligence = can think/decide*; (2) say "AI uses data to make decisions"; (3) give at least two examples; (4) for the "together" question, draw the flow IoT → Analytics → AI → Action and explain it with the room-AC example.

CHECK YOURSELF

1. Why is AI called "artificial"?
2. In a smart system, which technology is the "brain" and which is the "eyes"?
3. Is a spam filter in Gmail an example of AI? Why?

Answers: 1. Because it is created by humans. 2. AI is the brain; IoT is the eyes. 3. Yes — it uses data (past spam emails) to decide whether a new email is spam, a task that needs "thinking".

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. AI is:

- a. Machines performing tasks that need human intelligence
- b. Any Excel sheet
- c. A copper cable
- d. A primary key

MCQ 2. Machine learning is AI that:

- a. Learns patterns from data
- b. Only follows a fixed 5-line script forever
- c. Is analog only
- d. Is a pie chart

MCQ 3. A chatbot is an:

- a. AI application
- b. OSI hub
- c. AND gate
- d. MVP canvas

MCQ 4. AI needs:

- a. Data + model + compute
- b. Only a mouse
- c. Only paper
- d. Only Agile stickers

MCQ 5. An exam risk of AI answers is:

- a. Hallucination / wrong confident text
- b. Too much NAND
- c. Too much OSI
- d. Too much bubble sort

MCQ 6. This is a ★ topic because papers ask:

- a. Definition + examples + one issue
- b. Only cabling colours
- c. Only Access wizards
- d. Only Big O proofs

Extra short questions

1. Define AI with two examples.
2. AI vs ordinary software.
3. One benefit and one risk in exams/education.
4. Name two Pakistani/education uses.

Extra long question

1. Explain AI to a Class XI student: definition, two components, two applications, two ethical issues. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Intelligence in machines. Face unlock; Google Translate; board-result chatbots.
2. Ordinary: fixed rules. AI: improves from data / handles messy input.
3. Benefit: tutoring. Risk: cheating / wrong answers.
4. Urdu OCR; adaptive quizzes; NADRA biometrics (accept reasonable).

Long

1. Def. Data+algorithms(+sensors). Apps: health imaging, spam filter. Ethics: bias, privacy, job loss. One sentence on human remaining responsible.

5.1.2 Internet of Things (IoT) & Components

LEARN IT
The **Internet of Things (IoT)** is a system in which **physical devices are connected to the Internet** and can **collect and share data** to perform tasks **automatically**.
The "things" are ordinary objects — watches, cameras, cars, fans, water pumps — that have been given sensors and an Internet connection so they can "talk" to each other and to us.
Source example: A **smartwatch** collects your heart-rate data and sends it to your mobile phone, where it is displayed.

Components of IoT systems
IoT relies on **six foundational components** to work properly.

#	Component	What it does	Examples
1	Sensors	Devices that collect information from the physical world. They are the "eyes and ears" of the system.	Temperature sensor, motion sensor, fingerprint sensor, smoke sensor, soil moisture sensor
2	Actuators	Devices that perform physical actions in response to system commands. They convert digital signals into physical movements.	Electric motor, switch, automatic door opener, water valve, fan controller
3	Connectivity	The connection that allows devices to send and receive data . Without it, sensors can't talk to the system.	Wi-Fi, Bluetooth, ZigBee, 4G/5G
4	Data Processing	Changing raw data into useful information . Steps: collecting, organising, analysing and deciding.	Checking if the room temperature is too hot to trigger the AC
5	Cloud Computing	Storing data and using services over the Internet instead of local hard drives. Handles massive IoT data.	Google Drive, iCloud, online LMS
6	User Interface (UI)	The component that enables interaction between the user and the device . Helps users see information and give commands.	Mobile apps, touch screens, voice commands

Understanding each component
Sensors turn something in the real world (heat, movement, a fingerprint, smoke, wetness of soil) into data. A smoke sensor in a Karachi shopping mall "smells" smoke and reports it.
Actuators do the opposite: they take a digital command and make something move or change. The water valve that opens, the motor that turns, the door that slides open at a bank entrance.
Connectivity is the "road" for data. Short distances use Bluetooth (watch to phone); a house uses Wi-Fi; low-power sensor networks use **ZigBee**; devices far away in fields use mobile networks (4G/5G from Jazz, Zong, Telenor/Ufone).
Data processing is where raw numbers ("36") become meaning ("too hot — turn on AC"). Its four steps are collect → organise → analyse → decide.
Cloud computing stores and processes the huge amount of data that thousands of sensors produce every second — far more than a single small device can hold.
User interface is how you see the data and give orders — an app on your phone, a touch screen on a smart fridge, or saying "Hey Google, turn off the lights".

How the components connect



The six IoT components working as one system (data processing happens inside the cloud).

WORKED EXAMPLE
Smart fire alarm in a Karachi factory — identify all six components:
Step 1 — Sensor: A smoke sensor detects smoke near the machines.
Step 2 — Connectivity: It sends the reading over the factory Wi-Fi.
Step 3 — Cloud computing: The reading is stored on an online server along with the history of all sensors.
Step 4 — Data processing: The software checks: "Is the smoke level above the safe limit?" Yes → decide "Fire risk!"
Step 5 — Actuator: Water valves of the sprinklers open and the alarm bell switch turns on.
Step 6 — User interface: The manager's mobile app shows a red alert: "Smoke detected — Hall 3".

REMEMBER IT
Sensor senses, Actuator acts. Both words give you the answer: sensor = see/sense (input), actuator = act (output). Remember the six components with "Some Acts Carry Data Carefully Up" — Sensors, Actuators, Connectivity, Data processing, Cloud, UI.

COMMON MISTAKE
Mistake: Calling a fan controller or water valve a "sensor". **Fix:** Ask "does it measure something or do something?" A valve opens and closes — it does, so it is an **actuator**. A soil moisture sensor *only measures*, so it is a **sensor**.

آرڈو میں سمجھیں

انٹرنیٹ آف ٹھنگز (IoT) ایک ایسا نظام ہے جس میں مختلف آلات (جیسے گھڑیاں، کیچر، گاڑیاں) انٹرنیٹ سے جڑے ہوتے ہیں اور خودکار طریقے سے دیتا جمع اور شیئر کرتے ہیں۔ اس کی وجہ بنیادی اجزاء ہیں: سینسز (معلومات جمع کرتے ہیں)، ایکچوئرز (جسمانی کام انجام دیتے ہیں، جیسے موٹر چلانا یا دروازہ کھولنا)، کنیگٹیویٹی (وائی فائی، بلوٹوتھ) دیتا پروسیسنگ، کلاؤڈ کمپیوٹنگ، اور یوزر انٹرفیس (موبائل ایپ)۔

EXAM TIP
"Define IoT and explain its components" is one of the most frequent long questions. Write the definition with the three key ideas — physical devices, connected to the Internet, collect and share data automatically. Then list all six components, each with a one-line meaning and one example. A labelled flow diagram (Sensor → Wi-Fi → Cloud → Actuator → App) earns extra credit.
Short questions often ask: "Differentiate between a sensor and an actuator" — sensor collects data (input, eyes and ears), actuator performs physical action (output, converts digital signals into movement).

CHECK YOURSELF
1. Classify as sensor or actuator: (a) fingerprint scanner, (b) automatic door opener, (c) motion detector, (d) electric motor.
2. Name four types of connectivity used in IoT.
3. Why is cloud computing needed in IoT?
Answers: 1. (a) sensor, (b) actuator, (c) sensor, (d) actuator. 2. Wi-Fi, Bluetooth, ZigBee, 4G/5G. 3. Because IoT devices produce massive amounts of data; the cloud stores and processes it over the Internet instead of on small local hard drives.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. IoT is: a. Physical devices on the Internet sharing data b. Only desktop Word c. Only K-maps d. Only sprits	MCQ 2. A typical IoT chain is: a. Sensor → connectivity → data → action b. Query → form → report only c. SYN → ACK only d. Bubble → selection	MCQ 3. Connectivity might be: a. Wi-Fi, 4G, Bluetooth b. A primary key c. A pie chart d. A NAND-only bus	MCQ 4. An actuator: a. Does something in the real world (motor, relay) b. Only stores SQL c. Only sorts d. Only prints Urdu	MCQ 5. Without connectivity, sensors: a. Cannot send readings b. Become RDBMS c. Become AI models d. Become OSI layer 7	MCQ 6. A smart irrigation valve is IoT because: a. It senses, sends, and acts remotely b. It is made of paper c. It runs bubble sort d. It is a form wizard
---	--	---	--	--	--

Extra short questions

- Define IoT.
- List four components.
- Give a farm example.
- One security worry.

Extra long question

- Draw the IoT component diagram for a smart classroom (lights, attendance, AC). Label each component and one risk. ★ Golden.

Extra answer key
MCQs: 1. A 2. A 3. A 4. A 5. A 6. A
Short
1. Internet of Things: physical objects with sensors/software that connect and exchange data.
2. Devices/sensors, connectivity, data processing, user interface / actuators.
3. Soil moisture sensor → mobile network → app → pump on/off.
4. Unpatched cameras on the Internet; weak default passwords.
Long
1. Sensors (PIR, RFID), Wi-Fi, college server/analytics, dashboard, relays for lights. Risk: student location privacy. Mitigation: local processing, access control.

5.1.3 Data Analytics & Components

LEARN IT

Data Analytics is the process of **collecting, organising, cleaning, studying and presenting data** to find useful information. It helps people make better decisions.

Data means raw facts and figures (for example, "72, 45, 88"). **Information** is data that has been processed so it has meaning ("All scored 72%; he passed"). Data Analytics is the bridge from data to information.

Source example: A college collects exam marks, calculates percentages, and identifies which students need extra help. This entire process is Data Analytics.

Components of Data Analytics

Data Analytics comprises **five key components**, which happen in order like a pipeline:



- Data Collection** — Gathering raw information from multiple sources: websites, surveys, sensors, hospital records, bank transactions.
- Data Storage** — Storing data safely and properly after collection. It can be stored in files, databases, spreadsheets or the cloud.
- Data Cleaning** — Identifying and correcting errors in data. Raw data may contain:
 - **Duplication** of records (the same student entered twice),
 - **Incorrect values** (typos, e.g. marks "870" instead of "87"),
 - **Missing** files or records (a student's marks not entered),
 - **Improper formats** (dates written as 05/10/2026 in one place and "5 Oct 26" in another).
- Data Analysis** — Studying the clean data to identify patterns, trends and relevant information for problem-solving (e.g. finding out which subjects students failed the most).
- Data Visualization** — Creating visual representations of data (plots, charts, graphs) to provide valuable insights at a glance (e.g. a pie chart showing pass vs fail percentage).

WORKED EXAMPLE

A college in Sukkur analyses Physics test results (out of 50) for 6 students.

Step 1 — Collection: Marks are gathered from the teacher's register.

Roll No	Name	Marks (raw)
1	Ayesha	42
2	Bilal	18
3	Hina	35
3	Hina	35
4	Kashif	250
5	Sana	(missing)

Step 2 — Storage: The marks are typed into a spreadsheet saved on Google Drive (cloud).

Step 3 — Cleaning: Hina's record is a *duplicate* → delete one copy. Kashif's 250 is an *incorrect value* (more than 50) → the register shows 25, so correct it. Sana's marks are *missing* → ask the teacher; she was absent, so mark her "absent".

Step 4 — Analysis: Clean marks: 42, 18, 35, 25. Pass mark is 17 (33% of 50 = 16.5, rounded up). All 4 passed. Percentages: Ayesha 84%, Bilal 36%, Hina 70%, Kashif 50%. Average = $(42 + 18 + 35 + 25) \div 4 = 120 \div 4 = 30$ marks = 60%. Bilal is closest to failing → needs extra help.

Step 5 — Visualization: A bar chart shows each student's percentage; Bilal's short bar makes the problem visible at a glance.

REMEMBER IT

"Cows Sit Calmly And Vote" — Collection, Storage, Cleaning, Analysis, Visualization. Or think of cooking daal: buy the lentils (collect), keep them in a jar (store), pick out stones (clean), cook (analyse), serve beautifully on a plate (visualise).

COMMON MISTAKE

Mistake: Skipping cleaning and going straight to analysis. **Fix:** Dirty data gives wrong answers. In the example, Kashif's wrong "250" would have made the average $(42 + 18 + 35 + 250) \div 4 = 86.25$ — more than 50, which is impossible. Always clean first.

آرڈو میں سمجھیں

ڈیٹا اینالائٹکس ڈیٹا کو جمع کرنے، ترتیب دینے، صاف کرنے، اس کا مطالعہ کرنے اور پیش کرنے کا عمل ہے تاکہ مفید معلومات حاصل ہوں اور بہتر فیصلے کیے جا سکیں۔ اس کے پانچ اجزاء ہیں: ڈیٹا جمع کرنا، محفوظ کرنا، صاف کرنا (غلطیاں اور دہرائے گئے ریکارڈ ہٹانا)، تجزیہ کرنا، اور چارٹ یا گراف کی صورت میں دکھانا۔

CHECK YOURSELF

- List the five components of Data Analytics in order.
- Name four kinds of errors removed during data cleaning.
- A pie chart of pass/fail percentage belongs to which component?

Answers: 1. Collection, Storage, Cleaning, Analysis, Visualization. 2. Duplicate records, incorrect values (typos), missing records, improper formats. 3. Data Visualization.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Data analytics is:

- Collect, clean, study, present data for decisions
- Only drawing NAND
- Only cabling
- Only Figma

MCQ 2. Cleaning data means:

- Fixing missing/wrong values
- Washing the PC
- Defrag only
- Sorting OSI layers

MCQ 3. A dashboard is:

- A visual summary of analytics
- A primary key
- A sprint log only
- A K-map

MCQ 4. Analytics without a question is:

- Just a pile of charts
- Always AI
- Always IoT
- Always SQL keys

MCQ 5. Finding that "second shift falls more in CS" is:

- Insight from analysis
- A foreign key
- A gate delay
- A beachhead

MCQ 6. Python's later tool for this in XII is:

- Pandas + charts
- LogSim
- Figma only
- Access macros only

Extra short questions

- Define data analytics and list its steps.
- Why clean first?
- Give a college decision driven by analytics.
- How is analytics different from IoT?

Extra long question

- A principal has 3 years of BIEK results. Outline an analytics project: source, clean, one chart, one decision.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Collect → organise/clean → analyse → present → decide.
- Garbage in, garbage out — mean of marks with blanks is wrong.
- Extra classes for a subject whose fail rate jumped.
- IoT gathers live device data; analytics is the studying/presenting (often of that data).

Long

- Source: gazette CSVs. Clean: missing roll numbers. Chart: line of pass% by year. Decision: change lab hours if practical marks drag theory. Mention ethics (no public shaming of named students).

Table: IoT vs AI vs Data Analytics Comparison

LEARN IT These three technologies are often used together, so students mix them up. The table below, from the source, compares them on four aspects.			
Aspect	IoT	Artificial Intelligence (AI)	Data Analytics
Definition	Network of physical devices connected to the internet.	Technology enabling machines to think and decide.	Process of examining data to find patterns.
Main purpose	Data collection and automation.	Intelligent decision making and predictions.	Extracting meaningful insights.
Type of work	Works with physical devices (hardware).	Works with smart software systems.	Works with data (numbers, records).
Output	Raw data from the environment.	Smart decisions or actions.	Reports, graphs, insights.
Role in a smart system	Eyes and hands	Brain	Organiser / reporter
Pakistani example	Safe City cameras in Lahore/Karachi capturing traffic	Software recognising a car's number plate for an e-challan	Monthly report showing which roads have the most violations
WORKED EXAMPLE One problem, three technologies — a K-Electric smart meter: IoT: The smart electricity meter measures units used every 15 minutes and sends them over the mobile network. Output: raw readings. Data Analytics: The company cleans and studies a month of readings and draws a graph showing that most electricity is used between 7 pm and 11 pm. Output: report/graph. AI: Software learns each area's pattern, predicts tomorrow's demand, and decides how to plan load management. Output: smart decision.			
REMEMBER IT Ask "What is the output?" Raw readings → IoT. Charts and reports → Data Analytics. A decision or prediction → AI.			
COMMON MISTAKE Mistake: Writing that IoT "makes decisions". Fix: In the comparison table IoT's main purpose is <i>data collection and automation</i>; the <i>intelligent decision</i> belongs to AI.			
اردو میں سمجھیں IoT جسمانی آلات (ہارڈویئر) کا نیٹ ورک ہے جو ماحول سے خام ڈیٹا جمع کرتا ہے۔ AI ذہین سافٹ ویئر ہے جو فیصلے اور پیش گوئیاں کرتا ہے۔ ڈیٹا اینالیٹکس ڈیٹا کا جائزہ لے کر رپورٹس اور گراف بناتا ہے۔ تینوں مل کر ایک اسمارٹ نظام بناتے ہیں۔			

CHECK YOURSELF

1. Which of the three works mainly with hardware?

2. What is the output of Data Analytics?

Answers: 1. IoT. 2. Reports, graphs and insights.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Data analytics is:

a. Collect, clean, study, present data for decisions

b. Only drawing NAND

c. Only cabling

d. Only Figma

MCQ 2. Cleaning data means:

a. Fixing missing/wrong values

b. Washing the PC

c. Defrag only

d. Sorting OSI layers

MCQ 3. A dashboard is:

a. A visual summary of analytics

b. A primary key

c. A sprint log only

d. A K-map

MCQ 4. Analytics without a question is:

a. Just a pile of charts

b. Always AI

c. Always IoT

d. Always SQL keys

MCQ 5. Finding that "second shift fails more in CS" is:

a. Insight from analysis

b. A foreign key

c. A gate delay

d. A beachhead

MCQ 6. Python's later tool for this in XII is:

a. Pandas + charts

b. LogiSim

c. Figma only

d. Access macros only

Extra short questions

1. Define data analytics and list its steps.

2. Why clean first?

3. Give a college decision driven by analytics.

4. How is analytics different from IoT?

Extra long question

1. A principal has 3 years of BIEK results. Outline an analytics project: source, clean, one chart, one decision.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Collect → organise/clean → analyse → present → decide.

2. Garbage in, garbage out — mean of marks with blanks is wrong.

3. Extra classes for a subject whose fail rate jumped.

4. IoT gathers live device data; analytics is the studying/presenting (often of that data).

Long

1. Source: gazette CSVs. Clean: missing roll numbers. Chart: line of pass% by year. Decision: change lab hours if practical marks drag theory. Mention ethics (no public shaming of named students).

5.2 Uses of IoT in Different Areas

LEARN IT

IoT improves efficiency (doing more with less effort), saves time, and enhances the overall quality of life. It plays a significant role in developing modern infrastructure (the basic systems of a country — roads, power, water, hospitals). The source lists six areas.

1. Smart Cities

- Traffic management:** Sensors adjust traffic signals automatically to reduce congestion (crowding). Example: signals on a busy Karachi road stay green longer for the direction with more cars.
- Street lighting:** Lights turn ON/OFF based on daylight or movement, saving electricity.
- Parking:** Sensors guide drivers to empty parking spaces, e.g. in a large shopping mall car park.
- Waste management:** Smart bins send alerts when full, so trucks collect only full bins instead of driving to every bin.

2. Industrial Automation

- Sensors check machine temperature and vibration to prevent breakdowns (called predictive maintenance).
- Automated machines perform repeated tasks precisely.
- Quality-control sensors check products during manufacturing — for example, in the textile industries of Sindh, cameras and sensors spot faults in cloth as it is woven.

3. Healthcare (Smart Health)

- Smartwatches** continuously measure heart rate and vital signs (pulse, oxygen level).
- Remote monitoring devices** send patient data directly to doctors — vital for rural areas of Pakistan, where a specialist may be hundreds of kilometres away (e.g. a heart patient in Tharparkar monitored by a doctor in Karachi).
- Emergency alert devices** inform hospitals instantly, for example when an elderly person falls.

4. Education (Smart Learning)

- Smart classrooms:** digital boards and connected projectors.
- Attendance systems:** biometric automated attendance for students and teachers (used in many Sindh government schools and colleges).
- Resource management:** automated classroom lighting and AC control — off when the room is empty.

5. Home Automation

- Smart lighting:** controlled remotely via mobile apps.
- Security:** real-time monitoring via Wi-Fi cameras — you can watch your house gate on your phone.
- Voice control:** using assistants (like Alexa or Google Assistant) to control TVs and appliances.

6. Smart Farming

Smart farming is crucial for agriculture in Pakistan (especially Sindh and Punjab) to save water and improve yields (the amount of crop produced).

- Soil moisture sensors:** check if crops actually need water.
- Automated irrigation:** turns water pumps ON/OFF based on soil data.
- Drones:** monitor crop health from above, spotting disease or dry patches.

Smart farming process:



WORKED EXAMPLE

A cotton farmer near Nawabshah uses smart irrigation:

- Step 1.** A soil moisture sensor in the field reads 18% moisture.
 - Step 2.** It sends the reading over the 4G network to a cloud service.
 - Step 3.** The cloud AI checks: cotton needs at least 25% moisture, and the weather forecast shows no rain → decision "Needs water: YES".
 - Step 4.** The actuator (pump switch) turns the tube-well ON.
 - Step 5.** When moisture reaches 30%, the AI decides "enough" and the pump turns OFF.
- Result: water is used only when needed — important because Sindh faces water shortages — and the farmer sees everything on his phone app.

REMEMBER IT

Remember the six areas with "CHIEF H": Cities, Health, Industry, Education, Farming, Homes.

COMMON MISTAKE

Mistake: Giving only the name of the area ("smart cities") in an exam answer. **Fix:** Always add what IoT does there — e.g. "smart bins send alerts when full" — and, if possible, a Pakistani example.

اردو میں سمجھیں

IoT کارکردگی بہتر بناتا ہے، وقت بچاتا ہے اور زندگی کا معیار بلند کرتا ہے۔ اسمارٹ شہروں میں ٹریفک سگنل اور اسٹریٹ لائٹس خود کار ہوتی ہیں، اسپتالوں میں مریضوں کا ڈیٹا براہ راست ڈاکٹر تک پہنچتا ہے، اور کھیتوں میں مٹی کی نمی کیے سینسر بتاتے ہیں کہ فصل کو پانی چاہیے یا نہیں، جس سے سندھ اور پنجاب میں پانی کی بچت ہوتی ہے۔

CHECK YOURSELF

- 1. How do smart bins help waste management?
- 2. Why is remote health monitoring especially useful in Pakistan?
- 3. In smart farming, which device is the actuator?

Answers: 1. They send alerts when full, so only full bins are emptied. 2. Rural areas lack doctors; devices send patient data directly to doctors far away. 3. The water pump (its switch).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Smart cities use IoT for:

- a. Traffic, waste, lighting
- b. Only K-maps
- c. Only sprints
- d. Only Access reports

MCQ 2. Health IoT example:

- a. Remote heart-rate monitor
- b. Bubble sort
- c. Primary keys
- d. Figma frames

MCQ 3. Farms use IoT to:

- a. Water when soil is dry
- b. Compile C
- c. Draw ER
- d. Write OSI

MCQ 4. Homes: a smart lock is IoT if:

- a. It is on the network and reports/acts
- b. It is a mechanical padlock only
- c. It is a Python tuple
- d. It is a pie

MCQ 5. Education IoT:

- a. RFID attendance, smart boards
- b. Only textbooks
- c. Only NAND labs
- d. Only waterfalls

MCQ 6. A risk in all these areas:

- a. Privacy / hacked devices
- b. Too much paper
- c. Too few charts
- d. Too much Big O

Extra short questions

- 1. Four application areas of IoT from the book.
- 2. One benefit in health.
- 3. One farm sensor + actuator pair.
- 4. Why security matters more as IoT grows.

Extra long question

- 1. Pick city, hospital, farm. For each: one device, one data item, one action, one risk.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- 1. Cities, health, farms, homes, industry, education — any four.
- 2. Doctors see vitals without the patient travelling.
- 3. Moisture sensor + water pump.
- 4. More doors into private spaces (cameras, locks).

Long

- 1. City: traffic cam / count / signal / surveillance. Hospital: SpO2 / alert nurse / false alarm. Farm: moisture / pump / overwater if sensor fails.

5.2.1 Scope of AI in Education in Pakistan

LEARN IT

Artificial Intelligence is gradually becoming an important part of Pakistan's education system, improving **teaching, learning and administration** (managing the school: admissions, records, timetables).

Practical uses:

- Learning Management Systems (LMS) — online platforms (e.g. Google Classroom, Moodle) where teachers post lessons and assignments; AI features can recommend lessons to each student.
- Automated grading and digital testing — MCQ tests marked instantly by computer.
- AI-based career counselling — software that studies a student's marks and interests and suggests suitable fields.

Benefits:

- Helps students learn **at their own speed**.
- Identifies students who need extra help.
- Supports students with disabilities (**Assistive AI**), e.g. text-to-speech for a visually impaired student.

Major challenges in Pakistan:

- Limited **internet access in rural areas**.
- Lack of **computers and digital devices** for all students.
- Need for proper **teacher training** to use AI tools.
- Data privacy and security** issues — students' personal data must be protected.

Practical uses	Benefits	Challenges
LMS	Learn at own speed	Limited rural internet
Automated grading & digital testing	Identifies students needing help	Lack of computers/devices
AI career counselling	Supports students with disabilities	Teacher training needed
—	—	Data privacy & security

WORKED EXAMPLE

Scenario — Fatima in Larkana and an AI tutor app:

Step 1. Fatima takes a 10-question online maths quiz on the college LMS. It is graded instantly (automated grading).

Step 2. The AI notices she got all 3 trigonometry questions wrong.

Step 3. It recommends two short videos and five easy practice questions on trigonometry — she learns at her own speed.

Step 4. Her teacher's dashboard flags "Fatima – needs help in trigonometry" (identifies students who need help).

Challenge: At home Fatima's village has weak 3G signals, so the videos buffer — showing the rural internet challenge.

COMMON MISTAKE

Mistake: Writing that AI will replace teachers. Fix: The source says AI *improves* teaching and needs *teacher training* — teachers use AI as a tool; they are not replaced.

اردو میں سمجھیں

پاکستان کے تعلیمی نظام میں مصنوعی ذہانت آہستہ آہستہ اہم کردار ادا کر رہی ہے، جیسے لرننگ مینجمنٹ سسٹم (LMS)، خودکار جانچ اور کیریئر کونسلنگ۔ اس سے طلبہ اپنی رفتار سے سیکھ سکتے ہیں اور کمزور طلبہ کی نشاندہی ہوتی ہے، لیکن دیہی علاقوں میں انٹرنیٹ کی کمی، کمپیوٹرز کی قلت، اساتذہ کی تربیت اور ڈیٹا کی حفاظت بڑے چیلنج ہیں۔

CHECK YOURSELF

1. Give three practical uses of AI in education.

2. State any two challenges of AI in education in Pakistan.

Answers: 1. LMS, automated grading and digital testing, AI-based career counselling. 2. Any two: limited rural internet, lack of devices, need for teacher training, data privacy and security.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. AI in Pakistani classrooms can:

- Personalise practice, mark MCQs, translate
- Replace all teachers tomorrow by law
- Lay fibre
- Set primary keys

MCQ 2. A risk of AI homework tools is:

- Students submit work they cannot explain
- Faster bubble sort
- Better NAND
- Longer OSI

MCQ 3. Adaptive learning means:

- Difficulty changes with the student
- Everyone gets the same paper always
- No data is used
- Only analog TV

MCQ 4. Teachers still needed because:

- Care, judgment, fairness, lab skill
- AI cannot use electricity
- Books are illegal
- BIEK forbids computers

MCQ 5. Data used by education AI must be:

- Protected (student privacy)
- Posted publicly with names
- Sold always
- Ignored

MCQ 6. A realistic near-term use is:

- Urdu/English support and drill quizzes
- Fully autonomous colleges
- Replacing SDLC
- Replacing ER diagrams

Extra short questions

- Two uses of AI in education in Pakistan.
- Two limits.
- What should a student still be able to do unaided?
- One policy idea for a college.

Extra long question

- Write a balanced note: opportunities of AI for BIEK CS students vs three rules a college should set.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Language practice; auto-marking MCQs; plagiarism hints; accessibility readers.
- Bias, hallucinations, connectivity gaps, cheating.
- Explain the answer in the board paper without the chatbot.
- AI allowed for practice, banned in the exam hall; teach citation.

Long

- Opp: extra drills, Urdu help, code explainers. Rules: no AI in exams, no pasting private data into public bots, teacher reviews flagged work. Link to digital literacy.

10

5.3 Information Sources (Primary, Secondary, Tertiary) 🔗 📄


LEARN IT

Information sources are ways to find knowledge and data. The internet has vast information, but **not all of it is accurate**. Sources are divided into three main categories.

1. Primary sources give **original, firsthand information** straight from people, events or official records. They are **highly authentic** (genuine).
Examples: Interviews, photographs, diaries, NADRA official records.

2. Secondary sources contain information that has **already been collected and explained by someone else**. They **summarise or analyse primary data**.
Examples: textbooks, news reports, research papers, Pakistan Bureau of Statistics reports.

3. Tertiary sources provide **highly summarised and organised information** derived from both primary and secondary sources. They are used for **quick reference**.
Examples: encyclopedias, Wikipedia, dictionaries, handbooks.



The information pyramid: primary data is the base; each higher level is built from the levels below it and is more summarised.

Primary (firsthand)	Secondary (explained by others)	Tertiary (summarised, quick reference)
Interview with a flood victim in Dadu	Newspaper report on the 2022 floods	Encyclopedia entry "Floods in Pakistan"
Photograph taken at an event	Textbook chapter explaining the event	Wikipedia article
Personal diary or letter	Biography written by a historian	Dictionary
NADRA official records (CNIC data)	Pakistan Bureau of Statistics report analysing census data	Handbook / almanac of facts
Original survey responses	Research paper analysing the survey	Index or list of research papers
Sensor readings from an IoT weather station	TV news analysis of the weather	A school "fact sheet" on climate
Quaid-e-Azam's original speech recording	Article discussing the speech	Encyclopedia summary of his life

When do sources become unreliable?
In the digital age you must check facts carefully. A source is **unreliable** (cannot be trusted) if:

Source type	Reasons for unreliability
Primary	Information is incomplete, data is recorded incorrectly, or false information was deliberately provided.
Secondary	The information is outdated, lacks proper references/citations, or has not been verified by an expert.
Tertiary	Comes from an unknown/unverified website, or the information is oversimplified and misses key facts.

REMEMBER IT
Rule of thumb (Author – Date – References): If an online article does not state the **author's name**, the **date of publication**, or list its **references**, it should not be trusted for academic work. Remember **"ADR"** — like checking a bus has a driver, a route and a ticket before you board.

WORKED EXAMPLE

Classify these — worked solutions:

(a) **Your grandfather's handwritten diary from 1947.** Written by a person who lived through the event → **firsthand** → **Primary**.

(b) **A Dawn newspaper article analysing the budget.** A journalist collected facts and explained them → **Secondary**.

(c) **An Oxford English-Urdu dictionary.** Organised, summarised reference built from many sources → **Tertiary**.

(d) **A Bureau of Statistics report on literacy in Sindh.** It analyses census (primary) data → **Secondary**.

(e) **A photo you took of a road accident.** Original record of the event → **Primary**.

Method: Ask (1) "Was the creator there / is it the original record?" → Primary. (2) "Is someone explaining or analysing original data?" → Secondary. (3) "Is it a quick-reference summary of many sources?" → Tertiary.

CHECK YOURSELF

Exercise — classify these as Primary (P), Secondary (S) or Tertiary (T):

- A video interview with a cricketer after a match.
- Your Computer Science textbook.
- Wikipedia page on "Mohenjo-daro".
- A birth certificate issued by the union council.
- A research paper reviewing ten studies on smog in Lahore.
- A handbook of physics formulas.
- Original exam answer sheets of students.
- A TV news report summarising a court decision.

Answers: 1. P 2. S 3. T 4. P 5. S 6. T 7. P 8. S

COMMON MISTAKE
Mistake: Thinking "primary" means "most important" or "tertiary" means "useless". **Fix:** The names describe *how* the information is from the original event. Primary = straight from the source; tertiary = summarised summary. Each is useful for a different job. Also, Wikipedia is **tertiary** — not primary — because it summarises other sources.

آرڈو میں سمجھیں
معلومات کے ذرائع علم اور دنیا تلاش کرنے کے طریقے ہیں، جنہیں تین اقسام میں تقسیم کیا جاتا ہے: پرائمری ذرائع براہ راست اور اصل معلومات دیتے ہیں (جیسے انٹرویوز، تصاویر، ڈائری کا ریکارڈ)، سیکنڈری ذرائع وہ ہیں جن میں کسی اور نے پرائمری معلومات کی وضاحت یا تجزیہ کیا ہو (جیسے درسی کتابیں، خبریں)، تھرڈری ذرائع خلاصہ شدہ معلومات دیتے ہیں جیسے انسائیکلوپیڈیا، ویکی پیڈیا اور لغت۔ جس آن لائن مضمون میں مصنف کا نام تاریخ یا حوالہ جات نہ ہوں اس پر بھروسہ نہ کریں۔

EXAM TIP
Typical questions: "Differentiate between primary, secondary and tertiary sources with two examples each" (long/short), "Classify the following sources..." (MCQ/short), and "When does a source become unreliable?"
Write the definition key phrase for each — *firsthand/original, collected and explained by someone else, highly summarised for quick reference* — plus two examples each. Draw the pyramid with primary at the base. For unreliability, give one reason for each type and quote the author-date-references rule.

Extra board practice
These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A primary source is:

a. Original, first-hand
b. A summary of summaries
c. Always Wikipedia
d. A pie chart of rumours

MCQ 2. A secondary source is:

a. Someone else's analysis of primary material
b. Raw sensor logs only
c. Always false
d. A NAND gate

MCQ 3. A tertiary source is:

a. Highly summarised (encyclopaedia, textbook index)
b. A lab notebook
c. A witness interview
d. A packet capture

MCQ 4. Your own class survey is:

a. Primary
b. Tertiary
c. Always secondary
d. Not a source

MCQ 5. A newspaper report of that survey is:

a. Secondary
b. Primary always
c. Tertiary always
d. IoT

MCQ 6. Board papers want you to:

a. Judge reliability, not just copy Google
b. Use any blog
c. Ignore dates
d. Prefer unsigned forwards

Extra short questions

- Define the three source types with one example each.
- Which is a BIEK past paper for you as a student?
- One reliability test.
- Why tertiary is still useful.

Extra long question

- For a project "screen time vs grades", list two primary, two secondary, one tertiary source and how you would check each. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Primary: experiment, interview, sensor. Secondary: review article, textbook chapter discussing others. Tertiary: encyclopaedia, library catalogue.
- Primary: evidence of the exam; or secondary if you only read a guide about it — say so.
- Author, date, purpose, evidence, bias.
- Fast overview and pointers to better sources — not the final citation for a claim.

Long

- Primary: your survey, school lab logs. Secondary: a journalistic feature, a review paper. Tertiary: textbook definition of survey. Checks: sample size, date, conflict of interest.

5.4 Impacts of Computing in Various Fields

LEARN IT		
Computing has drastically changed society. It makes life faster and more connected , but it also brings challenges like privacy risks and technology addiction . For every field, think of both sides.		
Field	Positive impact (+)	Negative impact (-)
Education	Online classes, e-books and learning apps make studying highly flexible and accessible.	Excessive screen time reduces attention spans and causes physical health issues (eye strain, back pain).
Communication	Emails and video calls allow instant, global communication at almost zero cost (e.g. a WhatsApp video call to a relative in Dubai).	People interact less in person, leading to social isolation and reduced face-to-face skills.
Business	Online shopping, digital banking and automation dramatically improve speed and efficiency.	Traditional manual jobs are lost to machines; risk of severe cyber-attacks on banks.
Healthcare	Digital patient records and telemedicine allow doctors to treat remote patients accurately.	Patient data privacy is at risk if hospital servers are hacked.
Agriculture	Smart irrigation and weather forecasting massively increase crop yields.	Poor internet access in rural areas means many farmers cannot use these tools.

- Smart and responsible use
- Protect **personal information** and use **strong passwords** (long, with letters, numbers and symbols; never share your OTP or CNIC details with callers).
 - Do not share **fake news** or unverified WhatsApp forwards.
 - Balance **screen time** with physical sports and activities.

WORKED EXAMPLE

Scenario analysis — a bank in Karachi moves to mobile banking:

Step 1 — Identify the field: Business (banking).

Step 2 — Positive: Customers transfer money in seconds from home; no queue at the branch; the bank processes more transactions with fewer staff (speed and efficiency).

Step 3 — Negative: Some cashier jobs are no longer needed (job loss); hackers may attempt cyber-attacks or phishing SMS to steal accounts.

Step 4 — Responsible use: Customers should use strong passwords, never share OTPs, and report suspicious messages.

REMEMBER IT

For the five fields, remember **"E-C-B-H-A"** — Education, Communication, Business, Healthcare, Agriculture — and always write one + and one – for each.

COMMON MISTAKE

Mistake: Writing only positive impacts in a "discuss the impacts" question. **Fix:** "Impact" means both sides. Examiners expect a balanced answer: advantages, disadvantages, and how to use technology responsibly.

اردو میں سمجھیں

کمپیوٹنگ نے معاشرے کو بہت بدل دیا ہے۔ تعلیم، مواصلات، کاروبار، صحت اور زراعت میں اس نے کام تیز اور آسان بنائے ہیں، لیکن اس کے ساتھ اسکرین کی لت، سماجی تنہائی، ملازمتوں کا خاتمہ، پینکنگ اور پرائیویسی کے خطرات بھی پیدا ہوئے ہیں۔ ذمہ دارانہ استعمال کے لیے مضبوط پاس ورڈ رکھیں، جعلی خبریں نہ پھیلائیں، اور کھیل کود کے ساتھ اسکرین ٹائم میں توازن رکھیں۔

CHECK YOURSELF

- Give one positive and one negative impact of computing in healthcare.
- Why can't many farmers in Pakistan benefit from smart agriculture tools?
- State three rules of smart and responsible use.

Answers: 1. + Digital records and telemedicine help treat remote patients; – patient data privacy is at risk if servers are hacked. 2. Poor internet access in rural areas. 3. Protect personal information/use strong passwords; do not share fake news; balance screen time with physical activity.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Computing in health:

- a. Records, imaging, telemedicine
- b. Only games
- c. Only NAND
- d. Only sprints

MCQ 2. Computing in education:

- a. LMS, simulations, analytics
- b. Only chalk forever
- c. Only OSI layer 1
- d. Only keys

MCQ 3. A social harm is:

- a. Addiction / fake news / job loss
- b. Faster search in a library
- c. Safer banks always only
- d. Shorter SDLC only

MCQ 4. E-waste is:

- a. Discarded electronics
- b. A Python error
- c. A foreign key
- d. A histogram bin

MCQ 5. The exam pattern is:

- a. One field + one good + one bad + one control
- b. Only definitions
- c. Only code
- d. Only careers

MCQ 6. Banks use computing for:

- a. Accounts, ATMs, fraud analytics
- b. Growing wheat
- c. Drawing K-maps
- d. Sorting hats

Extra short questions

- Two fields and one impact each.
- One environmental issue.
- One social issue.
- One control/mitigation.

Extra long question

- "Computing has only benefits." Refute with three fields, each with a benefit, a harm, and a mitigation. 10 marks.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Health: telemedicine. Transport: ride apps / signals. Banking: mobile wallets.
- E-waste, energy of data centres.
- Digital divide — students without smartphones.
- Laws, privacy settings, recycling, lab access at college.

Long

- Health, education, media. Structure a table. Close: technology is a tool; policy and literacy decide the outcome.

5.5 Assistive Technologies ★ Golden

LEARN IT

Assistive technologies are **devices, software and systems** that help people with **disabilities or functional limitations** (difficulty in seeing, hearing, moving, speaking, remembering, etc.). They allow more people to **participate equally** in school, work and society. There are **four categories**:

Category	Purpose	Examples
1. Mobility aids	Help people move from one place to another.	Smart wheelchairs, stair lifts
2. Sensory aids	Support vision and hearing to improve interaction.	Hearing aids, screen readers (VoiceOver), Braille displays
3. Communication aids	Assist individuals with speech difficulties to express themselves.	Speech-generating devices, text-to-speech apps
4. Cognitive / learning aids	Help people with memory, reading and understanding.	Audiobooks, spell-checkers, digital reminder apps

Mobility · Sensory · Communication · Cognitive

- A **screen reader** is software that reads aloud the text on a screen, so a blind person can use a phone or computer. **VoiceOver** is Apple's screen reader; Android has TalkBack.
- A **Braille display** is a device with small pins that rise and fall to form Braille dots, so a blind user can read screen text with their fingers.
- A **speech-generating device** speaks out words that a person types or selects on a screen.
- A **smart wheelchair** can be controlled by a joystick, voice or head movement and may avoid obstacles with sensors.

WORKED EXAMPLE

Scenario — choose the right assistive technology:

- (a) Ahmed, a student in Hyderabad, is blind and wants to read his e-textbook. → **Sensory aid**: a screen reader or Braille display.
- (b) Mrs Rashida cannot climb the stairs of her house after a knee operation. → **Mobility aid**: stair lift (or smart wheelchair).
- (c) Zain cannot speak clearly due to a medical condition but can type. → **Communication aid**: text-to-speech app or speech-generating device.
- (d) Nani often forgets to take her medicine. → **Cognitive aid**: digital reminder app.
- (e) Usman has dyslexia (difficulty reading). → **Cognitive/learning aid**: audiobooks and spell-checkers.
- Method: Identify the *limitation* (moving, seeing/hearing, speaking, memory/reading) → choose the matching category.

REMEMBER IT

Four categories = **"My Small Cat Cries"**: **M**obility, **S**ensory, **C**ommunication, **C**ognitive. Link each to a body function: *legs* (mobility), *eyes/ears* (sensory), *mouth* (communication), *mind* (cognitive).

COMMON MISTAKE

Mistake: Putting text-to-speech and screen readers in the same category every time. **Fix**: In the source, the **screen reader** is a **sensory aid** (supports vision), while a **text-to-speech app** is listed as a **communication aid** (helps a person with speech difficulty express themselves). Decide by whose problem it solves.

آرڈو میں سمجھیں

معاون ٹیکنالوجیز (Assistive Technologies) وہ آلات، سافٹ ویئر اور نظام ہیں جو معذور افراد کی مدد کرتے ہیں تاکہ وہ اسکول، کام اور معاشرے میں برابر حصہ لے سکیں۔ ان کی چار اقسام ہیں: نقل و حرکت میں مدد (اسمارٹ ویبل چیئر)، حسی مدد (سماعتی آلہ، اسکرین ریڈر، بریل ڈسپلے)، گفتگو میں مدد (اسپیج جنریشننگ ڈیوائس) اور ذہنی و تعلیمی مدد (آڈیو بکس، اسپیل چیکر، یاد دہانی ایپس)۔

EXAM TIP

Expect: "What are assistive technologies? Explain their categories with examples" (long), "Name two sensory aids" (short), or "A screen reader is an example of ____" (MCQ).

For full marks write the definition (devices, software and systems; help people with disabilities; equal participation), then all **four** categories each with purpose + two examples. Finish with one line on importance (equal access, independence, inclusion).

CHECK YOURSELF

1. Which category does a hearing aid belong to?
2. Give two examples of cognitive/learning aids.
3. Define assistive technologies in one sentence.

Answers: 1. Sensory aids. 2. Any two: audiobooks, spell-checkers, digital reminder apps. 3. Devices, software and systems that help people with disabilities or functional limitations participate equally in school, work and society.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Assistive technology helps:

- a. People with disabilities use systems
- b. Only hackers
- c. Only DBMS keys
- d. Only Agile coaches

MCQ 2. A screen reader is for:

- a. Blind / low-vision users
- b. Faster bubble sort
- c. Wi-Fi
- d. Primary keys

MCQ 3. Captions help:

- a. Deaf / hard-of-hearing users (and many others)
- b. Routers
- c. NAND gates
- d. Pie charts only

MCQ 4. Importance: they support:

- a. Equal access to education and work
- b. Faster CPUs only
- c. Cheaper RAM only
- d. OSI layer 1 only

MCQ 5. A career path is:

- a. Accessibility specialist / AT developer
- b. Only analog radio
- c. Only waterfalls
- d. Only K-maps

MCQ 6. Good HCI + AT means:

- a. Design for a wide range of users from the start
- b. A separate broken version forever
- c. No keyboard needed ever
- d. No contrast ever

Extra short questions

1. Define assistive technology with two examples.
2. Why it matters in a Pakistani college.
3. Link to HCI accessibility principles.
4. One career connection from the book.

Extra long question

1. Propose AT + ordinary design changes so a student with low vision and a student with limited hands can use the college portal. 10 marks. ★ if tagged Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Devices/software that help functional limits: screen readers, switches, captions, magnification.
2. A blind student can still take CS if materials are readable by NVDA and papers have electronic copies.
3. Perceivable, operable, understandable, robust — AT relies on those.
4. AT designer, accessibility tester, special-education technologist.

Long

1. Low vision: contrast, zoom, screen reader labels. Limited hands: large targets, keyboard/switch, extra time. Test with real users. Do not ship a mouse-only form.

5.5.1 Importance of Assistive Technologies

LEARN IT

Assistive technologies are important for three main reasons:

1. **Equal access to education:** Screen readers allow blind students to read digital textbooks equally with their peers (classmates).
2. **Independence in daily life:** Mobility aids reduce the need for constant human assistance — a person in a smart wheelchair can go to the market without someone pushing.
3. **Social inclusion:** They break down barriers, allowing individuals to work, study and socialise confidently.

Equal Access → Independence → Inclusion

WORKED EXAMPLE

How one tool changes a life: A visually impaired student in Karachi uses a screen reader on her laptop. **Equal access** — she reads the same e-books as her class. **Independence** — she no longer needs someone to read to her. **Inclusion** — she joins the class WhatsApp group, takes online tests and later gets a job, contributing to society.

REMEMBER IT

Remember **"All"**: Access, Independence, Inclusion.

اردو میں سمجھیں

معاون ٹیکنالوجیز کی اہمیت تین باتوں میں ہے: تعلیم تک برابر رسائی (ناہینا طلبہ اسکرین ریڈر سے کتابیں پڑھ سکتے ہیں)، روزمرہ زندگی میں خود مختاری (کسی کی مسلسل مدد کی ضرورت کم ہوتی ہے)، اور سماجی شمولیت (لوگ اعتماد کے ساتھ پڑھ، کام اور میل جول کر سکتے ہیں)۔

CHECK YOURSELF

1. State three reasons why assistive technologies are important.
2. How do mobility aids support independence?

Answers: 1. Equal access to education, independence in daily life, social inclusion. 2. They reduce the need for constant human assistance.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Assistive technology helps:

- a. People with disabilities use systems
- b. Only hackers
- c. Only DBMS keys
- d. Only Agile coaches

MCQ 2. A screen reader is for:

- a. Blind / low-vision users
- b. Faster bubble sort
- c. Wi-Fi
- d. Primary keys

MCQ 3. Captions help:

- a. Deaf / hard-of-hearing users (and many others)
- b. Routers
- c. NAND gates
- d. Pie charts only

MCQ 4. Importance: they support:

- a. Equal access to education and work
- b. Faster CPUs only
- c. Cheaper RAM only
- d. OSI layer 1 only

MCQ 5. A career path is:

- a. Accessibility specialist / AT developer
- b. Only analog radio
- c. Only waterfalls
- d. Only K-maps

MCQ 6. Good HCI + AT means:

- a. Design for a wide range of users from the start
- b. A separate broken version forever
- c. No keyboard needed ever
- d. No contrast ever

Extra short questions

1. Define assistive technology with two examples.
2. Why it matters in a Pakistani college.
3. Link to HCI accessibility principles.
4. One career connection from the book.

Extra long question

1. Propose AT + ordinary design changes so a student with low vision and a student with limited hands can use the college portal. 10 marks. ★ if tagged Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Devices/software that help functional limits: screen readers, switches, captions, magnification.
2. A blind student can still take CS if materials are readable by NVDA and papers have electronic copies.
3. Perceivable, operable, understandable, robust — AT relies on those.
4. AT designer, accessibility tester, special-education technologist.

Long

1. Low vision: contrast, zoom, screen reader labels. Limited hands: large targets, keyboard/switch, extra time. Test with real users. Do not ship a mouse-only form.

5.5.2 Career Connection in Assistive Tech

LEARN IT

Designing assistive technology is a **highly rewarding career path** — you earn a living while improving people's lives.

Career	What they do
Assistive Software Developer	Creates tools such as speech-to-text software (e.g. Urdu voice typing for people who cannot use a keyboard).
Biomedical Engineer	Designs artificial limbs and hearing aids.
UX/UI Accessibility Expert	Ensures websites are easy to navigate for visually impaired users (e.g. adding text descriptions to images so screen readers can read them).

UX means *user experience* (how easy and pleasant a product is to use); **UI** means *user interface* (the screens and buttons you interact with). **Accessibility** means designing so that *everyone*, including people with disabilities, can use it.

اردو میں سمجھیں

معاون ٹیکنالوجی بنانا ایک قابل قدر پیشہ ہے۔ اسسٹو سافٹ ویئر ڈویلپر اسپیچ ٹو ٹیکسٹ جیسے ٹولز بناتا ہے، بائیو میڈیکل انجینئر مصنوعی اعضاء اور سماعتی آلات تیار کرتا ہے، اور UX/UI ایکسیسیبلٹی ماہر یقینی بناتا ہے کہ ویب سائٹس نابینا افراد کے لیے بھی آسانی سے استعمال ہو سکیں۔

CHECK YOURSELF

1. Who designs artificial limbs and hearing aids?
2. What does a UX/UI accessibility expert ensure?

Answers: 1. A biomedical engineer. 2. That websites are easy to navigate for visually impaired users.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Assistive technology helps:

- a. People with disabilities use systems
- b. Only hackers
- c. Only DBMS keys
- d. Only Agile coaches

MCQ 2. A screen reader is for:

- a. Blind / low-vision users
- b. Faster bubble sort
- c. Wi-Fi
- d. Primary keys

MCQ 3. Captions help:

- a. Deaf / hard-of-hearing users (and many others)
- b. Routers
- c. NAND gates
- d. Pie charts only

MCQ 4. Importance: they support:

- a. Equal access to education and work
- b. Faster CPUs only
- c. Cheaper RAM only
- d. OSI layer 1 only

MCQ 5. A career path is:

- a. Accessibility specialist / AT developer
- b. Only analog radio
- c. Only waterfalls
- d. Only K-maps

MCQ 6. Good HCI + AT means:

- a. Design for a wide range of users from the start
- b. A separate broken version forever
- c. No keyboard needed ever
- d. No contrast ever

Extra short questions

1. Define assistive technology with two examples.
2. Why it matters in a Pakistani college.
3. Link to HCI accessibility principles.
4. One career connection from the book.

Extra long question

1. Propose AT + ordinary design changes so a student with low vision and a student with limited hands can use the college portal. 10 marks. ★ if tagged Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Devices/software that help functional limits: screen readers, switches, captions, magnification.
2. A blind student can still take CS if materials are readable by NVDA and papers have electronic copies.
3. Perceivable, operable, understandable, robust — AT relies on those.
4. AT designer, accessibility tester, special-education technologist.

Long

1. Low vision: contrast, zoom, screen reader labels. Limited hands: large targets, keyboard/switch, extra time. Test with real users. Do not ship a mouse-only form.

Application and Impacts of Computing

12 single-page lessons · 4 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- Computing is vital in Pakistan's schools, hospitals, banks, farms and industries; it has both positive and negative impacts.
- **AI** is "artificial" (made by humans) and "intelligent" (does tasks needing thinking); it uses data to learn, recognise patterns and make decisions.
- In smart systems, IoT is the "eyes" that gather data, Analytics sorts it, and AI is the "brain" that decides the action.
- **IoT** is a system of physical devices connected to the internet that collect and share data to perform tasks automatically.
- The six IoT components are sensors (collect), actuators (act), connectivity, data processing, cloud computing and user interface.
- **Data Analytics** is a pipeline: collection → storage → cleaning → analysis → visualization.
- Data cleaning removes duplicates, incorrect values, missing records and improper formats.
- IoT outputs raw data (hardware); AI outputs smart decisions (software); Data Analytics outputs reports, graphs and insights (data).
- IoT is used in smart cities, industrial automation, healthcare, education, home automation and smart farming.
- Smart farming (soil sensor → cloud AI → water pump) saves water and improves yields in Sindh and Punjab.
- AI in Pakistani education: LMS, automated grading, career counselling; challenges are rural internet, lack of devices, teacher training and data privacy.
- IoT/AI careers (IoT engineer, data analyst) need programming, networking, electronics and problem-solving.
- Information sources: primary (firsthand/original), secondary (collected and explained by others), tertiary (summarised for quick reference).
- Do not trust an online article that lacks an author, a publication date or references.
- Computing helps education, communication, business, healthcare and agriculture but risks screen addiction, isolation, job loss, cyber-attacks and privacy loss.
- **Assistive technologies** — mobility, sensory, communication and cognitive aids — give equal access, independence and social inclusion to people with disabilities.

Key terms

Term	Meaning	اردو
Computing	Using computers and digital devices to store, process and share information.	کمپیوٹنگ
Artificial Intelligence (AI)	Human-made technology that lets machines think, learn and decide using data.	مصنوعی ذہانت
Internet of Things (IoT)	Physical devices connected to the internet that collect and share data to work automatically.	انٹرنیٹ آف تھنگز، اشیاء کا انٹرنیٹ
Sensor	Device that collects information from the physical world.	حساس آلہ (سینسر)
Actuator	Device that performs a physical action in response to a command.	عمل کار آلہ (ایکچوایٹر)
Connectivity	The link (Wi-Fi, Bluetooth, ZigBee, 4G/5G) that lets devices send and receive data.	رابطہ کاری
Data processing	Changing raw data into useful information.	ڈیٹا کی پروسیسنگ
Cloud computing	Storing data and using services over the internet instead of local drives.	کلاؤڈ کمپیوٹنگ
User interface (UI)	The part that lets a user see information and give commands to a device.	صارف انٹرفیس
Data Analytics	Collecting, storing, cleaning, analysing and presenting data to find useful information.	ڈیٹا کا تجزیہ
Data cleaning	Finding and correcting errors such as duplicates and missing values.	ڈیٹا کی صفائی
Data visualization	Showing data as charts, plots or graphs.	ڈیٹا کی بصری پیشکش

Application and Impacts of Computing

75 marks · 1 hour 15 minutes · no notes · no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 12 and the recap. **Section A** — all 15 MCQs (1 mark). **Section B** — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define · Explain · Example · Diagram · Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. AI is called "artificial" because it:
 - a. runs only on electricity
 - b. is created by humans
 - c. is always wrong
 - d. works without data
2. Which of the following is an actuator?
 - a. Temperature sensor
 - b. Motion sensor
 - c. Water valve
 - d. Wi-Fi router
3. ZigBee is an example of which IoT component?
 - a. Connectivity
 - b. Sensor
 - c. User interface
 - d. Actuator
4. Google Drive and iCloud are examples of:
 - a. Sensors
 - b. Data cleaning
 - c. Actuators
 - d. Cloud computing
5. Removing duplicate student records belongs to which component of Data Analytics?
 - a. Data collection
 - b. Data storage
 - c. Data cleaning
 - d. Data visualization
6. A pie chart showing pass vs fail percentage is an example of:
 - a. Data collection
 - b. Data storage
 - c. Data cleaning
 - d. Data visualization
7. According to the comparison table, the output of IoT is:
 - a. Raw data from the environment
 - b. Smart decisions
 - c. Reports and graphs
 - d. Printed documents
8. In a smart system, AI acts as the:
 - a. eyes
 - b. brain
 - c. hands
 - d. wires
9. NADRA's official records are a:
 - a. tertiary source
 - b. secondary source
 - c. primary source
 - d. unreliable source
10. Wikipedia is classified as a:
 - a. primary source
 - b. tertiary source
 - c. secondary source
 - d. firsthand record
11. Smart bins that send alerts when full are a use of IoT in:
 - a. smart farming
 - b. healthcare
 - c. home automation
 - d. smart cities
12. A system in which a soil sensor tells the cloud AI to switch on a water pump is used in:
 - a. smart farming
 - b. industrial automation
 - c. smart classrooms
 - d. traffic management
13. A screen reader such as VoiceOver is a:
 - a. mobility aid
 - b. communication aid
 - c. sensory aid
 - d. cognitive aid
14. A speech-generating device is a:
 - a. mobility aid
 - b. cognitive aid
 - c. sensory aid
 - d. communication aid
15. An online article should NOT be trusted for academic work if it lacks:
 - a. colourful pictures
 - b. the author's name, publication date or references
 - c. a long title
 - d. advertisements

Section B — Short questions (10 × 3 = 30)

1. Define Artificial Intelligence and give two examples from daily life.
2. Define the Internet of Things (IoT) with one example.
3. Differentiate between a sensor and an actuator with two examples of each.
4. What is the role of cloud computing in an IoT system?
5. List the five components of Data Analytics. What kinds of errors are removed in data cleaning?
6. Give two uses of IoT in smart cities and two in healthcare.
7. State two benefits and two challenges of AI in education in Pakistan.
8. Differentiate between primary and secondary sources with two examples each.
9. When does a secondary source become unreliable?
10. Give one positive and one negative impact of computing on (a) communication and (b) business.

Section C — Long questions (attempt any 3 × 10 = 30)

1. Define IoT. Explain its six components with an example of each. Draw a diagram showing how they connect.
2. Compare IoT, AI and Data Analytics in a table (definition, purpose, type of work, output). Then explain, with an example, how the three work together in a smart system.
3. A college in Mirpurkhas wants to find out why many students are failing Mathematics. Explain how it would use each of the five components of Data Analytics to solve this problem.
4. Explain the three types of information sources with examples. Classify the following: (i) a school textbook, (ii) a photograph of an event, (iii) an encyclopedia, (iv) an interview, (v) a Bureau of Statistics report, (vi) a dictionary. When does each type become unreliable?
5. What are assistive technologies? Explain their four categories with examples, state their importance, and name two related careers.
6. "Computing has both positive and negative impacts on society." Discuss with reference to education, healthcare and agriculture, and suggest three rules for smart and responsible use.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

- 5.1 Introduction to Computing Impacts.** Answers: 1. Any four of: schools, hospitals, banks, farms, industries. 2. The effect computing has on people and society — it can be positive or negative.
- 5.1.1 Artificial Intelligence (AI).** Answers: 1. Because it is created by humans. 2. AI is the brain; IoT is the eyes. 3. Yes — it uses data (past spam emails) to decide whether a new email is spam, a task that needs "thinking".
- 5.1.2 Internet of Things (IoT) & Components.** Answers: 1. (a) sensor, (b) actuator, (c) sensor, (d) actuator. 2. Wi-Fi, Bluetooth, ZigBee, 4G/5G. 3. Because IoT devices produce massive amounts of data; the cloud stores and processes it over the internet instead of on small local hard drives.
- 5.1.3 Data Analytics & Components.** Answers: 1. Collection, Storage, Cleaning, Analysis, Visualization. 2. Duplicate records, incorrect values (typos), missing records, improper formats. 3. Data Visualization.
- Table: IoT vs AI vs Data Analytics Comparison.** Answers: 1. IoT. 2. Reports, graphs and insights.
- 5.2 Uses of IoT in Different Areas.** Answers: 1. They send alerts when full, so only full bins are emptied. 2. Rural areas lack doctors; devices send patient data directly to doctors far away. 3. The water pump (its switch).
- 5.2.1 Scope of AI in Education in Pakistan.** Answers: 1. LMS, automated grading and digital testing, AI-based career counselling. 2. Any two: limited rural internet, lack of devices, need for teacher training, data privacy and security.
- 5.3 Information Sources (Primary, Secondary, Tertiary).** Answers: 1. P 2. S 3. T 4. P 5. S 6. T 7. P 8. S
- 5.4 Impacts of Computing in Various Fields.** Answers: 1. + Digital records and telemedicine help treat remote patients; – patient data privacy is at risk if servers are hacked. 2. Poor internet access in rural areas. 3. Protect personal information/use strong passwords; do not share fake news; balance screen time with physical activity.
- 5.5 Assistive Technologies.** Answers: 1. Sensory aids. 2. Any two: audiobooks, spell-checkers, digital reminder apps. 3. Devices, software and systems that help people with disabilities or functional limitations participate equally in school, work and society.
- 5.5.1 Importance of Assistive Technologies.** Answers: 1. Equal access to education, independence in daily life, social inclusion. 2. They reduce the need for constant human assistance.
- 5.5.2 Career Connection in Assistive Tech.** Answers: 1. A biomedical engineer. 2. That websites are easy to navigate for visually impaired users.

Answer key

Multiple choice

1. b
2. c
3. a
4. d
5. c
6. d
7. a
8. b
9. c
10. b
11. d
12. a
13. c
14. d
15. b

Short questions — model answers

1. AI is human-made ("artificial") technology that can perform tasks requiring thinking ("intelligence"); it uses data to make decisions. Examples: face recognition to unlock a phone; YouTube suggesting videos; chatbots answering questions.
2. IoT is a system in which physical devices are connected to the internet and can collect and share data to perform tasks automatically. Example: a smartwatch collects heart-rate data and sends it to a mobile phone for display.
3. A sensor collects information from the physical world (input; the "eyes and ears"), e.g. temperature sensor, motion sensor. An actuator performs a physical action in response to a command, converting digital signals into movement (output), e.g. electric motor, automatic door opener.
4. Cloud computing stores IoT data and provides processing services over the internet instead of local hard drives, so it can handle the massive amounts of data produced by many devices. Examples: Google Drive, iCloud, online LMS.
5. Collection, storage, cleaning, analysis, visualization. Cleaning removes duplicated records, incorrect values (typos), missing files/records, and improper formats.
6. Smart cities: sensors adjust traffic signals to reduce congestion; smart bins send alerts when full (also street lighting, parking). Healthcare: smartwatches measure heart rate and vitals; remote monitoring devices send patient data to doctors (also emergency alerts).
7. Benefits: students learn at their own speed; AI identifies students who need extra help (also supports students with disabilities). Challenges: limited internet access in rural areas; lack of computers/devices (also teacher training, data privacy).
8. Primary sources give original, firsthand information from people, events or official records (e.g. interviews, NADRA records). Secondary sources contain information already collected and explained by someone else, summarising or analysing primary data (e.g. textbooks, news reports).
9. When the information is outdated, lacks proper references/citations, or has not been verified by an expert.
10. (a) Communication: + emails and video calls give instant, global communication at almost no cost; – less in-person interaction causes social isolation. (b) Business: + online shopping, digital banking and automation improve speed and efficiency; – manual jobs are lost to machines and banks face cyber-attacks.

Long questions — model answers

1. **Definition:** IoT is a system in which physical devices are connected to the internet and collect and share data to perform tasks automatically. **Components:** (1) Sensors — collect information from the physical world, e.g. temperature, motion, fingerprint, smoke, soil moisture sensors. (2) Actuators — perform physical actions in response to commands, converting digital signals to movement, e.g. motor, switch, door opener, water valve, fan controller. (3) Connectivity — lets devices send/receive data, e.g. Wi-Fi, Bluetooth, ZigBee, 4G/5G. (4) Data processing — changes raw data into useful information through collecting, organising, analysing and deciding, e.g. checking if a room is too hot to switch on the AC. (5) Cloud computing — stores data and provides services over the internet, handles massive data, e.g. Google Drive, iCloud, LMS. (6) User interface — lets users see information and give commands, e.g. mobile apps, touch screens, voice commands. **Diagram:** Sensor (collects) → Wi-Fi → Cloud (processes) → Actuator (acts) → User App (UI).
2. **Table:** IoT — network of physical devices connected to the internet; purpose: data collection and automation; works with hardware; output: raw data from environment. AI — technology enabling machines to think and decide; purpose: intelligent decisions and predictions; works with smart software; output: smart decisions or actions. Data Analytics — process of examining data to find patterns; purpose: extracting meaningful insights; works with data (numbers, records); output: reports, graphs, insights. **Working together:** IoT is the eyes that gather data, Analytics sorts it, AI is the brain that decides. Example: a temperature sensor reads 36 °C (IoT) → recent readings are organised showing the room is heating up (Analytics) → AI decides the room is too hot (AI) → a switch turns on the AC (action).
3. (1) **Collection:** gather marks of all Maths tests, attendance and survey responses from students. (2) **Storage:** keep them safely in a spreadsheet or database, e.g. on the cloud. (3) **Cleaning:** remove duplicate records, correct typing errors (e.g. 120 out of 100), fill or mark missing records, and make formats (dates, roll numbers) consistent. (4) **Analysis:** study the clean data to find patterns — e.g. which chapters most students got wrong, whether low attendance links to failing. (5) **Visualization:** present results in bar charts or a pie chart of pass vs fail so the principal sees the problem at a glance and plans extra classes for weak chapters.
4. **Primary:** original, firsthand, highly authentic (interviews, photographs, diaries, NADRA records). **Secondary:** collected and explained by someone else, summarises/analyses primary data (textbooks, news reports, research papers, Bureau of Statistics reports). **Tertiary:** highly summarised and organised from primary and secondary sources for quick reference (encyclopedias, Wikipedia, dictionaries, handbooks). **Classification:** (i) secondary, (ii) primary, (iii) tertiary, (iv) primary, (v) secondary, (vi) tertiary. **Unreliability:** primary — incomplete, recorded incorrectly, or deliberately false; secondary — outdated, no references/citations, not verified by an expert; tertiary — unknown/unverified website, or oversimplified and missing key facts. Rule: do not trust an article without author, date or references.
5. **Definition:** devices, software and systems that help people with disabilities or functional limitations participate equally in school, work and society. **Categories:** (1) Mobility aids — help people move; smart wheelchairs, stair lifts. (2) Sensory aids — support vision and hearing; hearing aids, screen readers (VoiceOver), Braille displays. (3) Communication aids — help people with speech difficulties express themselves; speech-generating devices, text-to-speech apps. (4) Cognitive/learning aids — help with memory, reading, understanding; audiobooks, spell-checkers, reminder apps. **Importance:** equal access to education (screen readers let blind students read digital textbooks), independence in daily life (mobility aids reduce need for constant help), social inclusion (people work, study and socialise confidently). **Careers:** any two of assistive software developer (speech-to-text tools), biomedical engineer (artificial limbs, hearing aids), UX/UI accessibility expert (websites usable by visually impaired users).
6. **Introduction:** computing makes life faster and more connected but brings privacy risks and addiction. **Education:** + online classes, e-books and learning apps make study flexible and accessible; – excessive screen time reduces attention span and harms physical health. **Healthcare:** + digital patient records and telemedicine let doctors treat remote patients accurately (e.g. rural Sindh); – patient data privacy is at risk if hospital servers are hacked. **Agriculture:** + smart irrigation and weather forecasting greatly increase yields; – poor rural internet means many farmers cannot use these tools. **Responsible use:** protect personal information and use strong passwords; do not share fake news or unverified forwards; balance screen time with sports and physical activity. **Conclusion:** benefits are large if technology is used wisely.

Self-assessment: I can...

- ☐ define AI and explain why it is called "artificial intelligence".
- ☐ define IoT and name its six components with examples.
- ☐ list the five components of Data Analytics in order and describe data cleaning.
- ☐ describe IoT uses in smart cities, industry, healthcare, education, homes and farms.
- ☐ classify any source as primary, secondary or tertiary and judge its reliability.
- ☐ explain the four categories of assistive technologies and their importance.
- ☐ explain how IoT, Data Analytics and AI work together (eyes → sort → brain → action).
- ☐ tell the difference between a sensor and an actuator.
- ☐ compare IoT, AI and Data Analytics in a table.
- ☐ state uses, benefits and challenges of AI in education in Pakistan.
- ☐ discuss positive and negative impacts of computing in five fields.
- ☐ name careers linked to IoT, AI and assistive technology and the skills they need.

Lecture 06

Digital Literacy

Chapter lecture — 14 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XI · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — گیارہویں جماعت

14 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XI

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیئر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

Lectures in this pack

Chapter 6: Digital Literacy. Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 6.1 & 6.2 Introduction to Digital Literacy

L03. 6.4 Data-Collection Strategies

L05. 6.4.3 – 6.4.5 Prototypes, Observation, and Simulations

L07. 6.6 Designing a Data-Collection Approach

L09. 6.7.1 – 6.7.4 Spreadsheets, Presentations, Infographics, Reports

L11. Step 1 – 3: Advanced Search & Methodology

L13. Step 7 – 9: Secondary Data & Spreadsheet Organization

L02. 6.3 Types of Data (Qualitative vs Quantitative)

L04. 6.4.1 – 6.4.2 Interviews and Surveys

L06. 6.5 Primary and Secondary Data

L08. 6.7 Presenting Data Using Digital Tools

L10. 6.8 Case Study: Digital Inquiry Project

L12. Step 4 – 6: Survey Prep & Primary Data Collection

L14. Step 10 – 12: Data Analysis, Conclusion & Artefact

CHAPTER 6

Digital Literacy

This chapter teaches you how to find, collect, organise and present information using digital tools, safely and responsibly. You will learn about types of data, ways to collect it, and how to turn it into a useful report, presentation or infographic. At the end you will follow a complete research project from the first question to the final product.

اس باب میں آپ سیکھیں گے کہ ڈیجیٹل آلات کی مدد سے معلومات کو محفوظ اور ذمہ دارانہ طریقے سے کیسے تلاش کیا جائے، جمع کیا جائے، ترتیب دیا جائے اور پیش کیا جائے۔ آخر میں آپ ایک مکمل تحقیقی منصوبہ (Digital Inquiry Project) شروع سے آخر تک دیکھیں گے۔

What you will learn

- Define digital literacy and explain why it matters in the Information Age.
- Describe five data-collection strategies: interviews, surveys, prototypes, observation and simulations.
- Compare primary and secondary data by source, examples, purpose and control.
- Use spreadsheet formulas such as `=SUM()`, `=AVERAGE()` and `=COUNTIF()` to analyse data.
- Use advanced search operators (" ", `filetype:`, `site:`) and evaluate the reliability of a source.
- Distinguish between qualitative and quantitative data and give examples of each.
- Write clear, unbiased survey questions and recognise badly written ones.
- List the eight steps for designing a data-collection approach, including ethics and consent.
- Choose a suitable digital tool (spreadsheet, presentation, infographic, report, dashboard) to present findings.
- Carry out all 12 steps of a digital inquiry project and produce a final digital artefact.

6.1 & 6.2 Introduction to Digital Literacy

LEARN IT

Digital literacy is the ability to understand and use digital devices, the internet, and online tools in a **safe, effective, and responsible** manner.

Look at the three key words:

- **Safe** – you protect yourself and others online (for example, you do not share passwords or private details).
- **Effective** – you get the job done well (for example, you find the right information quickly).
- **Responsible** – you use information honestly and fairly (for example, you do not copy someone else’s work or spread false news).

In our increasingly digital world, digital literacy is essential for **everyone**, not only for computer experts. It enables you to:

- find information,
- communicate with others,
- produce digital content, and
- solve problems through technology.

Did you know? Digital literacy is not only using devices; it is using digital information safely and wisely. A digitally literate student can:

Locate information → Organise it properly → Turn it into something useful → Share it responsibly

WORKED EXAMPLE

Is this student digitally literate?

Ali can type fast and plays games on his phone all day. When his teacher asks him to find the population of Karachi, he copies the first number he sees on a random website and does not check where it came from.

Step 1 – Can he use devices? Yes. He has basic skills.

Step 2 – Can he locate and judge information? No. He did not check whether the website was reliable.

Step 3 – Conclusion: Ali has computer skills but is not yet fully digitally literate. A digitally literate student would compare two or three trusted sources (for example, the Pakistan Bureau of Statistics website) before using the number.

REMEMBER IT

Remember the four verbs of a digitally literate student: **Locate – Organise – Create – Share** ("LOCS": think of a lock that keeps your digital life safe).

COMMON MISTAKE

Mistake: "Digital literacy means knowing how to use a computer." **Fix:** Using a computer is only the start. Digital literacy also means finding, judging, creating and sharing information safely and responsibly.

اردو میں سمجھیں

ڈیجیٹل خواندگی (Digital Literacy) سے مراد ڈیجیٹل آلات، انٹرنیٹ اور آن لائن ٹولز کو محفوظ، مؤثر اور ذمہ دارانہ طریقے سے سمجھنا اور استعمال کرنا ہے۔ ایک ڈیجیٹل خواندہ طالب علم معلومات تلاش کر سکتا ہے، ایس ٹریپ دے سکتا ہے، ان سے کوئی مفید چیز بنا سکتا ہے اور ایس ذمہ داری سے دوسروں تک پہنچا سکتا ہے۔

CHECK YOURSELF

1. Write the definition of digital literacy in one sentence.

2. Name the four things digital literacy enables you to do.

Answers: 1. The ability to understand and use digital devices, the internet and online tools in a safe, effective and responsible manner. 2. Find information, communicate, produce digital content, and solve problems through technology.

LEARN IT

The **Information Age** is the period we live in now, where vast amounts of data are **produced, shared and accessed instantly** through the internet, mobile devices and digital platforms (websites, apps, social media). Simply **having access** to technology is **not enough**. Owning a smartphone does not make you good at using information. You must develop the skills to **understand, manage and use** information wisely.

Digital literacy goes beyond basic computer skills. It involves three kinds of ability:

Ability	What it means	Example
Technical	Knowing how to operate devices and software.	Creating a Google Form; using a spreadsheet.
Cognitive (thinking)	Thinking critically about information.	Checking whether a news story is true before believing it.
Social	Communicating and behaving well with others online.	Being polite in a class WhatsApp group; respecting privacy.

Together these abilities help you function successfully in a **digital society**.

WORKED EXAMPLE

Applying the three abilities. A video claims "Drinking hot water cures dengue." What does a digitally literate student do?

Technical: Uses a search engine to search: dengue treatment + site:.gov.

Cognitive: Notices the video has no doctor or source, and that official health websites do not support the claim. Concludes it is false.

Social: Does not forward the video, and politely tells the family group that it is not reliable.

REMEMBER IT

Three abilities = **"Tech, Think, Talk"**: Technical, Cognitive (think), Social (talk with others).

COMMON MISTAKE

Mistake: Thinking that "more information" automatically means "better information". **Fix:** In the Information Age the problem is not finding some information; it is choosing the **right, reliable** information from too much.

اردو میں سمجھیں

معلوماتی دور (Information Age) میں انٹرنیٹ اور موبائل کے ذریعے بے پناہ معلومات فوراً تیار اور شیئر ہوتی ہیں۔ صرف ٹیکنالوجی تک رسائی کافی نہیں، معلومات کو سمجھنے، سنبھالنے اور دانشمندی سے استعمال کرنے کی مہارت ضروری ہے۔ ڈیجیٹل خواندگی میں تکنیکی ذہنی (Cognitive) اور سماجی صلاحیتیں شامل ہیں۔

CHECK YOURSELF

1. What is the Information Age?

2. Name the three types of ability that digital literacy involves.

Answers: 1. A period in which vast amounts of data are produced, shared and accessed instantly through the internet, mobile devices and digital platforms. 2. Technical, cognitive and social abilities.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Digital literacy is:

a. Using digital tools safely and smartly

b. Owning a phone only

c. Typing 10 words

d. Watching any video

MCQ 2. It includes:

a. Search, evaluate, create, behave ethically

b. Only cabling

c. Only NAND

d. Only sprints

MCQ 3. A digitally literate student can:

a. Tell a reliable source from a forward

b. Believe every screenshot

c. Post passwords

d. Skip citations

MCQ 4. Information age means:

a. Value of data/knowledge is huge

b. Stone tools

c. No networks

d. No computers

MCQ 5. Safety in DI includes:

a. Passwords, privacy, respectful posts

b. Sharing OTPs

c. Unknown USBs always

d. Public exam photos of others without consent

MCQ 6. This chapter later asks you to:

a. Collect and present data yourself

b. Build CPUs

c. Lay fibre

d. Write OSI sniffers

Extra short questions

1. Define digital literacy.

2. Three skills besides "knowing Word".

3. One unsafe practice.

4. Why it is in a CS course, not only Islamiyat/civics.

Extra long question

1. A cousin forwards a "BIK result leaked" screenshot. Using digital literacy, write the steps you take before sharing, and how you would present your finding.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Ability to find, evaluate, use, create and share digital information safely.

2. Search operators, source judging, privacy, creating a chart, citing.

3. Using the same password for email and JazzCash.

4. You produce and analyse data — you are responsible for it.

Long

1. Check official site/data/URL, reverse-image, look for primary source. Do not share. Present as a short report: claim, checks, conclusion. Link to later inquiry project.

6.3 Types of Data (Qualitative vs Quantitative) Golden

LEARN IT

Data means facts, numbers, words or observations that we collect. The data gathered through a survey, an investigation or a classroom project can be described in two ways: **qualitatively** or **quantitatively**. Knowing the difference is critical, because each type is analysed in a different way.

6.3.1 Qualitative Data

Qualitative data describes what people **think, feel, notice or experience**. It is **non-numerical and descriptive**: it is made of words, not numbers. The word comes from *quality* (what something is like).

Examples: students' opinions about online classes; descriptions of study habits; observation notes ("The students looked bored after 20 minutes").

6.3.2 Quantitative Data

Quantitative data deals with **numbers**. The word comes from *quantity* (how much or how many). It is useful when you need to **count, measure, compare, calculate averages**, or **display results in charts**.

Examples: number of students using the internet daily; marks obtained in a test; time spent online in hours.

6.3.3 Comparing Qualitative and Quantitative Data

Type of data	Nature	Examples	Best used for
Qualitative	Descriptive, non-numerical	Opinions, reasons, behaviour	Understanding why and how something happens
Quantitative	Numerical, countable or measurable	Hours, scores, percentages, totals	Comparing results and making graphs/charts

LEARN IT

Going a little further (**background**). Quantitative data is sometimes split into two kinds:

- Discrete data can only take separate, countable values, e.g. number of students in a class (35, 36 – never 35.5).
- Continuous data can take any value in a range and is *measured*, e.g. height (162.4 cm) or time online (2.75 hours).

Also note: a question with fixed categories (e.g. "Which activity do you use your phone for most? Lectures / Notes / Social media / Games") gives **categories** that you can **count**. In this chapter's case study such answers are treated as **quantitative (categories)**, because you count how many students chose each option.

WORKED EXAMPLE

Classify each piece of data.

Data	Type	Reason
"I like online classes because I can replay lectures."	Qualitative	An opinion with a reason, in words.
Ayesha scored 78 out of 100.	Quantitative	A score – a number you can compare.
28 out of 40 students use the internet daily.	Quantitative	A count (and gives 70%).
Observer notes: "Students chat during the last period."	Qualitative	A description of behaviour.
Bilal spends 3.5 hours online per day.	Quantitative	A measurement of time.

Quick test: ask "Can I calculate an average of this?" If yes, it is quantitative. If the answer is words, it is qualitative.

REMEMBER IT

QUALitative – QUALity – words and feelings. QUANTitative – QUANTity – numbers and counts. Qualitative answers **why/how**; quantitative answers **how many/how much**.

COMMON MISTAKE

Mistake: Thinking that any data containing a number is quantitative. A phone number or a roll number is a *label*, not a quantity – averaging roll numbers is meaningless. **Fix:** Data is quantitative only if the number measures or counts something.

اردو میں سمجھیں

کیفیاتی ڈیٹا (Qualitative Data) الفاظ پر مشتمل ہوتا ہے اور بتاتا ہے کہ لوگ کیا سوچتے، محسوس کرتے یا تجربہ کرتے ہیں، جیسے اُن لائن کلاسز کے بارے میں رائے۔ مقداری ڈیٹا (Quantitative Data) اعداد پر مشتمل ہوتا ہے، جیسے ٹیسٹ کے نمبرز یا اُن لائن گزاریے کی گنتیں۔ کیفیتی ڈیٹا "کیوں اور کیسے" سمجھنے کے لیے، جبکہ مقداری ڈیٹا موازنہ کرنے اور چارٹ بنانے کے لیے بہترین ہے۔

EXAM TIP

Common questions: "Differentiate between qualitative and quantitative data" (4–5 marks) or "Classify the following data". Write the answer as a **table** with four rows: **nature, examples, best used for**, plus a one-line definition of each. Always give **two examples** of each type. The source's table (Nature / Examples / Best used for) is exactly what examiners expect.

CHECK YOURSELF

- Is "time spent online in hours" qualitative or quantitative?
- Which type of data is best for understanding **why** something happens?
- Classify: "The canteen food is too oily."

Answers: 1. Quantitative (measurable number). 2. Qualitative. 3. Qualitative (an opinion in words).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Qualitative data is: a. Categories / words (favourite subject) b. Heights in cm only c. Always continuous numbers d. Always bits	MCQ 2. Quantitative data is: a. Numeric measurements or counts b. Colours of bags only c. Always opinions d. Always URLs	MCQ 3. Favourite colour is: a. Qualitative b. Quantitative continuous c. A primary key always d. A gate	MCQ 4. Height is: a. Quantitative continuous b. Qualitative c. Boolean only d. Tertiary	MCQ 5. Number of siblings is: a. Quantitative discrete b. Qualitative c. Analog voltage d. A query	MCQ 6. Why the type matters: a. It decides the chart and statistic b. It decides OSI layer c. It decides NAND grouping d. It decides Agile sprint length
--	---	--	--	---	---

Extra short questions

- Define qualitative vs quantitative with examples.
- Discrete vs continuous quantitative.
- Which chart for qualitative shares?
- Which average for qualitative?

Extra long question

- A survey has: gender, hours of study, favourite app, test marks. Classify each, pick a chart, and say mean/median/mode which is legal.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Qual: labels (blood group). Quant: numbers (marks).
- Discrete: counts (students). Continuous: measurements (time, temperature).
- Bar or pie (few categories).
- Mode — mean of "red/blue" is meaningless.

Long

- Gender qual → pie/bar, mode. Hours quant cont → hist, mean/median. App qual → bar, mode. Marks quant → hist/box, mean/median. Table.

6.4 Data-Collection Strategies ★ Golden

LEARN IT

Digital literacy is not limited to finding information that **already exists** on the internet. You should also learn how to gather **original** (new) information yourself. A **data-collection strategy** is a planned method for gathering this information.

The five common strategies are:

Interviews · Surveys · Prototypes · Observation · Simulations

Strategy	How it works (one line)	Usual data type	Best when...
Interview	Planned conversation with a person or small group	Mostly qualitative	You need deep, detailed answers from a few people
Survey	Same questions asked to many people	Quantitative and qualitative	You need answers from many people quickly
Prototype	Users test an early version and give feedback	Both	You want to improve a product or solution
Observation	Watch and record; no questions asked	Notes (qualitative) or counts (quantitative)	You want to see what people actually do
Simulation	Computer model; change variables and see what happens	Mostly quantitative	Real experiments are costly, risky or difficult

REMEMBER IT

Mnemonic for the five strategies: **"I S P O S" – "I Saw People On Screens"**: Interviews, Surveys, Prototypes, Observation, Simulations.

اردو میں سمجھیں

ڈیجیٹل خواندگی صرف موجود معلومات تلاش کرنے تک محدود نہیں، بلکہ نئی معلومات خود جمع کرنا بھی اس کا حصہ ہے۔ ڈیٹا جمع کرنے کے پانچ عام طریقے یہ ہیں: انٹرویو، سروے، پروٹوٹائپ، مشاہدہ (Observation) اور سمیولیشن (Simulation)۔

EXAM TIP

"List and explain the data-collection strategies" is a frequent long question. Name all **five**, give a one-sentence definition and **one example** for each, and say what type of data each gives. Detailed notes on each follow in the next two topics.

CHECK YOURSELF

1. Name the five data-collection strategies.
2. What does "original information" mean?

Answers: 1. Interviews, surveys, prototypes, observation, simulations. 2. New information that you gather yourself, rather than information that already exists.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Data-collection strategies include:

- a. Interview, survey, prototype, observation, simulation
- b. Only NAND
- c. Only OSI ping
- d. Only K-maps

MCQ 2. You collect data when:

- a. Existing sources are not enough
- b. You already have the full census always
- c. The question is undefined
- d. You only need a meme

MCQ 3. A strategy must match:

- a. The question and the people
- b. The teacher's favourite chart only
- c. Agile always
- d. TCP window

MCQ 4. Bias in collection:

- a. Systematically distorts answers
- b. Improves SD always
- c. Is required in exams
- d. Is a primary key

MCQ 5. Ethics: people should:

- a. Know and consent
- b. Be filmed secretly always
- c. Hand over passwords
- d. Be named in viral posts

MCQ 6. This is ★ because papers ask:

- a. Name + when to use + one limit of a method
- b. Only Python turtles
- c. Only ER
- d. Only Big O

Extra short questions

1. List five strategies from the book.
2. One advantage of planning methods first.
3. One ethical rule.
4. What is a biased question?

Extra long question

1. Choose methods for: (a) why students skip practicals (b) how a new ID-card prototype feels (c) traffic at the gate. Justify. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Interview, survey, prototype, observation, simulation (and others in 6.4).
2. You do not collect the wrong type of data for your chart later.
3. Informed consent; anonymise students.
4. "Don't you agree our canteen is terrible?" — pushes the answer.

Long

1. (a) interview+survey (b) prototype test (c) observation/count or simulation. Limits of each. Ethics sentence.

6.4.1 – 6.4.2 Interviews and Surveys

6.4.1 Interviews

LEARN IT

An **interview** is a **planned conversation** used to gather information **directly from a person**.

- It may be **one-to-one** (you and one person) or in a **small group**.
- Questions are **planned in advance**, so you do not forget anything important.
- Answers are usually **qualitative** (opinions, reasons, experiences).

Strength: you get deep, detailed answers and can ask follow-up questions ("Why do you say that?"). **Weakness:** it takes a lot of time, so you can only interview a few people.

6.4.2 Surveys / Questionnaires

LEARN IT

A **survey** (or **questionnaire**) is useful when the **same set of questions** needs to be asked to **many people**.

- It may be on **paper** or created with **digital tools** such as **Google Forms** or **Microsoft Forms**.
- **Note:** online survey tools **automatically collect responses** and **display basic charts**, which makes data analysis much easier.

Types of survey and interview questions

Question type	What it looks like	Data it gives
Closed: Yes/No	Do you study with your phone nearby? (Yes / No)	Countable (quantitative)
Closed: Multiple choice	Which activity do you use your phone for most? (Lectures / Notes / Social media / Games)	Categories you can count
Number / scale	How many hours do you use your phone daily? ____	Quantitative
Rating scale	"My phone helps me study." 1 = Strongly disagree ... 5 = Strongly agree	Quantitative (you can average the ratings)
Open-ended	How does your phone help you in studies?	Qualitative (free text)

Good questions vs bad questions

A good question is **clear, short, unbiased** (it does not push the person towards one answer) and asks about **one thing at a time**.

Problem	Bad question	Better question
Leading / biased – suggests the "right" answer	Don't you agree that phones waste students' time?	How do phones affect your study time? (Helps a lot / Helps a little / No effect / Harms a little / Harms a lot)
Double-barrelled – two questions in one	Do you use your phone for lectures and games?	Split into two: "Do you use your phone for lectures?" and "Do you use your phone for games?"
Vague – unclear words	Do you use your phone a lot?	How many hours do you use your phone on a normal school day?
Overlapping options	1-3 hrs / 3-5 hrs / 5+ hrs (where does exactly 3 go?)	Less than 3 hrs / 3 to less than 5 hrs / 5 hrs or more
Sensitive / too personal	What is your father's monthly income?	Leave it out unless it is truly needed for the study.

WORKED EXAMPLE

Building a short Google Form, step by step. Research question: "How do Class XI students travel to college?"

Step 1: Open Google Forms → Blank form → Title: "Travel to College Survey". Add a description: "This survey is anonymous and for a class project. Do you agree to take part? (Yes/No)" – this is your **consent** question.

Step 2: Q1 (multiple choice): "How do you usually travel to college?" Walk / Bus / Rickshaw / Motorbike / Car / Other.

Step 3: Q2 (number): "How many minutes does your journey take?"

Step 4: Q3 (open-ended): "What is the biggest problem you face while travelling?"

Step 5: Click Send and share the link in the class group. Responses appear in the Responses tab with automatic pie/bar charts, and can be opened in Google Sheets.

Result: Q1 and Q2 give quantitative data; Q3 gives qualitative data.

REMEMBER IT

Interview – **In-depth with few. Survey** – **Same questions to many.** Think of a doctor talking to one patient (interview) vs a census form sent to every house (survey).

COMMON MISTAKE

Mistake: Writing only open-ended questions in a survey for 100 people. You will get 100 paragraphs that are very hard to analyse. **Fix:** Use mostly closed or number questions in a large survey, and only one or two open-ended questions.

آرٹو میں سمجھیں

انٹرویو ایک منصوبہ بند گفتگو ہے جس میں کسی ایک فرد یا چھوٹے گروہ سے براہ راست معلومات حاصل کی جاتی ہیں؛ اس کے جوابات عموماً کیفیتی ہوتے ہیں۔ سروے میں ایک ہی سوالات بہت سے لوگوں سے پوچھے جاتے ہیں، کاغذ پر یا گوگل فارمز (Google Forms) جیسے ڈیجیٹل ٹولز کے ذریعے، جو جوابات خودکار طور پر جمع کر کے چارٹ بھی دکھاتے ہیں۔ اچھا سوال واضح، مختصر، غیر جانبدار اور ایک وقت میں ایک ہی بات کہہ بازے میں ہوتا ہے۔

EXAM TIP

You may be asked to "differentiate between an interview and a survey" or to "identify what is wrong with this survey question and rewrite it". For rewriting, name the problem (leading, double-barrelled, vague, overlapping) and give the corrected version.

CHECK YOURSELF

1. Name two digital tools for creating surveys.
2. What is wrong with: "Do you enjoy maths and physics?"
3. Are interview answers usually qualitative or quantitative?

Answers: 1. Google Forms and Microsoft Forms. 2. It is double-barrelled (two subjects in one question); ask about each subject separately. 3. Usually qualitative.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An interview is: a. A spoken Q&A, often fewer people, deeper b. A 500-person tick sheet always c. A NAND d. A pie	MCQ 2. A survey is: a. The same questions to many people b. Always one celebrity chat c. A sort d. A cable	MCQ 3. Closed questions are easier to: a. Count and chart b. Explore feelings c. Build CPUs d. Route IP	MCQ 4. Open questions are better for: a. Reasons and quotes b. Instant averages c. Primary keys d. Gray codes	MCQ 5. A leading question is: a. Biased b. Required c. A foreign key d. A sprint	MCQ 6. Sampling matters because: a. Only asking prefects is not the whole college b. n always equals 1 c. Charts ignore n d. Ethics forbid samples
---	---	--	--	---	---

Extra short questions

1. Differentiate interview and survey.
2. Two question-writing rules.
3. When mix both?
4. What is a pilot?

Extra long question

1. Write 4 survey questions (2 closed, 2 open) on screen time, plus 3 interview prompts. Mark any bias you avoided.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Interview: deep, slow, few. Survey: standardised, many, shallower.
2. One idea per item; avoid leading; simple Urdu/English; pilot test.
3. Survey for numbers, then interview to explain a surprising number.
4. Try the form on 5 classmates and fix confusing items.

Long

1. Closed: hours bands; devices. Open: why night use; effect on sleep. Interview: walk me through yesterday evening. No "don't you think phones are evil".

6.4.3 – 6.4.5 Prototypes, Observation, and Simulations ★ Golden

6.4.3 Prototypes

LEARN IT

A **prototype** is a **simple early version** of a product, model or solution. It allows an idea to be **tested before** time and effort are spent on the final version. Users **try** the prototype and give **feedback**, and this feedback becomes useful **data for improvement**.
Example: Before building a full school app, you draw the screens on paper (or make a few clickable screens in a design tool) and ask five classmates to try "finding the timetable". You note where they get confused.

6.4.4 Observation

LEARN IT

In **observation**, the researcher **watches** what people do or what happens in a situation and **records the results carefully**. **No direct questions are asked**.
The data may be **qualitative** (written notes, e.g. "students push in the queue") or **quantitative** (counts, e.g. "42 students bought samosas in 10 minutes").
Why use it? People sometimes say one thing and do another. Observation shows what really happens.

6.4.5 Simulations

LEARN IT

A **simulation** is a **computer-based model of a real situation**. **Variables** (the things that can change, like speed, temperature or number of people) can be changed to see what happens.
Simulations are highly useful when **real experiments are costly, risky or difficult** to perform.
Examples: a flight simulator for training pilots (real crashes are dangerous); a traffic simulation to test what happens if a new signal is added (changing real roads is costly); a weather model to predict a cyclone (you cannot experiment with real weather).

WORKED EXAMPLE

Choosing the right method. Which method would you use?
(a) **"How many cars cross an intersection at 8 AM?"** → **Observation**. Stand at the corner from 8:00 to 8:15 and tally each car. Asking drivers would be impossible and unnecessary; you just count.
(b) **"How do students feel about the new cafeteria food?"** → **Survey or interview**. Feelings are inside people's heads, so you must ask them. Use a survey for many students, or interviews for deeper reasons.
(c) **"Will a new college website menu be easy to use?"** → **Prototype**. Build a rough version and let users try it.
(d) **"What happens to traffic if the bridge is closed for repairs?"** → **Simulation**. Closing a real bridge to test is costly and disruptive.

REMEMBER IT

Watch it → Observation. **Ask** it → Survey/Interview. **Try** it → Prototype. **Model** it → Simulation.

COMMON MISTAKE

Mistake: Saying that observation involves asking people questions. **Fix:** In observation, **no direct questions** are asked – the researcher only watches and records. Also, a prototype is not the finished product; it is an early test version.

آرڈو میں سمجھیں

پروٹوٹائپ کسی پروڈکٹ یا حل کا ابتدائی سادہ نمونہ ہے جسے صارفین آزما کر رائے دیتے ہیں تاکہ اسے بہتر بنایا جا سکے۔ مشاہدے (Observation) میں محقق کوئی سوال نہیں پوچھتا بلکہ صرف دیکھ کر نتائج درج کرتا ہے۔ سیمولیشن کسی حقیقی صورتحال کا کمپیوٹر ماڈل ہے، جو اس وقت مفید ہے جب حقیقی تجربہ مہنگا، خطرناک یا مشکل ہو۔

EXAM TIP

Scenario questions are popular: "Which data-collection method is most suitable for ... ? Give a reason." Always name the method **and** justify it using its key feature (e.g. "Simulation, because a real experiment would be risky").

CHECK YOURSELF

- Why would an engineer use a simulation instead of a real test?
- Can observation produce quantitative data? Give an example.
- What becomes the "data" when using a prototype?

Answers: 1. Because the real experiment may be costly, risky or difficult. 2. Yes – for example, counting the number of cars passing a point. 3. The feedback users give after trying the prototype.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A prototype here is:

- a. An early model to test an idea
- b. The final app store release
- c. A primary key
- d. A histogram

MCQ 2. Observation means:

- a. Watching what people actually do
- b. Only asking them
- c. Only simulating
- d. Only Googling

MCQ 3. Simulation is:

- a. A model of a system you can run
- b. A real flood in the campus
- c. A NAND chip
- d. A foreign key

MCQ 4. People say they wait 2 minutes but observation shows 10: trust:

- a. Observation of that behaviour
- b. The boast
- c. Neither ever
- d. OSI

MCQ 5. Paper screens of an app are a:

- a. Low-fidelity prototype
- b. MVP already selling
- c. Database schema
- d. Pie chart

MCQ 6. Simulations are useful when:

- a. Real experiments are costly or unsafe
- b. You already have all answers
- c. n=1 always
- d. Ethics forbid models

Extra short questions

- Define prototype, observation, simulation in one line each.
- One limit of observation.
- One limit of simulation.
- When is a prototype better than a survey?

Extra long question

- A team wants a quieter library. Combine prototype, observation and simulation in a plan with ethics.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Prototype: early model. Observation: watch. Simulation: run a model.
- Hawthorne effect — people act differently when watched.
- Wrong assumptions → pretty but false results.
- When you need to see if a design is usable, not just popular in words.

Long

- Observe noise sources; prototype signage/zones; simulate seating. Consent to watch; no filming faces for TikTok. What would change your mind (data).

6.5 Primary and Secondary Data ★ Golden

LEARN IT
Whenever you use data, it is important to know **where it came from**. The source affects how much **control** the researcher had over collecting it, and how **confidently** the results can be used.

6.5.1 Primary Data
Primary data is collected **first-hand** by the researcher for a **particular purpose**. It is gathered **directly** from people, events or situations, rather than taken from an already published source.
Sources: interviews, surveys, observations, experiments.

6.5.2 Secondary Data
Secondary data has **already been collected by someone else** and is being used again for a **new purpose**. It is taken from existing archives (stored collections of information).
Sources: books, research articles, official reports, web statistics, online databases.



Primary data is collected by you; secondary data was collected by others.

6.5.3 Difference Between Primary and Secondary Data

Aspect	Primary Data	Secondary Data
Source	Collected directly by the researcher.	Already collected by others.
Examples	Survey responses, interviews, observations.	Reports, articles, websites, databases.
Purpose	Prepared for a specific study.	Reused for a new purpose.
Control	High control over questions and collection process.	Limited control because the data already exists.

WORKED EXAMPLE
Primary or secondary? Hira is researching "Internet use among students in Hyderabad".
(a) She sends a Google Form to 50 students in her college. → **Primary** (she collected it herself, for this study).
(b) She uses a PTA (Pakistan Telecommunication Authority) report on the number of broadband users in Pakistan. → **Secondary** (PTA collected it for its own purpose; Hira reuses it).
(c) She counts how many students use phones in the library during one hour. → **Primary** (her own observation).
(d) She quotes a statistic from a research article. → **Secondary**.
Why use both? Her primary data tells her about *her own* college; the secondary data lets her **compare** it with the national picture.

REMEMBER IT
Primary = "1st hand" (you collect it first). **Secondary = "2nd hand"** (like a second-hand book – someone else used it first).

COMMON MISTAKE
Mistake: Thinking data from a website is always primary because "I found it myself". **Fix:** What matters is **who collected** the data. If someone else collected it and you only found it, it is secondary.

اردو میں سمجھیں

بنیادی ڈیٹا (Primary Data) محقق خود کسی خاص مقصد کے لیے براہ راست جمع کرتا ہے، مثلاً سروے، انٹرویو یا مشاہدہ۔ ثانوی ڈیٹا (Secondary Data) پہلے ہی کسی اور نے جمع کیا ہوتا ہے اور اسے نئے مقصد کے لیے دوبارہ استعمال کیا جاتا ہے، جیسے کتابیں، رپورٹس اور آن لائن ڈیٹا بیس۔ بنیادی ڈیٹا پر محقق کا کنٹرول زیادہ اور ثانوی ڈیٹا پر کم ہوتا ہے۔

EXAM TIP
"Differentiate between primary and secondary data" is one of the most-asked questions in this chapter. Draw the four-row table: **Source, Examples, Purpose, Control**. Learn it exactly. Add one example from each side to secure full marks.

CHECK YOURSELF
1. Which type of data gives the researcher high control?
2. Is a government census report primary or secondary data for your project?
3. Give two sources of primary data.

Answers: 1. Primary data. 2. Secondary (someone else collected it). 3. Any two: interviews, surveys, observations, experiments.

Extra board practice
These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Primary data is:
a. Collected by you for this question
b. Copied from a textbook table always
c. Always tertiary
d. A NAND output

MCQ 2. Secondary data is:
a. Collected by others, reused
b. Your interview today
c. Always fake
d. A pie only

MCQ 3. You control quality more with:
a. Primary
b. Secondary always
c. Tertiary always
d. None

MCQ 4. Secondary is often:
a. Faster and cheaper
b. Always more accurate
c. Always ethical-free
d. Always qualitative

MCQ 5. Census tables you download are:
a. Secondary for you
b. Primary for you
c. Not data
d. A query object

MCQ 6. A common exam pair is:
a. Define both + one difference + one example each
b. Only Big O
c. Only ER
d. Only Agile

Extra short questions
1. Table: primary vs secondary on source, control, cost, example.
2. One risk of secondary.
3. One risk of primary.
4. Can a project use both?

Extra long question
1. For "canteen waiting time", list primary and secondary data you would gather, and how each could lie. ★ Golden.

Extra answer key
MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short
1. You vs others; high vs low control; high vs low cost; survey vs PBS stats.
2. Out of date, different definitions, hidden bias.
3. Small sample, poor questions, time.
4. Yes — and the book's inquiry project does.

Long
1. Primary: observe queues, survey. Secondary: last year's complaint log, news on food inflation. Lies: observed only at 8am; old log incomplete. Triangulate.

6.6 Designing a Data-Collection Approach

LEARN IT

Before collecting data, a researcher must have a **plan**. A plan makes sure that the information gathered is **accurate**, **relevant** (related to the question) and **useful**. Follow these eight steps in order:

1. **Define the research question clearly.** What exactly do you want to find out?
2. **Decide the type of data needed:** quantitative, qualitative, or both.
3. **Select suitable methods** (survey, interview, observation).
4. **Choose the sample or target group** – the people who will give you data.
5. **Prepare the tools** such as forms, questions and observation sheets.
6. **Collect the data** carefully and accurately.
7. **Store the data digitally** in a spreadsheet and **keep a backup**.
8. **Follow ethical practice and respect privacy.** **Consent is mandatory** (you must get permission).

Question → Data type → Method → Sample → Tools → Collect → Store + backup → Ethics

WORKED EXAMPLE

Applying the eight steps. Topic: water wastage in your college.

1. **Question:** "How much water is wasted at the college taps during break time, and why?"
2. **Data type:** Both – quantitative (number of taps left running, minutes) and qualitative (reasons students give).
3. **Methods:** Observation (count running taps) + a short survey (ask about habits).
4. **Sample:** All 12 taps in the college; 30 students from different classes for the survey.
5. **Tools:** An observation sheet with columns *Tap no.* / *Time / Left running?* (Y/N) / *Minutes*; a Google Form with 5 questions.
6. **Collect:** Observe during break for five days; send the form link.
7. **Store:** Enter the observation counts into Google Sheets; download a copy to a USB drive as backup.
8. **Ethics:** Ask the principal's permission; tell students the survey is anonymous and voluntary; do not record names.

REMEMBER IT

Remember the steps with: "Quiet Teachers Make Students Think, Check, Save Ethically" → Question, Type, Method, Sample, Tools, Collect, Store, Ethics.

COMMON MISTAKE

Mistake: Starting to collect data before writing a clear research question. You then collect lots of data that does not answer anything. **Fix:** Always write the question first. Another mistake: keeping data in only one place – if the file is lost, the project is lost. Always keep a backup.

آردو میں سمجھیں

ڈیٹا جمع کرنے سے پہلے منصوبہ بندی ضروری ہے: تحقیقی سوال واضح کریں، ڈیٹا کی قسم طے کریں، مناسب طریقہ چنیں، نمونہ (Sample) منتخب کریں، فارم اور سوالات تیار کریں، احتیاط سے ڈیٹا جمع کریں، اسے اسپریڈشیٹ میں محفوظ کر کے بیک اپ رکھیں، اور اخلاقیات کا خیال رکھیں۔ اجازت (Consent) لینا لازمی ہے۔

CHECK YOURSELF

1. What is the first step in designing a data-collection approach?
2. Which step says "consent is mandatory"?
3. Where should collected data be stored?

Answers: 1. Define the research question clearly. 2. Step 8 – follow ethical practice and respect privacy. 3. Digitally, in a spreadsheet, with a backup copy.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Data-collection strategies include:

- a. Interview, survey, prototype, observation, simulation
- b. Only NAND
- c. Only OSI ping
- d. Only K-maps

MCQ 2. You collect data when:

- a. Existing sources are not enough
- b. You already have the full census always
- c. The question is undefined
- d. You only need a meme

MCQ 3. A strategy must match:

- a. The question and the people
- b. The teacher's favourite chart only
- c. Agile always
- d. TCP window

MCQ 4. Bias in collection:

- a. Systematically distorts answers
- b. Improves SD always
- c. Is required in exams
- d. Is a primary key

MCQ 5. Ethics: people should:

- a. Know and consent
- b. Be filmed secretly always
- c. Hand over passwords
- d. Be named in viral posts

MCQ 6. This is ★ because papers ask:

- a. Name + when to use + one limit of a method
- b. Only Python turtles
- c. Only ER
- d. Only Big O

Extra short questions

1. List five strategies from the book.
2. One advantage of planning methods first.
3. One ethical rule.
4. What is a biased question?

Extra long question

1. Choose methods for: (a) why students skip practicals (b) how a new ID-card prototype feels (c) traffic at the gate. Justify. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Interview, survey, prototype, observation, simulation (and others in 6.4).
2. You do not collect the wrong type of data for your chart later.
3. Informed consent; anonymise students.
4. "Don't you agree our canteen is terrible?" — pushes the answer.

Long

1. (a) Interview+survey (b) prototype test (c) observation/count or simulation. Limits of each. Ethics sentence.

6.7 Presenting Data Using Digital Tools

LEARN IT
Collecting data is only **one part** of the work. You must also **present** your findings so that others can understand them **quickly and easily**. Digital tools make this much easier. The four main tools are spreadsheets, presentations, infographics and reports.

6.7.1 Spreadsheets

LEARN IT
Spreadsheets such as **MS Excel**, **Google Sheets** and **Apple Numbers** arrange information in **rows** (horizontal, numbered 1, 2, 3...) and **columns** (vertical, lettered A, B, C...). The box where a row and column meet is a **cell**, named by its column and row, e.g. **B2**. With a spreadsheet you can:

- **Enter data** systematically (one record per row).
- **Calculate** totals, averages and percentages.
- **Sort** (arrange in order) and **filter** (show only some rows) records.
- **Create charts and graphs** automatically.

A **formula** always starts with =. A **range** such as B2:B4 means "cells B2 to B4".

Formula	What it does
=SUM(B2:B4)	Adds all values in B2 to B4.
=AVERAGE(B2:B4)	Mean: sum ÷ number of values.
=MAX(B2:B4) / =MIN(B2:B4)	Largest / smallest value.
=MEDIAN(B2:B4)	Middle value when sorted.
=COUNT(B2:B4)	Counts cells containing numbers.
=COUNTA(C2:C4)	Counts cells that are not empty (text or numbers).
=COUNTIF(C2:C4,"Yes")	Counts cells that match a condition.

WORKED EXAMPLE
Analysing the case-study spreadsheet. The data from the 6.8 case study (Step 8) is entered like this:

	A	B	C	D	E
1	Student	Hours	Study Use	Main Activity	Distracted?
2	1	3	Yes	Lectures	Sometimes
3	2	5	No	Social Media	Yes
4	3	2	Yes	Notes	No

Step 1 – Total hours: =SUM(B2:B4) → 3 + 5 + 2 = 10.
Step 2 – Average hours: =AVERAGE(B2:B4) → 10 ÷ 3 = **3.33** hours (to 2 decimal places).
Step 3 – Most and least: =MAX(B2:B4) → 5; =MIN(B2:B4) → 2.
Step 4 – Median: sorted values 2, 3, 5 → middle = 3. =MEDIAN(B2:B4) gives 3.
Step 5 – How many use the phone for study? =COUNTIF(C2:C4,"Yes") → 2.
Step 6 – Percentage: =COUNTIF(C2:C4,"Yes")/COUNTA(C2:C4) → 2 ÷ 3 = 0.667; format the cell as % → **66.7%**.
Step 7 – How many said "Yes" to distracted? =COUNTIF(E2:E4,"Yes") → 1 (only "Yes" matches; "Sometimes" does not).
Step 8 – Sort: select the data → Data → Sort by column B (largest to smallest) → order becomes Student 2 (5), Student 1 (3), Student 3 (2).

6.7.2 Presentations

LEARN IT
Presentation software such as **PowerPoint**, **Google Slides** and **Canva** helps you explain findings to an **audience** in an organised way. Good practice:

- Begin with a clear **title** and the **research question**.
- Use **short bullet points** instead of long paragraphs.
- Include **tables, charts and key findings**.
- Keep the design **simple and readable** (large font, few colours).

Spreadsheets and presentations work together: you make a chart from the spreadsheet data and insert it into the slides.

Spreadsheet data → Chart / Graph → Insert → Slides

REMEMBER IT
Presentation rule of thumb: **one idea per slide**, and no more than about **six short bullet points**. If you are reading long sentences off the slide, the slide has too much text.

COMMON MISTAKE
Mistake: Typing a result by hand (e.g. writing "3.33" in a cell) instead of using a formula. If the data changes, the typed result becomes wrong. **Fix:** Always use formulas like =AVERAGE(B2:B4) so results update automatically. Also remember every formula must begin with =.

آرڈو میں سمجھیں

ڈیٹا جمع کرنے کے بعد اسے پیش کرنا بھی ضروری ہے۔ اسپریڈشیت (جیسے اینکسل اور گوگل شیٹس) میں ڈیٹا فہرستوں اور ٹیبلوں میں ترتیب دیا جاتا ہے، اور (=SUM) اور (=AVERAGE) جیسے فارمولوں سے مجموعہ، اوسط اور فیصد نکالے جاتے ہیں۔ پریزنٹیشن سافٹ ویئر (جیسے پاور پوائنٹ) میں مختصر نکات، چارٹس اور سادہ ایڈز کے ساتھ نتائج سامعین کے سامنے پیش کیے جاتے ہیں۔

CHECK YOURSELF

1. Write the formula to find the average of cells D2 to D20.
2. Name three spreadsheet programs.
3. Give two rules for a good presentation.

Answers: 1. =AVERAGE(D2:D20) . 2. MS Excel, Google Sheets, Apple Numbers. 3. Any two: start with a clear title and research question; use short bullet points; include tables/charts/key findings; keep design simple and readable.

Extra board practice
These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Spreadsheets are good for:

a. Tables, calculations, simple charts
b. 3D games
c. NAND simulation
d. OSI sniffing

MCQ 2. A presentation (slides) is for:

a. Talking an audience through findings
b. Storing the only copy of raw data
c. Primary keys
d. Kernel drivers

MCQ 3. An infographic is:

a. A visual one-pager of facts
b. A 40-page appendix
c. A binary search
d. A foreign key

MCQ 4. A report is:

a. Structured writing with method, results, limits
b. Only memes
c. Only code
d. Only ER

MCQ 5. Choose the tool by:

a. Audience and purpose
b. Whatever is newest
c. Always infographic
d. Always 80 slides

MCQ 6. Raw 2000-row sheets in a 5-minute talk are:

a. A bad present
b. Ideal
c. Required by BIEK
d. A sort algorithm

Extra short questions

1. Four digital presentation tools in the book.
2. When spreadsheet > slides.
3. When infographic > report.
4. One rule for all four.

Extra long question

1. Same finding (70% of surveyed students want longer labs). Design: a spreadsheet cell, a slide headline, an infographic hook, and a report paragraph.

Extra answer key
MCQs: 1. A 2. A 3. A 4. A 5. A 6. A
Short
1. Spreadsheets, slides, infographics, reports.
2. When the audience must check the numbers or filter.
3. Awareness poster / social post – not a methods thesis.
4. Cite sources; label axes; do not crop axes to lie.
Long
1. Sheet table-bar. Slide: one number, one chart, one ask. Infographic: 7 of 10 icon row. Report: sample n, question wording, 70%, limit (one college).

6.7.1 – 6.7.4 Spreadsheets, Presentations, Infographics, Reports

6.7.3 Infographics

LEARN IT

An **infographic** (information + graphic) is a **visual way** of presenting information, facts or data so that people can understand the main idea **quickly and easily**. Tools such as **Canva**, **Power BI** or **Tableau** can be used. A good infographic should:

- **Simplify** complex concepts.
- **Highlight** the most important findings and results.
- Use **clear visuals**, **limited text** and **accurate** information.

6.7.4 Reports

LEARN IT

Reports are **structured documents** used to present collected data, findings, analysis and conclusions. Tools like **MS Word** or **Google Docs** are standard. A good report should:

- Start with a clear **title**, **introduction** and **purpose**.
- Present the collected data using **tables** or **charts**.
- Explain findings in **simple language**.
- Include **conclusions and recommendations** based on the data.

Optional: you may use AI tools carefully to improve wording, but **always review for accuracy**. AI can make mistakes or invent facts, and you are responsible for what you submit.

LEARN IT

Visual rule of thumb: a good chart or infographic can explain complex data **faster** than a long paragraph. However, visuals must always be **accurate** and based strictly on the **real data collected** – never exaggerated.

WORKED EXAMPLE

Which tool should you choose?

Situation	Best tool	Why
You must calculate the average marks of 40 students.	Spreadsheet	Formulas calculate instantly.
You will explain results to the class in assembly.	Presentation	Designed for a live audience.
You want a one-page poster for the notice board.	Infographic	Main result understood at a glance.
The principal wants the full study with method and recommendations.	Report	Detailed, structured document.

REMEMBER IT

Match tool to job: **Spreadsheet = Calculate**, **Presentation = Tell**, **Infographic = Show quickly**, **Report = Explain fully**.

COMMON MISTAKE

Mistake: Making a chart look more dramatic than the data – for example, starting the bar-chart axis at 18 instead of 0 so that 20 looks twice as big as 19. **Fix:** Start bar-chart axes at 0, label axes, and show real numbers only.

اردو میں سمجھیں

انفوگرافک معلومات کو تصویری انداز میں پیش کرنے کا طریقہ ہے تاکہ اصل بات جلدی سمجھ آ جائے، اس کے لیے کینوا (Canva) اور پاور بی آئی (Power BI) جیسے ٹولز استعمال ہوتے ہیں۔ رپورٹ ایک منظم دستاویز ہے جس میں عنوان، تعارف، ڈیٹا، نتائج، اختتامیہ اور سفارشات شامل ہوتی ہیں۔ تصاویر اور چارٹس ہمیشہ اصل ڈیٹا کے مطابق اور درست ہونے چاہئیں، مبالغہ آمیز نہیں۔

CHECK YOURSELF

1. Name two tools for making infographics.

2. What must you always do if you use AI to improve your report's wording?

3. What should a report end with?

Answers: 1. Any two: Canva, Power BI, Tableau. 2. Review it carefully for accuracy. 3. Conclusions and recommendations based on the data.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Spreadsheets are good for:

a. Tables, calculations, simple charts

b. 3D games

c. NAND simulation

d. OSI sniffing

MCQ 2. A presentation (slides) is for:

a. Talking an audience through findings

b. Storing the only copy of raw data

c. Primary keys

d. Kernel drivers

MCQ 3. An infographic is:

a. A visual one-pager of facts

b. A 40-page appendix

c. A binary search

d. A foreign key

MCQ 4. A report is:

a. Structured writing with method, results, limits

b. Only memes

c. Only code

d. Only ER

MCQ 5. Choose the tool by:

a. Audience and purpose

b. Whatever is newest

c. Always infographic

d. Always 80 slides

MCQ 6. Raw 2000-row sheets in a 5-minute talk are:

a. A bad present

b. Ideal

c. Required by BIEK

d. A sort algorithm

Extra short questions

1. Four digital presentation tools in the book.

2. When spreadsheet > slides.

3. When infographic > report.

4. One rule for all four.

Extra long question

1. Same finding (70% of surveyed students want longer labs). Design: a spreadsheet cell, a slide headline, an infographic hook, and a report paragraph.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Spreadsheets, slides, infographics, reports.

2. When the audience must check the numbers or filter.

3. Awareness poster / social post — not a methods thesis.

4. Cite sources; label axes; do not crop axes to lie.

Long

1. Sheet: table+bar. Slide: one number, one chart, one ask. Infographic: 7 of 10 icon row. Report: sample n, question wording, 70%, limit (one college).

6.8 Case Study: Digital Inquiry Project ★ Golden

LEARN IT

This case study shows how to apply **all** the ideas of this chapter to solve a real-world problem from start to finish. An **inquiry** is an investigation to find the answer to a question.

Research question: "How does daily mobile phone use affect the study habits of students?"

Scenario: Students notice classmates using phones during free periods and while studying. Some say phones **help** them learn; others say phones **waste time**. The class must investigate whether phone use helps or harms study habits.

The digital inquiry workflow



The project is carried out in **12 steps** that fit into this five-stage workflow:

Workflow stage	Steps
Question & Search	1 Advanced searches · 2 Identify data types · 3 Select methods
Collect	4 Prepare the survey · 5 Choose the sample · 6 Collect primary data ethically · 7 Use secondary data
Analyse	8 Organise in a spreadsheet · 9 Create charts · 10 Analyse results
Create	11 Write the conclusion · 12 Recommendations → final digital artefact

REMEMBER IT

Workflow in five words: **Ask → Search → Collect → Analyse → Create**. Every research project you ever do will follow this pattern.

اُردو میں سمجھیں

اس کیس اسٹڈی میں تحقیقی سوال یہ ہے: "روزانہ موبائل فون کا استعمال طلبہ کی پڑھائی کی عادات پر کیسے اثر ڈالتا ہے؟" تحقیق پانچ مراحل میں ہوتی ہے: سوال، تلاش، ڈیٹا جمع کرنا، تجزیہ اور آخری پروڈکٹ بنانا۔ یہ کام بارہ قدموں میں مکمل کیا جاتا ہے۔

EXAM TIP

Expect a long question: "Describe the steps of a digital inquiry project using the example of mobile phone use." Write the research question first, then the 12 steps with one or two lines each, and finish with the artefact. Learn the five-stage workflow as your skeleton.

CHECK YOURSELF

- What is the research question in the case study?
- Name the five stages of the digital inquiry workflow.

Answers: 1. "How does daily mobile phone use affect the study habits of students?" 2. Question, Search, Collect, Analyse, Create.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The digital inquiry project applies:

- All of chapter 6 in order
- Only careers
- Only NAND
- Only OSI

MCQ 2. Advanced search helps you:

- Narrow secondary sources (quotes, site, date)
- Hack Wi-Fi
- Draw K-maps
- Sort in $O(1)$

MCQ 3. Primary collection in the project is often:

- A class survey
- A CPU design
- A TCP stack
- A waterfall contract

MCQ 4. You organise results in a:

- Spreadsheet + charts
- Random WhatsApp dump only
- NAND netlist
- Figma only

MCQ 5. The artefact is:

- The final digital product that answers the question
- The first brainstorm sticky
- The career list
- The teacher's attendance

MCQ 6. A conclusion should:

- Answer the question and admit limits
- Ignore the data
- Name and shame students
- Invent $n=1$ million

Extra short questions

- List the project steps in order (grouped as in the book).
- What is a digital artefact here?
- Why include secondary if you surveyed?
- One sentence of a good limitation.

Extra long question

- Outline a 12-step inquiry: "Does extra screen time lower concentration in our class?" Name tools and the artefact. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Search/method; survey/primary; secondary+sheet; analyse/conclude; artefact.
- Slides, infographic, short video, site — that answers the inquiry question.
- To compare your small sample with a published claim.
- $n=40$ in one college, so we cannot speak for all Sindh.

Long

- Steps 1–3 search; 4–6 survey; 7–9 PBS/article + sheet; 10–12 charts, conclusion, artefact (infographic+spreadsheet). Ethics. One expected chart: hours vs self-reported focus.

Step 1 – 3: Advanced Search & Methodology ★ Golden

The **methodology** is the plan of methods a researcher uses to answer the question.

Step 1: Perform advanced searches

LEARN IT

Students first search for **background information** using search engines (such as Google or Bing). They use **advanced search operators** – special symbols or words typed into the search box – to **narrow down** results and find **reliable secondary data**.

Suggested query	Operator used	What it does
"mobile phone use" "study habits" students	" " (quotes)	Finds the exact phrases "mobile phone use" and "study habits", not the words scattered randomly.
"academic performance" filetype:pdf	filetype:	Finds only PDF documents (often official reports and research papers).
digital distraction site:.edu	site:	Searches only educational websites (addresses ending in .edu).

Other useful operators (background): - (minus) excludes a word, e.g. phone addiction -game; OR finds either word, e.g. smartphone OR mobile; site:.gov.pk searches only Pakistani government websites.

LEARN IT

Source evaluation checklist. Before trusting a source, ask:

- ☐ Is the **author/organisation** clearly mentioned?
- ☐ Is the website **reliable** (.edu, .gov, research-based)?
- ☐ Is the information **recent**?
- ☐ Does the source provide **facts/references**, or is it **biased** (one-sided, trying to sell something)?

WORKED EXAMPLE

Building a search query step by step. You want official PDF reports about screen time of students on Pakistani government websites.

Step 1 – Plain search: screen time students → millions of results, many blogs and adverts.

Step 2 – Exact phrase: "screen time" students → results must contain the exact phrase.

Step 3 – Only PDFs: "screen time" students filetype:pdf → mostly reports and papers.

Step 4 – Only government sites: "screen time" students filetype:pdf site:.gov.pk → a small number of highly relevant, reliable results.

Step 5 – Evaluate: open a result and check the checklist: author named? year recent? references given?

Step 2: Identify data types

LEARN IT

Students decide what kind of **primary data** they will collect:

- **Quantitative:** number of hours used daily; percentage who feel distracted.
- **Qualitative:** opinions on why they get distracted; suggestions for better use.

Step 3: Select data-collection methods

LEARN IT

Because they need to ask the **same questions to many students**, a **survey/questionnaire** (via Google Forms or on paper) is the **most efficient** method. Interviews would take too long for so many people, and observation could not reveal opinions.

REMEMBER IT

Three operators, three jobs: " " = **exact**, filetype: = **format**, site: = **where**. Note: there is **no space** after the colon (site:.edu, not site: .edu).

COMMON MISTAKE

Mistake: Assuming the first search result is the most reliable. Search results can be adverts or popular blogs. **Fix:** Always apply the source evaluation checklist. A website ending in .edu or .gov is usually more reliable, but you should still check the date and author.

اُردو میں سمجھیں

پہلے قدم میں طلبہ سرچ انجن پر جدید سرچ آپریٹرز (Advanced Search Operators) استعمال کرتے ہیں؛ کوئشن مارکس (") بالکل وہی جملہ تلاش کرتے ہیں، filetype:pdf صرف پی ڈی ایف فائلیں اور site:.edu صرف تعلیمی ویب سائٹس دکھاتا ہے۔ ہر ذریعے کو مصنف، تاریخ، قابل اعتماد ویب سائٹ اور حوالوں کی بنیاد پر پرکھا جاتا ہے۔ پھر دنیا کی اقسام طے کی جاتی ہیں اور بہت سے طلبہ سے سوال کرنے کے لیے سروے کو بہترین طریقہ چنا جاتا ہے۔

EXAM TIP

"Explain any three advanced search operators with examples" is a likely short question. For each, write the operator, an example query, and what it does. Also learn the four-point source evaluation checklist.

CHECK YOURSELF

1. Write a query that finds the exact phrase "online learning" only on educational websites.
2. Why was a survey chosen in Step 3?
3. Give one quantitative and one qualitative data item from Step 2.

Answers: 1. "online learning" site:.edu. 2. Because the same questions had to be asked to many students, and a survey is the most efficient way to do that. 3. Quantitative: hours used daily (or % who feel distracted). Qualitative: opinions on why they get distracted (or suggestions for better use).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The digital inquiry project applies: a. All of chapter 6 in order b. Only careers c. Only NAND d. Only OSI	MCQ 2. Advanced search helps you: a. Narrow secondary sources (quotes, site, date) b. Hack Wi-Fi c. Draw K-maps d. Sort in O(1)	MCQ 3. Primary collection in the project is often: a. A class survey b. A CPU design c. A TCP stack d. A waterfall contract	MCQ 4. You organise results in a: a. Spreadsheet + charts b. Random WhatsApp dump only c. NAND netlist d. Figma only	MCQ 5. The artefact is: a. The final digital product that answers the question b. The first brainstorm sticky c. The career list d. The teacher's attendance	MCQ 6. A conclusion should: a. Answer the question and admit limits b. Ignore the data c. Name and shame students d. Invent n=1 million
--	---	--	---	---	--

Extra short questions

1. List the project steps in order (grouped as in the book).
2. What is a digital artefact here?
3. Why include secondary if you surveyed?
4. One sentence of a good limitation.

Extra long question

1. Outline a 12-step inquiry: "Does extra screen time lower concentration in our class?" Name tools and the artefact. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Search/method; survey/primary; secondary+sheet; analyse/conclude; artefact.
2. Slides, infographic, short video, site — that answers the inquiry question.
3. To compare your small sample with a published claim.
4. n=40 in one college, so we cannot speak for all Sindh.

Long

1. Steps 1–3 search; 4–6 survey; 7–9 PBS/article + sheet; 10–12 charts, conclusion, artefact (infographic+spreadsheet). Ethics. One expected chart: hours vs self-reported focus.

Step 4 – 6: Survey Prep & Primary Data Collection ★ Golden

Step 4: Prepare the survey

LEARN IT

Design **clear, unbiased** questions. Each question is linked to the type of data it produces:

Question	Type of data
How many hours do you use your phone daily?	Quantitative
Which activity do you use your phone for the most?	Quantitative (categories)
How does your phone help you in studies?	Qualitative
Suggest one way to use phones responsibly.	Qualitative

Step 5: Choose the sample

LEARN IT

The **sample** is the group of people who provide the data. It is usually impossible to ask everyone (the whole **population**), so a smaller group is chosen. The students decide to survey **40 Class XI students from different sections** to get a **representative** mix of habits. "Representative" means the sample looks like the whole group – it includes different kinds of students, not just your friends.

Step 6: Collect primary data (ethically)

LEARN IT

Ethics means doing what is morally right. When conducting the survey, students must follow strict ethical guidelines:

- Ask **permission** before collecting responses (**consent**).
- Avoid collecting **sensitive personal information**.
- Do **not record names** unless absolutely necessary (**anonymity**).
- Keep the responses **private**.
- Use the data **only for educational purposes**.

WORKED EXAMPLE

Why "different sections" matters. Suppose the group surveyed only the 40 students of the Pre-Engineering section who sit in the front rows.

Problem: these students might study more than average, so the results would show less phone distraction than is true for the whole class.

Fix: pick students from every section (e.g. 10 each from Pre-Medical, Pre-Engineering, Computer Science and Commerce). Now the sample better represents all Class XI students.

Ethical opening text for the form: "This survey is for a class project on phone use and study habits. It is anonymous – do not write your name. Your answers will be kept private and used only for this project. Do you agree to take part? O Yes O No"

REMEMBER IT

Ethics in five words: **Consent, No-Sensitive, Anonymous, Private, Educational** – "**C-NAPE**". Think: "Cover the person's nape (neck) – protect them."

COMMON MISTAKE

Mistake: Thinking a bigger sample is always enough. A sample of 200 students all from one section is still biased. **Fix:** A sample must be **representative**, not just large.

اردو میں سمجھیں

چوتھے قدم میں واضح اور غیر جانبدار سوالات تیار کیے جاتے ہیں۔ پانچویں قدم میں نمونہ (Sample) چنا جاتا ہے۔ مختلف سیکشنز کے چالیس طلبہ تاکہ نتائج پوری جماعت کی نمائندگی کریں۔ چھٹے قدم میں اخلاقی اصولوں کے ساتھ ڈیٹا جمع کیا جاتا ہے: اجازت لیں، حساس معلومات نہ لیں، نام نہ لکھیں (گمنامی)، جوابات کو راز میں رکھیں اور صرف تعلیمی مقصد کے لیے استعمال کریں۔

EXAM TIP

Questions often ask: "What ethical guidelines should be followed when collecting data?" List all five points. Use the words **consent** and **anonymity** – examiners look for them. You may also be asked to classify the four survey questions by data type.

CHECK YOURSELF

1. What is a sample?
2. What does anonymity mean in a survey?
3. What type of data does "Suggest one way to use phones responsibly" give?

Answers: 1. The group of people who provide the data. 2. Not recording the names of participants (unless absolutely necessary). 3. Qualitative.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The digital inquiry project applies:

- a. All of chapter 6 in order
- b. Only careers
- c. Only NAND
- d. Only OSI

MCQ 2. Advanced search helps you:

- a. Narrow secondary sources (quotes, site, date)
- b. Hack Wi-Fi
- c. Draw K-maps
- d. Sort in **O(1)**

MCQ 3. Primary collection in the project is often:

- a. A class survey
- b. A CPU design
- c. A TCP stack
- d. A waterfall contract

MCQ 4. You organise results in a:

- a. Spreadsheet + charts
- b. Random WhatsApp dump only
- c. NAND netlist
- d. Figma only

MCQ 5. The artefact is:

- a. The final digital product that answers the question
- b. The first brainstorm sticky
- c. The career list
- d. The teacher's attendance

MCQ 6. A conclusion should:

- a. Answer the question and admit limits
- b. Ignore the data
- c. Name and shame students
- d. Invent n=1 million

Extra short questions

1. List the project steps in order (grouped as in the book).
2. What is a digital artefact here?
3. Why include secondary if you surveyed?
4. One sentence of a good limitation.

Extra long question

1. Outline a 12-step inquiry: "Does extra screen time lower concentration in our class?" Name tools and the artefact. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Search/method; survey/primary; secondary+sheet; analyse/conclude; artefact.
2. Slides, infographic, short video, site — that answers the inquiry question.
3. To compare your small sample with a published claim.
4. n=40 in one college, so we cannot speak for all Sindh.

Long

1. Steps 1–3 search; 4–6 survey; 7–9 PBS/article + sheet; 10–12 charts, conclusion, artefact (infographic+spreadsheet). Ethics. One expected chart: hours vs self-reported focus.

Step 7 – 9: Secondary Data & Spreadsheet Organization ★ Golden

Step 7: Use secondary data

LEARN IT

Students include a reliable online article stating that **"excessive screen time lowers concentration."** They will **compare** this secondary data with their own primary survey results. If both agree, the conclusion is stronger. If they disagree, the students must think about why (for example, a different age group or country).

Step 8: Organise data in a spreadsheet

LEARN IT

Responses are entered into **MS Excel** or **Google Sheets** to **sort, calculate totals and find averages**. Each row is one student; each column is one question.


Student	Hours	Study Use	Main Activity	Distracted?
1	3	Yes	Lectures	Sometimes
2	5	No	Social Media	Yes
3	2	Yes	Notes	No

(The full sheet has 40 rows, one per student. The formulas for this table are worked out in topic 6.7.1.)

Step 9: Create charts and graphs

LEARN IT

The spreadsheet data is converted into **visuals** to make it easy to digest. In the source, the "Daily Phone Use (Hours)" bar chart groups the 40 students into three bars: 1–3 hrs, 3–5 hrs and 5+ hrs, with the 3–5 hrs bar the tallest.



Bar chart of daily phone use for 40 students. The counts (12, 21, 7) are estimated from the bar heights in the source chart.

WORKED EXAMPLE

Making the chart in Google Sheets.

Step 1 – Count each group. If the hours are in B2:B41, use `=COUNTIF(B2:B41, "<3")` for under 3 hrs, `=COUNTIFS(B2:B41, ">= 3", B2:B41, "<5")` for 3 to under 5 hrs, and `=COUNTIF(B2:B41, ">= 5")` for 5 hrs or more. (This gives non-overlapping groups.)

Step 2 – Check the total. $12 + 21 + 7 = 40$ ✓ – every student is counted exactly once.

Step 3 – Percentages. $12 \div 40 = 30\%$; $21 \div 40 = 52.5\%$; $7 \div 40 = 17.5\%$. Total = 100% ✓.

Step 4 – Insert chart. Select the group labels and counts → Insert → Chart → choose *Column* chart. Add the title "Daily Phone Use (Hours)" and label the axes.

Step 5 – Choose the right chart. Bar/column chart to compare groups; pie chart to show parts of a whole (e.g. % in each group); line chart to show change over time.

REMEMBER IT

Chart chooser: **Bar = Compare, Pie = Parts of a whole, Line = Change over time.**

COMMON MISTAKE

Mistake: Using overlapping groups like "1–3" and "3–5": a student who uses the phone for exactly 3 hours could be counted twice or put in the wrong bar. **Fix:** Define groups clearly, e.g. "under 3", "3 to under 5", "5 or more", and check that the group counts add up to the sample size.

آزدو میں سمجھیں

ساتویں قدم میں ایک قابل اعتماد آن لائن مضمون کا ثانوی ڈیٹا ("زیادہ اسکرین ٹائم توجہ کم کرتا ہے") اپنے سروے کے بنیادی ڈیٹا سے موازنہ کرنے کے لیے لیا جاتا ہے۔ انھوں قدم میں جوابات ایکسل یا گوگل شیٹس میں درج کر کے ترتیب، مجموعہ اور اوسط نکالی جاتی ہے۔ نویں قدم میں اسپریڈشیت کے ڈیٹا سے چارٹ اور گراف بنائے جاتے ہیں تاکہ نتائج آسانی سے سمجھ آئیں۔

EXAM TIP

You may get the spreadsheet table and be asked to "write formulas to find the total and average hours" or "count students who use the phone for study". Write the full formula with `=`, the correct range, and the result.

CHECK YOURSELF

- What is the secondary data used in Step 7?
- Which formula counts how many students answered "Yes" in column C, rows 2 to 41?
- Which type of chart is best for comparing the three hour-groups?

Answers: 1. A reliable online article stating "excessive screen time lowers concentration". 2. `=COUNTIF(C2:C41, "Yes")`. 3. A bar (column) chart.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The digital inquiry project applies:

- a. All of chapter 6 in order
- b. Only careers
- c. Only NAND
- d. Only OSI

MCQ 2. Advanced search helps you:

- a. Narrow secondary sources (quotes, site, date)
- b. Hack Wi-Fi
- c. Draw K-maps
- d. Sort in **O(1)**

MCQ 3. Primary collection in the project is often:

- a. A class survey
- b. A CPU design
- c. A TCP stack
- d. A waterfall contract

MCQ 4. You organise results in a:

- a. Spreadsheet + charts
- b. Random WhatsApp dump only
- c. NAND netlist
- d. Figma only

MCQ 5. The artefact is:

- a. The final digital product that answers the question
- b. The first brainstorm sticky
- c. The career list
- d. The teacher's attendance

MCQ 6. A conclusion should:

- a. Answer the question and admit limits
- b. Ignore the data
- c. Name and shame students
- d. Invent n=1 million

Extra short questions

- List the project steps in order (grouped as in the book).
- What is a digital artefact here?
- Why include secondary if you surveyed?
- One sentence of a good limitation.

Extra long question

- Outline a 12-step inquiry: "Does extra screen time lower concentration in our class?" Name tools and the artefact. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Search/method; survey/primary; secondary+sheet; analyse/conclude; artefact.
- Slides, infographic, short video, site — that answers the inquiry question.
- To compare your small sample with a published claim.
- n=40 in one college, so we cannot speak for all Sindh.

Long

- Steps 1–3 search; 4–6 survey; 7–9 PBS/article + sheet; 10–12 charts, conclusion, artefact (infographic+spreadsheet). Ethics. One expected chart: hours vs self-reported focus.

Step 10 – 12: Data Analysis, Conclusion & Artefact

AGOLDEN

Step 10: Analyse the results

LEARN IT

To analyse means to study the data carefully to find patterns and trends. By looking at the spreadsheet and charts, the group identifies:

Most students (the majority) use phones for 3-5 hours daily.

Half use it for educational purposes (lectures/notes).

A clear trend: students who use phones mostly for entertainment report much higher distraction levels than those who use them for study.

Step 11: Write the conclusion

LEARN IT

A conclusion answers the research question using the evidence:

"The research shows mobile phones have both positive and negative effects. They provide access to learning materials. However, excessive use of social media and gaming reduces concentration. Therefore, phones should not be banned, but managed wisely."

Step 12: Recommendations

LEARN IT

Recommendations are practical suggestions based on the data. The students recommend:

Turn off social media notifications while studying.

Set daily screen-time limits.

Take physical breaks from screens to protect health.

WORKED EXAMPLE

From numbers to a finding: Using the estimated chart counts (10, 21, 7 out of 40):

Step 1: $21 \div 40 = 52.5\%$. Since $52.5\% > 50\%$, the statement "most students use phones for 3-5 hours" is supported.

Step 2: "Half use it for educational purposes" means about 20 of the 40 students chose Lectures or Notes as their main activity ($20 \div 40 = 50\%$). Formula: $=\text{COUNTIF}(D2:D41, "Lectures") + \text{COUNTIF}(D2:D41, "Notes")$.

Step 3 - Compare groups: filter the sheet to show only Social Media/Games users and count how many said "Yes" to distracted; then do the same for Lectures/Notes users. If the entertainment group has a much higher share of "Yes", that is the trend.

Step 4 - Link to secondary data: the article said excessive screen time lowers concentration; the survey agrees, so the conclusion is stronger.

REMEMBER IT

Conclusion formula: "The data shows ... However ... Therefore ..." - state the main finding, mention the other side, then give the overall answer.

COMMON MISTAKE

Mistake: Writing a conclusion that is not based on the data, e.g. "Phones should be banned" when the data showed phones also help learning. Fix: Every sentence in the conclusion and recommendations must be supported by your findings. Also, a trend between two things (entertainment use and distraction) shows a link, be careful before claiming one definitely causes the other.

آرڈو میں سمجھیں

ہمیں قدم میں پڑیں اور اسیریڈیٹ سے رجحانات تلاش کیے جائیں ہیں زیادہ تر طلبہ روزانہ تین سے پانچ گھنٹے فون استعمال کرتے ہیں، نصف اسے تعلیم کے لیے استعمال کرتے ہیں اور باقی تھیں۔ اس کے نتیجے میں یہ کہیں پریشان کن ہے کہ اس کا دانشور استعمال ہوتا ہے یا نہیں۔ ہمارے قدم میں سفارشات دی جاتی ہیں: پڑھائی کے دوران نوٹیفکیشن بند کریں، اسکرین ٹائم کی حد مقرر کریں اور وقفہ لیں۔

EXAM TIP

You may be asked to "write a conclusion and two recommendations" for given data. Use the "shows ... however ... therefore" pattern and make sure each recommendation follows from a finding.

CHECK YOURSELF

1. According to Step 10, which group reported higher distraction?

2. Should phones be banned according to the conclusion?

3. Give two of the students' recommendations.

Answers: 1. Students who use phones mostly for entertainment. 2. No - they should not be banned but managed wisely. 3. Any two: turn off social media notifications while studying; set daily screen-time limits; take physical breaks from screens.

LEARN IT

A digital artefact is a final product created using digital technologies. Students must create one final artefact that answers the original research question. It is not just a decorated file, it must present evidence and conclusions.

Standard option	Available digital tools	Main purpose
Digital Report	MS Word, Google Docs	Explain the full study in a structured text document.
Presentation	PowerPoint, Canva, Slides	Share key findings with a live audience.
Infographic	Canva, Adobe Express	Show the main results visually and quickly on one page.
Dashboard	Power BI, Tableau	Explore data through interactive charts and filters.

A dashboard is an interactive screen of charts; the viewer can click filters (e.g. "show only Commerce students") and the charts update.

Standard artefact structure

- Title
- Research Question
- Introduction
- Method of Data Collection
- Primary Data Findings
- Secondary Data Summary
- Charts and Graphs
- Conclusion
- Recommendations
- References

WORKED EXAMPLE

Planning a 10-slide presentation artefact for the phone study (one slide per structure item):

Slide 1 Title: "Phones and Study Habits - Class X Survey". Slide 2 Research question. Slide 3 Introduction: why the class investigated this. Slide 4 Method: Google Form survey, 40 students, different sections, anonymous with consent. Slide 5 Primary findings: 52.5% use phones 3-5 hours; half use for study. Slide 6 Secondary data: article on screen time and concentration. Slide 7 The bar chart of daily phone use. Slide 8 Conclusion: "manage wisely, don't ban". Slide 9 Three recommendations. Slide 10 References: the article's title, author, website and date.

REMEMBER IT

The structure follows the inquiry itself: What (title, question, intro) → How (method) → Found (primary, secondary, charts) → So what (conclusion, recommendations) → Credit (references).

COMMON MISTAKE

Mistake: Spending all your time on colours and animations and forgetting evidence. Fix: An artefact is judged on whether it answers the research question with evidence. Also never skip References - listing your secondary sources is honest and avoids plagiarism.

آرڈو میں سمجھیں

ڈیجیٹل آرٹیفیکٹ (Digital Artefact) ڈیجیٹل ٹیکنالوجی سے بنائی گئی امری پروڈکٹ ہے جو تعلیمی سوال کا جواب دیتا اور نتائج کے ساتھ پیش کرتی ہے۔ یہ صرف سچے سچے فائل نہیں۔ اس کی چار صورتیں ہیں: رپورٹ، پریزنٹیشن، انفوگرافک اور ڈیش بورڈ۔ معیاری ساخت میں عنوان، تحقیقی سوال، تعارف، طریقہ کار، پیمائی و ڈیٹا، نتیجہ، سفارشات اور حوالہ شامل ہیں۔

EXAM TIP

Learn the four artefact options with tools and purpose (a table question), and the ten-part structure in order: "What is a digital artefact?" - stress that it must present evidence and conclusions, not just decoration.

CHECK YOURSELF

1. Which artefact lets viewers explore data with interactive filters?

2. What is the last item in the standard artefact structure?

3. Name two tools for making an infographic artefact.

Answers: 1. A dashboard (Power BI, Tableau). 2. References. 3. Canva and Adobe Express.

Extra board practice These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.					
MCQ 1. The digital inquiry project applies: a. All of chapter 6 in order b. Only careers c. Only NAMD d. Only ISI		MCQ 2. Advanced search helps you: a. Narrow secondary sources (quotes, site, date) b. Hack Wi-Fi c. Draw K-maps d. Sort in Q0		MCQ 3. Primary collection in the project is often: a. A class survey b. A CPU design c. A TCP stack d. A waterfall chart	
MCQ 4. You organise results in a: a. Spreadsheet + charts b. Random WhatsApp dump only c. NAMD netlist d. Figma only		MCQ 5. The artefact is: a. The final digital product that answers the question b. The first brainstorm sticky c. The career list d. The teacher's attendance		MCQ 6. A conclusion should: a. Answer the question and admit limits b. Ignore the data c. Name and shame students d. Invent n=1 million	

Extra short questions

- List the project steps in order (grouped as in the book).
- What is a digital artefact here?
- Why include secondary if you surveyed?
- One sentence of a good limitation.

Extra long question

- Outline a 12-step inquiry: "Does extra screen time lower concentration in our class?" Name tools and the artefact. ★ Golden.

Extra answer key MCQs: 1. A, 2. A, 3. A, 4. A, 5. A, 6. A. Short 1. Search/method; survey/primary; secondary=sheet; analyse/conclude; artefact. 2. Sticky, Infographic, short video, site — that answers the inquiry question. 3. To compare your small sample with a published claim. 4. n=40 in one college, so we cannot speak for all Sindh. Long 1. Steps 1-3 search; 4-6 survey; 7-9 PBS/article + sheet; 10-12 charts, conclusion, artefact (Infographic+spreadsheet). Ethics. One expected chart: hours vs self-reported focus.	
---	--

Digital Literacy

14 single-page lessons · 10 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- **Digital literacy** is the ability to understand and use digital devices, the internet and online tools safely, effectively and responsibly – not just using devices, but finding, evaluating and creating information.
- In the **Information Age**, access to technology is not enough; digital literacy needs technical, cognitive and social abilities.
- **Qualitative data** is descriptive and non-numerical (opinions, reasons, behaviour) and explains why/how.
- **Quantitative data** is numerical, countable or measurable (hours, scores, percentages) and is used for comparing and charting.
- The five **data-collection strategies** are interviews, surveys, prototypes, observation and simulations.
- **Interviews** are planned conversations giving mostly qualitative data; **surveys** ask the same questions to many people, on paper or with Google/Microsoft Forms.
- Good survey questions are clear, short, unbiased and ask about one thing; avoid leading, double-barrelled, vague and overlapping questions.
- A **prototype** is an early version tested for feedback; **observation** records what happens without asking questions; a **simulation** is a computer model used when real experiments are costly, risky or difficult.
- **Primary data** is collected first-hand (high control); **secondary data** was collected by others and reused (limited control).
- Designing a data-collection approach has eight steps: question, data type, method, sample, tools, collect, store with backup, and ethics (consent is mandatory).
- **Spreadsheets** organise and calculate (e.g. `=SUM()`, `=AVERAGE()`, `=COUNTIF()`); **presentations** deliver to an audience; **infographics** give quick visual summaries; **reports** give detailed structure.
- Visuals must always be accurate and based strictly on real data, never exaggerated.
- **Advanced search operators** such as `" "`, `filetype:pdf` and `site:.edu` help find reliable sources efficiently; sources must be evaluated for author, date, reliability and bias.
- **Ethics**: get consent, avoid sensitive information, keep anonymity, keep responses private, and use data only for educational purposes.
- The **digital inquiry project** follows Question → Search → Collect → Analyse → Create in 12 steps.
- A **digital artefact** (report, presentation, infographic or dashboard) answers the research question using evidence and visuals, following a ten-part structure ending in references.

Key terms

Term	Meaning	اردو
Digital literacy	Ability to understand and use digital devices, the internet and online tools safely, effectively and responsibly.	ڈیجیٹل خواندگی
Information Age	Period in which vast amounts of data are produced, shared and accessed instantly.	معلوماتی دور
Data	Facts, numbers, words or observations collected for study.	مواد / ڈیٹا
Qualitative data	Descriptive, non-numerical data about thoughts, feelings and experiences.	کیفیتی ڈیٹا
Quantitative data	Numerical data that can be counted or measured.	مقداری ڈیٹا
Interview	Planned conversation to gather information directly from a person or small group.	انٹرویو / بالمشافہ گفتگو
Survey / Questionnaire	Same set of questions asked to many people.	سروے / سوالنامہ
Prototype	Simple early version of a product used to test an idea and get feedback.	ابتدائی نمونہ
Observation	Watching and recording what happens without asking questions.	مشاہدہ
Simulation	Computer-based model of a real situation in which variables can be changed.	نقلی ماڈل (سمیولیشن)
Variable	A factor that can be changed or measured.	متغیر
Primary data	Data collected first-hand by the researcher for a specific purpose.	بنیادی ڈیٹا

Digital Literacy

75 marks · 1 hour 15 minutes · no notes · no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 14 and the recap. **Section A** — all 15 MCQs (1 mark). **Section B** — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define · Explain · Example · Diagram · Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. Digital literacy is best described as the ability to:
 - a. type quickly on a keyboard
 - b. understand and use digital devices, the internet and online tools safely, effectively and responsibly
 - c. repair computer hardware
 - d. write computer programs
2. Which of the following is qualitative data?
 - a. Marks obtained in a test
 - b. Number of hours spent online
 - c. Students' opinions about online classes
 - d. Percentage of students using the internet
3. Which method is most suitable when the same questions must be asked to many people?
 - a. Survey
 - b. Interview
 - c. Prototype
 - d. Simulation
4. Simulations are especially useful when:
 - a. you want people's opinions
 - b. the data already exists in a report
 - c. you want to watch people without asking questions
 - d. real experiments are costly, risky or difficult
5. To find out how many cars cross an intersection at 8 AM, the best method is:
 - a. Interview
 - b. Observation
 - c. Survey
 - d. Prototype
6. Which of these is primary data?
 - a. Responses to a Google Form you created for your project
 - b. An official government report
 - c. A published research article
 - d. Web statistics from a website
7. A researcher has limited control over:
 - a. their own interviews
 - b. their own survey questions
 - c. their own observations
 - d. secondary data
8. The first step in designing a data-collection approach is to:
 - a. collect the data
 - b. choose the sample
 - c. define the research question clearly
 - d. store the data with a backup
9. Which spreadsheet formula finds the mean of cells B2 to B6?
 - a. =AVERAGE(B2:B6)
 - b. =SUM(B2:B6)
 - c. =COUNT(B2:B6)
 - d. =MAX(B2:B6)
10. The search query `digital distraction site:.edu` will:
 - a. find only PDF files
 - b. search only educational websites
 - c. find the exact phrase "digital distraction" only
 - d. exclude educational websites
11. The operator `filetype:pdf` is used to:
 - a. search for an exact phrase
 - b. search only government websites
 - c. convert a web page into PDF
 - d. find only PDF documents
12. "Do not record names unless absolutely necessary" describes the principle of:
 - a. consent
 - b. accuracy
 - c. anonymity
 - d. sampling
13. In the case study, how many Class XI students were surveyed?
 - a. 20
 - b. 40
 - c. 50
 - d. 100
14. Which tools are suggested for a dashboard artefact?
 - a. Power BI, Tableau
 - b. MS Word, Google Docs
 - c. PowerPoint, Google Slides
 - d. Google Forms, Microsoft Forms
15. A prototype is:
 - a. the final finished product
 - b. a published report
 - c. a type of survey question
 - d. a simple early version of a product used to test an idea

Section B — Short questions (10 × 3 = 30)

1. Define digital literacy. Name the three kinds of ability it involves.
2. Why is simply having access to technology not enough in the Information Age?
3. Differentiate between qualitative and quantitative data, giving two examples of each.
4. How is an interview different from a survey?
5. What is a prototype, and how does it produce useful data?
6. When is a simulation used? Give one example.
7. Compare primary and secondary data in terms of purpose and control.
8. List any four ethical guidelines to follow when collecting primary data.
9. Explain three advanced search operators with an example of each.
10. What is a digital artefact? Name its four options with one suitable tool each.

Section C — Long questions (attempt any 3 × 10 = 30)

1. Explain the eight steps of designing a data-collection approach. Apply each step to the research question: "How much water is wasted at the college taps during break time, and why?"
2. **Design a survey for** finding out how Class XI students in your college travel to college and how long the journey takes. Write a consent statement and at least six questions (mixing closed, number, rating and open-ended types), state the data type of each question, describe your sample, and explain how you will keep the data ethical.
3. Ten students recorded their daily phone use (hours) in cells B2 to B11: 2, 4, 3, 5, 6, 4, 3, 4, 1, 4. (a) Write the spreadsheet formulas and give the results for the total, mean, median, mode, maximum and minimum. (b) Write a formula to count students using the phone for more than 4 hours, and find the percentage. (c) Group the data into "1–2 hrs", "3–4 hrs" and "5+ hrs" and name a suitable chart.
4. Describe all 12 steps of the Digital Inquiry Project on the question "How does daily mobile phone use affect the study habits of students?", including the final digital artefact and its structure.
5. **Design a survey for** investigating "How do Class XI students use AI tools for homework?" Then explain which secondary sources you would search for (with advanced search queries), and which artefact you would create to present your findings to the principal, with reasons.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

1. **6.1 & 6.2 Introduction to Digital Literacy.** Answers: 1. The ability to understand and use digital devices, the internet and online tools in a safe, effective and responsible manner. 2. Find information, communicate, produce digital content, and solve problems through technology.
2. **6.3 Types of Data (Qualitative vs Quantitative).** Answers: 1. Quantitative (measurable number). 2. Qualitative. 3. Qualitative (an opinion in words).
3. **6.4 Data-Collection Strategies.** Answers: 1. Interviews, surveys, prototypes, observation, simulations. 2. New information that you gather yourself, rather than information that already exists.
4. **6.4.1 – 6.4.2 Interviews and Surveys.** Answers: 1. Google Forms and Microsoft Forms. 2. It is double-barrelled (two subjects in one question); ask about each subject separately. 3. Usually qualitative.
5. **6.4.3 – 6.4.5 Prototypes, Observation, and Simulations.** Answers: 1. Because the real experiment may be costly, risky or difficult. 2. Yes – for example, counting the number of cars passing a point. 3. The feedback users give after trying the prototype.
6. **6.5 Primary and Secondary Data.** Answers: 1. Primary data. 2. Secondary (someone else collected it). 3. Any two: interviews, surveys, observations, experiments.
7. **6.6 Designing a Data-Collection Approach.** Answers: 1. Define the research question clearly. 2. Step 8 – follow ethical practice and respect privacy. 3. Digitally, in a spreadsheet, with a backup copy.
8. **6.7 Presenting Data Using Digital Tools.** Answers: 1. `=AVERAGE(D2:D20)`. 2. MS Excel, Google Sheets, Apple Numbers. 3. Any two: start with a clear title and research question; use short bullet points; include tables/charts/key findings; keep design simple and readable.
9. **6.7.1 – 6.7.4 Spreadsheets, Presentations, Infographics, Reports.** Answers: 1. Any two: Canva, Power BI, Tableau. 2. Review it carefully for accuracy. 3. Conclusions and recommendations based on the data.
10. **6.8 Case Study: Digital Inquiry Project.** Answers: 1. "How does daily mobile phone use affect the study habits of students?" 2. Question, Search, Collect, Analyse, Create.
11. **Step 1 – 3: Advanced Search & Methodology.** Answers: 1. "online learning" site: .edu. 2. Because the same questions had to be asked to many students, and a survey is the most efficient way to do that. 3. Quantitative: hours used daily (or % who feel distracted). Qualitative: opinions on why they get distracted (or suggestions for better use).
12. **Step 4 – 6: Survey Prep & Primary Data Collection.** Answers: 1. The group of people who provide the data. 2. Not recording the names of participants (unless absolutely necessary). 3. Qualitative.
13. **Step 7 – 9: Secondary Data & Spreadsheet Organization.** Answers: 1. A reliable online article stating "excessive screen time lowers concentration". 2. `=COUNTIF(C2:C41, "Yes")`. 3. A bar (column) chart.
14. **Step 10 – 12: Data Analysis, Conclusion & Artefact.** Answers: 1. Students who use phones mostly for entertainment. 2. No – they should not be banned but managed wisely. 3. Any two: turn off social media notifications while studying; set daily screen-time limits; take physical breaks from screens.

Answer key

Multiple choice

1. b
2. c
3. a
4. d
5. b
6. a
7. d
8. c
9. a
10. b
11. d
12. c
13. b
14. a
15. d

Short questions — model answers

1. Digital literacy is the ability to understand and use digital devices, the internet and online tools in a safe, effective and responsible manner. It involves technical, cognitive and social abilities.
2. In the Information Age vast amounts of data are produced and shared instantly. Owning a device does not mean you can judge or use this information well. Users must develop skills to understand, manage and use information wisely, and to tell reliable information from unreliable.
3. Qualitative data is descriptive and non-numerical; it explains why and how (e.g. students' opinions about online classes; observation notes). Quantitative data is numerical, countable or measurable; it is used for comparing and making charts (e.g. marks in a test; hours spent online).
4. An interview is a planned conversation with one person or a small group, giving mostly qualitative, in-depth answers. A survey asks the same set of questions to many people (on paper or via Google/Microsoft Forms) and is efficient for large groups; online surveys also collect responses and make charts automatically.
5. A prototype is a simple early version of a product, model or solution. Users try it and give feedback; this feedback is data used to improve the product before time and effort are spent on the final version.
6. A simulation is used when real experiments are costly, risky or difficult. Example: a flight simulator to train pilots, or a traffic simulation to test the effect of closing a road.
7. Purpose: primary data is prepared for a specific study; secondary data is reused for a new purpose. Control: the researcher has high control over primary data (questions and process) and limited control over secondary data because it already exists.
8. Any four: ask permission (consent); avoid sensitive personal information; do not record names unless necessary (anonymity); keep responses private; use data only for educational purposes.
9. Quotes " " find an exact phrase, e.g. "study habits" students. filetype: finds a file format, e.g. "academic performance" filetype:pdf gives only PDFs. site: limits to a type of website, e.g. digital distraction site:.edu searches only educational sites.
10. A digital artefact is a final product created with digital technology that answers the research question with evidence and conclusions. Options: digital report (MS Word/Google Docs), presentation (PowerPoint/Canva/Slides), infographic (Canva/Adobe Express), dashboard (Power BI/Tableau).

Long questions — model answers

- 1. Eight steps applied to water wastage.** (1) **Define the question:** "How much water is wasted at the college taps during break time, and why?" (2) **Data type:** both – quantitative (number of taps left running, minutes running) and qualitative (students' reasons). (3) **Methods:** observation to count running taps; a short survey to learn habits and reasons. (4) **Sample:** all 12 taps observed over 5 break times; 30 students from different classes surveyed. (5) **Tools:** an observation sheet (Tap no., Time, Left running Y/N, Minutes) and a Google Form. (6) **Collect** carefully, at the same time each day, recording accurately. (7) **Store** data in Google Sheets and keep a backup copy (download or USB). (8) **Ethics:** get the principal's permission; the survey is voluntary and anonymous with a consent question; data used only for the project.
- 2. Survey on travel to college (model).** *Consent:* "This anonymous survey is for a Class XI project on travel to college. Do not write your name. Answers will be kept private and used only for this project. Do you agree to take part? Yes / No." *Questions:* Q1 How do you usually travel to college? Walk / Bus / Rickshaw / Motorbike / Car / Other – quantitative (categories). Q2 How many minutes does your journey usually take? ____ – quantitative. Q3 How many days a week are you late because of travel? 0 / 1 / 2 / 3 or more – quantitative. Q4 "My journey to college is safe." 1 (strongly disagree) to 5 (strongly agree) – quantitative (rating). Q5 Do you travel alone? Yes / No – quantitative (count). Q6 What is the biggest problem you face while travelling? – qualitative. Q7 Suggest one way the college could make travel easier. – qualitative. Questions are unbiased, ask one thing each, and options do not overlap. *Sample:* about 40 Class XI students, roughly 10 from each section, to be representative. *Ethics:* consent, no sensitive information (no home address), no names (anonymity), private storage, educational use only. Data is collected through Google Forms and exported to Google Sheets for analysis.
- 3. Spreadsheet problem.** (a) $\text{=SUM(B2:B11)} \rightarrow 2+4+3+5+6+4+3+4+1+4 = 36$. $\text{=AVERAGE(B2:B11)} \rightarrow 36 \div 10 = 3.6$ hours. Sorted: 1, 2, 3, 3, 4, 4, 4, 4, 5, 6; $\text{=MEDIAN(B2:B11)} \rightarrow (4 + 4) \div 2 = 4$. $\text{=MODE(B2:B11)} \rightarrow 4$ (appears 4 times). $\text{=MAX(B2:B11)} \rightarrow 6$; $\text{=MIN(B2:B11)} \rightarrow 1$. (b) $\text{=COUNTIF(B2:B11, ">4")}$ → values 5 and 6 → 2 students; percentage $\text{=COUNTIF(B2:B11, ">4")}/\text{COUNT(B2:B11)} \rightarrow 2 \div 10 = 20\%$. (c) 1–2 hrs: 2 students (2, 1); 3–4 hrs: 6 students (4, 3, 4, 3, 4, 4); 5+ hrs: 2 students (5, 6). Check: $2 + 6 + 2 = 10 \checkmark$. A **bar/column chart** is suitable for comparing the groups (or a pie chart to show 20%, 60%, 20%).
- 4. Twelve steps.** (1) Advanced searches with operators such as "mobile phone use" "study habits" students, "academic performance" filetype:pdf, digital distraction site:.edu; evaluate sources (author, recent, reliable site, facts/bias). (2) Identify data types: quantitative (hours daily, % distracted) and qualitative (reasons, suggestions). (3) Select method: survey via Google Forms/paper, because the same questions go to many students. (4) Prepare the survey: hours daily (quantitative), main activity (quantitative categories), how the phone helps (qualitative), one responsible-use suggestion (qualitative). (5) Sample: 40 Class XI students from different sections. (6) Collect ethically: consent, no sensitive data, anonymity, privacy, educational use only. (7) Secondary data: an article saying excessive screen time lowers concentration, to compare with results. (8) Organise in Excel/Google Sheets (Student, Hours, Study Use, Main Activity, Distracted?), sort, total, average. (9) Charts: bar chart of daily phone use (1–3, 3–5, 5+ hrs). (10) Analyse: majority use 3–5 hours; half use for education; entertainment users report more distraction. (11) Conclusion: phones have positive and negative effects; should be managed wisely, not banned. (12) Recommendations: turn off social media notifications, set screen-time limits, take physical breaks. **Artefact:** one of report, presentation, infographic or dashboard, structured as Title, Research Question, Introduction, Method, Primary Findings, Secondary Summary, Charts, Conclusion, Recommendations, References.
- 5. AI tools for homework (model).** *Survey:* consent statement (anonymous, voluntary, educational use only). Q1 Have you used an AI tool (e.g. ChatGPT, Gemini) for homework? Yes / No – quantitative. Q2 How many times a week? 0 / 1–2 / 3–5 / 6 or more – quantitative (non-overlapping categories). Q3 What do you use it for most? Explaining topics / Checking answers / Writing assignments / Translation / Other – quantitative (categories). Q4 "AI tools help me understand my subjects better." 1–5 rating – quantitative. Q5 Do you check AI answers against your textbook? Always / Sometimes / Never – quantitative. Q6 Describe one problem you have faced with AI answers. – qualitative. *Sample:* about 40 Class XI students from all sections. *Secondary sources:* "generative AI" students homework filetype:pdf; "AI in education" site:.edu; "artificial intelligence" policy site:.gov.pk; evaluate each for author, date, reliability and bias. *Artefact:* a **digital report** (MS Word/Google Docs) because the principal needs the full study – method, findings, charts, conclusion, recommendations and references – in a structured document; a one-page infographic could be attached as a quick summary. Charts would be made in Google Sheets from the form responses, and every visual must match the real data.

Self-assessment: I can...

- ☐ define digital literacy and explain why it matters in the Information Age.
- ☐ name and explain the five data-collection strategies and choose the right one for a scenario.
- ☐ compare primary and secondary data by source, examples, purpose and control.
- ☐ follow ethical rules: consent, anonymity, privacy and educational use.
- ☐ use advanced search operators and evaluate whether a source is reliable.
- ☐ describe the 12 steps of the digital inquiry project.
- ☐ classify data as qualitative or quantitative and explain the difference in a table.
- ☐ write clear, unbiased survey questions and fix leading, double-barrelled or vague ones.
- ☐ list the eight steps for designing a data-collection approach.
- ☐ use spreadsheet formulas such as `=SUM()` , `=AVERAGE()` and `=COUNTIF()` and calculate results correctly.
- ☐ choose a suitable tool (spreadsheet, presentation, infographic, report, dashboard) to present findings.
- ☐ plan a digital artefact using the ten-part standard structure.

Lecture 07

Final Revision and Mock Paper

Final revision lecture — 1 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XI · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — گیارہویں جماعت

01 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XI

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیریئر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

FINAL REVISION

One-page recaps and a mock paper

Use these pages in the last week before the exam. Read one recap, close the booklet, and say it aloud. Then sit the mock paper in 2 hours 30 minutes with no notes.

امتحان سے ایک ہفتہ پہلے یہ خلاصے زبانی دہرائیں، پھر ماک پیپر بغیر نوٹس کے حل کریں۔

Chapter 1 recap — Computer Systems

- Discrete = counted (stairs). Continuous = measured (ramp). Digital systems use bits 0 and 1; they are reliable, accurate, easy to design and programmable.
- Analog signal = smooth sine wave. Digital signal = square wave HIGH/LOW. Digital data resists noise.
- AND · output 1 only if all inputs 1. OR + output 1 if any input 1. NOT ' inverts. NAND = NOT-AND, NOR = NOT-OR (universal). XOR 1 when inputs differ. XNOR 1 when inputs same.
- Truth table rows = 2^n . SOP = sum of minterms where output is 1. POS = product of maxterms where output is 0.
- K-map: group 1, 2, 4, 8 adjacent 1s (power of 2, wrap-around allowed). Each group drops the variables that change.
- SDLC: requirement → design → implementation → testing → deployment → maintenance. Waterfall = sequential; Agile = short sprints and feedback.
- OSI 7: Physical, Data Link, Network, Transport, Session, Presentation, Application. Mnemonic: Please Do Not Throw Sausage Pizza Away. TCP/IP 4: Network Access, Internet, Transport, Application.

Chapter 2 recap — Computational Thinking & Algorithm

- CT pillars: decomposition, pattern recognition, abstraction, algorithms.
- Algorithm = finite, ordered, unambiguous steps. Pseudocode = structured English, not a programming language.
- Bubble Sort: compare neighbours, swap if out of order; largest "bubbles" to the end each pass. $O(n^2)$.
- Selection Sort: find the minimum in the unsorted part and swap it to the front. $O(n^2)$.
- Linear Search: check one by one. Works on unsorted data. $O(n)$.
- Binary Search: list MUST be sorted. Repeatedly test the middle. $O(\log n)$. Trace with low / mid / high.
- Judge an algorithm on correctness, efficiency (time and space) and clarity. Prefer binary search on large sorted lists; linear search on small or unsorted lists.

Chapter 3 recap — Programming Fundamentals

- Python: high-level, interpreted. Variables are names; types int, float, str, bool, list, dict. `input()` returns str.
- Arithmetic `+` `-` `*` `/` `//` `%` `**`. Relational. Logical `and` `or` `not`. Bitwise `&` `|` `^` `~` `<<` `>>`.
- Selection: `if` / `if-else` / `if-elif-else` / nested. Test from the top; first True wins.
- `for` = known count + range. `while` = unknown count; always update the condition. `break` leaves; `continue` skips one.
- Libraries: `import math` / `random` / `datetime`. Third-party via `pip`: NumPy, Pandas, Matplotlib.
- Syntax = will not run. Runtime = crash + traceback. Logical = runs, wrong answer.

Chapter 4 recap — Data and Analysis

- Data = raw facts. Information = processed data used for decisions. Database = organised related data. DBMS = software that manages it (reduces redundancy, improves security, sharing, integrity).
- Table / relation; row / record / tuple; column / field / attribute. Primary key uniquely identifies a row. Foreign key refers to another table's primary key.
- ER model: entity (rectangle), attribute (oval), relationship (diamond), cardinality 1:1, 1:M, M:N.
- Referential integrity: you cannot orphan a child row. Cascade Update / Cascade Delete copy or remove matching child rows.
- Access objects: tables, forms, queries, reports. Queries filter with criteria, wildcards (`*`, `?`), AND/OR. Totals: Count, Sum, Avg, Group By. Charts visualise the result.

Chapter 5 recap — Application and Impacts of Computing

- IoT = connected devices. Six parts: sensor, actuator, connectivity, processing, cloud, UI. AI = machines that learn and decide. Analytics = collect → store → clean → analyse → visualise.
- Together: IoT (eyes) → Analytics (sort) → AI (brain) → actuator (action).
- Sources: primary (firsthand), secondary (explained by others), tertiary (summaries). No author / date / references → do not trust.
- Assistive tech: mobility, sensory, communication, cognitive. Goal: equal access, independence, inclusion.

Chapter 6 recap — Digital Literacy

- Digital literacy = find, evaluate, create and share information with digital tools, safely.
- Qualitative = words/descriptions. Quantitative = numbers. Strategies: interview, survey, prototype, observation, simulation.
- Primary data you collect; secondary data already exists. Good survey questions are clear, single-idea, unbiased.
- Present with spreadsheets (formulas such as `=AVERAGE()`), slides, infographics and reports. Cite sources. Follow the 12-step inquiry project from question to artefact.

Mock paper — Computer Science XI

Time: 2 hours 30 minutes | Total: 75 marks | Answer all questions. Calculators allowed. Write Python with correct indentation.

Section A — Multiple choice (15 × 1 = 15)

1. Which quantity is discrete?
 - a. Room temperature
 - b. Number of desks
 - c. Car speed
 - d. Time of day
2. NAND is called universal because:
 - a. it has two inputs
 - b. any gate can be built from it
 - c. its output is always 1
 - d. it is faster than AND
3. The Boolean expression for XOR is:
 - a. $A \cdot B$
 - b. $A + B$
 - c. $A \oplus B$
 - d. $(A \cdot B)'$
4. OSI layer that chooses the best path (IP addresses) is:
 - a. Transport
 - b. Network
 - c. Data Link
 - d. Session
5. Which SDLC model delivers working software in short sprints?
 - a. Waterfall
 - b. Agile
 - c. Spiral only
 - d. Big Bang
6. Binary Search requires the list to be:
 - a. unsorted
 - b. sorted
 - c. all unique and unsorted
 - d. of even length
7. Worst-case time of Bubble Sort is:
 - a. $O(n)$
 - b. $O(\log n)$
 - c. $O(n^2)$
 - d. $O(1)$
8. `input()` in Python returns a:
 - a. int
 - b. str
 - c. float
 - d. bool
9. `17 // 5` equals:
 - a. 3.4
 - b. 3
 - c. 2
 - d. 3.0
10. A program that runs but prints the wrong total has a:
 - a. syntax error
 - b. runtime error
 - c. logical error
 - d. hardware fault
11. A field that uniquely identifies each record is a:
 - a. foreign key
 - b. primary key
 - c. composite description
 - d. query
12. An actuator in IoT:
 - a. collects temperature
 - b. opens a water valve
 - c. stores cloud files
 - d. draws a chart
13. Wikipedia is a:
 - a. primary source
 - b. secondary source
 - c. tertiary source
 - d. sensor
14. Marks out of 100 are:
 - a. qualitative data
 - b. quantitative data
 - c. tertiary data
 - d. metadata only
15. Which Access object is best for printing a formatted class list?
 - a. Table
 - b. Form
 - c. Query
 - d. Report

Section B — Short questions (10 × 3 = 30)

1. Differentiate analog and digital signals with one example of each.
2. Draw the symbol and truth table of a 2-input NOR gate.
3. List the four pillars of computational thinking in one sentence each.
4. Why can you not use Binary Search on an unsorted attendance list?
5. Write a Python `if-elif-else` that prints Pass if marks ≥ 40 , else Fail.
6. Define primary key and foreign key.
7. Name the six components of IoT.
8. Classify: (a) a photograph you took, (b) a textbook, (c) an encyclopedia.
9. Give two good and two bad survey questions about mobile-phone use in college.
10. State three advantages of a DBMS over paper files.

Section C — Long questions (3 × 10 = 30). Attempt any three.

1. Simplify $F(A,B,C) = \Sigma(1,3,5,7)$ using a 3-variable K-map. Show the grouping and the final expression. Draw the logic diagram.
2. Dry-run Bubble Sort on the list [5, 1, 4, 2]. Show every pass. Then search for 4 using Binary Search on the sorted result, with a low/mid/high table.
3. Write a complete Python program that reads n subject marks, prints the average, and prints "A" if average ≥ 80 , "B" if ≥ 70 , "C" if ≥ 60 , else "D". Include a sample run of four marks: 80, 70, 90, 60.
4. Design an ER diagram and relational schema for a school library (Student, Book, Issue). Mark keys. Write one Access/SQL query that lists all books issued to roll number 101.
5. Explain how IoT, Data Analytics and AI work together on a Sindh farm. Then discuss two positive and two negative impacts of computing on education in Pakistan.

Mock paper — answers

Section A

1. b
2. b
3. c
4. b
5. b
6. b
7. c
8. b
9. b
10. c
11. b
12. b
13. c
14. b
15. d

Section B

1. Analog: continuous, sine wave, e.g. human voice. Digital: two levels 0/1, square wave, e.g. computer data. Digital resists noise.
2. NOR symbol: OR-gate shape with a bubble on the output. $Y = (A+B)'$. Truth: 00→1, 01→0, 10→0, 11→0.
3. Decomposition = split a problem. Pattern recognition = reuse similarities. Abstraction = ignore extra detail. Algorithms = write ordered steps.
4. Binary Search repeatedly halves a sorted range. If the list is unsorted, the middle value does not tell you which half to keep, so the method is invalid.
5. `m = int(input("Marks: ")) then if m ≥ 40: print("Pass") else print("Fail").`
6. Primary key: unique identifier of a row (e.g. StudentID). Foreign key: a field that refers to the primary key of another table (e.g. StudentID in Issuance).
7. Sensors, actuators, connectivity, data processing, cloud computing, user interface.
8. (a) primary (b) secondary (c) tertiary.
9. Good: "How many hours per day do you use a phone for study?" / "Which apps do you use for class notes?" Bad: "Don't you agree phones are destroying students?" (leading) / "Do you like phones and also use laptops?" (double-barrelled).
10. Less redundancy, easier search and update, better security and multi-user access, integrity constraints. (Any three.)

Section C — outline

1. K-map 1s at m1, m3, m5, m7 form one group of 4 covering B=1 (or C=1 depending on labelling — with standard ABC order the 1s are all cells where C=1). $F = C$. Diagram: a single wire C to output (or a buffer). Show the map with the group circled.
2. Pass 1: [1,4,2,5]; Pass 2: [1,2,4,5]; Pass 3: already sorted. Sorted [1,2,4,5]. Search 4: low=0 high=3 mid=1 (2<4) → low=2; mid=2 (4=4) found at index 2.
3. Read n, loop n times adding `float(input())`, avg = total/n, then if-elif for A/B/C/D. Sample: total 300, avg 75.0, grade B.
4. Entities Student(StudentID PK, Name, Class), Book(BookID PK, Title, Author), Issue(IssueID PK, StudentID FK, BookID FK, Date). Query: `SELECT Book.Title FROM Issue INNER JOIN Book ON Issue.BookID = Book.BookID WHERE StudentID = 101;`
5. Soil sensor (IoT) → cloud spreadsheet of moisture (Analytics) → model decides "too dry" (AI) → pump (actuator). Education +: LMS, remote classes. Education -: screen addiction, urban/rural device gap.

BIEK LECTURE-WISE STUDY GUIDES

BIEK Computer Science XII

One PDF per lecture — plus a full chapter pack for each unit.

Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — بارہویں جماعت

XII

Lecture index

Chapter packs are named **Lecture 01–06**. Individual topics are **ChNN-LNN**. ★ marks Golden (high-yield) exam topics.

Code	File	Title
Lecture 01	CS-XII-Lecture-01-Computer-Systems-HCI.pdf	Computer Systems (HCI)
Ch01-L01	CS-XII-Ch01-L01-1.1-Fundamentals-of-Human-Computer-Interaction-HCI.pdf	1.1 Fundamentals of Human Computer Interaction (HCI)
Ch01-L02	CS-XII-Ch01-L02-1.1.1-1.1.2-Traditional-vs-Natural-Interaction.pdf	1.1.1 – 1.1.2 Traditional vs Natural Interaction
Ch01-L03	CS-XII-Ch01-L03-1.2-Applications-of-HCI-Domains-of-Life.pdf	1.2 Applications of HCI (Domains of Life) ★
Ch01-L04	CS-XII-Ch01-L04-1.3-Components-of-HCI.pdf	1.3 Components of HCI
Ch01-L05	CS-XII-Ch01-L05-1.3-Types-of-User-Interaction.pdf	1.3 Types of User Interaction
Ch01-L06	CS-XII-Ch01-L06-1.3-Interface-Types-Environment-Feedback.pdf	1.3 Interface Types, Environment & Feedback
Ch01-L07	CS-XII-Ch01-L07-1.4-Importance-of-HCI.pdf	1.4 Importance of HCI ★
Ch01-L08	CS-XII-Ch01-L08-1.5-Accessibility-Principles.pdf	1.5 Accessibility Principles
Ch01-L09	CS-XII-Ch01-L09-1.6-Need-Analysis-for-Interface-Design.pdf	1.6 Need Analysis for Interface Design
Ch01-L10	CS-XII-Ch01-L10-1.7-Human-Computer-Interaction-Problems.pdf	1.7 Human Computer Interaction Problems ★
Ch01-L11	CS-XII-Ch01-L11-1.8-Methods-for-Improving-HCI.pdf	1.8 Methods for Improving HCI
Ch01-L12	CS-XII-Ch01-L12-1.9-User-Interface-Design-UI-vs-UX.pdf	1.9 User Interface Design (UI vs UX) ★
Ch01-L13	CS-XII-Ch01-L13-1.9.3-1.9.5-Wireframing-Figma-and-Prototypes.pdf	1.9.3 – 1.9.5 Wireframing, Figma, and Prototypes
Ch01-L14	CS-XII-Ch01-L14-1.11-Test-and-Evaluate-HCI-Evaluation-Methods.pdf	1.11 Test and Evaluate HCI (Evaluation Methods)

Code	File	Title
Ch01-L15	CS-XII-Ch01-L15-1.11.2-Testing-Methods-Usability-AB-Automated.pdf	1.11.2 Testing Methods (Usability, A/B, Automated) ★
Lecture 02	CS-XII-Lecture-02-Computational-Thinking-Algorithms.pdf	Computational Thinking & Algorithms
Ch02-L01	CS-XII-Ch02-L01-2.1-Analyze-algorithms-for-correctness.pdf	2.1 Analyze algorithms for correctness
Ch02-L02	CS-XII-Ch02-L02-2.1.1-2.1.3-Trace-Tables-vs-Stepwise-Reasoning.pdf	2.1.1 – 2.1.3 Trace Tables vs Stepwise Reasoning ★
Ch02-L03	CS-XII-Ch02-L03-2.2-Evaluating-the-Clarity-of-an-Algorithm.pdf	2.2 Evaluating the Clarity of an Algorithm
Ch02-L04	CS-XII-Ch02-L04-2.2.1-2.2.2-Modularity-and-Readability.pdf	2.2.1 – 2.2.2 Modularity and Readability
Ch02-L05	CS-XII-Ch02-L05-2.3-Assess-Algorithm-Efficiency.pdf	2.3 Assess Algorithm Efficiency ★
Ch02-L06	CS-XII-Ch02-L06-2.3.1-Number-of-Steps-Big-O-Notation.pdf	2.3.1 Number of Steps (Big O Notation) ★
Ch02-L07	CS-XII-Ch02-L07-2.3.2-Number-of-Conditions.pdf	2.3.2 Number of Conditions
Ch02-L08	CS-XII-Ch02-L08-2.3.3-Number-of-Repetitions.pdf	2.3.3 Number of Repetitions
Ch02-L09	CS-XII-Ch02-L09-2.3.4-The-Efficiency-Evaluation-Framework.pdf	2.3.4 The Efficiency Evaluation Framework
Ch02-L10	CS-XII-Ch02-L10-2.4-Refinements-to-improve-clarity-and-efficiency.pdf	2.4 Refinements to improve clarity and efficiency
Ch02-L11	CS-XII-Ch02-L11-2.5-Concept-of-Data-Structure.pdf	2.5 Concept of Data Structure ★
Ch02-L12	CS-XII-Ch02-L12-2.5.1-Linear-Data-Structures-Array-Linked-List-Stack-Queue.pdf	2.5.1 Linear Data Structures (Array, Linked List, Stack, Queue) ★
Ch02-L13	CS-XII-Ch02-L13-2.5.2-Non-Linear-Data-Structures-Tree-Graph.pdf	2.5.2 Non-Linear Data Structures (Tree, Graph)
Ch02-L14	CS-XII-Ch02-L14-2.5.3-Operations-on-Data-Structures.pdf	2.5.3 Operations on Data Structures
Ch02-L15	CS-XII-Ch02-L15-2.6-Identify-data-structures-in-problem-scenarios.pdf	2.6 Identify data structures in problem scenarios

Code	File	Title
Ch02-L16	CS-XII-Ch02-L16-2.7-Trace-data-retrieval-in-Array-List-and-Queue.pdf	2.7 Trace data retrieval in Array, List and Queue
Lecture 03	CS-XII-Lecture-03-Programming-Fundamentals.pdf	Programming Fundamentals
Ch03-L01	CS-XII-Ch03-L01-3.1-Data-Structures-in-Python.pdf	3.1 Data Structures in Python
Ch03-L02	CS-XII-Ch03-L02-3.1.1-Lists-Ordered-Mutable-Methods.pdf	3.1.1 Lists (Ordered, Mutable, Methods) ★
Ch03-L03	CS-XII-Ch03-L03-3.1.2-Tuples-Ordered-Immutable.pdf	3.1.2 Tuples (Ordered, Immutable) ★
Ch03-L04	CS-XII-Ch03-L04-3.1.3-Sets-Unordered-Unique-Math-Operations.pdf	3.1.3 Sets (Unordered, Unique, Math Operations)
Ch03-L05	CS-XII-Ch03-L05-3.1.4-Dictionaries-Key-Value-pairs.pdf	3.1.4 Dictionaries (Key-Value pairs) ★
Ch03-L06	CS-XII-Ch03-L06-3.1.5-Common-Built-in-Functions-min-max-len-sum.pdf	3.1.5 Common Built-in Functions (min, max, len, sum)
Ch03-L07	CS-XII-Ch03-L07-3.1.6-Activity-Students-Attendance-Program.pdf	3.1.6 Activity: Students Attendance Program
Ch03-L08	CS-XII-Ch03-L08-3.1.7-Activity-Word-Frequency-Counter.pdf	3.1.7 Activity: Word Frequency Counter
Ch03-L09	CS-XII-Ch03-L09-3.2-Functions-in-Python.pdf	3.2 Functions in Python ★
Ch03-L10	CS-XII-Ch03-L10-3.2.1-Types-of-Functions-Built-in-vs-User-defined.pdf	3.2.1 Types of Functions (Built-in vs User-defined)
Ch03-L11	CS-XII-Ch03-L11-3.2.2-Functions-with-Return-Values.pdf	3.2.2 Functions with Return Values
Ch03-L12	CS-XII-Ch03-L12-3.2.3-Activity-Arithmetic-Calculator-Using-Functions.pdf	3.2.3 Activity: Arithmetic Calculator Using Functions
Ch03-L13	CS-XII-Ch03-L13-3.2.4-Scope-of-Local-and-Global-Variables.pdf	3.2.4 Scope of Local and Global Variables
Ch03-L14	CS-XII-Ch03-L14-3.3-3.4-File-Handling-and-Operations-Modes-r-w-a.pdf	3.3 & 3.4 File Handling and Operations (Modes r, w, a) ★
Ch03-L15	CS-XII-Ch03-L15-3.6-with-Statement-Context-Manager.pdf	3.6 with Statement (Context Manager) ★

Code	File	Title
Ch03-L16	CS-XII-Ch03-L16-3.8-Errors-and-Exceptions-Try-Except.pdf	3.8 Errors and Exceptions (Try-Except)
Ch03-L17	CS-XII-Ch03-L17-3.9-Mini-File-Handling-Project-Grade-Tracker.pdf	3.9 Mini File Handling Project: Grade Tracker
Lecture 04	CS-XII-Lecture-04-Data-and-Analysis.pdf	Data and Analysis
Ch04-L01	CS-XII-Ch04-L01-4.1-Concept-of-Data-Analysis.pdf	4.1 Concept of Data Analysis
Ch04-L02	CS-XII-Ch04-L02-4.1.1-4.1.2-Data-Sources-and-Database-Connection.pdf	4.1.1 – 4.1.2 Data Sources and Database Connection ★
Ch04-L03	CS-XII-Ch04-L03-4.2-Creating-a-SQLite-Database-in-Python.pdf	4.2 Creating a SQLite Database in Python
Ch04-L04	CS-XII-Ch04-L04-4.3-Basic-Operations-on-Data-using-Pandas.pdf	4.3 Basic Operations on Data using Pandas ★
Ch04-L05	CS-XII-Ch04-L05-4.3.3-Handling-Missing-Values-NaN.pdf	4.3.3 Handling Missing Values (NaN) ★
Ch04-L06	CS-XII-Ch04-L06-4.4-Data-Organization-and-Representation.pdf	4.4 Data Organization and Representation
Ch04-L07	CS-XII-Ch04-L07-4.5-Data-Visualization-Types-of-Graphs.pdf	4.5 Data Visualization & Types of Graphs ★
Ch04-L08	CS-XII-Ch04-L08-4.6-Descriptive-Statistics.pdf	4.6 Descriptive Statistics ★
Lecture 05	CS-XII-Lecture-05-Application-and-Impacts-of-Computing.pdf	Application and Impacts of Computing
Ch05-L01	CS-XII-Ch05-L01-5.1-Machine-Learning-Neural-Networks-Deep-Learning.pdf	5.1 Machine Learning, Neural Networks & Deep Learning
Ch05-L02	CS-XII-Ch05-L02-5.1.1-Machine-Learning-ML.pdf	5.1.1 Machine Learning (ML)
Ch05-L03	CS-XII-Ch05-L03-5.1.2-Neural-Networks-NN.pdf	5.1.2 Neural Networks (NN) ★
Ch05-L04	CS-XII-Ch05-L04-5.1.3-Deep-Learning-DL.pdf	5.1.3 Deep Learning (DL)
Ch05-L05	CS-XII-Ch05-L05-5.1.4-Components-of-Neural-Networks.pdf	5.1.4 Components of Neural Networks ★

Code	File	Title
Ch05-L06	CS-XII-Ch05-L06-5.1.5-Components-of-Deep-Learning.pdf	5.1.5 Components of Deep Learning
Ch05-L07	CS-XII-Ch05-L07-5.2-Applications-of-Neural-Networks-and-Deep-Learning.pdf	5.2 Applications of Neural Networks and Deep Learning
Ch05-L08	CS-XII-Ch05-L08-5.3-Secure-Collaboration-Authentication-Access-Control.pdf	5.3 Secure Collaboration (Authentication, Access Control) ★
Ch05-L09	CS-XII-Ch05-L09-5.3.2-Data-Protection-Encryption-Passwords-Backup-Firewall.pdf	5.3.2 Data Protection (Encryption, Passwords, Backup, Firewall)
Ch05-L10	CS-XII-Ch05-L10-5.4-Security-Threats-and-Mitigation-Techniques.pdf	5.4 Security Threats and Mitigation Techniques ★
Ch05-L11	CS-XII-Ch05-L11-5.4.2-Identify-Security-Threats.pdf	5.4.2 Identify Security Threats
Ch05-L12	CS-XII-Ch05-L12-5.4.3-Apply-Mitigation-Techniques.pdf	5.4.3 Apply Mitigation Techniques
Ch05-L13	CS-XII-Ch05-L13-5.5-Equity-and-Equal-Access-in-Digital-Collaboration.pdf	5.5 Equity and Equal Access in Digital Collaboration
Ch05-L14	CS-XII-Ch05-L14-5.5.1-Functions-of-Equity-and-Equal-Access.pdf	5.5.1 Functions of Equity and Equal Access ★
Ch05-L15	CS-XII-Ch05-L15-5.5.2-Collaboration-Tools.pdf	5.5.2 Collaboration Tools
Lecture 06	CS-XII-Lecture-06-Entrepreneurship-in-the-Digital-Age.pdf	Entrepreneurship in the Digital Age
Ch06-L01	CS-XII-Ch06-L01-6.1-Entrepreneur-and-Entrepreneurship.pdf	6.1 Entrepreneur and Entrepreneurship
Ch06-L02	CS-XII-Ch06-L02-6.2-Entrepreneurship-in-the-Digital-Age.pdf	6.2 Entrepreneurship in the Digital Age ★
Ch06-L03	CS-XII-Ch06-L03-Table-6.1-Local-examples-of-digital-entrepreneurship.pdf	Table 6.1 Local examples of digital entrepreneurship
Ch06-L04	CS-XII-Ch06-L04-6.3-From-Problem-to-Business-Idea.pdf	6.3 From Problem to Business Idea
Ch06-L05	CS-XII-Ch06-L05-6.4-Prototype.pdf	6.4 Prototype ★

Code	File	Title
Ch06-L06	CS-XII-Ch06-L06-6.5-Types-of-Prototypes-Low-Mid-High-Fidelity.pdf	6.5 Types of Prototypes (Low, Mid, High-Fidelity)
Ch06-L07	CS-XII-Ch06-L07-6.6-Prototype-Development-Cycle-Design-Build-Test-Iterate.pdf	6.6 Prototype Development Cycle (Design, Build, Test, Iterate) ★
Ch06-L08	CS-XII-Ch06-L08-6.7-Class-Activity-Create-a-Prototype.pdf	6.7 Class Activity: Create a Prototype
Ch06-L09	CS-XII-Ch06-L09-6.8-Minimum-Viable-Product-MVP.pdf	6.8 Minimum Viable Product (MVP) ★
Ch06-L10	CS-XII-Ch06-L10-6.9-Difference-between-Prototype-and-MVP.pdf	6.9 Difference between Prototype and MVP
Ch06-L11	CS-XII-Ch06-L11-6.10-Identifying-the-Riskiest-Assumption.pdf	6.10 Identifying the Riskiest Assumption
Ch06-L12	CS-XII-Ch06-L12-6.11-Developing-an-MVP.pdf	6.11 Developing an MVP
Ch06-L13	CS-XII-Ch06-L13-6.12-Case-Study-MVP-for-a-Canteen-Pre-Order-System.pdf	6.12 Case Study: MVP for a Canteen Pre-Order System
Ch06-L14	CS-XII-Ch06-L14-6.13-Testing-an-MVP.pdf	6.13 Testing an MVP
Ch06-L15	CS-XII-Ch06-L15-6.14-Beachhead-Market.pdf	6.14 Beachhead Market ★
Ch06-L16	CS-XII-Ch06-L16-6.15-6.16-Complete-Student-Project-Ethical-Use.pdf	6.15 & 6.16 Complete Student Project & Ethical Use
Lecture 07	CS-XII-Lecture-07-Final-Revision-and-Mock-Paper.pdf	Final Revision and Mock Paper

Lecture 01

Computer Systems (HCI)

Chapter lecture — 15 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XII · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — بارہویں جماعت

15 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XII

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیئریر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

Lectures in this pack

Chapter 1: Computer Systems (HCI). Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 1.1 Fundamentals of Human Computer Interaction (HCI)

L03. 1.2 Applications of HCI (Domains of Life)

L05. 1.3 Types of User Interaction

L07. 1.4 Importance of HCI

L09. 1.6 Need Analysis for Interface Design

L11. 1.8 Methods for Improving HCI

L13. 1.9.3 – 1.9.5 Wireframing, Figma, and Prototypes

L15. 1.11.2 Testing Methods (Usability, A/B, Automated)

L02. 1.1.1 – 1.1.2 Traditional vs Natural Interaction

L04. 1.3 Components of HCI

L06. 1.3 Interface Types, Environment & Feedback

L08. 1.5 Accessibility Principles

L10. 1.7 Human Computer Interaction Problems

L12. 1.9 User Interface Design (UI vs UX)

L14. 1.11 Test and Evaluate HCI (Evaluation Methods)

CHAPTER 1

Computer Systems (HCI)

This chapter teaches you Human-Computer Interaction (HCI): how people and computers talk to each other, how to design screens that are easy and fair to use, and how to test those designs before they go live. You will apply every idea to things you already use in Pakistan — a bank ATM, JazzCash, and a school portal.

اس باب میں آپ ہیومن کمپیوٹر انٹرایکشن (HCI) سیکھیں گے: انسان اور کمپیوٹر آپس میں کیسے بات کرتے ہیں، اسکرینیں کیسے آسان اور منصفانہ بنائی جاتی ہیں، اور انہیں عوام تک پہنچانے سے پہلے کیسے جانچا جاتا ہے۔

What you will learn

- Define HCI (also called CHI and MMI) and name the five sensory channels of interaction.
- Describe HCI applications in health care, banking, education, and networking.
- Explain environment and the two kinds of feedback.
- Carry out a need analysis before designing an interface.
- Differentiate UI from UX, and compare wireframes, Figma work and prototypes.
- Differentiate traditional interaction from natural interaction with local examples.
- Name the components of HCI and classify types of user interaction and interface.
- State why HCI is important and apply five accessibility principles.
- Identify common HCI problems and methods for improving HCI.
- Choose evaluation and testing methods (SUS, NPS, usability, A/B, automated audits).

1.1 Fundamentals of Human Computer Interaction (HCI)

LEARN IT

Human-Computer Interaction (HCI) is the study and design of technology so that it **serves people**. An HCI system is easy to use, efficient, and responsive to human needs. HCI is also known as **CHI** (Computer-Human Interface) or **MMI** (Man-Machine Interaction). The three names mean the same idea: the meeting point of a person and a machine.


HCI is not only "making a pretty screen". It asks: Can a student in Hyderabad find results on the school portal in 30 seconds? Can a grandmother send JazzCash without help? Can a person standing at an outdoor ATM in bright sunlight read the buttons?

Sensory channels of interaction

Humans and computers communicate through **sensory channels**. A sensory channel is a path that carries information to (or from) one of the human senses. Computers must send and receive signals on the same channels, or the conversation breaks.

Channel	How humans use it	How computers respond
Sight (بصارت)	Look at screens, graphics or videos.	Displays visuals on monitors and screens.
Touch (چھونا)	Tap, type or swipe.	Responds with clicks or vibrations (haptics).
Hearing (سنا)	Listen to sounds or voices.	Provides audio feedback via speakers.
Voice (آواز)	Speak commands (for example, "Alexa").	Processes speech and replies.
Spatial (مکانی)	Move in physical space.	Tracks position or body movement (for example, VR).

Haptics means physical feedback you can feel, such as a phone vibrating when a JazzCash payment succeeds. **Spatial** interaction means the system notices where your body is, as in a VR headset or a Kinect camera.



Five sensory channels meet at the human. HCI design must support the channels the user actually needs.

WORKED EXAMPLE

Worked example: map a JazzCash payment to channels. Sara in Sukkur sends Rs 500 to her brother.

1. **Sight:** she looks at the JazzCash home screen and the amount field.
2. **Touch:** she taps "Send Money" and types the mobile number.
3. **Voice (optional):** she could say "JazzCash, send five hundred rupees" if voice commands are on.
4. **Hearing + haptics:** a beep and a short vibration confirm "Payment successful".

If the app showed no tick, no sound and no vibration, Sara would not know whether the money left. That is an HCI failure, not a banking failure.

REMEMBER IT

Remember the three names: HCI = CHI = MMI. Think "Human meets Machine." Five channels: **S-T-H-V-S** — Sight, Touch, Hearing, Voice, Spatial. "See The Handy Voice in Space."

COMMON MISTAKE

Mistake: Writing "HCI is only about computer hardware" or mixing up Voice with Hearing.

Fix: HCI is about the *design of the conversation* between people and machines. Hearing is what you *listen to* (speakers). Voice is what you *speak* (microphone + speech software).

آردو میں سمجھیں

ہیومن کمپیوٹر انٹرایکشن (HCI) کا مطلب ہے لیکنالوجی کو اس طرح ڈیزائن کرنا کہ وہ انسانوں کے لیے فائدہ مند، آسان اور مؤثر ہو۔ اسے CHI یا MMI بھی کہتے ہیں۔ انسان اور کمپیوٹر پانچ جسی راستوں سے بات کرتے ہیں: بصارت، چھونا، سنا، آواز اور مکانی حرکت۔ ہیپٹکس (Haptics) وہ ارتعاش ہے جو آپ کو چھو کر محسوس ہوتا ہے۔

CHECK YOURSELF

1. Give two other names for HCI.
2. Which channel tracks body movement in VR?
3. Is a phone vibration sight, touch (haptics), or voice?

Answers: 1. CHI (Computer-Human Interface) and MMI (Man-Machine Interaction). 2. Spatial. 3. Touch / haptics.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. HCI studies: a. How people and computers work together b. Only CPU clocks c. Only NAND d. Only SQL keys	MCQ 2. Another name mentioned is: a. CHI / MMI b. MVP c. SDLC only d. K-map	MCQ 3. Sensory channels include: a. Sight, touch, hearing, voice, spatial b. Only smell in this course c. Only taste d. Only OSI layer 7	MCQ 4. Good HCI makes systems: a. Usable, efficient, fitting human needs b. Harder on purpose c. Mouse-only always d. Text in 4pt always	MCQ 5. Haptics are: a. Touch feedback (vibration) b. Pie charts c. Foreign keys d. Sprints
---	--	---	---	---

MCQ 6. VR tracking is a: a. Spatial channel b. Primary key c. Bubble sort d. Histogram

Extra short questions

1. Define HCI.
2. Five sensory channels from the notes.
3. Give a computer response for touch and for voice.
4. Why HCI is not "just drawing a pretty screen".

Extra long question

1. Tabulate the five channels with a human action and a computer response. Then explain one device that uses three channels at once.

Extra answer key MCQs: 1. A 2. A 3. A 4. A 5. A 6. A Short 1. Human-Computer Interaction: design of technology around people. 2. Sight, touch, hearing, voice, spatial. 3. Touch: click/haptic. Voice: speech recognition and spoken reply. 4. It includes users, tasks, environment, feedback, accessibility. Long 1. Smartphone: sight (GUI), touch (tap/haptic), hearing (ringtone), optional voice assistant. Closing: if one channel fails, another should still work (accessibility).
--

1.1.1 – 1.1.2 Traditional vs Natural Interaction

LEARN IT

1.1.1 **Traditional interaction** is the basic way people use everyday devices. It relies on standard input and output: a mouse, a keyboard, a keypad, a monitor, speakers, or a simple touchscreen tap and swipe.

- **Computer:** moving a mouse and typing on a keyboard; output via monitor and speakers.
- **Smartphone (traditional use):** tapping and swiping on a touchscreen; output via screen lighting and vibrations.

1.1.2 **Natural interaction** is advanced, smart technology that lets people interact **without a mouse or keyboard**. It feels more human — you speak, move, or show your face, and the system understands.

- **Voice:** speaking commands into a device (for example, "Alexa, play a song").
- **Body and gesture:** facial recognition to unlock a phone, or playing VR games by waving hands.

Feature	Traditional	Natural
Main input	Mouse, keyboard, keypad, simple tap/swipe	Voice, face, hand/body gesture, movement
Feels like	Operating a machine	Talking or moving as you do with people
Examples	TV remote, ATM keypad, school-portal login typed on a PC	FaceID, Siri, Kinect games, "Hey Google"
Typical output	Screen, speakers, vibration	Spoken reply, unlock, tracking of the body in VR

WORKED EXAMPLE

Worked example: sort today's tools. List three traditional and three natural interfaces you might use in one day in Sindh.

Traditional: (1) HBL ATM keypad to withdraw cash. (2) College computer lab: mouse + keyboard to open the school portal. (3) Television remote at home.

Natural: (1) Unlocking a phone with FaceID. (2) Asking Google Assistant "Call Aslam". (3) A VR science demo in which you pick a molecule by waving your hand.

Notice: the *same smartphone* can be traditional (you type a PIN) or natural (the camera reads your face). The classification depends on **how you interact**, not on the brand of the device.

REMEMBER IT

Test sentence: If you must press keys or tap labelled buttons, it is traditional. If the machine understands speech, face or body movement, it is natural.

COMMON MISTAKE

Mistake: "Touchscreens are always natural interaction."

Fix: Ordinary tapping and swiping on a phone is still listed as traditional in this chapter. Natural interaction starts when the system understands voice, face, or full-body gesture without a mouse or keyboard.

اردو میں سمجھیں

روایتی تعامل (Traditional Interaction) میں ماؤس، کی بورڈ، کی پیڈ یا عام ٹیپ اور سوائپ استعمال ہوتے ہیں، جیسے اے ٹی ایم کی پیڈ۔ قدرتی تعامل (Natural Interaction) میں آواز، چہرہ یا جسم کی حرکت سے کام ہوتا ہے، جیسے فیس آئی ڈی (FaceID) یا "الیکسا، گانا چلاؤ"۔ درجہ بندی آئی کی نہیں، تعامل کے طریقے کی ہوتی ہے۔

CHECK YOURSELF

1. Is an ATM keypad traditional or natural?

2. Give one voice example of natural interaction from the source.

3. Why can one smartphone be both traditional and natural?

Answers: 1. Traditional. 2. "Alexa, play a song" (or any spoken command). 3. Because typing a PIN is traditional, while FaceID or a voice assistant on the same phone is natural — it depends on the method, not the device.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Traditional interaction uses:

a. Standard controls — keys, mouse, menus

b. Gaze and gesture as the default 1980 PC

c. Smell

d. Telepathy

MCQ 2. Natural interaction tries to:

a. Use human skills (speech, gesture, touch) with less training

b. Force people to learn command codes only

c. Remove all feedback

d. Use only punch cards

MCQ 3. A command-line is more:

a. Traditional / learned

b. Natural baby-talk

c. IoT soil

d. A pie

MCQ 4. Pinch-to-zoom on a phone is more:

a. Natural (gesture)

b. A foreign key

c. A K-map

d. Waterfall

MCQ 5. Both still need:

a. Feedback so the user knows the system heard them

b. No UI

c. No errors ever

d. No accessibility

MCQ 6. Alexa-style speech is:

a. Natural-ish voice interaction

b. A datasheet

c. A histogram

d. A stack pop

Extra short questions

1. Define traditional vs natural interaction.

2. One example each in a college.

3. A drawback of "natural".

4. Can a product mix both?

Extra long question

1. Design a library search: one traditional UI and one natural UI. Compare learnability, errors, and accessibility.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Traditional: trained widgets (keyboard/mouse). Natural: speech, gesture, touch that feel like the real world.

2. Traditional: SIS forms. Natural: fingerprint attendance, touch kiosk.

3. False gesture recognition; privacy of voice; not natural for every disability.

4. Yes — a phone has icons (traditional GUI) and gestures/voice.

Long

1. Traditional: typed query + filters. Natural: speak the title / point at a shelf QR. Learnability vs noisy halls. Accessibility: keyboard vs voice. Recommend both.

1.2 Applications of HCI (Domains of Life) ★ Golden

LEARN IT

HCI is used to design and develop interactive systems such as **desktop applications, websites and mobile apps**. These are **human-centred solutions** built to meet user needs across many domains of life. A domain is an area of daily activity — health, money, school, talking to people. When you design for a domain, you design for that domain's **users, tasks and risks**. A mistake on a games app is annoying. A mistake on a medical or banking screen can harm a person or lose money. That is why examiners treat this topic as golden.

Domain	Application examples	User benefit
Health care	Patient portals, telemedicine apps, assistive technologies	Improves access to medical services remotely
Banking	Mobile banking apps, secure ATM interfaces	Enables quick transactions and secure financial management
Education	E-learning platforms (LMS), online exam portals	Enhances teaching, learning and student engagement
Networking and communication	Social media, messaging apps (WhatsApp), Zoom	Connects people globally through collaboration tools



HCI sits at the centre of four everyday domains: healthcare, banking, education and networking.

WORKED EXAMPLE

Worked example: the same HCI idea in three Pakistani systems.

- Step 1 — ATM (banking).** You insert a card, the screen shows large buttons (Fast Cash, Balance, Other), you enter a PIN on the keypad, and you take cash. HCI benefit: a quick, secure transaction without a human teller.
- Step 2 — JazzCash (banking + communication).** You log in with a PIN or fingerprint, choose Send Money, type a number and amount, confirm, and see "Successful" with a JazzCash SMS. HCI benefit: money moves in seconds from a shop in Larkana to a student in Karachi.
- Step 3 — School portal (education).** A Grade XII student opens the college LMS, taps "Download date sheet", and submits a leave form. HCI benefit: learning and admin tasks happen without standing in a queue at the office.
- Step 4 — Compare the user benefit.** Banking HCI saves time and keeps money safe. Education HCI raises engagement. Health HCI (a Sehat/telemedicine app) brings a doctor to a village phone. Networking HCI (WhatsApp, Zoom) keeps a family in Dubai in touch with parents in Sukkur.

REMEMBER IT

Exam mnemonic H-BEN: Health, Banking, Education, Networking. For each, write: one application + one user benefit. That structure scores full marks on "applications of HCI".

COMMON MISTAKE

Mistake: Listing brand names only ("WhatsApp, JazzCash, Zoom") without saying the *domain* and the *user benefit*.

Fix: Always write three parts: domain → example → what the user gains. "Banking: JazzCash mobile app — enables quick, secure transfers."

آرڈو میں سمجھیں

ایچ سی آئی کی ایپلیکیشنز صحت، بینکنگ، تعلیم اور نیٹ ورکنگ کے شعبوں میں انسانی ضروریات پوری کرتی ہیں۔ صحت میں مریض پورٹل اور نیلی میڈیسن دور سے علاج دیتے ہیں، بینکنگ میں موبائل ایپ اور لے ٹی ایم تیز اور محفوظ لین دین دیتے ہیں، تعلیم میں ای لرننگ اور آن لائن امتحان مشغولیت بڑھاتے ہیں، اور وائس ایپ یا ڈوم لوگوں کو جوڑتے ہیں۔

EXAM TIP

Very common 5–8 mark question: "Explain applications of HCI in different domains of life with examples." Draw a four-row table (Health care, Banking, Education, Networking & communication). Each row: one or two application names + the user benefit from the source. Add a local line (ATM / JazzCash / school portal) to show you can apply the idea. Do not write a story about only one app.

CHECK YOURSELF

- Name the four domains of HCI given in the source.
- What user benefit does HCI bring in banking?
- Give one education application and one networking application.

Answers: 1. Health care, banking, education, networking and communication. 2. Quick transactions and secure financial management. 3. Education: LMS or online exam portal. Networking: social media, WhatsApp or Zoom.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. HCI applies to:

- a. Desktops, web, mobile, kiosks, embedded, VR
- b. Only mainframes in 1970
- c. Only NAND trainers
- d. Only paper

MCQ 2. A hospital infusion pump UI is HCI in:

- a. Health / safety-critical life
- b. Sports memes only
- c. Fashion only
- d. OSI cabling only

MCQ 3. Education HCI example:

- a. LMS that students can actually submit homework on
- b. A random 4pt PDF
- c. An unlabelled form
- d. A hidden button

MCQ 4. Bad HCI in a bank app can:

- a. Make people send money to the wrong account
- b. Speed bubble sort
- c. Fix NAND
- d. Change Big O of Python

MCQ 5. Domains of life in the book include:

- a. Work, health, education, home, public services
- b. Only gaming
- c. Only compilers
- d. Only ER

MCQ 6. This is ★ because you must:

- a. Name domains with a concrete interface each
- b. Draw K-maps
- c. Write SQL only
- d. List sprints

Extra short questions

- Five domains of HCI application.
- Why HCI in medical devices is life-critical.
- A public-service example in Pakistan.
- What "application of HCI" means in a 3-mark.

Extra long question

- Pick four domains. For each: one system, one user, one HCI requirement. ★ Golden 10-mark.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Work software, health devices, education, home/consumer, government/public kiosks, transport...
- A confusing unit (mg vs ml) can dose wrongly.
- NADRA/passport kiosks, metro ticket machines.
- Not the definition — a place + the interface + why users matter.

Long


- Clinic: nurse, glanceable alarms. College portal: student, language + mobile. ATM: elderly, privacy hood + large text. Car dash: driver, eyes-up. Table.

1.3 Components of HCI

LEARN IT

HCI relies on several primary components that work together. If one component is weak, the whole interaction feels broken. The first four are the people, the machine, the conversation, and the job to be done.

	Component	Meaning
i	User (صارف)	Any individual or group that interacts with a computer system to achieve defined goals. Two categories: end users (people who directly operate the system, from beginners to experts) and stakeholders (people with an interest in the outcome, such as managers and clients).
ii	Computer system (کمپیوٹر سسٹم)	The platform where humans and computers communicate through input, output and feedback using an interface. It connects human actions with machine responses.
iii	User interaction (صارف کا تعامل)	The process through which a user communicates with a system by performing actions (clicking, tapping, typing, speaking). It transforms user intent into system responses.
iv	Task (کام)	The specific action users perform (for example, booking a ticket). It has three characteristics: task complexity (filling a form vs designing a 3D model), user knowledge (basic typing vs advanced programming), and time requirement (ATM withdrawal vs online passport application).



The user performs a task through interaction with a computer system. All four parts must fit together.

WORKED EXAMPLE

Worked example: label the four components of an HBL ATM withdrawal.

1. **User:** end user = the account holder standing at the machine; stakeholder = the bank that owns the ATM and must keep it safe and working.
2. **Computer system:** the ATM hardware plus the bank's software; it takes PIN input, shows a screen, and dispenses notes (output and feedback).
3. **User interaction:** insert card → type PIN → choose "Cash" → type amount → confirm. Intent ("I want Rs 5,000") becomes a machine response (cash + receipt).
4. **Task:** withdraw cash. Complexity: low (a few buttons). User knowledge: basic (PIN and amounts). Time: about one minute — much shorter than an online passport application.

REMEMBER IT

U-C-I-T: User, Computer system, Interaction, Task. "U Can Interact with Tasks." Then add three task questions: How hard? What skill? How long?

COMMON MISTAKE

Mistake: Calling the bank manager an "end user" of the ATM, or saying a task has only one property (difficulty).

Fix: The manager is usually a **stakeholder**. The person pressing the keys is the **end user**. A task always has complexity, knowledge and time — mention all three in long answers.

اردو میں سمجھیں

ایچ سی آئی کے چار بنیادی اجزاء ہیں: صارف (ایٹم پیوڑ جو خود سسٹم چلاتا ہے اور اسٹیک ہولڈر جس کا نتیجہ میں مفاد ہے)، کمپیوٹر سسٹم (ان پی، آرٹ پیٹ اور فیڈبیک کا پائپ فارم)، صارف کا تعامل (کلک، ٹیپ، ٹائپ، بولنا) اور کام (تاسک) جس کی پیچیدگی، مطلوبہ مہارت اور وقت مختلف ہوتا ہے۔ اے ٹی ایم سے رقم نکالنا آسان اور مختصر کام ہے؛ پاسپورٹ کی آن لائن درخواست لمبا کام ہے۔

CHECK YOURSELF

1. What is the difference between an end user and a stakeholder?
2. Name the three characteristics of a task.
3. In a school portal, who is a stakeholder?

Answers: 1. End users directly operate the system; stakeholders have an interest in the outcome (managers, clients) but may not click the buttons. 2. Task complexity, user knowledge, time requirement. 3. The principal, IT admin or board office — they care about results even if students are the end users.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The user in HCI is:

- a. The human with goals, limits, skills
- b. The CPU
- c. The database
- d. The sprint log

MCQ 2. The task is:

- a. What the user is trying to get done
- b. The Wi-Fi password
- c. The NAND count
- d. The pie flavour

MCQ 3. The context/environment is:

- a. Where/when/noise/light/stress
- b. Only RGB of the logo
- c. Only Big O
- d. Only SQL

MCQ 4. Missing any component in design causes:

- a. HCI problems
- b. Faster CPUs
- c. Better keys
- d. Shorter OSI

MCQ 5. A tired nurse at night is part of:

- a. User + environment
- b. Only the algorithm
- c. Only the DBMS
- d. Only Figma auto-layout

MCQ 6. Components work:

- a. Together
- b. In isolation always
- c. Only in waterfall phase 6
- d. Only after MVPs ship

Extra short questions

1. List the primary HCI components from the notes.
2. Give a college-lab example of each.
3. What if you design only for an expert user?
4. Why environment?

Extra long question

1. Analyse JazzCash (or a similar app) using HCI components. Where might it fail for a first-time Urdu user in bright sunlight?

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. User, task, interface, environment/context, feedback (and system).
2. User: XI student. Task: submit practical. UI: LMS upload. Env: noisy lab, short period. Feedback: "uploaded" tick.
3. Beginners fail — a typical HCI problem.
4. A UI that needs silence fails in a crowded canteen kiosk.

Long

1. User literacy/language; task send-money; UI contrast; outdoor glare; feedback of "success". Recommend larger type, Urdu toggle, confirmation screen.

1.3 Types of User Interaction

LEARN IT

User interaction can happen in many different ways depending on the technology used. Learn every type with one clean example — board questions often ask you to "list and explain" five or more.

Interaction type	Description	Examples
Direct manipulation	Handling digital objects on a screen exactly like physical objects.	Dragging files, zooming images with fingers
Command-based	Giving precise instructions through typed text commands.	MS-DOS, Linux terminal (<code>dir</code> , <code>cd</code> ..)
Menu-driven	Selecting from predefined lists or options instead of typing.	Clicking "Start Test" or "Download" on a portal
Form fill	Entering structured data into blank text fields.	Sign-up forms, ticket booking screens
Conversational	Communicating with systems using natural human language (text or voice).	Chatbots, ChatGPT, Google Assistant
Gesture-based	Using body or hand movements to control systems.	Swiping touchscreens, VR hand gestures
Voice interaction	Speaking commands directly to the system.	"Call Asiam" on a smartphone
Context-aware	Systems sense the environment and act automatically without a prompt.	Smart lighting turning on when you enter a room
Biometric	Using biological features for interaction and authentication.	Fingerprint unlock, FaceID
Haptic and tactile	Providing physical feedback to confirm actions.	Phone vibration when typing
Multimodal	Combining two or more interaction types together.	Voice + touch (speak a search, then tap)

WORKED EXAMPLE

Worked example: a full JazzCash "Send Money" session, labelled by type.

- Open the app with a fingerprint → **biometric**.
- Home screen shows Send Money, Bill Payment, Load → you tap Send Money → **menu-driven**.
- Type the receiver's mobile number and the amount → **form fill**.
- The keypad vibrates on each tap → **haptic**.
- Optional: say "Send five hundred to Ali" then tap Confirm → **multimodal** (voice + touch).

Same idea on a **school portal**: menu-driven ("Date Sheet", "Fee Challan"), form fill (leave application), conversational (a chatbot "When is the chemistry practical?").

REMEMBER IT

Group them: hands on screen (direct, gesture, haptic) · words (command, conversational, voice) · lists and blanks (menu, form) · automatic/body (context-aware, biometric) · mix (multimodal).

COMMON MISTAKE

Mistake: Treating "voice interaction" and "conversational" as identical, or calling a dropdown menu "command-based".

Fix: Voice is spoken commands only. Conversational includes typed chat (ChatGPT) as well as voice. Command-based means you type precise codes such as `dir` , not clicking a menu.

اردو میں سمجھیں

تعمیل کی اقسام میں براہ راست پیرا پھری، کمانڈ، مینو، فارم، گفتگو (چیٹ بوت)، اشارہ، آواز، سیاق و سباق سے آگاہ نظام، پایومیٹرک، بیپٹک اور ملٹی موڈل شامل ہیں۔ جاز کیش میں فنکر پرنٹ پایومیٹرک ہے، "رقم بھیجیں" مینو ہے، نمبر لکھنا فارم ہے، اور آواز کے ساتھ ٹیپ ملٹی موڈل ہے۔

CHECK YOURSELF

- Which type is a Linux `cd` .. command?
- Smart lighting that turns on when you enter a room is which type?
- Why is speaking a search and then tapping a result called multimodal?

Answers: 1. Command-based. 2. Context-aware. 3. Because it combines two or more types (voice + touch) in one task.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. GUI means:

a. Graphical User Interface

b. Great Universal Internet

c. Gate Unary Inverter

d. Grouped Unique Index

MCQ 2. CLI is:

a. Command-line (typed commands)

b. Only touch

c. Only VR

d. Only pie menus of 1990 Mac always

MCQ 3. Voice UI example:

a. Siri / Alexa / Google Assistant

b. A datasheet

c. A K-map

d. A foreign key

MCQ 4. Gesture UI example:

a. Swipe, pinch, Wii/Kinect-style move

b. SQL SELECT

c. Bubble swap

d. HTTP GET only

MCQ 5. The best interaction type depends on:

a. User, task, environment

b. Whatever is newest

c. Always voice

d. Always CLI

MCQ 6. A surgeon in a sterile field may prefer:

a. Voice/gesture over touch

b. A dusty mouse

c. Tiny 4pt CLI

d. Captcha on the pump

Extra short questions

- Name four interaction types with examples.
- One strength of CLI.
- One weakness of voice.
- Can one app offer two types?

Extra long question

- Recommend an interaction type for: (a) programmer (b) ATM (c) car while driving (d) museum kiosk. Justify with user+environment.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- GUI desktop; CLI terminal; touch; voice; gesture; AR/VR — any four.
- Fast and scriptable for experts.
- Noise, privacy, accents, no visual scan of options.
- Yes — VS Code GUI + terminal; phones GUI + voice.

Long

- (a) GUI+CLI (b) GUI+keys, privacy (c) voice/steering-wheel, eyes up (d) large touch, language choice. Table.

8

1.3 Interface Types, Environment & Feedback

LEARN IT

Components v-vii complete the HCI picture: the look of the controls, the place where you use them, and the signals that tell you "it worked" or "try again".

v) User interface (UI)

The **user interface** is the medium through which humans interact with computer systems.

- **Graphical User Interface (GUI):** visual elements such as windows, icons and menus (Windows OS, Android).
- **Command-Line Interface (CLI):** text-based typing (MS-DOS, Linux terminal).
- **Touch interface:** tapping, swiping, pinching (smartphones, tablets).
- **Voice User Interface (VUI):** spoken commands (smart speakers).
- **Natural User Interface (NUI):** gestures, body movements or immersive environments (VR headsets, Microsoft Kinect).

vi) Environment

The **environment** is the real-world setting where a person uses a computer system. It is shaped by:

- **Physical conditions** — an ATM outdoors in sunlight, heat, noise, rain.
- **Social conditions** — a quiet classroom, a crowded bazaar, privacy at a PIN pad.
- **Technical hardware** — slow college Wi-Fi, a cracked phone screen, an old browser.

vii) Feedback

Feedback is the signal or response given to confirm or guide actions.

System feedback	User feedback
Response from the computer: a "Loading..." bar, a "Message Sent!" tick, or an error sound.	Input from the user to the system: tapping a "Submit" button, giving a 5-star rating.

WORKED EXAMPLE

Worked example: environment and feedback at a roadside ATM in Hyderabad.

Physical: noon sunlight washes out a dim screen — the GUI must use high contrast.

Social: people stand in a queue; the user needs a privacy shield around the PIN pad.

Technical: the printer may be out of paper, so on-screen "Take your cash" plus a beep still has to confirm the transaction.

System feedback: "Please wait", cash coming out, a printed or SMS receipt.

User feedback: the user presses Confirm, or later rates the bank's app 4 stars.

On a **school portal** during board-exam week, hundreds of students on weak Wi-Fi need a visible "Loading results..." bar. Silence after clicking "View marks" is poor system feedback.

REMEMBER IT

GUI vs CLI vs NUI: GUI = pictures you click. CLI = words you type. NUI = body you move. VUI = voice you speak. Touch = fingers on glass.

Feedback rule: **system talks back; user talks in.**

COMMON MISTAKE

Mistake: Mixing up system feedback with user feedback, or saying "environment" means only the software theme (dark mode).

Fix: A tick mark is system feedback. A 5-star rating is user feedback. Environment is the *real world* around the user — sun, noise, hardware — not the colour of the app (though a good UI will adapt to that world).

اردو میں سمجھیں

یوزر انٹرفیس وہ واسطہ ہے جس سے انسان سسٹم سے بات کرتا ہے۔ GUI تصاویر اور مینو، CLI لکھی کمانڈز، ٹچ، آواز (VUI) اور قدرتی اشارے (NUI)، ماحول وہ حقیقی جگہ ہے جہاں سسٹم استعمال ہوتا ہے — دھوپ میں آئے ٹی ایم، خاموش کلاس روم، کمزور وائی فائی۔ سسٹم فیڈبیک مشین کا جواب ہے ("بھیج دیا گیا")؛ صارف کا فیڈبیک صارف کا ان پٹ ہے (سیٹ بن یا پانچ ستارے)۔

CHECK YOURSELF

1. Name five types of user interface given in the source.

2. Give one physical and one social example of environment.

3. Is a "Message Sent" tick system feedback or user feedback?

Answers: 1. GUI, CLI, Touch, VUI, NUI. 2. Physical: ATM in sunlight. Social: a quiet classroom. 3. System feedback.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Feedback is:

a. The system telling the user what happened

b. A student evaluation form only

c. A foreign key

d. A sprint retrospective only

MCQ 2. A spinner/progress bar is:

a. Feedback that work is ongoing

b. A primary key

c. A sort

d. A NAND

MCQ 3. No feedback after Save causes:

a. Double clicks / lost trust

b. Faster CPUs

c. Better Big O

d. Shorter OSI

MCQ 4. The environment includes:

a. Noise, light, device, social setting

b. Only CSS colours

c. Only RAM

d. Only Agile

MCQ 5. A GUI button should look:

a. Clickable (affordance) and then respond

b. Like body text

c. Invisible

d. Like a pie

MCQ 6. Error messages should:

a. Say what went wrong and what to do

b. Say ERROR 0xUnknown only

c. Be in 4pt grey

d. Vanish in 0.1s

Extra short questions

1. Define interface and feedback.

2. Three feedback channels.

3. Example of poor environment–UI fit.

4. What is an affordance?

Extra long question

1. Audit the college portal login: environment, UI type, three feedback events (success, fail, loading). Rewrite one bad message.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. UI: the medium of interaction. Feedback: system response the user can sense.

2. Visual (message), audio (beep), haptic (vibrate).

3. Voice-only help in a noisy canteen; tiny text on a sunny ticket machine.

4. The look that suggests how to use a control (a button looks pressable).

Long

1. Lab noise/shared PCs. GUI form. Success: "Welcome Ali". Fail: "Wrong password — try again or reset". Loading: spinner. Bad: "Error 500" → "Server busy, wait 1 min or see the lab attendant".

1.4 Importance of HCI ★ Golden

LEARN IT
HCI ensures that machines are approachable and usable, turning complex technology into everyday tools. **Good design** makes technology simple and enjoyable (touchscreens). **Poor design** causes confusion and risks (unclear buttons on medical devices). This is why HCI is not optional decoration. A confusing JazzCash confirm button can send money to the wrong number. A confusing school-portal "Submit" can lock a student out of an online exam. Importance questions in the board exam expect the five implications below, each with a sentence of explanation.

Implication	Description
1. Enhance productivity	Well-designed interfaces help users work faster, make fewer mistakes, and achieve goals efficiently.
2. Promotes inclusivity	Accessibility features (screen readers, voice commands) empower marginalized groups and ensure equal use of technology for everyone.
3. Drives innovation	Emerging tech such as AR/VR, AI and IoT rely strictly on solid HCI principles for people to actually adopt and use them.
4. Economic impact	User-friendly products gain higher adoption rates, customer loyalty and market success, driving profits.
5. Ethical responsibility	Responsible design ensures technology respects user privacy, reduces bias and supports human well-being.

WORKED EXAMPLE
Worked example: good vs poor HCI, same task.
Task: send Rs 2,000 through JazzCash to a parent.
Good HCI: large "Send Money" button, amount shown in words and numbers, last 4 digits of the number repeated, fingerprint confirm, green "Successful" plus SMS. Result: fast, few mistakes, the user trusts the app (productivity + economic loyalty + ethics of clear consent).
Poor HCI: tiny grey buttons, no amount-in-words, no confirm screen, no tick. Result: wrong number, no idea if it worked, user deletes the app and goes back to a bank queue.
Medical contrast from the source: unclear buttons on a medical device are not just ugly — they are dangerous. That is why ethical responsibility sits in this table.

REMEMBER IT
P-I-I-E-E: Productivity, Inclusivity, Innovation, Economic impact, Ethics. Sentence: "Please Include Innovative, Ethical Earnings."

COMMON MISTAKE
Mistake: Writing only "HCI is important because it makes apps look nice."
Fix: Looks are a tiny part of UI. Importance answers must name productivity, inclusivity, innovation, money and ethics. Quote the medical-device warning if you have time.

اردو میں سمجھیں
اچھا ایچ سی آئی پیچیدہ ٹیکنالوجی کو روزمرہ کا آسان اوزار بناتا ہے؛ برا ڈیزائن الجھن اور خطرہ پیدا کرتا ہے، جیسے طبی آلے پر غیر واضح بٹن۔ پانچ مضمرات: پیداواری بڑھتی ہے، شمولیت آتی ہے، جدت اپنائی جاتی ہے، معیشت مضبوط ہوتی ہے، اور رازداری و انصاف کی اخلاقی ذمہ داری پوری ہوتی ہے۔

EXAM TIP
Typical wording: "Why is HCI important? Discuss its implications." (8 marks) Write a short opening (good design vs poor design) then five numbered points with one example each. Local examples that earn marks: ATM PIN privacy (ethics), screen reader on a school portal (inclusivity), JazzCash one-tap send (productivity), a bank's app beating a rival because it is easier (economic), AR classroom app that students actually use (innovation). Do not skip ethics — examiners look for privacy and well-being.

CHECK YOURSELF
1. Give one example of poor design mentioned in the source.
2. Which implication is about screen readers and equal use?
3. How does HCI create economic impact?
Answers: 1. Unclear buttons on medical devices. 2. Promotes inclusivity. 3. User-friendly products get higher adoption, loyalty and profits.

Extra board practice
These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. HCI matters because:

- a. It turns complex machines into usable tools
- b. It makes CPUs clock faster by magic
- c. It replaces maths
- d. It deletes ethics

MCQ 2. Usability includes:

- a. Effectiveness, efficiency, satisfaction
- b. Only colour
- c. Only NAND count
- d. Only price

MCQ 3. Poor HCI costs:

- a. Errors, time, accidents, abandoned products
- b. Nothing
- c. Only printer ink
- d. Only font licences

MCQ 4. Good HCI can:

- a. Widen who can use the system (accessibility)
- b. Reduce RAM physically
- c. Change OSI to 2 layers
- d. Remove the need for passwords always

MCQ 5. This is ★: expect a question:

- a. Why HCI is important — 3–5 points with examples
- b. Trace a K-map
- c. Write bubble sort
- d. Normalise to 5NF

MCQ 6. A usable result portal:

- a. Students find the mark without a tutorial
- b. Hides the mark in 12 menus
- c. Uses 4pt text
- d. Needs a CS degree

Extra short questions

- Three reasons HCI is important.
- Link to a Pakistani e-service.
- HCI vs pretty graphics.
- One safety example.

Extra long question

- Write a 10-mark essay: Importance of HCI with five points, each with a local example. ★ Golden.

Extra answer key
MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Fewer errors; faster tasks; more users included; safer devices; product success.
- If the tax/passport site is confusing, people pay agents — HCI failure with social cost.
- A pretty unusable app still fails; a plain clear form can succeed.
- Car dashboards / medical pumps — confusion harms people.

Long

- Learnability (first-year portal); efficiency (JazzCash); safety (clinic software); accessibility (screen reader); business (app store ratings). Short intro/conclusion.

1.5 Accessibility Principles

LEARN IT

Accessibility principles are HCI guidelines that ensure digital systems are usable by **all** individuals, including people with diverse physical, sensory and cognitive abilities. They remove barriers to create equal access.

Accessibility is not a "special extra". It is how you make sure a student with low vision, a shopkeeper who cannot use a mouse, or a colour-blind driver can still complete the task.

Principle	What it means	Example
1. High contrast (واضح رنگ)	Make text and pictures stand out clearly against the background.	Black text on a white background in a railway app, readable in bright sunlight.
2. Readable fonts (پڑھنے میں آسان تحریر)	Clear, simple fonts with proper size and spacing.	A school website using large Calibri so homework instructions are easy to read.
3. Colour-blind friendly design (رنگوں کب پہچان)	Do not depend only on colours; also use symbols or text labels.	A traffic app showing a red circle with a "STOP" label, not just a red colour.
4. Inclusive navigation (آسان نیویگیشن)	Give users different ways to move around a system.	A website that lets you use the Tab key to jump between buttons if you cannot use a mouse.
5. Multimodal detection (متعدد حسوں ذرائع)	Present information in different formats (sight, sound, touch).	A video with text captions, or a phone vibrating to alert a user.

WORKED EXAMPLE

Worked example: audit a school portal against the five principles.

- Contrast:** are result PDFs pale grey on white? Fail — use dark text.
- Fonts:** is the fee-challan note in 9-point decorative script? Fail — large Calibri (or a similar simple font), as the source recommends.
- Colour:** is "fail" only a red row with no word "Fail"? Fail — add the word, for colour-blind students.
- Navigation:** can a student who cannot use a mouse reach "Download date sheet" with Tab + Enter? If not, fail.
- Multimodal:** does the principal's video assembly have captions, and does a fee-due alert vibrate as well as flash? If not, deaf or busy students miss it.

The same five checks apply to an outdoor ATM (sunlight contrast) and to JazzCash (large numerals, Urdu labels, vibration on success).

REMEMBER IT

C-F-C-N-M: Contrast, Fonts, Colour-blind, Navigation, Multimodal. "Can Friends Catch New Messages?"

COMMON MISTAKE

Mistake: "Accessibility is only for people with disabilities, so our class portal does not need it."

Fix: The source says usable by **all** individuals. High contrast also helps in sunlight; captions help in a noisy bus; large fonts help tired eyes during board exams.

اردو میں سمجھیں

رسائی پذیری (Accessibility) کے اصول یقینی بناتے ہیں کہ ہر انسان سسٹم استعمال کر سکے، بشمول مختلف جسمانی، حسی اور ذہنی صلاحیتوں والے افراد۔ پانچ اصول: اونچا تضاد (کنٹراسٹ)، پڑھنے میں آسان فونٹ، صرف رنگ پر انحصار نہ کرنا، کی بورڈ سمیت متبادل نیویگیشن، اور معلومات کو نظر، آواز اور لمس کئی شکلوں میں دینا۔

CHECK YOURSELF

- Why is a red-only "STOP" sign a problem?
- Which principle does the Tab key support?
- Give the source's school-website font example.

Answers: 1. Colour-blind users may not see the meaning if there is no symbol or "STOP" text. 2. Inclusive navigation. 3. Large Calibri on a school website for homework instructions.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Accessibility means:

a. People with diverse abilities can use the system
b. Only experts can use it
c. Colourful GIFs always
d. Mouse-only

MCQ 2. A principle is providing:

a. Multiple ways to see/operate (text, caption, keyboard)
b. Captcha of 12 steps
c. 4pt grey on grey
d. Auto-playing sound only

MCQ 3. Keyboard access helps:

a. Motor impairment and power users
b. Nobody
c. Only AI models
d. Only IoT soil

MCQ 4. Contrast helps:

a. Low vision
b. Faster bubble sort
c. TCP window
d. Primary keys

MCQ 5. Captions help:

a. Deaf users and noisy labs
b. Routers
c. NAND
d. K-maps

MCQ 6. Accessibility is part of:

a. HCI quality, not an optional sticker
b. Only marketing
c. Only XII entrepreneurship
d. Only physical cabling

Extra short questions

- Define accessibility in HCI.
- Four practical techniques.
- Who else benefits besides disabled users?
- Link to assistive tech in XI.

Extra long question

- Audit a video lecture page against accessibility: list 6 fixes. Include one for vision, hearing, motor, language.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Design so people with disabilities (and many others) can perceive, operate and understand the UI.
- Alt text, captions, keyboard, contrast, resizable text, Urdu/English toggle.
- Broken arm, noisy room, bright sun, second-language users.
- Screen readers need labelled buttons — that is an HCI job.

Long

- Transcript+captions; contrast; pause; keyboard; alt on diagrams; Urdu summary. Do not autoplay. Test with Tab and a screen reader.

11

1.6 Need Analysis for Interface Design

LEARN IT

Need analysis is the process of identifying the gap between the **existing situation** and the **desired outcome**. In HCI it is done **before** designing a UI, so that you understand users' goals, tasks, abilities and expectations.

If you skip need analysis, you guess. Guessing is how a school portal ends up with 40 menus and no "Download date sheet" button on the home screen.

Steps in need analysis:



1. **Identify the users:** who exactly will use the system? (elderly people, teenagers, ...)
2. **Information collection:** gather data using interviews, questionnaires or observations.
3. **Analyse user needs:** identify the core problems, goals and requirements.
4. **Prioritise needs:** decide which features are the most critical to build first.
5. **Develop solutions:** design a system that meets those verified needs.

WORKED EXAMPLE

Case study from the source: mobile banking app. Before building the app, the team interviews customers and discovers:

- Users want secure login via Fingerprint / FaceID.
- Elderly users need large buttons and simple navigation.
- Users want support for both English and local languages.

Result: the UI is designed around these proven needs, which makes success more likely.

Apply the five steps to a college portal in Sindh.

1. Users: Grade XI–XII students, parents, clerks, teachers. Not "everyone in Pakistan".
2. Collect: interview 20 students; questionnaire to parents; watch a queue at the office on fee day.
3. Analyse: students cannot find date sheets; parents cannot read English-only fee notices; clerks re-type the same form.
4. Prioritise: (1) date sheet on home screen, (2) Urdu/Sindhi fee notice, (3) online leave form. Fancy animations wait.
5. Solution: a simple portal with those three features, large buttons, bilingual labels.

REMEMBER IT

Need analysis = gap finding. Write: Existing = what hurts now. Desired = what "done" looks like. The UI must close that gap, not decorate it.

COMMON MISTAKE

Mistake: Starting in Figma on day one, then "asking users later".

Fix: Need analysis comes **before** UI design. Features you did not hear from users are guesses. Guessed features waste time and fail in exams when the question is "why do we analyse needs?"

اردو میں سمجھیں

نیڈ اینالیسس موجودہ صورتحال اور مطلوبہ نتیجے کے فرق کو یو آئی بنانے سے پہلے تلاش کرتا ہے۔ پانچ قدم: صارفین کی پہچان، انٹرویو یا مشاہدہ سے معلومات، ضروریات کا تجزیہ، اہم خصوصیات کو ترجیح، پھر تصدیق شدہ ضرورتوں پر حل۔ موبائل پینٹنگ کی مثال: فنگر پرنٹ لاگ ان، بزنس، اور انگریزی کے ساتھ مقامی زبان۔

CHECK YOURSELF

1. When in the design process is need analysis done?
2. List the five steps in order.
3. Name three needs found in the mobile-banking case study.

Answers: 1. Before designing the UI. 2. Identify users; collect information; analyse needs; prioritise; develop solutions. 3. Fingerprint/FaceID login; large buttons and simple navigation for elderly users; English plus local languages.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Need analysis finds:

- a. The gap between now and the desired UI outcome
- b. The CPU benchmark
- c. The NAND delay
- d. The sprint velocity only

MCQ 2. You study:

- a. Users, tasks, pain points, constraints
- b. Only colours you like
- c. Only competitors' logos
- d. Only Big O

MCQ 3. A persona is:

- a. A realistic portrait of a user type
- b. A primary key
- c. A pie chart
- d. A gate

MCQ 4. Skipping need analysis causes:

- a. Pretty UIs that solve the wrong problem
- b. Correct Big O automatically
- c. Free RAM
- d. Shorter OSI

MCQ 5. Constraints include:

- a. Time, devices, literacy, connectivity
- b. Only Figma seats
- c. Only NAND trainers
- d. Only exam memes

MCQ 6. Output of need analysis is:

- a. Requirements for the interface
- b. A compiled kernel
- c. A K-map
- d. A histogram of NAND

Extra short questions

1. Define need analysis in HCI.
2. Three techniques.
3. Give a college example.
4. What is a constraint here?

Extra long question

1. Do a mini need analysis for a hostel complaint app: users, top 3 tasks, environment, constraints, 5 requirements.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Identify the gap between the current situation and what users need the interface to do.
2. Interview, observe, survey, task analysis, look at old system logs.
3. Students miss fee deadlines → need SMS reminders + a 3-step mobile payment UI.
4. Many students on low-end Androids and 2G — no huge animations.

Long

1. Users: residents, warden. Tasks: report, track, urgent leak. Env: phone on the stairs. Constraints: Urdu, photos, weak wifi. Req: offline draft, photo, status, privacy, large buttons.

1.7 Human Computer Interaction Problems ★ Golden

LEARN IT

HCI problems are common difficulties that stop users from using technology smoothly. They happen when systems fail to meet human needs or cognitive limits. **Cognitive limits** means the mind can only hold and process so much at once — if an app asks you to remember three SMS codes at the same time, it has gone past that limit.

Board answers score well when you name the problem, explain it in one line, and give a concrete example (the source examples are safe; a matching local example is even better).

Problem	Explanation and example
Interface complexity	Too many options or a confusing layout. Example: a shopping app with so many menus you cannot find the checkout button.
Poor feedback	The system does not show if an action worked or failed. Example: clicking Submit and the screen freezes with no confirmation.
Inconsistency	Different parts of the app look or act differently. Example: a magnifying-glass icon for Search on one page, a binocular icon on another.
Accessibility gaps	Design ignores people with disabilities. Example: a video tutorial platform without captions for deaf users.
Compatibility issues	Interface fails on different devices or browsers. Example: a website that works on a laptop but crashes on a mobile browser.
Contextual neglect	The system does not adjust to the user's situation. Example: a map app with no dark mode, blinding the driver at night.
High cognitive load	Users must memorize too much or follow overly complex steps. Example: a registration system forcing you to remember three different SMS codes at once.
Trust deficiency	The system feels unsafe or hides security cues. Example: an online store asking for credit cards but lacking an SSL/HTTPS lock icon.

WORKED EXAMPLE

Worked example: diagnose three local systems.

ATM: six tiny unmarked buttons beside the screen and no "Cash is coming" message → Interface complexity + poor feedback. A user walks away while cash is still coming out.

JazzCash: "Send" is green on the home screen but orange on the confirm screen, and there is no padlock on the payment page → inconsistency + trust deficiency.

School portal: works in Chrome on a lab PC, blank on a student's Android browser; exam instructions are a caption-free video; login needs a portal password, an email OTP and an SMS OTP on the same screen → compatibility, accessibility gap, high cognitive load.

Once you can name the problem, Section 1.8 tells you how to fix it.

REMEMBER IT

Eight problems in two families: (1) Screen problems — complexity, inconsistency, accessibility, compatibility, context. (2) Mind-and-trust problems — poor feedback, cognitive load, trust. If the user is lost, look at the screen family. If the user is scared or exhausted, look at the mind family.

COMMON MISTAKE

Mistake: Writing "the app is bad" as an HCI problem, or mixing up cognitive load with compatibility.

Fix: Use the exact names from the table. Cognitive load is "too much to remember". Compatibility is "breaks on another device or browser".

اردو میں سمجھیں

ایچ سی آئی مسائل وہ رکاوٹیں ہیں جو مستخدم کو انسانی ضرورت یا ذہنی حد کے مطابق نہ ہونے پر پیدا ہوتی ہیں۔ آٹھ مسائل: انٹرفیس کی پیچیدگی، کمزور فیڈبیک، عدم مطابقت (ایک جیسا نہ ہونا)، رسائی کی کمی، آلہ/براؤزر سے ناسازگاری، سیاق کو نظرانداز کرنا، زیادہ ذہنی بوجھ، اور اعتماد کی کمی (جیسے HTTPS ٹالیے کے بغیر کارڈ ماسک)۔

EXAM TIP

Common 8-mark question: "Describe problems of HCI with examples." Aim for at least six of the eight, each in the pattern Name → one-line meaning → example. Memorise the source examples (checkout buried in menus, frozen Submit, binocular vs magnifying glass, no captions, laptop-only site, no dark mode, three SMS codes, missing HTTPS lock). Adding ATM / JazzCash / portal examples shows application and often gains the last marks.

CHECK YOURSELF

1. Which problem is a missing HTTPS lock on a payment page?

2. Why are three SMS codes at once an HCI problem?

3. A site works on a laptop but crashes on a phone. Name the problem.

Answers: 1. Trust deficiency. 2. High cognitive load — users must memorize too much. 3. Compatibility issues.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. HCI studies:

- a. How people and computers work together
- b. Only CPU clocks
- c. Only NAND
- d. Only SQL keys

MCQ 2. Another name mentioned is:

- a. CHI / MMI
- b. MVP
- c. SDLC only
- d. K-map

MCQ 3. Sensory channels include:

- a. Sight, touch, hearing, voice, spatial
- b. Only smell in this course
- c. Only taste
- d. Only OSI layer 7

MCQ 4. Good HCI makes systems:

- a. Usable, efficient, fitting human needs
- b. Harder on purpose
- c. Mouse-only always
- d. Text in 4pt always

MCQ 5. Haptics are:

- a. Touch feedback (vibration)
- b. Pie charts
- c. Foreign keys
- d. Sprints

MCQ 6. VR tracking is a:

- a. Spatial channel
- b. Primary key
- c. Bubble sort
- d. Histogram

Extra short questions

1. Define HCI.
2. Five sensory channels from the notes.
3. Give a computer response for touch and for voice.
4. Why HCI is not "just drawing a pretty screen".

Extra long question

1. Tabulate the five channels with a human action and a computer response. Then explain one device that uses three channels at once.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Human-Computer Interaction: design of technology around people.
2. Sight, touch, hearing, voice, spatial.
3. Touch: click/haptic. Voice: speech recognition and spoken reply.
4. It includes users, tasks, environment, feedback, accessibility.

Long

1. Smartphone: sight (GUI), touch (tap/haptic), hearing (ringtone), optional voice assistant. Closing: If one channel fails, another should still work (accessibility).

1.8 Methods for Improving HCI

LEARN IT

Once you can name an HCI problem, you fix it with a matching method. The source lists eight methods. Learn each with its tiny example — they pair almost one-to-one with Section 1.7.

- **Enhance usability:** simplify navigation (a clear "Buy Now" button).
- **Strengthen accessibility:** support disabilities (captions on videos).
- **Ensure consistency:** keep layouts uniform (the same "Save" button everywhere).
- **Provide clear feedback:** show action results ("Payment Successful" popup).
- **Improve adaptability:** responsive design (the website scales to mobile screens).
- **Apply user-centred design (UCD):** focus on real user goals and pilot-test.
- **Use multimodal interaction:** allow touch, voice or gesture inputs combined.
- **Continuous testing:** regularly update based on user feedback.

User-centred design (UCD) means the real user's goals drive every decision, and you trial (pilot-test) the design with those users instead of guessing in an office.

Responsive design means the layout rearranges itself for phone, tablet and PC, instead of staying a laptop-only page.

WORKED EXAMPLE

Worked example: match each JazzCash / portal problem to a fix.

Problem (1.7)	Method (1.8)
Cannot find "Send Money"	Enhance usability — one clear button
No captions on help video	Strengthen accessibility
Search icon changes from page to page	Ensure consistency
Submit freezes with no message	Clear feedback — "Payment Successful"
Portal crashes on mobile	Improve adaptability — responsive layout
Built features nobody asked for	UCD — interview, then pilot-test
Elderly user cannot type a long number	Multimodal — voice + touch
Complaints ignored after launch	Continuous testing and updates

REMEMBER IT

Think "problem → method" as a pair. Complexity ↔ usability. No captions ↔ accessibility. Different icons ↔ consistency. Freeze ↔ feedback. Phone crash ↔ adaptability. Guessing ↔ UCD. One input only ↔ multimodal. Launch and forget ↔ continuous testing.

COMMON MISTAKE

Mistake: Naming methods without saying *what they change* ("we will improve HCI" is not an answer).

Fix: Always attach the source example: "Provide clear feedback, for example a Payment Successful popup."

آردو میں سمجھیں

ایچ سی آئی بہتر بنانے کے طریقے: نیویگیشن آسان کرنا، رسائی پڑھانا (کپشن)، ایک جیسا لے آؤٹ، واضح فیڈبیک ("ادائیگی کامیاب")، ریسیانسیو ڈیزائن، صارف مرکز ڈیزائن (UCD) اور پائلٹ ٹیسٹ، ملٹی موڈل ان پٹ، اور مسلسل جانچ۔ ہر مسئلے کا ایک جوڑی دار حل یاد رکھیں۔

CHECK YOURSELF

1. What does UCD stand for, and what extra step does it include?
2. Which method stops a website from falling on a phone?
3. Give the source's example of clear feedback.

Answers: 1. User-Centred Design; focus on real user goals and pilot-test. 2. Improve adaptability (responsive design). 3. A "Payment Successful" popup.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Improving HCI often starts with:

- a. Watching real users (usability test)
- b. Adding more clipart
- c. Reducing contrast
- d. Hiding labels

MCQ 2. Consistency means:

- a. Same words/icons/positions for the same action
- b. A new metaphor every page
- c. Random colours
- d. Surprise menus

MCQ 3. Simple IA (information architecture) means:

- a. Fewer, clearer paths to tasks
- b. Deeper 12-level menus
- c. All links in a PDF dump
- d. No search

MCQ 4. Prototypes help you:

- a. Fix HCI cheaply before code
- b. Skip users
- c. Skip accessibility
- d. Skip feedback

MCQ 5. Training is a fix when:

- a. The task is rare/complex — but do not use it to excuse a bad UI
- b. The button is invisible
- c. Contrast is 1:1
- d. Errors are in hex only

MCQ 6. Iterative improvement is:

- a. Test → change → test again
- b. Ship once never look
- c. Waterfall with no users
- d. Only career slides

Extra short questions

1. Five methods to improve HCI.
2. Why test with real students not only the developer?
3. A quick win for a form.
4. What is a heuristic evaluation?

Extra long question

1. Take a 7-step fee-payment UI. Cut it to 3 steps, list the HCI problems you removed, and how you would re-test.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Simplify, consistent patterns, better feedback, accessibility, user tests, prototypes, reduce steps.
2. Developers know the map; users get lost.
3. Show required fields, inline errors, remember the class dropdown.
4. An expert checks the UI against rules (consistency, feedback...) before/besides user tests.

Long

1. Steps: amount → confirm → OTP. Removed: extra account-type screens, jargon, no progress. Re-test: 5 students timed, errors counted, one interview.

1.9 User Interface Design (UI vs UX) ★ Golden

LEARN IT

UI design is the process of creating and organizing the **visual elements** of a software application so users can interact with it easily and efficiently.

1.9.1 Components of a user interface

Component	Role
Buttons	Clickable elements that perform actions (Submit, Cancel).
Menus	Lists of options for navigating the system.
Icons	Small symbols representing tools or actions.
Text fields	Boxes where users type information (passwords, search).
Checkboxes / radio buttons	Selecting options in a form. Checkboxes allow several choices; radio buttons allow only one in a group.
Sliders	Adjusting values along a bar (volume, brightness).

1.9.2 User experience (UX)

UX is the overall experience a user has while interacting with a system — how smooth, comfortable and satisfying it feels.

UI is what you see; UX is how it feels.

WORKED EXAMPLE

Source example: food-delivery app. The UI is the nice pictures of burgers and the red buttons. The UX is that the app loads fast, tracking works, and the food arrives without the user getting frustrated.

Local walk-through: JazzCash.

- **UI:** green Send button, JazzCash logo, amount text field, fingerprint icon, menu of Bill / Load / Send.
- **UX:** login in two seconds, no crash in a weak-signal bazaar, money arrives, SMS comes, the user feels safe and finished — or, if it hangs with no tick, the UX is bad even if the buttons look pretty.

School portal: UI = logo, "Login" button, date-sheet menu icon. UX = a student finds the chemistry practical date in under a minute on a phone, without calling the clerk.

Pretty UI + slow, confusing flow = poor UX. Plain UI + fast, clear flow = good UX.

REMEMBER IT

Clothes vs day out. UI is the outfit (colours, buttons, icons). UX is the whole day (Did you arrive on time? Did you get wet? Were you stressed?). Examiners love the line: *UI is what you see; UX is how it feels.*

COMMON MISTAKE

Mistake: Writing "UI and UX are the same" or "UX is just colours".

Fix: UI = visual components (buttons, menus, icons, fields, checkboxes, sliders). UX = overall smoothness, comfort and satisfaction, including speed and whether the task succeeds.

اردو میں سمجھیں

یو آئی ڈیزائن بصری عناصر — بٹن، مینو، آئیکن، لیکسٹ فیلڈ، چیک باکس/ریڈیو، سلائیڈر — کو ترتیب دینا ہے۔ یو ایکس پورا تجربہ ہے: کتنا ہموار، آرام دہ اور اطمینان بخش لگا۔ یو آئی وہ ہے جو آپ دیکھتے ہیں؛ یو ایکس وہ ہے جو آپ محسوس کرتے ہیں۔ کھانے کی ڈیلیوری ایپ میں ہرگز کی خوبصورت تصویر یو آئی ہے، تیز لوڈنگ اور وقت پر کھانا یو ایکس ہے۔

EXAM TIP

Highest-yield short question in the chapter: "Differentiate between UI and UX with an example." Write: (1) the two definitions, (2) the sentence "UI is what you see; UX is how it feels", (3) the food-delivery example from the source, (4) optionally JazzCash or the school portal. For 5 marks also list four UI components. Do not spend the answer describing Figma — that is the next topic.

CHECK YOURSELF

1. List six UI components from the source.

2. In the food-delivery example, what is UX?

3. Complete: "UI is what you see; UX is ____."

Answers: 1. Buttons, menus, icons, text fields, checkboxes/radio buttons, sliders. 2. The app loads fast, tracking works, food arrives without frustration. 3. how it feels.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. UI is:

- a. The look and interactive controls
- b. The whole research journey only
- c. The database schema
- d. The sprint velocity

MCQ 2. UX is:

- a. The overall experience (useful, usable, satisfying)
- b. Only the colour palette
- c. Only the logo
- d. Only the NAND count

MCQ 3. You can have pretty UI and bad UX when:

- a. The task still takes 20 confusing steps
- b. Buttons are clear and short
- c. Feedback is excellent
- d. Accessibility is strong

MCQ 4. UX research includes:

- a. Interviews, tests, personas
- b. Only picking hex colours
- c. Only SQL
- d. Only OSI

MCQ 5. This is ★: define both, then:

- a. Give a product example of each going wrong
- b. Draw a K-map
- c. Write a sort
- d. List Access objects

MCQ 6. A progress tracker in a 3-step form is mainly:

- a. UX (and a bit of UI)
- b. A foreign key
- c. A histogram
- d. A gate

Extra short questions

1. Define UI vs UX.

2. Who typically does each job.

3. Example: ATM.

4. Why both matter in exams.

Extra long question

1. A food-delivery app is gorgeous but checkout fails twice. Analyse UI vs UX, then list 4 UX fixes that may not need new colours. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. UI: visual/interactive layer. UX: how the whole journey feels and whether the goal is achieved easily.

2. UI designer: screens/components. UX: research, flows, prototypes, testing. They overlap.

3. UI: button layout. UX: whether you felt safe and finished withdrawal quickly.

4. Papers ask the difference plus one example — do not mix the letters.

Long

1. UI may be fine. UX: errors, extra steps, unclear fees. Fixes: guest checkout, saved address, fee shown early, retry without losing the cart, better messages.

1.9.3 – 1.9.5 Wireframing, Figma, and Prototypes

LEARN IT

1.9.3 Wireframing is creating a basic visual outline or blueprint of a user interface **before** the final design. It plans the structure without focusing on colours or detailed graphics.

Low-fidelity wireframes (Lo-Fi)

A simple black-and-white sketch showing basic layout (boxes and lines). Used early to test and share ideas quickly. Focuses purely on structure and flow.

Lo-Fi sketch → Add details → Hi-Fi prototype

High-fidelity prototypes (Hi-Fi)

A detailed version that looks almost exactly like the final product. Includes real colours, fonts, images and interactive clickable buttons. Used for final user testing.



A school-portal login: Lo-Fi boxes and labels on the left; a coloured, realistic Hi-Fi prototype on the right.

1.10 What is Figma?

Figma is a popular, free, web-based tool used to design and collaborate on UI and prototypes. It works directly in a web browser — you do not have to install a heavy program on the college lab PCs.

Creating a low-fidelity design in Figma

1. **Sign up:** access the Figma workspace online.
2. **Create frames:** select the Frame tool (for example an iPhone-sized frame) to act as your screen canvas.
3. **Add shapes:** draw basic rectangles for buttons and circles for avatars.
4. **Add text:** use the text tool to label buttons (for example, "Sign Up").
5. **Duplicate and edit:** copy the frame to create the next screen (for example, the Home Screen).

1.9.5 Prototype design

A **prototype** is an early interactive model used to test design ideas **before writing actual code**. In Figma you use the Prototype tab to link screens together.

- Set a **Trigger** (for example, "On Tap").
- Set an **Action** (for example, "Navigate to Home Screen").

Real users can then click through the fake app to see if the navigation makes sense.

WORKED EXAMPLE

Worked example: JazzCash-style "Send Money" in Figma, without writing code.

1. Lo-Fi on paper or in Figma: three frames — Home (boxes: Send, Bills, Load), Amount (text field + Next), Success (tick + Done).
2. Show the sketch to two classmates. If they cannot find Send, move that box to the top. This is the point of Lo-Fi: cheap changes.
3. In Figma, add a phone frame, rectangles, and labels. Duplicate the frame for Home, Amount and Success.
4. Prototype tab: Trigger = On Tap of the Send rectangle; Action = Navigate to Amount. On Tap of Next → Success.
5. Hand the laptop to a student. If they tap Bills by mistake, the navigation is still wrong — fix it before any programmer writes Java or Kotlin.

REMEMBER IT

Lo-Fi = boxes. **Hi-Fi** = almost the real app. **Prototype** = clickable. Figma can hold all three stages. Trigger = what the user does. Action = where the fake app goes.

COMMON MISTAKE

Mistake: Colouring a Lo-Fi wireframe, or thinking a Figma prototype is the finished coded app.

Fix: Lo-Fi stays black-and-white on purpose so people discuss structure, not taste in colours. A prototype tests ideas before code; developers still have to build the real system afterwards.

آرڈو میں سمجھیں

وائر فریم یو آئی کا بنیادی خاکہ ہے، رنگوں سے پہلے۔ یو فائی سیاہ و سفید ڈیے ہیں؛ ہائی فائی تقریباً حتمی شکل ہے، رنگ، فونٹ اور کلک بونے والے بدن کے ساتھ۔ فگما (Figma) مفت ویب ٹول ہے؛ فریم بناؤ، شکل اور متن ڈالو، فریم کا پی کرو۔ پروٹو ٹائپ کوڈ سے پہلے کا چاہئے والا نمونہ ہے جس میں ٹرگر (On Tap) اور ایکشن (اگلی اسکرین) جوڑے جاتے ہیں۔

CHECK YOURSELF

1. What does a Lo-Fi wireframe deliberately leave out?
2. Where does Figma run?
3. In Figma prototyping, what is a trigger? Give the source example.

Answers: 1. Colours and detailed graphics (It is structure only). 2. Directly in a web browser. 3. The user event that starts a move between screens, e.g. "On Tap".

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A wireframe is:

- a. A low-detail blueprint of screens
- b. The final branded mock
- c. A running MVP
- d. A database dump

MCQ 2. Figma is:

- a. A collaborative UI/prototype tool in the browser
- b. A DBMS
- c. An OSI sniffer
- d. A sort

MCQ 3. A prototype here is:

- a. A clickable model of the UI
- b. The production server
- c. A primary key
- d. A pie

MCQ 4. You wireframe:

- a. Before polishing pixels
- b. After launch only
- c. Instead of need analysis
- d. Instead of testing ever

MCQ 5. Low fidelity means:

- a. Boxes and labels, not final art
- b. Photoreal 3D
- c. Compiled ARM
- d. Encrypted SQL

MCQ 6. Figma is taught because the book uses it to:

- a. Design and share UI without installing heavy tools
- b. Replace Python
- c. Replace ER
- d. Replace SDLC

Extra short questions

1. Define wireframe and prototype.
2. Why Figma (from the notes)?
3. Order: need analysis → wireframe → prototype → test.
4. What belongs on a wireframe?

Extra long question

1. Describe three Figma wireframe frames for college attendance: login, mark, confirm. List what you would test with five students.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Wireframe: structure/layout. Prototype: interactive simulation of the UI.
2. Free, web-based, collaborative, good for class.
3. Do not skip to colour before structure.
4. Boxes, headings, buttons, notes — not lorem-pretty photos.

Long

1. Frame contents; tap targets; Urdu. Test: time to mark, errors, could they undo. Change the prototype, not the database first.

1.11 Test and Evaluate HCI (Evaluation Methods)

LEARN IT

Testing checks if the product works properly (finding bugs). **Evaluation** determines whether it meets users' needs (usability). Together they improve the product before release.

A school portal can be "bug-free" (testing passed) and still unusable if students cannot find the date sheet (evaluation failed). You need both.

1.1.1 Evaluation methods

Method	Description
SUS (System Usability Scale)	A standard 10-item questionnaire used to calculate a score for how usable a system is.
NPS (Net Promoter Score)	Asks users: "How likely are you to recommend this app to a friend?" Measures user loyalty.
Formative evaluation	Done during development to collect early feedback and improve the design continuously.
Summative evaluation	Done at the end of development to measure overall success against the original goals.
Expert reviews	Usability specialists review the app against established design standards (heuristics).

Heuristics are agreed rules of good design (for example "show system status", "be consistent"). An expert review checks the product against those rules without waiting for a huge user survey.

WORKED EXAMPLE

Worked example: when to use each method on a school portal.

1. Week 2 of building: show the Lo-Fi to five students, change the menu. That is **formative** evaluation.

2. A teacher who has studied HCI checks the screens against standard rules (Is feedback visible? Are labels consistent?). That is an **expert review**.

3. After the portal is "finished", 30 students fill the 10 SUS questions. A low score means it is still hard to use, even if there are no crashes.

4. Ask: "On a scale of 0-10, would you recommend this portal to a friend in another college?" That is **NPS** (loyalty).

5. Compare the finished portal with the original goals (date sheet in one tap, bilingual fee notice). That is **summative** evaluation.

REMEMBER IT

Formative = forming it (during). Summative = summing it up (end). SUS = 10 questions on usability. NPS = "Would you recommend it?" Expert = specialist vs heuristics.

COMMON MISTAKE

Mistake: Saying testing and evaluation are the same, or mixing formative with summative.

Fix: Testing = bugs. Evaluation = does it meet human needs. Formative is during; summative is at the end against original goals.

اردو میں سمجھیں

ٹیسٹنگ یہ دیکھتی ہے کہ پروڈکٹ ٹھیک چلتا ہے (بگز)، ایویلیوایشن یہ دیکھتی ہے کہ صارف کی ضرورت پوری ہوئی۔ SUS دس سوالوں والا استعمال کا اسکور ہے، NPS پوچھتا ہے کہ آپ یہ ایپ دوست کو کتنی تجویز کریں گے۔ فارمیٹو جانچ ترقی کے دوران ہوتی ہے، سمیٹو آخر میں اہداف کے خلاف۔ مایر جائزہ ہیورسٹکس (Heuristics) پر ہوتا ہے۔

CHECK YOURSELF

1. What is the difference between testing and evaluation?

2. How many items are on the SUS questionnaire?

3. When is summative evaluation done?

Answers: 1. Testing finds bugs / checks the product works; evaluation checks it meets users' needs (usability). 2. 10. 3. At the end of development, against the original goals.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Testing asks:

a. Does it work / any bugs?

b. Is the logo pretty only

c. What is Big O

d. What is a FK

MCQ 2. Evaluation asks:

a. Does it meet user needs / usability goals?

b. Only CPU temp

c. Only compile errors

d. Only SQL syntax

MCQ 3. You need both because:

a. A bug-free UI can still be unusable

b. Bugs never matter

c. Users never matter

d. HCI is only art

MCQ 4. A usability goal example:

a. First-time student pays fees in < 3 minutes

b. More colours

c. More menus

d. More jargon

MCQ 5. Evaluation can be:

a. With users or with experts/heuristics

b. Only with the CEO's nephew

c. Only after 5 years

d. Only in assembly

MCQ 6. Do this:

a. After a prototype, not only after full code

b. Never

c. Only on paper NAND

d. Only on OSI diagrams

Extra short questions

1. Differentiate testing and evaluation in HCI.

2. Give a metric for each.

3. When is expert review useful?

4. Why include real students?

Extra long question

1. Plan an evaluation of the LMS assignment-upload: 2 test cases (bugs) and 2 evaluation questions (usability) with measures.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Testing: system behaviour/bugs. Evaluation: human fit/usability/need.

2. Test: crash rate. Eval: task success, time, SUS satisfaction, error types.

3. Early, cheap, catches obvious heuristic breaks before booking users.

4. They hold the real tasks and language.

Long

1. Test: 20MB PDF; no network. Eval: can a new student succeed unaided; time; satisfaction 1-5. n=8. What you would change if time > 5 min.

1.11.2 Testing Methods (Usability, A/B, Automated) ★ Golden

LEARN IT

Testing involves observing how the system behaves under specific conditions. Learn all seven methods. The three named in the heading — usability, A/B and automated — are the ones examiners ask most, but a complete answer also names the others.

1. **Usability testing:** observing real users while they perform realistic tasks, to measure efficiency and satisfaction. If the user gets stuck, designers know where to fix the UI.
2. **Task-based testing:** assigning a specific task (for example, "Find a product and add it to cart") and strictly measuring **completion time**, **success rate** and **number of errors**.
3. **Automated audits:** software bots scan websites to detect technical issues such as broken links, slow loading speeds or low colour contrast.
4. **A/B testing:** comparing two versions of an interface (A and B). Half the users see A, half see B. The one with more clicks or sign-ups wins.
5. **Compatibility testing:** verifying the system on different browsers (Chrome, Safari), devices (mobiles, tablets, PCs) and operating systems.
6. **Performance and load testing:** simulating high traffic (for example 10,000 users logging in at once) to see if speed drops or the server crashes.
7. **Keyboard and screen-reader walkthroughs:** navigating using only the keyboard (Tab/Enter) or assistive technologies, to check accessibility for users with disabilities.

Task-based "Add to cart" Time: 12 s Success: Yes	A/B test Version A Version B half / half users more clicks wins	Automated audit Bot scanning... 3 broken links Low contrast
--	---	---

Three golden testing pictures: timed tasks, A versus B, and a bot that finds broken links and weak contrast.

WORKED EXAMPLE

Worked example: test JazzCash "Send Money" and a school portal with numbers.

Usability testing. Sit beside five students. Task: "Send Rs 100 to this test number." Do not help. Note where they pause. If three people look for Confirm at the bottom and it is at the top, that is your UI fix.

Task-based testing (numbers). Same task for 10 students.

- Success: 8 of 10 finish = success rate $(8 \div 10) \times 100 = 80\%$.
- Times: 12, 14, 11, 40, 13, 12, 15, 50, 14, 12 seconds. The two slow times (40, 50) are the students who got stuck — they also made errors.
- Errors: extra taps, wrong field. Count them. High errors + high time = poor HCI, even if most people eventually succeed.

A/B testing. Version A: green "Send" at the top. Version B: large orange "Send" under the amount. 200 users each. If B gets 140 completed payments and A gets 90, B wins. You keep B.

Automated audit. A bot reports 3 broken "Fee challan" links and low contrast on the portal's grey-on-grey marks table. Fix those before the board-exam rush.

Load testing. On result day, 10,000 students log in at 9:00 a.m. If the server crashes, performance testing failed — the UI never even appears.

Keyboard walkthrough. Unplug the mouse. Can a student Tab to "Download date sheet" and press Enter? If focus jumps randomly, accessibility testing failed.

REMEMBER IT

Task-based three numbers: Time, Success, Errors. **A/B:** two versions, split users, the higher clicks/sign-ups win. **Bot:** links, speed, contrast. **Load:** many users at once. **Keyboard:** Tab and Enter only.

COMMON MISTAKE

Mistake: Calling A/B testing "showing both designs to the same user and asking which is prettier".

Fix: Half the users see only A, half see only B. You measure behaviour (clicks, sign-ups), not a taste vote. Also: an automated audit does not replace watching real users — bots cannot see that a student is confused.

اردو میں سمجھیں

سات ٹیسٹنگ طریقے: یوزیبلٹی (حقیقی صارف کو کام کرتے دیکھنا)، ٹاسک بیسڈ (وقت، کامیابی، غلطیاں ناپنا)، خودکار آڈٹ (بوت ٹولے لنک، سست رفتار، کم کنٹراسٹ ڈھونڈنے)، A/B ٹیسٹ (آدھا صارف A، آدھا B، زیادہ کلک والا جیتے)، کمپینٹیلٹی (براؤزر اور آڈ)، لوڈ ٹیسٹ (مثلاً دس ہزار لاگ ان)، اور صرف کی بورڈ یا اسکرین ریڈر سے جلی کر رسائی کی جائے۔

EXAM TIP

Golden 8-mark question: "Explain testing methods used in HCI." Write seven short paragraphs or a seven-row table. For full marks, define usability testing (observe real users on realistic tasks), give the three task-based measures, describe automated audits with the three bot findings (broken links, slow load, low contrast), explain A/B with the half-and-half rule, then add compatibility, load (10,000 users), and keyboard/screen-reader walkthroughs. If the paper asks only "usability, A/B and automated", go deep on those three and still mention the rest in one closing line.

CHECK YOURSELF

1. Name the three measurements in task-based testing.
2. In A/B testing, who sees version A?
3. Give two issues an automated audit can detect.

Answers: 1. Completion time, success rate, number of errors. 2. Half of the users (the other half see B). 3. Any two of: broken links, slow loading, low colour contrast.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Usability testing is: a. Watching people do real tasks b. Only ping-pong servers c. Only unit tests of Python d. Only load tests of CPUs	MCQ 2. A/B testing compares: a. Two versions on similar users b. NAND vs NOR only c. Mean vs mode only d. TCP vs UDP only	MCQ 3. Automated UI tests are good for: a. Regressions of known flows b. Discovering new user feelings c. Replacing all interviews d. Measuring joy perfectly	MCQ 4. Think-aloud means: a. Users speak while they try the task b. The computer reads NAND c. SQL dumps d. Sprinters shout	MCQ 5. A/B needs: a. A clear metric (clicks, success) b. Random colours with no goal c. $n=1$ d. No ethics	MCQ 6. This is ★: name the method, when to use it, one limit. a. Yes — that is the 5-mark recipe b. No — only definitions c. No — write code d. No — draw OSI
--	--	--	--	---	--

Extra short questions

1. Define usability testing, A/B, automated testing.
2. One limit of each.
3. When A/B is overkill in XI/XII class.
4. What do you record in a usability test?

Extra long question

1. Design a usability test + a tiny A/B for a "download slip" button (blue text vs big labelled button). Tasks, n, metric, ethics. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Usability: observe tasks. A/B: two live variants. Automated: scripts click through.
2. Usability: small n, lab effect. A/B: needs traffic, can harm half the users. Auto: misses confusion that does not throw errors.
3. Five classmates on a Figma prototype is enough — no live traffic.
4. Task, success, time, errors, quotes, where they hesitated.

Long

1. Task: get the slip. $n=10$ (5+5). Metric: success and time. Ethics: consent, no marks attached. Predict big button wins. Also one automated check that the link still works.

Computer Systems (HCI)

15 single-page lessons · 5 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- **HCI** (also CHI, MMI) designs technology to be easy, efficient and responsive to people, using five sensory channels: sight, touch (haptics), hearing, voice and spatial.
- **Traditional interaction** uses mouse, keyboard, keypad or simple tap/swipe; **natural interaction** uses voice, face or body gesture without a mouse or keyboard.
- HCI applications cover **health care, banking, education, and networking/communication**, each with a clear user benefit (remote care, quick secure money, better learning, global connection).
- Four core components: **user** (end user vs stakeholder), **computer system**, **user interaction**, and **task** (complexity, knowledge, time).
- Interaction types include direct manipulation, command-based, menu-driven, form fill, conversational, gesture, voice, context-aware, biometric, haptic and multimodal.
- Interfaces: GUI, CLI, touch, VUI, NUI. **Environment** is physical, social and technical. **System feedback** is the machine's reply; **user feedback** is what the person sends in.
- HCI matters for productivity, inclusivity, innovation, economic impact and ethical responsibility. Poor design (unclear medical buttons) creates risk.
- Five accessibility principles: high contrast, readable fonts, colour-blind friendly labels, inclusive navigation, multimodal presentation.
- **Need analysis** finds the gap before UI design: identify users, collect data, analyse, prioritise, develop solutions (banking case: FaceID, large buttons, local language).
- Eight HCI problems: complexity, poor feedback, inconsistency, accessibility gaps, compatibility, contextual neglect, high cognitive load, trust deficiency.
- Improve HCI with usability, accessibility, consistency, clear feedback, adaptability (responsive design), UCD and pilot tests, multimodal input, and continuous testing.
- **UI** is the visual components (buttons, menus, icons, fields, checkboxes, sliders); **UX** is how the whole experience feels. UI is what you see; UX is how it feels.
- Lo-Fi wireframes plan structure; Hi-Fi prototypes look real; **Figma** is a free browser tool; prototypes use Trigger (On Tap) and Action (navigate) before code.
- Evaluation (SUS, NPS, formative, summative, expert/heuristic reviews) checks needs; testing (usability, task-based, automated, A/B, compatibility, load, keyboard/screen-reader) checks behaviour under conditions.

Key terms

Term	Meaning	اردو
HCI	Human-Computer Interaction; designing technology that is easy, efficient and responsive to people. Also called CHI or MMI.	انسان اور کمپیوٹر کا باہمی تعامل
Haptics	Physical feedback you can feel, such as a vibration.	لمسی / ارتعاشی جواب
Traditional interaction	Using standard input/output such as mouse, keyboard, keypad or simple tap and swipe.	روایتی تعامل
Natural interaction	Interacting without mouse or keyboard, using voice, face or body gesture.	قدرتی تعامل
End user	A person who directly operates the system.	حتمی صارف
Stakeholder	A person or group with an interest in the system's outcome (manager, client).	فريقی مفاد
GUI	Graphical User Interface using windows, icons and menus.	تصویری صارف انٹرفیس
CLI	Command-Line Interface using typed text commands.	کمانڈ لائن انٹرفیس
NUI	Natural User Interface using gestures, body movement or immersive environments (VR, Kinect).	قدرتی صارف انٹرفیس
System feedback	The computer's response that confirms or guides an action.	نظام کا جواب
User feedback	Input the user sends to the system (Submit click, star rating).	صارف کی رائے / ان پٹ
Accessibility	Making digital systems usable by all, including people with diverse abilities.	رسائی پذیری

Computer Systems (HCI)

75 marks · 1 hour 15 minutes · no notes · no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 15 and the recap. **Section A** — all 15 MCQs (1 mark). **Section B** — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define · Explain · Example · Diagram · Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. HCI is also known as:
 - a. CPU and ALU
 - b. CHI or MMI
 - c. HTTP or HTML
 - d. GUI only
2. Which sensory channel tracks body movement in VR?
 - a. Sight
 - b. Hearing
 - c. Spatial
 - d. Voice
3. Unlocking a phone with FaceID is an example of:
 - a. natural interaction
 - b. command-based interaction only
 - c. traditional interaction
 - d. CLI
4. Which domain of HCI includes patient portals and telemedicine?
 - a. Banking
 - b. Education
 - c. Networking
 - d. Health care
5. A bank manager who never uses the ATM but cares that it works is a:
 - a. stakeholder
 - b. end user
 - c. haptic device
 - d. wireframe
6. Typing `dir` in MS-DOS is:
 - a. menu-driven
 - b. command-based
 - c. context-aware
 - d. biometric
7. A "Message Sent!" tick mark is:
 - a. user feedback
 - b. a stakeholder
 - c. need analysis
 - d. system feedback
8. Unclear buttons on a medical device mainly show that poor HCI:
 - a. only affects game apps
 - b. is a colour preference
 - c. causes confusion and risk
 - d. improves load testing
9. Not depending only on colour, but adding a "STOP" label, is:
 - a. colour-blind friendly design
 - b. load testing
 - c. CLI design
 - d. A/B testing
10. Need analysis for a UI should be done:
 - a. after the product is sold
 - b. before designing the UI
 - c. only by programmers
 - d. instead of testing
11. An online store that asks for a credit card but shows no HTTPS lock has:
 - a. high contrast
 - b. natural interaction
 - c. summative evaluation
 - d. trust deficiency
12. "UI is what you see; UX is how it feels" means:
 - a. UI and UX are identical
 - b. UX is only the logo colour
 - c. UI is code and UX is hardware
 - d. UI is visual elements; UX is the overall experience
13. A Lo-Fi wireframe should focus on:
 - a. final photographs and brand colours
 - b. structure and flow using boxes and lines
 - c. server load of 10,000 users
 - d. writing the finished Python code
14. The System Usability Scale (SUS) is:
 - a. a 10-item questionnaire that scores usability
 - b. a bot that finds broken links
 - c. a type of ATM keypad
 - d. a Figma trigger
15. In A/B testing:
 - a. every user sees both versions at once and votes for the prettier one
 - b. only experts review heuristics
 - c. half the users see A, half see B, and the version with more clicks or sign-ups wins
 - d. the server is crashed on purpose

Section B — Short questions (10 × 3 = 30)

1. Define HCI. Give two other names for it and list the five sensory channels.
2. Differentiate traditional interaction from natural interaction with one example of each from daily Pakistani use.
3. State four domains of HCI. For each, give one application and one user benefit.
4. Name the four primary HCI components. Distinguish end user from stakeholder, and list the three characteristics of a task.
5. Define GUI, CLI, VUI and NUI, with one example of each.
6. Write five implications of the importance of HCI.
7. List the five accessibility principles with one example each.
8. What is need analysis? Write its five steps and three findings from the mobile-banking case study.
9. Differentiate UI from UX using the food-delivery example. Name six UI components.
10. What is A/B testing? How is it different from an automated audit?

Section C — Long questions (attempt any 3 × 10 = 30)

1. Explain the components of HCI (user, computer system, user interaction, task, interface types, environment, feedback). Illustrate every part with a labelled walk-through of a person withdrawing cash from an outdoor ATM in Hyderabad.
2. Describe eight HCI problems with examples. Then match each problem to a method of improving HCI. Use JazzCash or a school portal wherever it makes the example clearer.
3. "UI is what you see; UX is how it feels." Explain UI design, its six components, and UX. Then describe Lo-Fi wireframes, Hi-Fi prototypes, the steps of making a low-fidelity design in Figma, and how a Figma prototype uses a trigger and an action. Sketch a Lo-Fi school-portal login.
4. Differentiate testing from evaluation. Explain SUS, NPS, formative evaluation, summative evaluation and expert reviews. Then explain usability testing, task-based testing (including the three measurements), automated audits, A/B testing, compatibility testing, performance/load testing, and keyboard/screen-reader walkthroughs. Apply three of these methods to a college portal on result day.
5. A team is designing a JazzCash-style "Send Money" screen for elderly users in Sukkur who speak Sindhi, stand in bright sunlight, and have never used a CLI. Carry out a need analysis (five steps), list accessibility principles you will apply, choose interaction types, and say which evaluation and testing methods you will use before launch and why.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

1. **1.1 Fundamentals of Human Computer Interaction (HCI).** Answers: 1. CHI (Computer-Human Interface) and MMI (Man-Machine Interaction). 2. Spatial. 3. Touch / haptics.
2. **1.1.1 – 1.1.2 Traditional vs Natural Interaction.** Answers: 1. Traditional. 2. "Alexa, play a song" (or any spoken command). 3. Because typing a PIN is traditional, while FaceID or a voice assistant on the same phone is natural — it depends on the method, not the device.
3. **1.2 Applications of HCI (Domains of Life).** Answers: 1. Health care, banking, education, networking and communication. 2. Quick transactions and secure financial management. 3. Education: LMS or online exam portal. Networking: social media, WhatsApp or Zoom.
4. **1.3 Components of HCI.** Answers: 1. End users directly operate the system; stakeholders have an interest in the outcome (managers, clients) but may not click the buttons. 2. Task complexity, user knowledge, time requirement. 3. The principal, IT admin or board office — they care about results even if students are the end users.
5. **1.3 Types of User Interaction.** Answers: 1. Command-based. 2. Context-aware. 3. Because it combines two or more types (voice + touch) in one task.
6. **1.3 Interface Types, Environment & Feedback.** Answers: 1. GUI, CLI, Touch, VUI, NUI. 2. Physical: ATM in sunlight. Social: a quiet classroom. 3. System feedback.
7. **1.4 Importance of HCI.** Answers: 1. Unclear buttons on medical devices. 2. Promotes inclusivity. 3. User-friendly products get higher adoption, loyalty and profits.
8. **1.5 Accessibility Principles.** Answers: 1. Colour-blind users may not see the meaning if there is no symbol or "STOP" text. 2. Inclusive navigation. 3. Large Calibri on a school website for homework instructions.
9. **1.6 Need Analysis for Interface Design.** Answers: 1. Before designing the UI. 2. Identify users; collect information; analyse needs; prioritise; develop solutions. 3. Fingerprint/FaceID login; large buttons and simple navigation for elderly users; English plus local languages.
10. **1.7 Human Computer Interaction Problems.** Answers: 1. Trust deficiency. 2. High cognitive load — users must memorize too much. 3. Compatibility issues.
11. **1.8 Methods for Improving HCI.** Answers: 1. User-Centred Design; focus on real user goals and pilot-test. 2. Improve adaptability (responsive design). 3. A "Payment Successful" popup.
12. **1.9 User Interface Design (UI vs UX).** Answers: 1. Buttons, menus, icons, text fields, checkboxes/radio buttons, sliders. 2. The app loads fast, tracking works, food arrives without frustration. 3. how it feels.
13. **1.9.3 – 1.9.5 Wireframing, Figma, and Prototypes.** Answers: 1. Colours and detailed graphics (it is structure only). 2. Directly in a web browser. 3. The user event that starts a move between screens, e.g. "On Tap".
14. **1.11 Test and Evaluate HCI (Evaluation Methods).** Answers: 1. Testing finds bugs / checks the product works; evaluation checks it meets users' needs (usability). 2. 10. 3. At the end of development, against the original goals.
15. **1.11.2 Testing Methods (Usability, A/B, Automated).** Answers: 1. Completion time, success rate, number of errors. 2. Half of the users (the other half see B). 3. Any two of: broken links, slow loading, low colour contrast.

Answer key

Multiple choice

1. b
2. c
3. a
4. d
5. a
6. b
7. d
8. c
9. a
10. b
11. d
12. d
13. b
14. a
15. c

Short questions — model answers

1. HCI is the design of technology to serve people; systems that are easy to use, efficient and responsive. Also called CHI (Computer-Human Interface) and MMI (Man-Machine Interaction). Channels: sight, touch, hearing, voice, spatial.
2. Traditional uses standard I/O (mouse, keyboard, keypad, simple tap/swipe), e.g. an ATM keypad or typing on a school portal. Natural lets people interact without mouse or keyboard, using voice, face or gesture, e.g. FaceID or "Alexa, play a song".
3. Health care: patient portals / telemedicine — remote access to medical services. Banking: mobile banking and ATMs — quick, secure transactions. Education: LMS and exam portals — better teaching, learning and engagement. Networking: WhatsApp, Zoom, social media — global connection and collaboration.
4. User, computer system, user interaction, task. End users directly operate the system; stakeholders (managers, clients) have an interest in the outcome. Task characteristics: complexity, user knowledge, time requirement.
5. GUI: windows, icons, menus (Windows, Android). CLI: typed commands (MS-DOS, Linux). VUI: spoken commands (smart speakers). NUI: gestures, body, immersive VR/Kinect.
6. Enhance productivity; promote inclusivity; drive innovation (AR/VR, AI, IoT need solid HCI); economic impact (adoption, loyalty, profit); ethical responsibility (privacy, less bias, well-being).
7. High contrast (black text on white in a railway app); readable fonts (large Calibri on a school site); colour-blind friendly (STOP label, not colour alone); inclusive navigation (Tab key); multimodal detection (captions or vibration).
8. Need analysis finds the gap between the existing situation and the desired outcome, before UI design. Steps: identify users; collect information (interviews, questionnaires, observation); analyse needs; prioritise; develop solutions. Banking case: Fingerprint/FaceID login; large buttons and simple navigation for elderly users; English and local languages.
9. UI is the visual elements so people can interact easily; UX is the overall smoothness, comfort and satisfaction. Food app: UI = burger pictures and red buttons; UX = fast load, working tracking, food arrives without frustration. Components: buttons, menus, icons, text fields, checkboxes/radio buttons, sliders.
10. A/B testing shows version A to half the users and version B to the other half; the version with more clicks or sign-ups wins. An automated audit uses bots to scan for technical issues such as broken links, slow loading or low contrast; it does not split users between two designs.

Long questions — model answers

- 1. Components through an outdoor ATM.** User: end user = account holder; stakeholder = bank. Computer system: ATM hardware and bank software linking PIN input to cash output. Interaction: insert card, type PIN, choose Cash, confirm — intent becomes a response. Task: withdraw cash; low complexity, basic knowledge, about one minute (contrast with a long passport application). Interface: GUI on screen + keypad (traditional); possibly fingerprint (biometric). Environment: physical sunlight so contrast must be high; social queue so a privacy shield is needed; technical printer or network may fail. System feedback: "Please wait", cash, receipt/SMS. User feedback: pressing Confirm. If any part is weak (glare, no "cash coming" message), HCI fails even if the bank account is correct.
- 2. Problems and methods.** Interface complexity (buried checkout / hidden Send Money) → enhance usability (clear Buy Now / Send). Poor feedback (frozen Submit) → Payment Successful popup. Inconsistency (magnifying glass vs binoculars, or Send changing colour) → same Save/Send control everywhere. Accessibility gaps (no captions) → strengthen accessibility. Compatibility (laptop-only portal) → responsive/adaptability. Contextual neglect (map with no night mode; ATM unreadable in sun) → design for environment. High cognitive load (three SMS codes) → simplify steps. Trust deficiency (no HTTPS lock on JazzCash-style payment) → show security cues. Also apply UCD with a pilot test, multimodal input (voice + touch for elderly users), and continuous testing after launch.
- 3. UI, UX, wireframe, Figma, prototype.** UI design organises visual elements. Six components: buttons (Submit/Cancel), menus, icons, text fields, checkboxes/radio, sliders. UX = overall experience; UI is what you see, UX is how it feels; food-delivery pictures vs fast delivery. Lo-Fi: black-and-white boxes for structure; Hi-Fi: real colour, type, images, clickable controls for final tests. Figma: sign up in the browser; Frame tool for a phone canvas; rectangles and circles; text labels such as Sign Up; duplicate frames for the next screen. Prototype: before code, Prototype tab, Trigger = On Tap, Action = Navigate to Home. Sketch: header "LOGO / Portal", dashed Username and Password boxes, a LOGIN rectangle, "Forgot password?" — the Lo-Fi login in this chapter.
- 4. Test vs evaluate, then methods.** Testing finds bugs / whether it works; evaluation checks whether it meets user needs. SUS: 10-item usability score. NPS: "recommend to a friend?" (loyalty). Formative: during development. Summative: at the end vs original goals. Expert reviews: specialists vs heuristics. Usability testing: watch real users on realistic tasks. Task-based: time, success rate, errors (e.g. Add to cart in 12 s, success yes). Automated audit: bots find broken links, slow load, low contrast. A/B: half/half, more clicks win. Compatibility: Chrome/Safari, phone/tablet/PC, OS. Load: 10,000 logins at once. Keyboard/screen-reader: Tab/Enter and assistive tech. Result-day portal: load-test the 9:00 a.m. rush; usability-test "find chemistry marks"; automated audit for broken result links and grey-on-grey contrast; optional A/B of two home-screen layouts.
- 5. Send Money for elderly users in Sukkur.** Need analysis: (1) users = elderly Sindhi speakers, not teenagers; (2) collect: interviews and watch them at a JazzCash shop agent; (3) analyse: fear of wrong number, cannot read small English, glare on the phone; (4) prioritise: huge Sindhi "رقم بھیجیں", amount in words, confirm screen, high contrast; (5) solution: that UI, not a CLI. Accessibility: high contrast for sunlight, large simple fonts, not colour-only status, Tab/large targets, vibration + spoken confirm (multimodal). Interaction: menu-driven + form fill + biometric + haptic; optional voice. Evaluate formatively on paper then in Figma; expert review against heuristics; SUS and NPS before launch. Test: usability and task-based ("send Rs 100") measuring time/success/errors; A/B two button sizes; compatibility on cheap Androids; keyboard if a kiosk is used; do not skip a confirm screen — trust and feedback are the main risks.

Self-assessment: I can...

- ☐ define HCI, CHI and MMI and name the five sensory channels.
- ☐ describe HCI in health, banking, education and networking.
- ☐ name the types of user interaction and give an example of each.
- ☐ apply the five accessibility principles and carry out a need analysis.
- ☐ differentiate UI from UX and list six UI components.
- ☐ choose evaluation methods (SUS, NPS, formative, summative, expert).
- ☐ tell traditional interaction from natural interaction with local examples.
- ☐ label user, computer system, interaction, task, UI type, environment and feedback on an ATM, JazzCash or portal.
- ☐ explain why HCI is important using the five implications.
- ☐ name eight HCI problems and the methods that fix them.
- ☐ compare Lo-Fi, Hi-Fi, Figma steps and prototype triggers/actions.
- ☐ explain usability, task-based, automated, A/B, compatibility, load and keyboard tests.

Lecture 02

Computational Thinking & Algorithms

Chapter lecture — 16 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XII · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — بارہویں جماعت

16 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XII

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیئریر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

Lectures in this pack

Chapter 2: Computational Thinking & Algorithms. Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 2.1 Analyze algorithms for correctness

L03. 2.2 Evaluating the Clarity of an Algorithm

L05. 2.3 Assess Algorithm Efficiency

L07. 2.3.2 Number of Conditions

L09. 2.3.4 The Efficiency Evaluation Framework

L11. 2.5 Concept of Data Structure

L13. 2.5.2 Non-Linear Data Structures (Tree, Graph)

L15. 2.6 Identify data structures in problem scenarios

L02. 2.1.1 – 2.1.3 Trace Tables vs Stepwise Reasoning

L04. 2.2.1 – 2.2.2 Modularity and Readability

L06. 2.3.1 Number of Steps (Big O Notation)

L08. 2.3.3 Number of Repetitions

L10. 2.4 Refinements to improve clarity and efficiency

L12. 2.5.1 Linear Data Structures (Array, Linked List, Stack, Queue)

L14. 2.5.3 Operations on Data Structures

L16. 2.7 Trace data retrieval in Array, List and Queue

Computational Thinking & Algorithms

Class XI taught you how to write algorithms. This chapter teaches you how to **judge** them: is the algorithm correct, clear and efficient? You will then learn the main **data structures** — array, linked list, stack, queue, tree and graph — so you can store data the smart way and trace how it is retrieved.

گیارہویں جماعت میں آپ نے الگورتھم لکھنا سیکھا۔ اس باب میں آپ سیکھیں گے کہ الگورتھم درست، واضح اور تیز ہے یا نہیں، اور ایرے، لنکڈ لسٹ، سٹیک، کیو، ٹری اور گراف جیسے ڈیٹا سٹرکچرز میں ڈیٹا کیسے رکھا اور نکالا جاتا ہے۔

What you will learn

- Define **correctness** and prove it with a complete **trace table**.
- Evaluate **clarity** using modularity (SRP, coupling, abstraction) and readability (names, flow, consistency).
- Explain how the number of **conditions** and **repetitions** changes efficiency, and apply the three-question efficiency framework.
- Define a **data structure** and classify it as linear or non-linear.
- Draw a tree and a graph, and name the five operations on data structures.
- Apply **stepwise reasoning** and compare it with a trace table on at least four points.
- Define **efficiency** in time and space, and state Big O for $O(1)$, $O(\log n)$, $O(n)$, $O(n \log n)$ and $O(n^2)$ with examples.
- Refine an algorithm for clearer names, modules, comments and fewer wasted steps.
- Draw and trace an array, linked list, stack (PUSH/POP) and queue (ENQUEUE/DEQUEUE).
- Choose a data structure for a real scenario and trace retrieval in an array, a linked list and a queue.

2.1 Analyze algorithms for correctness

LEARN IT

An algorithm is **correct** if its **output matches the expected results** for a given input. Analysing correctness means showing that the algorithm produces the intended output for **all valid inputs**, not just one lucky example. Two methods are used in this course:

Trace tables → paper execution, line by line → Stepwise reasoning → logic blocks, overall state

You already met the idea of a dry run in Class XI. Here you learn to do it formally, and to choose the method that fits the size of the algorithm.

WORKED EXAMPLE

Worked example: what "correct" means. An algorithm is supposed to count how many of the heights 1.91, 2.01, 1.87, 1.57, 1.48 lie between 1.57 m and 1.91 m inclusive.

Expected output: 3 (1.91, 1.87 and 1.57 qualify; 2.01 is too tall; 1.48 is too short).

If a program prints 4, it **runs** but it is **not correct**. Correctness is about the right answer, not about "no crash".

REMEMBER IT

Remember: **runs ≠ correct**. A logical error still produces output — just the wrong output. That is why we analyse correctness on paper before we trust the code.

COMMON MISTAKE

Mistake: testing only one "normal" input and calling the algorithm correct.

Fix: also try edge cases (empty list, $N = 0$, the exact boundary values 1.57 and 1.91). The definition says **all valid inputs**.

اردو میں سمجھیں

الگورتھم تب درست (Correct) سمجھا جاتا ہے جب دیے گئے ان پٹ پر اس کا آؤٹ پٹ وہی ہو جو ہونا چاہیے۔ صرف چل جانا کافی نہیں؛ منطقی غلطی سے غلط جواب بھی نکل سکتا ہے۔ درستگی جانچنے کے دو طریقے ہیں: ٹریس ٹیبل (Trace Table) اور مرحلہ وار استدلال (Stepwise Reasoning)۔

CHECK YOURSELF

1. When is an algorithm considered correct?
2. Name the two methods used to analyse correctness in this chapter.
3. Why is "the program ran without an error" not enough?

Answers: 1. When its output matches the expected results for a given input (and does so for all valid inputs). 2. Trace tables and stepwise reasoning. 3. Because a logical error can still produce output — the wrong output.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An algorithm is correct if:

- a. Outputs match the spec for the intended inputs (incl. edges)
- b. It is short
- c. It uses XOR
- d. It prints Hello

MCQ 2. A failed edge case means:

- a. Not fully correct
- b. Still correct enough always
- c. Faster Big O
- d. Better UX

MCQ 3. You demonstrate correctness in this chapter with:

- a. Trace tables / stepwise reasoning / tests
- b. Only careers
- c. Only Figma
- d. Only pie charts

MCQ 4. A spec is:

- a. The expected behaviour
- b. The CPU model
- c. The font
- d. The sprint name

MCQ 5. Partial correctness often means:

- a. If it halts, the answer is right — you still need termination
- b. It never needs to halt
- c. It is Agile
- d. It is a GUI

MCQ 6. Off-by-one in a loop is a:

- a. Correctness bug
- b. OSI issue
- c. NAND issue
- d. Career issue

Extra short questions

1. Define correctness.
2. Two ways it can fail.
3. Why test edges.
4. Link to later trace tables.

Extra long question

1. Give a "find maximum" algorithm, two traces (normal and $n=1$), and an incorrect version that fails on negatives. Explain.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. For every specified input, the algorithm produces the specified output and finishes.
2. Wrong answer; infinite loop (does not finish).
3. Empty, one element, already sorted, not found, max int.
4. A dry run is a manual proof for a small case.

Long

1. Init max to first element not 0. Trace [3,-1,5] and [-4]. Bug: init 0 fails all-negative lists. That is correctness, not Big O.

2.2 Evaluating the Clarity of an Algorithm

LEARN IT

Clarity means an algorithm is easy to **read, understand and modify**. In many cases, evaluating clarity is even more important than making the algorithm slightly faster. A clear algorithm is easier to **maintain, debug and extend** over time.

The two key aspects of clarity are:

Clarity → Modularity (parts) → Readability (text and flow)

WORKED EXAMPLE

Worked example: speed versus clarity. Algorithm A finds the class average in 8 confusing lines with variables a , b , c . Algorithm B uses two named functions and takes the same number of additions. Both are $O(n)$. Algorithm B is the better school solution because the next person (or you, in three months) can change it without breaking it.

REMEMBER IT

Ask two questions: “Can I split this into parts?” (modularity) and “Can another student read it aloud and understand it?” (readability).

COMMON MISTAKE

Mistake: treating a clever one-line trick as “better” than a clear five-line solution.

Fix: the source says clarity is often more important than speed. Board answers should praise meaningful names and modules, not compacted code.

اردو میں سمجھیں

وضاحت (Clarity) کا مطلب ہے الگورتھم پڑھنا، سمجھنا اور بدلنا آسان ہو۔ بہت سی صورتوں میں وضاحت رفتار سے بھی اہم ہے۔ اس کے دو حصے ہیں: ماڈیولریتی (Modularity) یعنی کام کو حصوں میں بانٹنا، اور پڑھائی پن (Readability) یعنی متن اور بہاؤ صاف ہونا۔

CHECK YOURSELF

1. What does clarity mean?
2. Name the two key aspects of clarity.
3. Why can clarity matter more than a small speed gain?

Answers: 1. The algorithm is easy to read, understand and modify. 2. Modularity and readability. 3. Because a clear algorithm is easier to maintain, debug and extend over time.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Clarity means the algorithm is:

- a. Easy to read, understand, change
- b. As short as possible even if cryptic
- c. Written in one letter variables only
- d. Uncommented hex

MCQ 2. Modularity helps clarity because:

- a. Named pieces have one job
- b. Everything is in main
- c. There are no names
- d. Gotos everywhere

MCQ 3. Readability includes:

- a. Names, structure, comments, consistent style
- b. Removing all spaces
- c. 1-letter names always
- d. No line breaks

MCQ 4. A 200-line monoblock is:

- a. Low modularity
- b. High modularity
- c. A primary key
- d. A pie

MCQ 5. Clarity can matter more than a tiny speed gain when:

- a. Humans must maintain the code
- b. $n=10^{12}$ always
- c. It is a one-off NAND
- d. It is OSI layer 1

MCQ 6. Poor names are a:

- a. Readability problem
- b. TCP problem
- c. Power problem
- d. RAM manufacturing problem

Extra short questions

1. Define clarity of an algorithm.
2. Two ways to improve it.
3. Can a correct algorithm be unclear?
4. Link to functions in Ch 3.

Extra long question

1. Rewrite a messy “average of array” monoblock as three modules (input, compute, output). Explain the clarity gain.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. A person can see the purpose and logic without running it.
2. Decompose into modules; meaningful names; comments on why; consistent structure.
3. Yes — and then it will be modified wrongly.
4. Functions are modularity in Python.

Long

1. Show before/after pseudocode. Each module tested. Names: `sum_list`, `mean`. Comments why $n=0$ is rejected.

2.2.1–2.2.2 Modularity and Readability

LEARN IT

Modularity means breaking an algorithm into smaller, independent parts such as **functions, classes or modules**. This makes the algorithm more organised and easier to work with.

How to evaluate modularity

1. **Single Responsibility Principle (SRP)**. Each module should focus on **one** specific task. If a function calculates a sum, prints a report and saves a file, it violates SRP.
2. **Coupling**. Modules should be reusable in different contexts. Good modularity means **loose coupling**: a change in one part does not smash the others. Tight coupling is when two functions share so many hidden details that you cannot reuse one without the other.
3. **Abstraction**. A well-designed algorithm hides complex implementation details. You can call a sorting function without knowing whether it uses Bubble Sort or Selection Sort inside.

WORKED EXAMPLE

Worked example: average of an array.

Poor modularity (monoblock)

All logic sits in one block, so you cannot reuse the sum.

```
Step 1: Start
Step 2: Set A = [1, 2, 3, 4, 5]
Step 3: Set n = 5
Step 4: Set total = 0
Step 5: Set avg = 0
Step 6: For i = 1 to n
Step 7: total = total + A[i]
Step 8: End For
Step 9: avg = total / n
Step 10: Print avg
Step 11: End
```

Good modularity (Functions)

Two clear functions: `CalculateSum()` and `FindAverage()`.

```
Step 1: Start
Step 2: Set A = [1, 2, 3, 4, 5]
Step 3: Set n = 5
Step 4: Print FindAverage(A, n)
Step 5: End
Function FindAverage(A, n)
Sum = CalculateSum(A, n)
Avg = Sum / n
Return Avg
End Function
Function CalculateSum(A, n)
Set Total = 0
For i = 1 to n
Total = Total + A[i]
End For
Return Total
End Function
```

SRP check: `CalculateSum` only adds; `FindAverage` only divides. Loose coupling: you can reuse `CalculateSum` to find a total without computing an average. Abstraction: the main algorithm just calls `FindAverage` and does not see the loop.

The source pseudocode numbers array positions from 1. Python numbers them from 0, so the loop is `For i in range(n)`.

```
def find_average(A, n):
    total = 0
    for i in range(1, n+1):
        total = total + A[i]
    return total

def find_average(A, n):
    return calculate_sum(A, n) / n

A = [1, 2, 3, 4, 5]
n = 5
print(find_average(A, n))

# output
2.0
```

REMEMBER IT

SRP is one line: **one function, one job**. If you cannot name the function with a short verb-phrase (`CalculateSum`, `FindAverage`), it is doing too much.

COMMON MISTAKE

Mistake: copying the 1-based loop `for i = 1 to n: total = total + A[i]` into Python. Then `A[i]` skips the first item and `A[5]` crashes.

Fix: In Python use `for i in range(n)` so the indices are 0, 1, 2, 3, 4.

آردن میں سمجھیں

ماتریکس کا مطلب اگر تم کو آئے جنوں (فکشن کتاب، مائیکل مین ہولڈ) میں ہوتا ہے، جانچ کر کہ اس میں اصل واقعہ اور دیکھو (SRP) یہی ایک فکشن ایک کام دیکھو جوت (Loose Coupling) ایک کام دیکھو یہی ہے۔ دوسرے د لوگوں اور اجرو (Abstraction) یہی انداز میں تبدیل دیکھو کہ صرف کام دیکھو۔ جیسے سورت نکلتی ہائی بھرے۔ جانچ کر کہ یہ یا سیکشن۔

CHECK YOURSELF

1. What does SRP say each module should do?
2. Is the good average algorithm, which function hides the loop?
3. Why is the monoblock harder to reuse?

Answers: 1. One specific task. 2. `CalculateSum`. `FindAverage` only divides; the main program only prints it. 3. All logic sits in one block, so you cannot call "just the sum" from another algorithm.

LEARN IT

Readability is how easily another person can understand the purpose and logic of an algorithm **without running it**. It is about how clear the text and the flow are.

How to evaluate readability

1. **Naming conventions** — consistent rules for names. Good names make an algorithm easier to search and understand.

Bad: `v = d / t`
Good: `velocity = distance / time`

2. **Self-documentation** — the algorithm explains itself, so you need fewer comments. Meaningful names and clean formatting make the purpose obvious.

3. **Control-flow simplicity** — keep the logic straightforward. Avoid deep nesting (if inside if inside if), limit extra conditions, and keep each function on one task.

4. **Consistency** — one style throughout: indentation, spacing, and casing (camelCase or snake_case). Then the logic stands out instead of the mess.

Names → Self-doc → Simple flow → Consistent

WORKED EXAMPLE

Worked example: the same formula, two styles.

```
# Read it: need
v = 50
t = 4
n = 20
v = v * t
if v > 10:
    print(v)

# output
20.0
```

```
# Readable
distance = 100
time = 4
velocity = distance / time
speed_limit = 20
if time > 0 and velocity > speed_limit:
    print(velocity)

# output
25.0
```

The second version uses names, avoids an if nested inside an if, and keeps one consistent snake_case style. You can understand it without running it. Both print 25.0, but only the second is clear.

REMEMBER IT

Remember readability as **N-S-D-C**: Names, Self-documentation, Simple flow, Consistency.

COMMON MISTAKE

Mistake: dumping a comment on every line (`total = total + 1 # add one to total`).

Fix: If the name already says it, skip the comment. Comments should explain **why**, not repeat **what**.

آردن میں سمجھیں

پڑھائی پر یہ کہ دوسرا شخص اگر تم کو پڑھائی دیکھو کہ اس کا مشق سمجھ کر آجائی نام (velocity = distance / time) خود بیان (کہ تجربہ) سادہ کنٹرول فلو (گری کی پڑھائی اور ایک جیسا انداز (consistent اور casing) اسے آسان دیکھیں۔

CHECK YOURSELF

1. Rewrite `v = d / t` with readable names.
2. What is deep nesting, and why is it a readability problem?
3. Name two style habits that support consistency.

Answers: 1. `velocity = distance / time`. 2. If inside if inside if (or similar); it makes the flow hard to follow. 3. Any two of: consistent indentation, spacing, and casing (camelCase or snake_case).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Modularity is:

- a. Splitting into independent places with clear interfaces
- b. One file of 2000 mixed lines
- c. Random copy-paste
- d. A chart type

MCQ 2. A module should have:

- a. One job
- b. Every job
- c. No name
- d. No inputs

MCQ 3. Readability is:

- a. How easily another person understands the algorithm
- b. Font size of the PDF only
- c. RAM size
- d. Cable length

MCQ 4. Reusing a module is easier if:

- a. It does not depend on hidden globals
- b. It prints inside and uses global n
- c. It is unnamed
- d. It mixes I/O and maths

MCQ 5. Comments should explain:

- a. Why, not every obvious `in=1`
- b. Nothing
- c. Only your WhatsApp
- d. Only Big O symbols

MCQ 6. Poor readability increases:

- a. Bugs when changing code
- b. CPU time
- c. OS layers
- d. Pie slices

Extra short questions

1. Define modularity and readability.
2. One benefit of each.
3. A readable name vs a bad one.
4. How they interact.

Extra long question

1. Take a messy attendance script (global, 1-letter names). Produce a modular readable version and a 5-point rubric a teacher could mark.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Modularity: parts. Readability: understandable text/structure.
2. Modularity: testhouse. Readability: fewer maintenance bugs.
3. total_marks vs x1.
4. Small named modules are easier to read.

Long

1. Modules: load, mark, save, report. Rubric: names, functions, no magic numbers, comments why, handles empty file.

2.3 Assess Algorithm Efficiency ★ Golden

LEARN IT

Algorithm efficiency is measured in terms of **time** and **space** — how fast it runs and how much memory it uses.

The key considerations for assessing efficiency are:

1. **Number of steps** (described with **Big O notation**).
2. **Number of conditions** (IF decisions).
3. **Number of repetitions** (loops).

Time (speed) + Space (memory) → Efficiency

WORKED EXAMPLE

Worked example: two ways to find a name in 1,000,000 sorted records.

Linear search checks about 1,000,000 names in the worst case (time grows with n). Binary search checks about 20 names (it halves the list each time). Both can be correct and clear. They are not equally efficient.

REMEMBER IT

Efficiency is always “as the input grows”. An algorithm that feels instant on 10 items can freeze on 10 million items if it is $O(n^2)$.

COMMON MISTAKE

Mistake: judging efficiency by how short the code looks.

Fix: a five-line nested loop can do n^2 work. Count steps, conditions and repetitions — not lines of text.

اردو میں سمجھیں

کارکردگی (Efficiency) وقت (رفتار) اور جگہ (میموری) سے ناپی جاتی ہے۔ تین چیزیں دیکھی جاتی ہیں: قدموں کی تعداد (پگ او)، شرطوں کی تعداد، اور دہرائی (لوپ) کی تعداد۔ چھوٹے ان پٹ پر تیز لگنے والا الگورتھم بڑے ان پٹ پر سست پڑ سکتا ہے۔

CHECK YOURSELF

1. Efficiency is measured in terms of which two resources?
2. List the three key considerations named in the source.

Answers: 1. Time (speed) and space (memory). 2. Number of steps (Big O), number of conditions, number of repetitions.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Efficiency is mainly:

- a. Time and extra memory vs n
- b. How pretty the UI is
- c. How many comments
- d. Font choice

MCQ 2. As n grows, we care about:

- a. Growth class (Big O), not a 2 ms blip
- b. Only the constant 2 ms
- c. Only variable names
- d. Only colours

MCQ 3. Space efficiency is:

- a. Extra RAM/disk beyond the input
- b. Screen size
- c. PDF margins
- d. Cable thickness

MCQ 4. An algorithm can be:

- a. Correct but inefficient
- b. Efficient but never correct and still useful always
- c. A pie
- d. A sprint

MCQ 5. This chapter's framework later uses:

- a. Steps, conditions, repetitions
- b. Only UX
- c. Only ER
- d. Only Figma

MCQ 6. Why efficiency is ★:

- a. Board likes compare-two-algorithms questions
- b. It replaces correctness
- c. It replaces HCI
- d. It replaces Python

Extra short questions

1. Define time and space efficiency.
2. Why not measure only one run on your PC?
3. Example of wasting space.
4. Example of wasting time.

Extra long question

1. Compare linear vs binary search on $n=2$, $n=1\,000\,000$ for time and space. State preconditions. 10-mark table.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Time: how running time grows with input. Space: extra memory.
2. Machines differ; we need growth vs n .
3. Copying a huge list on every recursive call.
4. Linear search 1 million times on a static sorted list instead of binary/index.

Long

1. Time $\sim n$ vs $\sim \log n$. Space $O(1)$ both (iterative). Binary needs sorted. For $n=1e6$, $\sim 1e6$ vs ~ 20 comparisons. Correctness not sacrificed.

2.3.1 Number of Steps (Big O Notation) 🔗

LEARN IT

When we discuss efficiency we ask how performance changes as the **input size** n increases. **Big O notation** is a mathematical method used to describe how the running time (or memory) **grows** as n grows. We ignore small constants and keep the most important term. If an algorithm does $5n + 5$ steps we write $O(n)$. In computer science, **log** n almost always means **log base 2** (how many times you can halve n until you reach 1).

Five common classes

Class	Name	What happens when n grows	Typical example	Grade
$O(1)$	Constant	Time stays the same for 10 items or 10 million.	Access <code>arr[5]</code> (or any known index).	Excellent
$O(\log n)$	Logarithmic	Time grows very slowly; the problem is halved each step.	Binary search on a sorted list.	Great
$O(n)$	Linear	If n doubles, time roughly doubles.	Linear search of an unsorted list.	Fair / Good
$O(n \log n)$	Linearithmic	A little worse than linear; much better than n^2 . Common in good sorting.	Merge Sort (split in half, then merge).	Good
$O(n^2)$	Quadratic	Time grows with the square of n . Nested loops. Painful for large n .	Bubble Sort; compare every item with every other item.	Poor


The source stresses $O(1)$, $O(\log n)$, $O(n)$ and $O(n \log n)$ is the class of efficient general-purpose sorts, so you should recognise it when a question says "better than Bubble Sort but more than linear".

Growth table (log is $\log_2$)

Each cell is the approximate number of operations for that n . Read down a column to see how fast that class explodes.

n	$O(1)$	$O(\log n)$	$O(n)$	$O(n \log n)$	$O(n^2)$
2	1	1	2	2	4
4	1	2	4	8	16
8	1	3	8	24	64
16	1	4	16	64	256
32	1	5	32	160	1,024
1,024	1	10	1,024	10,240	1,048,576
1,000,000	1	~20	1,000,000	~20,000,000	1,000,000,000,000

From $n = 8$ to $n = 1,000,000$, $O(1)$ does not move, $O(\log n)$ only goes from 3 to about 20, $O(n)$ becomes a million, and $O(n^2)$ becomes a million million — which is why nested loops "fail for large datasets".



Same $n = 16$. Quadratic work is already four times $n \log n$ and sixteen times linear.

WORKED EXAMPLE

Worked example A — $O(1)$ first element of an array. Whether the array holds 10 or 10 million values, `arr[5]` is one jump to a known address.

```
arr = [21, 76, 12, 99, 24, 48]
print(arr[5])
```

array
21

Worked example B — $O(n)$ linear search. Each extra item adds one extra check.

```
def linear_search(items, key):
    for i, value in enumerate(items):
        if value == key:
            return i
    return -1

print(linear_search([11, 20, 28, 76, 96, 101, 201])
print(linear_search([19, 29, 28, 76, 96, 201, 99])
```

array
-1

Worked example C — $O(\log n)$ binary search on a sorted list. Each step throws away half of the remaining items. For 8 sorted numbers the worst case is about 4 comparisons (from $\log_2 8 = 3$).

```
def binary_search(arr, key):
    low = 0
    high = len(arr) - 1
    while low < high:
        mid = (low + high) // 2
        if arr[mid] == key:
            return mid
        elif arr[mid] < key:
            low = mid + 1
        else:
            high = mid - 1
    return -1, steps

data = [1, 6, 12, 17, 22, 25, 48, 51]
print(binary_search(data, 48))
print(binary_search(data, 33))
```

array
(4, 3)

array
(-1, 3)

Key 48 is found at index 6 after 3 comparisons. Key 3 is found at index 0 after 3 comparisons. Never more than a handful of steps, even if the list later grows to a million (about 20 steps).

Worked example D — $O(n \log n)$ Merge Sort idea. To sort 8 items, Merge Sort makes $\log_2 8 = 3$ split-levels, and each level walks all 8 items once, so work = $8 \times 3 = 24$, which matches the growth table. Bubble Sort on 8 items is on the order of $8^2 = 64$ comparisons. That gap becomes enormous at $n = 1,000,000$.

Worked example E — $O(n^2)$ nested loops.

```
n = 6
count = 0
for i in range(n):
    for j in range(n):
        count += 1
print(count)
```

count
36

Inner body runs $n \times n = 36$ times. That is the pattern of Bubble Sort and of "compare every item with every other item".

REMEMBER IT

Order from fastest to slowest (for large n): $O(1) < O(\log n) < O(n) < O(n \log n) < O(n^2)$

Mnemonic: "Constant Logs Never Need Squares" — Constant, Logarithmic, N , $N \log N$, Squares.

COMMON MISTAKE

Mistake 1: writing $O(n)$ for binary search because "there is a loop". The loop runs about $\log n$ times, not n times.

Mistake 2: writing $O(n)$ or $O(n \log n)$. Big O drops constants both are $O(n)$.

Mistake 3: using binary search on an unsorted list. Binary search is $O(\log n)$ only on sorted data.

آردو میں سمجھیں

گت او (Big O) بتاتا ہے کہ ان قیمت ۵ پر وقت یا کمپیوٹر کیسے بڑھیں گی۔ $O(1)$ مستقل (ایر-ٹو) کا $O(\log n)$ پر قدم پر آگے (ڈائری سرچ) $O(n)$ کیوری (الینار سرچ) $O(n \log n)$ ایس مارکٹ جیسے سرچ مارکٹ اور $O(n^2)$ سبب (پیل مارکٹ اندرونی فورم) بڑھ ۵ پر $O(n^2)$ (تفاتی استعمال ہو جا تا ہے۔

EXAM TIP

Memorise the five rows of the class table (name, growth, one example, grade). Typical MCQ "Accessing `arr[0]` is ...?" → $O(1)$ "Binary search is ...?" → $O(\log n)$ "Nested loops / Bubble Sort ...?" → $O(n^2)$ Long questions ask you to fill or interpret a growth table, or to say what happens if n becomes 10 times larger (linear = 10x time; quadratic = 100x time). Always mention that $\log n$ is "halving" and n^2 is "nested loops".

CHECK YOURSELF

1. Give one example each of $O(1)$, $O(\log n)$, $O(n)$ and $O(n^2)$

2. From the growth table, how many operations does $O(n^2)$ need when $n = 32$?

3. Why is Merge Sort described as $O(n \log n)$?

Answers: 1. $O(1)$ → `arr[0]`, `len(arr)`; $O(\log n)$ → binary search; $O(n)$ → linear search; $O(n^2)$ → Bubble Sort / nested loops. 2. 1,024. 3. It makes about $\log n$ split-levels and does about n work on each level, so $n \times \log n$.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. $O(n)$ means: a. Constant time, independent of n b. Linear in n c. Quadratic d. Factorial	MCQ 2. $O(n)$ example: a. Linear search b. Binary search c. Needs $n \times n$ always d. Even $O(1)$ need always guaranteed	MCQ 3. $O(n \log n)$ example: a. Binary search b. Bubble sort c. Reading all n items once d. Nested loops n^2	MCQ 4. $O(n^2)$ example: a. Bubble / selection sort b. Binary search c. Closed formula sum d. Array index	MCQ 5. We drop constants and small terms because: a. Growth class dominates for large n b. They are always 0 c. Big O is UK d. Bounds forbid numbers	MCQ 6. $\log n$ grows: a. Slowly b. Faster than n^2 c. Faster than n d. As a straight 45° line always
--	---	---	---	---	--

Extra short questions

- Define Big O in one student sentence.
- Order these from fast to slow: n^2 , $\log n$, n .
- Why is $3n+5$ still $O(n)$?
- What does $O(n \log n)$ look like on a phone contacts list?

Extra long question

1. For each array index, binary search, linear search, bubble sort — state Big O and a 1-line why. Then pick one for $n=50$ vs $n=5$ million. ★ Golden.

Extra answer key

MCQs: 1. A, 2. A, 3. A, 4. A, 5. A, 6. A

Short

- No upper-class or how time (or space) grows as n gets large.
- $O(1)$, $O(\log n)$, $O(n)$, $O(n \log n)$, $O(n^2)$
- Constants ignored; linear term dominates.
- Each step halves the remaining names.

Long

- $O(1)$, $O(\log n)$, $O(n)$, $O(n \log n)$ → avoid anything fine; $n=50$ avoid n^2 ; prefer $\log$ /linear as appropriate. Mention sort cost if you need binary.

2.3.2 Number of Conditions

LEARN IT

Conditions (IF statements) are decision points. Every condition forces the CPU to evaluate True or False, so excessive branching reduces performance.

- **Computational cost.** Each IF is extra work, even if the rest of the algorithm is simple.
- **Nested conditions.** IF inside IF often means a brute-force approach. It hurts both readability and speed.
- **Short-circuiting** (the optimisation goal). Stop evaluating as soon as the result is known. In a logical AND, if the first part is False the second part is skipped. In a logical OR, if the first part is True the second part is skipped.

WORKED EXAMPLE

Worked example: cheap test first. You only divide if the denominator is not zero. Place the cheap, safe test on the left so Python never evaluates the dangerous part.

```
x = 0
y = 10
if x != 0 and (y / x) > 2:
    print("ratio is 'large'")
else:
    print("skipped safely")
```

OUTPUT
skipped safely

$x \neq 0$ is False, so AND short-circuits and y / x is never attempted. If you wrote the division first, the program would crash. Same idea in the soldier algorithm: a False height test skips Step 6.

REMEMBER IT

Put the **cheapest / most likely False** test first in an AND, and the **most likely True** test first in an OR. That is short-circuiting used on purpose.

COMMON MISTAKE

Mistake: writing a chain of nested IFs when one compound condition would do (as in the velocity example in 2.2.2).

Fix: flatten with AND/OR, and rely on short-circuiting instead of extra layers.

آردو میں سمجھیں

IF پر پروسیسر سے True/False پوچھتی ہے اس لیے زیادہ شاخیں کارکردگی گھٹاتی ہیں۔ اندرونی IF اکثر brute-force ہوتی ہے۔ ہارٹ سرکٹ (Short-circuit) کا مطلب ہے جیسے ہی جواب معلوم ہو جانچ روک دی جائے، مثلاً AND میں پہلی شرط False ہو تو دوسری نہ چلے۔

CHECK YOURSELF

1. Why do extra IF statements reduce performance?

2. What does nested IF often indicate?

3. In $x \neq 0$ and $(y / x) > 2$ with $x = 0$, why is there no division-by-zero?

Answers: 1. Each condition must be evaluated True/False by the CPU. 2. A brute-force approach (and it reduces readability and speed). 3. AND short-circuits: the first part is False, so the division is never evaluated.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Number of conditions affects:

a. How many decisions (and often branches) you pay for

b. Only the font

c. Only RAM manufacturing

d. Only UX colour

MCQ 2. A nested if inside a loop can make work:

a. Depend on data (sometimes skip inner work)

b. Always n^2

c. Always $O(1)$

d. Always crash

MCQ 3. Short-circuit and/or can:

a. Skip later tests

b. Sort the array

c. Open a file

d. Draw a pie

MCQ 4. Too many rare special cases:

a. Hurt clarity and can hurt time if mis-ordered

b. Always reduce Big O class

c. Always increase RAM

d. Always fix UX

MCQ 5. Binary search's conditions:

a. Few, but they cut n in half — very efficient

b. n^2

c. Are UX heuristics

d. Are SQL joins

MCQ 6. Counting conditions is part of the:

a. Efficiency evaluation framework

b. HCI Nielsen list only

c. ER cardinality only

d. MVP canvas only

Extra short questions

1. What is a "condition" in this chapter's sense?

2. How can conditions save time?

3. How can they waste time?

4. Link to readability.

Extra long question

1. Two versions of search: (A) no break (B) break when found. Compare conditions, time, traces on a hit at position 2 of 10.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. A true/false test the algorithm performs (if, loop test, while).

2. Early exit: if found, break; if $x < 0$, skip expensive work.

3. Re-testing the same expensive predicate; poorly ordered or/and.

4. A tower of nested ifs is slow to understand even if $O(n)$.

Long

1. A always 10 tests. B 2 tests. Same Big O class worst-case still $O(n)$, but average better. Show trace tables.

10

2.3.3 Number of Repetitions

LEARN IT

Repetitions (loops) are the most significant factor in algorithm efficiency. The **structure of the loop** decides how time grows with n .

Type of repetition	Conceptual impact	Efficiency grade
Linear loop	Processes each element exactly once. Time grows in proportion to size.	Good — $O(n)$
Logarithmic repetition	Reduces the problem size by half each iteration (binary search). Huge time savings.	Excellent — $O(\log n)$
Nested loops	For each element, process all other elements. Operations explode.	Poor — $O(n^2)$

WORKED EXAMPLE

Worked example: count the inner-body runs.

```
n = 5
linear = 0
for i in range(n):
    linear = linear + 1

nested = 0
for i in range(n):
    for j in range(n):
        nested = nested + 1

print(linear, nested)
```

```
OUTPUT
5 25
```

One loop: 5. Nested loops: 25 = 5^2 . For $n = 1,000$ that would be 1,000 versus 1,000,000.

REMEMBER IT

Find the **deepest loop**. One loop $\approx O(n)$. Loop inside a loop $\approx O(n^2)$. A loop that halves $n \approx O(\log n)$.

COMMON MISTAKE

Mistake: counting the word `for` and ignoring how the index moves.

Fix: a loop `while n > 1: n = n // 2` is logarithmic, even though it is still "a loop".

اردو میں سمجھیں

دہرائی (لوپ) کارکردگی کا سب سے بڑا عامل ہے۔ ایک بار پر عنصر پر چلنے والا لوپ $O(n)$ (اچھا)، ہر بار مسئلہ آدھا کرنے والا $O(\log n)$ (بہترین)، اور اندرونی لوپ $O(n^2)$ (خراب) ہے۔ اندرونی جسم کے چلنے کی گنتی سے یہ فرق صاف نظر آتا ہے۔

CHECK YOURSELF

- What grade does the source give nested loops?
- Why is binary search's loop logarithmic rather than linear?
- If $n = 5$, how many times does a fully nested n -by- n pair of loops run?

Answers: 1. Poor — $O(n^2)$. 2. Each iteration halves the remaining problem, so the number of iterations is about $\log n$. 3. 25.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. for i in range(3) runs:

- i=0,1,2
- i=1,2,3
- i=3,2,1
- forever

MCQ 2. while repeats while the condition is:

- True
- False
- A file
- None always

MCQ 3. break:

- Exits the loop immediately
- Skips one line only
- Closes Python
- Commits SQL

MCQ 4. continue:

- Skips the rest of this iteration
- Ends the program
- Defines a function
- Opens a file

MCQ 5. A nested loop: inner runs:

- Fully for each outer step
- Once in total
- Never
- Only if NAND

MCQ 6. range(2, 6) yields:

- 2,3,4,5
- 2,3,4,5,6
- 1,2,3,4,5,6
- 6,5,4

Extra short questions

- When for vs while?
- What is an infinite loop?
- Trace `s=0; for i in range(1,4): s+=i`.
- Shopping bill uses which loop typically?

Extra long question

- Write nested loops to print a 3×3 table of i,j . Then rewrite the shopping-bill outline with a while, a running total, and an if on quantity.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- for: known count / iterate a sequence. while: unknown count, stop on a condition.
- while True without break, or a condition that never becomes False.
- `i=1 s=1; i=2 s=3; i=3 s=6`.
- while more items (unknown count) or for a known list of items.

Long

- for i in range(3): for j in range(3): print(i,j). Bill: total=0; while True: read item/qty; if qty<=0: continue; if item=="end": break; total+=...; print total.

2.3.4 The Efficiency Evaluation Framework

LEARN IT

To evaluate an algorithm at a conceptual level, ask three questions:

- Does it scale?** If n grows 10 times, does time jump 10 times (linear) or 100 times (quadratic)? Quadratic scaling fails for large datasets.
- What is the bottleneck?** Focus on the most time-consuming section (usually the deepest loop) and try to improve that part.
- Is the cost worth it?** A theoretically faster $O(\log n)$ algorithm can be too complex to code and maintain. For a list of just 50 items, a simple $O(n)$ linear search is practically better because it is simple.

Does it scale?

→

Where is the bottleneck?

→

Is the extra complexity worth it?

WORKED EXAMPLE

Worked example: 50 names versus 1 million names.

Situation	Scale	Bottleneck	Worth the cost?	Choice
50 unsorted class names	Tiny n	A single linear scan	Binary search needs a sort first, which is extra work and extra code	Linear search $O(n)$
1,000,000 sorted account numbers, searched all day	$n \times 10$ compared with 100,000 is already huge; quadratic would be impossible	The search loop	Yes — binary search is standard and well understood	Binary search $O(\log n)$

REMEMBER IT

Framework mnemonic: **S-B-W** — Scale, Bottleneck, Worth it.

COMMON MISTAKE

Mistake: always choosing the theoretically fastest Big O.

Fix: question 3 exists for a reason. For $n = 50$, simple $O(n)$ beats a fragile $O(\log n)$ implementation.

اردو میں سمجھیں

کارکردگی کے تین سوال: کیا الگورتھم بڑے n پر چل سکتا ہے (Scale)؟ سب سے سست جگہ کون سی ہے (Bottleneck)، عموماً گہرا لوپ؟ کیا تیز تر طریقے کی پیچیدگی اس چھوٹے فائدے کے لائق ہے؟ پچاس ناموں کے لیے سادہ $O(n)$ تلاش عملی طور پر بہتر ہو سکتی ہے۔

CHECK YOURSELF

- If n grows $10\times$, how much slower is a quadratic algorithm?
- Where do you usually look for the bottleneck?
- Why might linear search beat binary search for 50 items?

Answers: 1. About $100\times$ slower (10^2). 2. The most time-consuming section, usually the deepest loop. 3. Binary search is more complex to code and maintain, and for $n = 50$ the simplicity of $O(n)$ is practically better.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The framework looks at:

- Steps, conditions, repetitions (then Big O)
- Only logos
- Only careers
- Only Figma

MCQ 2. "Number of steps" is:

- Basic operations in one pass / closed form
- The page count of the PDF
- OSI layers
- Sprint days

MCQ 3. You combine the three to:

- Justify a Big O class
- Pick a colour
- Pick a font
- Pick a career

MCQ 4. A 5-mark compare question wants:

- The framework on both algorithms + a verdict
- Only names
- Only Python libraries
- Only UX

MCQ 5. Constants matter at tiny n but the framework emphasises:

- Growth
- Hex colours
- Teacher names
- PDF margins

MCQ 6. If repetitions are nested $n \times n$, Big O is likely:

- n^2 regardless of a few extra ifs
- $\log n$
- 1
- $n!$

Extra short questions

- State the efficiency evaluation framework.
- Apply in one line to binary search.
- Apply to bubble sort.
- When would you still pick the slower class?

Extra long question

- Using the framework, compare selection sort vs binary search as if a student mixed them up. Then say why they are not alternatives.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Count significant steps, conditions, repetitions; combine into time/space class; compare to requirements.
- Few steps per shot, one/two conditions, $\log n$ repetitions $\rightarrow O(\log n)$ time, $O(1)$ space.
- Compare+swap steps, a condition, nested repetitions $\rightarrow O(n^2)$.
- Tiny n , need stability/simplicity, or the fast one needs a costly precondition (sort first).

Long

- Different problems (order vs find). Framework still: both have loops; sort n^2 vs search $\log n$. Verdict: sort then many binary queries if the list is reused.

12

2.4 Refinements to improve clarity and efficiency

LEARN IT

Improving an algorithm means reviewing it step by step: simplifying logic, removing redundant work, and picking smart data structures. A clear algorithm is easier to follow; an efficient one wastes fewer steps.

2.4.1 Refinements for clarity

1. Use meaningful names. Replace vague variables with descriptive ones. Bad: `a = b / c`. Good: `average = totalSum / totalItems`.

2. Break into modules. Divide a massive block into functions, for example separating `CalculateSum()` from the printing logic.

3. Improve structure and indentation. Packed loops and IF statements confuse the reader. Spacing reduces mental effort.

4. Add comments. Keep them short. Explain *why* something is done, not just what is happening, especially for tricky logic.

2.4.2 Refinements for efficiency

1. Reduce unnecessary steps. In Bubble Sort, after the first pass the largest value has settled at the end. Ignore that sorted tail on the next pass by shrinking the inner loop, and you save comparisons.

2. Use better algorithms. Searching 1 million sorted records with Binary Search instead of Linear Search changes the time from seconds to milliseconds.

3. Avoid re-computing values (memoization / caching). If a value never changes, compute it once outside the loop, store it, and reuse it.

4. Use appropriate data structures. Direct access → array. Hierarchical data → tree. Do not force one structure everywhere.

WORKED EXAMPLE

Worked example 1 — shrinking Bubble Sort's inner loop ($n = 5$). A naive inner loop always runs $n-1 = 4$ times, for 4 passes: 16 comparisons. The refined inner loop runs 4, then 3, then 2, then 1: 10 comparisons.

```
n = 5
naive = 0
for i in range(n - 1):
    for j in range(n - 1):
        naive = naive + 1

refined = 0
for i in range(n - 1):
    for j in range(n - 1 - i):
        refined = refined + 1

print(naive, refined)
```

OUTPUT

16 10

Worked example 2 — do not re-compute a constant inside the loop.

```
A = 3
B = 4
N = 5

# BAD: C is recalculated every time
for i in range(1, N + 1):
    C = A + B
    print(C * i)
```

OUTPUT

7
14
21
28
35

```
A = 3
B = 4
N = 5
# GOOD: compute C once
C = A + B
for i in range(1, N + 1):
    print(C * i)
```

OUTPUT

7
14
21
28
35

Same output, fewer additions. That is caching: compute once, reuse N times.

REMEMBER IT

Clarity: **N-M-I-C** (Names, Modules, Indentation, Comments). Efficiency: **S-A-C-D** (Shrink steps, Algorithm choice, Cache, Data structure).

COMMON MISTAKE

Mistake: "optimising" by renaming variables and thinking that is an efficiency refinement.

Fix: meaningful names improve clarity. Efficiency refinements change the **amount of work** (fewer loop iterations, a better algorithm, no re-compute, a better structure).

آرڈو میں سمجھیں

وضاحت بہتر کرنے کے لیے معنی خیز نام، مائیکرو، درست indentation اور مختصر تبصرے استعمال کریں۔ کارکردگی کے لیے فضول قدم ہٹائیں (بیل سارٹ میں ترتیب شدہ دم نظر انداز کریں)، بہتر الگورتھم چنیں (ایبیز کی جگہ ہائری سرچ)، لوپ کے اندر وہی حساب بار بار نہ کریں (Caching/Memoization)، اور مناسب ڈیٹا سٹرکچر رکھیں۔

CHECK YOURSELF

1. Rewrite `a = b / c` with meaningful names for an average.

2. After Bubble Sort's first pass, what should the next pass ignore?

3. In the A+B example, where should `C = A + B` be written?

Answers: 1. `average = totalSum / totalItems`. 2. The already-sorted largest value at the end (shrink the inner loop). 3. Once, outside the loop, then reuse C inside.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A clarity refinement is:
a. Rename, split, comment, simplify logic
b. Add more nested loops for fun
c. Shorten names to a,b,c
d. Remove all spaces

MCQ 2. An efficiency refinement is:
a. Cut extra work (e.g. already-sorted inner of bubble)
b. Add random sleeps
c. Copy the list 12 times
d. Print inside the inner loop 1e6 times

MCQ 3. Flagged bubble sort's early exit is:
a. Efficiency refinement
b. A new UX colour
c. A foreign key
d. A pie

MCQ 4. Extracting a function is:
a. Clarity (and sometimes reuse) refinement
b. Always worse Big O
c. OSI layering
d. A histogram

MCQ 5. Do not "optimise" first if:
a. The algorithm is still incorrect or unreadable
b. $n=10^{12}$ already proven
c. Tests all pass and profiler points here
d. It is $O(n!)$ on huge n and you must ship

MCQ 6. Redundant work means:
a. Computing the same thing twice
b. A needed loop
c. A primary key
d. A caption

Extra short questions

1. Two clarity refinements.

2. Two efficiency refinements from the book.

3. A refinement that hurts clarity for 1% speed is:

4. How do you know a refinement worked?

Extra long question

1. Show bubble sort before/after: (1) meaningful names (2) last-i unsorted bound (3) swapped flag. State what each changed (clarity vs efficiency).

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Better names; extract module; remove duplicate logic; add pre/post comments.

2. Stop inner bubble as the suffix grows sorted; avoid extra copies; fewer conditions in the inner loop.

3. Usually a bad deal in XU/XII and in teams.

4. Same tests (correctness) + fewer operations or clearer reading.

Long

1. Code/pseudocode both versions. (1) clarity (2) fewer comparisons $n^2/2$ still $O(n^2)$ (3) best case $O(n)$. Tests unchanged.

13

2.5 Concept of Data Structure ★ Golden

LEARN IT

A **data structure** is a systematic way of **organising, storing and managing** data so that an algorithm can access, modify and process it efficiently.

Real-life analogy. Books on a shelf are arranged in a set order, so you can find a title quickly. Files in folders are grouped on purpose. Data structures do the same job inside computer memory.


1. Linear data structures

Elements stand in a strict sequence, one after another. Each element (except the first and last) has exactly **one predecessor** and **one successor**.

Examples: Array, Linked List, Stack, Queue.

2. Non-linear data structures

Elements are connected in a hierarchy or a network. One element can connect to **several** others at the same time. Examples: Tree, Graph.



Linear: a line of neighbours. Non-linear: a node with more than one connection.

WORKED EXAMPLE

Worked example: classify each everyday picture.

1. Students standing in a single assembly line → **linear** (each has one in front and one behind).
2. A family tree of grandparents, parents and children → **non-linear** (one parent, several children).
3. Roads linking Karachi, Hyderabad, Sukkur and Larkana in many ways → **non-linear** (a network).

REMEMBER IT

Ask: "Does each item have at most one next item?" Yes → linear. "Can one item link to many, or can links form a net?" → non-linear.

COMMON MISTAKE

Mistake: calling a tree "linear" because you can walk it from top to bottom.

Fix: walking is traversal. The **shape** is hierarchical: one parent, many children. That is non-linear.

اردو میں سمجھیں

ڈیٹا سٹرکچر ڈیٹا کو منظم طریقے سے رکھنے کا نظام ہے تاکہ الگورتھم اسے جلدی استعمال کر سکے۔ لکیری ڈھانچوں میں عناصر قطار میں ہوتے ہیں (ایرے، لنکڈ لسٹ، سٹیک، کیو)۔ غیر لکیری میں ایک عنصر کئی سے جڑ سکتا ہے (ٹری، گراف)۔ الماری کی کتابیں اور فولڈرز کی مثال یاد رکھیں۔

EXAM TIP

Define data structure in full (organise, store, manage; efficient access and processing). Then split linear vs non-linear with the "one predecessor and one successor" test, and list the four linear and two non-linear examples. The shelf / folder analogy earns a mark. MCQs: "Which is non-linear?" → Tree or Graph.

CHECK YOURSELF

1. Define data structure.
2. Name four linear and two non-linear examples.
3. What is true of each middle element in a linear structure?

Answers: 1. A systematic way of organising, storing and managing data for efficient access, modification and processing. 2. Linear: array, linked list, stack, queue. Non-linear: tree, graph. 3. It has exactly one predecessor and one successor.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A data structure is:

- a. An organised way to store and access data
- b. A random pile
- c. A font
- d. A sprint

MCQ 2. We pick a structure for:

- a. The operations we need (fast insert? fast search?)
- b. The logo
- c. The teacher's birthday
- d. The PDF theme

MCQ 3. Linear vs non-linear is about:

- a. Whether elements form a sequence vs branches/links
- b. Colour
- c. File format .py vs .txt
- d. Agile vs waterfall

MCQ 4. An array gives fast:

- a. Index access $O(1)$
- b. Insert at front $O(1)$ always
- c. Arbitrary graph neighbours
- d. Sorted insert $O(1)$ always

MCQ 5. This is ★ because papers ask:

- a. Define + why we need DS + one example
- b. Only careers
- c. Only Figma
- d. Only OSI

MCQ 6. A queue of print jobs is a DS chosen because:

- a. Order of arrival matters (FIFO)
- b. LIFO undo
- c. Hierarchy of boss-staff
- d. Random friends links

Extra short questions

1. Define data structure.
2. Why not always use one big list?
3. Give one linear and one non-linear example.
4. What is an operation on a DS?

Extra long question

1. "If you pick the wrong structure, the algorithm looks harder." Explain with college examples of array, stack, queue, tree. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. A systematic way to organise data for efficient access and modification.
2. Some problems need LIFO, FIFO, hierarchy, or many-to-many links.
3. Linear: array/stack/queue. Non-linear: tree/graph.
4. Insert, delete, search, traverse, peek...

Long

1. Roll list: array. Undo typing: stack. Printer/canteen line: queue. Org chart/folders: tree. Wrong pick: using a stack for a fair queue angers people.

2.5.1 Linear Data Structures (Array, LinkedList, Stack, Queue)

Example 1
Write a function to determine if a number is prime or not. A prime number is a number that is only divisible by itself and 1. For example, 2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47, 53, 59, 61, 67, 71, 73, 79, 83, 89, 97, 101, 103, 107, 109, 113, 127, 131, 137, 139, 149, 151, 157, 163, 167, 173, 179, 181, 187, 191, 193, 197, 199, 211, 223, 227, 229, 233, 239, 241, 251, 257, 263, 269, 271, 277, 281, 283, 293, 307, 311, 313, 317, 331, 337, 347, 349, 353, 359, 367, 373, 379, 383, 389, 397, 401, 409, 419, 421, 431, 433, 439, 443, 449, 457, 461, 463, 467, 479, 487, 491, 499, 503, 509, 521, 523, 527, 539, 541, 547, 557, 563, 569, 571, 577, 587, 593, 599, 601, 607, 613, 617, 619, 623, 629, 631, 637, 641, 643, 647, 653, 659, 661, 667, 671, 673, 677, 683, 687, 691, 697, 701, 709, 713, 719, 727, 733, 739, 743, 751, 757, 761, 769, 773, 787, 797, 809, 811, 821, 823, 827, 829, 833, 839, 847, 853, 857, 859, 863, 869, 877, 881, 883, 887, 893, 899, 907, 911, 913, 917, 919, 929, 937, 941, 947, 953, 967, 971, 973, 977, 983, 989, 991, 997, 1009, 1013, 1019, 1021, 1031, 1033, 1037, 1039, 1043, 1049, 1051, 1057, 1061, 1063, 1067, 1069, 1073, 1079, 1087, 1091, 1093, 1097, 1103, 1107, 1117, 1123, 1127, 1129, 1133, 1137, 1141, 1147, 1151, 1153, 1157, 1163, 1167, 1171, 1177, 1181, 1183, 1187, 1193, 1197, 1201, 1207, 1213, 1217, 1223, 1229, 1231, 1237, 1241, 1247, 1253, 1259, 1261, 1267, 1271, 1277, 1283, 1289, 1291, 1297, 1301, 1303, 1307, 1313, 1319, 1321, 1327, 1331, 1333, 1337, 1343, 1349, 1351, 1357, 1361, 1363, 1367, 1373, 1379, 1381, 1387, 1391, 1397, 1403, 1409, 1411, 1417, 1423, 1427, 1433, 1439, 1441, 1447, 1453, 1459, 1463, 1469, 1471, 1477, 1481, 1483, 1487, 1493, 1499, 1501, 1507, 1511, 1513, 1517, 1523, 1529, 1531, 1537, 1541, 1543, 1547, 1553, 1559, 1561, 1567, 1571, 1573, 1577, 1583, 1589, 1591, 1597, 1601, 1603, 1607, 1609, 1613, 1617, 1621, 1627, 1631, 1633, 1637, 1643, 1649, 1651, 1657, 1661, 1663, 1667, 1673, 1679, 1681, 1687, 1691, 1693, 1697, 1703, 1709, 1711, 1717, 1721, 1723, 1727, 1733, 1739, 1741, 1747, 1753, 1759, 1763, 1769, 1771, 1777, 1783, 1789, 1793, 1799, 1801, 1807, 1811, 1813, 1817, 1823, 1829, 1831, 1837, 1841, 1843, 1847, 1853, 1859, 1861, 1867, 1871, 1873, 1877, 1883, 1889, 1891, 1897, 1901, 1903, 1907, 1913, 1919, 1921, 1927, 1931, 1933, 1937, 1943, 1949, 1951, 1957, 1961, 1963, 1967, 1973, 1979, 1981, 1987, 1991, 1993, 1997, 2003, 2009, 2011, 2017, 2021, 2023, 2027, 2029, 2033, 2039, 2041, 2047, 2051, 2053, 2057, 2063, 2069, 2071, 2077, 2081, 2083, 2087, 2093, 2099, 2101, 2107, 2111, 2113, 2117, 2123, 2129, 2131, 2137, 2141, 2143, 2147, 2153, 2159, 2161, 2167, 2171, 2173, 2177, 2183, 2189, 2191, 2197, 2203, 2209, 2213, 2217, 2221, 2227, 2231, 2233, 2237, 2243, 2249, 2251, 2257, 2261, 2263, 2267, 2273, 2279, 2281, 2287, 2291, 2293, 2297, 2303, 2309, 2311, 2317, 2321, 2323, 2327, 2333, 2339, 2341, 2347, 2351, 2353, 2357, 2363, 2369, 2371, 2377, 2381, 2383, 2387, 2393, 2399, 2401, 2407, 2411, 2413, 2417, 2423, 2429, 2431, 2437, 2441, 2443, 2447, 2453, 2459, 2461, 2467, 2471, 2473, 2477, 2483, 2489, 2491, 2497, 2503, 2509, 2511, 2517, 2521, 2523, 2527, 2533, 2539, 2541, 2547, 2551, 2553, 2557, 2563, 2569, 2571, 2577, 2581, 2583, 2587, 2593, 2599, 2601, 2607, 2611, 2613, 2617, 2623, 2629, 2631, 2637, 2641, 2643, 2647, 2653, 2659, 2661, 2667, 2671, 2673, 2677, 2683, 2689, 2691, 2697, 2701, 2703, 2707, 2711, 2713, 2717, 2723, 2729, 2731, 2737, 2741, 2743, 2747, 2753, 2759, 2761, 2767, 2771, 2773, 2777, 2783, 2789, 2791, 2797, 2803, 2809, 2811, 2817, 2821, 2823, 2827, 2833, 2839, 2841, 2847, 2851, 2853, 2857, 2863, 2869, 2871, 2877, 2881, 2883, 2887, 2893, 2899, 2901, 2907, 2911, 2913, 2917, 2923, 2929, 2931, 2937, 2941, 2943, 2947, 2953, 2959, 2961, 2967, 2971, 2973, 2977, 2983, 2989, 2991, 2997, 3001, 3003, 3007, 3011, 3013, 3017, 3023, 3029, 3031, 3037, 3041, 3043, 3047, 3053, 3059, 3061, 3067, 3071, 3073, 3077, 3083, 3089, 3091, 3097, 3101, 3103, 3107, 3113, 3119, 3121, 3127, 3131, 3133, 3137, 3143, 3149, 3151, 3157, 3161, 3163, 3167, 3173, 3179, 3181, 3187, 3191, 3193, 3197, 3203, 3209, 3211, 3217, 3221, 3223, 3227, 3233, 3239, 3241, 3247, 3251, 3253, 3257, 3263, 3269, 3271, 3277, 3281, 3283, 3287, 3293, 3299, 3301, 3307, 3311, 3313, 3317, 3323, 3329, 3331, 3337, 3341, 3343, 3347, 3353, 3359, 3361, 3367, 3371, 3373, 3377, 3383, 3389, 3391, 3397, 3401, 3403, 3407, 3413, 3419, 3421, 3427, 3431, 3433, 3437, 3443, 3449, 3451, 3457, 3461, 3463, 3467, 3473, 3479, 3481, 3487, 3491, 3493, 3497, 3503, 3509, 3511, 3517, 3521, 3523, 3527, 3533, 3539, 3541, 3547, 3551, 3553, 3557, 3563, 3569, 3571, 3577, 3581, 3583, 3587, 3593, 3599, 3601, 3607, 3611, 3613, 3617, 3623, 3629, 3631, 3637, 3641, 3643, 3647, 3653, 3659, 3661, 3667, 3671, 3673, 3677, 3683, 3689, 3691, 3697, 3701, 3703, 3707, 3711, 3713, 3717, 3723, 3729, 3731, 3737, 3741, 3743, 3747, 3753, 3759, 3761, 3767, 3771, 3773, 3777, 3783, 3789, 3791, 3797, 3803, 3809, 3811, 3817, 3821, 3823, 3827, 3833, 3839, 3841, 3847, 3851, 3853, 3857, 3863, 3869, 3871, 3877, 3881, 3883, 3887, 3893, 3899, 3901, 3907, 3911, 3913, 3917, 3923, 3929, 3931, 3937, 3941, 3943, 3947, 3953, 3959, 3961, 3967, 3971, 3973, 3977, 3983, 3989, 3991, 3997, 4001, 4003, 4007, 4013, 4019, 4021, 4027, 4031, 4033, 4037, 4043, 4049, 4051, 4057, 4061, 4063, 4067, 4073, 4079, 4081, 4087, 4091, 4093, 4097, 4103, 4109, 4111, 4117, 4121, 4123, 4127, 4133, 4139, 4141, 4147, 4151, 4153, 4157, 4163, 4169, 4171, 4177, 4181, 4183, 4187, 4193, 4199, 4201, 4207, 4211, 4213, 4217, 4223, 4229, 4231, 4237, 4241, 4243, 4247, 4253, 4259, 4261, 4267, 4271, 4273, 4277, 4283, 4289, 4291, 4297, 4301, 4303, 4307, 4313, 4319, 4321, 4327, 4331, 4333, 4337, 4343, 4349, 4351, 4357, 4361, 4363, 4367, 4373, 4379, 4381, 4387, 4391, 4393, 4397, 4403, 4409, 4411, 4417, 4421, 4423, 4427, 4433, 4439, 4441, 4447, 4451, 4453, 4457, 4463, 4469, 4471, 4477, 4481, 4483, 4487, 4493, 4499, 4501, 4507, 4511, 4513, 4517, 4523, 4529, 4531, 4537, 4541, 4543, 4547, 4553, 4559, 4561, 4567, 4571, 4573, 4577, 4583, 4589, 4591, 4597, 4601, 4603, 4607, 4613, 4619, 4621, 4627, 4631, 4633, 4637, 4643, 4649, 4651, 4657, 4661, 4663, 4667, 4673, 4679, 4681, 4687, 4691, 4693, 4697, 4703, 4709, 4711, 4717, 4721, 4723, 4727, 4733, 4739, 4741, 4747, 4751, 4753, 4757, 4763, 4769, 4771, 4777, 4781, 4783, 4787, 4793, 4799, 4801, 4807, 4811, 4813, 4817, 4823, 4829, 4831, 4837, 4841, 4843, 4847, 4853, 4859, 4861, 4867, 4871, 4873, 4877, 4883, 4889, 4891, 4897, 4901, 4903, 4907, 4913, 4919, 4921, 4927, 4931, 4933, 4937, 4943, 4949, 4951, 4957, 4961, 4963, 4967, 4973, 4979, 4981, 4987, 4991, 4993, 4997, 5003, 5009, 5011, 5017, 5021, 5023, 5027, 5033, 5039, 5041, 5047, 5051, 5053, 5057, 5063, 5069, 5071, 5077, 5081, 5083, 5087, 5093, 5099, 5101, 5107, 5111, 5113, 5117, 5123, 5129, 5131, 5137, 5141, 5143, 5147, 5153, 5159, 5161, 5167, 5171, 5173, 5177, 5183, 5189, 5191, 5197, 5201, 5203, 5207, 5213, 5219, 5221, 5227, 5231, 5233, 5237, 5243, 5249, 5251, 5257, 5261, 5263, 5267, 5273, 5279, 5281, 5287, 5291, 5293, 5297, 5303, 5309, 5311, 5317, 5321, 5323, 5327, 5333, 5339, 5341, 5347, 5351, 5353, 5357, 5363, 5369, 5371, 5377, 5381, 5383, 5387, 5393, 5399, 5401, 5407, 5411, 5413, 5417, 5423, 5429, 5431, 5437, 5441, 5443, 5447, 5453, 5459, 5461, 5467, 5471, 5473, 5477, 5483, 5489, 5491, 5497, 5501, 5503, 5507, 5513, 5519, 5521, 5527, 5531, 5533, 5537, 5543, 5549, 5551, 5557, 5563, 5569, 5571, 5577, 5581, 5583, 5587, 5593, 5599, 5601, 5607, 5611, 5613, 5617, 5623, 5629, 5631, 5637, 5641, 5643, 5647, 5653, 5659, 5661, 5667, 5671, 5673, 5677, 5683, 5689, 5691, 5697, 5701, 5703, 5707, 5711, 5713, 5717, 5723, 5729, 5731, 5737, 5741, 5743, 5747, 5753, 5759, 5761, 5767, 5771, 5773, 5777, 5783, 5789, 5791, 5797, 5803, 5809, 5811, 5817, 5821, 5823, 5827, 5833, 5839, 5841, 5847, 5851, 5853, 5857, 5863, 5869, 5871, 5877, 5881, 5883, 5887, 5893, 5899, 5901, 5907, 5911, 5913, 5917, 5923, 5929, 5931, 5937, 5941, 5943, 5947, 5953, 5959, 5961, 5967, 5971, 5973, 5977, 5983, 5989, 5991, 5997, 6001, 6003, 6007, 6013, 6019, 6021, 6027, 6031, 6033, 6037, 6043, 6049, 6051, 6057, 6061, 6063, 6067, 6073, 6079, 6081, 6087, 6091, 6093, 6097, 6103, 6109, 6111, 6117, 6121, 6123, 6127, 6133, 6139, 6141, 6147, 6151, 6153, 6157, 6163, 6169, 6171, 6177, 6181, 6183, 6187, 6193, 6199, 6201, 6207, 6211, 6213, 6217, 6223, 6229, 6231, 6237, 6241, 6243, 6247, 6253, 6259, 6261, 6267, 6271, 6273, 6277, 6283, 6289, 6291, 6297, 6301, 6303, 6307, 6313, 6319, 6321, 6327, 6331, 6333, 6337, 6343, 6349, 6351, 6357, 6361, 6363, 6367, 6373, 6379, 6381, 6387, 6391, 6393, 6397, 6403, 6409, 6411, 6417, 6421, 6423, 6427, 6433, 6439, 6441, 6447, 6451, 6453, 6457, 6463, 6469, 6471, 6477, 6481, 6483, 6487, 6493, 6499, 6501, 6507, 6511, 6513, 6517, 6523, 6529, 6531, 6537, 6541, 6543, 6547, 6553, 6559, 6561, 6567, 6571, 6573, 6577, 6583, 6589, 6591, 6597, 6601, 6603, 6607, 6613, 6619, 6621, 6627, 6631, 6633, 6637, 6643, 6649, 6651, 6657, 6661, 6663, 6667, 6673, 6679, 6681, 6687, 6691, 6693, 6697, 6703, 6709, 6711, 6717, 6721, 6723, 6727, 6733, 6739, 6741, 6747, 6751, 6753, 6757, 6763, 6769, 6771, 6777, 6781, 6783, 6787, 6793, 6799, 6801, 6807, 6811, 6813, 6817, 6823, 6829, 6831, 6837, 6841, 6843, 6847, 6853, 6859, 6861, 6867, 6871, 6873, 6877, 6883, 6889, 6891, 6897, 6901, 6903, 6907, 6913, 6919, 6921, 6927, 6931, 6933, 6937, 6943, 6949, 6951, 6957, 6961, 6963, 6967, 6973, 6979, 6981, 6987, 6991, 6993, 6997, 7003, 7009, 7011, 7017, 7021, 7023, 7027, 7033, 7039, 7041, 7047, 7051, 7053, 7057, 7063, 7069, 7071, 7077, 7081, 7083, 7087, 7093, 7099, 7101, 7107, 7111, 7113, 7117, 7123, 7129, 7131, 7137, 7141, 7143, 7147, 7153, 7159, 7161, 7167, 7171, 7173, 7177, 7183, 7189, 7191, 7197, 7201, 7203, 7207, 7213, 7219, 7221, 7227, 7231, 7233, 7237, 7243, 7249, 7251, 7257, 7261, 7263, 7267, 7273, 7279, 7281, 7287, 7291, 7293, 7297, 7303, 7309, 7311, 7317, 7321, 7323, 7327, 7333, 7339, 7341, 7347, 7351, 7353, 7357, 7363, 7369, 7371, 7377, 7381, 7383, 7387, 7393, 7399, 7401, 7407, 7411, 7413, 7417, 7423, 7429, 7431, 7437, 7441, 7443, 7447, 7453, 7459, 7461, 7467, 7471, 7473, 7477, 7483, 7489, 7491, 7497, 7501, 7503, 7507, 7513, 7519, 7521, 7527, 7531, 7533, 7537, 7543, 7549, 7551, 7557, 7561, 7563, 7567, 7573, 7579, 7581, 7587, 7591, 7593, 7597, 7603, 7609, 7611, 7617, 7621, 7623, 7627, 7633, 7639, 7641, 7647, 7651, 7653, 7657, 7663, 7669, 7671, 7677, 7681, 7683, 7687, 7693, 7699, 7701, 7707, 7711, 7713, 7717, 7723, 7729, 7731, 7737, 7741, 7743, 7747, 7753, 7759, 7761, 7767, 7771, 7773, 7777, 7783, 7789, 7791, 7797, 7801, 7803, 7807, 7813, 7819, 7821, 7827, 7831, 7833, 7837, 7843, 7849, 7851, 7857, 7861, 7863, 7867, 7873, 7879, 7881, 7887, 7891, 7893, 7897, 7903, 7909, 7911, 7917, 7921, 7923, 7927, 7933, 7939, 7941, 7947, 7951, 7953, 7957, 7963, 7969, 7971, 7977, 7981, 7983, 7987, 7993, 7999, 8001, 8007, 8011, 8013, 8017, 8023, 8029, 8031, 8037, 8041, 8043, 8047, 8053, 8059, 8061, 8067, 8071, 8073, 8077, 8083, 8089, 8091, 8097, 8101, 8103, 8107, 8113, 8119, 8121, 8127, 8131, 8133, 8137, 8143, 8149, 8151, 8157, 8161, 8163, 8167, 8173, 8179, 8181, 8187, 8191, 8193, 8197, 8203, 8209, 8211, 8217, 8221, 8223, 8227, 8233, 8239, 8241, 8247, 8251, 8253, 8257, 8263, 8269, 8271, 8277, 8281, 8283, 8287, 8293, 8299, 8301, 8307, 8311, 8313, 8317, 8323, 8329, 8331, 8337, 8343, 8349, 8351, 8357, 8361, 8363, 8367, 8373, 8379, 8381, 8387, 8391, 8393, 8397, 8403, 8409, 8411, 8417, 8421, 8423, 8427, 8433, 8439, 8441, 8447, 8451, 8453, 8457, 8463, 8469, 8471, 8477, 8481, 8483, 8487, 8493, 8499, 8501, 8507, 8511, 8513, 8517, 8523, 8529, 8531, 8537, 8541, 8543, 8547, 8553, 8559, 8561, 8567, 8571, 8573, 8577, 8583, 8589, 8591, 8597, 8601, 8603, 8607, 8613, 8619, 8621, 8627, 8631, 8633, 8637, 8643, 8649, 8651, 8657, 8661, 8663, 8667, 8673, 8679, 8681, 8687, 8691, 8693, 8697, 8703, 8709, 8711, 8717, 8721, 8723, 8727, 8733, 8739, 8741, 8747, 8751, 8753, 8757, 8763, 8769, 8771, 8777, 8781, 8783, 8787, 8793, 8799, 8801, 8807, 8811, 8813, 8817, 8823, 8829, 8831, 8837, 8841, 8843, 8847, 8853, 8859, 8861, 8867, 8871, 8873, 8877, 8883, 8889, 8891, 8897, 8901, 8903, 8907, 8913, 8919, 8921, 8927, 8931, 8933, 8937, 8943, 8949, 8951, 8957, 8961, 8963, 8967, 8973, 8979, 8981, 8987, 8991, 8993, 8997, 9001, 9003, 9007, 9013, 9019, 9021, 9027, 9031, 9033, 9037, 9043, 9049, 9051, 9057, 9061, 9063, 9067, 9073, 9079, 9081, 9087, 9091, 9093, 9097, 9103, 9109, 9111, 9117, 9121, 9123, 9127, 9133, 9139, 9141, 9147, 9151, 9153, 9157

2.5.2 Non-Linear Data Structures (Tree, Graph)

LEARN IT

A **tree** organises data in a **hierarchy**. Everything branches out from a single starting point called the **root**.

It creates a strict **one-to-many (parent-child)** relationship. That is an excellent way to show how roles flow in an organisation.

Real-life examples: a family tree (grandparents → parents → children) and folders inside folders on a drive.



College tree: one root (Principal), then parent-child branches. No child has two parents in this model.

WORKED EXAMPLE

Worked example: name the relationships.

- Root: Principal.
- Children of the root: Administrative Head, Academic Dean.
- Children of Academic Dean: HOD Math, HOD CS.
- HOD CS has one parent (Academic Dean), not two — that is the tree rule. If HOD CS also reported sideways to Accounts as an equal link, the picture would become a **graph**.

REMEMBER IT

Tree = family / folders / organogram. One root. Branches down. Parent-child, not a web of equals.

COMMON MISTAKE

Mistake: drawing a tree with two roots, or with an arrow going back up to the Principal from HOD CS (a cycle).

Fix: one root, links only parent → child, no loops. Cycles belong to graphs.

آرڈو میں سمجھیں

ٹری ٹیپا کو درجہ بندی (Hierarchy) میں رکھتی ہے جو ایک (Root) سے پھولتی ہے، تعلق والدین-بچہ (ایک سے کئی) ہوتا ہے، جیسے پرنسپل → ڈین → ایچ او ڈی، خاندانی شجرہ، یا فولڈر کے اندر فولڈر۔ دو چیزیں یا چکر لڑی کو گراف بنا دیتے ہیں۔

CHECK YOURSELF

1. What is the starting node of a tree called?
2. What kind of relationship does a tree model?
3. Give two real-life tree examples from the source.

Answers: 1. The root. 2. One-to-many parent-child. 3. A family tree, and folders inside folders (or a college organogram).

LEARN IT

A **graph** organises data when things connect in a flexible, complex way. Unlike a tree, there is **no strict hierarchy**: any node can connect to any other node.

- **Nodes (vertices)** — the items (cities, people).
- **Edges** — the connections (roads, friendships).

Examples: Facebook friends; GPS mapping (the fastest route between two cities).



Four vertices A, B, C, D. Edges can form a cycle (A-B-D-C-A). A tree cannot do that.

WORKED EXAMPLE

Worked example: Karachi – Hyderabad – Sukkur – Larkana. Cities are vertices. Roads are edges. You can travel Karachi → Hyderabad → Sukkur or Karachi → Larkana → Sukkur. There is no single “root city”. That is a graph, and GPS uses it to pick a fast route.

REMEMBER IT

Tree = Graph in shape-talk: a tree is a special graph with one root and no cycles. If you need cycles or many-to-many links, say **graph**.

COMMON MISTAKE

Mistake: using a tree for GPS because “Hyderabad comes under Sindh”.

Fix: administration can be a tree; **roads** are a graph because you can loop and take alternative paths.

آرڈو میں سمجھیں

گراف لچکدار روابط کے لیے ہے: کوئی سخت درجہ بندی نہیں، کوئی بھی نوڈ کسی سے جڑ سکتا ہے، نوڈز (Vertices) چڑیاں ہیں، کنارے (Edges) تعلق، قریبی یک دوست اور GPS نقشہ، کلاسیکی مثالیں ہیں، چکر (Cycle) اور کئی راستے، گراف کو لڑی سے الگ کرتے ہیں۔

CHECK YOURSELF

1. What are the two parts of a graph?
2. Give two source examples of graphs.
3. State one difference between a tree and a graph.

Answers: 1. Nodes/vertices and edges. 2. Social networks (Facebook friends) and GPS mapping. 3. A tree has a hierarchy and one root; a graph has no strict hierarchy and any node may connect to any other (cycles allowed).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An array stores items:

- a. In contiguous indexed slots of one type
- b. With arbitrary node links only
- c. As a hierarchy always
- d. As a pie

MCQ 2. A linked list stores items:

- a. In nodes with pointers to the next
- b. In one block of equal indexes only
- c. As a tree of bosses
- d. As a hash of pies

MCQ 3. A stack is:

- a. LIFO
- b. FIFO
- c. A graph
- d. A GUI

MCQ 4. A queue is:

- a. FIFO
- b. LIFO
- c. A binary tree
- d. A K-map

MCQ 5. Undo in an editor uses a:

- a. Stack
- b. Queue
- c. Pie
- d. OSI layer

MCQ 6. A printer line is a:

- a. Queue
- b. Stack
- c. AVL tree always
- d. NAND

Extra short questions

1. Define array, linked list, stack, queue in one line each.
2. One op each: push/pop, enqueue/dequeue.
3. Array vs list for insert at front.
4. Peek means:

Extra long question

1. Draw stack and queue after the sequence: insert A,B,C then remove one. Show remaining order and a real example of each. ★ Golden for stack/queue.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Array: Indexed block. List: nodes+links. Stack: LIFO. Queue: FIFO.
2. Stack push/pop top. Queue enqueue rear, dequeue front.
3. Array shifts $O(n)$; list pointer change $O(1)$ if you have the head.
4. Read the top/front without removing.

Long

1. Stack remaining B,A (C popped). Queue remaining B,C (A served). Examples: back button vs ticket counter. Diagrams with top/front labelled.

2.5.3 Operations on Data Structures

LEARN IT

Whatever the shape, you keep meeting the same five operations:

Operation	Meaning	Quick picture
Insertion	Adding a new item into the structure.	PUSH on a stack; ENQUEUE on a queue; putting 40 into an array.
Deletion	Removing an item that is no longer needed.	POP; DEQUEUE; deleting a node from a list.
Traversal	Going through each item one by one.	Walking HEAD → ... → NULL; visiting every tree node.
Searching	Finding a specific item.	Linear search in an array; following links until 87 is found.
Sorting	Arranging items in a proper order (ascending or descending).	Bubble Sort on an array of marks.

WORKED EXAMPLE

Worked example: name the operation.

1. "Print every song from the start of the playlist." → **Traversal**.
2. "Add a print job at the rear." → **Insertion** (ENQUEUE).
3. "Undo the last typing action." → **Deletion** (POP).
4. "Is roll number 87 in the list?" → **Searching**.
5. "Arrange heights from shortest to tallest." → **Sorting**.

REMEMBER IT

Memorise **I-D-T-S-S**: Insert, Delete, Traverse, Search, Sort.

COMMON MISTAKE

Mistake: calling a PUSH "sorting" because the stack looks tidy.

Fix: PUSH is insertion. Sorting means putting values in ascending or descending order.

اردو میں سمجھیں

پر ڈیٹا سٹرکچر پر پانچ عمل ہوتے ہیں: داخل کرنا (Insertion)، حذف کرنا (Deletion)، ایک ایک کر کے گزرتا (Traversal)، تلاش (Searching) اور ترتیب (Sorting، صعودی یا نزولی)۔

CHECK YOURSELF

1. List the five operations.
2. Which operation is ENQUEUE?
3. Traversal vs searching — one difference?

Answers: 1. Insertion, deletion, traversal, searching, sorting. 2. Insertion (at the rear of a queue). 3. Traversal visits every item; searching stops when the target is found (or the structure ends).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Common DS operations include:

- a. Insert, delete, search, traverse
- b. Only compile
- c. Only ping
- d. Only print the logo

MCQ 2. Traverse means:

- a. Visit elements in some order
- b. Delete all
- c. Encrypt all
- d. Sort the OS

MCQ 3. Search cost depends on:

- a. The structure (array vs sorted vs hash vs tree)
- b. The PDF theme
- c. The teacher name
- d. The sprint

MCQ 4. Insert in a full array may:

- a. Fail or require resizing
- b. Always **$O(1)$** no matter what
- c. Create a graph edge automatically
- d. Pop a stack

MCQ 5. Delete from a queue happens at the:

- a. Front
- b. Rear only always
- c. Random index
- d. Root of a tree

MCQ 6. You choose a DS by the:

- a. Operations you will do most
- b. First letter of the course
- c. Colour
- d. NAND count

Extra short questions

1. List five operations.
2. Give costs qualitatively: array index vs list search.
3. What does traverse a tree mean?
4. Why "update" might be search+insert.

Extra long question

1. For array, stack, queue, tree: name the natural insert/delete ends and one costly operation. Table.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Create, insert, delete, search, traverse, update, sort (as applicable).
2. Array index **$O(1)$** ; unsorted list search **$O(n)$** .
3. Visit every node (pre/in/post or level order).
4. You must find the item first.

Long

1. Array: insert middle costly. Stack: top only cheap. Queue: rear in front out. Tree: search/insert depend on balance. 8-row table.

2.6 Identify data structures in problem scenarios

LEARN IT

To pick a structure, first see how the data is organised. If each item has a clear "before and after", it is **linear**. If it branches or connects to many items, it is **non-linear**.

2.6.1 Linear scenarios

1. Storing student grades for a class → **Array**. You usually know how many students there are, and all grades are the same type. Indices give rapid lookup.

2. Music playlist / browser history → **Linked list**. Every song knows what comes next. When one finishes, follow the pointer. Frequent insert/delete is cheap.

3. Undo or Redo → **Stack (LIFO)**. Each typing or formatting action is PUSHed. Undo POPs the most recent action.

4. Printer task scheduling → **Queue (FIFO)**. Documents print in the exact order they were received. First-come, first-served.

2.6.2 Non-linear scenarios

1. Organisational chart of a college → **Tree**. Principal is the root, then deans, then HODs, then teachers. Clear parent-child links.

2. GPS navigation and maps → **Graph**. Cities are nodes, roads are edges. No strict top-down hierarchy. Several routes can reach the same destination.

If the data...	Then it is...	Recommended structure
Follows "next" or "previous" logic	Linear	Array, Linked list
Follows "parent" and "child" logic	Non-linear	Tree
Follows "first-come, first-served" logic	Linear	Queue
Follows "connections / relationships" logic	Non-linear	Graph
Needs to be accessed in the reverse order of entry	Linear	Stack

WORKED EXAMPLE

Worked example: match five school problems.

Scenario	Structure	Why (one line)
Store 40 practical marks you already counted	Array	Fixed size, same type, need A[i] lookup.
A playlist where the teacher inserts a nasheed between two songs	Linked list	Insert by moving two pointers, no big shift.
Ctrl+Z after formatting a heading	Stack	Last action must come off first.
Students lining up for the photocopier	Queue	First in line is served first.
Friend links in a class WhatsApp "everyone knows everyone"	Graph	Any student can connect to any other.

REMEMBER IT

Decision order: reverse-of-entry? → stack. First-come? → queue. Parent-child? → tree. Many-to-many routes? → graph. Known list with indexes? → array. Lots of insert/delete in a sequence? → linked list.

COMMON MISTAKE

Mistake: choosing an array for Undo because "actions are stored in a list".
Fix: the **access rule** matters more than "it is a list". Undo is reverse order of entry → stack.

اُردو میں سمجھیں

اگر ہر عنصر کا واضح اگلا/پچھلا ہے تو ڈھانچہ لکیری ہے، اگر شاخیں یا کئی روابط ہیں تو غیر لکیری۔ نمبر: ایروء؛ پلے لسٹ/ایسٹری؛ لنکڈ لسٹ؛ انڈو؛ سٹیک؛ پرنٹن؛ کیو؛ کالج کا چارٹ؛ ٹری؛ GPS۔ گراف۔ فیصلے کی جدول یاد کر لیں۔

CHECK YOURSELF

1. Which structure stores a class's grades, and why?

2. Printer jobs: stack or queue? Why?

3. "Needs reverse order of entry" maps to which structure?

Answers: 1. Array — known size, same type, fast index lookup. 2. Queue, because first-come, first-served. 3. Stack.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An IDE is:

a. One app to write, run and debug code

b. A printer

c. A sort

d. A cable

MCQ 2. VS Code is:

a. A popular editor/IDE

b. A DBMS

c. An OSI layer

d. A gate

MCQ 3. The terminal/run button is for:

a. Executing the program

b. Drawing pie charts only

c. Sending TCP SYN only

d. K-maps

MCQ 4. Syntax highlighting helps you:

a. See keywords and mistakes

b. Sort faster

c. Encrypt disks

d. Route packets

MCQ 5. A file explorer in VS Code shows:

a. Project files

b. OSI layer 1

c. NAND groups

d. Beachhead users

MCQ 6. Debugging in an IDE uses:

a. Breakpoints and variable watch

b. Only bubble sort

c. Only pie charts

d. Only Agile stickers

Extra short questions

1. Define IDE.

2. Name four VS Code areas.

3. Why not use Notepad only?

4. What is an extension?

Extra long question

1. Describe how you would create, run and debug a first Python file in VS Code. Include two interface elements from the notes.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Integrated Development Environment: editor + run + debug + files in one place.

2. Activity bar/sidebar (files), editor, terminal, status bar (and extensions).

3. No easy run, no highlighting, no debugger.

4. An add-on (Python plugin) that teaches VS Code a language.

Long

1. New file .py, type print, Run Python, read terminal. Mention top menu, explorer, terminal panel. Breakpoint on a wrong variable.

18

2.7 Trace data retrieval in Array, List and Queue

LEARN IT
Tracing data retrieval means following the step-by-step path of how an algorithm finds or accesses data. Array, linked list and queue are all linear, but the **effort** to find an item is very different because of how they are organised inside.

2.7.1 Retrieval in an array

Every element has a fixed index from 0 to n-1 pointing at a spot in memory. If the algorithm already knows the index, it does not search: it **jumps** (direct access, **O(1)**).

Array = [10, 50, 20, 70, 90, 30]. Direct access: Array[2] = 20.

Loop iteration	Index	Array access	Value
1	0	Array[0]	10
2	1	Array[1]	50
3	2	Array[2]	20

```
Array = [10, 50, 20, 70, 90, 30]
print("Direct Array[2] =", Array[2])
for i in range(3):
    print(i + 1, ":", f"Array[{i}]", Array[i])
```

```
OUTPUT
Direct Array[2] = 20
1 8 Array[0] 10
2 1 Array[1] 50
3 2 Array[2] 20
```

2.7.2 Retrieval in a linked list

Linked lists have **no index**. The only way is to start at HEAD and follow links one node at a time (sequential access, **O(n)**).

List: [12] → [98] → [23] → [87] → [56] → NULL. Search key: 87.

Step	Node data	Compare with 87	Action
1	12	12 != 87	Move next
2	98	98 != 87	Move next
3	23	23 != 87	Move next
4	87	87 == 87	FOUND — output True

```
nodes = [12, 98, 23, 87, 56]
key = 87
found = False
for i, value in enumerate(nodes, start=0):
    print(f"Step {i}: Check Node {i} ({value}).")
    if value == key:
        found = True
        print("FOUND! Output: True")
        break
    print("Not equal. Move Next.")
print("Result:", found)
```

```
OUTPUT
Step 1: Check Node 1 (12).
Not equal. Move Next.
Step 2: Check Node 2 (98).
Not equal. Move Next.
Step 3: Check Node 3 (23).
Not equal. Move Next.
Step 4: Check Node 4 (87).
FOUND! Output: True
Result: True
```

Key 87 sits at the fourth node, so you paid four checks. An array that already knew index 3 would have paid one jump.

2.7.3 Retrieval in a queue

A queue is FIFO. You **cannot** retrieve from the middle or the rear. The oldest item at the Front is always DEQUEUED first.



You cannot pull B until A has left.
Queue A, B, C. ENQUEUE D joins the rear. DEQUEUE must remove A, not C or B.

```
from collections import deque
q = deque(["A", "B", "C"])
q.append("D")
print("After ENQUEUE D:", list(q))
print("DEQUEUE:", q.popleft())
print("now:", list(q))
```

```
OUTPUT
After ENQUEUE D: ['A', 'B', 'C', 'D']
DEQUEUE: A
now: ['B', 'C', 'D']
```

WORKED EXAMPLE

Worked example: three retrievals compared for "get 20 / get 87 / get A".

Structure	Target	Path	Can you jump?
Array [10, 50, 20, ...]	20 at index 2	Array[2] in one step, or scan 10, 50, 20	Yes, if the index is known
Linked list 12→98→23→87→...	87	Must visit 12, 98, 23, then 87	No
Queue A-B-C	A (the only legal retrieval)	DEQUEUE Front	No — never the middle

REMEMBER IT

Array jumps, list walks, queue waits. If the exam asks "why is array retrieval different?", write **direct access by index** versus **sequential links** versus **Front only**.

COMMON MISTAKE

Mistake: DEQUEUEing C because "C is the interesting letter", or reading linked-list node 4 as 'list[3]' without walking.

Fix: show every hop in the table. Marks are for the path, not only for FOUND.

آرڈو میں سمجھیں

آرڈو میں اگر انڈیکس معلوم ہو تو سیدھی چھلانگ لگی ہے، جیسے Array[2] = 20. لنکڈ لسٹ میں HEAD سے ایک ایک نوڈ دیکھنا پڑتا ہے، 87 پونہی نوڈ پر ملا۔ کیوں سے صرف Front لنکڈ ہے، درمیان سے نہیں۔ A، B، C میں DEQUEUE یعنی A ہے۔

CHECK YOURSELF

- What is Array[2] in [10, 50, 20, 70, 90, 30]?
- How many nodes are checked before 87 is found in 12→98→23→87→56?
- In queue A, B, C, can you retrieve B without removing A?

Answers: 1. 20. 2. Four (12, 98, 23, 87). 3. No — a queue only DEQUEUEs the Front, so A must leave first.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Tracing retrieval means: a. Following how an algorithm finds/returns an item b. Deleting the DS c. Drawing Figma d. Running pip	MCQ 2. Array retrieval by index is: a. Direct: a[i] b. Walk from head always c. Pop until empty always d. BFS always	MCQ 3. Linked-list retrieval of the k-th is: a. Walk k links b. O(1) index c. A binary cut d. A hash	MCQ 4. Queue retrieval of the next client is: a. Dequeue front (FIFO) b. Pop top (LIFO) c. Random node d. Tree root	MCQ 5. You cannot take the middle of a queue without: a. Breaking FIFO (or using another DS) b. It is the definition of queue c. A pie d. A sprint	MCQ 6. A trace should show: a. Pointers/indices before and after b. Only the career names c. Only colours d. Only OSI
---	---	--	--	---	--

Extra short questions

- Trace getting a[2] from array [10,20,30,40].
- Trace finding 30 in a list 10→20→30.
- Trace queue A-B-C serve one.
- Why tracing retrieval is in the syllabus.

Extra long question

- Same three names stored in array, list, queue. Trace "get the second person" in each. Who is not allowed in a pure queue?

Extra answer key

MCQs: 1. A. 2. A. 3. A. 4. A. 5. A. 6. A.

Short

- Index 2 → 30 in one step.
- Start 10 ←, next 20 ←, next 30 ←. Three visits.
- Dequeue A; front is B. Remaining B-C.
- So you can justify the DS with actual steps, not slogans.

Long

- Array a[1]: list two hops; queue: you may only legally take the front — getting the second requires dequeue then the new front, which also removes the first. That is the point.

Computational Thinking & Algorithms

16 single-page lessons · 5 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- **Correctness:** output matches expected results for valid inputs. Test with a trace table (manual dry run) or stepwise reasoning (logic verification).
- A **trace table** is micro-level: line, variables, I/O, conditions. Best for small loops. The soldier heights [1.91, 2.01, 1.87, 1.57, 1.48] print Total = 3.
- **Stepwise reasoning** is macro-level: valid start, all cases, correct conditions, loop stays correct. Sum 1..N starts at 0; N = 0 stays 0; N = 5 becomes 15.
- **Clarity** (read, understand, modify) often beats a tiny speed gain. It has two parts: modularity and readability.
- **Modularity:** SRP (one job), loose coupling, abstraction (call Sort without knowing Bubble vs Selection). Split CalculateSum and FindAverage.
- **Readability:** names (`velocity = distance / time`), self-documentation, simple flow, consistent style.
- **Efficiency** = time + space. Drivers: number of steps (Big O), conditions, repetitions.
- **Big O:** $O(1)$ constant (`arr[0]`), $O(\log n)$ binary search, $O(n)$ linear search, $O(n \log n)$ Merge Sort, $O(n^2)$ nested loops / Bubble Sort. Quadratic fails as n grows.
- **Framework:** Does it scale? What is the bottleneck (deepest loop)? Is the extra complexity worth it? For $n = 50$, simple $O(n)$ can beat fragile $O(\log n)$.
- **Refinements:** meaningful names, modules, indentation, why-comments; shrink Bubble Sort's inner loop; better algorithms; cache constants; pick the right structure.
- **Data structure:** systematic organising of data. Linear (one after another): array, linked list, stack, queue. Non-linear: tree, graph.
- **Array:** contiguous, index from 0, direct access $O(1)$, shifting on mid-insert. **Linked list:** nodes of data+link, HEAD to NULL, sequential access.
- **Stack LIFO:** PUSH/POP at TOP (Undo). **Queue FIFO:** ENQUEUE rear, DEQUEUE front (printer).
- **Tree:** one root, parent-child (college chart). **Graph:** vertices + edges, no strict hierarchy (GPS, friends).
- Five operations: insert, delete, traverse, search, sort. Choose by next/previous, parent/child, FIFO, relationships, or reverse-of-entry.
- **Retrieval:** array can jump to an index; a list walks from HEAD; a queue only removes the Front.

Key terms

Term	Meaning	اردو
Correctness	The algorithm's output matches the expected results for valid inputs.	درستگی
Trace table	A paper dry-run table of steps, variables, I/O and conditions.	ٹریس ٹیبل
Dry run	Executing an algorithm by hand, line by line.	دستی اجرا
Stepwise reasoning	Checking each logic block's state; also called logic verification.	مرحلہ وار استدلال
Clarity	How easy an algorithm is to read, understand and modify.	وضاحت
Modularity	Breaking work into independent functions, classes or modules.	ماڈیولریتی
Single Responsibility Principle	Each module should do one specific task.	واحد ذمہ داری کا اصول
Coupling	How tightly modules depend on each other; loose coupling is the goal.	ماڈیولز کی جڑت
Abstraction	Hiding implementation details so a caller need not know the inner method.	تجريد
Readability	How easily another person understands the logic without running it.	پڑھائی پن
Efficiency	How well an algorithm uses time (speed) and space (memory).	کارکردگی
Big O notation	A description of how running time or memory grows as n grows.	بگ او نوٹیشن

Computational Thinking & Algorithms

75 marks · 1 hour 15 minutes · no notes · no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 16 and the recap. **Section A** — all 15 MCQs (1 mark). **Section B** — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define · Explain · Example · Diagram · Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. An algorithm is correct when:
 - a. it compiles with no syntax error
 - b. its output matches the expected results for the given input
 - c. it uses Big O notation
 - d. it has no comments
2. A trace table is best described as:
 - a. a paper execution that tracks variables line by line
 - b. a diagram of a tree
 - c. a type of graph edge
 - d. an $O(n^2)$ nested loop
3. Stepwise reasoning mainly checks:
 - a. printer ink levels
 - b. the colour of variable names
 - c. only the last printed line
 - d. the overall state of logic blocks
4. Which method is impractical if a loop runs 1,000 times?
 - a. Abstraction
 - b. A full trace table
 - c. Stepwise reasoning
 - d. Using a function
5. The Single Responsibility Principle says each module should:
 - a. focus on one specific task
 - b. print and save and calculate everything
 - c. avoid meaningful names
 - d. use nested IF only
6. Which assignment is more readable?
 - a. `v = d / t`
 - b. `x1 = a2 / b2`
 - c. `velocity = distance / time`
 - d. `a = b / c`
7. Accessing `arr[0]` is:
 - a. $O(n^2)$
 - b. $O(n \log n)$
 - c. $O(n)$
 - d. $O(1)$
8. Binary search on a sorted list is:
 - a. $O(\log n)$
 - b. $O(n^2)$
 - c. $O(1)$ always for any n
 - d. $O(n)$ because a loop exists
9. Bubble Sort and nested "compare every pair" loops are:
 - a. $O(1)$
 - b. $O(\log n)$
 - c. $O(n)$
 - d. $O(n^2)$
10. If n grows 10 times, a quadratic algorithm's time grows about:
 - a. 2 times
 - b. 10 times
 - c. 100 times
 - d. log 10 times
11. LIFO is the rule of a:
 - a. queue
 - b. graph of cities
 - c. tree root only
 - d. stack
12. ENQUEUE adds an item at the:
 - a. Front of a queue
 - b. TOP of a stack only
 - c. Rear of a queue
 - d. root of a tree
13. A college organogram with a Principal at the top is modelled as a:
 - a. tree
 - b. queue
 - c. stack
 - d. contiguous array of roads
14. GPS maps (cities and roads, many possible routes) need a:
 - a. stack of undo actions
 - b. graph
 - c. strict one-parent tree only
 - d. single array index
15. To retrieve 87 from `HEAD→12→98→23→87→56` you must:
 - a. jump with `Array[87]`
 - b. DEQUEUE the rear
 - c. follow four nodes from HEAD until 87 matches
 - d. POP from the bottom of a stack

Section B — Short questions ($10 \times 3 = 30$)

1. Define correctness of an algorithm. Name the two analysis methods used in this chapter.
2. List the components of a trace table. Why is a dry run useful for debugging?
3. Give four differences between a trace table and stepwise reasoning.
4. What is modularity? Explain SRP, coupling and abstraction in one sentence each.
5. State four ways to evaluate readability, with one example of a bad name and a good name.
6. Define Big O notation. Give one example each of $O(1)$, $O(\log n)$, $O(n)$, $O(n \log n)$ and $O(n^2)$.
7. Write the three questions of the efficiency evaluation framework and answer them for searching 50 unsorted names.
8. List four refinements for clarity and four for efficiency.
9. Define data structure. Distinguish linear from non-linear with examples.
10. Define stack and queue. Include LIFO/FIFO, PUSH/POP, ENQUEUE/DEQUEUE, and one real-life example of each.

Section C — Long questions (attempt any $3 \times 10 = 30$)

1. The soldier-eligibility algorithm uses AllHeights = [1.91, 2.01, 1.87, 1.57, 1.48] and counts heights from 1.57 to 1.91 inclusive. (a) Draw a complete trace table. (b) State the printed Total. (c) Explain in stepwise-reasoning style why the boundaries 1.57 and 1.91 are counted. (d) Write equivalent Python and its output.
2. Copy the monoblock average algorithm for A = [1, 2, 3, 4, 5] and rewrite it with CalculateSum and FindAverage. (a) Show that SRP, loose coupling and abstraction are improved. (b) Dry-run both versions to the same average. (c) Give two readability improvements you would still make to the functions.
3. Using the growth table idea, (a) fill n = 8 and n = 32 for $O(1)$, $O(\log_2 n)$, $O(n)$, $O(n \log_2 n)$ and $O(n^2)$. (b) Explain what happens if n becomes 10 times larger for $O(n)$ and for $O(n^2)$. (c) A library has 1,000,000 sorted IDs. Choose linear or binary search using the Scale / Bottleneck / Worth-it framework. (d) Show a 4-by-4 nested loop counts 16 operations in Python.
4. Draw a labelled stack and a labelled queue. Then trace: (a) PUSH Data1, PUSH Data2, PUSH Data3, POP, POP. (b) ENQUEUE 55, 76, 90, D then DEQUEUE. Include Python that matches both traces. (c) Why is Undo a stack and a printer a queue?
5. A college needs structures for: (i) 200 integer marks, (ii) a playlist with frequent insertions, (iii) Undo in the fee-office editor, (iv) photocopier jobs, (v) the Principal–Dean–HOD chart, (vi) roads between Sindh cities. Identify each structure using the decision guide, draw the tree and the graph, and then trace retrieval of 20 from Array = [10, 50, 20, 70, 90, 30] and of 87 from the linked list 12→98→23→87→56→NULL.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

1. **2.1 Analyze algorithms for correctness.** Answers: 1. When its output matches the expected results for a given input (and does so for all valid inputs). 2. Trace tables and stepwise reasoning. 3. Because a logical error can still produce output — the wrong output.
2. **2.1.1 – 2.1.3 Trace Tables vs Stepwise Reasoning.** Answers: 1. Line/step number, variables, input/output, condition check. 2. 1.57 is the lower boundary (inclusive, so True); 1.48 is below 1.57 (False). 3. 3 is printed; Step 6 runs three times (for 1.91, 1.87 and 1.57).
3. **2.2 Evaluating the Clarity of an Algorithm.** Answers: 1. The algorithm is easy to read, understand and modify. 2. Modularity and readability. 3. Because a clear algorithm is easier to maintain, debug and extend over time.
4. **2.2.1 – 2.2.2 Modularity and Readability.** Answers: 1. One specific task. 2. CalculateSum (FindAverage only divides; the main program only prints). 3. All logic is in one block, so you cannot call “just the sum” from another algorithm.
5. **2.3 Assess Algorithm Efficiency.** Answers: 1. Time (speed) and space (memory). 2. Number of steps (Big O), number of conditions, number of repetitions.
6. **2.3.1 Number of Steps (Big O Notation).** Answers: 1. $O(1)$ arr[0]; $O(\log n)$ binary search; $O(n)$ linear search; $O(n^2)$ Bubble Sort / nested loops. 2. 1,024. 3. It makes about $\log n$ split-levels and does about n work on each level, so $n \times \log n$.
7. **2.3.2 Number of Conditions.** Answers: 1. Each condition must be evaluated True/False by the CPU. 2. A brute-force approach (and it reduces readability and speed). 3. AND short-circuits: the first part is False, so the division is never evaluated.
8. **2.3.3 Number of Repetitions.** Answers: 1. Poor — $O(n^2)$. 2. Each iteration halves the remaining problem, so the number of iterations is about $\log n$. 3. 25.
9. **2.3.4 The Efficiency Evaluation Framework.** Answers: 1. About 100× slower (10^2). 2. The most time-consuming section, usually the deepest loop. 3. Binary search is more complex to code and maintain, and for $n = 50$ the simplicity of $O(n)$ is practically better.
10. **2.4 Refinements to improve clarity and efficiency.** Answers: 1. average = totalSum / totalItems. 2. The already-sorted largest value at the end (shrink the inner loop). 3. Once, outside the loop, then reuse C inside.
11. **2.5 Concept of Data Structure.** Answers: 1. A systematic way of organising, storing and managing data for efficient access, modification and processing. 2. Linear: array, linked list, stack, queue. Non-linear: tree, graph. 3. It has exactly one predecessor and one successor.
12. **2.5.1 Linear Data Structures (Array, Linked List, Stack, Queue).** Answers: 1. The items sit in one continuous block, next to each other. 2. 12. 3. Later elements must all be shifted right to make room.
13. **2.5.2 Non-Linear Data Structures (Tree, Graph).** Answers: 1. The root. 2. One-to-many parent-child. 3. A family tree, and folders inside folders (or a college organogram).
14. **2.5.3 Operations on Data Structures.** Answers: 1. Insertion, deletion, traversal, searching, sorting. 2. Insertion (at the rear of a queue). 3. Traversal visits every item; searching stops when the target is found (or the structure ends).
15. **2.6 Identify data structures in problem scenarios.** Answers: 1. Array — known size, same type, fast index lookup. 2. Queue, because first-come, first-served. 3. Stack.
16. **2.7 Trace data retrieval in Array, List and Queue.** Answers: 1. 20. 2. Four (12, 98, 23, 87). 3. No — a queue only DEQUEUES the Front, so A must leave first.

Answer key

Multiple choice

1. b
2. a
3. d
4. b
5. a
6. c
7. d
8. a
9. d
10. c
11. d
12. c
13. a
14. b
15. c

Short questions — model answers

1. An algorithm is correct if its output matches the expected results for a given input (and does so for all valid inputs). The two methods are trace tables and stepwise reasoning (logic verification).
2. Components: line/step number, a column per variable, input/output, and a condition-check column. A dry run acts as the computer, so you see logical errors where the program runs but the values go wrong, and you can validate that the intention is met.
3. Trace table: small blocks/complex loops/beginners; high effort (bad for 1,000 iterations); catches arithmetic/line mistakes; micro-level exact values. Stepwise reasoning: large systems and proofs; moderate effort; catches conceptual/structural flaws; macro-level overall state.
4. Modularity is breaking an algorithm into smaller independent parts (functions, classes, modules). SRP: each module does one task. Coupling: modules should be loosely coupled so a change in one does not break others. Abstraction: hide inner details (call Sort without knowing Bubble vs Selection).
5. Naming conventions, self-documentation, simple control flow, consistency of indentation/spacing/casing. Bad: $v = d / t$. Good: `velocity = distance / time`.
6. Big O describes how time or memory grows as n grows. $O(1)$: `arr[0]`; $O(\log n)$: binary search; $O(n)$: linear search; $O(n \log n)$: Merge Sort; $O(n^2)$: Bubble Sort / nested loops.
7. Does it scale? $n = 50$ is tiny, even $O(n)$ is fine. Bottleneck? A single scan of 50 names. Worth it? Binary search needs sorted data and more complex code, so linear search is practically better.
8. Clarity: meaningful names; modules; structure/indentation; short why-comments. Efficiency: reduce extra steps (shrink Bubble Sort's inner loop); better algorithms (binary vs linear on sorted millions); avoid re-computing (cache $C = A+B$ outside the loop); appropriate data structures (array for direct access, tree for hierarchy).
9. A data structure is a systematic way of organising, storing and managing data for efficient access, modification and processing. Linear: sequence with one predecessor and one successor (array, linked list, stack, queue). Non-linear: hierarchical or network links (tree, graph).
10. Stack: LIFO; PUSH adds at TOP; POP removes from TOP; example Undo. Queue: FIFO; ENQUEUE adds at Rear; DEQUEUE removes from Front; example printer jobs.

Long questions — model answers

1. (a) Columns: Step, Total, Height, AllHeights, condition, output. Step 2 sets Total = 0. Step 3 stores the five heights. Then five loop cycles:

- 1.91 → True → Total 1
- 2.01 → False → Total stays 1
- 1.87 → True → Total 2
- 1.57 → True (boundary) → Total 3
- 1.48 → False → Total stays 3

(b) Printed Total = **3**.

(c) The condition is height ≥ 1.57 AND height ≤ 1.91 , so the closed interval includes both ends. 1.57 and 1.91 satisfy the inequalities; 2.01 and 1.48 do not. Initial Total = 0 is valid; each True branch adds one; False skips the add; after five items Total is the count of eligible soldiers.

(d) Python:

```
AllHeights = [1.91, 2.01, 1.87, 1.57, 1.48]
Total = 0
for height in AllHeights:
    if height >= 1.57 and height <= 1.91:
        Total = Total + 1
print(Total)
```

OUTPUT
3

2. (a) Monoblock: one sequence does the loop, the division and the print, so you cannot reuse the sum. Modular version: CalculateSum only adds; FindAverage only divides; main only prints. SRP holds. CalculateSum can be called from another program (loose coupling). Main does not see the loop (abstraction).

(b) Both compute total = 15 and avg = $15/5 = 3.0$.

```
def calculate_sum(A, n):
    total = 0
    for i in range(n):
        total = total + A[i]
    return total

def find_average(A, n):
    return calculate_sum(A, n) / n

print(find_average([1, 2, 3, 4, 5], 5))
```

OUTPUT
3.0

(c) Keep snake_case names; avoid 1-based I in Python; a one-line comment on why you divide by n (empty-list guard could be added later) is enough — do not comment every addition.

3. (a) Growth ($\log_2$):

n	$O(1)$	$O(\log n)$	$O(n)$	$O(n \log n)$	$O(n^2)$
8	1	3	8	24	64
32	1	5	32	160	1,024

(b) $O(n)$: 10× input → about 10× time. $O(n^2)$: 10× input → about 100× time, which fails for large sets.

(c) Scale: a million IDs; linear worst case is a million checks, binary about 20. Bottleneck: the search. Worth it: the IDs are already sorted and binary search is standard, so choose **binary search** $O(\log n)$.

(d)

```
n = 4
count = 0
for i in range(n):
    for j in range(n):
        count = count + 1
print(count)
```

OUTPUT
16

4. Draw the vertical stack with TOP on Data3 after three PUSHes, and the horizontal queue with FRONT on 55 and REAR on 90 (then D).

(a) Stack: [] → [Data1] → [Data1, Data2] → [Data1, Data2, Data3] → POP Data3 → POP Data2 → [Data1].

```
stack = []
stack.append("Data1")
stack.append("Data2")
stack.append("Data3")
print(stack.pop())
print(stack.pop())
print(stack)
```

OUTPUT
Data3
Data2
['Data1']

(b) Queue: [55] → [55, 76] → [55, 76, 90] → [55, 76, 90, D] → DEQUEUE 55 → [76, 90, D].

```
from collections import deque
q = deque()
q.append(55)
q.append(76)
q.append(90)
q.append("D")
print(q.popleft())
print(list(q))
```

OUTPUT
55
[76, 90, 'D']

(c) Undo must cancel the most recent action (LIFO → stack). A printer must respect arrival order (FIFO → queue).

5. (i) Array — known count, same type, index lookup. (ii) Linked list — next-pointer, cheap insert. (iii) Stack — reverse order of entry. (iv) Queue — first-come, first-served. (v) Tree — parent-child from the Principal root (Administrative Head / Academic Dean, then Accounts, HR, HOD Math, HOD CS). (vi) Graph — cities as vertices, roads as edges, alternative routes.

Array retrieval: Array[2] = 20 in one direct access (or after visiting 10 then 50 then 20 if you scan).

List retrieval: Step1 12 ≠ 87, Step2 98 ≠ 87, Step3 23 ≠ 87, Step4 87 = 87 FOUND True.

Self-assessment: I can...

- ☐ prove correctness with a full trace table, including boundary values.
- ☐ judge modularity (SRP, coupling, abstraction) and readability (N-S-S-C).
- ☐ apply the Scale / Bottleneck / Worth-it framework, including the $n = 50$ warning.
- ☐ define a data structure and classify linear vs non-linear.
- ☐ draw a tree and a graph and pick a structure from a scenario using the decision guide.
- ☐ write stepwise reasoning (start, loop, finish, edges) and compare it with a trace table.
- ☐ state $O(1)$, $O(\log n)$, $O(n)$, $O(n \log n)$ and $O(n^2)$ with examples and a growth table.
- ☐ refine an algorithm for names, modules, fewer loop steps and cached values.
- ☐ draw and trace an array, linked list, stack (PUSH/POP) and queue (ENQUEUE/DEQUEUE).
- ☐ trace retrieval: array jump, list walk from HEAD, queue Front only.

Lecture 03

Programming Fundamentals

Chapter lecture — 17 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XII · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — بارہویں جماعت

17 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XII

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیئریر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

Lectures in this pack

Chapter 3: Programming Fundamentals. Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 3.1 Data Structures in Python

L03. 3.1.2 Tuples (Ordered, Immutable)

L05. 3.1.4 Dictionaries (Key-Value pairs)

L07. 3.1.6 Activity: Students Attendance Program

L09. 3.2 Functions in Python

L11. 3.2.2 Functions with Return Values

L13. 3.2.4 Scope of Local and Global Variables

L15. 3.6 with Statement (Context Manager)

L17. 3.9 Mini File Handling Project: Grade Tracker

L02. 3.1.1 Lists (Ordered, Mutable, Methods)

L04. 3.1.3 Sets (Unordered, Unique, Math Operations)

L06. 3.1.5 Common Built-in Functions (min, max, len, sum)

L08. 3.1.7 Activity: Word Frequency Counter

L10. 3.2.1 Types of Functions (Built-in vs User-defined)

L12. 3.2.3 Activity: Arithmetic Calculator Using Functions

L14. 3.3 & 3.4 File Handling and Operations (Modes r, w, a)

L16. 3.8 Errors and Exceptions (Try-Except)

Programming Fundamentals

This chapter teaches you how Python stores collections of data, how you write reusable functions, and how you save information in files so it is still there after the program ends. You will build small programs — attendance, a word counter, a calculator, and a grade tracker — that you can type and run yourself.

اس باب میں آپ سیکھیں گے کہ پائتھن (Python) ڈیٹا کو فہرست، ٹیپل، سیٹ اور ڈکشنری میں کیسے رکھتا ہے، فنکشن کیسے لکھے جاتے ہیں، اور فائلوں میں ڈیٹا کیسے محفوظ کیا جاتا ہے تاکہ پروگرام بند ہونے کے بعد بھی وہ موجود رہے۔

What you will learn

- Distinguish primitive types from abstract data structures (list, tuple, set, dictionary).
- Use tuples as ordered, immutable collections, including indexing and the two tuple methods.
- Store and retrieve key–value data with dictionaries, including safe access with `.get()`.
- Write user-defined functions with parameters and `return` values, and contrast them with built-in functions.
- Open text files in modes `r`, `w` and `a`, and close them safely with `with`.
- Create, index, slice, traverse and update lists using the main list methods.
- Build sets of unique items and compute union, intersection, difference and symmetric difference.
- Apply `min()`, `max()`, `len()`, `sum()` and `sorted()` across data structures.
- Explain local and global variable scope with short programs.
- Catch file errors with `try / except` and complete a grade-tracker file project.

3.1 Data Structures in Python

LEARN IT

A **data structure** is a way of organising values in a program so you can store them, find them and change them. Every useful program is built on data structures. Python gives you two layers:

- **Primitive data structures** — the basic types that hold **one** value. Examples: integers (`int`), floating-point numbers (`float`), and booleans (`bool`).
- **Abstract data structures** — higher-level containers built from primitive types so you can hold **many** values and run richer operations. Examples: **lists**, **tuples**, **sets**, **dictionaries**.

Python has these four abstract structures built in. You do not install anything extra. That is why collecting marks, names or settings is simpler in Python than in many other languages.

Category	Description	Examples
Primitive	Basic types that represent a single value.	<code>int</code> , <code>float</code> , <code>bool</code>
Abstract	Higher-level structures for collections and complex operations.	Lists, tuples, sets, dictionaries

WORKED EXAMPLE

One value versus a collection. A student's age is one integer. That student's three test marks need a list.

```
age = 17
height = 5.8
passed = True
marks = [80, 75, 90]
print(type(age))
print(type(height))
print(type(passed))
print(type(marks))
```

OUTPUT

```
<class 'int'>
<class 'float'>
<class 'bool'>
<class 'list'>
```

`type()` tells you which structure a value has. `age` is a primitive integer. `marks` is an abstract list that holds three integers together.

REMEMBER IT

Primitive = one piece. Abstract = a box of pieces. Think of a single rupee coin (primitive) versus a wallet that can hold many coins (list, tuple, set or dictionary).

COMMON MISTAKE

Do not call a list a "variable type" and stop there. A list is a **structure**: it has an order, methods, and rules. The four abstract structures look similar at first (they all hold several values) but they follow different rules. Learn those rules one by one in 3.1.1-3.1.4.

اردو میں سمجھیں

ڈیٹا سٹرکچر (Data Structure) پروگرام میں ڈیٹا کو ترتیب دینے کا طریقہ ہے۔ پرائیمینو اقسام جیسے عدد (int) صرف ایک قیمت رکھتی ہیں، جبکہ فرسٹ، ٹیبل، سیٹ اور ڈکشنری کئی قیمتیں ایک ساتھ سنبھالتی ہیں۔ پانٹھن میں یہ چاروں سٹرکچرز پہلے سے موجود ہیں، اس لیے ڈیٹا جمع کرنا دوسری زبانوں کے مقابلے میں آسان ہے۔

CHECK YOURSELF

1. Name two primitive types and two abstract data structures in Python.

2. Why is a list called an abstract data structure rather than a primitive type?

Answers: 1. Primitive: any two of int, float, bool. Abstract: any two of list, tuple, set, dictionary. 2. Because it is a higher-level container built from primitive values, holding many items and supporting operations such as append and slice.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Python built-in structures in this chapter include:

a. list, tuple, set, dict

b. only arrays of C

c. only trees

d. only graphs

MCQ 2. You choose among them by:

a. Order? Duplicates? Mutability? Key lookup?

b. The logo

c. The font

d. The sprint

MCQ 3. Mutable means:

a. You can change it in place

b. Frozen forever

c. Always sorted

d. Always unique

MCQ 4. A dict maps:

a. Keys to values

b. Only numbers to NAND

c. Only OSI layers

d. Only files

MCQ 5. A set is best for:

a. Unique items / membership tests

b. Ordered ranking with duplicates

c. LIFO

d. FIFO

MCQ 6. This lecture is the map; later lectures:

a. Zoom into each type

b. Delete Python

c. Draw only ER

d. Draw only Figma

Extra short questions

1. One-line each: list, tuple, set, dict.

2. Which for student names that may repeat seats?

3. Which for a record of roll→marks?

4. Which as a function return of (x,y) that must not change?

Extra long question

1. Four college needs → choose the Python DS and justify with one operation each.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. List: ordered mutable sequence. Tuple: ordered immutable. Set: unique unordered. Dict: key→value.

2. List (order). If unique roll numbers: set or dict.

3. Dict.

4. Tuple.

Long

1. Attendance ordered: list. RGB colour constant: tuple. Club unique IDs: set. Phonebook: dict. Show one line of code each.

3.1.2 Tuples (Ordered, Immutable) 🔒 LOCKED

LEARN IT

A **tuple** is an ordered collection that is **immutable** — once created, you cannot add, remove or replace items. Think of it as a **read-only list**. Tuples use **parentheses** `()`. Like lists, they allow duplicates, mixed types, and indexing from 0 (including negative indices).

List []
Can add / remove / replace

Tuple ()
LOCKED — read-only

A list is an open box you can refill. A tuple is a sealed box you may only look into.

```
t = (10, 20, 30, 40, 50)
print(t[0])
print(t[-2])
print(t[1:4])
print(t[::-1])
```

```
OUTPUT
10
50
(50, 40, 30, 20, 10)
```

Slicing a tuple returns a **new tuple**, not a list. Negative indexing and `[::-1]` work exactly as they do for lists.

Immutability

You cannot assign to an index of a tuple. Python raises `TypeError`.

```
t = (1, 2, 3)
t[0] = 99
```

```
OUTPUT
Traceback (most recent call last):
  File "tuple.py", line 2, in <module>
    t[0] = 99
TypeError: 'tuple' object does not support item assignment
```

Exception: if a tuple contains a **mutable object** (a list inside the tuple), that inner object's contents can still change. The tuple still holds the same two list objects; you changed a list, not the tuple's structure.

```
t = ((1, 2), [3, 4])
t[0].append(99)
print(t)
```

```
OUTPUT
((1, 2, 99), [3, 4])
```

`t[0] = [9, 9]` would still be illegal, because that would replace the tuple's first item. `t[0].append(99)` is legal because it mutates the list that already lives at index 0.

Traversal and methods

Traverse a tuple with `for`, just as you do a list. You are only reading, which is the usual reason to choose a tuple.

```
student = ("Ali", 20, "Computer Science")
for item in student:
    print(item)
```

```
OUTPUT
Ali
20
Computer Science
```

Because a tuple cannot grow or shrink, it has only two methods:

Method	Meaning
<code>.count(value)</code>	How many times the value appears.
<code>.index(value)</code>	Index of the first occurrence.

```
t = (10, 20, 10, 20, 20, 10)
print(t.count(10))
print(t.index(20))
```

```
OUTPUT
3
1
```

Advantages of tuples

Protection — coordinates, identity-card numbers or settings cannot be changed by accident.

Speed — a fixed-size tuple is processed slightly faster than a list.

Hashable keys — a tuple of immutables can be used as a dictionary key; a list cannot. (You will use dictionaries in 3.1.4.)

WORKED EXAMPLE

When to choose a tuple. A student's roll number, name and class form a record that should not be edited in place:

```
record = ("111-15-07", "Ayesha", "Computer Science")
print(record[0])
print(len(record))
```

```
OUTPUT
111-15-07
3
```

If later you need to change the class, you build a **new tuple**. You do not assign to `record[2]`.

REMEMBER IT

Tuple = locked lunchbox. You can see what is inside; you cannot swap the sandwich. Memory: "Tuple is Tight (immutable), written with round brackets that look like a hug holding the data still."

COMMON MISTAKE

One-item trap: `(5)` is just the integer 5 with extra parentheses. A one-item tuple needs a trailing comma: `(5,)`.

```
t1 = (5)
t2 = (5,)
print(type(t1), t1)
print(type(t2), t2)
```

```
OUTPUT
<class 'int'> 5
<class 'tuple'> (5,)
```

An empty tuple is `()`.

آپ کو میں سمجھیں

توپل (Tuple) کوں پرکھتہ () میں لکھا جاتا ہے تو توبہ رکھتا ہے مگر تبدیل نہیں ہو سکتا (Immutable)، انڈیکس اور سلاش فرسٹ جیسی ہیں لیکن t[0] = 99 جیسے TypeError آتا ہے۔ صرف دو مینٹاز ہیں: count() اور index()۔ حساس ڈیٹا کے لیے ٹوپل محفوظ ہے اگر لیبل کے اندر فرسٹ ہو تو اس فرسٹ کے اندر کی ادبیاء بدل سکتی ہیں۔

EXAM TIP

Expect "Differentiate list and tuple" (at least four points: brackets, mutability, methods, speed/protection), "Why use a tuple?", and "What happens if you write `t[0] = 1`?" Quote the `TypeError` wording. Mention the inner-list exception if the question is a 6-mark "explain with example." A one-item tuple `(5,)` is a favourite trick question.

CHECK YOURSELF

1. Name the two tuple methods.

2. What error does `t[0] = 99` raise for a tuple?

3. After `t = ((1, 2), [3, 4]); t[0].append(99)`, what is `t`?

Answers: 1. count and index. 2. `TypeError: 'tuple' object does not support item assignment`. 3. `((1, 2, 99), [3, 4])`.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A tuple is:

- a. Ordered and immutable
- b. Mutable like a list
- c. A set of unique keys
- d. A file mode

MCQ 2. `{0}:-5` on a tuple:

- a. `TypeError`
- b. Works
- c. Deletes `t`
- d. Converts to list silently always

MCQ 3. Why immutability?

- a. Safe so dict keys, after returns, can be hashed
- b. It makes tuples faster than CPls
- c. It allows append()
- d. It stores files

MCQ 4. A 1-item tuple is written:

- a. `(1)`
- b. `a=(1,2)`
- c. `[5]`
- d. `{5}`

MCQ 5. Unpacking `a,b = (1,2)` sets:

- a. `a=1, b=2`
- b. `a=(1,2)`
- c. Syntax error
- d. `a=2`

MCQ 6. tuple methods include:

- a. count, index
- b. append, sort
- c. add, discard
- d. keys, items

Extra short questions

1. Define tuple and one use.
2. How to "change" a tuple?
3. Why `(5)` not `[5]`?
4. Can a tuple contain a list?

Extra long question

1. Write code that stores student (name, roll) tuples in a list, prints each, and explain two errors: mutate the tuple; forget the comma in a 1-tuple.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Immutable ordered sequence. RGB colour; returning two values.
2. Build a new one, or convert to list, change, convert back.
3. `(5)` is just int 5; comma makes a tuple.
4. Yes — the tuple's slots cannot be rebound, but the inner list can still mutate (a subtle exam point).

Long

1. records.append("Ali", 123). for `n, r` in records. `t[0] = ...` `TypeError: (5) vs (5,)`. 10-mark with output.

3.1.3 Sets (Unordered, Unique, Math Operations)

LEARN IT

A set stores an **unordered, unindexed** collection of **unique** elements. It is inspired by mathematical sets. You write a set with **curly braces** {}. Duplicates are removed as soon as the set is created. Because there is no index, `myset[0]` is illegal.

The set itself is **mutable** (you can add and remove items). Each item inside must be **immutable** (numbers, strings, tuples of immutables — not lists).

```
myset = {1, 4, 3, 3, 3, 2, 2}
print(myset)
```

```
myset = {1, 2, 3, 4}

# Output
{1, 2, 3, 4}
```

Adding and removing

Method	Description
<code>.add(value)</code>	Adds one element.
<code>.update(values)</code>	Adds many elements from a list, tuple or set.
<code>.remove(value)</code>	Removes the value. <code>RuntimeError</code> if it's missing.
<code>.discard(value)</code>	Removes the value. Does not crash if it's missing.
<code>.clear()</code>	Removes every element. Result is: <code>set()</code> .

```
s = {1, 2, 3}
s.add(4)
print(s)
s.update([5, 6])
print(s)
s.discard(99)
print(s)
s.remove(2)
print(s)
s.clear()
print(s)
```

```
# Output
{1, 2, 3, 4}
{1, 2, 3, 4, 5, 6}
{1, 2, 3, 4, 5, 6}
{1, 2, 3, 4, 5, 6}
{1, 2, 3, 4, 5, 6}
set()
```

discard(99) quietly does nothing. After clear() Python prints set(), not {}, because {} already means an empty **dictionary**.

Compare with `.remove(99)` on a set that does not contain 99:

```
s = {1, 2, 3}
s.remove(99)
```

```
# Output
Traceback (most recent call last):
  File "test_remove.py", line 2, in <module>
    s.remove(99)
RuntimeError: 99
```

Prefer `.discard()` when the item might not be there, so a missing value does not crash the program.

Mathematical operations

Sets are built for union, intersection, difference and symmetric difference.

Set A

2

Set B

5

1, 2, 3, 4, 5, 6

1, 2, 3, 4, 5, 6

Overlap (3, 4) is the intersection. Left-only (1, 2) is A - B. Right-only (5, 6) is B - A.

Operation	Meaning	Python	Result for A & B above
Union	All unique items from both	<code>A B</code> or <code>A.union(B)</code>	{1, 2, 3, 4, 5, 6}
Intersection	Items in both	<code>A & B</code> or <code>A.intersection(B)</code>	{3, 4}
Difference	B \ A, not in B	<code>A - B</code> or <code>A.difference(B)</code>	{1, 2}
Symmetric difference	In either, but not both	<code>A ^ B</code> or <code>A.symmetric_difference(B)</code>	{1, 2, 5, 6}

```
A = {1, 2, 3, 4}
B = {3, 4, 5, 6}
print(A | B)
print(A & B)
print(A - B)
print(A ^ B)
```

```
# Output
{1, 2, 3, 4, 5, 6}
{3, 4}
{1, 2}
{1, 2, 5, 6}
```

B - A would be {5, 6} — difference is not symmetric. Symmetric difference A ^ B is (A - B) | (B - A).

Set traversal

There is no index, so you loop with `for`. Print order is not guaranteed. Use `sorted()` when you need a stable alphabetical or numerical order (it returns a `list`).

```
colors = ["red", "green", "blue"]
for color in sorted(colors):
    print(color)
```

```
# Output
blue
green
red
```

WORKED EXAMPLE

Deduplication. A teacher types roll numbers and some are repeated. A set keeps each roll once:

```
rolls = [12, 5, 12, 8, 5, 19]
unique = set(rolls)
print(unique)
print(sorted(unique))
```

```
# Output
{5, 8, 12, 19}
[5, 8, 12, 19]
```

`set(rolls)` drops duplicates. `sorted(unique)` gives a list in numeric order for a register.

REMEMBER IT

SET = Same-Item Twice-never. Empty set is `set()`, never `{}.` Sets `delete = discard`; angry `delete = remove`.

COMMON MISTAKE

`myset[0]` raises `TypeError` because sets are unindexed. Convert with `list(myset)` only if you accept that the order is arbitrary. Do not put a list inside a set — lists are mutable, so they cannot be set elements.

آردو میں سمجھیں

سٹ (Set) مندرجہ عناصر یا پھر ترتیب اور پھر انڈیکس مجموعہ ہے جو {} میں لکھا جاتا ہے۔ دہرائی ہوئی قیمتیں خود بخود ختم ہو جاتی ہیں۔ .add() اور .update() عناصر جوڑتی ہیں۔ .discard() محفوظ طریقے سے ہٹاتا ہے جبکہ .remove() غیر موجود عنصر پر KeyError پیدا کرتا ہے۔ اشتراک (Intersection) &، فرق - اور متوازی فرق ^ یہاں تک کارروائی ہیں۔

CHECK YOURSELF

1. What is printed by `print({1, 4, 3, 3, 2, 2})` ?

2. Why prefer `.discard()` over `.remove()` ?

3. If A = {1, 2, 3, 4} and B = {3, 4, 5, 6}, what is A ^ B ?

Answers: 1. {1, 2, 3, 4} (duplicates removed; order may vary). 2. `discard` does not raise `KeyError` if the value is missing. 3. {1, 2, 5, 6}.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A set holds:

a. Unique unordered items

b. Ordered duplicates

c. Key-value pairs

d. File handles only

MCQ 2. {1,2,2,3} becomes:

a. {1,2,3}

b. {1,2,2,3}

c. {1,2,2,3}

d. {1,2,2,3}

MCQ 3. s.add is for:

a. Insert (no-op if present)

b. Append at index 0

c. Sort

d. Open a file

MCQ 4. Union of {1,2} and {2,3} is:

a. {1,2,3}

b. {2}

c. {1}

d. {}

MCQ 5. You cannot:

a. Index s[0] on a set

b. Iterate a set

c. Test x in s

d. Compute intersection

MCQ 6. Sets are great for:

a. Membership and unique collections

b. FIFO queues

c. LIFO undo

d. Stable sorted ranks with duplicates

Extra short questions

1. Define set and two operations.

2. Why no index?

3. How to make unique names from a list?

4. Empty set syntax?

Extra long question

1. Two clubs A and B as sets. Write Python for members in both, only A, either. Show a sample.

Extra answer key

MCQs: 1. A, 2. A, 3. A, 4. A, 5. A, 6. A

Short

1. Unordered unique, union | intersection & difference -.

2. No order — use a loop, not s[0].

3. set(names) — order lost.

4. set() not {} (that is a dict).

Long

1. A-B, A-B, A\B. Sample Ali/Sara. Mention add/discard. One exam warning: {} is dict.

7

3.1.5 Common Built-in Functions (min, max, len, sum)

LEARN IT

Several built-in functions work across lists, tuples, sets and dictionaries. You do not call them with a dot on the object (except when a type also has its own method, such as list.sort()).

Function	Purpose	Works on
min()	Smallest element (numeric or alphabetical)	List, tuple, set, dictionary keys
max()	Largest element	List, tuple, set, dictionary keys
len()	Number of elements (for a dict: number of keys)	List, tuple, set, dictionary
sum()	Adds numeric elements	List, tuple, set, dictionary values via sum(d.values())
sorted()	Returns a new sorted list ; original unchanged	List, tuple, set, dictionary keys

```
s = {5, 1, 9, 3, 7}
print(len(s))
print(min(s))
print(max(s))
print(sum(s))
print(sorted(s))
```

```
OUTPUT
5
1
9
25
[1, 3, 5, 7, 9]
```

5 + 1 + 9 + 3 + 7 = 25. sorted(s) always returns a **list**, even when the input is a set.

WORKED EXAMPLE

The same five functions on four structures.

```
nums = [8, 3, 5, 3]
t = (8, 3, 5, 3)
s = {8, 3, 5}
d = {"math": 80, "eng": 70, "cs": 90}
print(len(nums), min(nums), max(nums), sum(nums), sorted(nums))
print(len(t), min(t), max(t), sum(t), sorted(t))
print(len(s), min(s), max(s), sum(s), sorted(s))
print(len(d), min(d), max(d), sum(d.values()), sorted(d))
```

```
OUTPUT
4 3 8 19 [3, 3, 5, 8]
4 3 8 19 [3, 3, 5, 8]
3 3 8 16 [3, 5, 8]
3 cs math 240 ['cs', 'eng', 'math']
```

On the dictionary, min(d) and max(d) compare **keys as strings**: "cs" comes first alphabetically, "math" last. sum(d) would try to add the keys "math" + "eng" + ... and fail. Use sum(d.values()) — 80 + 70 + 90 = 240. The set dropped the duplicate 3, so len(s) is 3 and sum(s) is 16.

sorted() versus .sort()

```
original = [8, 3, 5]
print("before sort:", original)
print("sorted():", sorted(original))
print("after sorted():", original)
original.sort()
print("after .sort():", original)
```

```
OUTPUT
before sort: [8, 3, 5]
sorted(): [3, 5, 8]
after sorted(): [8, 3, 5]
after .sort(): [3, 5, 8]
```

.sort() exists only on lists and rewrites the original. sorted() works on any iterable and leaves the original alone.

REMEMBER IT

LEN-MIN-MAX-SUM — count, smallest, largest, total. For a dictionary: len/min/max/ sorted use **keys**; sum needs .values().

COMMON MISTAKE

sum() needs numbers. sum(["a", "b"]) raises TypeError. Empty structures: len({}) is 0, but min({}) and max({}) raise ValueError because there is no smallest of nothing.

آرڈو میں سمجھیں

len() عناصر گنتا ہے، min() سب سے چھوٹا، max() سب سے بڑا، sum() اعداد کا مجموعہ، اور sorted() نئی ترتیب شدہ فہرست دیتا ہے بغیر اصل کو بدلے ہیں۔ دکھائی پر min اور max کلیدوں پر چلتے ہیں؛ قدروں کا مجموعہ sum(d.values()) سے نکالیں۔ .sort() صرف فہرست کا متبعہ ہے جو اصل فہرست بدل دیتا ہے۔

CHECK YOURSELF

1. For s = {5, 1, 9, 3, 7}, what are len(s), min(s), max(s), sum(s)?
2. Does sorted(s) return a set or a list?
3. How do you total the values of {"math": 80, "eng": 70, "cs": 90}?

Answers: 1. 5, 1, 9, 25. 2. A list: [1, 3, 5, 7, 9]. 3. sum(d.values()) → 240.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. len(x) works on:

a. Sequences and many collections
b. Only ints
c. Only files
d. Only NAND

MCQ 2. min([3,1,2]) is:

a. 1
b. 3
c. 2
d. 6

MCQ 3. sum([1,2,3]) is:

a. 6
b. 123
c. Error always
d. {1,2,3}

MCQ 4. max on a dict without a key function uses:

a. Keys (careful!)
b. Values always
c. Lengths always
d. Random

MCQ 5. These functions expect:

a. Non-empty for min/max
b. Always empty
c. Only sets
d. Only files

MCQ 6. len("CS") is:

a. 2
b. 1
c. 0
d. 3

Extra short questions

1. Four built-ins and a type they work on.
2. What happens min({})?
3. sum of a list of strings?
4. len vs count in a list.

Extra long question

1. Given marks = [70, 80, 90] write expressions for n, total, mean, best, worst using built-ins. Show values. Warn about empty lists.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. len list; min tuple; max set; sum list of numbers.
2. ValueError.
3. TypeError — sum starts at 0.
4. len whole length; count(x) occurrences of x.

Long

1. n=len=3; sum=240; mean=80; max=90; min=70. Empty: don't divide; min/max error. Link to Ch 4 statistics.

9

3.1.6 Activity: Students Attendance Program

LEARN IT
Teachers need a quick way to mark who is in class. This program stores names in a **list**, asks about each student, counts how many said yes, and prints a summary with `len()`.

Store names in a list → Ask present? for each → Count yes → Print totals

```
students = ["Ali", "Sara", "Ayesha"]
present_count = 0
print("--- Attendance System ---\n")
for student in students:
    status = input(f"Is {student} present? (yes/no): ").lower()
    if status == "yes":
        present_count += 1
print("\n--- Attendance Summary ---")
print("Total Students:", len(students))
print("Students Present:", present_count)
print("Students Absent:", len(students) - present_count)
```

WORKED EXAMPLE
Sample run. Ali yes, Sara no, Ayesha yes. `.lower()` means YES or Yes still counts as present.

```
OUTPUT
--- Attendance System ---

Is Ali present? (yes/no): yes
Is Sara present? (yes/no): no
Is Ayesha present? (yes/no): yes

--- Attendance Summary ---
Total Students: 3
Students Present: 2
Students Absent: 1
```

Student	Typed answer	After <code>.lower()</code>	Count
Ali	yes	yes → add 1	1
Sara	no	not yes	1
Ayesha	yes	yes → add 1	2

`Absent = len(students) - present_count = 3 - 2 = 1`. The counter must start at 0 **before** the loop. If you put `present_count = 0` inside the loop, the count would reset for every student.

REMEMBER IT
Counter pattern: start at 0, loop, add 1 when a condition is true. You will reuse this in the word-frequency program (add 1 per word) and the grade tracker (add each mark).

COMMON MISTAKE
Only the exact string "yes" after `.lower()` counts as present. "y" or "present" is treated as absent. In a longer program you could also accept "y"; this activity keeps the rule simple.

اردو میں سمجھیں

حاضری کا پروگرام طلبہ کے نام ایک فہرست میں رکھتا ہے، ہر نام کے لیے پوچھتا ہے، اور yes پر شمار کار (Counter) ایک بڑھاتا ہے۔ کل طلبہ `len(students)` سے، غیر حاضر کل - حاضر سے نکلتے ہیں۔ شمار کار لوپ سے پہلے صفر ہونا چاہیے۔

- CHECK YOURSELF**
- If all three students type `no`, what is printed for present and absent?
 - Why is `.lower()` used on the answer?

Answers: 1. Present 0, Absent 3. 2. So that YES, Yes and yes all match the string "yes".

Extra board practice
These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A sensible structure for present/absent flags by name is:

- dict name → status or two lists/sets
- a pie without data
- A NAND net
- An OSI capture

MCQ 2. You should still:

- Validate input (yes/no)
- Trust any string
- Use `eval`
- Open the OS

MCQ 3. Printing a report uses:

- A loop over the collection
- A single print of the object id
- TCP
- Figma

MCQ 4. This activity combines:

- DS + input + selection + repetition
- Only HCI colours
- Only ER
- Only Big O proofs

MCQ 5. A set of absentees is useful to:

- Unique names, fast membership
- Keep duplicate absences as a stack
- FIFO print jobs
- Store key-value marks

MCQ 6. Never store:

- Passwords in the same toy script unprotected
- Names
- P/A flags
- Dates

- Extra short questions**
- Outline the attendance program's data and loop.
 - Two Python DS options.
 - How do you count presents?
 - One improvement for XII files.

- Extra long question**
- Write a complete small attendance program for 3 names using a dict, print a tidy table, and a sample run.

Extra answer key
MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- For each student: ask status; store; then print counts.
- `dict[str, str]` or `present_set/absent_set`.
- Counter in the loop or `list.count / sum(1 for ...)`.
- Save to a text file with `with-open`.

Long

- Working code, output, and one validation (only P/A). Mention a logic error if you forget to store.

3.1.7 Activity: Word Frequency Counter

LEARN IT

Count how many times each word appears in a sentence. This is a classic use of a **dictionary** plus `.get()`: the word is the key, the count is the value.

```
sentence = "python is easy python is fun python is powerful"
words = sentence.split()
word_freq = {}
for word in words:
    word_freq[word] = word_freq.get(word, 0) + 1
print(f"Sentence: '{sentence}'\n")
print("Word Frequency Table:")
for word, count in word_freq.items():
    print(f"{word:<10} : {count}")
top_word = max(word_freq, key=word_freq.get)
print(f"\nMost Frequent: '{top_word}' ({word_freq[top_word]} times)")
```

WORKED EXAMPLE

Logic, step by step.

1. `sentence.split()` cuts on spaces and gives
['python', 'is', 'easy', 'python', 'is', 'fun', 'python', 'is', 'powerful'].

2. For a new word, `word_freq.get(word, 0)` is 0, then you store `0 + 1 = 1`.

3. For a word already in the dictionary, `.get(word, 0)` returns the current count, then you add 1.

4. `{word:<10}` pads the word to 10 characters so the colons line up.

5. `max(word_freq, key=word_freq.get)` picks the key whose value is largest. If two words share the top count, `max` returns the first of those keys in insertion order.

OUTPUT

Sentence: 'python is easy python is fun python is powerful'

Word Frequency Table:

python : 3

is : 3

easy : 1

fun : 1

powerful : 1

Most Frequent: 'python' (3 times)

After seeing	
python	{'python': 1}
is	{'python': 1, 'is': 1}
easy	{'python': 1, 'is': 1, 'easy': 1}
python (again)	{'python': 2, 'is': 1, 'easy': 1}
... end of sentence	{'python': 3, 'is': 3, 'easy': 1, 'fun': 1, 'powerful': 1}

Here `python` and `is` both occur 3 times. `max` returns `'python'` because it appears first in the dictionary.

REMEMBER IT

The heart of every counter is one line: `d[item] = d.get(item, 0) + 1`. You can count letters, roll numbers or votes with the same pattern.

COMMON MISTAKE

This program is case-sensitive and space-based. `"Python"` and `"python"` would be two keys. Punctuation such as `easy.` would not match `easy`. For a class exercise, keep the sentence lowercase with spaces only, as here. If you wrote `word_freq[word] += 1` without `.get` on a new word, you would get `KeyError`.

اردو میں سمجھیں

جملے کو `.split()` سے الفاظ کی فہرست بنائے ہیں، پھر ہر لفظ ڈکشنری میں کلید ہوتا ہے اور اسی کی گنتی قدر نئے لفظ کے لیے `.get(word, 0) + 1` سے گنتی 1 سے شروع ہوتی ہے۔ `max(..., key=word_freq.get)` سب سے زیادہ بار آنے والا لفظ دیتا ہے۔

CHECK YOURSELF

1. How many times does "is" occur in the sample sentence?

2. Why use `.get(word, 0)` instead of `word_freq[word]` on the right-hand side?

Answers: 1. Three times. 2. Because a brand-new word is not yet a key; `.get` returns 0 instead of raising `KeyError`.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Word frequency uses a dict as:

a. word → count

b. count → word only

c. A stack of letters

d. A queue of files

MCQ 2. A standard pattern is:

a. `d[w] = d.get(w,0)+1`

b. sort first always $O(n^2)$

c. binary search the sentence

d. draw OSI

MCQ 3. You usually:

a. `split()` and maybe `lower()`

b. Keep punctuation attached always

c. Use a set so counts die

d. Use a tuple of counts you cannot update

MCQ 4. `split("a a b")` has length:

a. 3

b. 2

c. 1

d. 0

MCQ 5. This activity shows:

a. Dicts + loops + strings

b. Only Access reports

c. Only NAND

d. Only HCI

MCQ 6. Most frequent word is:

a. The key with max count

b. Always the first word

c. Always the last

d. A foreign key

Extra short questions

1. Write the counting pattern.

2. How to print nicely.

3. A limitation of naive `split`.

4. Why a dict not a list of pairs?

Extra long question

1. Count words in "to be or not to be". Show the dict, then the mode word(s). Full code.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. for w in text.lower().split(): d[w]=d.get(w,0)+1

2. for k,v in d.items(): print(k,v) or sorted by count.

3. Punctuation ("hello,") is a different word.

4. $O(1)$ average update by word.

Long

1. to:2 be:2 or:1 not:1. Bimodal to/be. Code with `get`. Mention `lower()`.

11

3.2 Functions in Python ★ Golden

LEARN IT
When the same instructions are written again and again, that is **duplicate code**. Duplicate code makes a program longer, harder to read, and painful to update (you must fix every copy). A **function** lets you write the instructions **once** and run them whenever you call the function's name.

Benefit	Meaning
Code reusability	Write once, use anywhere.
Modularity	Break a big problem into small named tasks.
Readability	Shorter, cleaner files with meaningful names.
Maintainability	Fix a bug in one place and every call is fixed.

```
def greet():  
    print("Hello, World!")  
  
greet()  
greet()
```

OUTPUT
Hello, World!
Hello, World!

The body is written once. Two calls run it twice. To change the message you edit one line inside `greet`.

Key components of a function



- **Keyword** — Python uses `def` to start a definition.
- **Function name** — the identifier you call, e.g. `greet`.
- **Parameters** — input names inside the parentheses. When you call the function, the values you pass are called **arguments**.
- **Body** — the indented block that runs on each call.
- **Return statement** — sends a result back to the caller (3.2.2).

```
def add(a, b):  
    print(f"Adding {a} + {b}")  
    return a + b  
  
result = add(4, 6)  
print(result)
```

OUTPUT
Adding 4 + 6
10

Here `a` and `b` are parameters. `4` and `6` are arguments. `return a + b` sends 10 back, and that 10 is stored in `result`.

WORKED EXAMPLE
Without a function you would copy the print-and-add lines every time you needed a sum. With a function, a new sum is one call: `add(10, 20)`, `add(1.5, 2.5)`.

REMEMBER IT
DRY — Don't Repeat Yourself. If you are about to copy-paste a block, wrap it in `def`. Name functions with verbs: `greet`, `add`, `save_grades`.

COMMON MISTAKE
Defining is not calling. After `def greet()`: nothing prints until you write `greet()`. Forgetting the parentheses — writing `greet` alone — does not run the body. The body must be indented; a line at column 0 is outside the function.

آزادو میں سمجھیں

فُنکشن (Function) ہدایات کا وہ بلاک ہے جو ایک بار لکھا جاتا ہے اور بار بار یادیا جا سکتا ہے۔ اس سے کوڈ مختصر، مائڈیوار اور آسان اصلاح والا بنتا ہے۔ تعریف `def` سے شروع ہوتی ہے، نام اور پیرامیٹرز قوسین میں ہوتے ہیں، جسم انڈینٹ ہوتا ہے اور `return` نتیجہ واپس بھیج سکتا ہے۔ تعریف کرتے سے فُنکشن چلتا نہیں جب تک آپ اسے کال نہ کریں۔

EXAM TIP
Write the four benefits (reusability, modularity, readability, maintainability) as separate bullets — that is a standard short question. For long questions, define a function, label `def`, name, parameters, body and `return`, then show one call. "What is duplicate code and how do functions solve it?" is also common.

CHECK YOURSELF
1. What keyword starts a function definition?
2. How many times does `Hello, World!` print in the `greet` program above, and why?
Answers: 1. `def`. 2. Twice, because `greet()` is called twice.

Extra board practice
These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A function is:

- a. A named reusable block
- b. A random line in main only
- c. A pie
- d. A cable

MCQ 2. You define with:

- a. `def name(params):`
- b. function name `{}`
- c. fun name
- d. lambda only always

MCQ 3. A call is:

- a. `name(arguments)`
- b. `def` again
- c. import name always
- d. print the source only

MCQ 4. Duplicate code is bad because:

- a. Fixes must be repeated; more bugs
- b. Python forbids functions
- c. It is faster always
- d. It is required by BIEK

MCQ 5. This is *****: expect

- a. Write a small function + call + output
- b. Only define HCI
- c. Only OSI
- d. Only ER

MCQ 6. Parameters are:

- a. Placeholders in the definition
- b. The values at the call (arguments)
- c. Always globals
- d. Always files

Extra short questions
1. Define function, parameter, argument.
2. Why functions (three reasons).
3. Show a 3-line add function.
4. What happens if you `def` but never call?

Extra long question
1. Write functions to compute area of rectangle and circle, call both from main, show output. Explain `def` vs call. ★ Golden.

Extra answer key
MCQs: 1. A 2. A 3. A 4. A 5. A 6. A
Short
1. Reusable block; names in `def`; values you pass.
2. Reuse, clarity, testing, less duplication.
3. `def add(a,b): return a+b`
4. Nothing runs — no output.
Long
1. Two `defs`, two calls, printed numbers. Mention `return` vs `print` inside. $\pi=3.14$ or `math.pi`.

3.2.1 Types of Functions (Built-in vs User-defined)

LEARN IT

There are two main types of functions in Python.

a) Built-in functions are already defined by Python. You just call them. Examples you have already used: len(), range(), sum(), print(), input(), min(), max(), sorted(), int(), float(), type().

b) User-defined functions are functions you create with def for tasks that no built-in covers in one step — greeting a user, dividing with a zero check, writing a grade file.

	Built-in	User-defined
Who writes it?	The Python language	The programmer
How you start	Just call the name	First write def name(...):
Examples	len("Ali") → 3	def add(a, b): return a + b
Purpose	Everyday operations needed by everyone	Your program's specific jobs

WORKED EXAMPLE

Side by side. Counting letters is built-in. Combining a greeting with a name is user-defined.

```
print(len("Sindh"))

def greet_student(name):
    print("Hello," + name)

greet_student("Hassan")
greet_student("Malika")
```

```
OUTPUT
5
Hello, Hassan
Hello, Malika
```

You did not write the code inside len. You did write the code inside greet_student, then reused it for two names.

REMEMBER IT

If Python already has it (len, sum, max), do not rewrite it. Write a user-defined function when you are packaging your steps.

COMMON MISTAKE

Do not name your function list, print, sum or input. You would hide the built-in name for the rest of that file. Choose names such as print_bill or sum_marks.

آرڈو میں سمجھیں

بلٹ ان فنکشن پائتھن میں پہلے سے موجود ہوتے ہیں، جیسے len() اور print()۔ یوزر ڈیفائنڈ فنکشن وہ ہیں جو پروگرامر def سے خود بناتا ہے تاکہ مخصوص کام بار بار کیا جا سکے۔ جو کام بلٹ ان پہلے کر دیتے ہیں انہیں دوبارہ نہ لکھیں۔

CHECK YOURSELF

1. Is range() built-in or user-defined?

2. Which keyword creates a user-defined function?

Answers: 1. Built-in. 2. def.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Built-in functions include:

a. len, print, min (provided by Python)

b. Only ones you def

c. Only pip packages

d. Only SQL

MCQ 2. User-defined functions are:

a. Ones you write with def

b. print and len

c. CPU instructions

d. OSI layers

MCQ 3. You still:

a. Call both with name()

b. Cannot call built-ins

c. Must recompile C

d. Must draw Figma

MCQ 4. A module function like math.sqrt is:

a. Library/built-in-standard, not your def

b. A user def in your file

c. A dict

d. A stack

MCQ 5. Why write your own if print exists?

a. Your problem's chunks (bill tax, grade band) are not built in

b. Python forbids print

c. Built-ins cannot be called

d. def is illegal

MCQ 6. Help(len) documents a:

a. Built-in

b. Your secret function always

c. A table

d. A query

Extra short questions

1. Differentiate built-in vs user-defined with examples.

2. Can user-defined call built-in?

3. Where do library functions sit?

4. One exam trap.

Extra long question

1. In one program use a built-in, a standard-library function, and a user-defined function. Label each and show output.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Built-in: print, len. User: def grade(m): ...

2. Yes — that is normal.

3. Neither in your file nor mysterious — imported modules.

4. Calling a function you never defined and is not built-in → NameError.

Long

1. print/len; math.sqrt; def mean. Three labels in comments. Exact numeric output.

3.2.2 Functions with Return Values

LEARN IT

A function can either **print** a result (show it on the screen) or **return** a result (send it back to the caller). A returned value can be stored in a variable, printed later, or used in a further calculation. The call is replaced by the returned value, as if you had written that value in its place.

```
def multiply(a, b):  
    return a * b  
  
result = multiply(5, 3)  
print("The answer is:", result)
```

```
OUTPUT  
The answer is: 15
```

`multiply(5, 3)` evaluates to 15. That 15 is stored in `result`.

WORKED EXAMPLE

Print versus return. This is the difference examiners want.

```
def show_sum(a, b):  
    print(a + b)  
  
def give_sum(a, b):  
    return a + b  
  
x = show_sum(2, 3)  
print("stored from show_sum:", x)  
y = give_sum(2, 3)  
print("stored from give_sum:", y)  
print("double it:", y * 2)
```

```
OUTPUT  
5  
stored from show_sum: None  
stored from give_sum: 5  
double it: 10
```

`show_sum` prints 5 inside the function, then returns `None` (the default when there is no `return`). You cannot double that answer later. `give_sum` hands 5 back, so `y * 2` is 10. Use `print` for messages; use `return` for results the rest of the program still needs.

REMEMBER IT

return = send back; print = show now. `return` also **exits** the function immediately. Lines after `return` in the same function do not run.

COMMON MISTAKE

Writing `print(a * b)` inside `multiply` and then `result = multiply(5, 3)` stores `None` in `result`, not 15. If you later write `result + 1` you get `TypeError`. Return the number; let the caller decide whether to print it.

اردو میں سمجھیں

`return` نتیجہ کال کرنے والے پروگرام کو واپس بھیجتا ہے تاکہ وہ متغیر میں محفوظ ہو سکے یا آگے حساب میں لگے۔ اگر `return` نہ ہو تو فنکشن `None` دیتا ہے۔ `print` صرف اسکرین پر دکھاتا ہے؛ اس سے حاصل شدہ قیمت دوبارہ استعمال نہیں ہوتی۔

CHECK YOURSELF

1. What is stored in `result` after `result = multiply(5, 3)` with `return a * b`?
2. What does a function return if it has no `return` statement?

Answers: 1. 15. 2. `None`.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. `return` sends a value:

- a. Back to the caller
- b. To the printer always
- c. To a file always
- d. To OSI layer 1

MCQ 2. A function with only `print`:

- a. Shows something but gives `None` to the caller
- b. Returns the text automatically
- c. Returns 0
- d. Cannot run

MCQ 3. `x = f()` if `f` has no `return`:

- a. `x` is `None`
- b. `x` is 0
- c. Error always
- d. `x` is `f`

MCQ 4. `return` also:

- a. Exits the function immediately
- b. Loops forever
- c. Defines a class
- d. Opens a socket

MCQ 5. You can `return`:

- a. Any object (number, str, tuple, list, dict)
- b. Only ints
- c. Only `True`
- d. Only files

MCQ 6. `print(f())` prints the:

- a. Returned value (or `None`)
- b. Source code
- c. The name `f`
- d. A pie

Extra short questions

1. Why `return` rather than `print` inside?
2. Show both styles for doubling 5.
3. Returning two values.
4. What is `None`?

Extra long question

1. Write `mean(a,b,c)` that returns a float. Show a test print and a logic error version that prints but returns `None`. Explain the bug in a unit-test style.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. The caller can store, test, or reuse the value.
2. `print` inside vs `return` 10 and `print` in main.
3. `return a,b` → `a` tuple, unpack.
4. The default `return` if you fall off the end.

Long

1. Correct `return (a+b+c)/3`. Buggy `print` only → `assert mean(1,2,3)==2` fails with `None`. Teaching point of `return`.

3.2.3 Activity: Arithmetic Calculator Using Functions

LEARN IT

Each arithmetic operation is a **separate function**. That is modularity: addition is one small task, division is another (with a guard against dividing by zero). The main program only asks for two numbers and calls the functions.

```
def add(a, b):
    return a + b

def subtract(a, b):
    return a - b

def multiply(a, b):
    return a * b

def divide(a, b):
    if b == 0:
        return a / b
    else:
        return "Cannot divide by zero"

num1 = float(input("Enter first number: "))
num2 = float(input("Enter second number: "))
print("Addition:", add(num1, num2))
print("Subtraction:", subtract(num1, num2))
print("Multiplication:", multiply(num1, num2))
print("Division:", divide(num1, num2))
```

WORKED EXAMPLE

Sample run with 12 and 4. `float` is used so decimals work; even whole numbers print with a decimal (12 becomes 12.0).

```
OUTPUT
Enter first number: 12
Enter second number: 4
Addition: 16.0
Subtraction: 8.0
Multiplication: 48.0
Division: 3.0
```

Check: $12 + 4 = 16$, $12 - 4 = 8$, $12 \times 4 = 48$, $12 \div 4 = 3$. In Python 3, `/` always produces a float, so 3.0 not 3.

Zero divisor:

```
def divide(a, b):
    if b == 0:
        return a / b
    else:
        return "Cannot divide by zero"

print(divide(10, 0))
print(divide(10, 2))
```

```
OUTPUT
Cannot divide by zero
5.0
```

Without the `if b == 0` test, `10 / 0` would raise `ZeroDivisionError` and stop the program.

REMEMBER IT

Four functions, four names: `add`, `subtract`, `multiply`, `divide`. The main program should look like a contents page — a sequence of calls — not a pile of formulae.

COMMON MISTAKE

`input()` returns a string. If you skip `float()` (or `int()`), `add` would concatenate: `"12" + "4"` is `"124"`. Convert first. Also, `divide` returns either a number or a string; do not later do arithmetic on the error message.

اردو میں سمجھیں

کیلکولیٹر میں ہر عمل الگ فنکشن ہے: جمع، تفریق، ضرب، تقسیم۔ یہ مائیولاریٹی ہے۔ تقسیم سے پہلے صفر کی جانچ ضروری ہے ورنہ پروگرام رک جاتا ہے۔ `input()` سے ملنے والی تار کو `float()` سے عدد بنانا لازمی ہے ورنہ جمع جوڑنے کے بجائے الفاظ جوڑ دے گی۔

CHECK YOURSELF

1. What does `divide(10, 0)` return in this activity?
2. Why are the numbers converted with `float()` ?

Answers: 1. The string "Cannot divide by zero". 2. Because `input()` returns text; `float()` turns it into a number so `+`, `-`, `*` / do arithmetic, including decimals.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A calculator activity should use:

- a. A function per operation
- b. One 200-line print spaghetti only
- c. No functions
- d. Only globals named a,b,c,d,e

MCQ 2. Division must consider:

- a. Zero divisor
- b. NAND grouping
- c. OSI layer
- d. Figma frames

MCQ 3. Menu + functions is:

- a. Selection + modularity
- b. A stack hardware
- c. A pie
- d. A foreign key

MCQ 4. return lets you:

- a. Print nicely in one place
- b. Hide errors
- c. Skip tests
- d. Avoid operators

MCQ 5. `float(input)` may raise:

- a. `ValueError`
- b. A pie
- c. A K-map
- d. A sprint

MCQ 6. This activity prepares:

- a. Reusable functions + later try/except
- b. Only Access
- c. Only HCI colours
- d. Only ER

Extra short questions

1. Outline four functions for `+`, `-`, `*`, `÷`.
2. How do you stop divide by zero?
3. Where does the menu live?
4. Why not copy the formula 12 times?

Extra long question

1. Write a mini calculator with four functions, a loop menu, and a safe divide. Sample session of 3 operations then quit.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. add, sub, mul, div with two params, return.
2. If `b==0`: return a message / raise / skip.
3. In main: while True: choice...
4. One fix in one function.

Long

1. Working structure, sample I/O, ZeroDivision handled. Mention return vs print.

3.2.4 Scope of Local and Global Variables

LEARN IT

Scope is the region of a program where a variable can be seen and used. Python has two scopes you must know for this chapter.

i) **Local scope**. A **local variable** is created inside a function. It exists only while that function is running. The main program cannot read it.

ii) **Global scope**. A **global variable** is created outside all functions. Any function may **read** it, and the main program can use it too.

WORKED EXAMPLE

Local — the name is invisible outside.

```
def calc():
    secret = 50
    print(secret)

calc()
print(secret)
```

```
OUTPUT
50
Traceback (most recent call last):
  File "local_scope.py", line 5, in <module>
    print(secret)
NameError: name 'secret' is not defined
```

First the function prints 50. Then the main program tries `print(secret)` and fails: `secret` was born inside `calc` and died when `calc` finished.

Global — readable inside and outside.

```
x = 10

def show():
    print("Inside function:", x)

show()
print("Outside function:", x)
```

```
OUTPUT
Inside function: 10
Outside function: 10
```

Assignment inside a function creates a new local with the same name. It does not change the global:

```
x = 10

def show():
    x = 99
    print("Inside:", x)

show()
print("Outside:", x)
```

```
OUTPUT
Inside: 99
Outside: 10
```

Inside, `x = 99` is a local. After the call, the global is still 10.

REMEMBER IT

Local = inside the room; global = in the corridor. Everyone can see the corridor. Things left in a room are gone when you leave. Prefer locals. Too many globals make bugs hard to find because any function might be using them.

COMMON MISTAKE

If you only **read** `x` inside the function, Python uses the global. If you **assign** to `x` anywhere in that function, Python treats `x` as local for the whole function. Mixing the two without care causes `UnboundLocalError`. Keep function inputs as parameters and outputs as `return` values instead of editing globals.

آزاد میں سمجھیں

دائرہ کار (Scope) بتاتا ہے کہ متغیر کہاں دکھائی دیتا ہے۔ لوکل متغیر فنکشن کے اندر بنتا ہے اور فنکشن ختم ہوتے ہی غائب ہو جاتا ہے؛ باہر سے پڑھنے پر `NameError` آتا ہے۔ گلوبل متغیر تمام فنکشنز سے باہر بنتا ہے اور اندر سے پڑھا جا سکتا ہے۔ فنکشن کے اندر اسی نام کو نئی قدر دینے سے نیا لوکل بنتا ہے، گلوبل نہیں بدلتا۔

CHECK YOURSELF

1. Where is a local variable defined?

2. In the last example, what does the main program print for `x` after `show()` ?

Answers: 1. Inside a function. 2. 10 (the global is unchanged).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A local variable lives:

- a. Inside the function
- b. In the whole file always
- c. On the disk
- d. In OS!

MCQ 2. A global variable lives:

- a. At module level (the file)
- b. Only in one for-loop
- c. Only in a dict key
- d. Only in RAM of another PC

MCQ 3. Reading a global from a function:

- a. Works
- b. Always error
- c. Deletes it
- d. Makes it local

MCQ 4. Assigning to a name in a function without global:

- a. Creates a local (does not change the outer)
- b. Always updates global
- c. Syntax error
- d. Opens a file

MCQ 5. global `x` is needed to:

- a. Rebind a global from inside a function
- b. Import math
- c. Draw a pie
- d. Sort a list

MCQ 6. Prefer:

- a. Parameters and return, not lots of globals
- b. All globals
- c. No names
- d. eval

Extra short questions

1. Define local vs global.
2. A classic bug.
3. How to share results instead of globals?
4. Can two functions have locals named total?

Extra long question

1. Show a 10-line program where a global count is incremented with global, then rewrite it with return so you do not need global. Explain which is clearer.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Local: created in function, dies when it ends. Global: file-level.
2. `x=1; def f(): x=x+1` without global → `UnboundLocalError`.
3. return values / pass them as arguments.
4. Yes — they are different variables.

Long

1. Both outputs match. Prefer return. `UnboundLocalError` snippet as a warning.

3.3 & 3.4 File Handling and Operations (Modes r, w, a) Golden

LEARN IT

File handling is a program's ability to create, read, write, update and delete files on disk. Variables live in **RAM** and vanish when the program ends. Files live on a **hard disk or SSD** and stay there — they are **persistent**.



Read copies data from disk into RAM. Write copies data from RAM onto disk.

Type	What it stores	Examples
Text file	Human-readable characters. You can open it in a text editor.	.txt, .csv, .py
Binary file	Raw bytes, not meant to be read as text.	.jpg, .mp3, .dat

This chapter uses text files.

The `open()` function and modes

You must open a file before you use it: `open(filepath, mode)`.

Mode	Name	Description
'r'	Read	Open for reading. Fails if the file does not exist.
'w'	Write	Open for writing. Erases existing content. Creates the file if it is missing.
'a'	Append	Open for writing at the end . Keeps old content. Creates the file if it is missing.
'rb' / 'ab'	Binary	Read or write bytes (images, audio).

File object methods	What it does
<code>.read()</code>	Whole file as one string.
<code>.readlines()</code>	All lines as a list of strings (each usually ends with <code>\n</code>).
<code>.write('text')</code>	Writes a string. You must add <code>\n</code> yourself for a new line.
<code>.close()</code>	Saves to disk, closes the file, frees RAM. Essential if you did not use <code>with</code> .

WORKED EXAMPLE

Create a file in write mode.

```
new_file = open('myfile.txt', 'w')
new_file.write('The quick brown fox jumps over the lazy dog!!!\n')
new_file.close()
print("File has been created successfully.")
```

OUTPUT

File has been created successfully.

If `myfile.txt` did not exist, `'a'` created it. The sentence is now on disk. `.close()` flushes the buffer so the bytes actually reach the disk.

Danger of `'a'`: opening an existing file in `'a'` deletes everything first.

```
f = open('myfile.txt', 'a')
f.write("FIRST\n")
f.close()
f = open('myfile.txt', 'a')
f.write("SECOND\n")
f.close()
with open('myfile.txt', 'r') as f:
    print(f.read(), end="")
```

OUTPUT

SECOND

FIRST is gone. To keep old lines and add a new one, use `'a'`:

```
f = open('notes.txt', 'a')
f.write("Line 1\n")
f.close()
f = open('notes.txt', 'a')
f.write("Line 2\n")
f.close()
with open('notes.txt', 'r') as f:
    print(f.read(), end="")
```

OUTPUT

Line 1
Line 2

REMEMBER IT
r = Read existing, w = Wipe then write, a = Add at end. Remember: write does not add a newline unless you type `\n`.

COMMON MISTAKE
Forgetting `.close()` can leave data in a memory buffer so the file on disk looks empty or incomplete — or the file can stay locked. Section 3.6 shows `with`, which closes for you even after an error. Never use `'w'` when you only meant to add a line; that is the most common way students wipe their own data.

آزمو میں سمجھیں
فائل پیدائش سے لیا ڈسک پر مستقل (Persistent) رہتا ہے، برخلاف RAM کے متغيرات کے جو پروگرام بند ہوتے ہی مٹ جاتے ہیں۔ `open(path, mode)` سے فائل کھلتی ہے: `'a'` پڑھنے کے لیے (فائل یونی جائے)، `'w'` لکھنے کے لیے (پراٹھا مواد مٹ جائے یا)، `'a'` آخر میں جوڑنے کے لیے۔ `تاکم` کے بعد `.close()` ضروری ہے اگر استعمال نہ ہو۔

EXAM TIP
Define file handling, contrast RAM with disk, list modes `r / w / a` with one property each, and warn that `w` overwrites. Short programs that write one line and close the file are common. Mention `.read()`, `.readlines()`, `.write()` and `.close()` by name.

CHECK YOURSELF

1. Which mode overwrites an existing file?
2. Which mode fails if the file is missing?
3. Why must `.write` often include `\n`?

Answers: 1. `'w'`. 2. `'r'`. 3. Because `write()` does not start a new line by itself; without `\n` the next write continues on the same line.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. `open(path, "r")` is for:
a. Reading
b. Wiping the file
c. Appending only
d. Creating a DB

MCQ 2. Mode `'w'`:
a. Write (truncates existing)
b. Read only
c. Append
d. Binary XOR

MCQ 3. Mode `'a'`:
a. Append at the end
b. Overwrite from start
c. Read
d. Delete the file

MCQ 4. You should:
a. `close()` (or use `with`)
b. Leave files locked
c. Never flush
d. Always use `w` for logs

MCQ 5. `read()` returns:
a. The whole content as `str` (text mode)
b. A dict always
c. A pandas DataFrame
d. A stack

MCQ 6. This is ✖ because practicals ask you to:
a. Write a small file program
b. Draw only ER
c. Only HCI
d. Only OSI

Extra short questions

1. The three text modes and a danger of `w`.
2. write vs writelines.
3. Why close?
4. A `FileNotFoundError` happens when:

Extra long question

1. Write a program that appends a line to marks.txt and then reads all lines. Show the file after two runs. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. `r` read, `w` write/overwrite, `a` append. `w` erases previous content.
2. write a string: writelines a sequence of strings.
3. Flush + unlock. Crash before close can lose data.
4. `r` on a path that does not exist.

Long

1. open `a`; write; close; open `r`; print. Second run has two lines. Warn that `w` would have kept only the last.

3.6 with Statement (Context Manager) ★ Golden

LEARN IT

It is easy to forget `.close()`. If the program crashes before `.close()` runs, the file may be incomplete or corrupted. Python's `with` statement is a **context manager**: it opens the file, runs the indented block, and **always closes** the file when the block ends — even if an error occurs inside.



```
with open('myfile.txt', 'w') as new_file:
    new_file.write("Context managers are safe!\n")
# no .close() here — with already closed the file
```

After the indented block, `new_file` is closed. You do not write `new_file.close()`.

3.7 Activity: reading file content

`.read()` pulls the whole file into RAM. For a huge file that can waste memory. The professional pattern is to **iterate line by line**.

```
with open('myfile.txt', 'w') as new_file:
    new_file.write("Context managers are safe!\n")

with open('myfile.txt', 'r') as read_file:
    for line in read_file:
        print(line, end="")
print("\nFile read successfully.")
```

OUTPUT

Context managers are safe!
File read successfully.

`end=""` stops `print` from adding a second newline: each line from the file already ends with `\n`.

WORKED EXAMPLE

Three ways to read the same small file.

```
with open('sample.txt', 'a') as f:
    f.write('Ali 88\nSara 90\nAyesha 75\n')

with open('sample.txt', 'r') as f:
    print(f.read())
    print(repr(f.read()))

with open('sample.txt', 'r') as f:
    print(f.readlines())
    print(f.readlines())

with open('sample.txt', 'r') as f:
    print(f"line by line")
    for line in f:
        print(line, end="")
```

OUTPUT
==
.read() ==
"Ali 88\nSara 90\nAyesha 75\n"
==
.readlines() ==
['Ali 88\n', 'Sara 90\n', 'Ayesha 75\n']
==
line by line ==
Ali 88
Sara 90
Ayesha 75

`repr` shows the hidden `\n` characters. `.readlines()` is handy when you need a list (the grade tracker uses this). Line-by-line looping is best for large files because only one line sits in memory at a time.

REMEMBER IT

with = "take, use, put back." Prefer `with open(...) as f:` in every new program. You still choose the mode: `'r'`, `'a'` or `'a'`.

COMMON MISTAKE

You cannot read from `f` after the `with` block — the file is already closed. Do all reading and writing inside the block. Also, `print(line)` without `end=""` looks double-spaced because both the `line` and `print` add a newline.

آرڈو میں سمجھیں

`with` بیان ایک کانٹیکسٹ مینیجر (Context Manager) ہے جو فائل کو پاک کیے اختتام پر خود بند کر دیتا ہے، چاہے اندر غلطی ہو جائے۔ پڑی فائلیں ایک ایک سطر کیے لوپ سے پڑھنا بہتر ہے بجائے پورے مواد کو `.read()` سے میموری میں بھرنے کیے۔ `print(line, end="")` دگنی خالی سطر روکتا ہے۔

EXAM TIP

Define the `with` statement as a context manager that guarantees close. Contrast it with manual `open / close`. Be ready to write a four-line program that writes with `with` and a four-line program that reads line by line. Mention memory: Iterating is safer for large files than `.read()`.

CHECK YOURSELF

- What does a context manager guarantee for a file?
- Why pass `end=""` when printing each line from a file?

Answers: 1. That the file is closed when the `with` block ends, even if an error occurs. 2. Because each line already ends with `\n`; `print` would otherwise add another newline and the output would look double-spaced.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. with open(...) as f:

- Closes the file automatically, even after errors
- Never closes
- Deletes the path
- Converts to pandas

MCQ 2. The with-block is a:

- Context manager
- Thread
- Socket always
- K-map

MCQ 3. If an exception happens inside with:

- The file still closes
- The file stays locked forever
- Python uninstalls
- The disk formats

MCQ 4. You still choose the mode:

- `r/w/a` as before
- `with` replaces modes
- Modes are only for SQL
- Modes are HCI

MCQ 5. This is ★ because it is the:

- Safe modern pattern for files
- Old optional style
- Only for pandas
- Only for Figma

MCQ 6. f is only valid:

- Inside the `with` block
- After the block always
- Before open
- In another file automatically

Extra short questions

- Write the canonical read pattern.
- Why it beats `try/finally` for beginners.
- Can you nest `with` for two files?
- What if the path is wrong in `with-open`?

Extra long question

- Rewrite a grade-tracker snippet from `open/close` to `with`, and show what happens if `int()` fails on a line. Why is `with` safer? ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- `with open("a.txt") as f: data=f.read()`
- Less boilerplate; close is guaranteed.
- Yes — `with open(a) as f; open(b) as g:`
- Still `FileNotFoundError` — `with` does not create the file in `r`.

Long

- Exception in `parse` still closes. Compare to forgotten `close` on the error path. Sample file 3 lines, one bad.

3.8 Errors and Exceptions (Try-Except)

LEARN IT

An **exception** is an error raised while the program is running — for example opening a file that is not there. Without handling, Python prints a traceback and **stops**. A `try / except` block catches the error and lets you show a clear message instead of crashing.

Error type	Meaning
FileNotFoundError	The path does not exist.
PermissionError	The operating system will not let you read or write that file.
IOError	A general input/output problem (disk full, disk disconnected).

Put risky code in `try`. Put the recovery in `except`. `ErrorType`. A final `except` `Exception` as `e` can catch anything else, using `e` as the error object.

```
try:
    with open('missing_data.txt', 'r') as f:
        content = f.read()
        print(content)
except FileNotFoundError:
    print("Error: The file does not exist. Please check the name.")
except Exception as e:
    print(f"An unexpected error occurred: {e}")
```

OUTPUT

Error: The file does not exist. Please check the name.

Without `try`, the same open raises:

OUTPUT

Traceback (most recent call last):
 File "missing.py", line 1, in <module>
 open('missing_data.txt', 'r')
FileNotFoundError: [Errno 2] No such file or directory: 'missing_data.txt'

WORKED EXAMPLE

When the file exists, the except blocks are skipped.

```
with open('ok.txt', 'w') as f:
    f.write("Present\n")

try:
    with open('ok.txt', 'r') as f:
        content = f.read()
        print(content, end='')
except FileNotFoundError:
    print("Error: The file does not exist. Please check the name.")
```

OUTPUT

Present

Professional software does not dump a red traceback on a user. If a file is missing or a disk fails, the user should see a calm sentence such as "Please check the file name" or "Please try again later."

REMEMBER IT

`try = attempt`, `except = backup plan`. Catch the **specific** error first (`FileNotFoundError`), then a general `Exception` if you need it. Order matters: a bare `except` `Exception` first would swallow the specific error.

COMMON MISTAKE

Do not wrap your entire program in one silent `except:` that ignores every mistake. You would hide real bugs. Catch the errors you expect, and keep the message honest. `'w'` and `'a'` create a missing file, so they do not raise `FileNotFoundError`; `'r'` does.

اردو میں سمجھیں

ایکسپشن (Exception) چلتے پروگرام کی غلطی ہے، جیسے غیر موجود فائل کھولنا۔ `try` میں خطرناک کواڈ لکھیں اور `except` `FileNotFoundError` میں صاف پیغام دکھائیں تاکہ پروگرام کریش نہ ہو۔ پیشہ ورانہ سافٹ ویئر صارف کو سرخ لڑیس ہیک کی بجائے سمجھ آنے والا جملہ دکھاتا ہے۔

CHECK YOURSELF

1. Which exception is raised when `open('missing_data.txt', 'r')` cannot find the file?
2. Does the sample program crash, or print a message, when the file is missing?

Answers: 1. `FileNotFoundError`. 2. It prints "Error: The file does not exist. Please check the name." and continues.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. `try/except` is for:

a. Handling runtime errors without crashing the whole program
b. Fixing syntax errors (missing colons)
c. Faster Big O
d. Drawing pie charts

MCQ 2. `FileNotFoundError` is raised when:

a. open r on a missing path
b. 1/0
c. int("a")
d. A logic bug that prints 3 instead of 4

MCQ 3. `except ValueError` catches:

a. int("hi")
b. Missing files
c. `SyntaxError` of a colon
d. Logic silent bugs

MCQ 4. `except Exception` is:

a. Broad — use with care
b. The way to hide all bugs always
c. A sort
d. A key

MCQ 5. else on `try` runs when:

a. No exception occurred
b. Always
c. Only on errors
d. On syntax errors

MCQ 6. finally runs:

a. Always (cleanup)
b. Only on success
c. Only on error
d. Never with with

Extra short questions

1. Why exceptions in file programs?
2. Show a `try` around `int(input)`.
3. Does `try` fix logic errors?
4. Order of `except` clauses.

Extra long question

1. Write a reader that tries to open `marks.txt`, handles missing file, skips bad lines with `ValueError`, and prints a count of good rows.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Missing files and bad lines are expected; crash is a poor UX.
2. `try: n=int(input()) except ValueError: print("Enter a number").`
3. No — wrong formula still wrong.
4. Specific first, broader later.

Long

1. Full code. Sample: file missing message; file with 80, x, 90 → 2 good. Mention not using bare `except`.

3.9 Mini File Handling Project: Grade Tracker

LEARN IT

This project uses 'w' to create a grades file, 'a' to add a student later, and 'r' to read every line and compute an average. It combines file handling, string methods and arithmetic.



```
with open("grades.txt", "w") as f:
    f.write("Alice: 88\n")
    f.write("Bob: 75\n")
    f.write("Carol: 92\n")
    print("Grades file created.")

with open("grades.txt", "a") as f:
    f.write("David: 81\n")
    print("New student appended.")

with open("grades.txt", "r") as f:
    lines = f.readlines()
    total = 0
    for line in lines:
        name, grade = line.strip().split(":")
        print(f"{name} scored {grade}")
        total += int(grade)
    average = total / len(lines)
    print(f"\nClass average: {average:.1f}")
```

WORKED EXAMPLE

What happens in memory and on disk.

- 'w' creates grades.txt (or wipes an old one) with three lines.
- 'a' adds David: 81\n at the end. Alice, Bob and Carol stay.
- .readlines() returns ['Alice: 88\n', 'Bob: 75\n', 'Carol: 92\n', 'David: 81\n'].
- .strip() removes the trailing \n. .split(":") turns "Alice: 88" into ["Alice", " 88"].
- int(grade) accepts the extra space: int(" 88") is 88.
- Total = 88 + 75 + 92 + 81 = 336. Average = 336 / 4 = 84.0. The format :.1f prints one decimal place.

OUTPUT

Grades file created.
New student appended.
Alice scored 88
Bob scored 75
Carol scored 92
David scored 81

Class average: 84.0

The extra space before each mark in the output comes from the space after the colon in the file ("Alice: 88"). int() ignores it. To tidy the printout you could use grade.strip() as well; the average would not change.

REMEMBER IT

Same file, three modes, three with blocks. Never open the same file in 'w' when you only meant to add David — that would delete Alice, Bob and Carol.

COMMON MISTAKE

If a line has no colon, split(":") will not produce two parts and the unpacking name, grade = ... will raise ValueError. Keep the Name: mark format. An empty file would make len(lines) zero and then total / 0 would fail — a real system should check that, just as divide checked for zero.

آرڈو میں سمجھیں

گریڈ ٹریکر پہلے 'w' سے فائل بناتا ہے، پھر 'a' سے نیا طالب علم جوڑتا ہے، پھر 'r' سے تمام سطریں پڑھ کر اوسط نکالتا ہے۔ ہر سطر کو strip اور split(":") سے نام اور نمبر میں توڑا جاتا ہے۔ اوسط = کل نمبر ÷ طلبہ کی تعداد۔ 'w' دوبارہ استعمال کرنے سے پرانے ریکارڈ مٹ جائیں گے۔

CHECK YOURSELF

- What is the class average in the sample, and how is it calculated?
- Why is David written with mode "a" rather than "w" ?

Answers: 1. 84.0 because (88+75+92+81)/4 = 336/4 = 84.0. 2. Because "a" appends; "w" would erase the three existing students.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. open(path, "r") is for:

a. Reading

b. Wiping the file

c. Appending only

d. Creating a DB

MCQ 2. Mode "w":

a. Write (truncates existing)

b. Read only

c. Append

d. Binary XOR

MCQ 3. Mode "a":

a. Append at the end

b. Overwrite from start

c. Read

d. Delete the file

MCQ 4. You should:

a. close() (or use with)

b. Leave files locked

c. Never flush

d. Always use w for logs

MCQ 5. read() returns:

a. The whole content as str (text mode)

b. A dict always

c. A pandas DataFrame

d. A stack

MCQ 6. This is ★ because practicals ask you to:

a. Write a small file program

b. Draw only ER

c. Only HCI

d. Only OSI

Extra short questions

- The three text modes and a danger of w.
- write vs writelines.
- Why close?
- A FileNotFoundError happens when:

Extra long question

- Write a program that appends a line to marks.txt and then reads all lines. Show the file after two runs. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- r read, w write/overwrite, a append. w erases previous content.
- write a string; writelines a sequence of strings.
- Flush = unlock. Crash before close can lose data.
- r on a path that does not exist.

Long

- open a; write; close; open r; print. Second run has two lines. Warn that w would have kept only the last.

Programming Fundamentals

17 single-page lessons · 6 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- Python programs rest on primitive types (`int`, `float`, `bool`) and abstract structures: lists, tuples, sets and dictionaries.
- A **list** is ordered and mutable, written with `[]`. Index from 0; `[-1]` is last. Slice stop is exclusive. Methods include `append`, `insert`, `remove`, `sort`, `reverse`, `clear`.
- A **tuple** is ordered and immutable, written with `()`. Item assignment raises `TypeError`. Only `count` and `index` exist as methods.
- A **set** is unordered and unique, written with `{}`. Use `|` & `-` & `^` for union, intersection, difference and symmetric difference. Prefer `discard` over `remove`.
- A **dictionary** maps unique keys to values. `d[key]` can raise `KeyError`; `d.get(key, default)` is safe. Duplicate keys keep the last value.
- `min`, `max`, `len`, `sum` and `sorted` work across structures. On a dict, `min` / `max` / `sorted` use keys; total values with `sum(d.values())`. `sorted()` returns a new list; `.sort()` changes a list in place.
- Functions written with `def` give reusability, modularity, readability and maintainability. Built-in functions already exist; user-defined functions solve your tasks.
- `return` sends a value to the caller. Without `return`, the result is `None`. Local variables live inside a function; global variables live outside all functions.
- Files persist on disk. Modes: `r` read (must exist), `w` write (overwrites), `a` append. Methods: `read`, `readlines`, `write`, `close`.
- The `with` statement is a context manager that closes the file automatically. Loop line by line to read large files safely.
- `try / except FileNotFoundError` stops a missing file from crashing the program.
- The grade tracker writes with `w`, appends with `a`, reads with `r`, splits each `Name: mark` line, and computes the mean.

Key terms

Term	Meaning	اردو
Data structure	A way of organising values so a program can store and use them.	ڈیٹا سٹرکچر
Primitive type	A basic single value: <code>int</code> , <code>float</code> , <code>bool</code> .	بنیادی قسم
List	Ordered, mutable sequence written with <code>[]</code> .	فہرست
Index	The position of an item, starting at 0 (or -1 from the end).	انڈیکس
Slicing	Copying a portion of a sequence with <code>start:stop:step</code> .	سلائسنگ
Traversal	Visiting each element in turn, usually with a loop.	گشت / تراورسل
Mutable	Can be changed after creation.	قابل تبدیلی
Immutable	Cannot be changed after creation.	ناقابل تبدیلی
Tuple	Ordered, immutable sequence written with <code>()</code> .	ٹیپل
Set	Unordered collection of unique items written with <code>{}</code> .	سیٹ
Union	All unique items from two sets (<code> </code>).	اجتماع
Intersection	Items common to both sets (<code>&</code>).	اشتراک

Programming Fundamentals

75 marks · 1 hour 15 minutes · no notes · no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 17 and the recap. **Section A** — all 15 MCQs (1 mark). **Section B** — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define · Explain · Example · Diagram · Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. Which structure is ordered and mutable?
 - a. List
 - b. Tuple
 - c. Set
 - d. Frozen set
2. What does `nums[2:6]` return if `nums = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]`?
 - a. `[2, 3, 4, 5, 6]`
 - b. `[2, 3, 4, 5, 6, 7]`
 - c. `[2, 3, 4, 5]`
 - d. `[3, 4, 5, 6]`
3. `t = (1, 2, 3)` then `t[0] = 99` raises
 - a. `KeyError`
 - b. `TypeError`
 - c. `ValueError`
 - d. `IndexError`
4. A set is best described as
 - a. ordered with duplicates
 - b. indexed and mutable
 - c. key-value pairs
 - d. unordered with unique elements
5. If `A = {1, 2, 3, 4}` and `B = {3, 4, 5, 6}`, then `A & B` is
 - a. `{3, 4}`
 - b. `{1, 2}`
 - c. `{1, 2, 3, 4, 5, 6}`
 - d. `{1, 2, 5, 6}`
6. `{"a": 1, "a": 2, "a": 3}` prints
 - a. `{'a': 1}`
 - b. `{'a': 1, 'a': 2, 'a': 3}`
 - c. `{'a': 3}`
 - d. a `KeyError`
7. The safe way to read a possibly missing dictionary key is
 - a. `d[key]`
 - b. `d.get(key)`
 - c. `d.keys(key)`
 - d. `d.index(key)`
8. For `s = {5, 1, 9, 3, 7}`, `sum(s)` is
 - a. 5
 - b. 9
 - c. 7
 - d. 25
9. Which statement is true?
 - a. `sorted(x)` returns a new list and leaves `x` unchanged
 - b. `sorted(x)` works only on lists
 - c. `.sort()` works on tuples
 - d. `.sort()` returns a new list
10. A function is created with the keyword
 - a. `func`
 - b. `def`
 - c. `define`
 - d. `return`
11. A function that has no `return` statement returns
 - a. `0`
 - b. `False`
 - c. `None`
 - d. an empty string
12. A variable defined inside a function is
 - a. local
 - b. global
 - c. persistent
 - d. public
13. Opening a file with mode `'w'`
 - a. fails if the file already exists
 - b. adds new text at the end
 - c. is read-only
 - d. erases existing content (and creates the file if needed)
14. The `with open(...) as f:` statement is used mainly because
 - a. it makes the file binary
 - b. it closes the file automatically
 - c. it is faster than lists
 - d. it prevents `KeyError`
15. Reading a missing file in mode `'r'` without `try` raises
 - a. `TypeError`
 - b. `KeyError`
 - c. `FileNotFoundError`
 - d. `ValueError`

Section B — Short questions (10 × 3 = 30)

1. Define a data structure. Distinguish primitive from abstract data structures with one example of each.
2. What is negative indexing? Give the expression that returns the last item of a list named `fruits`.
3. State four differences between a list and a tuple.
4. Differentiate `.remove()` and `.discard()` on a set.
5. Why can a dictionary not have two identical keys? What happens if you write the same key twice?
6. Contrast `sorted()` with list `.sort()`.
7. List four benefits of using functions.
8. Define local scope and global scope.
9. Write the meaning of file modes `'r'`, `'w'` and `'a'`.
10. What is a context manager? Why is `with` safer than calling `.close()` yourself?

Section C — Long questions (attempt any 3 × 10 = 30)

1. Compare list, tuple, set and dictionary in a table (syntax, order, mutability, duplicates, how you access an item, one typical use). Then write two lines of Python that create one example of each holding the numbers 1, 2 and 2, and state what each structure actually stores.
2. Write a complete Python program that takes a sentence, counts the frequency of each word using a dictionary and `.get()`, prints a two-column table, and prints the most frequent word. Trace your program on `"python is easy python is fun python is powerful"`.
3. Write an arithmetic calculator with four user-defined functions `add`, `subtract`, `multiply` and `divide`. `divide` must not crash when the second number is 0. Explain how `return` is used and why `input` values are converted with `float`.
4. Explain file handling. Describe modes `r`, `w` and `a`, the `with` statement, and `try/except FileNotFoundError`. Include a short program that writes one line with `with` and another that reads a file that might be missing.
5. The grade tracker writes three students with `'w'`, appends David with `'a'`, then computes the class average. Write the full program, show the exact output for marks 88, 75, 92 and 81, and explain `strip`, `split(":")` and `average:.1f`.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

- 3.1.1 Data Structures in Python.** Answers: 1. Primitive: any two of int, float, bool. Abstract: any two of list, tuple, set, dictionary. 2. Because it is a higher-level container built from primitive values, holding many items and supporting operations such as append and slice.
- 3.1.1 Lists (Ordered, Mutable, Methods).** Answers: 1. [2, 3, 4, 5]. 2. ['banana', 'apple'] (only the first apple is removed). 3. To stop scanning once the value is found, so the rest of a long list is not checked.
- 3.1.2 Tuples (Ordered, Immutable).** Answers: 1. count and index. 2. TypeError: 'tuple' object does not support item assignment. 3. ([1, 2, 99], [3, 4]).
- 3.1.3 Sets (Unordered, Unique, Math Operations).** Answers: 1. {1, 2, 3, 4} (duplicates removed; order may vary). 2. discard does not raise KeyError if the value is missing. 3. {1, 2, 5, 6}.
- 3.1.4 Dictionaries (Key-Value pairs).** Answers: 1. {'a': 3}. 2. 0. 3. A set.
- 3.1.5 Common Built-in Functions (min, max, len, sum).** Answers: 1. 5, 1, 9, 25. 2. A list: [1, 3, 5, 7, 9]. 3. sum(d.values()) → 240.
- 3.1.6 Activity: Students Attendance Program.** Answers: 1. Present 0, Absent 3. 2. So that YES, Yes and yes all match the string "yes".
- 3.1.7 Activity: Word Frequency Counter.** Answers: 1. Three times. 2. Because a brand-new word is not yet a key; .get returns 0 instead of raising KeyError.
- 3.2 Functions in Python.** Answers: 1. def. 2. Twice, because greet() is called twice.
- 3.2.1 Types of Functions (Built-in vs User-defined).** Answers: 1. Built-in. 2. def.
- 3.2.2 Functions with Return Values.** Answers: 1. 15. 2. None.
- 3.2.3 Activity: Arithmetic Calculator Using Functions.** Answers: 1. The string "Cannot divide by zero". 2. Because input() returns text; float() turns it into a number so + - * / do arithmetic, including decimals.
- 3.2.4 Scope of Local and Global Variables.** Answers: 1. Inside a function. 2. 10 (the global is unchanged).
- 3.3 & 3.4 File Handling and Operations (Modes r, w, a).** Answers: 1. 'w'. 2. 'r'. 3. Because write() does not start a new line by itself; without \n the next write continues on the same line.
- 3.6 with Statement (Context Manager).** Answers: 1. That the file is closed when the with block ends, even if an error occurs. 2. Because each line already ends with \n; print would otherwise add another newline and the output would look double-spaced.
- 3.8 Errors and Exceptions (Try-Except).** Answers: 1. FileNotFoundError. 2. It prints "Error: The file does not exist. Please check the name." and continues.
- 3.9 Mini File Handling Project: Grade Tracker.** Answers: 1. 84.0 because (88+75+92+81)/4 = 336/4 = 84.0. 2. Because "a" appends; "w" would erase the three existing students.

Answer key

Multiple choice

- a
- c
- b
- d
- a
- c
- b
- d
- a
- b
- c
- a
- d
- b
- c

Short questions — model answers

1. A data structure organises values in a program. Primitive types hold one value (e.g. `int 17`). Abstract structures hold collections and richer operations (e.g. a list of marks).
2. Negative indexing counts from the right. `fruits[-1]` is the last item. `fruits[-2]` is the second last.
3. List: `[]`, mutable, many methods, slightly slower, use when data will change. Tuple: `()`, immutable, only `count / index`, slightly faster, use for protected records. Both are ordered and allow duplicates and indexing.
4. Both delete an element. `remove` raises `KeyError` if the value is absent. `discard` does nothing in that case, so it is the safer choice.
5. Each key must identify one value (like one roll number per student). A repeated key does not crash; the last assigned value overwrites the earlier one, e.g. `{"a": 3}`.
6. `sorted(x)` is a built-in function for any iterable; it returns a new list and does not change `x`. `.sort()` is a list method that sorts in place and returns `None`.
7. Reusability (write once, call many times), modularity (small named tasks), readability (shorter files), maintainability (fix one definition).
8. Local: defined inside a function; invisible outside; gone when the function ends. Global: defined outside all functions; readable throughout the program.
9. `'r'` read, error if missing. `'w'` write, create if missing, erase old content. `'a'` append at the end, create if missing, keep old content.
10. A context manager sets up a resource and cleans it up. `with open(...)` as `f` closes the file when the block ends, even after an exception, so you cannot forget `.close()` and you are safer if the program crashes mid-write.

Long questions — model answers

1. Use the comparison table from 3.1.4 (brackets, ordered/mutable/duplicates/access/empty/use). Examples:

```
print([1, 2, 2])
print((1, 2, 2))
print({1, 2, 2})
print({"a": 1, "b": 2, "b": 2})
```

OUTPUT

```
[1, 2, 2]
(1, 2, 2)
{1, 2}
{'a': 1, 'b': 2}
```

The list and tuple keep both 2s and an order. The set drops the extra 2. The dictionary keeps unique keys; the second "b" overwrites the first.

2. Use the program in 3.1.7. Trace: nine tokens; `python` and `is` end at 3; others at 1. Output matches the worked example, including Most Frequent: 'python' (3 times) because `max` returns the first key among ties. Heart of the loop:
`word_freq[word] = word_freq.get(word, 0) + 1`.
3. Use the four functions from 3.2.3. `return` sends each result to `print` in the main program. `divide` returns the string "Cannot divide by zero" when `b == 0`. `float(input(...))` is required because `input` returns a string and `"12" + "4"` would concatenate. Sample 12 and 4: 16.0, 8.0, 48.0, 3.0.
4. File handling stores data on disk so it outlives the program. Modes: `r` read / must exist; `w` wipe-or-create; `a` add-or-create. `with` closes automatically. Try/except:

```
with open("note.txt", "w") as f:
    f.write("Saved\n")
try:
    with open("note.txt", "r") as f:
        print(f.read(), end="")
except FileNotFoundError:
    print("Error: The file does not exist. Please check the name.")
```

OUTPUT

```
Saved
```

If the name were wrong, the except message would print instead of a traceback.

5. Full program as in 3.9. Disk after append:

OUTPUT

```
Alice: 88
Bob: 75
Carol: 92
David: 81
```

Output of the program (exact):

OUTPUT

```
Grades file created.
New student appended.
Alice scored 88
Bob scored 75
Carol scored 92
David scored 81

Class average: 84.0
```

`strip` removes `\n`; `split(":")` separates name and mark; `int(grade)` allows the extra space; `{average:.1f}` prints one decimal. $336 \div 4 = 84.0$.

Self-assessment: I can...

- ☐ Choose list, tuple, set or dictionary for a given problem and justify the choice.
- ☐ Explain tuple immutability and the inner-list exception, and use `count / index`.
- ☐ Update a dictionary, access values with `.get()`, and loop with `.items()`.
- ☐ Write a user-defined function with parameters and a `return` value, and contrast it with a built-in.
- ☐ Open a text file in `r`, `w` or `a` using `with`, and read it line by line.
- ☐ Index, slice, traverse and update a list, including `[-1]` and the main methods.
- ☐ Build a set, drop duplicates, and compute union, intersection, difference and symmetric difference.
- ☐ Apply `min`, `max`, `len`, `sum` and `sorted` correctly, including on dictionaries.
- ☐ State whether a name is local or global and predict a `NameError`.
- ☐ Catch `FileNotFoundError` and complete the grade-tracker project with the correct average.

Lecture 04

Data and Analysis

Chapter lecture — 8 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XII · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — بارہویں جماعت

08 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XII

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیئر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

Lectures in this pack

Chapter 4: Data and Analysis. Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 4.1 Concept of Data Analysis

L02. 4.1.1 – 4.1.2 Data Sources and Database Connection

L03. 4.2 Creating a SQLite Database in Python

L04. 4.3 Basic Operations on Data using Pandas

L05. 4.3.3 Handling Missing Values (NaN)

L06. 4.4 Data Organization and Representation

L07. 4.5 Data Visualization & Types of Graphs

L08. 4.6 Descriptive Statistics

CHAPTER 4

Data and Analysis

This chapter shows you how to pull data from a SQLite database with Python, clean it in Pandas, draw the right chart, and summarise a dataset with mean, median, mode and standard deviation. These are the same steps a data analyst uses every day.

اس باب میں آپ سیکھیں گے کہ پائتھن سے ایس کیو لائٹ ڈیٹا بیس کیسے جوڑا جاتا ہے، پینڈاز میں ڈیٹا کیسے صاف ہوتا ہے، درست چارٹ کیسے بنتا ہے، اور اوسط، میڈین، موڈ اور معیاری انحراف سے خلاصہ کیسے نکلتا ہے۔

What you will learn

- Define data analysis and say why Python is used for it.
- Create a SQLite database, table, insert, select, commit and close.
- Create calculated columns and handle NaN with isnull, fillna and dropna.
- Choose and code bar, line, pie, histogram, scatter and box plots.
- Name the five parts of a Python database connection in order.
- Build a Pandas DataFrame from a dictionary, CSV or Excel file.
- Organise data in tables and frequency distributions.
- Compute mean, median, mode, range, variance, standard deviation, min and max by hand, and know that pandas `.std()` uses $n-1$.

4.1 Concept of Data Analysis

LEARN IT

Data analysis is examining, organising and interpreting data so you can extract useful information. Schools study results, shops study sales, hospitals study patient records — all to make a decision, spot a trend or solve a problem.

Python is popular for this work because it is readable, talks to files and databases, does statistics, and draws graphs. Five lines of Pandas often replace an hour of spreadsheet clicking.

WORKED EXAMPLE

A Hyderabad college has 400 CS marks in a spreadsheet. Analysis answers: What is the average? How many failed? Is the second shift weaker than the first? The numbers are data; those answers are information.

اردو میں سمجھیں

ڈیٹا کا تجزیہ یعنی اعداد کو ترتیب دے کر ان سے فیصلے کے قابل معلومات نکالنا۔ پائتھن اس لیے منتخب کیا جاتا ہے کہ وہ فائلیں، ڈیٹا بیس، حساب اور گراف سب سنبھال لیتا ہے۔

CHECK YOURSELF

1. Give one school use of data analysis.
2. Name two Python superpowers for analysis.

Answers: 1. Study results to improve teaching (or similar). 2. Any two: read CSV/Excel/databases, organise tables, statistics, charts.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Data analysis is:

- a. Examining data to extract useful information
- b. Only collecting rumours
- c. Only drawing logos
- d. Only cabling

MCQ 2. Python is used because:

- a. Files, databases, stats, plots in one language
- b. It is analog
- c. It cannot loop
- d. It cannot import

MCQ 3. Raw marks vs “class average 62”:

- a. Data vs information
- b. Information vs data
- c. Both keys
- d. Both NAND

MCQ 4. A decision is the:

- a. Point of analysis
- b. First NAND
- c. Last OSI layer always
- d. Sprint name

MCQ 5. Without a question, analysis is:

- a. Aimless charting
- b. Always AI
- c. Always IoT
- d. Always HCI

MCQ 6. XII tools for analysis include:

- a. sqlite3, pandas, matplotlib, statistics
- b. Only LogiSim
- c. Only Figma
- d. Only Access macros

Extra short questions

1. Define data analysis with a college example.
2. Four Python superpowers listed in the notes.
3. What is not analysis?
4. Link to XI digital literacy.

Extra long question

1. A Hyderabad college has 400 CS marks. Write four analysis questions and which Python tool answers each.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Process marks to decide who needs extra class.
2. Read files, talk to DB, statistics, charts (and readable syntax).
3. Dumping 400 rows on a slide with no summary.
4. Same collect-present loop, now with code.

Long

1. Average: pandas mean. Fail count: filter. Shift compare: groupby. Trend: matplotlib line if by year. Mention cleaning NaNs first.

4.1.1 – 4.1.2 Data Sources and Database Connection ★ Golden

LEARN IT

Data sources are where information comes from: school records, websites, sensors, databases. **Connectivity** is the conversation between your Python program and that source so you can read and update data.

Five components of a database connection, in the order they actually work:

#	Component	Role
1	Database	Organised store (SQLite = one .db file; MySQL = a server for big apps)
2	Driver	Translator between Python and that DBMS (sqlite3 is built in)
3	Connection object	Opens, manages and closes the pipeline
4	Cursor object	Runs SQL and walks through result rows
5	SQL queries	CREATE, INSERT, SELECT, UPDATE, DELETE



EXAM TIP

Write the five names in order and one line each. A common trap is swapping cursor and connection: the connection is the pipe; the cursor is the messenger that travels through it.

اردو میں سمجھیں

خمسہ اجزاء: ڈیٹا بیس، ڈرائیور، کنکشن، کرسر، ایس کیو ایل۔ کنکشن پائپ ہے، کرسر اس پائپ میں چل کر حکم چلاتا ہے۔

CHECK YOURSELF

- Which object executes SELECT * ?
- Is SQLite a driver, a database, or both?

Answers: 1. The cursor. 2. SQLite is the database; the sqlite3 module is the driver.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The five connection parts in order start with:

- Database then driver
- Cursor then database
- SQL then mouse
- Chart then file

MCQ 2. The cursor:

- Executes SQL and fetches rows
- Is the .db file
- Is matplotlib
- Is Figma

MCQ 3. The connection object is the:

- Pipeline
- SQL text
- Driver brand only
- Pie

MCQ 4. sqlite3 is the:

- Built-in driver (+ DB engine in-process)
- A web browser
- An OSI layer
- A sort

MCQ 5. SQL examples:

- SELECT, INSERT, CREATE
- def, for, if
- AND, OR, NOT gates
- HTTP GET only

MCQ 6. Swapping cursor and connection in an answer is a:

- Classic 0-mark mix-up
- Required trick
- Big O class
- UX heuristic

Extra short questions

- Name the five components in order.
- Why a driver?
- SQLite vs MySQL in one line.
- Draw the flow.

Extra long question

- Label a 9-line sqlite snippet with the five components. Explain commit vs close. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Database, driver, connection, cursor, SQL.
- Translates Python calls to the DBMS protocol/API.
- SQLite: file, no server. MySQL: server for many users.
- Python → driver → connection → cursor → SQL → DB.

Long

- import=driver; connect=connection; cursor=cursor; execute=SQL; school.db=database. commit saves; close unlocks. Missing commit → empty next run.

4.2 Creating a SQLite Database in Python

LEARN IT
SQLite is built into Python. The whole database is one .db file next to your script — no password, no port, no server. Nine steps you must be able to write from memory:

```
import sqlite3
conn = sqlite3.connect("school.db") # 1-2 driver + connection
cur = conn.cursor() # 3 cursor
cur.execute("CREATE TABLE IF NOT EXISTS students (id INTEGER, name TEXT, marks INTEGER)")
cur.execute("INSERT INTO students VALUES (1, 'Ali', 85)")
conn.commit() # 6 SAVE or the row vanishes
cur.execute("SELECT * FROM students")
rows = cur.fetchall()
for r in rows:
    print(r)
conn.close() # 9 unlock the file
```

OUTPUT
(1, 'Ali', 85)

Step	Why it matters
connect	Creates the file if it does not exist
cursor	Vehicle that carries SQL
execute	Runs one SQL command
commit	Writes INSERT/UPDATE/DELETE to disk
fetchall	Brings SELECT results into a Python list of tuples
close	Frees memory and unlocks the file

COMMON MISTAKE
Forgetting `commit()` is the classic bug: the program prints nothing next time because the insert was never saved. Forgetting `close()` can lock `school.db` so the next run fails.

REMEMBER IT
Strings inside SQL use single quotes: `'Ali'`. Python strings around the SQL use double quotes (or a triple-quoted string).

اردو میں سمجھیں
ایس کیو لائٹ پائٹھن کے ساتھ آتی ہے، پورا ڈیٹا بیس ایک فائل ہے۔ ترتیب: امپورٹ، کنکٹ، کرسر، COMMIT.EXECUTE, COMMIT, SELECT, FETCALL, CLOSE نہ ہو تو اندراج ضائع ہو جاتا ہے۔

CHECK YOURSELF
1. What does * mean in SELECT *?
2. Which call must follow INSERT?

Answers: 1. All columns. 2. `conn.commit()`.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. `sqlite3.connect("school.db")` will:

- a. Open or create the file
- b. Always error if missing
- c. Start MySQL server
- d. Draw a pie

MCQ 2. After INSERT you must:

- a. `commit()`
- b. only close
- c. drop the table
- d. `pip install sqlite`

MCQ 3. `fetchall()` returns:

- a. A list of tuples (rows)
- b. A DataFrame always
- c. A dict of dicts always
- d. A string of SQL

MCQ 4. CREATE TABLE IF NOT EXISTS avoids:

- a. Error on re-run
- b. The need for types
- c. The need for keys
- d. `commit`

MCQ 5. `close()` is needed to:

- a. Unlock the file
- b. Create pandas
- c. Sort rows
- d. Encrypt OSI

MCQ 6. SELECT * means:

- a. All columns
- b. All tables in the folder
- c. A pie of all apps
- d. Drop everything

Extra short questions

- Nine-step sequence from the notes.
- What does * mean?
- Two classic bugs.
- How do you see the data next run?

Extra long question

- Write a complete program: table students(id, name, marks), insert Ali 85 and Sara 90, print rows. Number the five connection components in comments.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- import, connect, cursor, create, insert, commit, select, fetch, close.
- Every column.
- No commit; forgotten close; SQL string quotes mixed up.
- It is in school.db — connect again and SELECT.

Long

- Full working code and output two tuples. Comments: driver/connection/cursor/SQL/database.

4.3 Basic Operations on Data using Pandas ★ Golden

LEARN IT

Pandas is a third-party library for tables. Install once: `pip install pandas` in the terminal (not inside the `.py` file). Convention: `import pandas as pd`.

A **DataFrame** is a 2-D table of rows and columns, like Excel or an SQL table. You can filter, sort and calculate whole columns without writing a `for` loop.

```
import pandas as pd
data = {
    "Name": ["Ali", "Sara", "Ahmed"],
    "Math": [85, 90, 78],
    "Science": [80, 88, 70],
}
df = pd.DataFrame(data)
print(df)
```

OUTPUT

	Name	Math	Science
0	Ali	85	80
1	Sara	90	88
2	Ahmed	78	70

`read_csv('students.csv')` and `read_excel('students.xlsx', sheet_name='Sheet1')` load files. `df.head()` prints the first five rows — use it on large files so you do not flood the screen.

```
df["Total"] = df["Math"] + df["Science"]
df["Average"] = df["Total"] / 2
print(df)
```

OUTPUT

	Name	Math	Science	Total	Average
0	Ali	85	80	165	82.5
1	Sara	90	88	178	89.0
2	Ahmed	78	70	148	74.0

WORKED EXAMPLE

Check: Ali $85+80=165$, $165/2=82.5$. Sara $90+88=178$, 89.0 . Ahmed $78+70=148$, 74.0 .

اردو میں سمجھیں

پینڈا ڈیٹا فریم دیتا ہے۔ ڈکشنری، سی ایس وی یا ایکسل سے لوڈ کریں۔ نئے کالم بغیر لوپ کے پوری قطار پر حساب کر کے بنتے ہیں۔ `head()` صرف پہلی پانچ قطاریں دکھاتا ہے۔

CHECK YOURSELF

- What is `pd`?
- Why not `print(df)` on a million-row file?

Answers: 1. The usual alias for pandas. 2. It would print everything; use `df.head()`.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Common DS operations include:

- Insert, delete, search, traverse
- Only compile
- Only ping
- Only print the logo

MCQ 2. Traverse means:

- Visit elements in some order
- Delete all
- Encrypt all
- Sort the OS

MCQ 3. Search cost depends on:

- The structure (array vs sorted vs hash vs tree)
- The PDF theme
- The teacher name
- The sprint

MCQ 4. Insert in a full array may:

- Fail or require resizing
- Always $O(1)$ no matter what
- Create a graph edge automatically
- Pop a stack

MCQ 5. Delete from a queue happens at the:

- Front
- Rear only always
- Random index
- Root of a tree

MCQ 6. You choose a DS by the:

- Operations you will do most
- First letter of the course
- Colour
- NAND count

Extra short questions

- List five operations.
- Give costs qualitatively: array index vs list search.
- What does traverse a tree mean?
- Why "update" might be search+insert.

Extra long question

- For array, stack, queue, tree: name the natural insert/delete ends and one costly operation. Table.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Create, insert, delete, search, traverse, update, sort (as applicable).
- Array index $O(1)$; unsorted list search $O(n)$.
- Visit every node (pre/in/post or level order).
- You must find the item first.

Long

- Array: insert middle costly. Stack: top only cheap. Queue: rear in front out. Tree: search/insert depend on balance. 8-row table.

4.3.3 Handling Missing Values (NaN) ★ Golden

LEARN IT
Missing cells are **NaN** ("Not a Number"). Statistics crash or lie if you ignore them. Three tools: `isnull()` (True where empty), `fillna(value)` (replace), `dropna()` (delete the row).

```
import pandas as pd
df = pd.DataFrame({
    "Name": ["Ali", "Sara", "Ahmed", "Ayesha"],
    "Marks": [85.0, None, 78.0, 92.0],
    "Grade": ["A", "A", None, "A"],
})
print(df.isnull().sum())
```

OUTPUT
Name 0
Marks 1
Grade 1
dtype: int64

WORKED EXAMPLE
Replace Marks with the mean of the known marks, and Grade with a label. Known marks 85, 78, 92 → mean = 255/3 = **85.0**.

```
avg = df["Marks"].mean() # 85.0
df["Marks"] = df["Marks"].fillna(avg)
df["Grade"] = df["Grade"].fillna("Not Assigned")
print(df)
```

OUTPUT

	Name	Marks	Grade
0	Ali	85.0	A
1	Sara	85.0	A
2	Ahmed	78.0	Not Assigned
3	Ayesha	92.0	A

`df = df.dropna()` would instead delete Sara's row and Ahmed's row (any row that still had a NaN).

EXAM TIP
State: identify with `isnull / sum`, fill numeric gaps with the mean, fill categories with a label, or drop rows if filling would invent a lie. Never analyse first and clean second.

COMMON MISTAKE
Filling a salary gap with the mean of a company that includes the CEO can hide poverty (the same outlier problem as the mean). Know *why* the value is missing before you fill.

اردو میں سمجھیں
خالی خانے NaN ہیں۔ isnull تلاش، fillna بھرنا (اکثر اوسط سے)، dropna قطار ہٹانا۔ پہلے صاف کرو، پھر تجزیہ۔

CHECK YOURSELF
1. What does `df.isnull().sum()` return?
2. Does `dropna()` delete a column or a row by default?

Answers: 1. Count of NaNs in each column. 2. Any row that contains at least one NaN.

Extra board practice
These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. NaN means:

- a. Not a Number — missing
- b. A huge number
- c. Zero always
- d. A pie slice

MCQ 2. `isnull().sum()` gives:

- a. Count of missing per column
- b. The mean
- c. The PK
- d. The chart type

MCQ 3. `fillna(mean)` :

- a. Replaces gaps with the average
- b. Deletes the column names
- c. Sorts
- d. Commits SQL

MCQ 4. `dropna()` by default:

- a. Drops rows that contain any NaN
- b. Drops the whole DataFrame always
- c. Fills with 0
- d. Draws a box plot

MCQ 5. You should clean NaNs:

- a. Before analysing
- b. After publishing
- c. Never
- d. Only in Figma

MCQ 6. Filling salary with the mean can:

- a. Hide poverty if a CEO is in the data
- b. Fix ethics
- c. Create keys
- d. Route packets

Extra short questions

- Three tools: find, fill, drop.
- Mean of 85, None, 78, 92 for filling.
- When drop is better than fill.
- `isnull()` returns what type of frame?

Extra long question

1. Given Marks [85, None, 78, 92] and Grade [A,A,None,A]: show `isnull` sum, fill marks with mean and grade with "Not Assigned", print the frame. ★ Golden.

Extra answer key
MCQs: 1. A 2. A 3. A 4. A 5. A 6. A
Short
1. `isnull/sum; fillna; dropna`.
2. $85+78+92=255/3=85.0$.
3. If inventing a value would lie (unknown category, huge outlier).
4. Booleans True where missing.
Long
1. Counts 1 and 1. Sara marks 85.0, Ahmed grade Not Assigned. Code + table. Warn about `dropna` deleting two rows if used first.

4.4 Data Organization and Representation

LEARN IT

Organised data is easier to read. Three everyday forms:

- **Table** — exact values side by side (Ali 85 Math, 80 Science).
- **Frequency distribution** — how many items fall in each range (bin).
- **Graph** — a picture of a trend or comparison (next topics).

Range of marks	Frequency (students)
50–59	5
60–69	7
70–79	9
80–89	4
90–100	2

Most students scored 70–79. That pattern is hard to see in a raw list of 27 marks, and obvious in this table. Matplotlib (`import matplotlib.pyplot as plt`) turns tables into graphs: `import` → `figure` → `plot` → `labels` → `title` → `show()` .

اردو میں سمجھیں

ٹیبل درست عدد دکھاتی ہے، تعدد کی جدول بتاتی ہے کتنے طلبہ کس رینج میں ہیں، گراف رجحان دکھاتا ہے۔ میٹپلاٹ لب گراف بناتی ہے۔

CHECK YOURSELF

1. How many students scored 80 or above in the table?
2. Name the library that draws graphs in Python.

Answers: 1. $4 + 2 = 6$. 2. Matplotlib (pyplot).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Tabular form is for:

- a. Exact values in rows/columns
- b. Only a pretty poster
- c. Only NAND
- d. Only sprints

MCQ 2. A frequency table shows:

- a. How many in each bin/range
- b. The ER diagram
- c. The OSI stack
- d. The Figma layers

MCQ 3. Most students in the notes' table scored:

- a. 70–79
- b. 90–100
- c. 0–10
- d. Exactly 100

MCQ 4. Graphical representation is for:

- a. Seeing patterns fast
- b. Storing PKs
- c. Compiling C
- d. Routing

MCQ 5. Matplotlib import line:

- a. `import matplotlib.pyplot as plt`
- b. `import pie`
- c. `import osi`
- d. `import nand`

MCQ 6. `plt.show()` :

- a. Renders the figure
- b. Commits SQL
- c. Closes sqlite
- d. Starts Figma

Extra short questions

1. Three organisation methods in the notes.
2. From the frequency table, how many scored 80+?
3. Steps of a matplotlib figure.
4. Why frequencies for large n?

Extra long question

1. Build a frequency table for 12 marks you invent, then say which graph you would draw and why. Include axis titles.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Table, frequency distribution, graph.
2. $4+2=6$.
3. `import`, `figure`, `plot`, `labels`, `title`, `show`.
4. A list of 2000 marks is unreadable; bins are not.

Long

1. Bins of 10. Most-filled bin noted. Histogram (numeric distribution) or column if you treat bands as categories — say which and why bars touch or not.

4.5 Data Visualization & Types of Graphs ★ Golden

LEARN IT

Pick the graph that matches the question. Then label axes and give a title — an unlabelled chart scores zero in an exam.

Chart	Shows	Watch out
Bar / column	Compare discrete categories (subjects, departments)	Column = vertical; bar often = horizontal
Line	Change over time (temperature, visitors)	Needs an ordered x-axis (months, years)
Pie	Parts of one whole as percentages	Bad with many or almost-equal slices
Histogram	Distribution of one numeric variable in bins	Bars touch (continuous range), unlike a bar chart
Scatter	Relationship of two numeric variables	Each dot is one pair (x, y)
Box plot	Min, Q1, median, Q3, max, and outliers	Best tool for spotting extreme values

4.5.1 Bar / column

```
import matplotlib.pyplot as plt
subjects = ["English", "Math", "Science", "History"]
marks = [64, 82, 71, 49]
plt.bar(subjects, marks, color="skyblue", edgecolor="black")
plt.title("Marks vs Subjects")
plt.xlabel("Subjects")
plt.ylabel("Marks out of 100")
```

4.5.2 Line

```
months = ["Jan", "Feb", "Mar", "Apr", "May", "Jun"]
temps = [12, 15, 20, 25, 30, 35]
plt.plot(months, temps, markers="o")
plt.title("Average Monthly Temperature")
plt.grid(True)
```

4.5.3 Pie

```
subjects = ["Math", "Physics", "CS", "Biology"]
students = [25, 15, 30, 10] # total 80
plt.pie(students, labels=subjects, autopct="%1.1f%%", startangle=90)
```

Check: Math 25/80 = 31.25% → 31.2%. Physics 15/80 = 18.8%. CS 30/80 = 37.5%. Biology 10/80 = 12.5%.

4.5.4 Histogram

```
scores = [45, 50, 55, 60, 62, 65, 68, 70, 72, 75, 78, 80, 82, 85, 90, 95]
plt.hist(scores, bins=[40, 50, 60, 70, 80, 90, 100], edgecolor="black")
```

4.5.5 Scatter

```
plt.scatter([10, 20, 30, 40, 50, 60, 70, 80],
            [2, 4, 5, 4, 7, 8, 9, 12], color="green", alpha=0.7)
plt.title("Rainfall vs Crop Yield") # positive correlation
```

4.5.6 Box plot

```
plt.boxplot([[55, 60, 65, 70, 75, 80, 85],
            [40, 65, 70, 72, 75, 80, 95]],
            tick_labels=["Class A", "Class B"])
```

The box is the middle 50% (Q1 to Q3). The line inside is the median. Whiskers reach min and max (or a fence, with outliers drawn as dots). Class B is more spread out than Class A.



Column compares; line shows a trend; pie shows share; the box summarises spread around the median.

EXAM TIP

"Which graph and why?" is a 3-mark gift. Write the name, what it shows, and one reason the others are worse.

آرٹو میں سمجھیں

بار/کالم اقسام کا موازنہ، لائن وقت کا رجحان، پائی حصے، ہسٹوگرام مسلسل تقسیم (دار آیس میں لگی)، اسکینڈر دو متغیرات کا تعلق، ہائکس پلاٹ پانچ اعداد اور آؤٹ لائن۔

CHECK YOURSELF

1. Why do histogram bars touch?

2. Rainfall vs yield — which chart?

Answers: 1. The x-axis is a continuous numeric range, not separate categories. 2. Scatter (two numeric variables, looking for correlation).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Bar/column charts compare:

- a. Discrete categories
- b. Parts of one whole only
- c. A single time point of one var as a distribution
- d. A 5-number summary

MCQ 2. Line graphs are for:

- a. Trends over time
- b. Unrelated categories with gaps
- c. Shares of a budget
- d. Outliers in five numbers

MCQ 3. Pie charts need:

- a. Parts of one whole; few slices
- b. 60 slices of 1%
- c. Time on x
- d. Two numeric axes of correlation

MCQ 4. Histogram bars:

- a. Touch (continuous bins)
- b. Must have large gaps
- c. Are always time
- d. Replace the mean

MCQ 5. Scatter plots show:

- a. Two numeric variables (correlation)
- b. One category vs colour
- c. FIFO order
- d. OSI layers

MCQ 6. A box plot shows:

- a. Min, Q1, median, Q3, max (+ outliers)
- b. Only the mean
- c. Only mode
- d. Only n

Extra short questions

1. One-line job of each of the six charts.
2. Why histogram ≠ bar.
3. When pie fails.
4. Rainfall vs yield?

Extra long question

1. Six school questions → pick the chart and a matplotlib function (bar, plot, pie, hist, scatter, boxplot). Justify in one sentence each. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Bar categories; line time; pie share; hist distribution; scatter relationship; box spread/outliers.
2. Numeric bins, touching bars vs separate categories.
3. Too many / nearly equal slices.
4. Scatter; look for positive correlation.

Long

1. Enrolment by faculty: bar. Hits by month: plot. Club shares: pie. Heights: hist. Hours vs marks: scatter. Two classes' spread: boxplot. Unlabelled charts score 0.

4.6 Descriptive Statistics ★ Golden

LEARN IT

Descriptive statistics squeeze a long list into a few honest numbers. **Central tendency** asks “what is typical?”. **Spread** asks “how mixed is the list?”.

4.6.1 Mean, median, mode

Measure	How	Use when
Mean	Sum ÷ n. Uses every value.	Values sit close together. Example: ordinary test scores.
Median	Middle after sorting. Odd n: centre. Even n: mean of the two centre values.	Outliers would wreck the mean (CEO salary).
Mode	Most frequent value. May be none, one, or several.	Most popular choice (shoe size).

WORKED EXAMPLE

Marks 70, 80, 90. Mean = 240/3 = 80.
Odd list 35, 10, 15, 70, 95. Sort: 10, 15, 35, 70, 95. Median = 35.
Bottles sold 20, 25, 20, 30, 20, 30, 25, 20. Mode = 20 (appears four times).
Outlier trap: nine people earn 10, one earns 1000. Mean = 1090/10 = 109 (looks rich). Median = 10 (tells the truth).

4.6.2 Spread: range, variance, standard deviation, min, max

- Min / max — smallest and largest. Marks 70, 80, 90, 60, 75 → min 60, max 90.
- Range = max – min. Sales 120, 150, 180 → range 60.
- Population variance $\sigma^2 = \frac{1}{n} \sum (x_i - \mu)^2$.
- Sample variance s^2 uses $\frac{1}{n-1}$. pandas.Series.std() uses the sample version.
- Standard deviation $\sigma = \sqrt{\sigma^2}$. Same units as the data (marks, not marks²). Low SD → tight, consistent. High SD → spread out, unpredictable.

$$\sigma^2 = \frac{1}{n} \sum_{i=1}^n (x_i - \mu)^2, \quad \sigma = \sqrt{\sigma^2}, \quad s^2 = \frac{1}{n-1} \sum_{i=1}^n (x_i - \bar{x})^2$$

WORKED EXAMPLE

Full working on 70, 80, 90. Mean $\mu = 80$. Deviations -10, 0, +10. Squares 100, 0, 100. Sum = 200.
Population variance $\sigma^2 = 200/3 = 66.67$ (2 d.p.). Population SD $\sigma = \sqrt{200/3} = 8.16$ (2 d.p.).
Sample variance $s^2 = 200/2 = 100$. Sample SD $s = 10$. That is what pd.Series([70,80,90]).std() returns.

EXAM TIP

Always state whether you used n or n-1. Show the sorted list for the median. For SD, show: mean → deviations → squares → divide → square root. A box plot pictures min, Q1, median, Q3, max of the same data.

COMMON MISTAKE

Do not report variance as if it were in “marks”. Variance is marks². Quote the standard deviation when you want a sentence in the original units.

اردو میں سمجھیں

اوسط سب کا مجموعہ تقسیم تعداد، میڈین ترتیب کے بعد بیچ، موڈ سب سے زیادہ بار آنے والا۔ رینج بڑا منفی چھوٹا۔ ویرینس اوسط سے فاصلوں کے مربع کی اوسط ہے، معیاری انحراف اس کا جذر ہے اور اصل اکائی میں ہوتا ہے۔ پینڈا (n-1) نمونے والا (n-1) استعمال کرتا ہے۔

CHECK YOURSELF

1. Median of 4, 8, 6, 10, 2?
2. Range of 120, 150, 180?
3. Does pandas .std() divide by n or n-1?

Answers: 1. Sorted 2,4,6,8,10 → 6. 2. 60. 3. n-1 (sample).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Mean of 70,80,90 is:
a. 80
b. 70
c. 90
d. 240

MCQ 2. Median of 10,15,35,70,95 is:
a. 35
b. 10
c. 70
d. 45

MCQ 3. Mode of 20,25,20,30,20,25,20 is:
a. 20
b. 25
c. 30
d. 7

MCQ 4. Range of 120,150,180 is:
a. 60
b. 30
c. 150
d. 180

MCQ 5. pandas .std() uses:
a. n-1 (sample)
b. n always
c. 2n
d. zero

MCQ 6. SD is the square root of:
a. Variance
b. Mean
c. Median
d. n

Extra short questions

1. When mean vs median vs mode.
2. Population variance formula idea.
3. Why square root for SD?
4. Outlier trap with 9×10 and one 1000.

Extra long question

1. For 4,8,8,10,2 compute mean, median, range, population variance and SD. Then say what pandas std reports. Show every step. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Mean typical no outliers; median with outliers; mode popular category/value.
2. Mean of squared deviations; ÷n. Sample ÷ (n-1).
3. Back to original units.
4. Mean 109 vs median 10.

Long

1. Sorted 2,4,6,8,10. Mean 6, median 6, range 8. Devs -4,-2,0,2,4 sq 16,4,0,4,16 sum 40. $\sigma^2=8$, $\sigma=\sqrt{8}=2.828$. pandas 40/4=10, $\sqrt{10}=3.162$.

Data and Analysis

8 single-page lessons · 5 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- Data analysis turns raw facts into decisions. Python reads files and databases, calculates and plots.
- Connection chain: database → driver → connection → cursor → SQL.
- SQLite: connect, cursor, execute, commit, fetchall, close. No commit means no save.
- A DataFrame is a 2-D table. Load with a dictionary, `read_csv` or `read_excel`. New columns are vectorised arithmetic.
- NaN: find (`isnull`), fill (`fillna` , often with the mean), or drop (`dropna`).
- Tables give exact values; frequency bins show how many in each range.
- Bar/column = categories; line = time; pie = parts of a whole; histogram = numeric distribution (touching bars); scatter = two variables; box = five-number summary + outliers.
- Mean uses every value and is sensitive to outliers; median is the middle; mode is the most common.
- Range = max–min. Variance = mean squared deviation ($\div n$ or $\div n-1$). SD = $\sqrt{\text{variance}}$. pandas `.std()` uses $n-1$.

Key terms

Term	Meaning	اردو
Data analysis	Examining data to extract useful information.	ڈیٹا کا تجزیہ
Connectivity	Link between a program and a data source.	رابطہ کاری
Driver	Translator between Python and a DBMS.	ڈرائیور
Connection	Open pipeline to the database.	کنکشن
Cursor	Object that executes SQL and fetches rows.	کرسر
SQLite	Built-in file-based database.	ایس کیو لائٹ
commit	Save INSERT/UPDATE/DELETE to disk.	کمیت / محفوظ کرنا
Pandas	Library for table-like data.	پینڈاز
DataFrame	2-D labelled table of rows and columns.	ڈیٹا فریم
NaN	Missing value ("Not a Number").	خالی / غیر موجود قدر
Frequency	How many items fall in a class/bin.	تعدد
Histogram	Distribution chart whose bars touch.	ہسٹوگرام

Data and Analysis

75 marks · 1 hour 15 minutes · no notes · no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 08 and the recap. **Section A** — all 15 MCQs (1 mark). **Section B** — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define · Explain · Example · Diagram · Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. The object that executes SQL is the:
 - a. driver
 - b. cursor
 - c. DataFrame
 - d. histogram
2. After INSERT you must:
 - a. close then commit
 - b. commit
 - c. drop the table
 - d. call head()
3. Pandas is installed with:
 - a. import pandas
 - b. pip install pandas
 - c. sqlite3.connect
 - d. plt.show()
4. `df.head()` shows:
 - a. the last 5 rows
 - b. the first 5 rows
 - c. only NaNs
 - d. the standard deviation
5. Missing Pandas values appear as:
 - a. NULL in every chart
 - b. NaN
 - c. 0 always
 - d. a pie slice
6. To delete every row that contains a gap:
 - a. fillna
 - b. dropna
 - c. fetchall
 - d. commit
7. A line graph is best for:
 - a. parts of a whole
 - b. a trend over months
 - c. two unrelated categories
 - d. a primary key
8. Histogram bars:
 - a. must have gaps
 - b. touch, because bins are a continuous range
 - c. always show time
 - d. replace the mean
9. Rainfall vs crop yield is a:
 - a. pie chart
 - b. scatter plot
 - c. primary key
 - d. mode
10. A box plot's inner line is the:
 - a. mean
 - b. mode
 - c. median
 - d. range
11. Mean of 70, 80, 90 is:
 - a. 70
 - b. 80
 - c. 90
 - d. 240
12. Median of 10, 15, 35, 70, 95 is:
 - a. 10
 - b. 35
 - c. 70
 - d. 45
13. Mode of 20, 25, 20, 30, 20, 25, 20 is:
 - a. 25
 - b. 30
 - c. 20
 - d. 7
14. Range of 120, 150, 180 is:
 - a. 30
 - b. 60
 - c. 150
 - d. 180
15. pandas `.std()` divides by:
 - a. n
 - b. n-1
 - c. 2n
 - d. zero

Section B — Short questions (10 × 3 = 30)

1. List the five components of a Python database connection in order.
2. Why is `conn.commit()` required after INSERT?
3. What is a DataFrame? How do you load a CSV into one?
4. Differentiate `fillna` and `dropna`.
5. When is a pie chart a poor choice?
6. Differentiate a bar chart and a histogram.
7. Why is the median better than the mean for company salaries?
8. Define range, min and max with the list 70, 80, 90, 60, 75.
9. Why do we take the square root of variance?
10. State two careers that use this chapter's skills.

Section C — Long questions (attempt any 3 × 10 = 30)

1. Write a complete Python program that creates `school.db`, a `students` table, inserts Ali 85 and Sara 90, commits, prints all rows, and closes. Number the five connection components beside the matching lines.
2. Starting from the dictionary of Ali/Sara/Ahmed marks, write Pandas code to build a DataFrame, add Total and Average columns, and print it. Show the exact output.
3. Given Marks [85, None, 78, 92] and Grade ["A","A", None, "A"], show `isnull().sum()`, then fill Marks with the mean and Grade with "Not Assigned". Compute the mean by hand.
4. For each goal pick a chart and justify in one sentence: (a) CS vs IT vs Eng enrolment, (b) website hits from Jan to Jun, (c) share of four clubs in one college, (d) distribution of 200 heights, (e) hours studied vs marks, (f) comparing spread of two classes.
5. For 4, 8, 6, 10, 2 compute mean, median, range, population variance and population SD. Show every step. Then say what pandas `.std()` would report instead.
6. Explain, with a numeric example, how an outlier distorts the mean but not the median. Link this to when you would draw a box plot.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

- 4.1 Concept of Data Analysis.** Answers: 1. Study results to improve teaching (or similar). 2. Any two: read CSV/Excel/databases, organise tables, statistics, charts.
- 4.1.1– 4.1.2 Data Sources and Database Connection.** Answers: 1. The cursor. 2. SQLite is the database; the `sqlite3` module is the driver.
- 4.2 Creating a SQLite Database in Python.** Answers: 1. All columns. 2. `conn.commit()`.
- 4.3 Basic Operations on Data using Pandas.** Answers: 1. The usual alias for pandas. 2. It would print everything; use `df.head()`.
- 4.3.3 Handling Missing Values (NaN).** Answers: 1. Count of NaNs in each column. 2. Any **row** that contains at least one NaN.
- 4.4 Data Organization and Representation.** Answers: 1. $4 + 2 = 6$. 2. Matplotlib (pyplot).
- 4.5 Data Visualization & Types of Graphs.** Answers: 1. The x-axis is a continuous numeric range, not separate categories. 2. Scatter (two numeric variables, looking for correlation).
- 4.6 Descriptive Statistics.** Answers: 1. Sorted 2,4,6,8,10 → 6. 2. 60. 3. $n-1$ (sample).

Answer key

Multiple choice

1. b
2. b
3. b
4. b
5. b
6. b
7. b
8. b
9. b
10. c
11. b
12. b
13. c
14. b
15. b

Short questions — model answers

1. Database, driver, connection object, cursor object, SQL queries.
2. Without commit the insert stays in memory and disappears when the program ends, so the next run cannot see the row.
3. A 2-D table of labelled rows and columns. `df = pd.read_csv("file.csv")`.
4. `fillna(v)` replaces NaN with v (the row stays). `dropna()` deletes any row that still contains a NaN.
5. When there are many slices, or the values are almost equal, so the eye cannot compare them.
6. Bar: separate categories, gaps between bars. Histogram: one numeric variable grouped into bins; bars touch.
7. A huge CEO salary pulls the mean up; the median stays with the typical worker.
8. Min 60, max 90, range 30.
9. Variance is in squared units. The SD brings the spread back to the original units (marks, rupees, °C).
10. Any two: data analyst, DBA, data scientist, visualisation specialist, BI analyst, backend developer.

Long questions — model answers

1. Use the nine-step listing in 4.2 with two INSERTs. Label: sqlite3 = driver, connect = connection, cursor = cursor, execute strings = SQL, school.db = database.
2. Output is the three-row table with Total 165, 178, 148 and Average 82.5, 89.0, 74.0 (see the worked example).
3. isnull sum: Marks 1, Grade 1. Mean of 85, 78, 92 = $255/3 = 85.0$. After fill: Sara Marks 85.0, Ahmed Grade "Not Assigned".
4. (a) column/bar — compare categories. (b) line — time. (c) pie — parts of a whole. (d) histogram — numeric distribution. (e) scatter — two numeric variables. (f) box — spread and outliers.
5. Sorted 2,4,6,8,10. Sum 30, mean 6, median 6, range 8. Deviations -4,-2,0,2,4. Squares 16,4,0,4,16 sum 40. $\sigma^2 = 40/5 = 8$. $\sigma = \sqrt{8} = 2.828$ (3 d.p.). pandas `.std()` uses $40/4 = 10$, $\sqrt{10} \approx 3.162$.
6. Nine salaries of 10 and one of 1000: mean 109, median 10. Draw a box plot — the 1000 appears as an outlier dot above the whisker, so the distortion is visible.

Self-assessment: I can...

- | | |
|--|--|
| ☐ name the five connection components in order. | ☐ write SQLite connect / create / insert / commit / select / close. |
| ☐ build a DataFrame and add a calculated column. | ☐ find, fill and drop missing values. |
| ☐ choose bar, line, pie, histogram, scatter or box for a problem. | ☐ compute mean, median, mode, range, variance and SD by hand. |
| ☐ state that pandas std uses $n-1$. | |

Lecture 05

Application and Impacts of Computing

Chapter lecture — 15 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XII · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — بارہویں جماعت

15 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XII

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیئریر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

Lectures in this pack

Chapter 5: Application and Impacts of Computing. Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 5.1 Machine Learning, Neural Networks & Deep Learning

L02. 5.1.1 Machine Learning (ML)

L03. 5.1.2 Neural Networks (NN)

L04. 5.1.3 Deep Learning (DL)

L05. 5.1.4 Components of Neural Networks

L06. 5.1.5 Components of Deep Learning

L07. 5.2 Applications of Neural Networks and Deep Learning

L08. 5.3 Secure Collaboration (Authentication, Access Control)

L09. 5.3.2 Data Protection (Encryption, Passwords, Backup, Firewall)

L10. 5.4 Security Threats and Mitigation Techniques

L11. 5.4.2 Identify Security Threats

L12. 5.4.3 Apply Mitigation Techniques

L13. 5.5 Equity and Equal Access in Digital Collaboration

L14. 5.5.1 Functions of Equity and Equal Access

L15. 5.5.2 Collaboration Tools

Application and Impacts of Computing

This chapter shows you how computers learn from data with machine learning, neural networks and deep learning, how to collaborate online without leaking secrets, how to protect data and stop cyber threats, and how to keep digital teamwork fair for every student in Sindh.

اس باب میں آپ سیکھیں گے کہ مشین لرننگ، نیورل نیٹ ورکس اور ڈیپ لرننگ کمپیوٹر کو ڈیٹا سے کیسے سکھاتے ہیں، ان لائن کام کو محفوظ کیسے رکھا جائے، ڈیٹا کی حفاظت اور سائبر خطرات کا مقابلہ کیسے کیا جائے، اور ڈیجیٹل تعاون کو سب کے لیے منصفانہ کیسے بنایا جائے۔

What you will learn

- Define **machine learning (ML)** and describe the three steps: data input, learning, prediction.
- Define **deep learning (DL)** and draw the relationship **AI $\supset$ ML $\supset$ DL**.
- List the six components of deep learning and give applications of NN and DL in daily life and in Pakistan.
- Protect data using encryption (including a Caesar cipher), strong passwords, the 3-2-1 backup rule and a firewall.
- Distinguish **equal access** from **equity** and describe the functions of equity in digital collaboration.
- Explain a **neural network (NN)** as a brain-inspired model with an input layer, hidden layers and an output layer.
- Name the eight components of a neural network and compute a neuron's output from given numbers.
- Explain **secure collaboration**: authentication, multi-factor authentication (MFA) and access control.
- Identify common threats (malware, phishing, DoS) and apply mitigation techniques.
- Name common collaboration tools and use them fairly and safely.

5.1 Machine Learning, Neural Networks & Deep Learning

LEARN IT


Machine learning (ML), neural networks (NN) and deep learning (DL) are important areas of **artificial intelligence (AI)**. **AI** is the broad field in which computers perform tasks that normally need human thinking, such as recognising a face, understanding speech or making a decision.

These technologies help computers **learn from data** and make useful decisions **without being explicitly programmed for every single step**. You do not write a separate rule for every possible face or every Urdu accent. You show the computer many examples, and it finds the patterns itself.

They are used in many modern systems:

- **Face unlock** on smartphones.
- **Speech recognition** (for example Siri, Alexa, or Urdu voice typing on a phone).
- **Photo search** categorisation (typing "car" in a gallery and seeing car photos).
- **Medical diagnosis** from X-rays and scans.
- **Language translation** (English to Urdu or Sindhi).

Remember the nesting: **AI is the biggest set**. Inside AI sits **ML**. Inside ML sits **DL**. Every deep-learning system is a kind of machine learning, and every machine-learning system is a kind of AI — but not every AI system is deep learning.



The set relationship AI > ML > DL. Deep learning is a method of machine learning; machine learning is a part of artificial intelligence.

WORKED EXAMPLE

Worked example: place each system in the correct set. Sara in Karachi uses three features on her phone.

1. A **chess app that follows fixed if-then rules** written by a programmer ("if the queen is attacked, move it"). This is **AI** (the machine decides), but it is **not ML**, because it does not learn from data.
2. A **JazzCash fraud filter** that was trained on thousands of past transactions and then flags a new unusual payment. This is **ML** (and therefore also AI). If it uses only a simple model with few layers, it may **not** be DL.
3. **Face unlock** that studied millions of face images through many hidden layers. This is **DL** — and therefore also ML and AI.

Exam sentence you can write: *All DL is ML, all ML is AI, but not all AI is ML, and not all ML is DL.*

REMEMBER IT

Russian-doll memory trick. Picture three boxes. The outer box is **AI**. Inside it is a smaller box **ML**. Inside that is the smallest box **DL**. You cannot take DL out of ML, and you cannot take ML out of AI.

COMMON MISTAKE

Mistake: "AI, ML and DL are three different, separate subjects."

Fix: They nest. DL < ML < AI. A deep-learning face-unlock system is all three at once.

اردو میں سمجھیں

مصنوعی ذہانت (AI) سب سے بڑا میدان ہے۔ اس کے اندر مشین لرننگ (ML) ہے، اور مشین لرننگ کے اندر ڈیپ لرننگ (DL) ہے۔ یہ لیکنالوجیز کمپیوٹر کو ڈیٹا سے سکھاتی ہیں تاکہ ہر قدم الگ الگ پروگرام کے بغیر فیصلے کیے جا سکیں، جیسے چہرے سے فون کھولنا یا آواز پہچاننا۔

CHECK YOURSELF

1. Which is the largest set: AI, ML or DL?
2. Is every neural-network face-unlock system an example of AI? Why?
3. Give one modern system from this section that uses these technologies.

Answers: 1. AI (AI > ML > DL). 2. Yes — DL is inside ML, and ML is inside AI. 3. Any of: face unlock, speech recognition, photo search, medical diagnosis, language translation.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. ML, NN and DL are parts of: a. AI b. OSI layer 1 only c. Access wizards only d. Waterfall only	MCQ 2. They all need: a. Data to learn from b. Only copper cable c. Only primary keys d. Only Figma	MCQ 3. The course order is: a. ML as the idea, NN as a model, DL as deep NNs b. DL then stone tools c. SQL then NAND d. HCI then K-maps	MCQ 4. Pakistan's AI policy is mentioned as: a. A future/local context b. A Python library c. A chart type d. A file mode	MCQ 5. A student mistake is: a. Treating the three terms as identical b. Giving one example c. Mentioning data d. Mentioning layers
MCQ 6. This lecture is the map; later ones: a. Define each term properly b. Delete the chapter c. Only careers d. Only MVPs				

Extra short questions

1. Place ML, NN, DL in one nested sentence.
2. What do they share?
3. What should an XI/XII answer still include?
4. One Pakistani hope from the notes.

Extra long question

1. Draw a nested diagram AI > ML > NN > DL and write one example at each ring.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. DL is a kind of NN which is a way to do ML which is a kind of AI.
2. Learn patterns from data instead of only hand-written rules.
3. A human-responsible, data-quality, bias warning.
4. Agriculture, health, Urdu NLP, public service — any from the book.

Long

1. AI: chess rules engine. ML: spam filter. NN: digit recognition. DL: speech-to-Urdu. One limit at the DL ring (needs lots of data/compute).

5.1.1 Machine Learning (ML)

LEARN IT

A **machine learning model** is the system that **learns from data and gives an output**. Think of it as the **trained brain** of a computer program.

In ordinary programming you write every rule yourself: *If marks ≥ 40 then "Pass"*. In machine learning you **do not list every rule**. You give the model many examples (data), it finds the patterns, and later it decides about new cases it has never seen.

How it works — three steps:



1. **Data input.** The model is given massive amounts of data — for example thousands of past BISE marksheets, or millions of crop photos from Sindh fields.
2. **Learning.** It studies the data and **learns patterns and rules automatically**. It might notice that students who scored low in Chapter 3 also failed the board exam, or that yellow spots on cotton leaves often mean a pest.
3. **Prediction.** After training, it can make **accurate predictions or decisions** when given **new, unseen data** — a new student's record, or a new leaf photograph.

Note from the source: there are many types of machine-learning models. A **neural network** is one important type. **Deep learning** is a highly advanced method of machine learning.

WORKED EXAMPLE

Worked example: a wheat-yield model for a farm near Sukkur.

Step 1 — Data input. For 8 years the farm recorded: rainfall (mm), temperature, fertiliser bags used, and the actual yield (maunds per acre).

Step 2 — Learning. The model studies those rows. It finds, for example, that yield rises with fertiliser up to a point, and falls when temperature is very high in April.

Step 3 — Prediction. This year the farmer types in this season's rainfall and temperature. The model has never seen this exact year before, but it predicts "about 32 maunds per acre." The farmer plans storage and a buyer in advance.

Nobody wrote a giant list of "if rain = 120 and temp = 38 then yield = ...". The model learned the pattern from data.

REMEMBER IT

D-L-P. Machine learning is **D**ata in, **L**earn patterns, **P**redict. "Data Learns to Predict."

COMMON MISTAKE

Mistake: "The computer is intelligent on day one."

Fix: An ML model is useful only **after training** on enough good data. Garbage data → garbage predictions. Also, neural networks are one type of ML, not the only type; deep learning is a *method* that uses deep neural networks.

اردو میں سمجھیں

مشین لرننگ ماڈل وہ نظام ہے جو ڈیٹا سے سیکھ کر نتیجہ دیتا ہے — کمپیوٹر پروگرام کا تربیت یافتہ دماغ۔ پہلے بہت سا ڈیٹا دیا جاتا ہے، پھر ماڈل خود اصول اور پیٹرن سیکھتا ہے، اور تربیت کے بعد نئے ان دیکھے ڈیٹا پر پیش گوئی کرتا ہے۔ فیوڈل نیٹ ورک مشین لرننگ کی ایک اہم قسم ہے، اور ڈیپ لرننگ اس کا ایک اعلیٰ طریقہ ہے۔

CHECK YOURSELF

1. What are the three steps of how an ML model works?

2. What is a machine-learning model compared to in the source?

3. After training, what kind of data can the model handle?

Answers: 1. Data input, learning, prediction. 2. The trained brain of a computer program. 3. New, unseen data.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Machine learning lets a model:

a. Improve from examples, not only hard-coded rules

b. Run without data

c. Replace all maths

d. Ignore errors always

MCQ 2. Training data is:

a. Examples used to fit the model

b. The final user password

c. OSI headers

d. Figma frames

MCQ 3. A model that memorizes noise is:

a. Overfitting

b. Perfect science

c. A stack

d. A pie

MCQ 4. Supervised learning uses:

a. Labels (the right answers)

b. No data

c. Only unsupervised always

d. Only cables

MCQ 5. ML in this book is the "trained brain" metaphor for:

a. Mapping inputs to outputs after seeing examples

b. A DBMS trigger

c. A foreign key

d. A sprint

MCQ 6. Garbage data yields:

a. Garbage predictions

b. Perfect fairness

c. $O(1)$ time always

d. Free RAM

Extra short questions

1. Define ML in the book's words/your own accurate line.

2. Give two applications.

3. What is a label?

4. One ethical issue.

Extra long question

1. Explain ML to a principal who wants to predict drop-outs: data, train, test, a risk, a human check.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. A model that learns from data to produce outputs without being explicitly programmed for every case.

2. Spam; recommendations; marks prediction; vision.

3. The known answer attached to a training example.

4. Bias in the training data is copied into decisions.

Long

1. Past attendance+marks → model → test on held-out year. Risk: punishing poverty correlated with absence. Human counsellor decides, model only flags.

5.1.2 Neural Networks (NN) ★ Golden

LEARN IT

A **neural network** is a computer model that **learns patterns from data**. It is **directly inspired by the human brain**, but it works as a **mathematical computer system** — not as living tissue.

Your brain has billions of nerve cells (**neurons**) that pass signals to each other. A neural network copies this idea with small processing units also called **neurons** or **nodes**. These nodes are **connected** and **pass information from one layer to another**, performing calculations at each step.

A typical neural network has three kinds of layer:

- **Input layer** — receives the raw data (pixels of a face, samples of a sound, marks of a student).
- **Hidden layer(s)** — the “thinking” in the middle. Nodes here combine the inputs and learn features (eye distance, nose shape, an edge in a photo).
- **Output layer** — gives the final answer (unlock / keep locked; “this is a cat”; “pass / fail”).



WORKED EXAMPLE

Practical example from the source: face unlock.

Step 1 — Input layer. You look at your phone. The camera captures your face as numbers (brightness of each pixel). Those numbers enter the input layer.

Step 2 — Hidden layers. The system studies face features such as **eye distance** and **nose shape**. Early hidden nodes may detect edges and shadows; later hidden nodes combine those into “this looks like Sara’s face.” It compares them with stored data from when you first set up the phone.

Step 3 — Output layer. If the features match, the phone **unlocks**. If they do not (your brother holds the phone), it stays locked.

The same three-layer story works for an NADRA-style biometric gate at a college: camera (input) → feature matching (hidden) → open the turnstile or not (output).

REMEMBER IT

I-H-O. Input receives, Hidden thinks, Output decides. “In Hidden Out.” A neural network is a **brain-inspired maths machine**, not a copy of a living brain.

COMMON MISTAKE

Mistake: “A neural network is an actual human brain inside the computer.”

Fix: It is only **inspired by** the brain. It is mathematics: numbers, multiplications and additions running on ordinary hardware.

اردو میں سمجھیں

نیورل نیٹ ورک ایک کمپیوٹر ماڈل ہے جو ڈیٹا سے پیٹرن سیکھتا ہے۔ یہ انسانی دماغ سے متاثر ہے مگر ایک ریاضیاتی نظام کے طور پر کام کرتا ہے۔ چھوٹی اکائیاں نیوروں یا نوڈ کہلاتی ہیں، جو تجربوں میں جڑی ہوتی ہیں: ان پٹ تہ ڈیٹا لیتی ہے، پوشیدہ تہ سوچتی ہے، اور آؤٹ پٹ تہ فیصلہ دیتی ہے — جیسے چہرے سے فون کھولنا۔

EXAM TIP

Very common questions: “What is a neural network?” (2–3 marks), “Name its three layers and explain each with the face-unlock example” (5 marks), and “How is a neural network related to the human brain?”

Full-mark recipe: (1) definition — computer model that learns patterns from data, inspired by the brain, mathematical; (2) neurons/nodes connected across layers; (3) Input / Hidden / Output, each in one sentence; (4) walk the camera → features (eye distance, nose shape) → unlock path. Draw the three boxes if the paper asks for a diagram.

CHECK YOURSELF

1. What are the small processing units of a neural network called?

2. In face unlock, which layer studies eye distance and nose shape?

3. Is a neural network a living brain? Explain in one sentence.

Answers: 1. Neurons or nodes. 2. Hidden layers. 3. No — it is inspired by the brain but works as a mathematical computer system.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A neural network is inspired by:

a. The brain's networks of neurons (loosely)
b. OSI cables
c. Access forms
d. Bubble sort

MCQ 2. It learns:

a. Weights that turn inputs into outputs
b. SQL indexes
c. TCP windows
d. Figma auto-layout

MCQ 3. Simple NNs have:

a. Input, hidden, output layers
b. Only a pie
c. Only one Excel cell
d. No numbers

MCQ 4. This is ★: define, then:

a. One diagram + two uses
b. Only careers
c. Only MVPs
d. Only keys

MCQ 5. NN vs linear formula:

a. NN can stack non-linear layers for complex patterns
b. NN cannot use data
c. NN is a queue
d. NN is HCI only

MCQ 6. Digits on paper are a classic:

a. NN / vision example
b. Primary key example
c. Waterfall example
d. K-map example

Extra short questions

1. Define neural network.
2. Three layer types.
3. Two applications.
4. Need for data.

Extra long question

1. Draw a 3-layer net for pass/fail from 3 marks. Label input, hidden, output. Explain one training idea in words (weights change). ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. A computer model of connected units that learns patterns from data, loosely like neurons.
2. Input, hidden, output.
3. Image recognition; speech; translation.
4. Without enough varied examples the net does not generalise.

Long

1. 3 input nodes, few hidden, 1 output. Training: compare prediction to label, adjust weights. Limit: not a biological brain.

5.1.3 Deep Learning (DL)

LEARN IT

Deep learning is a machine-learning method in which computers use **multi-layer neural networks** to learn **complex patterns** from data.

The word **"deep"** is used because data passes through **several hidden layers** before the system produces the final output. Each layer learns a **different level of detail**:

- **Early layers** learn simple features — edges, shapes, colours.
- **Deeper layers** combine those simple features to understand complex patterns — a whole face, or a specific car model (a Cultus versus a Corolla).

A network with only one or two hidden layers is a **shallow** neural network. Deep learning is always "deep": it needs **huge amounts of data** and **processing power**.

Neural network vs deep learning

	Neural network (the model)	Deep learning (the method)
What it is	A system/model that has layers, nodes and connections to help it learn.	A specific method that trains neural networks containing many hidden layers .
Depth	Can be simple (shallow) with just one or two hidden layers.	Always "deep," requiring huge amounts of data and processing power to learn complex patterns.
Role	The architecture (the "machine").	The way we train a deep version of that machine.

WORKED EXAMPLE

Real-world example from the source: photo gallery search.

A modern gallery app on a smartphone uses deep learning to recognise faces, objects or places in thousands of photos.

Step 1. During training (done by the company, using millions of images) early layers learned edges and colours; deeper layers learned "wheel", "petal", "minaret".

Step 2. The trained network has already scanned your phone's photos and tagged them.

Step 3. You type **"car"** or **"flower"** in the search bar. The app instantly shows related photos because its deep neural network has already learned visual patterns from millions of training images.

A student in Hyderabad can type "Ajrak" or "cricket" and jump to those pictures without scrolling for ten minutes.

REMEMBER IT

Deep = many hidden layers. Shallow NN: 1–2 hidden layers. Deep NN: many hidden layers, huge data, strong computers. Simple features first, complex meaning later.

COMMON MISTAKE

Mistake: "Deep learning and neural networks are two names for the same thing."

Fix: A neural network is the **model** (layers + nodes + connections). Deep learning is the **method** of training networks that have **many** hidden layers. A small NN with one hidden layer is not deep learning.

اردو میں سمجھیں

ڈیپ لرننگ مشین لرننگ کا وہ طریقہ ہے جس میں کئی پوشیدہ تہوں والے نیورل نیٹ ورک استعمال ہوتے ہیں۔ "ڈیپ" اس لیے کہ ڈیٹا کئی تہوں سے گزر کر پیچیدہ پیٹرن سیکھتا ہے: پہلی تہیں کنارے اور رنگ سیکھتی ہیں، گہری تہیں پورا چہرہ یا گاڑی کی قسم پہچانتی ہیں۔ یہ طریقہ بہت سے ڈیٹا اور طاقتور کمپیوٹنگ کا طالب ہے۔

CHECK YOURSELF

1. Why is the method called "deep" learning?

2. What do early layers learn, and what do deeper layers learn?

3. Can a neural network with one hidden layer be called deep learning?

Answers: 1. Because data passes through several hidden layers. 2. Early: simple features (edges, shapes, colours). Deeper: complex patterns (a whole face, a car model). 3. No — that is a shallow network; DL always uses many hidden layers.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Deep learning uses:

a. Many-layer neural nets
b. One if-statement
c. Only Access macros
d. Only OSI

MCQ 2. "Deep" refers to:

a. Many hidden layers
b. Deep sea cables only
c. Deep stacks in Python only
d. Deep queues

MCQ 3. DL shines at:

a. Images, speech, complex patterns
b. Two-row Excel averages
c. Primary keys
d. K-maps of 2 vars

MCQ 4. A cost of DL is:

a. Lots of data and compute
b. No data needed
c. No energy use
d. Perfect fairness always

MCQ 5. DL is a subset of:

a. NN / ML / AI
b. HCI only
c. SQL only
d. SDLC only

MCQ 6. Medical imaging in the book is a:

a. DL application
b. A foreign key
c. A pie of NAND
d. A sprint

Extra short questions

1. Define deep learning.

2. How is it different from a shallow net?

3. Two applications.

4. One Pakistani constraint.

Extra long question

1. Compare ML vs NN vs DL in a 6-row table (definition, depth, data need, example, limit). 10 marks.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. ML using multi-layer neural networks to learn complex patterns.

2. More layers can build higher-level features (edges → shapes → faces).

3. X-ray analysis; voice assistants; translation.

4. GPUs/data/labels are expensive; start with smaller models.

Long

1. Clear nesting. Example row: spam vs digit net vs speech net. Limits: data, bias, black box, energy.

5.1.5 Components of Deep Learning

LEARN IT		
Deep learning relies on specific advanced components to achieve its high accuracy. These components differentiate it from basic machine learning .		
#	Component	What it means
1	Large input data	Deep learning is "data hungry." It needs massive datasets (thousands or millions of records) for better learning and accuracy.
2	Many hidden layers	Uses dozens or hundreds of hidden layers to learn deeper, more intricate patterns.
3	Automatic feature learning	Unlike older models where humans had to manually highlight important features, deep learning extracts important features by itself .
4	Learning algorithm	Math routines (like backpropagation) that help the system reduce mistakes and improve learning continuously.
5	High computing power	Processing millions of data points across deep layers needs specialised, strong hardware, such as GPUs (Graphics Processing Units).
6	Training process	The model is trained again and again in loops called epochs to gradually improve its final performance.

A **GPU** was originally made for video games' graphics, but it can do thousands of small multiplications in parallel — exactly what deep networks need. An **epoch** is one full pass through the training data. Ten epochs means the model has seen every training example ten times, adjusting weights a little each time.

Backpropagation means sending the error (from the loss function) **backwards** through the layers so each weight can be nudged in the direction that reduces the next error.

WORKED EXAMPLE

Worked example: cotton-leaf disease detector for a farm in Mirpurkhas. Match each DL component.

- 1. Large input data.** Researchers collect 80,000 labelled photos: healthy leaves and leaves with whitefly damage.
- 2. Many hidden layers.** The network has 20 hidden layers so it can go from "green edge" to "this exact pest pattern."
- 3. Automatic feature learning.** No agronomist types in "look for yellow circles." The network finds the useful spots itself.
- 4. Learning algorithm.** After a wrong guess ("healthy" when it was diseased), backpropagation lowers the weights that caused the mistake.
- 5. High computing power.** Training runs on a GPU workstation at a university lab in Karachi; a school laptop would take weeks.
- 6. Training process.** They train for 30 epochs. After epoch 1 accuracy is 62%; after epoch 30 it is 94% on photos it has not trained on.

REMEMBER IT

D-L-A-L-G-T. Data (lots), Layers (many), Automatic features, Learning algorithm, GPU power, Training epochs. "Deep Learners Always Love Good Training."

COMMON MISTAKE

Mistake: "Deep learning is just 'a neural network'."

Fix: Name the six extras: huge data, many hidden layers, automatic features, a learning algorithm (backpropagation), GPUs, and repeated epochs. A shallow NN with a small spreadsheet is ordinary ML, not DL.

آرڈو میں سمجھیں

ڈیپ لرننگ کو عام مشین لرننگ سے یہ چیزیں الگ کرتی ہیں: بہت بڑا ڈیٹا، بہت ہی پوسہیدہ تپیں، خود بخود خصوصیات نکالنا، سیکھنے کا الگورتھم جیسے بیک پروپیگیشن (Backpropagation)، طاقتور ہارڈویئر جیسا کہ جی پی یو (GPU)، اور بار بار تربیت جسے ایپوک (Epoch) کہتے ہیں۔

CHECK YOURSELF

1. Why is deep learning called "data hungry"?
2. What is an epoch?
3. Name the hardware often used for DL, and the learning algorithm named in the source.

Answers: 1. It needs massive datasets (thousands or millions of records) for accuracy. 2. One training loop — one full pass through the training data. 3. GPUs (Graphics Processing Units); backpropagation.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. DL components include:
a. Deep stacks of layers, lots of data, lots of compute, specialised architectures
b. A single if
c. A single Access form
d. A single NAND

MCQ 2. CNNs are often for:
a. Images
b. Undo stacks
c. Printer queues
d. Primary keys

MCQ 3. RNNs/transformers often for:
a. Sequences (text/speech)
b. Pie charts
c. ER diamonds
d. K-map groups

MCQ 4. GPUs help because:
a. Many multiply-adds in parallel
b. They store FKs
c. They draw OSI
d. They boil water

MCQ 5. Pretrained models let you:
a. Reuse features (transfer) when you have less data
b. Skip ethics
c. Skip labels forever
d. Skip HCI

MCQ 6. A practical school limit is:
a. Not enough labelled images/GPU
b. Too many GPUs always
c. Too few ethics issues
d. Too much labelled data always

Extra short questions

1. Name DL-specific components vs a tiny NN.
2. Why not train ImageNet in a college lab from scratch?
3. One architecture name at definition level.
4. Ethics still apply.

Extra long question

1. A team wants DL for Urdu speech marks entry. List DL components they need and three reasons to start smaller (ML or rules).

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Depth, specialised layers (conv), big datasets, accelerators, regularisation.
2. Compute and labelled data; use a pretrained net if anything.
3. CNN for images / transformer for language — no need for full maths.
4. Medical DL that is biased still harms patients.

Long

1. Need: audio data, labels, model, GPU, evaluation. Start smaller: n small, accents, privacy of children's voices, electricity/cost. Human checks the marks.

5.2 Applications of Neural Networks and Deep Learning

LEARN IT Machine learning, neural networks and deep learning will play a key role in Pakistan's future. The National AI Policy 2025 highlights how artificial intelligence is now part of national planning, focusing on innovation, skill-building, ethical use and digital growth .	
Sector	Potential impact in Pakistan
Education	Smart learning systems, online tutoring, automatic assessments, and finding where students need specific help.
Healthcare	Disease detection, medical image analysis, and managing hospital data. Crucial for rural areas lacking specialist doctors.
Agriculture	Monitoring crops, predicting weather, managing irrigation, and estimating yields — highly important for Pakistan's economy.
Business and banking	Fraud detection, customer support (chatbots), market forecasting, and intelligent risk analysis.
Local languages	Speech recognition, translation and text-to-speech tools for Urdu, Sindhi and other regional languages.

To benefit from this future, Pakistan needs skilled individuals. You should focus on **programming** (such as Python), **mathematics**, **data analysis**, **problem-solving** and the **ethical use of technology**.

WORKED EXAMPLE
Worked example: pick a sector and write a three-line "impact paragraph" for 5 marks.
Agriculture: A cotton grower in Sanghar photographs leaves on a cheap phone. A deep-learning model trained on Pakistani crop images flags whitefly early. The farmer sprays only the affected block, saves pesticide cost, and protects yield — which matters because agriculture is a large part of Pakistan's economy.

REMEMBER IT
Five sectors: E-H-A-B-L. Education, Healthcare, Agriculture, Business/banking, Local languages. Policy words: Innovation, skills, ethics, digital growth.

COMMON MISTAKE
Mistake: Writing only "AI will make Pakistan modern" with no sector or example.
Fix: Name the National AI Policy 2025, pick two sectors from the table, and give a local example (rural hospital without a specialist; Urdu/Sindhi speech tools; bank fraud).

آرہو میں سمجھیں

قومی اے آئی پالیسی 2025 کی مطابق منصوبہ بناتے پاکستان کی منصوبہ بندی کا حصہ ہے۔ جدت، مہارت، اخلاقی استعمال اور انجینئرنگ اور اردو و سندھی جیسے مقامی زبانوں میں اے آئی کے اثرات ہوں گے۔ طلبہ کو پائین، ریاضی، لینا کا اجزاء، مسئلہ حل کرنا اور لیکچاؤ میں اخلاقی استعمال سیکھا جائیے۔

CHECK YOURSELF
1. Name the national policy mentioned for AI in Pakistan.
2. Why is AI in healthcare especially important for rural areas?
3. List three skills students should learn to prepare for this future.

Answers: 1. National AI Policy 2025. 2. Those areas often lack specialist doctors; AI can help with disease detection and medical image analysis. 3. Any three of: programming (Python), mathematics, data analysis, problem-solving, ethical use of technology.

LEARN IT Neural networks and deep learning are widely used in modern life. Many intelligent systems use them in the background to recognise information, make predictions and support users .			
#	Application	What it does	Example
1	Image recognition	Identifies objects, faces or patterns in images. Used in security cameras, photo search and biometric tools.	Unlocking a smartphone using face recognition; a camera at a Karachi plaza matching a face with a staff list.
2	Speech recognition	Converts spoken words into digital text or commands. Deep learning helps with accents, pronunciation and voice patterns.	A student speaks to Google Assistant or Alexa to set a morning alarm; Urdu voice search on a phone.
3	Natural Language Processing (NLP)	Helps computers understand, process and respond to human language grammatically and in context. Core of chatbots, translators and AI writers.	Using Google Translate to turn a difficult English paragraph into Urdu; a bank chatbot answering in Urdu.
4	Healthcare systems	Analyse complex medical images (X-rays, CT scans, MRIs) to detect diseases early and accurately.	A hospital system highlighting abnormal patterns in a lung X-ray that might indicate pneumonia or tumours — useful at a CHQ hospital that has few radiologists.
5	Recommendation systems	Analyse past behaviour and preferences to suggest content, products or services.	A student watches computer science videos on YouTube; the platform recommends more programming tutorials.
6	Autonomous vehicles	Self-driving cars use neural networks to process real-time camera and radar data: roads, signals, pedestrians, obstacles.	A self-driving car detects a pedestrian crossing and automatically applies the brakes.
7	Fraud detection	Banks compare current activity with previous spending patterns to catch unusual transactions.	An HBL or Meezan app flags a sudden Rs 80,000 payment from a new city at 3 a.m.
8	Assistive technologies	AI supports people with disabilities.	Speech-to-text tools for users who have difficulty typing; screen readers that speak Urdu text aloud.

WORKED EXAMPLE
Worked example: match the app to the application name — a day in Ahmed's life in Hyderabad.
1. 7:00 am — phone unlocks by face. → **Image recognition**.
2. 7:05 am — "Ok Google, set alarm for Maghrib." → **Speech recognition**.
3. 8:00 pm — Google Translate helps with an English article. → **NLP**.
4. 8:00 pm — YouTube suggests a Python tutorial after he watched Chapter 5 notes. → **Recommendation system**.
5. 9:00 pm — JazzCash texts "We blocked a payment that does not match your pattern." → **Fraud detection**.

REMEMBER IT
Eight applications: I-S-N-H-R-A-F-A. Image, Speech, NLP, Healthcare, Recommendations, Autonomous vehicles, Fraud, Assistive tech. "I See New Hospitals Recommend Autonomous Fraud-Assist."

COMMON MISTAKE
Mistake: Mixing up speech recognition and NLP.
Fix: Speech recognition turns **sound into text** (or a command); NLP understands the **meaning of language** (grammar, context, translation, chat replies). You can have NLP on typed text with no microphone at all.

آرہو میں سمجھیں

نیچرل لینگ ویژن اور ڈیپ لرننگ کی مشینز ایپلی کیٹنز۔ یہیں تصویر کی پہچان، آواز کی پہچان، قدرتی زبان کی پروسسنگ (NLP) صحت کی نظام، انویز کرار والی نظام، خود چلنے والی گاڑیاں، فراڈ کی نمائندگی اور معاون ٹیکنالوجی۔ روزمرہ میں چیز۔ سے فون کھولنا، پوچھوہ کی اجازت اور بینک کا مشکوڑا لین میں پکڑنا سب اسی خاندان سے ہیں۔

CHECK YOURSELF
1. Which application converts spoken words into text or commands?
2. Give the source example of a recommendation system.
3. How do self-driving cars use neural networks?

Answers: 1. Speech recognition. 2. YouTube recommending more programming tutorials after a student watches computer-science videos. 3. They process real-time camera and radar data to understand roads, traffic signals, pedestrians and obstacles (for example braking for a pedestrian).

Extra board practice
These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Vision applications include:
a. Face unlock, medical images, number-plate reads
b. Primary keys
c. Bubble sort
d. OSI ping

MCQ 2. Language applications include:
a. Translation, speech-to-text, chatbots
b. NAND grouping
c. Foreign keys
d. Pie charts of cables

MCQ 3. Healthcare DL must still:
a. Be checked by clinicians
b. Replace doctors unsupervised always
c. Ignore bias
d. Train on one patient

MCQ 4. A local example could be:
a. Urdu voice assistants / crop images
b. K-maps of farms
c. Access reports of OSI
d. Digma of NAND

MCQ 5. Recommendation systems are:
a. ML/NN apps (what to watch/buy)
b. Queues in printers only
c. Stacks of plates only
d. ER only

MCQ 6. The exam wants:
a. Named field + how NN/DL helps + one risk
b. Only the word Pakistan
c. Only careers list
d. Only math of backprop

Extra short questions
1. Four application areas from the book.
2. One risk in health.
3. One risk in security/surveillance.
4. Why "application" questions still need a definition line.

Extra long question
1. Pick vision, health, language. For each: system, data it needs, a benefit, a harm. 10-mark. 10-mark. table.

Extra answer key
MCQs: 1. A, 2. A, 3. A, 4. A, 5. A, 6. A
Short
1. Vision, speech, health, transport, security, education — any four with a concrete system.
2. False negative on an X-ray; bias against a skin tone.
3. Misidentification; privacy.
4. 1 mark for the term, rest for use+limit.
Long
1. Face gate / Images / fast entry / racism in scores. X-ray / labelled scans / earlier catch / missed cases. Urdu STT / audio / inclusion / waking class recordings.

5.3 Secure Collaboration (Authentication, Access Control) ★ Golden

LEARN IT

Digital tools allow people to **share files**, **attend online classes**, **edit documents** and **work together from different locations**. Collaboration is useful only when **data is protected** and **communication remains safe**.
Secure collaboration means using digital tools to work together in a **safe, controlled and responsible** way. It depends on several key elements.

i) Authentication / Identity verification

Authentication is confirming the identity of a user before allowing access. Common methods:

Username and password

PIN (a short number code)

OTP — One-Time Password, a code that works only once, usually sent by SMS or an authenticator app

Biometrics — fingerprint or face

Source example: a **banking app sending an OTP to your phone before login**.

Multi-factor authentication (MFA) and two-factor authentication (2FA)

A factor is a category of proof:

Something you know — password or PIN.

Something you have — your phone, an OTP, a bank SMS.

Something you are — fingerprint, face (biometric).

Multi-factor authentication (MFA) means the system asks for **two or more different factors** before it trusts you. **Two-factor authentication (2FA)** is the common case of MFA that uses **exactly two factors** — usually password + OTP.

If a thief in another city steals only your password, MFA still blocks them because they do not have your phone (or your fingerprint).

ii) Access control

Access control decides **what an authenticated user is allowed to do**: View, Edit, Comment, Download, Share.

Authentication answers **"Who are you?"** Access control answers **"What may you do?"**

Source example: a teacher shares a Google Doc with students as **"view only"**, but gives group leaders **"edit"** permissions.

iii) Accountability and tracking

User actions are linked to **verified accounts**. You can see who opened, edited, deleted or shared a file. Example: a school **LMS** (Learning Management System) tracks which teacher uploaded an assignment and which student submitted it.

iv) Data privacy

Data **privacy** means protecting personal and sensitive information and using it **only for the purpose it was collected**. It involves:

Protection — keeping names, numbers, marks and passwords secure.

Controlled sharing — sharing only with the right people.

Confidentiality — data stays private during storage and transmission.

Compliance — following legal and ethical rules for data handling.

v) Safe communication / transmission

Exchanging information through digital platforms **securely**, protecting messages from unauthorised interception or wiretapping. Example: a teacher shares class instructions through an **official, encrypted LMS** rather than an open public forum or an unknown WhatsApp broadcast.

WORKED EXAMPLE

Worked example: a Class XII Google Classroom in Sukkur.

Step 1 — Authentication. Each student signs in with a school email and password. The college turns on MFA: after the password, Google sends an OTP to the student's registered Jazz/Zong number.

Step 2 — Access control. All 40 students can **view** the assignment sheet. Only the four group leaders can **edit** the shared report. Nobody except the teacher can **delete** the class materials. A student who left the college is removed from the class (access revoked).

Step 3 — Accountability. Version history shows that Ali edited paragraph 2 at 8:14 pm and that Hina submitted the PDF at 9:02 pm.

Step 4 — Privacy and safe transmission. Marks stay inside Classroom; the teacher does not post CNIC numbers or phone numbers in a public Facebook group. Traffic to Google is encrypted, unlike an open public forum.

If Ali shares his password with a cousin, authentication is broken. If the teacher gives every student "edit" on the marksheet, access control is broken even though login still works.

REMEMBER IT

A-A-P-S. Authentication, Access control, Accountability, Privacy, Safe transmission. MFA = at least two different factor types (know / have / are). 2FA is MFA with two factors.

COMMON MISTAKE

Mistake: Treating authentication and access control as the same thing.

Fix: Login only proves identity. After login, access control still limits View / Edit / Comment / Download / Share. A student who is authenticated must not automatically get teacher rights.

آرڈو میں سمجھیں

محفوظ تعاون کا مطلب ہے ڈیجیٹل ٹولز سے محفوظ، کنٹرول شدہ اور نمد، دارالہ انداز میں ساتھ کام کرنا۔ تصدیق (Authentication) یہ جانچتی ہے کہ صارف کون ہے؛ رسائی کنٹرول (Access Control) یہ طے کرتا ہے کہ وہ کیا کر سکتا ہے (صرف دیکھنا، ترمیم، تبصرہ)۔ کثیر عنصری تصدیق (MFA) دو یا زیادہ مختلف ثبوت مانگتی ہے، جیسے پاس ورڈ اور او ٹی پی (OTP)۔ حساب دہی، ڈیٹا پرائیویسی اور محفوظ ترسیل بھی ضروری ہیں۔

EXAM TIP

Typical items: "Define secure collaboration", "Differentiate authentication and access control", "What is MFA/2FA?", "Explain five elements of secure collaboration with examples."

Write the five headings (authentication, access control, accountability, privacy, safe transmission). For MFA, name the three factor types and say that 2FA is password + OTP in a banking app. Use the Google Doc "view only vs edit" example — examiners look for it.

CHECK YOURSELF

1. What question does authentication answer, and what question does access control answer?

2. Password + OTP is an example of which idea?

3. Give the source example of access control in a Google Doc.

Answers: 1. Authentication: who are you? Access control: what may you do? 2. Two-factor / multi-factor authentication (2FA/MFA). 3. Teacher shares the document as view-only with students but gives group leaders edit permission.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Authentication is:

a. Proving who you are

b. What you are allowed to do

c. Encrypting a disk

d. A pie chart

MCQ 2. MFA means:

a. More than one factor (password + OTP/phone)

b. Many files always

c. Many Figma frames

d. Many OSI layers

MCQ 3. Access control is:

a. What an authenticated user may do

b. The login spelling

c. A histogram

d. A stack

MCQ 4. Accountability needs:

a. Actions tied to accounts (logs)

b. Shared "class" password

c. No names

d. Disabled logs

MCQ 5. A shared Google-doc with "anyone can edit" falls:

a. Access control / accountability

b. Big O

c. NAND

d. Median

MCQ 6. This is ★: define collaboration risk, then:

a. Auth, MFA, access control, tracking

b. Only careers

c. Only MVPs

d. Only charts

Extra short questions

1. Define authentication vs access control.

2. Two MFA factors.

3. Why logs?

4. A class example of bad practice.

Extra long question

1. Design login for a college LMS: password rules, MFA, roles (student/teacher/admin), and what an audit log stores. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Auth: who. Access: what they can do.

2. Something you know (password) + have (phone OTP) / are (fingerprint).

3. After a leak you can see who opened the file.

4. One Facebook password on the projector.

Long

1. Roles table. Students cannot edit marks. Teachers cannot drop the DB. MFA for admin. Logs: user, time, action, IP. No shared accounts.

5.3.2 Data Protection (Encryption, Passwords, Backup, Firewall)

LEARN IT

Data protection means keeping digital information safe from **unauthorised access, misuse, loss, damage or accidental deletion**.

1. Data encryption

Encryption changes readable data (**plaintext**) into a coded form called **ciphertext**. Unauthorised users cannot understand ciphertext without the key.

Symmetric encryption — the **same key** is used to encrypt and to decrypt.

Asymmetric encryption — **two keys**: a **public key** to encrypt, a **private key** to decrypt.

A simple exam cipher is the **Caesar cipher** (a symmetric substitution cipher). You shift every letter a fixed number of places along the alphabet. Shift 3 is the classic key: A → D, B → E, ..., Z → C (the alphabet wraps around).

2. Strong passwords

A strong password includes **uppercase, lowercase, numbers and symbols**. It resists **brute-force** guessing (trying every possible combination). Source example: Zk@2024#Pass .

Weak: ahmed123 , pakistan , sindh , your date of birth. Never reuse the same password on the college LMS and on JazzCash.

3. Backup and recovery — the 3-2-1 rule

A **backup** is a copy of data in a safe location (cloud or external drive) so you can **restore** it after hardware damage, ransomware or accidental deletion.

The **3-2-1 backup rule** is a practical standard:

- 3 copies of the data (the original plus two backups).
- 2 different types of storage media (for example laptop disk + USB, or disk + cloud).
- 1 copy **off-site** (a different building or the cloud), so a fire or theft at home does not destroy every copy.

4. Firewall and antivirus software

A **firewall** is a security **barrier** that **monitors network traffic** and **blocks suspicious internet access**. Think of it as a checkpoint on the road between your device (or college lab) and the Internet.

Antivirus software detects and removes harmful software (viruses, spyware and other malware) from the **local machine**.

Firewall = guards the **door to the network**. Antivirus = searches **inside the house** for intruders already present.

WORKED EXAMPLE

Worked example A — Caesar cipher, shift = 3. Encrypt the plaintext **SINDH**, then decrypt the result.

Write the alphabet and count three letters forward. Wrap after Z back to A.

Plain	S	I	N	D	H
+3	V	L	Q	G	K

Ciphertext = **VLOGK**.

Decrypt: shift each letter **back** by 3: V → S, L → I, Q → N, G → D, K → H. You recover **SINDH**.

Spaces and punctuation are often left unchanged. The same key (3) is used both ways, so Caesar is **symmetric**.

Second check: **CAT + 3 → C→F, A→D, T→W → FDW**.

```
def caesar(text, shift):
    result = ""
    for ch in text:
        if ch.isalpha():
            base = ord("A") if ch.isupper() else ord("a")
            result += chr((ord(ch) - base + shift) % 26 + base)
        else:
            result += ch
    return result

print(caesar("SINDH", 3))
print(caesar("VLOGK", -3))
print(caesar("CAT", 3))
```

OUTPUT
SINDH
SINDH
FDW

Worked example B — 3-2-1 for Fatima's Class XII project in Hyderabad.

- Copy 1 (original):** project folder on her laptop hard disk.
- Copy 2 (different media):** the same folder on a USB drive she keeps in her bag.
- Copy 3 (off-site):** uploaded to Google Drive (cloud servers are not in her house).

That is 3 copies, 2 media types (internal disk + USB, with cloud as the off-site copy), 1 off-site. When her brother deletes the laptop folder, she restores from USB or Drive.

Password check: Zk@2024#Pass has uppercase Z, lowercase letters, digits 2026, and symbols @ and #. fat1sa has none of those extras — reject it.

3 copies → 2 media types → 1 copy off-site

REMEMBER IT

Cipher = lock the message. **Password** = lock the door. **3-2-1** = spare keys in three places. **Firewall** = gate. **Antivirus** = indoor search. Caesar: shift letters; same key both ways (symmetric).

COMMON MISTAKE

Mistake 1: Shifting the wrong way, or forgetting wrap-around (X, Y, Z + 3 → A, B, C).

Mistake 2: Two copies on the same laptop (Documents and Desktop) and calling it 3-2-1. That is still one disk in one house.

Fix: Count letters on a written alphabet. For backups, different media and one copy that would survive a house fire.

CHECK YOURSELF

- Encrypt PAK with a Caesar shift of 3.
- What do the 3, the 2 and the 1 stand for in 3-2-1 backup?
- In asymmetric encryption, which key encrypts and which key decrypts?

Answers: 1. SDN (P→S, A→D, K→N). 2. 3 copies, 2 different media, 1 off-site copy. 3. Public key encrypts; private key decrypts.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Encryption makes data:

- a. Unreadable without a key
- b. Faster to sort
- c. A primary key
- d. A pile

MCQ 2. A strong password is:

- a. Long, unique, not a word+123
- b. AI!123 for every site
- c. Written on the monitor
- d. OTP posted in the group

MCQ 3. Backup is:

- a. A second copy you can restore
- b. A stronger GPU
- c. A prettier UI
- d. A faster sort

MCQ 4. A firewall:

- a. Filters traffic in/out
- b. Encrypts Excel cells one-by-one always
- c. Sorts arrays
- d. Draws ER

MCQ 5. Ransomware defence includes:

- a. Offline/offline-ish backups
- b. Paying and hoping always
- c. No updates
- d. Shared admin

MCQ 6. Data protection is about:

- a. Confidentiality, integrity, availability (CIA idea)
- b. Only colours
- c. Only NAND
- d. Only sprints

Extra short questions

- Four protection techniques from the notes.
- Why unique passwords?
- 3-2-1 backup idea (simple).
- Firewall vs antivirus in one line.

Extra long question

- A college lab is hit by ransomware. Using encryption, passwords, backup, firewall: what should already have been in place, and what do you do now (without paying if possible)?

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Encryption, strong passwords, backup, firewall (and updates, least privilege).
- One leaked site should not open email+JazzCash.
- More than one copy, not only on the same laptop.
- Firewall: traffic gate. AV: looks for malware on the host (both useful).

Long

- Before: backups offline, least admin, updates, firewall. Now: isolate PCs, restore from backup, change passwords, report. Paying is not a syllabus requirement to endorse.

آرڈو میں سمجھیں

ڈیٹا پروزیکشن کا مطلب یہ معلومات کو غیر مجاز رسائی، غلط استعمال، نقصان یا حادثاتی حذف سے بچانا۔ انکرپشن پڑھے جانے والے متن کو سائفر ٹیکسٹ بنا دیتی ہے، سیزر سائفر میں ہر حرف کو مقررہ جگہوں سے آگے سرکایا جاتا ہے۔ مضبوط پاس ورڈ میں بڑے، چھوٹے حروف، عدد اور علامات ہوتے ہیں۔ 1-2-3 ایک آپ-آپن-آپریا، دو قسم کے میڈیا، ایک کاپی باور (آف سائٹ)، فائر وال اینڈ ایک ورک ٹریک روکنی ہے؛ اپنی وائرس مقامی نقصان دہ سافٹ ویئر ہٹاتا ہے۔

CHECK YOURSELF

- Encrypt PAK with a Caesar shift of 3.
- What do the 3, the 2 and the 1 stand for in 3-2-1 backup?
- In asymmetric encryption, which key encrypts and which key decrypts?

Answers: 1. SDN (P→S, A→D, K→N). 2. 3 copies, 2 different media, 1 off-site copy. 3. Public key encrypts; private key decrypts.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Encryption makes data:

- a. Unreadable without a key
- b. Faster to sort
- c. A primary key
- d. A pile

MCQ 2. A strong password is:

- a. Long, unique, not a word+123
- b. AI!123 for every site
- c. Written on the monitor
- d. OTP posted in the group

MCQ 3. Backup is:

- a. A second copy you can restore
- b. A stronger GPU
- c. A prettier UI
- d. A faster sort

MCQ 4. A firewall:

- a. Filters traffic in/out
- b. Encrypts Excel cells one-by-one always
- c. Sorts arrays
- d. Draws ER

MCQ 5. Ransomware defence includes:

- a. Offline/offline-ish backups
- b. Paying and hoping always
- c. No updates
- d. Shared admin

MCQ 6. Data protection is about:

- a. Confidentiality, integrity, availability (CIA idea)
- b. Only colours
- c. Only NAND
- d. Only sprints

Extra short questions

- Four protection techniques from the notes.
- Why unique passwords?
- 3-2-1 backup idea (simple).
- Firewall vs antivirus in one line.

Extra long question

- A college lab is hit by ransomware. Using encryption, passwords, backup, firewall: what should already have been in place, and what do you do now (without paying if possible)?

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Encryption, strong passwords, backup, firewall (and updates, least privilege).
- One leaked site should not open email+JazzCash.
- More than one copy, not only on the same laptop.
- Firewall: traffic gate. AV: looks for malware on the host (both useful).

Long

- Before: backups offline, least admin, updates, firewall. Now: isolate PCs, restore from backup, change passwords, report. Paying is not a syllabus requirement to endorse.

12

5.4 Security Threats and Mitigation Techniques ★ Golden

LEARN IT			
A security threat is any action, event or weakness that can harm a computer system or its data. Mitigation techniques are protective measures used to prevent threats or reduce their impact. This section names the common threats; later sections show how to spot them and how to reduce the damage.			
#	Threat	What it is	Example
1	Malware	Harmful software designed to damage a computer, steal data, or gain unauthorised access. Includes viruses, worms, spyware, ransomware and Trojans.	Installing cracked software that secretly corrupts files, or a "free game" USB that encrypts a college lab's coursework (ransomware).
2	Phishing	A social-engineering trick that deceives users into sharing personal information (passwords, bank details, OTPs) using fake emails or websites that look genuine.	An SMS that looks like JazzCash or HBL asking you to "verify" by typing your OTP on a fake page.
3	Unauthorised access	Entering a system, account or file without permission. Often caused by weak passwords, shared passwords, or leaving devices unlocked.	A classmate using an unlocked lab PC to open someone else's Google Classroom.
4	Data theft / identity theft	Data theft is stealing or copying data without permission. Identity theft is using another person's stolen details (name, CNIC, bank details) to pretend to be them online and commit fraud.	A leaked list of CNICs used to open a SIM or a wallet in someone else's name.
5	Denial of Service (DoS)	A website or system is flooded with thousands of fake requests, causing it to slow down or crash, so real users cannot access the service.	Hackers flooding an online exam portal so students cannot log in on BISE result day or during an e-test.
6	Human error	Mistakes by legitimate users: accidentally deleting files, sending confidential data to the wrong email, or falling for a simple scam.	A teacher emailing the whole marksheet to the wrong parent; a student forwarding an OTP "to help the bank."

Malware types in one line each: a virus attaches to files and spreads when you share them; a worm spreads by itself across a network; spyware secretly watches you; ransomware locks your files and demands money; a Trojan pretends to be useful software but hides harm. Social engineering means tricking a person, not breaking a lock with maths. Phishing is the most common exam example.



Three high-yield threats: phishing (fake messages), DoS (server overload), identity theft (stolen CNIC or bank details).

WORKED EXAMPLE

Worked example: classify the incident.

1. Bilal downloads a "cracked" Photoshop. Next day his project files are unreadable and a note asks for Bitcoin. → **Malware** (ransomware), started by cracked software.
2. Aysha gets an email "Your Meezan account will close in 2 hours. Click here and send OTP." The link is meezn-pk.tk, not the real bank. → **Phishing**.
3. On e-test morning the college portal spins forever; the admin graph shows 200,000 requests from one pattern of fake traffic. → **DoS**.
4. Someone opens a JazzCash wallet using Ahmed's CNIC copy from a leaked form. → **Identity theft** (after data theft).
5. The lab assistant emails the password list to the whole staff by choosing the wrong group. → **Human error**.

REMEMBER IT

Malware = bad program. Phishing = fake message. DoS = flood. Identity theft = stolen 'you'. Human error = honest mistake. Cracked software and unknown USBs are the usual door for malware in Pakistani colleges.

COMMON MISTAKE

Mistake: Calling every cyber problem a "virus", or mixing phishing with malware.

Fix: A virus is only one kind of malware. Phishing is a trick against the user; it may not install any file at all. DoS does not steal your password — it makes the service unusable for everyone.

آرڈو میں سمجھیں

سیکیورٹی خطرہ وہ عمل یا کمزوری ہے جو نظام یا ڈیٹا کو نقصان پہنچاے۔ مہلک سافٹ ویئر (malware) سے شروع ہوتا ہے، جیسے کہ کرکڈ سافٹ ویئر یا ویسٹ ویئر (worm)۔ فیشنگ (phishing) ای میل یا ویب سائٹ سے پاس ورڈ اور او ٹی پی (OTP) کی چھٹی ہے۔ ڈوس (DoS) جھٹی درخواستوں کی بارش سے سائٹ کریش کر دیتا ہے۔ دیگر خطرات: غیر مجاز رسائی، ڈیٹا/نفاذت کی چوری، اور انسانی غلطی۔

EXAM TIP

Expect "Define a security threat", "Explain malware / phishing / DoS with examples", and "Differentiate data theft and identity theft." List all six threats if the question says "common security threats." For DoS, write: flood of fake requests → slowdown or crash → real users blocked, and quote the online exam portal. For phishing, write social engineering + fake genuine-looking email/site + passwords/OTPs.

CHECK YOURSELF

1. Name five types of malware listed in the source.
2. What does a DoS attack do to a website?
3. How is identity theft different from data theft?

Answers: 1. Viruses, worms, spyware, ransomware, Trojans. 2. Floods it with thousands of fake requests so it slows down or crashes and real users cannot access it. 3. Data theft is stealing/copying data; identity theft is using stolen personal details (name, CNIC, bank) to pretend to be that person and commit fraud.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Malware is:

- a. Malicious software (virus, worm, trojan, ransomware...)
- b. A friendly backup
- c. A primary key
- d. A caption

MCQ 2. Phishing is:

- a. Tricking you into giving secrets (fake mail/site)
- b. A fishing sport in the syllabus
- c. A sort
- d. A chart

MCQ 3. DoS aims to:

- a. Make a service unavailable by flooding it
- b. Encrypt with your key
- c. Fix UX
- d. Normalise tables

MCQ 4. A threat is:

- a. Anything that can harm system or data
- b. Only earthquakes
- c. Only NAND delay
- d. Only slow Wi-Fi in exams

MCQ 5. This is ★: name, one example, one mitigation.

- a. The 3-mark recipe
- b. Only the name
- c. Only Python
- d. Only Figma

MCQ 6. A fake BIEK result link is likely:

- a. Phishing
- b. A K-map
- c. A stack
- d. A median

Extra short questions

1. Define malware, phishing, DoS.
2. One extra threat from the notes (theft/identity).
3. A student-level mitigation for phishing.
4. Why USB etiquette?

Extra long question

1. Table of four threats: what it is, a Sindh-college example, a sign, a mitigation. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Malware: bad software. Phishing: social trick. DoS: flood to outage.
2. Data/identity theft — using someone's CNIC/account.
3. Check URL, don't tap unknown SMS, official portal only.
4. Worms travel on sticks.

Long

1. Malware, phishing, DoS, theft. Signs: slowness, fake from-addresses, site down, unknown logins. Mitigations: updates/AV, URL check, backups+capacity, MFA.

5.4.2 Identify Security Threats

LEARN IT

Identifying security threats means **noticing signs** that data or systems may be at risk. Early identification helps you act before serious damage occurs.

Sign / indicator	What it likely means
Slow performance, missing files, or random pop-ups.	Malware or background unauthorised activity.
Failed login attempts or strange login locations.	Attempted unauthorised access .
Emails urging quick action, asking for an OTP, or containing bad grammar / strange links.	Classic phishing .
Unexpected deletion, copying or movement of records.	Data theft or insider misuse.
Sudden massive spike in server requests or a very slow website.	An ongoing DoS attack.

The first line of defence is also simple behaviour: avoid **unsafe downloads**, **cracked software**, **unverified websites** and **infected USB drives**.

WORKED EXAMPLE

Worked example: read the signs in a college computer lab in Khairpur.

1. Three PCs show pop-ups and Word files have vanished after students used a "game" USB. → Treat as **malware**. Disconnect from the network; run antivirus; stop USB use.
2. Google Classroom emails: "Your account will be deleted in 30 minutes. Confirm password here." Link spelling is goOgle. → **Phishing**. Do not click; report to the teacher.
3. The e-portal that was fine at 8:00 am is unreachable at 8:05; the technician sees a sudden spike in requests. → Suspect **DoS**.
4. Nadia's Gmail security page shows a login from another country at 4 a.m. → **Unauthorised access** attempt. Change password; turn on MFA.

REMEMBER IT

Slow/pop-ups → malware. Odd logins → unauthorised access. Urgent OTP email → phishing. Files moving → theft. Traffic spike → DoS.

COMMON MISTAKE

Mistake: Ignoring early signs ("the PC is just old") until the ransomware note appears.

Fix: One unusual login or one OTP email is enough to investigate. Early action is cheaper than recovery.

اردو میں سمجھیں

خطرے کی جلد پہچان نقصان سے پہلے اقدام ممکن بناتی ہے۔ سست روی، غائب فائلیں یا پاپ اپ میلویئر کی علامت ہیں؛ عجیب لاگ ان غیر مجاز رسائی کی؛ فوری او ٹی پی والی ای میل فحشنگ کی؛ ریکارڈ کا اچانک منتقل ہونا ڈیٹا چوری کی؛ سرور پر درخواستوں کا دھماکہ۔
ڈو ایس کی۔ کریک سافٹ ویئر، نامعلوم یو ایس پی اور غیر تصدیق شدہ ویب سائٹوں سے بچیں۔

CHECK YOURSELF

1. Random pop-ups and missing files most likely indicate what?
2. An email with bad grammar that demands your OTP is a sign of what?
3. Name four unsafe habits that invite these threats.

Answers: 1. Malware (or background unauthorised activity). 2. Phishing. 3. Unsafe downloads, cracked software, unverified websites, infected USB drives.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An IDE is:

- a. One app to write, run and debug code
- b. A printer
- c. A sort
- d. A cable

MCQ 2. VS Code is:

- a. A popular editor/IDE
- b. A DBMS
- c. An OSI layer
- d. A gate

MCQ 3. The terminal/run button is for:

- a. Executing the program
- b. Drawing pie charts only
- c. Sending TCP SYN only
- d. K-maps

MCQ 4. Syntax highlighting helps you:

- a. See keywords and mistakes
- b. Sort faster
- c. Encrypt disks
- d. Route packets

MCQ 5. A file explorer in VS Code shows:

- a. Project files
- b. OSI layer 1
- c. NAND groups
- d. Beachhead users

MCQ 6. Debugging in an IDE uses:

- a. Breakpoints and variable watch
- b. Only bubble sort
- c. Only pie charts
- d. Only Agile stickers

Extra short questions

1. Define IDE.
2. Name four VS Code areas.
3. Why not use Notepad only?
4. What is an extension?

Extra long question

1. Describe how you would create, run and debug a first Python file in VS Code. Include two interface elements from the notes.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Integrated Development Environment: editor + run + debug + files in one place.
2. Activity bar/sidebar (files), editor, terminal, status bar (and extensions).
3. No easy run, no highlighting, no debugger.
4. An add-on (Python plugin) that teaches VS Code a language.

Long

1. New file .py, type print, Run Python, read terminal. Mention top menu, explorer, terminal panel. Breakpoint on a wrong variable.

5.4.3 Apply Mitigation Techniques

LEARN IT

Mitigation techniques are actions taken to prevent security threats or reduce their harmful effects once identified. Technology helps, but it cannot stop all threats if the user is careless.

#	Technique	How it helps
1	Antivirus and firewalls	Antivirus scans and removes harmful software (for example from USB drives). A firewall monitors network traffic and blocks suspicious access from the internet.
2	Strong passwords and 2FA	Complex passwords slow brute-force guessing. 2FA adds an extra layer: an OTP on your phone as well as the password.
3	Data encryption	Converts data into unreadable code during transmission. Protects passwords and sensitive data if they are intercepted.
4	Regular backups	Copies on cloud or external drives allow quick recovery after a crash, human error or ransomware.
5	User awareness (the human factor)	Training users to avoid unknown links, suspicious attachments and password sharing. The human is often the weakest link — and the strongest defence when trained.

WORKED EXAMPLE

Worked example: match each threat to a mitigation — BISE e-test week at a college in Larkana.

Threat seen	Mitigation to apply
USB games in the lab, pop-ups starting.	Scan with antivirus ; block unknown USBs; enable the lab firewall .
Phishing SMS about "update your portal password."	User awareness : do not click; verify on the official site typed by hand. Turn on 2FA .
Fear that intercepted Wi-Fi could show passwords.	Use sites with encryption (HTTPS / encrypted LMS); never send passwords in plain WhatsApp.
Ransomware risk to project files.	Regular 3-2-1 backups so files can be restored without paying.
Shared passwords on a sticky note on the monitor.	Strong unique passwords + 2FA; remove the note; awareness session.

REMEMBER IT

Five shields: **A-F, P-2, E, B, U**. Antivirus+Firewall, Passwords+2FA, Encryption, Backups, User awareness. Ransomware is why backups matter: if files are locked, a clean copy brings them back.

COMMON MISTAKE

Mistake: "If I installed antivirus I am 100% safe."
Fix: Antivirus does not stop you from typing an OTP into a fake page. Mitigation is a **set** of techniques plus human caution.

اردو میں سمجھیں

تحفظ کی تدابیر خطرات کو روکتی یا ان کا نقصان کم کرتی ہیں: اینٹی وائرس اور فائر وال، مضبوط پاس ورڈ اور دو عنصری تصدیق (2FA)، انکریپشن، یاقاعدہ بیک اپ، اور صارف کی آگاہی۔ ٹیکنالوجی تب ناکام ہو جاتی ہے جب صارف نامعلوم لنک کھولے یا پاس ورڈ بانٹے۔

CHECK YOURSELF

1. How does 2FA add a layer on top of a password?
2. Why do regular backups help after ransomware?
3. What three careless behaviours should awareness training stop?

Answers: 1. It also requires an OTP sent to your phone (a second factor). 2. You can restore a clean copy instead of losing the files (or paying). 3. Unknown links, suspicious attachments, and password sharing.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Mitigation means:
a. Prevent or reduce harm from threats
b. Ignore them
c. Rename the threat
d. Draw them in Figma

MCQ 2. Updates/patches:
a. Close known holes
b. Always break Python
c. Replace HCI
d. Replace ER

MCQ 3. Least privilege means:
a. Only the rights you need
b. Everyone is admin
c. No passwords
d. No backups

MCQ 4. User education fights:
a. Phishing / bad USB / weak passwords
b. Cosmic rays only
c. NAND delay
d. Median bias only

MCQ 5. Incident plan includes:
a. Isolate, preserve, restore, report
b. Panic format twice
c. Pay first always
d. Post OTPs

MCQ 6. Technical + human controls together are:
a. Stronger than either alone
b. Illegal
c. Useless
d. Only for banks

Extra short questions

1. Five mitigation techniques from the book.
2. Map one technique to phishing, one to ransomware, one to DoS.
3. What not to do?
4. Why backups must be tested?

Extra long question

1. Write a one-page lab policy: 8 rules that mitigate the threats in 5.4.1. Tag each rule with the threat.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short
1. Updates, AV, firewall, backup, MFA, training, least privilege, encryption — any five.
2. Phishing: training+MFA. Ransomware: backup. DoS: filtering/capacity (high level).
3. Share the malware "to warn friends" as an attachment.
4. A backup you cannot restore is theatre.

Long
1. No shared admin (malware/theft); USB scan; official links (phishing); weekly backup (ransomware); firewall; MFA email; report SMS; no pirated cracks. Table.

15

5.5 Equity and Equal Access in Digital Collaboration

LEARN IT
Collaboration tools are vital for online learning and teamwork. To use these tools fairly, all users must participate **without barriers**. You must understand the difference between **equal access** and **equity**.

Equal access
Giving everyone the **exact same** opportunity, tools and resources.
Example: providing every student with the **same login ID** to access a Zoom class.
Equal access is the same starting kit. Equity is extra help so a person who faces a barrier can still finish the race with everyone else. Fair collaboration needs **both**: the same Zoom link for all (equal access) **and** captions, recorded lectures or a low-data app where needed (equity).

Equity
Giving **additional, specific support** to users who need it, so they can reach the **same outcome**.
Example: turning on live **subtitles/captions** in Zoom specifically for a student who has hearing difficulties.

WORKED EXAMPLE
Worked example: one class, two ideas. A teacher in Thatta starts online classes.
Equal access: every student receives the same Zoom ID and password. That is fair in the sense of "same tool," but a student with hearing loss still cannot follow the spoken lecture, and a student in a village with a weak 2G signal cannot join video.
Equity: the teacher turns on captions, posts a low-size audio recording, and accepts the assignment as a Google Doc in the browser (not only through a heavy app). Now those two students can reach the **same learning outcome**.

REMEMBER IT
Equal = same tools. Equity = extra support for the same outcome. Same shoes for all vs a ramp for the wheelchair user.

COMMON MISTAKE
Mistake: "We gave everyone the same login, so the class is fair."
Fix: Same login is equal access only. If some students still cannot hear, see, afford a smartphone, or get electricity, you still need equity.

اردو میں سمجھیں
مساوی رسائی (Equal Access) سب کو ایک جیسے اوزار دیتی ہے، جیسے ایک ہی زوم لاگ ان۔ انصاف (Equity) ضرورت مند کو اضافی مدد دیتی ہے تاکہ وہی نتیجہ نکل سکے، جیسے سماعت کی مشکل والے طالب علم کے لیے زندہ ذیلی عنوانات (Captions)، منصفانہ تعاون کے لیے دونوں چاہییں۔

CHECK YOURSELF
1. Define equal access in one sentence.
2. Define equity in one sentence.
3. Why are Zoom captions an example of equity, not merely equal access?
Answers: 1. Giving everyone the exact same opportunity, tools and resources. 2. Giving additional, specific support so users who need it can reach the same outcome. 3. Because they are extra support for a student with hearing difficulties, not the same identical tool given to all.

Extra board practice
These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Equity in digital collaboration means:
a. Fair access to tools and participation, not only "same link for all"
b. Giving everyone the identical laptop always without support
c. Banning assistive tech
d. English-only 4pt PDFs

MCQ 2. Equal access includes:
a. Devices, connectivity, language, disability support
b. Only the top 10 students
c. Only computer labs at midnight
d. Only paid apps

MCQ 3. A student on 2G with no laptop needs:
a. Low-data options / lab time
b. A 4K video lecture only
c. A VR headset
d. A GPU DL assignment first

MCQ 4. Collaboration tools fail equity when:
a. They require an expensive phone feature
b. They have captions and Urdu
c. They work on a lab PC
d. They allow keyboard only

MCQ 5. This is ★ for 5.5.1: functions of equity are:
a. Inclusion, fairness of voice, accessible tools, support
b. Faster CPUs
c. Shorter OSI
d. Nicer NAND

MCQ 6. A fair group project:
a. Roles + shared docs + offline option
b. One member who owns the only laptop does all
c. Voice chat only at 2am
d. Uncaptioned 1-hour video mandatory

Extra short questions
1. Define equity vs "everyone got the WhatsApp".
2. Functions of equity (book).
3. Two practical college moves.
4. Link to XI assistive tech.

Extra long question
1. A group of 5: one blind, one with no smartphone, one in a village on weekends. Design the collaboration so all can submit. 10 marks ★.

Extra answer key
MCQs: 1. A 2. A 3. A 4. A 5. A 6. A
Short
1. Same message is not the same opportunity if some have no data bundle or cannot hear.
2. Access, participation, support, accessible design, respect.
3. Lab hours; printed alternative; captions; Urdu UI; extra time.
4. Screen readers + accessible docs are equity, not charity.
Long
1. Shared doc that works in lab PCs; keyboard/screen reader; tasks that don't need 2am Zoom; recorded captions; warden-lab timetable. Assessment not based on who has 4G.

5.5.1 Functions of Equity and Equal Access ★ Golden

LEARN IT

Equity and equal access are not slogans. They **do work** in a digital classroom. The source lists four functions.

Function	What it does	Pakistani example
1. Providing need-based support (equity)	Help tailored to individuals.	Audio descriptions for visually impaired students; a screen reader so a blind student in Karachi can hear a digital textbook.
2. Removing barriers	Help students in remote areas attend online classes.	Mobile-friendly, low-data apps so a student in Tharparkar or the katcha areas of Sindh can join without a fibre connection.
3. Enabling active participation	Students who miss live class can still take part.	Recorded lectures so load-shedding or an internet outage in Hyderabad does not make a student fall behind.
4. Supporting different learning needs	Offer more than one format.	Videos, text notes and audio of the same Chapter 5 topic so each student learns in the way that suits them best.

WORKED EXAMPLE

Worked example: design four functions for one class WhatsApp + Classroom group in Nawabshah.

- Need-based support:** Ali is visually impaired — share materials as selectable text (not only photos) so a screen reader can speak them; add a short audio description of each diagram.
- Remove barriers:** post a 5 MB audio summary instead of a 200 MB video for students on expensive mobile data.
- Active participation:** upload the Zoom recording within an hour; students whose lights went out at 7 pm watch it at 11 pm.
- Different learning needs:** the same lesson as (a) a 12-minute video, (b) a one-page PDF, (c) an Urdu audio note.

Discussion from the source: if a teacher **only** accepts assignments via an app that needs a **high-end smartphone**, is that equal access? **No**. It creates a **hardware barrier** for lower-income students. Web-based or light apps give better access.

REMEMBER IT

Four functions: Support, Remove, Participate, Formats. "Some Rural Pupils Fail" without them — Support (need-based), Remove barriers, Participate via recordings, Formats (video/text/audio).

COMMON MISTAKE

Mistake: Describing only captions and stopping.

Fix: Examiners want all four functions. Include remote-area low-data apps, recorded lectures for power cuts, and multiple formats — these are in the Sindh source on purpose.

اردو میں سمجھیں

انصاف اور مساوی رسائی کے چار کام ہیں: ضرورت کے مطابق مدد (جیسے نابینا طالب علم کے لیے آڈیو وضاحت)، رکاوٹیں ہٹانا (دور دراز علاقوں کے لیے کم ڈیٹا والی ایپس)، فعال شرکت ممکن بنانا (نوٹ شیئنگ کے لیے ریکارڈ شدہ لیکچر)، اور مختلف اندازِ تعلیم کی حمایت (ویڈیو، متن، آڈیو)۔ مہنگے فون والی ایپ پر صرف اسی طرح اسائنمنٹ لینا مساوی رسائی نہیں۔

EXAM TIP

Golden question: "Explain the functions of equity and equal access in digital collaboration" (5–8 marks). Write the four headings in order, one example each, and add the hardware-barrier point (high-end app vs light/web app). Another favourite: "Differentiate equal access and equity with examples" — same login vs captions.

CHECK YOURSELF

- List the four functions of equity and equal access.
- How do recorded lectures enable active participation in Pakistan?
- Why is a high-end-smartphone-only assignment unfair?

Answers: 1. Need-based support; removing barriers; enabling active participation; supporting different learning needs. 2. Students who face power or internet outages can watch later and not fall behind. 3. It creates a hardware barrier for lower-income students; web-based or light apps give better access.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Equity in digital collaboration means:

- Fair access to tools and participation, not only "same link for all"
- Giving everyone the identical laptop always without support
- Banning assistive tech
- English-only 4pt PDFs

MCQ 2. Equal access includes:

- Devices, connectivity, language, disability support
- Only the top 10 students
- Only computer labs at midnight
- Only paid apps

MCQ 3. A student on 2G with no laptop needs:

- Low-data options / lab time
- A 4K video lecture only
- A VR headset
- A GPU DL assignment first

MCQ 4. Collaboration tools fail equity when:

- They require an expensive phone feature
- They have captions and Urdu
- They work on a lab PC
- They allow keyboard only

MCQ 5. This is ★ for 5.5.1: functions of equity are:

- Inclusion, fairness of voice, accessible tools, support
- Faster CPUs
- Shorter OSI
- Nicer NAND

MCQ 6. A fair group project:

- Roles + shared docs + offline option
- One member who owns the only laptop does all
- Voice chat only at 2am
- Uncaptioned 1-hour video mandatory

Extra short questions

- Define equity vs "everyone got the WhatsApp".
- Functions of equity (book).
- Two practical college moves.
- Link to XI assistive tech.

Extra long question

- A group of 5: one blind, one with no smartphone, one in a village on weekends. Design the collaboration so all can submit. 10 marks ★.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Same message is not the same opportunity if some have no data bundle or cannot hear.
- Access, participation, support, accessible design, respect.
- Lab hours; printed alternative; captions; Urdu UI; extra time.
- Screen readers + accessible docs are equity, not charity.

Long

- Shared doc that works in lab PCs; keyboard/screen reader; tasks that don't need 2am Zoom; recorded captions; warden-lab timetable. Assessment not based on who has 4G.

5.5.2 Collaboration Tools

LEARN IT	
Digital collaboration tools are online platforms that support communication, file sharing, learning and teamwork across different locations.	
Tool	Primary function and educational use
Google Docs	Write, edit, comment and share documents in real time. Excellent for group assignments.
Zoom	Online meetings, virtual classes, screen sharing and video-based communication.
Microsoft Teams	A unified workspace for online meetings, file sharing, class groups and structured teamwork.
Google Classroom / LMS	Learning Management Systems help teachers manage lectures, distribute assignments, conduct quizzes and grade student activities.
WhatsApp	Quick class announcements, urgent reminders and instant group communication. Must be used responsibly.
Email	Formal communication, official notices, submitting large attachments, and keeping a professional written record.

Responsibly on WhatsApp means: no leaking of classmates' marks or photos, no fake forwards, and no forcing a student who has no smartphone to miss official work that was never posted on the LMS.

WORKED EXAMPLE

Worked example: choose the right tool for each job in a Hyderabad college group project.

1. Write the report together after school, from different houses. → **Google Docs** (real-time edit and comments).
2. Sunday 7 pm teacher explanation with slides. → **Zoom** or **Teams** (video + screen share). Turn on captions (equity).
3. Collect homework, quiz and grades in one place. → **Google Classroom / LMS**.
4. "Tomorrow's test is postponed — tell everyone in the next ten minutes." → **WhatsApp** class group (then repeat on Classroom so nobody is left out).
5. Send the principal a formal complaint with a 8 MB scanned letter. → **Email** (written record + attachment).

REMEMBER IT

Docs = write together. Zoom/Teams = meet. Classroom = official class hub. WhatsApp = fast but informal. Email = formal record.

COMMON MISTAKE

Mistake: Running the whole course only on WhatsApp.

Fix: WhatsApp is for quick reminders. Assignments, marks and lectures belong on an LMS so there is access control, a record, and a path that does not depend on one person's phone.

آردو میں سمجھیں

ڈیجیٹل تعاون کے اوزار مختلف مقامات سے بات چیت، فائل شیئرنگ اور ٹیم ورک چلاتے ہیں: گوگل ڈاکس مشترکہ تحریر کے لیے، Zoom اور مائیکروسافٹ ٹیمز میٹنگ کے لیے، گوگل کلاس روم یا ایل ایم ایس باقاعدہ پڑھائی کے لیے، واٹس ایپ فوری اطلاع کے لیے (نہم داری سے)، اور ای میل رسمی ریکارڈ کے لیے۔

CHECK YOURSELF

1. Which tool is excellent for real-time group writing?
2. What four jobs does an LMS / Google Classroom help a teacher do?
3. What is email especially good for?

Answers: 1. Google Docs. 2. Manage lectures, distribute assignments, conduct quizzes, grade activities. 3. Formal communication, official notices, large attachments, and a professional written record.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Collaboration tools include:

- a. Docs, chat, video, boards, LMS
- b. Only NAND trainers
- c. Only K-maps
- d. Only copper

MCQ 2. A good tool match: editing a report together →

- a. Shared document
- b. Only SMS
- c. Only a pie chart
- d. Only a stack

MCQ 3. Video class needs:

- a. Captions + low-bandwidth option
- b. 4K only
- c. No mute
- d. Forced camera in hostels always

MCQ 4. Permissions on a shared folder are:

- a. Access control (Ch 5.3)
- b. A histogram
- c. A median
- d. A sprint

MCQ 5. Chat is poor for:

- a. Final marks sheets (no audit, easy leak)
- b. Quick questions
- c. Memes the teacher banned
- d. Reminders

MCQ 6. Choose tools after:

- a. The task and the weakest connection in the group
- b. The trendiest brand
- c. The teacher's cousin's startup
- d. The GPU

Extra short questions

1. Four tool types and a school use.
2. One security setting per tool.
3. One equity setting.
4. When not to use public WhatsApp.

Extra long question

1. Plan a 1-week group CS project using three tools. For each: purpose, permission, equity tweak, security tweak.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Docs: assignment. Chat: quick. Video: guest lecture. LMS: submit. Board: brainstorm.
2. Docs: restricted link. Video: waiting room. Chat: no OTP sharing.
3. Captions; allow phone upload not only desktop app.
4. CNIC photos, marks, minors' data.

Long

1. LMS submit; Google Doc restricted; recorded Meet with captions. No personal numbers in the file. Lab slot for the student without data. Table.

Application and Impacts of Computing

15 single-page lessons · 5 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- **ML** is a model (a trained brain) that learns from data in three steps: input, learning, prediction on new unseen data — without a hand-written rule for every case.
- **AI** $\supset$ **ML** $\supset$ **DL**: deep learning sits inside machine learning, which sits inside artificial intelligence.
- A **neural network** is a brain-inspired mathematical model of connected neurons in an input layer, hidden layer(s) and output layer (face unlock: camera $\rightarrow$ features $\rightarrow$ unlock).
- **Deep learning** trains neural networks with many hidden layers; early layers learn simple features, deeper layers learn complex patterns. It needs huge data and computing power.
- NN components: input layer, neurons, hidden layers, weights, bias, activation function, output layer, loss function. A neuron computes $s = \sum(x \times w) + b$, then an activation gate.
- DL components: large data, many hidden layers, automatic feature learning, learning algorithm (backpropagation), GPUs, training epochs. Pakistan's National AI Policy 2025 covers education, health, agriculture, banking and local languages.
- Applications: image and speech recognition, NLP, healthcare imaging, recommendations, autonomous vehicles, fraud detection, assistive tech.
- **Secure collaboration**: authentication (who), MFA/2FA (two or more factors), access control (what you may do), accountability, privacy, safe transmission.
- **Data protection**: encryption (plaintext $\rightarrow$ ciphertext; symmetric vs asymmetric; Caesar shift), strong passwords, 3-2-1 backup, firewall and antivirus.
- Threats: malware, phishing, unauthorised access, data/identity theft, DoS, human error. Spot them by pop-ups, odd logins, urgent OTP emails, missing files, traffic spikes.
- Mitigation: antivirus + firewall, strong passwords + 2FA, encryption, regular backups, user awareness.
- **Equal access** = same tools for all; **equity** = extra support for the same outcome. Functions: need-based support, removing barriers, recorded participation, multiple formats. Tools: Docs, Zoom, Teams, Classroom/LMS, WhatsApp, email.

Key terms

Term	Meaning	اردو
Artificial intelligence (AI)	The broad field in which machines perform tasks that normally need human thinking.	مصنوعی ذہانت
Machine learning (ML)	A model that learns patterns from data and then predicts on new data.	مشین لرننگ
Neural network (NN)	A brain-inspired mathematical model of connected neurons in layers.	نیورل نیٹ ورک
Deep learning (DL)	An ML method that trains neural networks with many hidden layers.	ڈیپ لرننگ
Weight	A number showing the strength or importance of a connection between neurons.	وزن (وزن تعلق)
Bias	An extra constant added to a neuron's sum to improve accuracy.	بائیس
Activation function	A gate that decides whether a signal is important enough to pass on.	ایکٹیویشن فنکشن
Loss function	A measure of how wrong the model's answer is compared with reality.	لاس فنکشن
Epoch	One full training pass through the dataset.	ایپوک (تربیتی چکر)
GPU	Graphics Processing Unit — specialised hardware used to train deep networks.	جی پی یو
NLP	Natural Language Processing — computers understanding and producing human language.	قدرتی زبان کی پروسیسنگ
Authentication	Confirming a user's identity before access (password, PIN, OTP, biometrics).	تصدیق شناخت

Application and Impacts of Computing

75 marks · 1 hour 15 minutes · no notes · no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 15 and the recap. **Section A** — all 15 MCQs (1 mark). **Section B** — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define · Explain · Example · Diagram · Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. A machine-learning model works in which order?
 - a. Prediction, then data input, then learning
 - b. Data input, learning, then prediction on new data
 - c. Only prediction, with no data
 - d. Writing a separate rule for every case
2. A neural network is best described as:
 - a. a living human brain placed in a computer
 - b. a backup disk
 - c. a brain-inspired mathematical model of connected neurons
 - d. a type of firewall
3. The word "deep" in deep learning refers to:
 - a. several hidden layers through which data passes
 - b. very loud speakers
 - c. using only one neuron
 - d. storing data underground
4. In the relationship $AI \supset ML \supset DL$, the innermost set is:
 - a. AI
 - b. ML
 - c. equal access
 - d. DL
5. Weights in a neural network show the:
 - a. colour of the screen
 - b. importance or strength of connections between neurons
 - c. size of the hard disk
 - d. student's roll number
6. For $x_1 = 1$, $x_2 = 0$, $w_1 = 0.5$, $w_2 = 0.5$, $b = 0$ and threshold 0.4, the neuron output y is:
 - a. 1
 - b. 0
 - c. 0.4
 - d. 2
7. Which of the following is a component of deep learning (not of a tiny shallow network)?
 - a. Exactly one hidden layer and ten rows of data
 - b. Manual listing of every feature by a human, always
 - c. Many hidden layers, huge datasets and GPUs
 - d. A Caesar cipher
8. Unlocking a phone by matching facial features is mainly an example of:
 - a. a DoS attack
 - b. 3-2-1 backup
 - c. equal access
 - d. image recognition
9. Authentication means:
 - a. choosing who may edit a file
 - b. confirming a user's identity before allowing access
 - c. shifting letters in a cipher
 - d. flooding a server with requests
10. Password plus an OTP sent to a phone is an example of:
 - a. MFA / 2FA
 - b. a worm
 - c. a shallow neural network
 - d. equity captions

11. With a Caesar cipher of shift 3, the plaintext CAT becomes:
 - a. DBU
 - b. CAW
 - c. FDW
 - d. ZXQ
12. The 3-2-1 backup rule requires:
 - a. three passwords only
 - b. one copy on the same laptop twice
 - c. no off-site copy
 - d. three copies, two media types, one copy off-site
13. Phishing is:
 - a. a social-engineering trick using fake emails or sites to steal passwords or OTPs
 - b. a type of GPU
 - c. an activation function
 - d. a collaboration tool like Zoom
14. A Denial of Service (DoS) attack:
 - a. always steals a CNIC
 - b. floods a system with fake requests so it slows or crashes
 - c. is the same as a strong password
 - d. is a hidden layer
15. Turning on live captions in Zoom for a student with hearing difficulties is an example of:
 - a. malware
 - b. a DoS attack
 - c. equal access only, with no extra support
 - d. equity

Section B — Short questions (10 × 3 = 30)

1. Define a machine-learning model and state the three steps of how it works.
2. What is a neural network? Name its three kinds of layer and link them to face unlock.
3. Differentiate a neural network (the model) from deep learning (the method).
4. State the relationship $AI \supset ML \supset DL$ in words.
5. List eight components of a neural network. What do weights and bias do?
6. Name six components of deep learning.
7. Differentiate authentication, MFA and access control with one example each.
8. Encrypt SINDH using a Caesar cipher with shift 3. State whether this cipher is symmetric or asymmetric.
9. Define malware, phishing and DoS. Give one Pakistani-style example of each.
10. Differentiate equal access and equity. List four functions of equity and equal access.

Section C — Long questions (attempt any 3 × 10 = 30)

1. Explain machine learning, neural networks and deep learning. Draw and label the set diagram $AI \supset ML \supset DL$. Include the face-unlock walk-through and the photo-gallery example.
2. A neuron has inputs $x_1 = 0.8$, $x_2 = 0.5$, weights $w_1 = 0.4$, $w_2 = 0.6$, bias $b = 0.1$ and threshold 0.5. (a) Compute the weighted sum s and the output y . (b) Repeat for $x_1 = 0.2$, $x_2 = 0.3$. (c) Name all eight NN components and sketch a 3-4-2 network. (d) List the six DL components and map them onto a cotton-leaf disease detector in Sindh.
3. Describe eight applications of neural networks and deep learning with examples. Then discuss the future of AI in Pakistan with reference to the National AI Policy 2025 and five sectors.
4. What is secure collaboration? Explain authentication, MFA/2FA, access control, accountability, data privacy and safe transmission, using a Google Classroom / banking-app scenario from Pakistan.
5. Define data protection. Explain encryption (symmetric vs asymmetric) with a full Caesar-cipher working of SINDH (shift 3). Describe strong passwords, the 3-2-1 backup rule, firewall and antivirus.
6. Define a security threat. Explain malware, phishing, unauthorised access, data/identity theft, DoS and human error. Give a table of identifying signs and a matching set of mitigation techniques. End with equity versus equal access and a fair choice of collaboration tools.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

1. **5.1 Machine Learning, Neural Networks & Deep Learning.** Answers: 1. AI ($AI \supset ML \supset DL$). 2. Yes — DL is inside ML, and ML is inside AI. 3. Any of: face unlock, speech recognition, photo search, medical diagnosis, language translation.
2. **5.1.1 Machine Learning (ML).** Answers: 1. Data input, learning, prediction. 2. The trained brain of a computer program. 3. New, unseen data.
3. **5.1.2 Neural Networks (NN).** Answers: 1. Neurons or nodes. 2. Hidden layers. 3. No — it is inspired by the brain but works as a mathematical computer system.
4. **5.1.3 Deep Learning (DL).** Answers: 1. Because data passes through several hidden layers. 2. Early: simple features (edges, shapes, colours). Deeper: complex patterns (a whole face, a car model). 3. No — that is a shallow network; DL always uses many hidden layers.
5. **5.1.4 Components of Neural Networks.** Answers: 1. The importance or strength of connections between neurons. 2. $s = 1 \times 0.5 + 0 \times 0.5 + 0 = 0.5$; $0.5 \geq 0.4$ so $y = 1$. 3. The error — how much the model's answer is wrong compared with reality.
6. **5.1.5 Components of Deep Learning.** Answers: 1. It needs massive datasets (thousands or millions of records) for accuracy. 2. One training loop — one full pass through the training data. 3. GPUs (Graphics Processing Units); backpropagation.
7. **5.2 Applications of Neural Networks and Deep Learning.** Answers: 1. National AI Policy 2025. 2. Those areas often lack specialist doctors; AI can help with disease detection and medical image analysis. 3. Any three of: programming (Python), mathematics, data analysis, problem-solving, ethical use of technology.
8. **5.3 Secure Collaboration (Authentication, Access Control).** Answers: 1. Authentication: who are you? Access control: what may you do? 2. Two-factor / multi-factor authentication (2FA/MFA). 3. Teacher shares the document as view-only with students but gives group leaders edit permission.
9. **5.3.2 Data Protection (Encryption, Passwords, Backup, Firewall).** Answers: 1. SDN ($P \rightarrow S$, $A \rightarrow D$, $K \rightarrow N$). 2. 3 copies, 2 different media, 1 off-site copy. 3. Public key encrypts; private key decrypts.
10. **5.4 Security Threats and Mitigation Techniques.** Answers: 1. Viruses, worms, spyware, ransomware, Trojans. 2. Floods it with thousands of fake requests so it slows down or crashes and real users cannot access it. 3. Data theft is stealing/copying data; identity theft is using stolen personal details (name, CNIC, bank) to pretend to be that person and commit fraud.
11. **5.4.2 Identify Security Threats.** Answers: 1. Malware (or background unauthorised activity). 2. Phishing. 3. Unsafe downloads, cracked software, unverified websites, infected USB drives.
12. **5.4.3 Apply Mitigation Techniques.** Answers: 1. It also requires an OTP sent to your phone (a second factor). 2. You can restore a clean copy instead of losing the files (or paying). 3. Unknown links, suspicious attachments, and password sharing.
13. **5.5 Equity and Equal Access in Digital Collaboration.** Answers: 1. Giving everyone the exact same opportunity, tools and resources. 2. Giving additional, specific support so users who need it can reach the same outcome. 3. Because they are extra support for a student with hearing difficulties, not the same identical tool given to all.
14. **5.5.1 Functions of Equity and Equal Access.** Answers: 1. Need-based support; removing barriers; enabling active participation; supporting different learning needs. 2. Students who face power or internet outages can watch later and not fall behind. 3. It creates a hardware barrier for lower-income students; web-based or light apps give better access.
15. **5.5.2 Collaboration Tools.** Answers: 1. Google Docs. 2. Manage lectures, distribute assignments, conduct quizzes, grade activities. 3. Formal communication, official notices, large attachments, and a professional written record.

Answer key

Multiple choice

1. b
2. c
3. a
4. d
5. b
6. a
7. c
8. d
9. b
10. a
11. c
12. d
13. a
14. b
15. d

Short questions — model answers

1. An ML model is the system that learns from data and gives an output — the trained brain of a program. Steps: (1) data input — massive data is given; (2) learning — it studies data and finds patterns/rules automatically; (3) prediction — after training it decides on new, unseen data.
2. A neural network is a computer model that learns patterns from data; it is inspired by the human brain but works as a mathematical system of connected neurons/nodes. Input layer receives the camera image; hidden layers study features such as eye distance and nose shape; output layer unlocks the phone if they match stored data.
3. A neural network is the model: layers, nodes and connections; it can be shallow (one or two hidden layers). Deep learning is the method of training networks that have many hidden layers, needing huge data and processing power for complex patterns.
4. Artificial intelligence is the largest set; machine learning is a part of AI; deep learning is a part of ML. All DL is ML and all ML is AI, but not all AI is ML and not all ML is DL.
5. Input layer; neurons/nodes; hidden layer(s); weights; bias; activation function; output layer; loss function. Weights show connection strength/importance. Bias is an extra constant that helps adjust the result and improve accuracy.
6. Large input data; many hidden layers; automatic feature learning; learning algorithm (e.g. backpropagation); high computing power (GPUs); training process (epochs).
7. Authentication confirms identity before access (password, PIN, OTP, biometrics — e.g. bank OTP). MFA/2FA requires two or more factor types, typically password + OTP. Access control decides what that user may do (view/edit/comment/download/share — e.g. Google Doc view-only for the class, edit for group leaders).
8. $S \rightarrow V, I \rightarrow L, N \rightarrow Q, D \rightarrow G, H \rightarrow K$ so ciphertext VLQ GK. Caesar uses the same shift key to encrypt and decrypt, so it is symmetric.
9. Malware: harmful software (viruses, worms, spyware, ransomware, Trojans) — e.g. cracked software that corrupts files. Phishing: fake genuine-looking email/SMS/site stealing passwords or OTPs — e.g. fake JazzCash OTP page. DoS: flood of fake requests that slows or crashes a service — e.g. online exam portal students cannot enter.
10. Equal access: same tools/opportunity for everyone (same Zoom login). Equity: extra specific support so people with barriers reach the same outcome (captions for hearing difficulties). Functions: need-based support; removing barriers (low-data apps for remote areas); enabling participation (recorded lectures during load-shedding); supporting different learning needs (video, text, audio).

Long questions — model answers

1. **ML**: trained-brain model; data → learn patterns → predict on unseen data; used in face unlock, speech, photo search, diagnosis, translation. **NN**: brain-inspired maths model; neurons pass information through Input, Hidden, Output; face unlock: camera (input), eye distance/nose shape (hidden), unlock (output). **DL**: ML method with multi-layer NNs; “deep” = several hidden layers; early layers: edges/shapes/colours; deeper: whole face or car model; gallery search example. **Diagram**: three nested sets labelled AI, ML, DL with AI outermost. Sentence: $DL \subset ML \subset AI$.
2. **(a)** $s = 0.8 \times 0.4 + 0.5 \times 0.6 + 0.1 = 0.32 + 0.30 + 0.1 = 0.72$; $0.72 \geq 0.5$ so $y = 1$. **(b)** $s = 0.2 \times 0.4 + 0.3 \times 0.6 + 0.1 = 0.08 + 0.18 + 0.1 = 0.36$; $0.36 < 0.5$ so $y = 0$. **(c)** Eight components as in the table; sketch three input circles, four hidden, two output, labelled layers. **(d)** Huge labelled leaf photos; many hidden layers; features learned automatically; backpropagation; GPU training; many epochs until accuracy rises — cotton pest detector for a Sindh farm.
3. Cover all eight: image recognition (face lock, cameras); speech (assistant alarm, Urdu voice); NLP (Translate, chatbots); healthcare (X-ray/CT/MRI, pneumonia); recommendations (YouTube CS videos); autonomous vehicles (brake for pedestrian); fraud (unusual bank transaction); assistive (speech-to-text). Then Policy 2025: innovation, skills, ethics, digital growth. Sectors: education (tutoring, assessments); healthcare (rural diagnosis); agriculture (crops, irrigation, yield); business/banking (fraud, chatbots); local languages (Urdu, Sindhi). Students need Python, maths, data analysis, problem-solving, ethics.
4. Secure collaboration = working together with digital tools in a safe, controlled, responsible way. Authentication: prove identity (password/PIN/OTP/biometrics); bank OTP example. MFA: two or more of know/have/are; 2FA = password + phone OTP. Access control: view/edit/comment/download/share; teacher view-only vs group-leader edit. Accountability: LMS tracks who uploaded/submitted. Privacy: protect names, marks, passwords; share only with the right people; confidentiality; legal/ethical compliance. Safe transmission: encrypted official LMS, not an open public forum. Classroom scenario: school email + MFA, role permissions, version history, no CNICs on public WhatsApp.
5. Data protection = keeping digital information safe from unauthorised access, misuse, loss, damage or accidental deletion. Encryption: plaintext → ciphertext; symmetric = same key both ways; asymmetric = public encrypt, private decrypt. Caesar shift 3: SINDH → VLQKG; decrypt by -3; wrap-around at Z. Strong password: upper, lower, number, symbol (e.g. Zk@2026#Pass) against brute force. 3-2-1: three copies, two media, one off-site (laptop + USB + Google Drive). Firewall: barrier monitoring/blocking suspicious network traffic. Antivirus: detects/removes malware on the local machine.
6. A security threat is any action, event or weakness that can harm a system or its data. Malware (cracked software); phishing (fake bank mail); unauthorised access (unlocked PC, weak/shared passwords); data theft vs identity theft (stolen CNIC used for fraud); DoS (exam portal flood); human error (wrong email, deleting files, falling for a scam). Signs table: pop-ups/missing files → malware; odd logins → unauthorised access; urgent OTP/bad grammar → phishing; records moved → theft; traffic spike → DoS. Mitigation: antivirus+firewall; strong passwords+2FA; encryption in transit; regular backups; user awareness (no unknown links, attachments, or shared passwords). Equal access vs equity; do not require a high-end phone-only app. Tools: Docs, Zoom, Teams, Classroom/LMS, WhatsApp (responsible), email (formal record).

Self-assessment: I can...

- | | |
|--|--|
| ☐ define ML and explain data input → learning → prediction. | ☐ draw $AI \supset ML \supset DL$ and give a system that belongs in each layer. |
| ☐ describe a neural network and the face-unlock I-H-O path. | ☐ compute a neuron's weighted sum and threshold output from numbers. |
| ☐ list eight NN components and six DL components. | ☐ give eight applications of NN/DL and Pakistan's AI policy sectors. |
| ☐ explain authentication, MFA/2FA and access control with examples. | ☐ encrypt a short word with a Caesar cipher and apply the 3-2-1 backup rule. |
| ☐ identify malware, phishing and DoS from signs and name mitigations. | ☐ distinguish equal access from equity and state four functions of equity. |
| ☐ choose a fair collaboration tool (Docs, Zoom, Teams, LMS, WhatsApp, email). | |

Lecture 06

Entrepreneurship in the Digital Age

Chapter lecture — 16 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XII · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — بارہویں جماعت

16 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XII

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیریئر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

Lectures in this pack

Chapter 6: Entrepreneurship in the Digital Age. Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 6.1 Entrepreneur and Entrepreneurship

L03. Table 6.1 Local examples of digital entrepreneurship

L05. 6.4 Prototype

L07. 6.6 Prototype Development Cycle (Design, Build, Test, Iterate)

L09. 6.8 Minimum Viable Product (MVP)

L11. 6.10 Identifying the Riskiest Assumption

L13. 6.12 Case Study: MVP for a Canteen Pre-Order System

L15. 6.14 Beachhead Market

L02. 6.2 Entrepreneurship in the Digital Age

L04. 6.3 From Problem to Business Idea

L06. 6.5 Types of Prototypes (Low, Mid, High-Fidelity)

L08. 6.7 Class Activity: Create a Prototype

L10. 6.9 Difference between Prototype and MVP

L12. 6.11 Developing an MVP

L14. 6.13 Testing an MVP

L16. 6.15 & 6.16 Complete Student Project & Ethical Use

Entrepreneurship in the Digital Age

This chapter shows you how a real problem in your home, college or bazaar can become a business idea, and how you can test that idea cheaply with paper sketches, prototypes and a Minimum Viable Product (MVP) before you spend a lot of money. You will also learn how to choose your first users, the beachhead market, and how to collect feedback honestly and safely.

اس باب میں آپ سیکھیں گے کہ روزمرہ زندگی کے کسی حقیقی مسئلے کو کاروباری خیال میں کیسے بدلا جائے، اور پروٹوٹائپ (Prototype) اور ایم وی پی (MVP) کے ذریعے کم خرچ میں اس خیال کو کیسے آزمایا جائے۔

What you will learn

- Define **entrepreneur** and **entrepreneurship** and describe the habits of an entrepreneur.
- Explain how digital tools (WhatsApp, Google Forms, Facebook pages, simple websites) make it cheap and quick to start and test a business.
- Turn an everyday problem into a business idea using the steps Observe, Ask Users, Select One Problem, Suggest Solution, Test Early.
- Define a **prototype**, list its uses, and compare low-, mid- and high-fidelity prototypes.
- Draw and explain the prototype development cycle: Design, Build, Test, Iterate.
- Define a **Minimum Viable Product (MVP)** and state at least five differences between a prototype and an MVP.
- Identify the **riskiest assumption** of a business idea and design a small test for it.
- Prepare an MVP plan using the MVP planning checklist, and test the MVP with number-based and comment-based feedback.
- Choose a focused **beachhead market** for a new idea.
- Complete a small group project and use digital tools ethically, safely and fairly.

6.1 Entrepreneur and Entrepreneurship

LEARN IT

An **entrepreneur** is a person who **identifies a problem, thinks of a solution, and tries to change that solution into a product or service.**

An entrepreneur does not always begin with a large company or a big office. Many begin with a small idea, limited resources, and a strong wish to solve a problem. Think of a young person in Karachi who starts by delivering home-cooked lunch boxes to a few offices, or a student in Sukkur who repairs mobile phones for neighbours. They started small.

Entrepreneurs usually show three habits:

- **They observe people and listen to their needs.** They notice what annoys people again and again.
- **They take calculated risks.** A *calculated risk* is a risk you take after thinking about what you could lose and how to keep that loss small. It is not gambling.
- **They improve their idea step by step.** They do not expect the first attempt to be perfect.

What is entrepreneurship?

Entrepreneurship is the **process of planning, starting, testing, and improving** a business idea. It involves **creativity, problem-solving, teamwork, communication, and calculated risk.**

Notice the difference: the *entrepreneur* is the **person**; *entrepreneurship* is the **process** that person goes through.

REMEMBER IT

Simple meaning. An entrepreneur asks: "*What problem can I solve?*" Entrepreneurship is the process of testing and improving that solution until it becomes useful for people.

Remember the three-step journey:

1. Problem

→

2. Solution

→

3. Product

WORKED EXAMPLE

Worked example: spotting the three steps. Ayesha lives in Larkana. Her mother and other women in the street make beautiful hand-embroidered *rillis*, but they can only sell them to visitors.

Step 1, Problem: skilled women have products but very few buyers.

Step 2, Solution: show the rillis online so buyers from other cities can see them.

Step 3, Product/Service: a Facebook page with photos, prices and a "message to order" button.

Ayesha is the **entrepreneur**. Planning the page, posting photos, seeing which designs sell, and changing prices is **entrepreneurship**.

COMMON MISTAKE

Mistake: "Only rich people with big offices can be entrepreneurs."

Fix: The source clearly says many entrepreneurs begin with a small idea and limited resources. What matters is a real problem, a useful solution, and the willingness to improve it.

اردو میں سمجھیں

کاروباری شخص (Entrepreneur) وہ ہوتا ہے جو کسی مسئلے کو پہچانتا ہے، اس کا حل سوچتا ہے اور اس حل کو کسی پراڈکٹ یا سروس میں بدلنے کی کوشش کرتا ہے۔ کاروبار شروع کرنے، آزمائے اور بہتر بنانے کے پورے عمل کو انٹریپرائیوشرپ (Entrepreneurship) کہتے ہیں۔ ایسا شخص لوگوں کی بات سنتا ہے، سوچ سمجھ کر خطرہ مول لیتا ہے اور اپنے خیال کو قدم بہ قدم بہتر بناتا ہے۔

CHECK YOURSELF

1. Is "entrepreneurship" a person or a process?

2. Name the three habits of an entrepreneur given in the source.

3. What is a calculated risk?

Answers: 1. A process (planning, starting, testing and improving a business idea). 2. Observing people and listening to their needs; taking calculated risks; improving the idea step by step. 3. A risk taken after thinking carefully about the possible loss and keeping that loss small.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An entrepreneur:

a. Turns a problem into a product/service and takes the risk

b. Only works in a bank job

c. Only draws NAND

d. Only writes OSI

MCQ 2. Entrepreneurship is the:

a. Process of doing that (test and improve until useful)

b. Logo

c. First tweet

d. Compiler

MCQ 3. A student can be entrepreneurial by:

a. A small local solution (notes, tutoring, canteen queue)

b. Waiting for a billion-dollar app

c. Avoiding all users

d. Skipping tests

MCQ 4. Risk in the book's sense includes:

a. It might not work / no one pays

b. NAND delay

c. Median of 1

d. OSI layer 2

MCQ 5. Not every shopkeeper in the bazaar is automatically:

a. A digital entrepreneur (needs the digital-age piece)

b. A failure

c. A programmer

d. A UX designer

MCQ 6. Ethics still apply:

a. Don't scam, don't leak user data

b. Scams are clever entrepreneurship

c. Spy on classmates

d. Copy a bank app's OTP

Extra short questions

1. Define entrepreneur and entrepreneurship.

2. A local non-app example.

3. Why "risk" is in the definition.

4. One quality of an entrepreneur from class discussion.

Extra long question

1. Is a class fellow who sells printed notes an entrepreneur? Use the book definitions, then say what would make it "digital age".

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Person vs process: problem → solution → offer to users, with risk.

2. A photocopy stall that also sells past papers at the gate — still entrepreneurship; digital comes next lecture.

3. You may waste time/money; users may not come.

4. Observes problems, tests, iterates — not just dreams.

Long

1. Yes if they identified a problem and run a small offer. Digital: WhatsApp catalogue, JazzCash, PDF store. Ethics: copyright of the textbook.

6.2 Entrepreneurship in the Digital Age ★ Golden

LEARN IT

Entrepreneurship in the digital age means using **digital tools to start, test, improve, and grow** a business idea.

These tools may include **mobile phones, social media, websites, online forms, digital payments, maps, videos, and simple apps**. In Pakistan you already know many of them: WhatsApp, Facebook, Instagram, TikTok, YouTube, Google Forms, Google Maps, and digital payments such as JazzCash, Easypaisa or Raast.

The power of digital tools

A digital entrepreneur **does not always need to create a complex mobile app**. Sometimes a **WhatsApp group**, a **Google Form**, a **Facebook page**, or a **simple website** is enough to test an idea.

In the past

- Large investment needed.
- Offices and shops had to be rented first.
- Long planning before anyone saw the product.
- A failed idea meant a big loss.

Today (digital age)

- A small idea can be tested **quickly**.
- Free tools: WhatsApp, Google Forms, Facebook.
- Feedback arrives in hours or days.
- If users do not like the idea, the team can **change it before spending too much money**.

WORKED EXAMPLE

Real-world relevance (from the source).

Example 1: A student selling **handmade cards through Instagram**. She posts photos of her Eid cards, people message her, and she delivers. No website, no app.

Example 2: A shopkeeper creating a **WhatsApp catalogue for Ajrak**. WhatsApp Business lets him list each Ajrak with a photo and price. Customers in Hyderabad or Karachi browse and order through chat.

Both are digital entrepreneurship **without writing a single line of code**.

Walk-through: how the Ajrak seller tests a new design cheaply.

1. He photographs 3 new Ajrak designs and adds them to the catalogue (cost: almost zero).
2. He sends the catalogue link to his customer broadcast list.
3. After one week he counts the orders per design.
4. He prints more of the design that sold most and stops the one nobody ordered.

He learned what customers want **before** printing a large stock.

REMEMBER IT

Remember "S-T-I-G": digital tools help you **Start, Test, Improve and Grow**. Think: "Start The Idea Growing."

COMMON MISTAKE

Mistake: "Digital entrepreneurship means building a mobile app."

Fix: An app is only one option. A WhatsApp group, Google Form, Facebook page or simple website is often enough, and much cheaper, to test whether people want your idea.

اردو میں سمجھیں

ڈیجیٹل دور میں انٹرنیٹ پر مبنی کاروبار شروع کرنا، آزمائش اور بڑھانا۔ ہر بار پیچیدہ ایپ بنانا ضروری نہیں؛ والٹس ایپ گروپ یا گولگل فارم بھی کافی ہو سکتا ہے۔ اگر لوگوں کو خیال پسند نہ آئے تو زیادہ پیسہ خرچ ہونے سے پہلے اسے بدلا جا سکتا ہے۔

EXAM TIP

Common questions: "Define entrepreneurship in the digital age", "How have digital tools changed entrepreneurship?" and "Give examples of digital entrepreneurship without coding." Write the definition (start, test, improve, grow using digital tools), list 4-5 tools, give the past-versus-today contrast (big investment versus quick, cheap testing), and quote the Instagram cards and the WhatsApp Ajrak catalogue examples.

CHECK YOURSELF

1. List four digital tools that the source mentions.
2. Why is it easier to change a business idea today than in the past?
3. Give one example of digital entrepreneurship that needs no coding.

Answers: 1. Any four of: mobile phones, social media, websites, online forms, digital payments, maps, videos, simple apps. 2. Because a small idea can be tested quickly and cheaply, so if users do not like it the team can change it before spending too much money. 3. Selling handmade cards through Instagram, or a WhatsApp catalogue for Ajrak.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Digital-age entrepreneurship uses:

- a. Digital tools to start, test, improve, grow
- b. Only a physical shop with no phone
- c. Only NAND labs
- d. Only paper ledgers forever

MCQ 2. A WhatsApp business catalogue is:

- a. A digital channel
- b. OSI layer 1 hardware
- c. A primary key
- d. A K-map

MCQ 3. Low cost of testing online means:

- a. You can try an MVP cheaply
- b. You skip users
- c. You skip ethics
- d. You skip problems

MCQ 4. This is ★: define + two local examples + one risk.

- a. The recipe
- b. Only Silicon Valley names
- c. Only Python lists
- d. Only ER

MCQ 5. Payment via JazzCash is:

- a. Digital infrastructure an entrepreneur can use
- b. A sort algorithm
- c. A pile of NAND
- d. A Figma auto-layout

MCQ 6. Copying an app without a real user problem is:

- a. Not the book's method
- b. Guaranteed success
- c. A stack
- d. A median

Extra short questions

1. Define entrepreneurship in the digital age.
2. Two tools a student actually has.
3. A risk unique to digital.
4. Why local problems beat fake "Uber for X".

Extra long question

1. Take a photocopier stall. List 5 digital upgrades that fit Chapter 6 (not a full app). For each, the problem it tests. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Using digital tools to start/test/improve/grow a business.
2. Phone camera, WhatsApp, Google Form, Canva, GitHub pages — any two.
3. Cyber fraud, copycats, platform bans, data leak.
4. You can talk to users this week (canteen, hostels, tuition).

Long

1. WhatsApp queue, prepay JazzCash, Google Form for notes list, simple status stories, PDF sample. Each tests demand. Ethics: no pirated books.

Table 6.1 Local examples of digital entrepreneurship

LEARN IT			
Digital entrepreneurship can begin from ordinary problems . The examples below are close to the context of Sindh and Pakistan, where many students, parents, and small service providers already use mobile phones.			
Problem	Digital Idea	Possible First Users	Urdu Context
Parents miss college notices.	WhatsApp notice and reminder service.	Parents of first-year students.	والدین تک کالج کے نوٹس پہنچانے کے لیے واٹس ایپ سروس۔
Small embroidery shop has few customers.	Simple catalogue with order form on Facebook or WhatsApp.	Customers in the same city.	کڑھائی کی دکان کے لیے واٹس ایپ کیٹلاگ۔
Students forget test dates.	Google Calendar guide or simple reminder app.	Grade XII students.	ٹیسٹ کی تاریخیں یاد دلانے والی ایپ یا کیلنڈر۔
Canteen has long queues during break.	Pre-order form for snacks.	Students and teachers.	کینٹین کے لیے بڑی آرڈر فارم۔

Read each row from left to right: a **problem** → a **simple digital idea** → a **small group of first users**. You will see these same examples again later in the chapter (the canteen pre-order system becomes a full case study).

WORKED EXAMPLE

Worked example: adding your own row. Follow the same pattern for a new local problem.

Problem	Digital Idea	Possible First Users
Students in a Mirpurkhas college lose water bottles, calculators and ID cards and never find them.	Lost-and-found Google Form plus a WhatsApp group where found items are posted with a photo.	Students of one college.

Check: Is it a **real** problem? Yes, it happens every week. Is the idea **simple**? Yes, a form and a group. Are the first users **reachable**? Yes, they are in the same college.

COMMON MISTAKE

Important: A digital business idea should **not** be selected only because it sounds modern. It should solve a **real problem for real users**. If the problem is weak, the business idea will also be weak.
For example, "an AI app that chooses your shirt colour" sounds modern, but if nobody actually struggles with that, nobody will use it.

REMEMBER IT

Think **"Problem first, tool second."** Start with the pain, not with the technology.

اردو میں سمجھیں

جدول 6.1 بتاتی ہے کہ ڈیجیٹل کاروبار عام مسائل سے شروع ہو سکتا ہے، جیسے والدین کا کالج نوٹس نہ دیکھ پانا، کڑھائی کی دکان پر کم گاہک، ٹیسٹ کی تاریخ بھول جانا یا کینٹین پر لمبی قطار۔ کوئی خیال صرف اس لیے نہ چنیں کہ وہ جدید لگتا ہے، اسے حقیقی لوگوں کا حقیقی مسئلہ حل کرنا چاہیے۔

CHECK YOURSELF

1. In Table 6.1, what digital idea is suggested for a small embroidery shop?
2. Who are the possible first users of the canteen pre-order form?
3. Why should an idea not be chosen only because it sounds modern?

Answers: 1. A simple catalogue with an order form on Facebook or WhatsApp. 2. Students and teachers. 3. Because it must solve a real problem for real users; a weak problem gives a weak business idea.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Table 6.1 is there to show:
a. Ordinary local problems can start digital businesses
b. Only US startups count
c. Only AI labs count
d. Only OSI consultants count

MCQ 2. A good exam use of the table is:
a. One example, the problem, the digital twist
b. Copying 20 rows unread
c. Ignoring Pakistan
d. Only listing apps

MCQ 3. "Local" means:
a. Your college/bazaar/city, not only Silicon Valley
b. Only Karachi DHA
c. Only English users
d. Only GPUs

MCQ 4. If you invent an example it must still:
a. Be realistic and ethical
b. Promise billions
c. Need NASA
d. Need a compiler in C

MCQ 5. The table sits after 6.2 because:
a. It illustrates digital-age entrepreneurship
b. It replaces prototypes
c. It is HCI only
d. It is SQL only

MCQ 6. A rickshaw app idea should still start from:
a. A real pain (wait, fare fights)
b. A random blockchain
c. A random NFT
d. A random pie

Extra short questions

1. From memory, give two local digital entrepreneurship examples (book or equivalent).
2. For one example: problem → digital twist.
3. Why the board likes local examples.
4. One unethical "business".

Extra long question

1. Add three rows in Table 6.1 style for your college: problem, idea, digital tool, first test.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Food delivery, online tuition, used-books WhatsApp, ride apps, handicraft Instagram — mapped to a problem.
2. Long canteen line → pre-order form.
3. Shows you understood 6.2, not just American brand names.
4. Selling leaked papers; fake job ads.

Long

1. Queue, lost keys, hostel laundry. Tools: form, group, JazzCash. First test: 10 users this week. Ethics column.

6

6.3 From Problem to Business Idea

LEARN IT

A good business idea usually starts from **observing daily life**. Look around your home, college, market, village, or city and ask these simple questions:

- 1. **What problem do people face?**
- 2. **Who faces this problem?**
- 3. **How often does it happen?**
- 4. **What do people currently do to solve it?**
- 5. **Can technology help in a simple way?**

A short way to remember them: **What? Who? How often? Current fix? Tech help?**

WORKED EXAMPLE

Example scenario (from the source): study material before exams.

Students cannot find study material before exams. The quick answer is "students are careless", but that is not the real issue.

Apply the five questions:

- 1. **What problem?** Students cannot find notes before exams.
- 2. **Who?** Students of a class or college.
- 3. **How often?** Before every test and exam.
- 4. **Current fix?** Notes are shared in many places: WhatsApp, email, photocopies, and class groups. Students search all of them.
- 5. **Tech help?** Yes: a simple **subject-wise notes organizer** where all files are placed in one location (for example, one shared Google Drive folder per subject).

The real problem is **scattered notes**, and the idea solves exactly that.

Scope of the problem

Avoid choosing **very large problems** at the start, such as "improving the whole education system". A better problem is **smaller and clear**, such as helping Grade XII students track **practical file submission dates**. Smaller problems are **easier to test and improve**.

Table 6.2: From problem to idea

The journey from observing a problem to creating an idea follows a structured path.

Step	What Students Do	Example
Observe	Notice repeated problems around home, college, or market.	Students forget practical file dates.
Ask Users	Talk to people who face the problem.	Ask five classmates how they remember deadlines.
Select One Problem	Choose one clear problem only.	Practical file reminder.
Suggest Solution	Think of a simple digital or paper-based solution.	Reminder form or app screen.
Test Early	Show the idea to users before final development.	Ask classmates if they will use it.

After this, the idea moves along the full path that the rest of this chapter follows:



REMEMBER IT

Mnemonic for Table 6.2: "Only Ask Simple Solutions Today": Observe, Ask users, Select one problem, Suggest solution, Test early.

COMMON MISTAKE

Mistake 1: Choosing a huge problem ("fix traffic in Karachi"). **Fix:** Narrow it ("help students of one college know when their van will arrive").

Mistake 2: Skipping "Ask Users" and guessing what people need. **Fix:** Talk to at least five real people who face the problem.

اردو میں سمجھیں

اچھا کاروباری خیال روزمرہ زندگی کے مشاہدے سے شروع ہوتا ہے۔ پوچھیں: مسئلہ کیا ہے، کس کو ہے، کتنی بار ہوتا ہے، لوگ ابھی کیا کرتے ہیں، اور کیا ٹیکنالوجی آسان طریقے سے مدد کر سکتی ہے؟ شروع میں چھوٹا اور واضح مسئلہ چنیں، کیونکہ اسے آزمانا اور بہتر بنانا آسان ہوتا ہے۔

CHECK YOURSELF

- 1. Write the five steps of Table 6.2 in order.
- 2. Why is "improving the whole education system" a poor first problem?
- 3. In the study-material example, what is the real problem?

Answers: 1. Observe, Ask Users, Select One Problem, Suggest Solution, Test Early. 2. It is too large and unclear; small, clear problems are easier to test and improve. 3. Notes are scattered in many places (WhatsApp, email, photocopies, class groups), not that students are careless.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An IDE is:

- a. One app to write, run and debug code
- b. A printer
- c. A sort
- d. A cable

MCQ 2. VS Code is:

- a. A popular editor/IDE
- b. A DBMS
- c. An OSI layer
- d. A gate

MCQ 3. The terminal/run button is for:

- a. Executing the program
- b. Drawing pie charts only
- c. Sending TCP SYN only
- d. K-maps

MCQ 4. Syntax highlighting helps you:

- a. See keywords and mistakes
- b. Sort faster
- c. Encrypt disks
- d. Route packets

MCQ 5. A file explorer in VS Code shows:

- a. Project files
- b. OSI layer 1
- c. NAND groups
- d. Beachhead users

MCQ 6. Debugging in an IDE uses:

- a. Breakpoints and variable watch
- b. Only bubble sort
- c. Only pie charts
- d. Only Agile stickers

Extra short questions

- 1. Define IDE.
- 2. Name four VS Code areas.
- 3. Why not use Notepad only?
- 4. What is an extension?

Extra long question

- 1. Describe how you would create, run and debug a first Python file in VS Code. Include two interface elements from the notes.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- 1. Integrated Development Environment: editor + run + debug + files in one place.
- 2. Activity bar/sidebar (files), editor, terminal, status bar (and extensions).
- 3. No easy run, no highlighting, no debugger.
- 4. An add-on (Python plugin) that teaches VS Code a language.

Long

- 1. New file .py, type print, Run Python, read terminal. Mention top menu, explorer, terminal panel. Breakpoint on a wrong variable.

6.4 Prototype ★ Golden

LEARN IT

A **prototype** is an **early model** of a product, service, website, or app. It shows **how the idea may look or work**. It is **NOT the final product**. It is made to **test the idea and collect feedback**.

Think of the clay model an architect makes before building a house, or the sample kameez a tailor stitches before making 50 for a shop. The model lets people say "make this bigger" or "move that here" before real money is spent.

Why is a prototype useful?

A prototype helps students and entrepreneurs **explain their idea clearly**, because users can **see something** instead of only listening to words.

- It **makes the idea visible**.
- It **helps the team find mistakes early**. Users can point out if a button is hard to find, if a screen has too much text, or if a feature is missing.
- It **saves time and money** before final coding begins. Fixing a pencil sketch takes a minute; fixing finished code can take days.

What form can a prototype take?

A prototype may be a **paper sketch**, a **cardboard model**, a **clickable PowerPoint**, a **Canva design**, a **Figma wireframe**, a **simple website layout**, or a **sample service process chart**. A **wireframe** is a simple outline drawing of a screen that shows where things go (boxes, buttons, text) without colours or pictures.

For example, for a **canteen pre-order system**, students can just **draw the screens on paper**.



A paper prototype of a canteen pre-order system: three hand-drawn screens joined by arrows (select item → enter name → collect order).

WORKED EXAMPLE

Worked example: how a paper prototype finds a mistake early. Bilal's team in a Nawabshah college draws the three screens above on A4 paper.

1. They hand screen 1 to a classmate and say, "Order a samosa."
2. The classmate looks for a quantity box and cannot find one. She asks, "What if I want two?"
3. The team notes: **feature missing: quantity**.
4. They add a small "Qty: []" box with a pencil in 30 seconds.

If they had already coded an app, adding quantity would have meant changing the database, the screen and the order list. The prototype **saved time and money**.

REMEMBER IT

Prototype = "practice model". It is like a rough draft of an essay: you show it, get corrections, and rewrite it before the final copy.

COMMON MISTAKE

Mistake: Thinking a prototype must work or must look beautiful.

Fix: A prototype only has to make the idea **visible** so users can react. A pencil sketch is a valid prototype.

اردو میں سمجھیں

پروتوٹائپ (Prototype) کسی پرائڈکٹ، سروس، ویب سائٹ یا ایپ کا ابتدائی نمونہ ہوتا ہے جو دکھاتا ہے کہ خیال کیسا نظر آئے گا یا کیسے کام کرے گا۔ یہ جتنی پرائڈکٹ نہیں ہوتا بلکہ خیال کو آزمائے اور رائے (Feedback) لینے کے لیے بنایا جاتا ہے۔ یہ کاغذ کا خاکہ، گتے کا ماڈل، ہاوریوائنٹ یا فگما (Figma) ڈیزائن بھی ہو سکتا ہے، اور اس سے غلطیاں جلد پکڑی جاتی ہیں اور وقت اور پیسہ بچتا ہے۔

EXAM TIP

Expect "Define prototype and write its benefits" (3–5 marks). Write: (1) definition with the words *early model*, *not the final product*, *test the idea and collect feedback*; (2) three benefits: makes the idea visible, finds mistakes early, saves time and money; (3) forms it can take (paper sketch, cardboard model, clickable PowerPoint, Canva, Figma wireframe); (4) the canteen paper-screens example.

CHECK YOURSELF

1. Is a prototype the final product?
2. Name four forms a prototype can take.
3. Give two kinds of problems users can point out by looking at a prototype.

Answers: 1. No. It is an early model made to test the idea and collect feedback. 2. Any four: paper sketch, cardboard model, clickable PowerPoint, Canva design, Figma wireframe, simple website layout, sample service process chart. 3. Any two: a button is hard to find, a screen has too much text, a feature is missing.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A prototype is:

- a. An early model of how it may look/work — not the final product
- b. The finished mass-produced item
- c. A database backup
- d. A pile of revenue

MCQ 2. You build it to:

- a. Learn, not to impress investors first
- b. Win a logo contest only
- c. Replace users
- d. Skip tests

MCQ 3. This is ★: define, purpose, what it is NOT.

- a. The 5-mark
- b. Only draw Figma pretty
- c. Only Python
- d. Only OSI

MCQ 4. A paper phone screen is still a:

- a. Prototype (low fidelity)
- b. MVP already charged
- c. Compiler
- d. Firewall

MCQ 5. Prototype before code when:

- a. The question is "do people understand the idea?"
- b. You already have 1 million users
- c. The law froze the spec like waterfall NASA
- d. You are only drawing NAND

MCQ 6. Throwing a prototype away can be:

- a. Success (you learned cheaply)
- b. Shame
- c. A SQL error
- d. A median

Extra short questions

1. Define prototype from the book.
2. Three purposes.
3. What it is not.
4. A non-app prototype.

Extra long question

1. Design a paper prototype of a "lost-and-found" college app: 3 screens, 3 things you would watch in a test. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Early model of a product/service/app that shows how it may look or work. Not the final thing.
2. Communicate idea, test with users, find problems early.
3. Not the finished product; not necessarily coded; not an MVP (next topics).
4. A cardboard token for a queue system.

Long

1. Home, report item, search. Watch: do they find report in 30s, do they understand photos, do they trust privacy. Don't code yet.

6.5 Types of Prototypes (Low, Mid, High-Fidelity)

LEARN IT

Prototypes are commonly divided into **three types** according to their level of detail, called **fidelity**. **Fidelity means how close the prototype is to the final product.** Low fidelity = far from final; high fidelity = very close to final.

6.5.1 Low-Fidelity Prototype

A **quick and rough** model made at the **very beginning**. It is **drawn on paper**. It does **not focus on colours or fonts**. It shows the **main idea and flow** (which screen comes after which). It is **very suitable for students** because it is **cheap, fast, and easy to change**.

6.5.2 Mid-Fidelity Prototype

Clearer than a paper sketch. It is created in **PowerPoint, Canva, or Figma**. It shows screens and **navigation** in a more organised way, but **without final graphics**. It is useful to **test screen-to-screen navigation**, for example by linking slides so that clicking "Next" opens the next screen.

6.5.3 High-Fidelity Prototype

Looks **very close to the final product**. It includes **realistic colours, buttons, sample data, and working features**. It **takes more time** and should **only be created after the basic idea is tested**.

Comparison of prototype types

For most school and college projects, you should **begin with a low-fidelity prototype**. A common mistake is to start building a full app before knowing whether users need it. A rough prototype protects you from this mistake.

Table 6.3: Types of prototypes

Type	Meaning	Best Use	Example
Low-Fidelity	A quick and rough model of the idea.	Very early testing.	Hand-drawn app screens for homework reminder.
Mid-Fidelity	A clearer model that shows layout and flow.	Testing navigation.	Clickable screens in PowerPoint or Figma.
High-Fidelity	A detailed model close to the final product.	Testing realistic experience.	Working demo of a small order form website.



Extra comparison to help you revise:

Feature	Low-Fidelity	Mid-Fidelity	High-Fidelity
Tool	Paper and pencil	PowerPoint, Canva, Figma	Figma (detailed), HTML
Colours and fonts	No	Not final	Realistic
Clickable?	No (you move papers by hand)	Yes, basic links	Yes, with working features
Cost and time	Lowest, fastest	Medium	Highest, slowest
Easy to change?	Very easy	Fairly easy	Harder
When	Very beginning	After the flow is agreed	Only after the basic idea is tested

WORKED EXAMPLE

Worked example: one idea, three fidelities. Idea: a Homework Reminder for a college in Jacobabad.

- Low-fi:** Sana draws three screens on paper in 15 minutes: "Today", "Add homework", "Reminder". Classmates point at the drawings to "use" them.
- Mid-fi:** After feedback, she makes three PowerPoint slides with grey boxes and links them with hyperlinks, so tapping "Add" opens the Add slide. Now she tests whether people can move between screens easily.
- High-fi:** Once users clearly want it, she builds a small HTML page with real colours, a working form and sample homework data.

Each step costs more, so she **only** moves up when the previous step proves the idea is worth it.

REMEMBER IT

Fidelity = "faithfulness" to the final product. Remember **Paper → PowerPoint → Polished** (low → mid → high).

COMMON MISTAKE

Mistake: Starting with a high-fidelity prototype or a full app because it "looks professional".

Fix: Begin with low fidelity. If users do not need the idea, you have lost only paper and an hour, not weeks of work.

آڈو میں سمجھیں

فڈیلیٹی (Fidelity) کا مطلب ہے کہ پروٹوٹائپ حتمی پراڈکٹ سے کتنا ملتا جلتا ہے۔ لو فڈیلیٹی پاورپوائنٹ، کینوا یا فگما میں بنتا ہے اور اسکرینوں کی درمیان آنا جانا (Navigation) دکھاتا ہے؛ ہائی فڈیلیٹی بالکل اصل پراڈکٹ جیسا لگتا ہے اور اسے بنیادی خیالات آزمائے کے بعد ہی بنانا چاہیے۔

CHECK YOURSELF

- What does "fidelity" mean?
- Which type of prototype is best for testing navigation?
- Why should students begin with low fidelity?

Answers: 1. How close the prototype is to the final product. 2. Mid-fidelity (e.g. clickable screens in PowerPoint or Figma). 3. It is cheap, fast and easy to change, and it protects them from building a full app before knowing whether users need it.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An IDE is:

- a. One app to write, run and debug code
- b. A printer
- c. A sort
- d. A cable

MCQ 2. VS Code is:

- a. A popular editor/IDE
- b. A DBMS
- c. An OSI layer
- d. A gate

MCQ 3. The terminal/run button is for:

- a. Executing the program
- b. Drawing pie charts only
- c. Sending TCP SYN only
- d. K-maps

MCQ 4. Syntax highlighting helps you:

- a. See keywords and mistakes
- b. Sort faster
- c. Encrypt disks
- d. Route packets

MCQ 5. A file explorer in VS Code shows:

- a. Project files
- b. OSI layer 1
- c. NAND groups
- d. Beachhead users

MCQ 6. Debugging in an IDE uses:

- a. Breakpoints and variable watch
- b. Only bubble sort
- c. Only pie charts
- d. Only Agile stickers

Extra short questions

- Define IDE.
- Name four VS Code areas.
- Why not use Notepad only?
- What is an extension?

Extra long question

- Describe how you would create, run and debug a first Python file in VS Code. Include two interface elements from the notes.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Integrated Development Environment; editor + run + debug + files in one place.
- Activity bar/sidebar (files), editor, terminal, status bar (and extensions).
- No easy run, no highlighting, no debugger.
- An add-on (Python plugin) that teaches VS Code a language.


Long

- New file .py, type print, Run Python, read terminal. Mention top menu, explorer, terminal panel. Breakpoint on a wrong variable.

6.6 Prototype Development Cycle (Design, Build, Test, Iterate) ★ Golden

LEARN IT

Prototype development is **not a one-time activity**. A prototype is **created, tested, improved, and tested again**. This repeating process is called **iteration**. The main stages are **Design, Build, Test, and Iterate**.



The prototype development cycle: Design → Build → Test → Iterate, then back to Design.

Stage	What happens
1. Design	Understand the problem and plan the solution. Decide what the prototype should show (e.g. screen flow, features).
2. Build	Create the first version (physical or digital). The aim is not beauty; the aim is to make the idea visible.
3. Test	Show the prototype to users. Observe what they understand and what they find difficult.
4. Iterate	Improve the prototype based on user feedback. Remove unnecessary parts and add missing features.

WORKED EXAMPLE

Worked example: **two rounds of the cycle**. A team in Thatta wants a WhatsApp catalogue for a local Ajrak shop.

Round 1

- **Design:** The problem is that customers do not know which designs and prices are available. Plan: one page per design with photo, price and an "Order" message.
- **Build:** They make a paper booklet with 6 hand-drawn "catalogue pages".
- **Test:** They show it to 5 customers. Three ask, "Is this single or double-sided Ajrak? What size?"
- **Iterate:** They add size and type to every page.

Round 2

- **Design:** Add the size and type fields, and a delivery note.
- **Build:** They make the catalogue in WhatsApp Business with real photos.
- **Test:** 5 new customers browse it. Now nobody asks about size; one says the delivery charge is unclear.
- **Iterate:** They add "Delivery in Thatta: Rs 100" to each item.

Each round produces a clearer version, because each change comes from real feedback.

REMEMBER IT

Mnemonic: **"Do Big Things Iteratively"** = Design, Build, Test, Iterate. And remember the arrow at the end goes **back to Design**: it is a **cycle**, not a line.

COMMON MISTAKE

Mistake 1: Drawing the stages as a straight line that ends at "Iterate". **Fix:** Always draw a loop with an arrow from Iterate back to Design.

Mistake 2: Making the Build stage beautiful. **Fix:** The source says "The aim is not beauty; the aim is to make the idea visible."

اردو میں سمجھیں

پروٹوٹائپ ایک پی یار میں بنتا، اسے پتایا، آزمایا، بہتر کیا اور دوبارہ آزمایا جاتا ہے۔ اس بار بار دہرانے کے عمل کو **ایٹریشن** (Iteration) کہتے ہیں۔ چار مراحل ہیں: ڈیزائن (مسئلہ سمجھ کر حل کی منصوبہ بندی)، بیلڈ (پہلا نمونہ بنانا)، ٹیسٹ (صارفین کو دکھانا) اور ایٹریت (رائے کی بنیاد پر بہتری)۔

EXAM TIP

A favourite long question: "Explain the prototype development cycle with a diagram." Draw the four boxes in a **circle** with arrows, write one or two lines for each stage using the source's words, define **iteration**, and finish with a short example (e.g. the ClassBuddy activity in 6.7). Marks are often lost for drawing a straight line instead of a cycle.

CHECK YOURSELF

1. What is iteration?

2. At which stage do you observe what users find difficult?

3. What is the aim of the Build stage?

Answers: 1. The repeating process of creating, testing, improving and testing a prototype again. 2. The Test stage. 3. To make the idea visible (not to make it beautiful).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The cycle is:
a. Design → build → test → Iterate (repeat)
b. Build once, never look
c. Test on no one
d. Advertise first

MCQ 2. Iterate means:
a. Change the prototype from what you learned
b. Print more logos
c. Hire 50 people
d. Write OSI parsers

MCQ 3. This is ★ because:
a. Entrepreneurship is not one-shot in the book
b. Waterfall never iterates even in software
c. Users are optional
d. Ethics are optional

MCQ 4. If tests fail, you:
a. Return to design
b. Ship anyway always
c. Delete the users
d. Change the syllabus

MCQ 5. A cycle can be:
a. Hours (paper) not months
b. Only yearly
c. Only after IPO
d. Only in Silicon Valley

MCQ 6. Skipping test in the cycle turns it into:
a. Just building in the dark
b. HCI gold
c. SQL gold
d. Big O gold

Extra short questions

1. Name the four stages.

2. What do you carry from test to design?

3. How many cycles is "enough" for class?

4. Link to Agile from XI.

Extra long question

1. Document two cycles of a homework-reminder prototype. Each cycle: what you built, who tested, what changed. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Design, build, test, iterate.

2. Notes: where people stuck, what they asked for, what they ignored.

3. At least two documented rounds.

4. Same spirit: small loops with feedback. Don't over-claim they are identical.

Long

1. Cycle1 paper: people wanted SMS not email. Cycle2 Figma with SMS mock. Metric: 4/5 could complete. Table.

6.7 Class Activity: Create a Prototype

LEARN IT

Business idea scenario. Students often forget **homework deadlines**, **test dates**, and **required class items**. A group of students wants to design a simple "Homework Helper" or "ClassBuddy" reminder system.

The team will **not** immediately build a complete mobile app. They will first **understand the problem**, **draw a low-fidelity prototype**, **test it with classmates**, and **improve it**. This activity is the development cycle of 6.6 in action.



Step 1: Understand the problem

The team **interviews ten students**. They find that **7 out of 10** students (that is 70%) forget at least one task in a week. Students want **reminders before leaving home**, and some prefer a **very simple design**.

Table 6.4: Understanding user needs

Finding	Meaning	Design Decision
7 out of 10 forget tasks.	The problem is common.	App should show a daily task list.
Reminders needed before leaving home.	Reminder time is important.	Add morning notification option.
Students want simple apps.	Design must be simple.	Use large buttons and clear labels.

Step 2: Draw a low-fidelity prototype

The team draws **three screens on paper**: (1) **Today's classes**, (2) **Add homework**, (3) **Show reminder**. **Arrows** show how a user moves from one screen to another.

Step 3: Test the prototype

The team gives the paper screens to **five classmates**. The **observer watches silently** to see if users can understand the design by themselves. Users are given one task: "**add one homework task**".

Step 4: Analyse feedback

The team looks for **repeated problems** in the feedback to identify what actually needs fixing.

Table 6.5: Changing feedback into improvement

User Feedback	Problem Identified	Improvement
"I cannot quickly find Add Homework."	Button is not visible.	Make Add Homework button larger and centre it.
"I want reminders by subject."	Reminder is too general.	Add subject name and due date fields.
"I want to see all tasks for the week."	Only daily view is not enough.	Add a "Weekly View" button.

Step 5: Improve the prototype

The team **redraws the home screen** with a **larger Add Homework button**, a **subject list**, and a **weekly view**. This second version is clearer because it is based on real user feedback.

A **prototype has not failed** when users give **negative feedback**; it **only fails** if the team **ignores useful feedback**.

WORKED EXAMPLE

Worked example: **link the activity to the cycle**.

Cycle stage	ClassBuddy activity step
Design	Step 1: interview 10 students, make design decisions (Table 6.4).
Build	Step 2: draw three paper screens with arrows.
Test	Step 3: five classmates try "add one homework task" while the observer watches silently.
Iterate	Steps 4 and 5: analyse feedback (Table 6.5) and redraw the home screen.

Why watch silently? If the observer explains ("tap here"), the team never learns that the button is hard to find. Silence shows the real difficulty.

REMEMBER IT

Feedback → Problem → Improvement. Every comment should be turned into a problem statement and then one clear change, exactly like the three columns of Table 6.5.

COMMON MISTAKE

Mistake: Feeling that negative feedback means the prototype "failed", or changing the design for every single comment.

Fix: Negative feedback is useful information. Look for **repeated** problems and fix those first. The prototype only fails if you ignore useful feedback.

اردو میں سمجھیں

اس سرگرمی میں طلبہ "کلاس بڈی" (ClassBuddy) نامی یاد دہانی نظام بناتے ہیں۔ پہلے دس طلبہ سے بات کر کے مسئلہ سمجھتے ہیں، پھر کاغذ پر تین اسکرینیں بناتے ہیں، پانچ ساتھیوں سے خاموشی سے آزمائش کرتے ہیں، رائے کا تجزیہ کرتے ہیں اور تیزاں بہتر کرتے ہیں۔ منفی رائے سے پروتوتائپ ناکام نہیں ہوتا، ناکامی تب ہے جب مفید رائے کو نظرانداز کیا جائے۔

CHECK YOURSELF

- In Step 1, how many students forgot at least one task in a week, and what percentage is that?
- Name the three paper screens drawn in Step 2.
- What improvement was made for the feedback "I want to see all tasks for the week"?

Answers: 1. 7 out of 10, which is 70%. 2. Today's classes, Add homework, Show reminder. 3. A "Weekly View" button was added.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The class activity exists to: a. Make you build and test a prototype, not only define it b. Replace the exam c. Teach NAND d. Teach OSI	MCQ 2. Forgotten deadlines is a: a. Problem you can prototype b. GPU problem c. Primary key problem d. K-map problem	MCQ 3. Five classmates as testers are: a. Enough for a class test if you watch silently b. A statistically perfect census c. Useless d. A DoS attack	MCQ 4. The observer should: a. Watch, not rescue immediately b. Click for them c. Shout answers d. Grade their fashion	MCQ 5. You record: a. Where they hesitate and what they say b. Only a selfie c. Only the logo poll d. Only Big O	MCQ 6. After the activity you still: a. Iterate b. Ship to Play Store same hour c. Skip ethics d. Skip the write-up
---	---	---	---	---	--

Extra short questions

- Summarise the book's activity scenario.
- Three paper screens you would draw.
- How to test without coding.
- One ethical rule in class tests.

Extra long question

- Write a lab report of the activity: idea, 3 screens, 5-user results, 3 changes. Use the cycle words.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Students forget homework/tests/items; team prototypes a reminder.
- Today's tasks; add task; alarm confirm.
- Ask a classmate to "use" paper as if it were a phone; you swap sheets.
- Don't mock testers; don't collect their personal timetable into a public group.

Long

- Results: 2/5 missed Add. Changes: bigger button, Urdu, confirm. Iterate. Marks-style headings.

6.8 Minimum Viable Product (MVP) ★ Golden

LEARN IT

A **Minimum Viable Product (MVP)** is the **simplest working version** of a product. It includes **only the most important features** needed to **test the idea with real users**.

- Minimum:** It has only the **essential** features. No extras.
- Viable:** It is **usable enough** to actually solve the main problem. ("Viable" means able to work successfully.)

An MVP is **not the final product**. It is also **not only a drawing**. It is a **small working version** used to test whether users actually need the solution.

WORKED EXAMPLE

Example from the source: canteen app.

Complete canteen app (final product)	Canteen MVP
Login, online payment, delivery tracking, discount offers...	A simple Google Form where students select snacks before break.

Step-by-step: how to cut a big idea down to an MVP.

- List all features you dream of: login, payment, delivery tracking, discounts.
- Ask of each one: "Without this, can a student still pre-order a snack?"
- Login? Not needed; the student can type name and class. Payment? Not needed; pay at the counter. Delivery tracking? Not needed; students collect. Discounts? Not needed.
- What is left is the core: **choose snack + name + class**. A Google Form does this for free.

That form is **minimum** (no extras) and **viable** (students really can pre-order with it).

REMEMBER IT

Simple meaning. An MVP answers: "**Will people actually use this solution?**" It tests **real use and behaviour**, not only the visual design.

Analogy: before opening a full restaurant, a cook in Hyderabad sells biryani from home to office workers for two weeks. If people keep ordering, the idea is worth growing. That home kitchen is the MVP.

COMMON MISTAKE

Mistake 1: Calling a paper sketch an MVP. **Fix:** A sketch is a prototype. An MVP must **work** and be used by **real users**.

Mistake 2: Thinking MVP means a low-quality or broken product. **Fix:** It is small but **viable**; it must genuinely solve the main problem.

اردو میں سمجھیں

ایم وی پی (Minimum Viable Product) کسی پراڈکٹ کا سب سے سادہ مگر کام کرنے والا ورژن ہے جس میں صرف ضروری خصوصیات ہوتی ہیں۔ "مینیم" کا مطلب ہے صرف ضروری چیزیں، اور "وائیبل" کا مطلب ہے کہ وہ اصل مسئلہ حل کرنے کے قابل ہو۔ یہ حتمی پراڈکٹ نہیں بلکہ یہ جانچنے کا ذریعہ ہے کہ کیا لوگ واقعی اسے استعمال کریں گے، جیسے کینٹین کے لیے ایک سادہ گوگل فارم۔

EXAM TIP

Typical questions: "What is an MVP? Explain the words Minimum and Viable" and "Give an example of an MVP." Write the full form, the definition (simplest working version, only most important features, test with real users), explain both words, state that it is neither the final product nor only a drawing, and give the canteen Google Form example. Mention the key question: "Will people actually use this solution?"

CHECK YOURSELF

- Write the full form of MVP.
- What does "Viable" mean in MVP?
- What question does an MVP answer?

Answers: 1. Minimum Viable Product. 2. Usable enough to actually solve the main problem. 3. "Will people actually use this solution?"

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An MVP is:

- The simplest working version that can test the riskiest assumption
- A paper sketch only
- The full app with every feature
- A logo

MCQ 2. Working means:

- Real users can get the core value (even if ugly/manual)
- It compiles Hello World
- It has 40 screens
- It has AI always

MCQ 3. This is ★: contrast with prototype in the next lecture, but here emphasise:

- Learning from a real offer
- Colours
- NAND
- OSI

MCQ 4. A WhatsApp group that actually takes canteen orders is:

- Closer to MVP than a Figma only
- Not digital
- A stack
- A pie

MCQ 5. Building extra features first is:

- The usual MVP failure
- Required
- Agile gold always
- HCI gold always

MCQ 6. The goal is to learn:

- Whether people use/pay, cheaply
- Whether the CEO likes purple
- Whether Big O is n³
- Whether ER is 3NF

Extra short questions

- Define MVP from the book.
- What "viable" means.
- What "minimum" means.
- One example.

Extra long question

- Design an MVP for "notes exchange" that you could run next week without an app store. List in/out features and the learning question. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Minimum Viable Product: simplest working version with only essential features, used to learn from real users.
- Someone can complete the core job (order food, book notes).
- Strip extras (reviews, AI, dark mode) until the core is tested.
- Google Form + JazzCash + pickup window, before an app.

Long

- In: list of notes, request, pickup. Out: chat, ratings, payments maybe later. Question: will 20 students actually exchange? How you measure.

6.9 Difference between Prototype and MVP

LEARN IT

Prototype and MVP are **related, but not the same**. A **prototype** is mainly used to **show and test the design** of an idea. An **MVP** is used to **test real use and market demand**. *Market demand* means whether enough people want the product and will use (or pay for) it.

Usually a prototype comes first and an MVP comes after it: Problem → Idea → Prototype → Feedback → MVP.

Table 6.6: Prototype and MVP comparison

Point	Prototype	MVP
Main purpose	To show how the idea may look or work.	To test whether users will actually use the solution.
Working status	May not work; can be a sketch or model.	Must work at least in a basic way.
Users	Small group gives feedback on design.	Early real users test the product in daily life.
Cost	Very low cost.	Low cost but may need some basic development.
Example	Paper screens for a canteen order system.	Google Form used for real canteen orders for three days.

REMEMBER IT

Key takeaway

Prototype = "Does it look right and make sense?"

MVP = "Will people **actually use it** and find value in it?"

Memory hook: Prototype → Picture of the idea; MVP → Market test of the idea.

WORKED EXAMPLE

Worked example: **classify each item**. Decide whether each is a prototype or an MVP and give the reason.

1. Hand-drawn screens of a tuition-finder app shown to 6 friends. → **Prototype**: it does not work; it tests design.

2. A WhatsApp broadcast group that really sends van arrival times to parents of one route for a week. → **MVP**: it works and real users use it daily.

3. Clickable PowerPoint screens of a notes organizer. → **Prototype** (mid-fidelity): links work, but nobody uses it for real notes.

4. A shared Google Drive folder per subject that a class actually uses before the monthly test. → **MVP**: real use in daily life.

Rule used: **Does it work, and is it used by real users in real life?** If yes → MVP. If it only shows the design → prototype.

COMMON MISTAKE

Mistake: Thinking "high-fidelity prototype" and "MVP" are the same because both look good.

Fix: The difference is **purpose and real use**, not appearance. A beautiful Figma design that nobody uses for real orders is still a prototype; a plain Google Form taking real orders is an MVP.

اردو میں سمجھیں

پروٹوٹائپ اور ایم وی بی آپس میں جڑے ہیں مگر ایک جیسے نہیں۔ پروٹوٹائپ خیال کا ڈیزائن دکھاتا اور آزماتا ہے اور ضروری نہیں کہ کام کرے، جبکہ ایم وی بی کم از کم بنیادی طور پر کام کرتا ہے اور اصل صارفین روزمرہ زندگی میں اسے استعمال کرتے ہیں۔ پروٹوٹائپ پوچھتا ہے "کیا یہ ٹھیک لگتا ہے؟" اور ایم وی بی پوچھتا ہے "کیا لوگ واقعی اسے استعمال کریں گے؟"

CHECK YOURSELF

1. Which one must work at least in a basic way?

2. Give the source's example of a prototype and of an MVP for the canteen.

3. Which question does a prototype answer?

Answers: 1. The MVP. 2. Prototype: paper screens for a canteen order system. MVP: a Google Form used for real canteen orders for three days. 3. "Does it look right and make sense?"

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A prototype mainly:

a. Shows/tests the design

b. Takes real payments at scale always

c. Replaces the company

d. Is the beachhead

MCQ 2. An MVP mainly:

a. Delivers the core working offer to real users to learn

b. Is always paper

c. Is always high-fi Figma only

d. Has every feature

MCQ 3. You can have a prototype that is:

a. Not working software

b. Already the full product

c. A DBMS

d. An OSI stack

MCQ 4. You should not call a clickable mock the:

a. MVP (if nobody can actually complete the job)

b. Prototype

c. Wireframe

d. Test

MCQ 5. Order often is:

a. Need → prototype → MVP → later product

b. MVP → ignore users → prototype

c. IPO → problem

d. GPU → problem

MCQ 6. Exam 5-mark: table of:

a. Purpose, working?, users, fidelity, example

b. Only definitions swapped

c. Only careers

d. Only Python

Extra short questions

1. Four differences prototype vs MVP.

2. Can an MVP look ugly?

3. Can a prototype be digital?

4. One sentence you should memorise.

Extra long question

1. Table + one paragraph: for the canteen idea, what is the prototype and what is the MVP. Do not mix them.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Purpose design vs learning from a real offer; may not work vs must work; testers vs customers; cheap fake vs minimum real.

2. Yes — viability ≠ beauty.

3. Yes (Figma) — still not MVP if it doesn't deliver the job.

4. Prototype answers "do they understand it?"; MVP answers "do they use it?".

Long

1. Prototype: paper/Figma order flow. MVP: form that cooks actually receive and food is collected. Learning: % of orders picked up.

6.10 Identifying the Riskiest Assumption

LEARN IT

Every business idea is based on **assumptions**. An **assumption** is something we **believe to be true, but have not tested yet**. The **riskiest assumption** is the belief that can make the **entire business fail** if it turns out to be wrong. Entrepreneurs should **identify and test the riskiest assumption early**, because it **saves time and money**. If it is wrong, you find out before building everything else.

Table 6.7: Testing risky assumptions

Business Idea	Possible Risky Assumption	How to Test It (MVP)
Online tuition finder	Students will pay for online tutoring.	Ask 20 students and offer a trial class to see if they sign up.
Canteen pre-order form	Students will order snacks before break.	Test a Google Form for one week in real time.
Ajrak online catalogue	Customers will place orders through WhatsApp.	Share catalogue with 30 customers and record actual orders.
College van update system	Parents and students will check van updates daily.	Create a trial WhatsApp broadcast group for one route.

Notice that every test measures **what people actually do** (sign up, order, check), not just what they say.

WORKED EXAMPLE

Worked example: finding the riskiest assumption. Idea: a home-tutor booking service for Grade IX–X students in Sukkur.

Step 1, list assumptions:

1. Parents want home tutors for their children.
2. Good tutors in Sukkur are willing to join.
3. Parents will **pay a booking fee** through our service instead of finding tutors through relatives.
4. Parents will like our logo.

Step 2, ask of each: "If this is wrong, does the whole business fail?" Logo (4): no, easily changed. Parents wanting tutors (1): very likely true; many already hire tutors. Tutors joining (2): important, but easy to check by phoning a few tutors. Paying a booking fee (3): if parents refuse to pay, the business earns nothing, so **this is the riskiest assumption**.

Step 3, design a small MVP test: post the offer in 3 parent WhatsApp groups for one week, offer a first booking at a small fee, and **count how many actually pay**.

REMEMBER IT

Ask: "What would kill this idea?" The answer is usually the riskiest assumption. Test it **first**, cheaply, with real behaviour.

COMMON MISTAKE

Mistake: Testing easy, safe assumptions (colours, names) first and leaving the dangerous one for later.

Fix: Test the assumption that could make the whole business fail first. Also, do not trust only "Yes, I would use it". Measure actual sign-ups or orders.

اردو میں سمجھیں

پر کاروباری خیال کچھ مفروضوں (Assumptions) پر قائم ہوتا ہے، یعنی وہ باتیں جنہیں ہم سچ سمجھتے ہیں مگر ابھی آزمایا نہیں۔ سب سے خطرناک مفروضہ (Riskiest Assumption) وہ ہے جو غلط نکلے تو پورا کاروبار ناکام ہو جائے۔ اسے شروع میں ہی چھوٹے ایم وی سے آزمانا چاہیے تاکہ وقت اور پیسہ بچ سکے۔

CHECK YOURSELF

1. Define assumption.
2. What is the risky assumption for the Ajrak online catalogue, and how is it tested?
3. Why test the riskiest assumption early?

Answers: 1. Something we believe to be true but have not tested yet. 2. Customers will place orders through WhatsApp; share the catalogue with 30 customers and record actual orders. 3. Because if it is wrong the whole business fails, so testing it early saves time and money.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An IDE is:

- a. One app to write, run and debug code
- b. A printer
- c. A sort
- d. A cable

MCQ 2. VS Code is:

- a. A popular editor/IDE
- b. A DBMS
- c. An OSI layer
- d. A gate

MCQ 3. The terminal/run button is for:

- a. Executing the program
- b. Drawing pie charts only
- c. Sending TCP SYN only
- d. K-maps

MCQ 4. Syntax highlighting helps you:

- a. See keywords and mistakes
- b. Sort faster
- c. Encrypt disks
- d. Route packets

MCQ 5. A file explorer in VS Code shows:

- a. Project files
- b. OSI layer 1
- c. NAND groups
- d. Beachhead users

MCQ 6. Debugging in an IDE uses:

- a. Breakpoints and variable watch
- b. Only bubble sort
- c. Only pie charts
- d. Only Agile stickers

Extra short questions

1. Define IDE.
2. Name four VS Code areas.
3. Why not use Notepad only?
4. What is an extension?

Extra long question

1. Describe how you would create, run and debug a first Python file in VS Code. Include two interface elements from the notes.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Integrated Development Environment: editor + run + debug + files in one place.
2. Activity bar/sidebar (files), editor, terminal, status bar (and extensions).
3. No easy run, no highlighting, no debugger.
4. An add-on (Python plugin) that teaches VS Code a language.

Long

1. New file .py, type print, Run Python, read terminal. Mention top menu, explorer, terminal panel. Breakpoint on a wrong variable.

6.11 Developing an MVP

LEARN IT

To develop an MVP, the team must **select only the essential features**. Extra features should be avoided at the beginning. A common mistake is **trying to build everything at once**. This makes the product **difficult, costly, and slow**.
An **MVP plan** should clearly explain: the **problem, target users, main feature, basic design, estimated cost, marketing method, feedback method, and improvement plan**.

Table 6.8: MVP planning checklist

MVP Element	Question to Ask	Example Answer
Problem	What problem are we solving?	Students wait too long at canteen.
Target users	Who will use it first?	Grade XII students in one college.
Main feature	What is the ONE feature that solves it?	Pre-order snacks before break.
Basic design	What steps are needed?	Menu, name, class, order time.
Cost	What free/low-cost tools to use?	Google Form or printed slips.
Marketing	How will early users hear about it?	WhatsApp message to class group.
Feedback	How will users respond?	Short feedback form after 3 days.

The eighth element, the **improvement plan**, answers "What will we change after feedback?" (you will see it in the case study in 6.12).

WORKED EXAMPLE

Worked example: filling the checklist for a new idea. Idea: a college notice reminder for parents in Hyderabad (from Table 6.1).

MVP Element	Answer
Problem	Parents miss college notices (fee dates, PTMs, holidays).
Target users	Parents of first-year (Class XI) students of one college.
Main feature	Send each notice to parents' phones on the same day.
Basic design	Photo of notice + 2-line summary in Urdu and Sindhi + date.
Cost	Free: WhatsApp broadcast list from the college office phone.
Marketing	Students give a printed slip to parents with the number to save.
Feedback	After 2 weeks, a 3-question voice-note or phone survey of 20 parents.
Improvement plan	If parents say notices come too late, send a reminder 1 day before each date.

Notice: only **one** main feature, a **free** tool, and a clear way to collect feedback.

REMEMBER IT

Mnemonic for the 8 elements: "**People Try My Bakery; Cheap Muffins Find Improvement**": Problem, Target users, Main feature, Basic design, Cost, Marketing, Feedback, Improvement plan.

COMMON MISTAKE

Mistake: Writing a list of ten "main features".
Fix: The checklist asks for the **ONE** feature that solves the problem. Everything else waits until the MVP proves people want it.

اردو میں سمجھیں

ایم وی پی بنانے وقت صرف ضروری خصوصیات چنیں؛ سب کچھ ایک ساتھ بنانے سے کام مشکل، مہنگا اور سست ہو جاتا ہے۔ ایم وی پی منصوبے میں مسئلہ، پہلے صارفین، ایک بنیادی خصوصیت، سادہ ڈیزائن، کم خرچ ٹولز، تشریح کا طریقہ، رائے لینے کا طریقہ اور بہتری کا منصوبہ واضح ہونا چاہیے۔

CHECK YOURSELF

1. Why is building everything at once a mistake?
2. List the eight elements of an MVP plan.
3. In Table 6.8, what is the marketing method?

Answers: 1. It makes the product difficult, costly and slow. 2. Problem, target users, main feature, basic design, estimated cost, marketing method, feedback method, improvement plan. 3. A WhatsApp message to the class group.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Developing an MVP means:
a. Choosing only essential features and a way to deliver them
b. Hiring 40 engineers first
c. Designing 12 themes
d. Writing the TOS of a unicorn

MCQ 2. A feature is essential if:
a. The core job fails without it
b. A competitor has it
c. It is AI
d. It is animated

MCQ 3. Manual-behind-the-scenes is allowed if:
a. The user still gets the job done (concierge MVP)
b. You lie that it is fully automatic forever
c. You skip users
d. You skip ethics

MCQ 4. Time-box the build to:
a. Days/weeks, not years
b. A decade
c. Until perfect
d. Until the logo shines

MCQ 5. You still need:
a. A way to measure the learning
b. No metric
c. Only likes
d. Only press

MCQ 6. Extra features before the core works are:
a. Waste
b. Professionalism
c. Required by BIEK
d. HCI law

Extra short questions

1. Steps to develop an MVP from the notes.
2. Concierge MVP meaning.
3. Tools a student can use.
4. One ethics line.

Extra long question

1. Turn the notes-exchange idea into an MVP plan: features in/out, tools, 7-day schedule, metric, kill-criteria.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Core job, essential features, drop extras, pick tools, build, measure.
2. You perform the service by hand (WhatsApp) while pretending the "product" exists — to test demand.
3. Forms, sheets, WhatsApp, JazzCash, a landing page.
4. If you take money, deliver or refund; don't ghost testers.

Long

1. In: list+request. Out: chat/AI. Tools: sheet+group. Metric: 10 completed exchanges. Kill if <2. Schedule table.

15

6.12 Case Study: MVP for a Canteen Pre-Order System

LEARN IT

Problem: In a college, students wait in long lines at the canteen. Sometimes snacks finish before students reach the counter. A group wants to test a canteen pre-order idea.
Goal: Their aim is **NOT** to create a complete app immediately. Their aim is to test **whether students will place orders before break** and **whether the canteen can manage these orders**.

The approach

- 1. The team creates a **paper prototype** showing three steps: **select item, enter name, collect order**.
- 2. **Feedback** from the prototype suggests the **menu should be short** and **payment should be at collection time**.
- 3. For the actual MVP, the team uses a **Google Form**. Students **select one of five items**.
- 4. The canteen prepares these pre-orders. This MVP is tested for **three days only** to learn quickly.



Table 6.9: MVP plan for canteen pre-order system

MVP Element	Decision
Features	Menu list, student name, class, item, and quantity.
Cost & Tools	Free Google Form or printed order slips.
Marketing	Class announcement and WhatsApp group message.
Testing period	Three days.
Feedback method	Ask students if they saved time and would use it again.
Improvement	Keep only 5 items; close orders 20 minutes before break.

Result: Students liked saving time, but **canteen staff found too many items difficult**. The team improved the MVP by **keeping only five items** and creating a **separate collection line**. This improvement is based on real feedback.

WORKED EXAMPLE

Worked example: trace the case study through the chapter's ideas.

Chapter idea	Where it appears in the case study
Real problem (6.3)	Long queues; snacks finish before students reach the counter.
Low-fidelity prototype (6.5)	Paper screens: select item, enter name, collect order.
Iteration (6.6)	Feedback led to a short menu and payment at collection.
MVP (6.8)	Google Form with one of five items, used for real orders.
Riskiest assumption (6.10)	Students will order before break, and the canteen can manage the orders.
Beachhead market (6.14)	One college canteen during break.

Why "close orders 20 minutes before break"? Staff need time to prepare. If orders arrive at the last minute, the pre-order line becomes as slow as the normal line, and the main benefit disappears.

REMEMBER IT

Remember the case study as **"5 items, 3 days, 20 minutes"**: five menu items, a three-day test, orders closing twenty minutes before break.

COMMON MISTAKE

Mistake: Thinking only the students' opinion matters.

Fix: The case study tested **two things**: whether students will order **and** whether the canteen can manage the orders. The **staff's feedback** (too many items) caused the key improvement.

اردو میں سمجھیں

ایک کالج میں طلبہ کینٹین کی لمبی قطاروں میں انتظار کرتے تھے۔ ٹیم نے فوراً آپ بنانے کے بجائے پہلے کاغذی پروٹوٹائپ بنایا، پھر تین دن کے لیے گوگل فارم کو ایم وی پی کے طور پر آزمایا جس میں پانچ اشیاء تھیں۔ طلبہ کو وقت کی بچت پسند آئی مگر عملے کو زیادہ اشیاء مشکل لگیں، اس لیے صرف پانچ اشیاء رکھے گئیں، الگ قطار بنائی گئی اور بریک سے بیس منٹ پہلے آرڈر بند کیے گئے۔

CHECK YOURSELF

- 1. Which tool was used for the canteen MVP, and for how long was it tested?
- 2. What two things did the team want to test?
- 3. What two improvements were made after the result?

Answers: 1. A Google Form, tested for three days. 2. Whether students will place orders before break, and whether the canteen can manage these orders. 3. Keeping only five items and creating a separate collection line (orders also close 20 minutes before break).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The canteen case is there to:

- a. Show a full MVP story on a local problem
- b. Teach NAND
- c. Teach OSI
- d. Teach ER only

MCQ 2. The problem is:

- a. Queues / food running out
- b. GPUs
- c. Primary keys
- d. Figma auto-layout

MCQ 3. A sensible MVP is:

- a. Pre-order a few items for pickup, not a full restaurant OS
- b. Drone delivery in week 1
- c. AI chefs
- d. Blockchain loyalty

MCQ 4. The kitchen is a:

- a. User/constraint you must test
- b. A pie
- c. A stack
- d. An OSI hub

MCQ 5. If nobody pre-orders, the idea:

- a. Failed the risky assumption — good you learned cheap
- b. Needs more gradients
- c. Needs a CEO
- d. Needs C++

MCQ 6. Write the case as:

- a. Problem, users, assumption, MVP, test, result, next
- b. Only the logo
- c. Only careers
- d. Only Python lists

Extra short questions

- 1. Retell the case in 5 bullets.
- 2. Two user groups with different needs.
- 3. A metric.
- 4. A next step if it works.

Extra long question

- 1. Write the canteen case as a 10-mark structured answer with a tiny flow diagram (order → kitchen → pickup).

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- 1. Queue; students+staff+cooks; assume pre-order helps; form/WhatsApp MVP; measure wait/orders; iterate.
- 2. Students (speed); kitchen (simple tickets, not 40 modifiers).
- 3. Orders completed; average wait; food wasted.
- 4. Add payment; then maybe an app.

Long

- 1. Headings as above. Diagram three boxes. One risk: kitchen overwhelmed at 10:55. Mitigation: cap orders. Ethics: allergies.

6.13 Testing an MVP

LEARN IT

MVP testing means giving the basic working version to **real users** and **studying their response**. The team should collect **both numbers and comments**.

- **Numbers** (quantitative data) show how many users tried the MVP and how many may use it again.
- **Comments** (qualitative data) explain what users liked, disliked, or found confusing.

Testing should be **planned before the MVP is launched**. Decide:

1. **How many users** will test it.
2. **How long** the test will continue.
3. **What information** will be collected.

Table 6.10: Feedback during MVP testing

Type of Feedback	Question	Example Result
Number-based	How many users tried it?	40 students used the form.
Number-based	How many would use it again?	30 out of 40 said yes.
Comment-based	What was confusing?	Did not know order closing time.
Observation	Where did users face difficulty?	Forgot to enter class name.

Observation means the team watches users and notes difficulties themselves, even ones users do not mention.

WORKED EXAMPLE

Worked example: studying the results in Table 6.10.

1. **Repeat-use rate** = (users who would use it again + users who tried it) × 100 = (30 + 40) × 100 = **75%**.
2. **Did not want to use again** = 40 – 30 = **10 students** = (10 + 40) × 100 = **25%**.
3. **Comment**: "Did not know order closing time" → **Fix**: write "Orders close 20 minutes before break" at the top of the form and in the WhatsApp message.
4. **Observation**: "Forgot to enter class name" → **Fix**: make the Class field **required** in the Google Form so it cannot be submitted empty.
5. **Decide what to fix first**: the closing-time problem stops people from ordering at all, so fix it first; the class-name problem only makes collection slower.

Three out of four users would come back, which is a promising sign; fixing the two problems could raise that number further.

REMEMBER IT

Data skill link. Feedback is useful only when it is studied: **Count** the responses → **Look** for repeated problems → **Decide** which improvement comes first. Remember "**C-L-D**": Count, Look, Decide."

COMMON MISTAKE

Mistake: Launching the MVP first and deciding later what to measure.

Fix: Plan the number of users, the test length and the questions **before** launch. Otherwise you may forget to record important data (for example, how many people opened the form but did not submit).

اردو میں سمجھیں

ایم وی پی کی جانچ کا مطلب ہے کہ بنیادی کام کرنے والا ورژن اصل صارفین کو دیا جائے اور ان کے ردعمل کا مطالعہ کیا جائے۔ اعداد بتاتے ہیں کتنے لوگوں نے استعمال کیا اور کتنے دوبارہ کریں گے، جبکہ تبصرے بتاتے ہیں کیا پسند آیا اور کیا الجھن تھی۔ جانچ کی منصوبہ بندی پہلے سے کریں، جوابات گنتیں، بار بار آنے والے مسائل تلاش کریں اور پہلے سب سے اہم بہتری کریں۔

CHECK YOURSELF

1. Name the three types of feedback in Table 6.10.
2. If 50 people tried an MVP and 35 would use it again, what is the repeat-use rate?
3. Name the three things to decide before launching an MVP test.

Answers: 1. Number-based, comment-based, observation. 2. (35 ÷ 50) × 100 = 70%. 3. How many users will test it, how long the test will continue, and what information will be collected.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Testing an MVP means:
a. Real users, real core task, collect numbers and comments
b. Only your friends saying "cool logo"
c. Only the teacher's mark
d. Only a unit test of Python

MCQ 2. Vanity metrics are:
a. Likes with no usage
b. Completed jobs
c. Repeat orders
d. Time to complete

MCQ 3. You want both:
a. Numbers and quotes
b. Only numbers
c. Only vibes
d. Only press

MCQ 4. A failed test is useful when:
a. You write what you will change or stop
b. You hide it
c. You add features at random
d. You buy ads

MCQ 5. Sample of 5–20 users is:
a. OK for class MVPs if honest
b. A national census
c. Useless always
d. A DoS

MCQ 6. Don't help the user in the test if you are measuring:
a. Whether the offer is understandable/usable
b. Kindness in general life
c. SQL skill
d. NAND skill

Extra short questions

1. What to measure (book + good practice).
2. How to collect.
3. Bias: testing only your friends.
4. Then what?

Extra long question

1. Write a test plan for the canteen MVP: n, tasks, 3 metrics, 3 questions, pass/fail thresholds, ethics (food safety).

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Did they finish? Time? Would they repeat? Pay? Quotes of confusion.
2. Tally sheet + 3 interview questions after.
3. They are too nice — include one stranger in the line.
4. Iterate the MVP (or the assumption).

Long

1. n=15 lunch buyers. Task: order and collect. Metrics: % complete, wait, errors. Questions: would you do this tomorrow? Thresholds: 70% complete. Don't poison anyone; allergens.

6.14 Beachhead Market ★ Golden

LEARN IT

A **beachhead market** is a **small and focused group of first users**. These users have a **clear need** and are **likely to try the product early**.

Instead of trying to serve everyone, entrepreneurs **first focus on one small group**. This helps them **test the MVP properly** and **improve it before expanding**.

The word comes from the army: a beachhead is the small piece of beach soldiers capture first when they land; from there they move inland. In business, your beachhead is the first small group you "win".


Characteristics of a good beachhead market

It should be **specific and narrowly defined**.

It should be **reachable** by the startup team.

The users should have a **strong, immediate need** for the solution.

For example, targeting **"all students in Pakistan"** is too broad for a new study app. **"Grade XII students preparing for board exams in one college"** is much more focused and easier to reach.



Start with the small inner circle (beachhead), learn and improve, then expand outward.

Table 6.11: Choosing a focused beachhead market

Business Idea	Weak First Market	Better Beachhead Market
Study app	All students in Pakistan.	Grade XII students preparing for exams in one college.
Canteen pre-order	All canteens in the city.	One college canteen during lunch break.
Ajrak catalogue	All online shoppers.	Existing customers of one local shop.
Van update system	All transport users.	Students and parents of ONE specific college van route.

Choosing a small first market **does not mean the idea will remain small forever**. After learning from this group, the idea can be improved and expanded, even globally.

WORKED EXAMPLE

Worked example: test a proposed beachhead against the three characteristics. Idea: an app that reminds farmers about irrigation water turns (warabandi).

Proposed market	Specific?	Reachable?	Strong, immediate need?	Verdict
All farmers in Sindh	No	No (millions of people, many districts)	Varies	Weak
Farmers on one watercourse near Badin whose sons/daughters study in the team's college	Yes	Yes (through classmates)	Yes (missing a turn damages crops)	Good beachhead

Expansion path: one watercourse → nearby watercourses → the whole district → other districts.

REMEMBER IT

Remember S-R-U: Specific, Reachable, Urgent need. If you cannot meet your first users within a week, your market is too big.

COMMON MISTAKE

Mistake: Thinking a bigger first market means more success ("everyone can use my app").

Fix: A broad market is hard to reach and hard to learn from. Win a small group first, learn, improve, then expand.

اردو میں سمجھیں

بیج ہیڈ مارکیٹ (Beachhead Market) پہلے صارفین کا ایک چھوٹا اور مخصوص گروہ ہے جسے حل کی واضح اور فوری ضرورت ہو اور جو پراکتک جلد آزمائے پر تیار ہو۔ سب کو ایک ساتھ خدمت دینے کے بجائے پہلے ایک چھوٹے گروہ پر توجہ دیں، جیسے "پاکستان کے تمام طلبہ" کے بجائے "ایک کالج کے باریوں جماعت کے طلبہ"۔ وہاں سے سیکھ کر خیال کو بعد میں پھیلایا جا سکتا ہے۔

EXAM TIP

Asked as "Define beachhead market and give its characteristics" or "Suggest a beachhead market for ...". Write the definition (small, focused group of first users with a clear need, likely to try early), the three characteristics (specific, reachable, strong immediate need), one weak-versus-better pair from Table 6.11, and the line that a small first market does not mean the idea stays small.

CHECK YOURSELF

- Give the three characteristics of a good beachhead market.
- What is the better beachhead market for the van update system?
- Does choosing a small first market mean the business will stay small?

Answers: 1. Specific and narrowly defined; reachable by the team; users have a strong, immediate need. 2. Students and parents of ONE specific college van route. 3. No. After learning from the first group, the idea can be improved and expanded.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A beachhead market is: a. A small focused first group of users b. The whole country on day 1 c. Random Twitter d. Every age/city/income at once	MCQ 2. You pick them because: a. They feel the pain strongly and you can reach them b. They are richest always c. They are abroad always d. They hate the product	MCQ 3. This is ★: define, why small, one example. a. The recipe b. Only the D-Day story without CS c. Only Python d. Only ER	MCQ 4. XI CS students in one college as first users of a notes app is a: a. Beachhead b. Global TAM c. OSI layer d. NAND net	MCQ 5. After the beachhead works you: a. Expand to the next similar group b. Immediately advertise on TV nationwide c. Quit d. Rewrite in assembly	MCQ 6. A beachhead that is too broad is: a. Hard to test and to talk to b. Ideal c. Required d. A median
---	--	---	---	---	---

Extra short questions

- Define beachhead market.
- Why not "all Pakistan" first?
- Example from college.
- How it links to MVP.

Extra long question

- For a canteen pre-order, choose a beachhead (who, where, when), why they are best, and who you refuse at first. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

- Small, focused first users with a clear need, likely to try.
- You cannot learn; message becomes vague; cost explodes.
- Hostel Block B, not all Karachi youth.
- The MVP is aimed at that beachhead, not every imaginary user.

Long

- XI 10:00 break, one stall. They queue worst. Refuse staff catering and evening shift until the kitchen process works. Success: 20 repeating students.

LEARN IT

You will work in **groups** and complete one small entrepreneurship project. The project should be **simple, local, and possible in the classroom**.

The purpose is to practise the **complete journey**: problem → prototype → feedback → MVP plan → risky assumption → beachhead market.

Suggested project ideas: homework and test reminder system, college notice organizer, canteen pre-order system, small shop WhatsApp catalogue, college van update system, lost and found item reporting system, study notes organizer.

WORKED EXAMPLE	
Worked example: a completed project sheet (Lost and Found system).	
Item	Answer
Problem statement	Students of our college in Myanmar have items (jottings, calculators, CD cards) and rarely get them back because there is no central place to report them.
Target users	Students and staff of our college.
Business idea	A Lost and Found WhatsApp group plus a Google Form to report lost or found items.
Low-fidelity prototype	Two paper screens: "Report lost item" (item, colour, place, phone of class reg) and "Found items list" with sketches.
Feedback from users	6 of 8 teachers asked for photos, I did not want their own phone number shown.
Improvement made	Added a photo upload, replaced personal numbers with "collected from the library desk".
Setup plan	Google Form + new WhatsApp group run by two volunteers, less, tested for two weeks.
Initial assumption	Students who find items will take the trouble to report them.
How to test it	Count how many "found" reports arrive in two weeks compared with "lost" reports.
Beachhead market	Grade XI students of our college.
Marketing method	Announcement in morning assembly, a poster at the library and a message in each class group.

A rubric is a marking guide that describes what excellent, satisfactory and weak work looks like for each part of a project

REMEMBER IT
Use the rubric **before** you submit: read your project sheet row by row and ask, "Is this Excellent yet?" For "Feedback & Fixes", always write **which** feedback caused **which** change.

Use the rubric **before** you submit: read your project sheet row by row and ask, "Is this Excellent yet?" For "Feedback & Fixes", always write **which** feedback caused **which** change.

Mistake: Writing an MVP plan that lists every feature of the dream app. The rubric marks this as "Confused with the final product".

آرڈو میں منجملہ:

ظفر گروہوں میں ایک جھولہ مقامی اور آسان منصوبہ سمکارا کرچے ہیں جس میں مسئلے سے پروانلابہ رانی ایم وی یں منصوبہ، سب سے خطرناک مفروضہ اور بیچ بیلہ مارکیٹ کو پورا سفر شامل ہوتا ہے منصوبہ جو چالنجے کے لیے (Robust) استعمال ہوتا ہے جو مسئلے کی بجائ، پروانلابہ رانی و برتری اور ایم وی میں منصوبہ کو بہترین ایشی نکل یا برتری کی ضرورت کے درجوں میں رکھتا ہے۔

1. Name four suggested project ideas.

Privacy: people's personal information belongs to them.

Truthfulness: report results honestly; do not make up numbers or hide bad feedback.

Fairness: treat all users equally.

You should **not** collect unnecessary personal information or share phone numbers or photos without permission.

A good digital solution should consider users who have **weak internet**, **limited devices**, or **language difficulty**. A design with **large buttons**, **simple Urdu/Sindhi instructions**, and **low data usage** helps ensure **equal access**. Equity means making sure everyone, including people with fewer resources, can use the solution.

Mistake: "More data is always better, so let's collect everything."

Fix: Collect only what you need to answer your test questions. Extra personal data creates risk for users and gives you no benefit.

Extra board practice
These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

1. Write a one-page project proposal that

2. Permission for

3. You can test this week with people you can walk to.
4. Secretly recording students in the canteen.

Long

1. e.g. lab-equipment booking. Headings match rubric. Ethics: no shame list of late students on a public wall. Metric: 10 bookings honoured.

Entrepreneurship in the Digital Age

16 single-page lessons · 5 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- **Entrepreneur:** a person who identifies a problem, thinks of a solution, and turns it into a product or service; observes people, takes calculated risks, improves step by step.
- **Entrepreneurship:** the process of planning, starting, testing and improving a business idea until it becomes useful (Problem → Solution → Product).
- **Digital age:** entrepreneurs use accessible digital tools (social media, forms, websites, WhatsApp, digital payments) to start and test ideas quickly with low investment; often no coding is needed.
- A digital idea must solve a **real problem for real users**, not just sound modern (Table 6.1 examples: notices, embroidery shop, test dates, canteen queues).
- **Business ideas** come from observing daily life and talking directly to users: Observe → Ask Users → Select One Problem → Suggest Solution → Test Early. Start with a small, clear problem.
- **Prototype:** an early model used to show and test the design of an idea; not the final product; makes the idea visible, finds mistakes early, saves time and money.
- **Fidelity** is how close a prototype is to the final product: Low (paper), Mid (PowerPoint/Canva/Figma, tests navigation), High (realistic, Figma/HTML, only after the idea is tested).
- **Development cycle:** Design → Build → Test → Iterate, repeated (iteration). Feedback is crucial; a prototype fails only if useful feedback is ignored.
- **MVP:** the simplest working version with only essential features (Minimum) that still solves the main problem (Viable); it tests real use and market demand.
- **Prototype vs MVP:** prototype asks "Does it look right?"; MVP asks "Will people actually use it?" A prototype may not work; an MVP must.
- **Riskiest assumption:** the untested belief that, if wrong, will make the business fail; test it early with real behaviour.
- **MVP plan:** problem, target users, ONE main feature, basic design, cost, marketing, feedback, improvement plan. Do not build everything at once.
- **Canteen case study:** paper prototype → Google Form MVP with 5 items for 3 days → staff found too many items hard → kept 5 items, separate line, orders close 20 minutes before break.
- **MVP testing:** plan users, duration and data in advance; collect numbers (40 tried, 30 would return = 75%) and comments/observations; count, look for repeated problems, fix the most important first.
- **Beachhead market:** a small, focused, reachable group of first users with a strong, immediate need; win it first, then expand.
- **Ethics and equity:** respect privacy, truthfulness and fairness; collect no unnecessary data; share nothing without permission; design for weak internet, limited devices and Urdu/Sindhi speakers.

Key terms

Term	Meaning	اردو
Entrepreneur	A person who identifies a problem, thinks of a solution, and turns it into a product or service.	کاروباری شخص
Entrepreneurship	The process of planning, starting, testing and improving a business idea.	کاروبار کاری
Calculated risk	A risk taken after carefully thinking about the possible loss and keeping it small.	سوچا سمجھا خطرہ
Digital entrepreneurship	Using digital tools to start, test, improve and grow a business idea.	ڈیجیٹل کاروبار کاری
Business idea	A proposed product or service that solves a real problem for real users.	کاروباری خیال
Target users	The people who will use the product first.	ہدف صارفین
Prototype	An early model of a product, service, website or app made to test the idea and collect feedback.	ابتدائی نمونہ
Fidelity	How close a prototype is to the final product.	اصل سے مطابقت کا درجہ
Low-fidelity prototype	A quick, rough paper model showing the main idea and flow.	کم تفصیل والا نمونہ
Mid-fidelity prototype	A clearer model in PowerPoint, Canva or Figma showing layout and navigation without final graphics.	درمیانی تفصیل والا نمونہ
High-fidelity prototype	A detailed model close to the final product with realistic colours, buttons, data and working features.	زیادہ تفصیل والا نمونہ
Wireframe	A simple outline drawing of a screen showing where items go, without colours or pictures.	اسکرین کا خاکہ

Entrepreneurship in the Digital Age

75 marks • 1 hour 15 minutes • no notes • no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 16 and the recap. **Section A** — all 15 MCQs (1 mark). **Section B** — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define • Explain • Example • Diagram • Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. An entrepreneur is best described as a person who:
 - a. only invests money in big companies
 - b. identifies a problem and tries to turn a solution into a product or service
 - c. always works from a large office
 - d. only writes computer programs
2. In prototyping, "fidelity" means:
 - a. the cost of the prototype
 - b. the number of users
 - c. how close the prototype is to the final product
 - d. the speed of the internet
3. Which of these is a low-fidelity prototype?
 - a. Hand-drawn app screens on paper
 - b. A working demo website of an order form
 - c. Clickable screens in Figma
 - d. An app published on the Play Store
4. A mid-fidelity prototype is mainly useful for testing:
 - a. online payments
 - b. screen-to-screen navigation
 - c. market demand over three days
 - d. investor interest
5. The correct order of the prototype development cycle is:
 - a. Build, Design, Iterate, Test
 - b. Test, Build, Design, Iterate
 - c. Design, Test, Build, Iterate
 - d. Design, Build, Test, Iterate
6. Creating, testing, improving and testing a prototype again is called:
 - a. iteration
 - b. incubation
 - c. marketing
 - d. assumption
7. In MVP, the letter "V" stands for:
 - a. Visual
 - b. Valuable
 - c. Viable
 - d. Virtual
8. Which is the best MVP for a canteen pre-order idea?
 - a. A full app with login, payment, delivery tracking and discounts
 - b. A Google Form used for real orders for three days
 - c. Paper sketches shown to five friends
 - d. A colourful poster of the menu
9. A prototype mainly answers which question?
 - a. Does it look right and make sense?
 - b. Will people pay for it every month?
 - c. How big is the national market?
 - d. How much profit will we make?
10. The riskiest assumption is:
 - a. the cheapest feature to build
 - b. the colour scheme of the app
 - c. the name of the company
 - d. the belief that, if wrong, can make the whole business fail
11. Which is the best beachhead market for a new study app?
 - a. All students in Pakistan
 - b. All online shoppers
 - c. Grade XII students preparing for board exams in one college
 - d. All transport users
12. Which is NOT a characteristic of a good beachhead market?
 - a. Specific and narrowly defined
 - b. Reachable by the startup team
 - c. Users have a strong, immediate need
 - d. As large as possible from the first day
13. "30 out of 40 said they would use it again" is which type of feedback?
 - a. Number-based
 - b. Comment-based
 - c. Observation
 - d. Rubric-based
14. Which is an ethical practice when collecting user feedback?
 - a. Collect CNIC numbers of all users
 - b. Share users' phone numbers in the class group
 - c. Collect only necessary information and share nothing without permission
 - d. Change results so the idea looks better
15. To support users with weak internet and language difficulty, a design should use:
 - a. heavy videos on every screen
 - b. English-only instructions
 - c. features that need the latest phone
 - d. large buttons, simple Urdu/Sindhi instructions and low data usage

Section B — Short questions (10 × 3 = 30)

1. Define entrepreneur and entrepreneurship. How are they different?
2. What is meant by entrepreneurship in the digital age? Give two local examples that need no coding.
3. Write the five questions you should ask to find a problem in daily life.
4. Why should a student choose a small problem at the start? Give one example of a too-large and one of a suitable problem.
5. Define prototype and give three reasons why it is useful.
6. Differentiate between low-, mid- and high-fidelity prototypes, with one example of each.
7. Define MVP and explain the words "Minimum" and "Viable".
8. What is the riskiest assumption? Give the risky assumption and its test for the college van update system.
9. An MVP was tried by 40 students and 30 said they would use it again. Calculate the repeat-use rate and name two other kinds of feedback to collect.
10. State the three characteristics of a good beachhead market and give one weak and one better first market for an Ajrak catalogue.

Section C — Long questions (attempt any 3 × 10 = 30)

1. Explain the prototype development cycle with a labelled diagram. Use the ClassBuddy class activity to show what happens at each stage, and explain why negative feedback does not mean the prototype has failed.
2. Compare a prototype and an MVP under five headings (purpose, working status, users, cost, example). Use the canteen pre-order system as your example and state the key question each one answers.
3. **Plan an MVP for a college van update system** for a college in Hyderabad, where students and parents often do not know when the van will arrive. Fill in all eight elements of the MVP planning checklist, and also state the riskiest assumption, how to test it, and the beachhead market.
4. **Plan an MVP for a small Sindhi topi and Ajrak shop in Hala** that wants online customers. Describe a low-fidelity prototype, the MVP, its riskiest assumption and test, the beachhead market, the marketing method, and two ethical or equity points the shop must follow.
5. A team tested a Lost and Found MVP (Google Form + WhatsApp group) in a college of 60 Grade XII students for two weeks. 45 students tried it; 36 of them said they would use it again; 12 of the users said they did not know where to collect found items; the team observed that many reports had no photo. (a) Calculate the percentage of the class who tried it, the repeat-use rate among users, and the percentage of users confused about collection. (b) Classify each piece of feedback by type. (c) Decide which improvement to make first and justify it.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

1. **6.1 Entrepreneur and Entrepreneurship.** Answers: 1. A process (planning, starting, testing and improving a business idea). 2. Observing people and listening to their needs; taking calculated risks; improving the idea step by step. 3. A risk taken after thinking carefully about the possible loss and keeping that loss small.
2. **6.2 Entrepreneurship in the Digital Age.** Answers: 1. Any four of: mobile phones, social media, websites, online forms, digital payments, maps, videos, simple apps. 2. Because a small idea can be tested quickly and cheaply, so if users do not like it the team can change it before spending too much money. 3. Selling handmade cards through Instagram, or a WhatsApp catalogue for Ajrak.
3. **Table 6.1 Local examples of digital entrepreneurship.** Answers: 1. A simple catalogue with an order form on Facebook or WhatsApp. 2. Students and teachers. 3. Because it must solve a real problem for real users; a weak problem gives a weak business idea.
4. **6.3 From Problem to Business Idea.** Answers: 1. Observe, Ask Users, Select One Problem, Suggest Solution, Test Early. 2. It is too large and unclear; small, clear problems are easier to test and improve. 3. Notes are scattered in many places (WhatsApp, email, photocopies, class groups), not that students are careless.
5. **6.4 Prototype.** Answers: 1. No. It is an early model made to test the idea and collect feedback. 2. Any four: paper sketch, cardboard model, clickable PowerPoint, Canva design, Figma wireframe, simple website layout, sample service process chart. 3. Any two: a button is hard to find, a screen has too much text, a feature is missing.
6. **6.5 Types of Prototypes (Low, Mid, High-Fidelity).** Answers: 1. How close the prototype is to the final product. 2. Mid-fidelity (e.g. clickable screens in PowerPoint or Figma). 3. It is cheap, fast and easy to change, and it protects them from building a full app before knowing whether users need it.
7. **6.6 Prototype Development Cycle (Design, Build, Test, Iterate).** Answers: 1. The repeating process of creating, testing, improving and testing a prototype again. 2. The Test stage. 3. To make the idea visible (not to make it beautiful).
8. **6.7 Class Activity: Create a Prototype.** Answers: 1. 7 out of 10, which is 70%. 2. Today's classes, Add homework, Show reminder. 3. A 'Weekly View' button was added.
9. **6.8 Minimum Viable Product (MVP).** Answers: 1. Minimum Viable Product. 2. Usable enough to actually solve the main problem. 3. "Will people actually use this solution?"
10. **6.9 Difference between Prototype and MVP.** Answers: 1. The MVP. 2. Prototype: paper screens for a canteen order system. MVP: a Google Form used for real canteen orders for three days. 3. "Does it look right and make sense?"
11. **6.10 Identifying the Riskiest Assumption.** Answers: 1. Something we believe to be true but have not tested yet. 2. Customers will place orders through WhatsApp; share the catalogue with 30 customers and record actual orders. 3. Because if it is wrong the whole business fails, so testing it early saves time and money.
12. **6.11 Developing an MVP.** Answers: 1. It makes the product difficult, costly and slow. 2. Problem, target users, main feature, basic design, estimated cost, marketing method, feedback method, improvement plan. 3. A WhatsApp message to the class group.
13. **6.12 Case Study: MVP for a Canteen Pre-Order System.** Answers: 1. A Google Form, tested for three days. 2. Whether students will place orders before break, and whether the canteen can manage these orders. 3. Keeping only five items and creating a separate collection line (orders also close 20 minutes before break).
14. **6.13 Testing an MVP.** Answers: 1. Number-based, comment-based, observation. 2. $(35 \div 50) \times 100 = 70\%$. 3. How many users will test it, how long the test will continue, and what information will be collected.
15. **6.14 Beachhead Market.** Answers: 1. Specific and narrowly defined; reachable by the team; users have a strong, immediate need. 2. Students and parents of ONE specific college van route. 3. No. After learning from the first group, the idea can be improved and expanded.
16. **6.15 & 6.16 Complete Student Project & Ethical Use.** Answers: 1. Any four: homework and test reminder system, college notice organizer, canteen pre-order system, small shop WhatsApp catalogue, college van update system, lost and found reporting system, study notes organizer. 2. Clear, local, and important. 3. Needs Improvement (for the MVP Plan).

Answer key

Multiple choice

1. b
2. c
3. a
4. b
5. d
6. a
7. c
8. b
9. a
10. d
11. c
12. d
13. a
14. c
15. d

Short questions — model answers

1. An **entrepreneur** is a person who identifies a problem, thinks of a solution and tries to change that solution into a product or service. **Entrepreneurship** is the process of planning, starting, testing and improving a business idea, involving creativity, problem-solving, teamwork, communication and calculated risk. The entrepreneur is the person; entrepreneurship is the process.
2. It means using digital tools such as mobile phones, social media, websites, online forms, digital payments, maps, videos and simple apps to start, test, improve and grow a business idea. Examples: a student selling handmade cards through Instagram; a shopkeeper making a WhatsApp catalogue for Ajrak.
3. What problem do people face? Who faces this problem? How often does it happen? What do people currently do to solve it? Can technology help in a simple way?
4. Small, clear problems are easier to test and improve. Too large: "improving the whole education system". Suitable: "helping Grade XII students track practical file submission dates".
5. A prototype is an early model of a product, service, website or app that shows how the idea may look or work; it is not the final product and is made to test the idea and collect feedback. Useful because it makes the idea visible, helps find mistakes early (hard-to-find buttons, too much text, missing features), and saves time and money before final coding.
6. Low-fidelity: quick, rough paper model showing main idea and flow, e.g. hand-drawn homework-reminder screens. Mid-fidelity: clearer model in PowerPoint/Canva/Figma showing layout and navigation without final graphics, e.g. clickable PowerPoint screens. High-fidelity: detailed model close to the final product with realistic colours, buttons, sample data and working features, e.g. a working demo of a small order-form website.
7. An MVP (Minimum Viable Product) is the simplest working version of a product with only the most important features, used to test the idea with real users. Minimum: only the essential features, no extras. Viable: usable enough to actually solve the main problem.
8. It is the belief that can make the entire business fail if it turns out to be wrong. For the van update system: "Parents and students will check van updates daily." Test: create a trial WhatsApp broadcast group for one route.
9. Repeat-use rate = $(30 \div 40) \times 100 = 75\%$. Other feedback: comment-based (e.g. "What was confusing?") and observation (e.g. where users faced difficulty, such as forgetting to enter class name).
10. Specific and narrowly defined; reachable by the team; users have a strong, immediate need. Ajrak catalogue: weak = all online shoppers; better = existing customers of one local shop.

Long questions — model answers

1. **Prototype development cycle.** Draw four boxes in a loop: Design → Build → Test → Iterate → back to Design. Prototype development is not one-time; repeating the cycle is called iteration.
 - **Design:** understand the problem and plan what the prototype shows. ClassBuddy: interview 10 students; 7 of 10 forget tasks, so show a daily task list; reminders are needed before leaving home, so add a morning notification; students want simplicity, so use large buttons and clear labels.
 - **Build:** create the first version to make the idea visible (not beautiful). ClassBuddy: three paper screens (Today's classes, Add homework, Show reminder) joined by arrows.
 - **Test:** show it to users and observe. ClassBuddy: five classmates try "add one homework task" while the observer watches silently.
 - **Iterate:** improve from feedback. ClassBuddy: larger, centred Add Homework button; subject name and due date fields; a Weekly View button.

Negative feedback is information that shows what to fix; the prototype fails only if the team ignores useful feedback.

2. **Prototype vs MVP.** Purpose: prototype shows how the idea may look or work; MVP tests whether users will actually use it. Working status: prototype may not work (sketch or model); MVP must work at least in a basic way. Users: prototype, a small group giving design feedback; MVP, early real users in daily life. Cost: prototype very low; MVP low but may need basic development. Example: prototype = paper screens for a canteen order system; MVP = Google Form used for real canteen orders for three days. Key questions: prototype, "Does it look right and make sense?"; MVP, "Will people actually use it and find value in it?"

3. **MVP plan: college van update system (Hyderabad).**

- Problem: students and parents do not know when the van will arrive, so students wait outside for a long time or miss the van.
- Target users: students and parents on one van route.
- Main feature: the driver or a route monitor sends a short "Van left / 5 minutes away" message.
- Basic design: one WhatsApp broadcast message with route stop name, time and status; voice note option for parents who cannot read.
- Cost: free, using a WhatsApp broadcast list on the monitor's phone.
- Marketing: a message in the class WhatsApp group and a printed slip for parents with the number to save.
- Feedback: after one week, a 3-question Google Form or phone call: Did you check the updates daily? Did you wait less? Would you continue?
- Improvement plan: if messages arrive too late, send them earlier; if many parents do not read, switch to voice notes; then expand to a second route.
- Riskiest assumption: parents and students will check van updates daily. Test: trial broadcast group for one route for one week, counting how many people read or reply to messages each day.
- Beachhead market: students and parents of ONE specific college van route.

4. **MVP plan: topi and Ajrak shop in Hala.**

- Low-fidelity prototype: paper catalogue pages, one per product, with a sketch, price, size/type and "Message to order"; shown to 5 customers to see if information is clear.
- MVP: a WhatsApp Business catalogue with real photos and prices for 10–15 best-selling items; orders by chat; payment by cash on delivery or JazzCash/Easypaisa.
- Riskiest assumption: customers will actually place orders through WhatsApp. Test: share the catalogue with 30 existing customers and record actual orders for two weeks.
- Beachhead market: existing customers of this one shop (people who have bought before and whose numbers the shop already has with permission).
- Marketing: broadcast message to existing customers, a QR code at the shop counter, posts in local Facebook groups.
- Ethics: share no customer numbers or photos without permission; give truthful prices, sizes and photos. Equity: simple Urdu/Sindhi descriptions and compressed photos for low data use.
- Improvement plan: drop designs nobody orders, add more of the popular ones, then expand to customers in Hyderabad and Karachi.

5. Lost and Found MVP analysis.

- (a) Tried: $(45 \div 60) \times 100 = 75\%$ of the class. Repeat-use rate: $(36 \div 45) \times 100 = 80\%$. Confused about collection: $(12 \div 45) \times 100 = 26.7\%$ (about 27%).
- (b) "45 tried" and "36 would use again": number-based. "Did not know where to collect": comment-based (12 users said it). "Many reports had no photo": observation.
- (c) Fix the collection confusion first: it is a repeated problem (more than a quarter of users) and it stops the system's main purpose, which is returning items to owners. Add "Collect found items from the library desk" at the top of the form and pin it in the WhatsApp group. Next, make the photo field strongly encouraged (or required for found items), since photos help owners recognise items. Re-test for another week and compare the numbers.

Self-assessment: I can...

- | | |
|--|--|
| ☐ define entrepreneur and entrepreneurship and describe an entrepreneur's habits. | ☐ explain how digital tools let me start and test an idea cheaply, with local examples. |
| ☐ use the five questions and the steps of Table 6.2 to turn a problem into an idea. | ☐ define a prototype and list its benefits and possible forms. |
| ☐ compare low-, mid- and high-fidelity prototypes. | ☐ draw and explain the Design–Build–Test–Iterate cycle. |
| ☐ turn user feedback into problems and improvements, as in Table 6.5. | ☐ define an MVP and explain how it differs from a prototype. |
| ☐ identify the riskiest assumption of an idea and design a test for it. | ☐ fill in an MVP plan and analyse MVP test results with percentages. |
| ☐ choose a specific, reachable beachhead market. | ☐ collect feedback ethically and design for equal access. |

Lecture 07

Final Revision and Mock Paper

Final revision lecture — 1 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XII · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — بارہویں جماعت

01 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XII

How to use this BIEK study-guide lecture

Each PDF follows one textbook lecture from the BIEK / Sindh Computer Science notes (New Sindh Curriculum). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر کتاب کے درس کے مطابق ہے۔ کتاب کے بعد اضافی MCQs اور سوالات ہیں۔ جو اضافی کیریئر صفحات کتاب کی فہرست میں نہیں تھے وہ ہٹا دیے گئے ہیں۔

FINAL REVISION

One-page recaps and a mock paper

Use these pages in the last week before the exam. Read one recap aloud from memory, then sit the mock paper in 2 hours 30 minutes with no notes.

امتحان سے ایک ہفتہ پہلے خلاصے زبانی دہرائیں، پھر ماک پیپر بغیر نوٹس کے حل کریں۔

Chapter 1 recap — Human Computer Interaction

- HCI = study of how people and computers work together so systems are usable, useful and satisfying.
- Traditional interaction = keyboard, mouse, menus. Natural interaction = touch, voice, gesture, gaze.
- Components: user, computer, interaction (input + output + feedback) inside an environment.
- UI = how it looks and the controls. UX = how the whole experience feels. Wireframe → prototype (Figma) → test.
- Evaluate with usability tests, heuristic evaluation, A/B tests and automated checks. Golden: accessibility, HCI problems, UI vs UX, testing methods.

Chapter 2 recap — Algorithms and Data Structures

- Correctness: trace table (variable values after every step) or stepwise reasoning.
- Clarity: modularity (small named parts) and readability (names, comments, indentation).
- Efficiency: count steps, conditions, repetitions. Big O: $O(1)$ constant, $O(\log n)$ binary search, $O(n)$ linear, $O(n \log n)$ good sorts, $O(n^2)$ nested loops.
- Linear DS: array, linked list, stack (LIFO, push/pop), queue (FIFO, enqueue/dequeue). Non-linear: tree (one root, parent-child), graph (nodes + edges).
- Pick the structure from the problem: undo → stack; printer jobs → queue; hierarchy → tree; maps → graph; fast index → array.

Chapter 3 recap — Python Data Structures, Functions and Files

- list [] ordered, mutable. tuple () ordered, immutable. set {} unordered, unique. dict {k:v} key-value, mutable.
- Functions: def, parameters, return. Local vs global scope. Built-in vs user-defined.
- Files: "r" read, "w" overwrite, "a" append. Always prefer with open(...) as f so the file closes itself.
- Exceptions: try / except / else / finally. Catch specific errors (ValueError, FileNotFoundError).

Chapter 4 recap — Data and Analysis

- SQLite in Python: connect → cursor → execute → commit → close. Always commit writes.
- Pandas DataFrame = table. load CSV/Excel, `isnull`, `dropna`, `fillna`, `sort`, `filter`, `groupby`.
- Charts: bar (categories), line (trend over time), pie (parts of a whole, few slices), histogram (distribution), scatter (relationship of two variables), box (spread and outliers).
- Mean = average. Median = middle after sorting. Mode = most frequent. Range = max–min. Variance / std-dev measure spread. pandas `.std()` uses sample $n-1$.

Chapter 5 recap — AI, Security and Collaboration

- AI ⊃ Machine Learning ⊃ Deep Learning. A neuron: weighted sum + bias, then an activation function. Deep = many hidden layers.
- Secure collaboration: authentication (passwords, MFA), access control (who may do what).
- Protect data: encryption, strong passwords, 3-2-1 backup, firewall. Threats: malware, phishing, DoS/DDoS, social engineering.
- Equity: everyone can take part (devices, language, disability, bandwidth). Tools: shared docs, video, LMS, versioning.

Chapter 6 recap — Entrepreneurship in the Digital Age

- Entrepreneur = person who turns a problem into a venture, taking risk. Digital tools make testing cheap (WhatsApp, Forms, a Facebook page).
- Prototype = experimental model. Low / mid / high fidelity. Cycle: Design → Build → Test → Iterate.
- MVP = smallest product that tests the riskiest assumption with real users. Prototype ≠ MVP (MVP is used in the real market).
- Beachhead market = the first, narrow group you can win. Measure retention, not only sign-ups. Use data ethically.

Mock paper — Computer Science XII

Time: 2 hours 30 minutes | Total: 75 marks | Answer all of A and B; attempt three from C.

Section A — Multiple choice (15 × 1 = 15)

1. HCI stands for:
 - a. Human Computer Interaction
 - b. High Code Interface
 - c. Hardware Control Input
 - d. Hybrid Computing Internet
2. A wireframe is:
 - a. the final coloured UI
 - b. a simple layout sketch of screens
 - c. a compiled program
 - d. an encryption key
3. Which is $O(\log n)$?
 - a. Linear search
 - b. Nested for-loops
 - c. Binary search
 - d. Reading one array cell
4. A stack is:
 - a. FIFO
 - b. LIFO
 - c. random access only
 - d. unordered unique items
5. Which Python type is immutable?
 - a. list
 - b. dict
 - c. set
 - d. tuple
6. The file mode that overwrites an existing file is:
 - a. r
 - b. a
 - c. w
 - d. x+
7. `with open("t.txt") as f` is useful because:
 - a. it encrypts the file
 - b. it closes the file automatically
 - c. it creates a DataFrame
 - d. it skips exceptions
8. After INSERT in sqlite3 you must:
 - a. rollback always
 - b. commit
 - c. drop the table
 - d. print the cursor
9. A pie chart is a poor choice when:
 - a. you have 3 parts of a total
 - b. you have 20 tiny slices
 - c. you show percentages of a whole
 - d. you label each slice
10. pandas `df['x'].std()` uses:
 - a. population n
 - b. sample n-1
 - c. median
 - d. mode
11. Deep Learning is a subset of:
 - a. only statistics
 - b. Machine Learning
 - c. only HCI
 - d. only networking
12. MFA means:
 - a. Many File Archives
 - b. Multi-Factor Authentication
 - c. Main Firewall Access
 - d. Minimum Function API
13. A Caesar cipher is a form of:
 - a. phishing
 - b. encryption
 - c. a firewall
 - d. a prototype
14. An MVP is:
 - a. the most polished version of a product
 - b. the smallest product that tests the riskiest assumption
 - c. a paper sketch only
 - d. a full company registration
15. A printer job list is best modelled as a:
 - a. stack
 - b. queue
 - c. binary tree
 - d. set

Section B — Short questions (10 × 3 = 30)

1. Differentiate UI and UX with one example.
2. What is a trace table? Why is it better than "it looks right"?
3. Draw a 3-node stack after push 10, push 20, pop. Label TOS.
4. Write one difference each: list vs tuple vs set vs dictionary.
5. Write a Python function `area(l, w)` that returns $l*w$, and a call that prints it.
6. Name the five steps of a database connection in Python.
7. When would you draw a scatter plot rather than a line graph?
8. Compute mean, median and range of 4, 8, 6, 10, 2.
9. List three signs of a phishing message.
10. Differentiate a prototype and an MVP.

Section C — Long questions (3 × 10 = 30). Attempt any three.

1. A college wants a new student-portal. Describe need analysis, a low-fidelity wireframe of the login + timetable screens, three accessibility principles you would apply, and one usability test you would run.
2. Trace this algorithm with a table for $n = 5$: $total=0$; for i in $1..n$: $total = total + i$; return $total$. State its Big O and rewrite it as a formula that is $O(1)$.
3. Write a Python program that reads a text file of lines "name,marks", stores results in a dictionary, and writes "name: grade" to an output file using `with`. Grade A if marks ≥ 80 else B. Include exception handling if the file is missing.
4. Using the dataset 12, 18, 12, 20, 15, compute mean, median, mode, range, population variance and population standard deviation, showing every step. Then state which chart you would use to show the distribution and why.
5. A Karachi canteen wants a pre-order app. Identify the problem, the riskiest assumption, an MVP, a beachhead market, two test metrics, and one ethical rule for student data.

Mock paper — answers

Section A

1. a
2. b
3. c
4. b
5. d
6. c
7. b
8. b
9. b
10. b
11. b
12. b
13. b
14. b
15. b

Section B

1. UI is the screens and controls (buttons, colours). UX is the whole journey (time to complete a task, frustration, trust). Example: a JazzCash send-money screen (UI) vs how safe and quick the payment felt (UX).
2. A trace table lists each variable after every instruction. It proves correctness on a chosen input; "it looks right" misses off-by-one and uninitialised variables.
3. After push 10, TOS=10. After push 20, TOS=20 (10 below). After pop, 20 removed, TOS=10.
4. list: ordered mutable. tuple: ordered immutable. set: unordered unique. dict: keyed pairs.
5. `def area(l, w): return l * w then print(area(3, 4))` → 12.
6. connect, cursor, execute, commit, close.
7. Scatter: two measured variables (height vs marks) with no single time axis. Line: one quantity changing over an ordered time or sequence.
8. Sorted: 2,4,6,8,10. Mean = $30/5 = 6$. Median = 6. Range = $10-2 = 8$.
9. Unknown sender, urgent threat ("account will close today"), a link that does not match the real bank, request for OTP/password, poor Urdu/English, unexpected attachment.
10. A prototype is a model used to learn (often internal). An MVP is a real, usable product with just enough features to test the riskiest assumption with actual customers.

Section C — outline

1. Need analysis: who (students, teachers), tasks (view timetable, submit leave), constraints (mobile, slow internet). Wireframe: simple boxes for logo, fields, button, a second screen with a 5-day table. Accessibility: large tap targets, colour not the only signal, Urdu/English labels, screen-reader names. Test: five students think-aloud while logging in; record errors and time.
2. $i=1$ total=1; $i=2$ total=3; $i=3$ total=6; $i=4$ total=10; $i=5$ total=15. Loop body runs n times → $O(n)$. Formula $n*(n+1)/2$ is $O(1)$.
3. try: with open(path) as f: for line in f: name, m = line.strip().split(","); d[name]=int(m) except FileNotFoundError: print("missing"). Then with open(out,"w") as g: write grades. Show one sample dictionary.
4. Sorted 12,12,15,18,20. Mean $77/5=15.4$. Median 15. Mode 12. Range 8. Population variance: deviations -3.4,-3.4,-0.4,2.6,4.6; squares 11.56,11.56,0.16,6.76,21.16; sum 51.2; $/5 = 10.24$. std = 3.2. Histogram to show distribution (or bar of frequencies).
5. Problem: long canteen queues between periods. Riskiest assumption: students will pre-order 10 minutes before break. MVP: WhatsApp number + Google Form, pickup tokens, no app. Beachhead: one shift of first-year students. Metrics: % of orders picked up, time-to-collect, repeat use. Ethical: do not publish phone numbers; delete form responses after the term.