

COACHING ACADEMY EDITION

Computer Science XI

For coaching academies — 90-minute batch plans, full-mark recipes, timed drills with answers, and batch homework.

Bilingual support: English + اردو

کوچنگ اکیڈمی کے لیے — 90 منٹ کلاس، مکمل نمبر، ڈرل اور ہوم ورک

01 Computer Systems

02 Computational Thinking & Algorithm

03 Programming Fundamentals

04 Data and Analysis

05 Application and Impacts of Computing

06 Digital Literacy

XI

Contents

Chapter 1: Computer Systems

- 1.1.1 Discrete and Continuous Quantities
- 1.1.3 Analog and Digital Signals
- 1.1.5 Boolean Operations
- 1.1.7 Logic Gates (Basic Gates: AND, OR, NOT)
- 1.1.7 Advanced Logic Gates (XOR and XNOR)
- 1.1.11 Logic Diagrams
- LogiSim Evolution: Simulation Tool
- 1.2.1 – 1.2.3 Software Development Life Cycle (SDLC)
- 1.2.4 The Agile Model
- 1.1.2 Introduction to Digital Systems
- 1.1.4 Boolean Algebra
- 1.1.6 Truth Tables
- 1.1.7 Universal Logic Gates (NAND and NOR)
- 1.1.8 – 1.1.10 Logic Expressions, Minterms and Maxterms
- 1.1.13 Karnaugh Maps (K-Maps)
- Building a Circuit in LogiSim
- 1.2.4 The Waterfall Model
- 1.2.5 – 1.2.7 Waterfall vs Agile: Comparison and Case Studies
- 1.3.1 – 1.3.4 Communication Models and the OSI 7-Layer Model
- 1.3.5 – 1.3.6 TCP/IP Model vs OSI Model

Chapter 2: Computational Thinking & Algorithm

- 2.1 Computational Thinking
- 2.2.2 Algorithm vs Pseudocode
- 2.3.2 Pattern Recognition
- 2.4 Sorting and Searching Algorithms
- 2.4.1 Sorting Algorithms: Selection Sort
- 2.4.2 Searching Algorithms: Binary Search
- 2.6 How to Decide Which Algorithm to Use
- 2.2 Algorithm
- 2.3.1 Decomposition
- 2.3.3 Abstraction
- 2.4.1 Sorting Algorithms: Bubble Sort
- 2.4.2 Searching Algorithms: Linear Search
- 2.5 Evaluation Criteria of Algorithm

Chapter 3: Programming Fundamentals

- 3.1 Programming
- 3.2 Career Growth with Python
- 3.3.1 Visual Studio Code (VS Code)
- 3.4.1 Variables
- 3.4.2 Input and Output Handling
- 3.4.3 Relational, Logical and Membership Operators
- 3.5 Control Structures
- 3.5.2 Selection Statements: if and if-else
- 3.5.3 Repetition Statements: the for Loop and range()
- 3.5.3 Nested Loops and for vs while
- 3.6 Libraries in Python
- 3.6.2 Third-Party Libraries
- 3.1.1 Programming Language Types
- 3.3 Integrated Development Environment (IDE)
- 3.4 Fundamentals of Python Programming
- 3.4.1 Data Types in Python
- 3.4.3 Operators and Operands: Arithmetic and Assignment
- 3.4.3 Bitwise Operators
- 3.5.1 Sequence
- 3.5.2 Selection Statements: if-elif-else and Nested if
- 3.5.3 The while Loop, break and continue
- Practical Activity: Shopping Bill Calculator
- 3.6.1 Built-in Libraries
- 3.7 Debugging Code in Python

Chapter 4: Data and Analysis

- 4.1.1 Data, Information and Database
- 4.2 Database Components (Tables, Records, Fields)
- 4.3 Relational Database Management System (RDBMS)
- 4.5 Referential Integrity
- 4.7 Case Study — Library Management System
- 4.9 Creation of Tables in Microsoft Access
- 4.11 Creating Queries in MS Access
- 4.11.6 Data Visualization in MS Access (Charts)
- 4.1.2 Database Management System (DBMS)
- 4.3.1 Keys and Integrity Constraints
- 4.4 Entity Relationship Model (ER-Model)
- 4.6 Relational Schema Development
- 4.8 Database Objects (Tables, Forms, Queries, Reports)
- 4.10 Designing Forms for Data Manipulation
- 4.11.4 Data Summarization and Statistical Analysis

Chapter 5: Application and Impacts of Computing

- 5.1 Introduction to Computing Impacts
- 5.1.2 Internet of Things (IoT) & Components
- Comparison: IoT vs AI vs Data Analytics
- 5.2.1 Scope of AI in Education in Pakistan
- 5.3 Information Sources (Primary, Secondary, Tertiary)
- 5.5 Assistive Technologies
- 5.5.2 Career Connection in Assistive Tech
- 5.1.1 Artificial Intelligence (AI)
- 5.1.3 Data Analytics & Components
- 5.2 Uses of IoT in Different Areas
- 5.2.2 Career Connection in IoT and AI
- 5.4 Impacts of Computing in Various Fields
- 5.5.1 Importance of Assistive Technologies

Chapter 6: Digital Literacy

- 6.1 Introduction to Digital Literacy
- 6.3 Types of Data
- 6.4.1 – 6.4.2 Interviews and Surveys
- 6.5 Primary and Secondary Data
- 6.7 Presenting Data Using Digital Tools: 6.7.1 Spreadsheets and 6.7.2 Presentations
- 6.8 Case Study: Digital Inquiry Project
- 6.8 Steps 4 – 6: Survey Preparation and Primary Data Collection
- 6.8 Steps 10 – 12: Data Analysis, Conclusion and Recommendations
- Careers in Digital Research
- 6.2 Digital Literacy in the Information Age
- 6.4 Data-Collection Strategies
- 6.4.3 – 6.4.5 Prototypes, Observation and Simulations
- 6.6 Designing a Data-Collection Approach
- 6.7.3 – 6.7.4 Infographics and Reports
- 6.8 Steps 1 – 3: Advanced Search and Methodology
- 6.8 Steps 7 – 9: Secondary Data and Spreadsheet Organisation
- 6.8 The Final Digital Artefact

Final Revision: one-page summaries, mock paper and answers

How to run this Coaching Academy Edition

This book is for a **coaching academy batch** (not a 40-minute school period). A standard academy class is **90 minutes**. Golden topics (★) get a full class. Other topics pair into one class. Every topic below the notes has a full-mark recipe, an academy drill with answers, and batch homework.

یہ کتاب کوچنگ اکیڈمی کے بیچ کے لیے ہے۔ ایک کلاس 90 منٹ کی ہے۔ گولڈن موضوع پوری کلاس لیتا ہے۔ ہر موضوع پر نمبر بنانے کا طریقہ، ڈرل اور ہوم ورک ہے۔

The 90-minute academy class

1. **0–10 min — Starter test.** Three oral or written 1-mark questions from last class. Marks go in the batch register.
2. **10–35 min — Concept lock.** Write the definition, table and diagram on the whiteboard. Students copy. No phones.
3. **35–55 min — Board working.** Do the worked example. Then hide it. Two students redo it on the board.
4. **55–75 min — Academy drill.** Timed. 1-mark then 3-mark then 5-mark. Mark at once with the recipe in this book.
5. **75–85 min — Error clinic.** Collect the three most common wrong answers. Correct them in one box on the board.
6. **85–90 min — Homework out.** One 5-mark question + one drawing/code/trace. Collect next class and mark to the scheme.

How academy answers score marks

- **1 mark:** one exact definition or one named fact.
- **2 marks:** definition + one example (preferably local: JazzCash, school portal, NADRA, load-shedding).
- **3 marks:** definition + two clear points + example.
- **5 marks:** definition, a four-point table or explanation, example, and a labelled diagram if the topic has one.
- **8–10 marks:** 5-mark structure + full working (trace, K-map, code, ER diagram) + a one-line conclusion.

Train this wording in every class: *Define. Explain. Example. Diagram. Working.* Examiners award method marks. An answer with no working is a half-answer.

What the extra academy boxes mean

ACADEMY SESSION

How to run this topic in a 90-minute batch: board, drill, error clinic.

FULL-MARK ANSWER RECIPE

The sentence pattern that scores 1, 3, 5 and 8 marks.

ACADEMY DRILL

Timed extra questions with answers — for class, not homework peeking.

BATCH HOMEWORK

What the batch takes home, and how you will mark it tomorrow.

ACADEMY CALENDAR

Chapter session calendar and weekly test.

GOLDEN TOPIC

★ **Golden** — never skip, never rush, test it every week until the exam.

CHAPTER 1

Computer Systems

This chapter shows you how a computer thinks in 0s and 1s, how logic gates turn those bits into decisions, how software is planned and built step by step, and how data travels across a network. These three ideas — digital logic, software development and communication models — are the foundation of everything else in Computer Science.

اس باب میں آپ سیکھیں گے کہ کمپیوٹر صفر اور ایک کی زبان میں کیسے کام کرتا ہے، لاجک گیٹس فیصلے کیسے کرتے ہیں، سافٹ ویئر مرحلہ وار کیسے بنایا جاتا ہے، اور نیٹ ورک پر ڈیٹا ایک جگہ سے دوسری جگہ کیسے پہنچتا ہے۔

What you will learn

- Tell the difference between discrete and continuous quantities, and between analog and digital signals, with examples.
- Use the Boolean operations AND, OR and NOT, and apply the order of precedence.
- Draw the symbol, write the expression and give the truth table of AND, OR, NOT, NAND, NOR, XOR and XNOR gates.
- Simplify Boolean expressions using 2-variable and 3-variable Karnaugh maps.
- Describe the six phases of the SDLC and compare the Waterfall and Agile models using case studies.
- State the advantages of digital systems.
- Build a complete truth table for any expression with 2 or 3 inputs.
- Write minterms (SOP) and maxterms (POS) from a truth table, and draw a logic diagram from an expression.
- Build and test a simple circuit in LogiSim Evolution.
- Explain the seven layers of the OSI model and map them to the four layers of the TCP/IP model.

ACADEMY CALENDAR

Academy calendar: 20 topics · 8 Golden · **16 classes of 90 minutes** + one 40-minute weekly test after this chapter.

Class	Topics	Kind	Board focus
Class 01	Discrete and Continuous Quantities + Introduction to Digital Systems	Paired · 90 min	Everything around you that can be measured or counted is a quantity.
Class 02	Analog and Digital Signals	★ Golden · 90 min	A signal is a changing voltage (or other quantity) that carries information.
Class 03	Boolean Algebra + Boolean Operations	Paired · 90 min	Boolean algebra was developed by the English mathematician George Boole.
Class 04	Truth Tables	Single · 90 min	A truth table shows all possible input combinations and the output for each one, for a...
Class 05	Logic Gates (Basic Gates: AND, OR, NOT)	★ Golden · 90 min	Logic gates are electronic circuits that perform Boolean operations.
Class 06	Universal Logic Gates (NAND and NOR) + Advanced Logic Gates (XOR and XNOR)	Paired · 90 min	NAND means "NOT AND": it is an AND gate followed by a NOT.
Class 07	Logic Expressions, Minterms and Maxterms	Single · 90 min	A logic expression (Boolean expression) combines variables with operations, for example Y...
Class 08	Logic Diagrams	★ Golden · 90 min	A logic diagram shows how logic gates are connected to create a circuit.

Class	Topics	Kind	Board focus
Class 09	Karnaugh Maps (K-Maps)	★ Golden · 90 min	A Karnaugh map (K-map) is a graphical tool used to simplify Boolean expressions.
Class 10	LogiSim Evolution: Simulation Tool + Building a Circuit in LogiSim	Paired · 90 min	LogiSim Evolution is a free graphical tool for designing and simulating logic circuits.
Class 11	Software Development Life Cycle (SDLC)	★ Golden · 90 min	The Software Development Life Cycle (SDLC) is a structured process that guides software...
Class 12	The Waterfall Model	★ Golden · 90 min	The Waterfall model is a linear, sequential approach to the SDLC.
Class 13	The Agile Model	★ Golden · 90 min	The Agile model is an iterative approach: the software is built in small, repeated cycles...
Class 14	Waterfall vs Agile: Comparison and Case Studies	Single · 90 min	Both models follow the same SDLC phases.
Class 15	Communication Models and the OSI 7-Layer Model	★ Golden · 90 min	A communication model explains how data travels from one device to another through a...
Class 16	TCP/IP Model vs OSI Model	Single · 90 min	The OSI model is mainly a reference model used for teaching and design.

Weekly test: 15 MCQ from this chapter + two 5-mark Golden questions. Mark to the recipes. Re-teach any Golden below 60% in the next starter.

گولڈن موضوع پوری کلاس لیتا ہے۔ ہفتہ وار ٹیسٹ کے بعد کمزور گولڈن دوبارہ پڑھائیں۔

1.1.1 Discrete and Continuous Quantities

ACADEMY SESSION

Session 1 of 16 · 45 minutes (first half) · paired with Introduction to Digital Systems.

10–45 min — this topic. Lock the definition and table for **Discrete and Continuous Quantities**. Starter (0–10) is from last class. Second half is Introduction to Digital Systems.

On the board: Everything around you that can be measured or counted is a quantity.

Error clinic: Students sometimes say "money is continuous because amounts are large".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Discrete and Continuous Quantities**. Write: Everything around you that can be measured or counted is a quantity.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Quantities come in two kinds. (2) Discrete quantities are separate, countable items with specific values. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.


LEARN IT

Everything around you that can be measured or counted is a **quantity**. Quantities come in two kinds.

Discrete quantities are separate, countable items with specific values. You can count them one by one: 1, 2, 3 ... There is nothing "in between". You cannot have 2.5 students in a classroom.

Continuous quantities can take *any* value within a range. They flow smoothly without breaks. Water can be 30 °C, 30.5 °C, 30.51 °C, and so on — there is always another value in between.

Discrete (counted)	Continuous (measured)
Number of students in a classroom	Temperature of water
Number of cars in a parking lot	Speed of a moving car
Has fixed, separate values	Has any value in a range



Discrete (Stairs)



Continuous (Ramp)

Stairs have fixed steps (discrete). A ramp lets you stand at any point (continuous).

REMEMBER IT

Stairs vs Ramp. On stairs you can only stand on step 1, 2 or 3 — that is discrete data. On a ramp you can stand at any height — that is continuous data. Ask yourself: "Do I *count* it or *measure* it?" Count → discrete. Measure → continuous.

COMMON MISTAKE

Students sometimes say "money is continuous because amounts are large". No — rupees and paise are counted in fixed units, so money is discrete. Size does not matter; what matters is whether values in between are possible.

اردو میں سمجھیں

منفصل (Discrete) مقداریں وہ ہیں جنہیں ایک ایک کر کے گنا جا سکے، جیسے کلاس میں طلبہ کی تعداد۔ مسلسل (Continuous) مقداریں کسی حد کے اندر کوئی بھی قیمت لے سکتی ہیں، جیسے پانی کا درجہ حرارت۔ سیڑھیاں منفصل ڈیٹا کی مثال ہیں اور ڈھلوان (ریمپ) مسلسل ڈیٹا کی۔

CHECK YOURSELF

1. Is the number of pages in a book discrete or continuous?
2. Is your height discrete or continuous?
3. In the stairs/ramp analogy, which one shows continuous data?

Answers: 1. Discrete (you count pages). 2. Continuous (height is measured and can be any value). 3. The ramp.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Is the number of pages in a book discrete or continuous?

3 marks. Explain Discrete and Continuous Quantities with two clear points and one example.

5 marks. Write a 5-mark answer on Discrete and Continuous Quantities: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Discrete (you count pages) 3. Quantities come in two kinds.; Discrete quantities are separate, countable items with specific values. 5. Use the recipe in the blue box. Model opening: Everything around you that can be measured or counted is a quantity.

BATCH HOMEWORK

Write a 5-mark answer on **Discrete and Continuous Quantities** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.1.2 Introduction to Digital Systems

ACADEMY SESSION

Session 1 of 16 · 45 minutes (second half) · paired with Discrete and Continuous Quantities.

45–75 min — this topic. Board working for **Introduction to Digital Systems**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: A digital system is an electronic system that uses only two values: 0 and 1.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Introduction to Digital Systems**. Write: A digital system is an electronic system that uses only two values: 0 and 1.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) 0 represents OFF, LOW, or FALSE. (2) 1 represents ON, HIGH, or TRUE. — + example.

5 marks: 3-mark structure + table: Advantage / Detail + the worked example from this topic.

LEARN IT

A **digital system** is an electronic system that uses only two values: **0** and **1**. These two values are called **binary digits**, or **bits** for short.

- **0** represents OFF, LOW, or FALSE.
- **1** represents ON, HIGH, or TRUE.

Why only two values? Because it is easy for an electronic circuit to tell "voltage present" from "no voltage". Every number, letter, photo and song in a computer is finally stored as a long pattern of these bits.

Advantages of digital systems

Advantage	Detail
Reliable	Less affected by noise and interference.
Accurate	No loss of quality when copying data.
Easy to design	Only two states (0 and 1) to handle.
Programmable	Can be easily controlled by software.

Examples of digital systems

- **Computers:** process data as 0s and 1s.
- **Smartphones:** store photos and music as binary data.
- **Digital cameras:** capture images as binary code.

WORKED EXAMPLE

Why is copying digital data "accurate"?

Step 1: A song is stored as bits, for example 10110010...

Step 2: When you copy it to a USB, the computer copies each bit exactly: 1 stays 1, 0 stays 0.

Step 3: Even after 100 copies the bits are identical, so the song sounds the same. An old cassette tape (analog) loses a little quality every time it is copied.

REMEMBER IT

Think of a bit as a light switch: it is either ON (1) or OFF (0). A digital system is a huge panel of such switches.

اردو میں سمجھیں

ڈیجیٹل نظام صرف دو قیمتیں استعمال کرتا ہے: 0 اور 1، جنہیں بٹ (Bit) کہتے ہیں۔ 0 کا مطلب بند، کم یا غلط ہے اور 1 کا مطلب چالو، زیادہ یا درست ہے۔ ڈیجیٹل نظام قابل بھروسہ، درست، بنانے میں آسان اور سافٹ ویئر سے قابو میں رہنے والے ہوتے ہیں۔

CHECK YOURSELF

1. What does a 1 represent in a digital system?
2. Give two advantages of digital systems.

Answers: 1. ON, HIGH or TRUE. 2. Any two of: reliable (less affected by noise), accurate (no loss when copying), easy to design (two states), programmable (controlled by software).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does a 1 represent in a digital system?

3 marks. Explain Introduction to Digital Systems with two clear points and one example.

5 marks. Write a 5-mark answer on Introduction to Digital Systems: definition, two points, a labelled diagram or table, and one example.

Answers: 1. ON, HIGH or TRUE 3. 0 represents OFF, LOW, or FALSE.; 1 represents ON, HIGH, or TRUE. 5. Use the recipe in the blue box. Model opening: A digital system is an electronic system that uses only two values: 0 and 1.

BATCH HOMEWORK

Write a 5-mark answer on **Introduction to Digital Systems** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.1.3 Analog and Digital Signals ★ Golden

ACADEMY SESSION

Session 2 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A signal is a changing voltage (or other quantity) that carries information.

Error clinic: Do not draw a digital signal with sloping sides.

Exam wording to train: Common questions: "Differentiate between analog and digital signals" (3–4 marks) and "Draw an analog and a digital signal." Write the comparison as a table...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Analog and Digital Signals**. Write: A signal is a changing voltage (or other quantity) that carries information.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Analog signals are continuous signals that change smoothly over time, like a sine wave. (2) Examples: the human voice, a traditional mercury thermometer. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.


8–10 marks: 5-mark structure + a fully labelled diagram copied from the board + a one-line conclusion. Method marks are awarded for working.

LEARN IT


A **signal** is a changing voltage (or other quantity) that carries information.

Analog signals are continuous signals that change smoothly over time, like a **sine wave**. Examples: the human voice, a traditional mercury thermometer.

Digital signals have only two levels: **HIGH (1)** and **LOW (0)**. They jump instantly between these values, which creates a **square wave**. Example: computer data.



Analog Signal (Sine Wave)



Digital Signal (Square Wave)

An analog signal changes smoothly; a digital signal jumps between only two levels.

Feature	Analog data	Digital data
Nature	Continuous flow.	Discrete, separate values (bits).
Wave shape	Sine wave (smooth curve).	Square wave (sudden jumps).
Reliability	Low (affected by noise).	High (resistant to noise).
Examples	Human voice, traditional thermometer.	Computer data.

WORKED EXAMPLE

Why is digital more resistant to noise?

Step 1: Suppose a wire carries 5 V for HIGH and 0 V for LOW.

Step 2: Noise adds a small error, so 5 V arrives as 4.6 V and 0 V arrives as 0.3 V.

Step 3: The receiver only asks "Is it closer to HIGH or LOW?" 4.6 V is still read as 1 and 0.3 V is still read as 0. The data is perfect.

Step 4: In an analog signal, every exact value carries meaning, so 4.6 V instead of 5 V really changes the sound or reading. The noise cannot be removed.

REMEMBER IT

Analog = A smooth curve. Digital = Doorsteps. Analog looks like ocean waves; digital looks like a castle wall (square teeth).

COMMON MISTAKE

Do not draw a digital signal with sloping sides. A digital signal jumps *instantly*, so its edges are straight vertical lines. Also do not confuse "digital" with "electronic": an analog signal can also be electronic.

اردو میں سمجھیں

اینا لاگ سگنل وقت کے ساتھ ہموار انداز میں بدلتا ہے، جیسے سائن ویو (Sine Wave)؛ انسانی آواز اس کی مثال ہے۔ ڈیجیٹل سگنل کی صرف دو سطحیں ہوتی ہیں، HIGH (1) اور LOW (0)، اور یہ اچانک ایک سے دوسری پر جاتا ہے، اس لیے مربع لہر (Square Wave) بنتی ہے۔ ڈیجیٹل سگنل شور سے کم متاثر ہوتا ہے، اس لیے زیادہ قابل بھروسہ ہے۔

EXAM TIP

Common questions: "Differentiate between analog and digital signals" (3–4 marks) and "Draw an analog and a digital signal." Write the comparison as a table with at least three features (nature, wave shape, reliability, example). Always label your diagrams: axes V and t, and HIGH(1)/LOW(0) on the square wave.

CHECK YOURSELF

1. What shape of wave does a digital signal make?
2. Which type of signal is more affected by noise?
3. Give one example of an analog signal.

Answers: 1. A square wave. 2. Analog. 3. Human voice (or a traditional thermometer reading).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What shape of wave does a digital signal make?

3 marks. Explain Analog and Digital Signals with two clear points and one example.

5 marks. Common questions: "Differentiate between analog and digital signals" (3–4 marks) and "Draw an analog and a digital signal." Write the comparison as a table with at least three features (nature, wave...)

8 marks. Analog and Digital Signals: 5-mark answer plus a fully labelled diagram copied from the board.

Answers: 1. A square wave 3. Analog signals are continuous signals that change smoothly over time, like a sine wave.; Examples: the human voice, a traditional mercury thermometer. 5. Use the recipe in the blue box. Model opening: A signal is a changing voltage (or other quantity) that carries information. 8. Same 5-mark body + a fully labelled diagram copied from the board + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Analog and Digital Signals** using the recipe in this topic. Include a fully labelled diagram copied from the board. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.1.4 Boolean Algebra

ACADEMY SESSION

Session 3 of 16 · 45 minutes (first half) · paired with Boolean Operations.

10–45 min — this topic. Lock the definition and table for **Boolean Algebra**. Starter (0–10) is from last class. Second half is Boolean Operations.

On the board: Boolean algebra was developed by the English mathematician George Boole.

Error clinic: In Boolean algebra "+" means OR, not addition.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Boolean Algebra**. Write: Boolean algebra was developed by the English mathematician George Boole.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It is a kind of algebra that deals with only two values: TRUE (1) and FALSE (0). (2) It is the foundation of digital electronics and computer programming — every if condition in a program is a small piece of Boolean algebra. — + example.

5 marks: 3-mark structure + table: Concept / Description / Example + the worked example from this topic.

LEARN IT

Boolean algebra was developed by the English mathematician **George Boole**. It is a kind of algebra that deals with only two values: **TRUE (1)** and **FALSE (0)**. It is the foundation of digital electronics and computer programming — every if condition in a program is a small piece of Boolean algebra.

Concept	Description	Example
Variables	Letters that hold the value 0 or 1.	A, B, C, X, Y
Operations	Actions performed on variables.	AND, OR, NOT
Expressions	Combinations of variables and operations.	A AND B, $Y = A + B$

Some simple rules (laws) follow directly from the meaning of AND, OR and NOT. They are useful when you check or simplify answers:

OR rules	AND rules	NOT rules
$A + 0 = A$	$A \cdot 1 = A$	$(A')' = A$
$A + 1 = 1$	$A \cdot 0 = 0$	$A + A' = 1$
$A + A = A$	$A \cdot A = A$	$A \cdot A' = 0$

WORKED EXAMPLE

Using a law: Simplify $Y = A'B + AB$.

Step 1: Both terms contain B, so take B out: $Y = B(A' + A)$.

Step 2: $A' + A = 1$ (a variable OR its opposite is always 1).

Step 3: $Y = B \cdot 1 = B$.

COMMON MISTAKE

In Boolean algebra "+" means OR, not addition. So $1 + 1 = 1$ (TRUE OR TRUE is TRUE), not 2. There is no value bigger than 1.

اردو میں سمجھیں

بولین الجبرا جارج بول (George Boole) نے بنایا۔ اس میں صرف دو قیمتیں ہوتی ہیں: درست (1) اور غلط (0)۔ متغیرات (Variables) جیسے A اور B صرف 0 یا 1 رکھتے ہیں، آپریشنز AND، OR اور NOT ہیں، اور ان کے ملاپ سے ایکسپریشن (Expression) بنتا ہے۔

CHECK YOURSELF

1. Who developed Boolean algebra?

2. In Boolean algebra, what is $1 + 1$?

Answers: 1. George Boole. 2. 1 (because + means OR).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Who developed Boolean algebra?

3 marks. Explain Boolean Algebra with two clear points and one example.

5 marks. Write a 5-mark answer on Boolean Algebra: definition, two points, a labelled diagram or table, and one example.

Answers: 1. George Boole 3. It is a kind of algebra that deals with only two values: TRUE (1) and FALSE (0).; It is the foundation of digital electronics and computer programming — every if condition in a program is a small piece of Boolean algebra. 5. Use the recipe in the blue box. Model opening: Boolean algebra was developed by the English mathematician George Boole.

BATCH HOMEWORK

Write a 5-mark answer on **Boolean Algebra** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.1.5 Boolean Operations

ACADEMY SESSION

Session 3 of 16 · 45 minutes (second half) · paired with Boolean Algebra.

45–75 min — this topic. Board working for **Boolean Operations**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: There are three basic Boolean operations.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Boolean Operations**. Write: There are three basic Boolean operations.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Every other operation can be made from them. (2) AND operation ($\cdot$) — gives output 1 only when ALL inputs are 1. — + example.

5 marks: 3-mark structure + table: Operation / Real-life analogy + the worked example from this topic.

LEARN IT

There are three basic Boolean operations. Every other operation can be made from them.

1. AND operation ($\cdot$) — gives output 1 **only when ALL inputs are 1**. Expression: $Y = A \cdot B$ (often written just AB).

2. OR operation ($+$) — gives output 1 **when ANY input is 1**. Expression: $Y = A + B$.

3. NOT operation (' or $\bar{}$) — **inverts** (flips) the input. If the input is 1 the output is 0, and if the input is 0 the output is 1. It is a **unary** operation, meaning it works on only one operand. Expression: $Y = A'$ (also written as A with a bar on top, $\bar{A}$).

Operation	Real-life analogy
AND	A door with two locks. The door opens only when both locks are unlocked.
OR	A room with two doors. You can enter if either door is open.
NOT	A room light switch. When the switch is ON the room is lit; when it is OFF the room is dark — the state is the opposite of "dark".

WORKED EXAMPLE

Evaluate each expression for $A = 1$, $B = 0$.

- (a) $A \cdot B = 1 \cdot 0 = 0$ (not all inputs are 1).
- (b) $A + B = 1 + 0 = 1$ (at least one input is 1).
- (c) $B' = 0' = 1$ (NOT flips 0 to 1).
- (d) $A \cdot B' = 1 \cdot 1 = 1$.

REMEMBER IT

AND is "strict" — everyone must agree (all 1s). OR is "easy-going" — one 1 is enough. NOT is "the rebel" — it always says the opposite.

اردو میں سمجھیں

AND آپریشن تب ہی 1 دیتا ہے جب تمام ان پٹ 1 ہوں (دو تالوں والا دروازہ). OR آپریشن تب 1 دیتا ہے جب کوئی ایک ان پٹ بھی 1 ہو (دو دروازوں والا کمرہ). NOT آپریشن ان پٹ کو الٹ دیتا ہے اور صرف ایک ان پٹ پر کام کرتا ہے، اس لیے اسے یونری (Unary) کہتے ہیں۔

CHECK YOURSELF

- 1. What symbol is used for the OR operation?
- 2. Why is NOT called a unary operation?
- 3. Find $A + B'$ when $A = 0$, $B = 1$.

Answers: 1. "+". 2. Because it works on only one operand (one input). 3. $B' = 0$, so $0 + 0 = 0$.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What symbol is used for the OR operation?

3 marks. Explain Boolean Operations with two clear points and one example.

5 marks. Write a 5-mark answer on Boolean Operations: definition, two points, a labelled diagram or table, and one example.

Answers: 1. "+" 3. Every other operation can be made from them.; AND operation ($\cdot$) — gives output 1 only when ALL inputs are 1. 5. Use the recipe in the blue box. Model opening: There are three basic Boolean operations.

BATCH HOMEWORK

Write a 5-mark answer on **Boolean Operations** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.1.6 Truth Tables

ACADEMY SESSION

Session 4 of 16 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A truth table shows all possible input combinations and the output for each one, for a logic gate or a circuit.

Error clinic: Do not list rows in a random order — you may miss or repeat a combination.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Truth Tables**. Write: A truth table shows all possible input combinations and the output for each one, for a logic gate or a circuit.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Calculate total rows = 2^n . (2) List all input combinations in binary counting order (0, 1, 2, 3 ... in binary). — + example.

5 marks: 3-mark structure + table: A / B / Combination + the worked example from this topic.

LEARN IT

A **truth table** shows **all possible input combinations** and the output for each one, for a logic gate or a circuit. It is the "complete record" of how the circuit behaves.

How to create a truth table:

1. Count the number of inputs (n).
2. Calculate total rows = 2^n .
3. List all input combinations in binary counting order (0, 1, 2, 3 ... in binary).
4. Calculate the output for each combination.

2-input example ($n = 2$, rows = 4)

A	B	Combination
0	0	Row 1
0	1	Row 2
1	0	Row 3
1	1	Row 4

3-input example ($n = 3$, rows = 8)

A	B	C	Decimal
0	0	0	0
0	0	1	1
0	1	0	2
0	1	1	3
1	0	0	4
1	0	1	5
1	1	0	6
1	1	1	7

REMEMBER IT

Quick fill trick for 3 inputs: In column C write 0,1,0,1... (change every row). In column B write 0,0,1,1... (change every 2 rows). In column A write 0,0,0,0,1,1,1,1 (change every 4 rows). For n inputs the leftmost column changes every 2^{n-1} rows.

WORKED EXAMPLE

Make the truth table of a 3-input AND: $Y = A \cdot B \cdot C$.

Step 1: $n = 3$, so rows = $2^3 = 8$.

Step 2: List the 8 combinations in binary order.

Step 3: AND gives 1 only when all inputs are 1, so only row 111 gives 1.

A	B	C	$Y = A \cdot B \cdot C$
0	0	0	0
0	0	1	0
0	1	0	0
0	1	1	0
1	0	0	0
1	0	1	0
1	1	0	0
1	1	1	1

COMMON MISTAKE

Do not list rows in a random order — you may miss or repeat a combination. Always count in binary from 000 to 111. Also remember rows = 2^n , not $2 \times n$: 3 inputs give 8 rows, not 6.

اردو میں سمجھیں

ٹروٹھ ٹیبل (Truth Table) کسی گیٹ یا سرکٹ کے تمام ممکنہ ان پٹ اور ان کے آؤٹ پٹ دکھاتا ہے۔ اگر ان پٹ n ہوں تو قطاریں (Rows) 2 کی طاقت n ہوں گی؛ دو ان پٹ کے لیے 4 اور تین ان پٹ کے لیے 8 قطاریں۔ ان پٹ ہمیشہ بائینری ترتیب میں لکھیں۔

CHECK YOURSELF

1. How many rows does a truth table with 4 inputs have?
2. In a 3-input table, what is the 6th row (counting from row 1 = 000)?

Answers: 1. $2^4 = 16$. 2. 101.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. How many rows does a truth table with 4 inputs have?

3 marks. Explain Truth Tables with two clear points and one example.

5 marks. Write a 5-mark answer on Truth Tables: definition, two points, a labelled diagram or table, and one example.

Answers: 1. $2^4 = 16$ 3. Calculate total rows = $2n$.; List all input combinations in binary counting order (0, 1, 2, 3 ... in binary). 5. Use the recipe in the blue box. Model opening: A truth table shows all possible input combinations and the output for each one, for a logic gate or a circuit.

BATCH HOMEWORK

Write a 5-mark answer on **Truth Tables** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.1.7 Logic Gates (Basic Gates: AND, OR, NOT) ★ Golden

ACADEMY SESSION

Session 5 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Logic gates are electronic circuits that perform Boolean operations.

Error clinic: Do not mix up the AND and OR symbols.

Exam wording to train: You are often asked to "draw the symbol, write the expression and truth table" of a gate (2–3 marks each).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Logic Gates (Basic Gates: AND, OR, NOT)**. Write: Logic gates are electronic circuits that perform Boolean operations.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) They take one or more input bits and produce one output bit. (2) They are the building blocks of all digital systems — a processor contains billions of them. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a complete truth table and a labelled gate / logic diagram + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Logic gates are electronic circuits that perform Boolean operations. They take one or more input bits and produce one output bit. They are the **building blocks of all digital systems** — a processor contains billions of them.

The three basic gates match the three basic operations: the **AND gate**, the **OR gate** and the **NOT gate** (also called an **inverter**).



$$\text{AND: } Y = A \cdot B$$



$$\text{OR: } Y = A + B$$



$$\text{NOT: } Y = A'$$

Symbols of the basic gates. AND has a flat back and round front ("D" shape); OR has a curved back and pointed front; NOT is a triangle with a small circle (bubble).

AND gate — $Y = A \cdot B$

A	B	Y
0	0	0
0	1	0
1	0	0
1	1	1

OR gate — $Y = A + B$

A	B	Y
0	0	0
0	1	1
1	0	1
1	1	1

NOT gate — $Y = A'$

A	Y
0	1
1	0

WORKED EXAMPLE

A school bell circuit. The bell (Y) should ring when the timer says "period over" ($A = 1$) **and** the school is open ($B = 1$).

Step 1: The bell needs both conditions, so use an AND gate: $Y = A \cdot B$.

Step 2: Sunday, timer fires: $A = 1$, $B = 0 \rightarrow Y = 1 \cdot 0 = 0$. No bell.

Step 3: Monday, timer fires: $A = 1$, $B = 1 \rightarrow Y = 1$. The bell rings.

If instead the bell should ring when *either* the timer fires *or* the principal presses a button, you would use an OR gate.

REMEMBER IT

Shortcut: AND output is 0 if *any* input is 0. OR output is 1 if *any* input is 1. Learn just the "special row": AND is 1 only at 11; OR is 0 only at 00.

COMMON MISTAKE

Do not mix up the AND and OR symbols. AND has a **flat** input side (like the letter D). OR has a **curved** input side and a **pointed** output, like a shield or arrowhead.

اردو میں سمجھیں

لاجک گیٹس الیکٹرانک سرکٹ ہیں جو بولین آپریشن انجام دیتے ہیں اور تمام ڈیجیٹل نظاموں کی بنیادی اینٹیں ہیں۔ AND گیٹ صرف تب 1 دیتا ہے جب دونوں ان پٹ 1 ہوں، OR گیٹ صرف تب 0 دیتا ہے جب دونوں ان پٹ 0 ہوں، اور NOT گیٹ ان پٹ کو الٹ دیتا ہے۔

EXAM TIP

You are often asked to "draw the symbol, write the expression and truth table" of a gate (2–3 marks each). Draw neat symbols with labelled inputs A, B and output Y. Write the full truth table in binary order. A frequent MCQ: "Which gate gives 1 only when all inputs are 1?" (AND).

CHECK YOURSELF

1. What is the output of an OR gate when $A = 0$ and $B = 0$?
2. What is another name for the NOT gate?
3. For which input does a 2-input AND gate output 1?

Answers: 1. 0. 2. Inverter. 3. Only $A = 1, B = 1$.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is the output of an OR gate when $A = 0$ and $B = 0$?

3 marks. Explain Logic Gates (Basic Gates: AND, OR, NOT) with two clear points and one example.

5 marks. You are often asked to "draw the symbol, write the expression and truth table" of a gate (2–3 marks each). Draw neat symbols with labelled inputs A, B and output Y. Write the full truth table in...

8 marks. Logic Gates (Basic Gates: AND, OR, NOT): 5-mark answer plus a complete truth table and a labelled gate / logic diagram.

Answers: 1. 0. 3. They take one or more input bits and produce one output bit.; They are the building blocks of all digital systems — a processor contains billions of them. 5. Use the recipe in the blue box. Model opening: Logic gates are electronic circuits that perform Boolean operations. 8. Same 5-mark body + a complete truth table and a labelled gate / logic diagram + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Logic Gates (Basic Gates: AND, OR, NOT)** using the recipe in this topic. Include a complete truth table and a labelled gate / logic diagram. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.1.7 Universal Logic Gates (NAND and NOR)

ACADEMY SESSION

Session 6 of 16 · 45 minutes (first half) · paired with Advanced Logic Gates (XOR and XNOR).

10–45 min — this topic. Lock the definition and table for **Universal Logic Gates (NAND and NOR)**. Starter (0–10) is from last class. Second half is Advanced Logic Gates (XOR and XNOR).

On the board: NAND means "NOT AND": it is an AND gate followed by a NOT.

Error clinic: Do not forget the bubble.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Universal Logic Gates (NAND and NOR)**. Write: NAND means "NOT AND": it is an AND gate followed by a NOT.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) NOR means "NOT OR": an OR gate followed by a NOT. (2) On the symbol, the NOT is shown as a small bubble at the output. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

NAND means "NOT AND": it is an AND gate followed by a NOT. **NOR** means "NOT OR": an OR gate followed by a NOT. On the symbol, the NOT is shown as a small bubble at the output.

NAND and NOR are called **universal gates** because **any logic circuit in the world can be built using only NAND gates (or only NOR gates)**. Factories like this: they can mass-produce one type of chip and build everything from it.



$$\text{NAND: } Y = (A \cdot B)'$$



$$\text{NOR: } Y = (A + B)'$$

NAND = AND symbol + bubble. NOR = OR symbol + bubble.

NAND (NOT AND) — $Y = (A \cdot B)'$

A	B	A·B	Y
0	0	0	1
0	1	0	1
1	0	0	1
1	1	1	0

NOR (NOT OR) — $Y = (A + B)'$

A	B	A+B	Y
0	0	0	1
0	1	1	0
1	0	1	0
1	1	1	0

WORKED EXAMPLE

Show that a NAND gate can work as a NOT gate.

Step 1: Connect the same input A to both inputs of the NAND gate. Then $Y = (A \cdot A)'$.

Step 2: Since $A \cdot A = A$, we get $Y = A'$.

Step 3: Check: $A = 0 \rightarrow (0 \cdot 0)' = 0' = 1$. $A = 1 \rightarrow (1 \cdot 1)' = 1' = 0$. This is exactly the NOT truth table.

In the same way, a NOR gate with both inputs tied together gives $(A + A)' = A'$. And a NAND followed by a NAND-as-NOT gives $((A \cdot B)')' = A \cdot B$, an AND gate. This is why they are "universal".

REMEMBER IT

NAND is the exact **opposite** of AND (0 only at 11). NOR is the exact opposite of OR (1 only at 00). Just flip the AND/OR output column.

COMMON MISTAKE

Do not forget the bubble. Without the small circle, a NAND symbol becomes an AND symbol and your answer is wrong. Also, $(A \cdot B)'$ is **not** the same as $A' \cdot B'$: for $A = 1, B = 0, (1 \cdot 0)' = 1$ but $0 \cdot 1 = 0$.

اردو میں سمجھیں

NAND کا مطلب ہے NOT AND اور NOR کا مطلب ہے NOT OR. انہیں یونیورسل (عالمگیر) گیٹ کہتے ہیں کیونکہ صرف NAND یا صرف NOR گیٹس سے دنیا کا کوئی بھی لاجک سرکٹ بنایا جا سکتا ہے۔ NAND صرف تب 0 دیتا ہے جب دونوں ان پٹ 1 ہوں، اور NOR صرف تب 1 دیتا ہے جب دونوں ان پٹ 0 ہوں۔

CHECK YOURSELF

1. Why are NAND and NOR called universal gates?
2. What is the NOR output for $A = 0, B = 1$?
3. How do you make a NOT gate from a NAND gate?

Answers: 1. Any logic circuit can be built using only NAND gates or only NOR gates. 2. 0. 3. Join both inputs together and feed A into them: $(A \cdot A)' = A'$.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Why are NAND and NOR called universal gates?

3 marks. Explain Universal Logic Gates (NAND and NOR) with two clear points and one example.

5 marks. Write a 5-mark answer on Universal Logic Gates (NAND and NOR): definition, two points, a labelled diagram or table, and one example.

Answers: 1. Any logic circuit can be built using only NAND gates or only NOR gates. 3. NOR means "NOT OR": an OR gate followed by a NOT.; On the symbol, the NOT is shown as a small bubble at the output. 5. Use the recipe in the blue box. Model opening: NAND means "NOT AND": it is an AND gate followed by a NOT.

BATCH HOMEWORK

Write a 5-mark answer on **Universal Logic Gates (NAND and NOR)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.1.7 Advanced Logic Gates (XOR and XNOR)

ACADEMY SESSION

Session 6 of 16 · 45 minutes (second half) · paired with Universal Logic Gates (NAND and NOR).

45–75 min — this topic. Board working for **Advanced Logic Gates (XOR and XNOR)**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: XOR (Exclusive OR) gives output 1 when the inputs are different.

Error clinic: XOR is not the same as OR.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Advanced Logic Gates (XOR and XNOR)**. Write: XOR (Exclusive OR) gives output 1 when the inputs are different.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) In terms of basic operations, $A \oplus B = A'B + AB'$. (2) XNOR (Exclusive NOR) is XOR followed by NOT. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

XOR (Exclusive OR) gives output 1 when the inputs are **different**. Expression: $Y = A \oplus B$. In terms of basic operations, $A \oplus B = A'B + AB'$.

XNOR (Exclusive NOR) is XOR followed by NOT. It gives output 1 when the inputs are the **same**. Expression: $Y = (A \oplus B)'$ $= A'B' + AB$.

The XOR symbol is an OR symbol with an extra curved line at the input side. XNOR adds a bubble at the output.



$$\text{XOR: } Y = A \oplus B$$



$$\text{XNOR: } Y = (A \oplus B)'$$

XOR = OR symbol with an extra curve at the back. XNOR = XOR symbol + bubble.

XOR — $Y = A \oplus B$

A	B	Y
0	0	0
0	1	1
1	0	1
1	1	0

XNOR — $Y = (A \oplus B)'$

A	B	Y
0	0	1
0	1	0
1	0	0
1	1	1

All seven gates at a glance

A	B	AND	OR	NAND	NOR	XOR	XNOR
0	0	0	0	1	1	0	1
0	1	0	1	1	0	1	0
1	0	0	1	1	0	1	0
1	1	1	1	0	0	0	1

(NOT has one input: $A = 0 \rightarrow 1$, $A = 1 \rightarrow 0$.)

WORKED EXAMPLE

A staircase light. A light has one switch at the bottom (A) and one at the top (B) of a staircase. Flipping either switch should change the light.

Step 1: Start with both switches down: $A = 0$, $B = 0$, light off ($Y = 0$).

Step 2: Flip the bottom switch: $A = 1$, $B = 0 \rightarrow$ light on ($Y = 1$).

Step 3: Walk up and flip the top switch: $A = 1$, $B = 1 \rightarrow$ light off ($Y = 0$).

Step 4: The pattern 0, 1, 1, 0 is the XOR truth table. So the light is $Y = A \oplus B$.

REMEMBER IT

Memory trick: XOR outputs 1 when inputs are "eXclusively" different. XNOR outputs 1 when inputs are the **same**. XNOR is sometimes called the "equality gate".

COMMON MISTAKE

XOR is not the same as OR. They differ only in the last row: for $A = 1, B = 1$, OR gives 1 but XOR gives 0.

اردو میں سمجھیں

XOR گیٹ تب 1 دیتا ہے جب دونوں ان پٹ مختلف ہوں، اور XNOR گیٹ تب 1 دیتا ہے جب دونوں ان پٹ ایک جیسے ہوں۔ XNOR دراصل XOR کے بعد NOT ہے۔ OR اور XOR میں فرق صرف آخری قطار میں ہے جہاں دونوں ان پٹ 1 ہوں۔

CHECK YOURSELF

1. What is $1 \oplus 1$?
2. Which gate outputs 1 when both inputs are the same?
3. Write XOR using AND, OR and NOT.

Answers: 1. 0. 2. XNOR. 3. $A \oplus B = A'B + AB'$.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is $1 \oplus 1$?

3 marks. Explain Advanced Logic Gates (XOR and XNOR) with two clear points and one example.

5 marks. Write a 5-mark answer on Advanced Logic Gates (XOR and XNOR): definition, two points, a labelled diagram or table, and one example.

Answers: 1. 0. 3. In terms of basic operations, $A \oplus B = A'B + AB'$; XNOR (Exclusive NOR) is XOR followed by NOT. 5. Use the recipe in the blue box. Model opening: XOR (Exclusive OR) gives output 1 when the inputs are different.

BATCH HOMEWORK

Write a 5-mark answer on **Advanced Logic Gates (XOR and XNOR)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.1.8 – 1.1.10 Logic Expressions, Minterms and Maxterms

ACADEMY SESSION

Session 7 of 16 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A logic expression (Boolean expression) combines variables with operations, for example $Y = A + B'C$.

Error clinic: Two classic errors: (1) writing minterms for the 0-rows — minterms come only from rows where $Y = 1$; (2) forgetting precedence — in $A + B \cdot C$ you must do $B \cdot C$...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Logic Expressions, Minterms and Maxterms**. Write: A logic expression (Boolean expression) combines variables with operations, for example $Y = A + B' \cdot C$.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) A logic expression (Boolean expression) combines variables with operations, for example $Y = A + B' \cdot C$. (2) To evaluate it correctly you must follow the order of precedence, just like BODMAS in maths: 1. — + example.

5 marks: 3-mark structure + table: $A / B / C / B' / B' \cdot C / Y = A + B' \cdot C$ + the worked example from this topic.

LEARN IT

A **logic expression** (Boolean expression) combines variables with operations, for example $Y = A + B' \cdot C$. To evaluate it correctly you must follow the **order of precedence**, just like BODMAS in maths:

1. Parentheses () → 2. NOT (') → 3. AND (·) → 4. OR (+)

WORKED EXAMPLE

Worked example 1: truth table of $Y = A + B' \cdot C$

Step 1: 3 inputs, so 8 rows.

Step 2: Precedence: first find B' (NOT), then $B' \cdot C$ (AND), then $A + (B' \cdot C)$ (OR). Make a column for each step.

A	B	C	B'	$B' \cdot C$	$Y = A + B' \cdot C$
0	0	0	1	0	0
0	0	1	1	1	1
0	1	0	0	0	0
0	1	1	0	0	0
1	0	0	1	0	1
1	0	1	1	1	1
1	1	0	0	0	1
1	1	1	0	0	1

Step 3: $Y = 1$ in rows 1, 4, 5, 6, 7 (decimal). Check one row by hand: $A=0, B=0, C=1 \rightarrow B' = 1, B' \cdot C = 1, Y = 0 + 1 = 1$. ✓

WORKED EXAMPLE

Worked example 2: truth table of $Y = (A + B) \cdot C'$

Step 1: Parentheses first: find $A + B$. Then NOT: C' . Then AND the two.

A	B	C	$A+B$	C'	Y
0	0	0	0	1	0
0	0	1	0	0	0
0	1	0	1	1	1
0	1	1	1	0	0
1	0	0	1	1	1
1	0	1	1	0	0
1	1	0	1	1	1
1	1	1	1	0	0

Step 2: $Y = 1$ in rows 2, 4 and 6 (decimal).

Minterms (SOP) and Maxterms (POS)

LEARN IT

Sometimes you are given a truth table and must *find* the expression. There are two standard ways.

Minterm (used in SOP — Sum of Products): a **product (AND)** of all the variables, written for a row whose output is **1**. A variable is **complemented (A')** if its value is 0, and **uncomplemented (A)** if its value is 1. OR-ing all the minterms gives the SOP expression.

Maxterm (used in POS — Product of Sums): a **sum (OR)** of all the variables, written for a row whose output is **0**. A variable is **complemented (A')** if its value is 1, and **uncomplemented (A)** if its value is 0. AND-ing all the maxterms gives the POS expression.

A	B	Output (Y)	Minterm (SOP)	Maxterm (POS)
0	0	0	–	$A + B$
0	1	1	$A'B$	–
1	0	0	–	$A' + B$
1	1	1	AB	–

Final SOP expression: $Y = A'B + AB$. **Final POS expression:** $Y = (A + B)(A' + B)$. Both describe the same table. (Both simplify to $Y = B$ — look at the table: Y always equals B. You will confirm this with a K-map later.)

WORKED EXAMPLE

Worked example 3: write the SOP for a 3-input "majority" circuit. $Y = 1$ when at least two of A, B, C are 1.

Row	A	B	C	Y	Minterm
0	0	0	0	0	–
1	0	0	1	0	–
2	0	1	0	0	–
3	0	1	1	1	$A'BC$
4	1	0	0	0	–
5	1	0	1	1	$AB'C$
6	1	1	0	1	ABC'
7	1	1	1	1	ABC

Step 1: Pick the rows with $Y = 1$: rows 3, 5, 6, 7.

Step 2: Row 3 is $A=0, B=1, C=1 \rightarrow A$ is 0 so write A' ; B and C are 1 so write B, C $\rightarrow A'BC$.

Step 3: Do the same for the other rows and OR them: **$Y = A'BC + AB'C + ABC' + ABC$** . In short form: $Y = \Sigma m(3, 5, 6, 7)$. We will simplify this with a K-map in 1.1.13.

REMEMBER IT

SOP = 1s, POS = 0s. Minterm: 0 $\rightarrow$ bar, 1 $\rightarrow$ plain. Maxterm: the reverse (1 $\rightarrow$ bar, 0 $\rightarrow$ plain). Think "Min likes 1s, Max likes 0s".

COMMON MISTAKE

Two classic errors: (1) writing minterms for the 0-rows — minterms come only from rows where $Y = 1$; (2) forgetting precedence — in $A + B \cdot C$ you must do $B \cdot C$ first. $A + B \cdot C$ is **not** $(A + B) \cdot C$: for $A=1, B=0, C=0$ the first gives 1 and the second gives 0.

اردو میں سمجھیں

ایکسپریشن حل کرتے وقت ترتیب یہ ہے: پہلے قوسین، پھر NOT، پھر AND اور آخر میں OR۔ مینٹرم (Minterm) اُن قطاروں سے بنتا ہے جن کا آؤٹ پٹ 1 ہو؛ اس میں 0 والے متغیر پر بار لگتی ہے۔ میکس ٹرم (Maxterm) اُن قطاروں سے بنتا ہے جن کا آؤٹ پٹ 0 ہو؛ اس میں 1 والے متغیر پر بار لگتی ہے۔

CHECK YOURSELF

1. Which comes first: AND or OR?
2. Write the minterm for $A = 1, B = 0, C = 1$.
3. Write the maxterm for $A = 0, B = 1$.

Answers: 1. AND. 2. $AB'C$. 3. $A + B'$.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which comes first: AND or OR?

3 marks. Explain Logic Expressions, Minterms and Maxterms with two clear points and one example.

5 marks. Write a 5-mark answer on Logic Expressions, Minterms and Maxterms: definition, two points, a labelled diagram or table, and one example.

Answers: 1. AND 3. A logic expression (Boolean expression) combines variables with operations, for example $Y = A + B' \cdot C$; To evaluate it correctly you must follow the order of precedence, just like BODMAS in maths: 1. 5. Use the recipe in the blue box. Model opening: A logic expression (Boolean expression) combines variables with operations, for example $Y = A + B' \cdot C$.

BATCH HOMEWORK

Write a 5-mark answer on **Logic Expressions, Minterms and Maxterms** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.1.11 Logic Diagrams ★ Golden

ACADEMY SESSION

Session 8 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A logic diagram shows how logic gates are connected to create a circuit.

Error clinic: Do not draw a separate wire for a variable each time it appears and then leave one unconnected.

Exam wording to train: Typical question: "Draw the logic diagram of $Y = \dots$ " and sometimes "also make its truth table" (4–5 marks).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Logic Diagrams**. Write: A logic diagram shows how logic gates are connected to create a circuit.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It is a "picture" of a Boolean expression. (2) To draw one, use the order of precedence: the operation with the highest priority is drawn first (nearest the inputs), and the last... — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a complete truth table and a labelled gate / logic diagram + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **logic diagram** shows how logic gates are connected to create a circuit. It is a "picture" of a Boolean expression. To draw one, use the order of precedence: the operation with the **highest priority is drawn first** (nearest the inputs), and the last operation is the gate that gives the final output.


WORKED EXAMPLE

Example 1: Draw the logic diagram for $Y = A \cdot B + C$.

Step 1: Find the operations: AND ($\cdot$) and OR ($+$).

Step 2: AND has higher precedence than OR, so draw the AND gate first, with inputs A and B. Its output is $A \cdot B$.

Step 3: Draw an OR gate. Feed it $A \cdot B$ and C. Its output is Y.



$Y = A \cdot B + C$: AND first, then OR.


WORKED EXAMPLE

Example 2: Draw the logic diagram for $Y = (A + B) \cdot C'$.

Step 1: Parentheses have the highest priority, so draw the OR gate for $A + B$ first.

Step 2: NOT is next: draw a NOT gate on input C to get C' .

Step 3: The last operation is AND: feed $(A + B)$ and C' into an AND gate to get Y.



$Y = (A + B) \cdot C'$: OR and NOT first, then AND.

You can check this circuit against the truth table in 1.1.8 (worked example 2): $Y = 1$ only for rows 010, 100 and 110.

REMEMBER IT

Read the expression and ask "What is done **last**?" That gate goes on the far right, next to Y. Work backwards to the inputs. Count gates: $Y = A \cdot B + C$ needs 2 gates; $Y = (A+B) \cdot C'$ needs 3.

COMMON MISTAKE

Do not draw a separate wire for a variable each time it appears and then leave one unconnected. Every gate input must be joined to an input variable or to another gate's output, and every wire should be clearly labelled in exams.

اردو میں سمجھیں

لاجک ڈایاگرام دکھاتا ہے کہ گیٹس آپس میں کیسے جڑ کر سرکٹ بناتے ہیں۔ ترجیحی ترتیب کے مطابق جو آپریشن پہلے ہوتا ہے اس کا گیٹ پہلے (ان پٹ کے قریب) بنایا جاتا ہے، اور آخری آپریشن کا گیٹ آؤٹ پٹ Y دیتا ہے۔ مثلاً $Y = A \cdot B + C$ میں پہلے AND گیٹ اور پھر OR گیٹ بنتا ہے۔

EXAM TIP

Typical question: "Draw the logic diagram of $Y = \dots$ " and sometimes "also make its truth table" (4–5 marks). Write the precedence steps in one line, draw neat gate symbols with labelled intermediate outputs (like $A \cdot B$), and finish with the truth table. Marks are lost for wrong gate shapes and missing bubbles.

CHECK YOURSELF

1. In $Y = A + B \cdot C$, which gate is drawn first?
2. How many gates are needed for $Y = A' \cdot B$?

Answers: 1. The AND gate (for $B \cdot C$). 2. Two: one NOT gate (for A') and one AND gate.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. In $Y = A + B \cdot C$, which gate is drawn first?

3 marks. Explain Logic Diagrams with two clear points and one example.

5 marks. Typical question: "Draw the logic diagram of $Y = \dots$ " and sometimes "also make its truth table" (4–5 marks). Write the precedence steps in one line, draw neat gate symbols with labelled intermediate...

8 marks. Logic Diagrams: 5-mark answer plus a complete truth table and a labelled gate / logic diagram.

Answers: 1. The AND gate (for $B \cdot C$) 3. It is a "picture" of a Boolean expression.; To draw one, use the order of precedence: the operation with the highest priority is drawn first (nearest the inputs), and the last... 5. Use the recipe in the blue box. Model opening: A logic diagram shows how logic gates are connected to create a circuit. 8. Same 5-mark body + a complete truth table and a labelled gate / logic diagram + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Logic Diagrams** using the recipe in this topic. Include a complete truth table and a labelled gate / logic diagram. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.1.13 Karnaugh Maps (K-Maps) ★ Golden

ACADEMY SESSION

Session 9 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A Karnaugh map (K-map) is a graphical tool used to simplify Boolean expressions.

Error clinic: Most common K-map mistakes: (1) writing the columns as 00, 01, 10, 11 — this puts m_2 and m_3 in the wrong places; (2) making groups of 3 or 6 — only 1, 2, 4, 8...

Exam wording to train: K-maps are a favourite long question (5–6 marks): "Simplify $F(A,B,C) = \sum m(\dots)$ using a K-map." Draw the map with labelled Gray-code headings, fill every cell...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Karnaugh Maps (K-Maps)**. Write: A Karnaugh map (K-map) is a graphical tool used to simplify Boolean expressions.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It is a grid of cells — one cell for each row of the truth table. (2) The cells are arranged so that neighbouring (adjacent) cells differ by only ONE bit. — + example.

5 marks: 3-mark structure + table: $B = 0 / B = 1 / A = 0 / A = 1$ + the worked example from this topic.

8–10 marks: 5-mark structure + a completed K-map with legal groups (1, 2, 4 or 8) and the simplified Boolean expression + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **Karnaugh map (K-map)** is a graphical tool used to **simplify Boolean expressions**. It is a grid of cells — one cell for each row of the truth table. The cells are arranged so that **neighbouring (adjacent) cells differ by only ONE bit**. This ordering is called **Gray code**.

You write the output (1 or 0) of each row into its cell, then **group the 1s** in rectangles of size 1, 2, 4 or 8 (powers of 2). Each group becomes one simple term. This simplifies the equation without long algebra.

Two-variable K-map (A, B)

2 variables need $2^2 = 4$ cells.

	B = 0	B = 1
A = 0	Cell 0 ($A'B'$)	Cell 1 ($A'B$)
A = 1	Cell 2 (AB')	Cell 3 (AB)

Three-variable K-map (A, B, C)

3 variables need $2^3 = 8$ cells. The columns follow the Gray code sequence **00, 01, 11, 10** (not 00, 01, 10, 11). This makes adjacent cells differ by only one variable.

	BC = 00	BC = 01	BC = 11	BC = 10
A = 0	$m_0 (A'B'C')$	$m_1 (A'B'C)$	$m_3 (A'BC)$	$m_2 (A'BC')$
A = 1	$m_4 (AB'C')$	$m_5 (AB'C)$	$m_7 (ABC)$	$m_6 (ABC')$

LEARN IT

Grouping rules

1. Group only 1s. Groups must be rectangles of size 1, 2, 4 or 8 — never 3, 5 or 6.
2. Make groups **as large as possible**. Bigger groups give simpler terms.
3. Use **as few groups as possible**, but every 1 must be in at least one group.
4. **Overlapping is allowed** — a 1 may be used in more than one group.
5. **Wrapping around the edges is allowed**: a cell in the far-left column is adjacent to the cell in the far-right column (BC = 00 is next to BC = 10).
6. To read a group: variables that **change** (0 to 1) inside the group are **eliminated**. Variables that stay the same are kept — plain if they stay 1, complemented if they stay 0.

Group size tells you how many variables disappear: in a 3-variable map, a group of 2 leaves 2 variables, a group of 4 leaves 1 variable, and a group of 8 means $Y = 1$.

WORKED EXAMPLE

K-map example 1 (2 variables): simplify $Y = A'B + AB$.

Step 1: The minterms are $A'B$ (cell 1) and AB (cell 3). Put 1 in those cells, 0 elsewhere.

	B = 0	B = 1
A = 0	0	1
A = 1	0	1

Step 2: The two 1s are in the same column, one above the other. Make one group of 2.

Step 3: Inside the group, A changes (0 then 1) → eliminate A. B stays 1 → keep B.

Result: $Y = B$. This agrees with the algebra in 1.1.4 and the minterm table in 1.1.8.

WORKED EXAMPLE

K-map example 2 (2 variables, overlapping): simplify $Y = A'B' + A'B + AB$.

Step 1: Put 1s in cells 0, 1 and 3.

	B = 0	B = 1
A = 0	1	1
A = 1	0	1

Step 2: Group 1 = the top row (cells 0 and 1). A stays 0, B changes → term **A'** .

Step 3: Group 2 = the right column (cells 1 and 3). A changes, B stays 1 → term **B** . Cell 1 is used twice — overlapping is allowed.

Result: $Y = A' + B$. Check: $A' + B$ is 0 only when $A = 1$ and $B = 0$, which is exactly the one 0 cell (cell 2).

✓

WORKED EXAMPLE

K-map example 3 (3 variables): simplify the majority function $Y = \Sigma m(3, 5, 6, 7) = A'BC + AB'C + ABC' + ABC$.

Step 1: Fill the map. Careful — the columns are in Gray order 00, 01, 11, 10, so m_3 is in the third column and m_2 in the fourth.

	BC = 00	BC = 01	BC = 11	BC = 10
A = 0	0	0	1 (m_3)	0
A = 1	0	1 (m_5)	1 (m_7)	1 (m_6)

Step 2: No group of 4 is possible (there is no 2×2 block or full row of 1s). So make groups of 2, each using m_7 :

- Group 1: $m_3 + m_7$ (column BC = 11). A changes; B = 1, C = 1 stay $\rightarrow$ **BC**.
- Group 2: $m_5 + m_7$ (row A = 1, columns 01 and 11). B changes; A = 1, C = 1 stay $\rightarrow$ **AC**.
- Group 3: $m_7 + m_6$ (row A = 1, columns 11 and 10). C changes; A = 1, B = 1 stay $\rightarrow$ **AB**.

Result: $Y = AB + BC + AC$. Four 3-variable terms (needing 4 three-input AND gates) became three 2-variable terms.

Check one row: A=1, B=0, C=1 $\rightarrow$ AB = 0, BC = 0, AC = 1 $\rightarrow$ Y = 1. In the truth table, row 5 is 1. ✓

WORKED EXAMPLE

K-map example 4 (3 variables, wrap-around): simplify $Y = \Sigma m(0, 2, 4, 6)$.

	BC = 00	BC = 01	BC = 11	BC = 10
A = 0	1	0	0	1
A = 1	1	0	0	1

Step 1: The 1s are in the far-left column (BC = 00) and the far-right column (BC = 10).

Step 2: Because the map wraps around, these two columns are adjacent. Make **one group of 4**: m_0, m_4, m_2, m_6 .

Step 3: In this group A changes (0, 1) and B changes (0, 1). Only C stays the same: C = 0 $\rightarrow$ term **C'**.

Result: $Y = C'$. Without wrapping you would get two groups ($B'C' + BC'$), which is correct but not the simplest.

WORKED EXAMPLE

K-map example 5 (3 variables): simplify $Y = \Sigma m(1, 4, 5, 6, 7)$ — this is the output of $Y = A + B'C$ from 1.1.8.

	BC = 00	BC = 01	BC = 11	BC = 10
A = 0	0	1	0	0
A = 1	1	1	1	1

Step 1: Group of 4: the whole row A = 1 (m_4, m_5, m_7, m_6). B and C both change; A stays 1 $\rightarrow$ **A**.

Step 2: m_1 is still alone. Pair it with m_5 below it (column BC = 01). A changes; B = 0, C = 1 stay $\rightarrow$ **B'C**.

Result: $Y = A + B'C$ — the K-map confirms the original expression was already in its simplest form.

WORKED EXAMPLE

Going further — a 4-variable K-map: simplify $Y = \Sigma m(0, 2, 5, 7, 8, 10, 13, 15)$. (Not required by the slides, but a good test of the same rules.) 4 variables need 16 cells; both rows (AB) and columns (CD) use Gray order 00, 01, 11, 10.

	CD = 00	CD = 01	CD = 11	CD = 10
AB = 00	1 (m_0)	0	0	1 (m_2)
AB = 01	0	1 (m_5)	1 (m_7)	0
AB = 11	0	1 (m_{13})	1 (m_{15})	0
AB = 10	1 (m_8)	0	0	1 (m_{10})

Step 1: The centre 2×2 block (m_5, m_7, m_{13}, m_{15}) is a group of 4. A and C change; B = 1 and D = 1 stay $\rightarrow$ **BD**.

Step 2: The four corners (m_0, m_2, m_8, m_{10}) are adjacent through wrap-around (left-right and top-bottom). A and C change; B = 0 and D = 0 stay $\rightarrow$ **B'D'**.

Result: $Y = BD + B'D'$ (this is B XNOR D). Eight 4-variable minterms became two 2-variable terms.

REMEMBER IT

Gray code song: "zero-zero, zero-one, one-one, one-zero" — only one bit flips at each step. Imagine the K-map is drawn on a tube, so the left and right edges touch. For reading groups: "**If it changes, it goes.**"

COMMON MISTAKE

Most common K-map mistakes: (1) writing the columns as 00, 01, 10, 11 — this puts m_2 and m_3 in the wrong places; (2) making groups of 3 or 6 — only 1, 2, 4, 8 are allowed; (3) grouping diagonally — groups must be rectangles of side-by-side cells; (4) stopping at small groups when a bigger group (or a wrap-around group) is possible.

اردو میں سمجھیں

کارنو میپ (K-Map) بولین ایکسپریشن کو آسان بنانے کا تصویری طریقہ ہے۔ اس کے ساتھ والے خانوں میں صرف ایک بیت کا فرق ہوتا ہے (گرے کوڈ: 00, 01, 10, 11)۔ 1 والے خانوں کو 0, 1, 2, 4 یا 8 کے گروپوں میں جتنا بڑا ممکن ہو جوڑیں؛ گروپ ایک دوسرے پر چڑھ سکتے ہیں اور کناروں سے گھوم کر بھی بن سکتے ہیں۔ گروپ کے اندر جو متغیر بدلتا ہے وہ ختم ہو جاتا ہے۔

EXAM TIP

K-maps are a favourite long question (5–6 marks): "Simplify $F(A,B,C) = \Sigma m(\dots)$ using a K-map." Draw the map with labelled Gray-code headings, fill every cell (write the 0s too), circle the groups clearly, write the term for each group beside it, and give the final simplified expression. Examiners often add "draw the logic diagram of the result" — so practise drawing it too.

CHECK YOURSELF

1. In a 3-variable K-map, which column is next to BC = 01 on the right?
2. Simplify $Y = \Sigma m(2, 3)$ for two variables A, B.
3. Simplify $Y = \Sigma m(4, 5, 6, 7)$ for three variables.

Answers: 1. BC = 11. 2. Cells 2 and 3 are the row A = 1; B changes $\rightarrow Y = A$. 3. The whole row A = 1 is a group of 4 $\rightarrow Y = A$.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. In a 3-variable K-map, which column is next to BC = 01 on the right?

3 marks. Explain Karnaugh Maps (K-Maps) with two clear points and one example.

5 marks. K-maps are a favourite long question (5–6 marks): "Simplify $F(A,B,C) = \Sigma m(\dots)$ using a K-map." Draw the map with labelled Gray-code headings, fill every cell (write the 0s too), circle the groups...

8 marks. Karnaugh Maps (K-Maps): 5-mark answer plus a completed K-map with legal groups (1, 2, 4 or 8) and the simplified Boolean expression.

Answers: 1. BC = 11 3. It is a grid of cells — one cell for each row of the truth table.; The cells are arranged so that neighbouring (adjacent) cells differ by only ONE bit. 5. Use the recipe in the blue box. Model opening: A Karnaugh map (K-map) is a graphical tool used to simplify Boolean expressions. 8. Same 5-mark body + a completed K-map with legal groups (1, 2, 4 or 8) and the simplified Boolean expression + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Karnaugh Maps (K-Maps)** using the recipe in this topic. Include a completed K-map with legal groups (1, 2, 4 or 8) and the simplified Boolean expression. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

LogiSim Evolution: Simulation Tool

ACADEMY SESSION

Session 10 of 16 · 45 minutes (first half) · paired with Building a Circuit in LogiSim.

10–45 min — this topic. Lock the definition and table for **LogiSim Evolution: Simulation Tool**. Starter (0–10) is from last class. Second half is Building a Circuit in LogiSim.

On the board: LogiSim Evolution is a free graphical tool for designing and simulating logic circuits.

Error clinic: If your output wire is blue, the circuit is not wrong in logic — a wire is simply not touching a pin.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **LogiSim Evolution: Simulation Tool**. Write: LogiSim Evolution is a free graphical tool for designing and simulating logic circuits.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).


3 marks: definition + two points — (1) "Simulating" means the computer pretends to be the real circuit: you can switch inputs on and off and watch the output change. (2) It lets you see the truth tables and Boolean expressions you learn in theory. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

LogiSim Evolution is a free graphical tool for **designing and simulating logic circuits**. "Simulating" means the computer pretends to be the real circuit: you can switch inputs on and off and watch the output change. It lets you see the truth tables and Boolean expressions you learn in theory.

1. The interface areas



The main areas of the LogiSim Evolution window.

Area	What it does
Menu Bar (top)	File, Edit, Project, Simulate menus — open/save files and control the simulation.
Toolbar	Quick access to standard tools: Wiring, Poke, and AND, OR, NOT gates.
Explorer Panel (left)	Contains the component libraries: Gates, I/O, Wiring.
Attribute Table (bottom left)	Adjust the properties of the selected gate, e.g. Number of Inputs or Facing direction.
Drawing Canvas (right)	The dotted grid where you place and wire the gates.

Wiring colours during simulation

Colour	Meaning
Bright green	Logic 1 (HIGH)
Dark green	Logic 0 (LOW)
Blue	Unknown / unconnected pin
Red	Error / short circuit

REMEMBER IT

Colours like a traffic light: Green means "working" (bright = 1, dark = 0). Blue means "the wire is lonely — not connected". Red means "stop, something is wrong".

COMMON MISTAKE

If your output wire is blue, the circuit is not wrong in logic — a wire is simply not touching a pin. Zoom in and make sure every wire end sits exactly on a connection point.

لاجی سیم ایوولوشن (LogiSim Evolution) لاجک سرکٹ بنانے اور چلا کر دیکھنے کا سافٹ ویئر ہے۔ اس میں مینو بار، ٹول بار، ایکسپلورر پینل، ایٹری بیوٹ ٹیبل اور ڈرائنگ کینوس ہوتے ہیں۔ چمکدار سبز تار 1، گہری سبز 0، نیلی تار غیر منسلک اور سرخ تار غلطی کو ظاہر کرتی ہے۔

CHECK YOURSELF

1. Where do you change the number of inputs of a gate?
2. What does a red wire mean?

Answers: 1. In the Attribute Table (bottom left). 2. An error or short circuit.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Where do you change the number of inputs of a gate?

3 marks. Explain LogiSim Evolution: Simulation Tool with two clear points and one example.

5 marks. Write a 5-mark answer on LogiSim Evolution: Simulation Tool: definition, two points, a labelled diagram or table, and one example.

Answers: 1. In the Attribute Table (bottom left) 3. "Simulating" means the computer pretends to be the real circuit: you can switch inputs on and off and watch the output change.; It lets you see the truth tables and Boolean expressions you learn in theory. 5. Use the recipe in the blue box. Model opening: LogiSim Evolution is a free graphical tool for designing and simulating logic circuits.

BATCH HOMEWORK

Write a 5-mark answer on **LogiSim Evolution: Simulation Tool** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Building a Circuit in LogiSim

ACADEMY SESSION

Session 10 of 16 · 45 minutes (second half) · paired with LogiSim Evolution: Simulation Tool.

45–75 min — this topic. Board working for **Building a Circuit in LogiSim**, then a short drill. 75–85 error clinic covers both topics in this class.

Error clinic: Students often try to poke inputs while the Wiring or Select tool is active — then clicking moves the pin instead of changing it.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Building a Circuit in LogiSim**. Write: one exact sentence that defines Building a Circuit in LogiSim

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).


3 marks: definition + two points — (1) First key fact about Building a Circuit in LogiSim (2) Second distinct point (not a repeat of the definition) — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

WORKED EXAMPLE

Step by step: building $Y = A \cdot B$

1. Select the **AND gate** from the Toolbar (or from the Gates library) and place it on the canvas.
2. Select the **Input Pin** (square icon with a 0) and place two pins to the left of the gate. Label them A and B.
3. Select the **Output Pin** (circle icon with a 0) and place it to the right. Label it Y.
4. Use the **Wiring Tool** to click and drag wires from the input pins to the AND gate's input ports. Wires must be horizontal or vertical.
5. Wire the gate's output to the output pin Y.
6. Select the **Poke Tool** (pointing finger) and click inputs A and B to toggle them between 0 and 1. Test the circuit!



Testing with the Poke Tool: A = 1 (bright green wire), B = 0 (dark green), so $Y = 1 \cdot 0 = 0$.

WORKED EXAMPLE

Testing the circuit = making its truth table. Poke the inputs through all four combinations and write what Y shows:

Poke A	Poke B	Y shows	Output wire colour
0	0	0	Dark green
0	1	0	Dark green
1	0	0	Dark green
1	1	1	Bright green

This matches the AND truth table, so the circuit is correct. Try the same with $Y = A \cdot B + C$ from 1.1.11 (add a second gate and a third input pin).

REMEMBER IT

Input pin = **square** (you push it). Output pin = **circle** (it shows a light). Poke = finger — you "poke" inputs to change them.

COMMON MISTAKE

Students often try to poke inputs while the Wiring or Select tool is active — then clicking moves the pin instead of changing it. Switch to the Poke Tool first.

اردو میں سمجھیں

لاجی سیم میں $Y = A \cdot B$ بنانے کے لیے AND گیٹ رکھیں، بائیں جانب دو ان پٹ پین (چوکور) اور دائیں جانب ایک آؤٹ پٹ پین (گول) رکھیں، پھر وائرنگ ٹول سے تاریں جوڑیں۔ آخر میں پوک ٹول (انگلی) سے ان پٹ کو 0 اور 1 کر کے سرکٹ کو جانچیں۔

CHECK YOURSELF

1. Which icon is the input pin: square or circle?
2. Which tool do you use to change an input between 0 and 1?

Answers: 1. Square (output pin is the circle). 2. The Poke Tool (pointing finger).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which icon is the input pin: square or circle?

3 marks. Explain Building a Circuit in LogiSim with two clear points and one example.

5 marks. Write a 5-mark answer on Building a Circuit in LogiSim: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Square (output pin is the circle) 3. 5. Use the recipe in the blue box. Model opening:

BATCH HOMEWORK

Write a 5-mark answer on **Building a Circuit in LogiSim** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.2.1 – 1.2.3 Software Development Life Cycle (SDLC) ★ Golden

ACADEMY SESSION

Session 11 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The Software Development Life Cycle (SDLC) is a structured process that guides software development from beginning to end.

Error clinic: Do not say the SDLC ends at deployment.

Exam wording to train: "Explain the phases of SDLC" is a very common long question (5–8 marks).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Software Development Life Cycle (SDLC)**. Write: The Software Development Life Cycle (SDLC) is a structured process that guides software development from beginning to end.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It ensures clear goals, better planning, risk reduction and high quality. (2) Without it, teams forget features, go over budget and deliver buggy software. — + example.


5 marks: 3-mark structure + table: Phase / Activities and details / Deliverable (what it produces) + the worked example from this topic.

8–10 marks: 5-mark structure + a comparison table plus a named local case (school portal / NADRA) + a one-line conclusion. Method marks are awarded for working.

LEARN IT

The **Software Development Life Cycle (SDLC)** is a structured process that guides software development from beginning to end. It ensures **clear goals, better planning, risk reduction and high quality**. Without it, teams forget features, go over budget and deliver buggy software.

SDLC has **6 phases**:



Phases 1–3 in detail

Phase	Activities and details	Deliverable (what it produces)
1. Requirement Analysis	Meet clients, understand their needs, list the features. This is the most important phase — mistakes here spread to every later phase.	SRS Document (Software Requirements Specification)
2. System Design	Create the High-Level Design (overall architecture), the Low-Level Design (database, UI screens) and flowcharts.	Design Document
3. Implementation	Write the actual code in programming languages (Python, Java, etc.) based on the design documents.	Working Source Code

Phases 4–6 in detail

Phase	Activities and details	Deliverable
4. Testing	Find and fix bugs (errors), using Black Box and White Box testing.	Test Reports, bug-free software
5. Deployment	Release the software to end-users: Direct, Phased, or Pilot release.	Live Software
6. Maintenance	Provide support and updates, and fix post-release issues.	Patches, Updated Versions

Deployment methods: In a **direct** release the old system is switched off and the new one switched on at once. In a **phased** release the new system is introduced part by part. In a **pilot** release one small group (for example one branch or one class) uses it first before everyone else.

Testing methods

Black Box Testing

- The tester does **not** see the code.
- Tests functionality: give inputs, check outputs.
- Done by dedicated testers.

White Box Testing

- The tester **can** see the code.
- Tests the internal logic and structure.
- Done by developers.

WORKED EXAMPLE

Building a house = SDLC.

Phase 1 (Requirements): you ask the family what rooms they need — 3 bedrooms, a kitchen, a garage.

Phase 2 (Design): the architect draws the blueprints.

Phase 3 (Implementation): the builders lay the bricks.

Phase 4 (Testing): an inspector checks the wiring and the plumbing.

Phase 5 (Deployment): the family moves in.

Phase 6 (Maintenance): repairs, painting and a new room added later.

WORKED EXAMPLE

Black box vs white box on a login screen. A black-box tester types a correct password and a wrong password and checks that the first is accepted and the second rejected — without looking at the code. A white-box tester (the developer) reads the code and checks that every `if` branch, for example the "account locked after 3 tries" branch, actually runs correctly.

REMEMBER IT

Remember the order with "Real Developers Implement, Test, Deploy, Maintain" (R-D-I-T-D-M). Black box = a closed box (you can't see inside). White box = a glass box (you can see inside).

COMMON MISTAKE

Do not say the SDLC ends at deployment. Maintenance is a full phase and often lasts the longest. Also, the SRS is the deliverable of Requirement Analysis, not of Design.

اردو میں سمجھیں

ایس ڈی ایل سی (SDLC) سافٹ ویئر بنانے کا منظم طریقہ ہے جس کے چھ مراحل ہیں: ضروریات کا تجزیہ، سسٹم ڈیزائن، کوڈنگ (Implementation)، ٹیسٹنگ، تنصیب (Deployment) اور دیکھ بھال (Maintenance)۔ پہلا مرحلہ سب سے اہم ہے اور اس سے SRS دستاویز بنتی ہے۔ بلیک باکس ٹیسٹنگ میں کوڈ نظر نہیں آتا جبکہ وائٹ باکس ٹیسٹنگ میں کوڈ دیکھ کر اندرونی منطق جانچی جاتی ہے۔

EXAM TIP

"Explain the phases of SDLC" is a very common long question (5–8 marks). Name all 6 phases in order, write 1–2 lines of activities for each, and state the deliverable of each (SRS, Design Document, Source Code, Test Reports, Live Software, Patches). A short question often asks you to differentiate black box and white box testing — answer in a 3-row table (see code?, what is tested?, who does it?).

CHECK YOURSELF

1. Which phase produces the SRS document?
2. Who usually performs white box testing?
3. Name the three ways to deploy software.

Answers: 1. Requirement Analysis. 2. Developers. 3. Direct, Phased and Pilot release.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which phase produces the SRS document?

3 marks. Explain Software Development Life Cycle (SDLC) with two clear points and one example.

5 marks. "Explain the phases of SDLC" is a very common long question (5–8 marks). Name all 6 phases in order, write 1–2 lines of activities for each, and state the deliverable of each (SRS, Design Document,...

8 marks. Software Development Life Cycle (SDLC): 5-mark answer plus a comparison table plus a named local case (school portal / NADRA).

Answers: 1. Requirement Analysis 3. It ensures clear goals, better planning, risk reduction and high quality.; Without it, teams forget features, go over budget and deliver buggy software. 5. Use the recipe in the blue box. Model opening: The Software Development Life Cycle (SDLC) is a structured process that guides software development from beginning to end. 8. Same 5-mark body + a comparison table plus a named local case (school portal / NADRA) + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Software Development Life Cycle (SDLC)** using the recipe in this topic. Include a comparison table plus a named local case (school portal / NADRA). Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.2.4 The Waterfall Model ★ Golden

ACADEMY SESSION

Session 12 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The Waterfall model is a linear, sequential approach to the SDLC.

Error clinic: Do not choose Waterfall for a project where the customer is still unsure what they want.

Exam wording to train: Expect "Explain the Waterfall model with its advantages and disadvantages" or "When should the Waterfall model be used?" Draw the step diagram, list the three...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **The Waterfall Model**. Write: The Waterfall model is a linear, sequential approach to the SDLC.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).


3 marks: definition + two points — (1) Each phase must be completed before the next one begins, like water falling down steps. (2) There is no easy way to go back to a previous phase. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a comparison table plus a named local case (school portal / NADRA) + a one-line conclusion. Method marks are awarded for working.

LEARN IT

The **Waterfall model** is a **linear, sequential** approach to the SDLC. Each phase must be completed before the next one begins, like water falling down steps. There is no easy way to go back to a previous phase.



The Waterfall model: each phase "falls" into the next, in one direction only.

When to use it

- Requirements are clear, fixed and well understood.
- The project is small to medium in size.
- The technology is stable (not new or experimental).

Advantages (Pros)	Disadvantages (Cons)
Simple to understand and manage.	Not flexible to changes.
Well documented at every step.	Testing happens very late in the process.

WORKED EXAMPLE

Case study: Al-Noor Library Management System. The textbook uses this system as a Waterfall case study because the requirements were **100% fixed before coding began**.

Step 1: The librarian listed exactly what was needed: add books, issue books, return books, calculate fines. Nothing would change.

Step 2: Because the list was fixed, the team could finish the full design, then all the coding, then all the testing, in order.

Step 3: Every phase produced a document, so the library has a complete record for future maintenance.

REMEMBER IT

Waterfall = water only flows downwards. Once water has fallen it cannot climb back up — once a phase is finished you do not go back.

COMMON MISTAKE

Do not choose Waterfall for a project where the customer is still unsure what they want. A late change means going back through design, coding and testing, which is slow and costly.

اردو میں سمجھیں

وائرفال (آبشار) ماڈل ایک سیدھا اور ترتیب وار طریقہ ہے؛ ہر مرحلہ مکمل ہونے کے بعد ہی اگلا شروع ہوتا ہے اور پیچھے جانا مشکل ہوتا ہے۔ یہ تب بہتر ہے جب ضروریات واضح اور طے شدہ ہوں، جیسے النور لائبریری مینجمنٹ سسٹم میں۔ یہ سمجھنے میں آسان ہے مگر تبدیلیوں کے لیے لچکدار نہیں اور ٹیسٹنگ دیر سے ہوتی ہے۔

EXAM TIP

Expect "Explain the Waterfall model with its advantages and disadvantages" or "When should the Waterfall model be used?" Draw the step diagram, list the three "when to use" conditions, and give at least two pros and two cons. Mention the Al-Noor Library case study as your example.

CHECK YOURSELF

1. Why is the Waterfall model called "sequential"?
2. Why did the Al-Noor Library system use Waterfall?

Answers: 1. Because each phase must be completed before the next begins, in a fixed order. 2. Because its requirements were 100% fixed before coding began.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Why is the Waterfall model called "sequential"?

3 marks. Explain The Waterfall Model with two clear points and one example.

5 marks. Expect "Explain the Waterfall model with its advantages and disadvantages" or "When should the Waterfall model be used?" Draw the step diagram, list the three "when to use" conditions, and give at...

8 marks. The Waterfall Model: 5-mark answer plus a comparison table plus a named local case (school portal / NADRA).

Answers: 1. Because each phase must be completed before the next begins, in a fixed order 3. Each phase must be completed before the next one begins, like water falling down steps.; There is no easy way to go back to a previous phase. 5. Use the recipe in the blue box. Model opening: The Waterfall model is a linear, sequential approach to the SDLC. 8. Same 5-mark body + a comparison table plus a named local case (school portal / NADRA) + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **The Waterfall Model** using the recipe in this topic. Include a comparison table plus a named local case (school portal / NADRA). Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.2.4 The Agile Model ★ Golden

ACADEMY SESSION

Session 13 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The Agile model is an iterative approach: the software is built in small, repeated cycles called sprints (usually 2–4 weeks long).

Error clinic: "Less documentation" does not mean "no documentation" or "no planning".

Exam wording to train: Questions ask you to define Agile, explain sprints, list pros/cons, or say when to use it.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **The Agile Model**. Write: The Agile model is an iterative approach: the software is built in small, repeated cycles called sprints (usually 2–4 weeks long).

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Each sprint plans, builds and tests a small part of the software, and then shows it to the customer. (2) Customer feedback is gathered continuously and used in the next sprint. — + example.

5 marks: 3-mark structure + table: Advantages (Pros) / Disadvantages (Cons) + the worked example from this topic.

8–10 marks: 5-mark structure + a comparison table plus a named local case (school portal / NADRA) + a one-line conclusion. Method marks are awarded for working.

LEARN IT

The **Agile model** is an **iterative** approach: the software is built in small, repeated cycles called **sprints** (usually 2–4 weeks long). Each sprint plans, builds and tests a small part of the software, and then shows it to the customer. **Customer feedback is gathered continuously** and used in the next sprint.



When to use it

- Requirements are unclear or may change.
- The customer wants frequent progress updates (early delivery).
- The project is complex or innovative.

Advantages (Pros)	Disadvantages (Cons)
Highly flexible to changes.	Less documentation.
Early delivery of working software.	Unpredictable end-time and cost.

WORKED EXAMPLE

Case study: Al-Noor Student Mobile Application. This app used Agile because teachers, parents and students **constantly requested new features** during development.

Sprint 1 (2 weeks): build login and the timetable screen. Show it to users.

Feedback: parents ask, "Can we see attendance too?"

Sprint 2: add attendance. Teachers now ask for homework notifications.

Sprint 3: add notifications. Each sprint delivers a working app, and new ideas are welcomed instead of causing a restart.

REMEMBER IT

Agile = agile athlete: quick and able to change direction. Think of making a pizza where the customer tastes each slice and you adjust the next one.

COMMON MISTAKE

"Less documentation" does not mean "no documentation" or "no planning". Agile teams still plan every sprint; they simply value working software over long documents.

اردو میں سمجھیں

ایجائل (Agile) ماڈل میں سافٹ ویئر چھوٹے چھوٹے ادوار میں بنتا ہے جنہیں اسپرنٹ (Sprint) کہتے ہیں، جو عموماً دو سے چار ہفتے کے ہوتے ہیں۔ ہر اسپرنٹ کے بعد گاہک کی رائے لی جاتی ہے۔ یہ تبدیلیوں کے لیے بہت لچکدار ہے اور جلد کام کرنے والا سافٹ ویئر دیتا ہے، مگر اس میں دستاویزات کم ہوتی ہیں اور وقت و لاگت کا اندازہ مشکل ہوتا ہے۔ انور اسٹوڈنٹ موبائل ایپ اس کی مثال ہے۔

EXAM TIP

Questions ask you to define Agile, explain sprints, list pros/cons, or say when to use it. Always mention the words "iterative", "sprints (2–4 weeks)" and "continuous customer feedback". Use the Al-Noor Student Mobile App as your case study.

CHECK YOURSELF

1. What is a sprint and how long does it usually last?
2. Give one disadvantage of Agile.

Answers: 1. A short development cycle that delivers a working part of the software; usually 2–4 weeks. 2. Less documentation, or unpredictable end-time and cost.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is a sprint and how long does it usually last?

3 marks. Explain The Agile Model with two clear points and one example.

5 marks. Questions ask you to define Agile, explain sprints, list pros/cons, or say when to use it. Always mention the words "iterative", "sprints (2–4 weeks)" and "continuous customer feedback". Use the...

8 marks. The Agile Model: 5-mark answer plus a comparison table plus a named local case (school portal / NADRA).

Answers: 1. A short development cycle that delivers a working part of the software; usually 2–4 weeks. 3. Each sprint plans, builds and tests a small part of the software, and then shows it to the customer.; Customer feedback is gathered continuously and used in the next sprint. 5. Use the recipe in the blue box. Model opening: The Agile model is an iterative approach: the software is built in small, repeated cycles called sprints (usually 2–4 weeks long). 8. Same 5-mark body + a comparison table plus a named local case (school portal / NADRA) + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **The Agile Model** using the recipe in this topic. Include a comparison table plus a named local case (school portal / NADRA). Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.2.5 – 1.2.7 Waterfall vs Agile: Comparison and Case Studies

ACADEMY SESSION

Session 14 of 16 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Both models follow the same SDLC phases.

Error clinic: Do not say one model is always "better".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Waterfall vs Agile: Comparison and Case Studies**. Write: Both models follow the same SDLC phases.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Both models follow the same SDLC phases. (2) The difference is how they move through them: Waterfall goes through each phase once, in a straight line; Agile goes through all phases... — + example.

5 marks: 3-mark structure + table: Dimension / Waterfall model / Agile model + the worked example from this topic.

LEARN IT

Both models follow the same SDLC phases. The difference is **how** they move through them: Waterfall goes through each phase **once**, in a straight line; Agile goes through all phases **many times**, in small loops.

Dimension	Waterfall model	Agile model
Flexibility	Rigid. Hard to make changes later.	Very flexible. Adapts to changes easily in the next sprint.
Customer involvement	Only at the start (requirements) and the end (delivery).	Continuous throughout the project (after every sprint).
Delivery of software	Single delivery at the very end.	Frequent, partial deliveries after every sprint.
Testing	Done late, in a dedicated testing phase.	Continuous testing within every sprint.
Documentation	Heavy documentation required.	Light documentation. Focus is on working software.

WORKED EXAMPLE

Choosing a model — think like the textbook.

Case A: Al-Noor Library Management System. Requirements fixed 100% before coding → no changes expected → **Waterfall**.

Case B: Al-Noor Student Mobile Application. Teachers, parents and students keep asking for features → requirements change → **Agile**.

Practice case: A bank wants a salary-calculation program for a fixed government formula that will not change. Requirements are clear and fixed, the project is medium-sized, and the technology is stable → **Waterfall**.

Practice case: A start-up wants a new food-delivery app and is not sure which features customers will like. Requirements are unclear and the project is innovative → **Agile**.

REMEMBER IT

One question decides it: **"Will the requirements change?"** No → Waterfall. Yes / not sure → Agile.

COMMON MISTAKE

Do not say one model is always "better". Each suits a different situation. In exams, justify your choice using the project's features (fixed vs changing requirements, size, customer involvement).

اردو میں سمجھیں

وائرفال ماڈل سخت (Rigid) ہے، گاہک صرف شروع اور آخر میں شامل ہوتا ہے، سافٹ ویئر ایک ہی بار آخر میں ملتا ہے اور دستاویزات زیادہ ہوتی ہیں۔ ایجائل ماڈل لچکدار ہے، گاہک ہر اسپرینٹ کے بعد شامل ہوتا ہے، سافٹ ویئر بار بار حصوں میں ملتا ہے اور ٹیسٹنگ مسلسل ہوتی ہے۔ اگر ضروریات طے شدہ ہوں تو وائرفال اور اگر بدلتی رہیں تو ایجائل منتخب کریں۔

CHECK YOURSELF

1. In which model is the customer involved only at the start and the end?
2. Which model delivers software in frequent, partial deliveries?
3. A school wants an exam-result system with rules that never change. Which model?

Answers: 1. Waterfall. 2. Agile. 3. Waterfall (fixed, clear requirements).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. In which model is the customer involved only at the start and the end?

3 marks. Explain Waterfall vs Agile: Comparison and Case Studies with two clear points and one example.

5 marks. Write a 5-mark answer on Waterfall vs Agile: Comparison and Case Studies: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Waterfall 3. Both models follow the same SDLC phases.; The difference is how they move through them: Waterfall goes through each phase once, in a straight line; Agile goes through all phases... 5. Use the recipe in the blue box. Model opening: Both models follow the same SDLC phases.

BATCH HOMEWORK

Write a 5-mark answer on **Waterfall vs Agile: Comparison and Case Studies** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.3.1 – 1.3.4 Communication Models and the OSI 7-Layer Model ★ Golden

ACADEMY SESSION

Session 15 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A communication model explains how data travels from one device to another through a network.

Error clinic: Do not mix up the two addresses: IP address = logical address = Network layer (3); MAC address = physical address = Data Link layer (2).

Exam wording to train: A guaranteed long question: "Explain the seven layers of the OSI model." Draw the 7-layer stack (numbered, layer 7 on top), then write one function and one or...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Communication Models and the OSI 7-Layer Model**. Write: A communication model explains how data travels from one device to another through a network.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Because sending data is complicated, the job is split into layers; each layer does one part of the job and passes the data to the next... (2) The OSI (Open Systems Interconnection) model was developed by ISO (International Organization for Standardization) in 1984. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a labelled ER diagram (rectangle / oval / diamond) or the relational schema + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **communication model** explains how data travels from one device to another through a network. Because sending data is complicated, the job is split into **layers**; each layer does one part of the job and passes the data to the next layer.

The **OSI (Open Systems Interconnection) model** was developed by **ISO** (International Organization for Standardization) in **1984**. It divides communication into **7 layers**. When you send data, it goes **down** the layers on your device (7 → 1), travels as bits over the cable or air, and goes **up** the layers on the receiving device (1 → 7).



The 7 layers of the OSI model with the mnemonic "Please Do Not Throw Sausage Pizza Away".

REMEMBER IT

Mnemonic (bottom to top, 1 → 7): "Please Do Not Throw Sausage Pizza Away" = Physical, Data Link, Network, Transport, Session, Presentation, Application. (Top to bottom you can use "All People Seem To Need Data Processing".)

OSI layers — top layers (7 to 4)

Layer	Function	Protocols / examples
7. Application	Provides network services directly to user applications (browser, email program).	HTTP, HTTPS, FTP, SMTP, DNS
6. Presentation	Data translation, encryption (security) and compression.	SSL/TLS, JPEG, MP3, ASCII
5. Session	Opens, maintains and closes communication sessions.	NetBIOS, RPC
4. Transport	Reliable end-to-end delivery, error checking, port numbering.	TCP (reliable), UDP (fast)

OSI layers — bottom layers (3 to 1)

Layer	Function	Protocols / hardware
3. Network	Logical addressing (IP addresses) and routing packets across networks.	IP, ICMP (Ping), Routers
2. Data Link	Physical addressing (MAC addresses) and error detection in frames.	Ethernet, MAC, Switches
1. Physical	Transmits raw bits (0, 1) over cables or wireless media.	Cables, Hubs, Wi-Fi radio

TCP vs UDP at the Transport layer

	TCP	UDP
Main feature	Reliable — checks that all data arrives correctly and in order.	Fast — sends data without waiting for checks.
Use when	Accuracy matters.	Speed matters more than perfection.
Examples	Web browsing, emails	Video streaming, online gaming

WORKED EXAMPLE

Tracing an email through the OSI layers (sender side).

Layer 7 (Application): you press Send; your email program uses **SMTP**.

Layer 6 (Presentation): the text is encoded (ASCII) and may be encrypted with TLS.

Layer 5 (Session): a session is opened with the mail server.

Layer 4 (Transport): **TCP** breaks the data into segments and numbers them, so nothing is lost (email needs accuracy).

Layer 3 (Network): each packet gets the **IP address** of the destination; **routers** choose the path.

Layer 2 (Data Link): packets are put in **frames** with **MAC addresses**; a **switch** forwards them on the local network.

Layer 1 (Physical): the frames are sent as raw **bits** over the cable or Wi-Fi radio.

At the receiver, the same steps happen in reverse order (1 → 7).

COMMON MISTAKE

Do not mix up the two addresses: **IP address** = logical address = **Network layer (3)**; **MAC address** = physical address = **Data Link layer (2)**. Also, routers work at layer 3, switches at layer 2 and hubs at layer 1.

اردو میں سمجھیں

کمپونیکیشن ماڈل بتاتا ہے کہ ڈیٹا نیٹ ورک کے ذریعے ایک ڈیوائس سے دوسری تک کیسے پہنچتا ہے۔ او ایس آئی (OSI) ماڈل 1984 میں آئی ایس او (ISO) نے بنایا اور اس کی سات تہیں (Layers) ہیں: فزیکل، ڈیٹا لنک، نیٹ ورک، ٹرانسپورٹ، سیشن، پریزنٹیشن اور ایپلی کیشن۔ ہر تہ کا الگ کام ہے، جیسے نیٹ ورک تہ IP ایڈریس اور روٹنگ سنبھالتی ہے۔ TCP درستگی کے لیے اور UDP رفتار کے لیے استعمال ہوتا ہے۔

EXAM TIP

A guaranteed long question: "Explain the seven layers of the OSI model." Draw the 7-layer stack (numbered, layer 7 on top), then write one function and one or two protocols/devices for each layer. MCQs often ask: "Which layer handles routing?" (Network), "Which layer does encryption?" (Presentation), "Who developed OSI and when?" (ISO, 1984), "Which protocol is used for video streaming?" (UDP).

CHECK YOURSELF

1. Which OSI layer is responsible for encryption and compression?
2. At which layer do switches and MAC addresses work?
3. Should online gaming use TCP or UDP? Why?

Answers: 1. Presentation layer (6). 2. Data Link layer (2). 3. UDP, because speed matters more than perfect accuracy.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which OSI layer is responsible for encryption and compression?

3 marks. Explain Communication Models and the OSI 7-Layer Model with two clear points and one example.

5 marks. A guaranteed long question: "Explain the seven layers of the OSI model." Draw the 7-layer stack (numbered, layer 7 on top), then write one function and one or two protocols/devices for each layer....

8 marks. Communication Models and the OSI 7-Layer Model: 5-mark answer plus a labelled ER diagram (rectangle / oval / diamond) or the relational schema.

Answers: 1. Presentation layer (6) 3. Because sending data is complicated, the job is split into layers; each layer does one part of the job and passes the data to the next...; The OSI (Open Systems Interconnection) model was developed by ISO (International Organization for... 5. Use the recipe in the blue box. Model opening: A communication model explains how data travels from one device to another through a network. 8. Same 5-mark body + a labelled ER diagram (rectangle / oval / diamond) or the relational schema + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Communication Models and the OSI 7-Layer Model** using the recipe in this topic. Include a labelled ER diagram (rectangle / oval / diamond) or the relational schema. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.3.5 – 1.3.6 TCP/IP Model vs OSI Model

ACADEMY SESSION

Session 16 of 16 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The OSI model is mainly a reference model used for teaching and design.

Error clinic: The OSI "Network" layer (3) matches the TCP/IP "Internet" layer, not the TCP/IP "Network Access" layer.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **TCP/IP Model vs OSI Model**. Write: The OSI model is mainly a reference model used for teaching and design.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).


3 marks: definition + two points — (1) The TCP/IP model is the practical model used on the real Internet. (2) It condenses the 7 OSI layers into just 4 layers. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

The OSI model is mainly a **reference** model used for teaching and design. The **TCP/IP model** is the **practical model used on the real Internet**. It condenses the 7 OSI layers into just **4 layers**.

TCP/IP model (4 layers)	Corresponds to OSI layers
1. Application	Application, Presentation, Session (7, 6, 5)
2. Transport	Transport (4)
3. Internet	Network (3)
4. Network Access	Data Link, Physical (2, 1)



How the 7 OSI layers map onto the 4 TCP/IP layers.

Point	OSI model	TCP/IP model
Number of layers	7	4
Use	Reference / teaching model	Practical model used on the real Internet
Top layers	Separate Application, Presentation and Session layers	All three combined into one Application layer
Bottom layers	Separate Data Link and Physical layers	Combined into one Network Access layer

WORKED EXAMPLE

Where does each protocol/device go in TCP/IP?

HTTP (OSI layer 7) → TCP/IP **Application**.

SSL/TLS (OSI layer 6) → TCP/IP **Application** (layers 7, 6, 5 are merged).

UDP (OSI layer 4) → TCP/IP **Transport**.

IP and routers (OSI layer 3) → TCP/IP **Internet**.

Ethernet, switches, cables (OSI layers 2 and 1) → TCP/IP **Network Access**.

REMEMBER IT

Count it as **3-1-1-2**: the TCP/IP Application layer takes 3 OSI layers, Transport takes 1, Internet takes 1, Network Access takes 2. Total $3+1+1+2 = 7$.

COMMON MISTAKE

The OSI "Network" layer (3) matches the TCP/IP "**Internet**" layer, not the TCP/IP "Network Access" layer. The similar names confuse many students.

اردو میں سمجھیں

ٹی سی پی / آئی پی (TCP/IP) ماڈل حقیقی انٹرنیٹ پر استعمال ہونے والا عملی ماڈل ہے اور اس کی صرف چار تہیں ہیں۔ اس کی ایپلی کیشن تہ OSI کی 7، 6 اور 5 تہوں کے برابر ہے، ٹرانسپورٹ تہ 4 کے، انٹرنیٹ تہ 3 کے، اور نیٹ ورک ایکسیس تہ 2 اور 1 کے برابر ہے۔

CHECK YOURSELF

1. How many layers does the TCP/IP model have?
2. Which TCP/IP layer corresponds to OSI layers 2 and 1?
3. Which TCP/IP layer contains the OSI Session layer?

Answers: 1. Four. 2. Network Access. 3. Application.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. How many layers does the TCP/IP model have?

3 marks. Explain TCP/IP Model vs OSI Model with two clear points and one example.

5 marks. Write a 5-mark answer on TCP/IP Model vs OSI Model: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Four 3. The TCP/IP model is the practical model used on the real Internet.; It condenses the 7 OSI layers into just 4 layers. 5. Use the recipe in the blue box. Model opening: The OSI model is mainly a reference model used for teaching and design.

BATCH HOMEWORK

Write a 5-mark answer on **TCP/IP Model vs OSI Model** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Chapter 1 Review

Chapter summary

- Discrete quantities are counted (students, cars); continuous quantities are measured and can take any value (temperature, speed). Stairs vs ramp.
- A digital system uses only two values, 0 (OFF/LOW/FALSE) and 1 (ON/HIGH/TRUE), called bits. It is reliable, accurate, easy to design and programmable.
- Analog signals change smoothly (sine wave) and are affected by noise; digital signals jump between HIGH and LOW (square wave) and resist noise.
- Boolean algebra, by George Boole, works with only TRUE (1) and FALSE (0) using variables, operations and expressions.
- AND (·) gives 1 only when all inputs are 1; OR (+) gives 1 when any input is 1; NOT (') inverts its single input (unary).
- A truth table lists all 2^n input combinations in binary order with their outputs.
- Logic gates are the building blocks of digital systems: AND, OR, NOT (basic); NAND, NOR (universal); XOR, XNOR (advanced).
- NAND and NOR are universal: any circuit can be built using only one of them.
- XOR gives 1 when inputs are different; XNOR gives 1 when inputs are the same.
- Order of precedence: Parentheses → NOT → AND → OR. A logic diagram is drawn in the same order.
- Minterms (SOP) come from rows with output 1; maxterms (POS) come from rows with output 0.
- K-maps use Gray code (00, 01, 11, 10); group 1s in sizes 1, 2, 4, 8, as large as possible; overlap and wrap-around are allowed; changing variables are eliminated.
- LogiSim Evolution simulates circuits: input pins are squares, output pins circles; the Poke Tool toggles inputs; bright green = 1, dark green = 0, blue = unconnected, red = error.
- SDLC has 6 phases: Requirement Analysis (SRS), Design, Implementation, Testing (black box/white box), Deployment (direct/phased/pilot), Maintenance.
- Waterfall is linear and suits fixed requirements (AI-Noor Library); Agile is iterative with 2–4 week sprints and suits changing requirements (AI-Noor Student App).
- The OSI model (ISO, 1984) has 7 layers — "Please Do Not Throw Sausage Pizza Away"; the practical TCP/IP model has 4 layers: Application, Transport, Internet, Network Access.

Key terms

Term	Meaning	اردو
Discrete quantity	A countable quantity with separate, fixed values.	منفصل مقدار
Continuous quantity	A quantity that can take any value within a range.	مسلسل مقدار
Bit	A binary digit, 0 or 1.	بائری ہندسہ
Digital system	An electronic system that uses only the values 0 and 1.	ڈیجیٹل نظام
Analog signal	A continuous signal that changes smoothly, like a sine wave.	اینالوگ سگنل (مسلسل اشارہ)
Digital signal	A signal with only two levels, HIGH and LOW (square wave).	ڈیجیٹل سگنل
Noise	Unwanted interference that disturbs a signal.	شور (مداخلت)
Boolean algebra	Algebra of two values, TRUE (1) and FALSE (0), developed by George Boole.	بولین الجبرا
Truth table	A table of all input combinations and their outputs.	ٹروٹھ ٹیبل (صداقت جدول)
Logic gate	An electronic circuit that performs a Boolean operation.	منطقی گیٹ
Universal gate	A gate (NAND or NOR) from which any circuit can be built.	عالمگیر گیٹ
Unary operation	An operation with only one operand, e.g. NOT.	یک عددی عمل
Minterm	A product (AND) of all variables for a row with output 1.	منٹرم
Maxterm	A sum (OR) of all variables for a row with output 0.	میکس ٹرم
SOP	Sum of Products: minterms joined with OR.	حاصل ضرب کا مجموعہ
POS	Product of Sums: maxterms joined with AND.	مجموعوں کا حاصل ضرب
Karnaugh map (K-map)	A grid used to simplify Boolean expressions by grouping 1s.	کارنو نقشہ
Gray code	An ordering where neighbouring values differ by only one bit.	گرے کوڈ
Simulation	Running a computer model of a circuit to test it.	نقلی عمل (سمیولیشن)

Term	Meaning	اردو
SDLC	Software Development Life Cycle: the 6-phase process for building software.	سافٹ ویئر کی تیاری کا دورِ حیات
SRS	Software Requirements Specification: document listing what the software must do.	سافٹ ویئر ضروریات کی دستاویز
Black box testing	Testing inputs and outputs without seeing the code.	بلیک باکس جانچ
White box testing	Testing the internal logic while seeing the code.	وائٹ باکس جانچ
Waterfall model	A linear SDLC model; each phase is finished before the next.	آبشار ماڈل
Agile model	An iterative SDLC model using short sprints and constant feedback.	ایجائل (لچکدار) ماڈل
Sprint	A short development cycle in Agile, usually 2–4 weeks.	اسپرینٹ (مختصر ترقیاتی دور)
Protocol	A set of rules for communication, e.g. HTTP, TCP.	پروٹوکول (ضوابطِ ابلاغ)
OSI model	ISO's 7-layer reference model of network communication (1984).	او ایس آئی ماڈل
TCP/IP model	The practical 4-layer model used on the Internet.	ٹی سی پی/آئی پی ماڈل

Practice: multiple choice

1. Which of the following is a continuous quantity?
 - a. Number of students in a class
 - b. Number of cars in a parking lot
 - c. Temperature of water
 - d. Number of books on a shelf
2. In a digital system, the value 1 represents:
 - a. OFF
 - b. LOW
 - c. FALSE
 - d. ON / HIGH / TRUE
3. A square wave represents a:
 - a. Digital signal
 - b. Analog signal
 - c. Sine wave
 - d. Noise signal
4. Boolean algebra was developed by:
 - a. Charles Babbage
 - b. George Boole
 - c. Alan Turing
 - d. Maurice Karnaugh
5. How many rows does a truth table with 4 inputs have?
 - a. 4
 - b. 8
 - c. 16
 - d. 32
6. Which gate gives output 1 only when all inputs are 1?
 - a. OR
 - b. AND
 - c. NOR
 - d. XOR
7. Which pair of gates are called universal gates?
 - a. AND and OR
 - b. XOR and XNOR
 - c. NOT and AND
 - d. NAND and NOR
8. What is the output of a NOR gate when $A = 0$ and $B = 0$?
 - a. 1
 - b. 0
 - c. Unknown
 - d. Depends on the gate size
9. An XOR gate gives output 1 when:
 - a. Both inputs are 1
 - b. Both inputs are 0
 - c. The inputs are different
 - d. The inputs are the same
10. After parentheses, which operation has the highest precedence?
 - a. OR
 - b. NOT
 - c. AND
 - d. XOR
11. The minterm for the row $A = 1, B = 0$ is:
 - a. AB'
 - b. $A'B$
 - c. $A + B'$
 - d. $A' + B$
12. The columns of a 3-variable K-map (BC) are written in the order:
 - a. 00, 01, 10, 11
 - b. 00, 10, 01, 11
 - c. 11, 10, 01, 00
 - d. 00, 01, 11, 10
13. In black box testing, the tester:
 - a. Reads the source code line by line
 - b. Does not see the code and tests inputs/outputs
 - c. Is always the developer
 - d. Tests only the internal structure
14. Which OSI layer handles logical (IP) addressing and routing?
 - a. Data Link
 - b. Transport
 - c. Network
 - d. Session
15. The TCP/IP Network Access layer corresponds to which OSI layers?
 - a. 7, 6 and 5
 - b. 4
 - c. 3
 - d. 2 and 1

Practice: short questions

1. Define discrete and continuous quantities. Give two examples of each.
2. State four advantages of digital systems.
3. Differentiate between analog and digital signals (any three points).
4. Why is NOT called a unary operation? Write its truth table.
5. How many rows are needed in a truth table for 3 inputs? List all the input combinations.
6. Why are NAND and NOR called universal gates? Show how a NAND gate can be used as a NOT gate.
7. A 2-input truth table has $Y = 1$ only for rows $A=0, B=1$ and $A=1, B=0$. Write the SOP expression and name the gate.
8. Name the deliverable of each SDLC phase.
9. Differentiate between black box testing and white box testing.
10. When should TCP be used and when should UDP be used? Give one example of each.

Practice: long / problem questions

1. Draw the symbol, write the Boolean expression and give the truth table for each of these gates: AND, OR, NOT, NAND, NOR, XOR and XNOR.
2. A function is given as $F(A, B, C) = \sum m(1, 3, 5, 6, 7)$. (a) Make its truth table. (b) Simplify it using a 3-variable K-map, explaining each group. (c) Draw the logic diagram of the simplified expression.
3. For $Y = A \cdot B' + C$: (a) state the order in which the operations are done; (b) make the complete truth table; (c) draw the logic diagram.
4. Explain the six phases of the Software Development Life Cycle with the activities and deliverable of each phase. Use the house-building analogy.
5. Compare the Waterfall and Agile models under five headings. Explain why the Al-Noor Library Management System used Waterfall and the Al-Noor Student Mobile Application used Agile.
6. Explain the seven layers of the OSI model with the function and one protocol/device for each layer. Then show how they map onto the four layers of the TCP/IP model.

Answer key

Multiple choice

1. c
2. d
3. a
4. b
5. c
6. b
7. d
8. a
9. c
10. b
11. a
12. d
13. b
14. c
15. d

Short questions — model answers

1. Discrete quantities are separate, countable items with specific values (number of students in a classroom, number of cars in a parking lot). Continuous quantities can take any value within a range and flow without breaks (temperature of water, speed of a moving car).
2. Reliable (less affected by noise and interference); accurate (no loss of quality when copying); easy to design (only two states, 0 and 1); programmable (easily controlled by software).
3. Nature: analog is a continuous flow; digital has discrete values (bits, HIGH/LOW). Shape: analog is a sine wave; digital is a square wave. Reliability: analog is low (affected by noise); digital is high (resistant to noise). Examples: human voice vs computer data.
4. NOT works on only one operand (one input), so it is unary. Truth table: $A = 0 \rightarrow Y = 1$; $A = 1 \rightarrow Y = 0$.
5. $2^3 = 8$ rows: 000, 001, 010, 011, 100, 101, 110, 111.
6. Any logic circuit can be built using only NAND gates, or only NOR gates. NAND as NOT: join both inputs and feed A: $Y = (A \cdot A)' = A'$. Check: $A = 0 \rightarrow 1$, $A = 1 \rightarrow 0$.
7. Minterms: $A'B$ (row 01) and AB' (row 10). $Y = A'B + AB'$. This is the XOR gate, $Y = A \oplus B$.
8. Requirement Analysis $\rightarrow$ SRS document; System Design $\rightarrow$ Design Document; Implementation $\rightarrow$ Working Source Code; Testing $\rightarrow$ Test Reports / bug-free software; Deployment $\rightarrow$ Live Software; Maintenance $\rightarrow$ Patches / Updated Versions.
9. Black box: tester does not see the code, tests functionality (inputs/outputs), done by dedicated testers. White box: tester can see the code, tests internal logic/structure, done by developers.
10. Use TCP when accuracy matters, e.g. web browsing or email. Use UDP when speed matters more than perfection, e.g. video streaming or online gaming.

Long questions — model answers

- Symbols as drawn in 1.1.7 (AND = D shape; OR = curved back, pointed front; NOT = triangle + bubble; NAND = AND + bubble; NOR = OR + bubble; XOR = OR with extra back curve; XNOR = XOR + bubble). Expressions: AND $Y = A \cdot B$; OR $Y = A + B$; NOT $Y = A'$; NAND $Y = (A \cdot B)'$; NOR $Y = (A + B)'$; XOR $Y = A \oplus B$; XNOR $Y = (A \oplus B)'$. Outputs for inputs 00, 01, 10, 11: AND 0,0,0,1; OR 0,1,1,1; NAND 1,1,1,0; NOR 1,0,0,0; XOR 0,1,1,0; XNOR 1,0,0,1. NOT: 0 $\rightarrow$ 1, 1 $\rightarrow$ 0.
- (a) Truth table ($ABC \rightarrow F$): 000 $\rightarrow$ 0, 001 $\rightarrow$ 1, 010 $\rightarrow$ 0, 011 $\rightarrow$ 1, 100 $\rightarrow$ 0, 101 $\rightarrow$ 1, 110 $\rightarrow$ 1, 111 $\rightarrow$ 1.

(b) K-map:

	BC = 00	BC = 01	BC = 11	BC = 10
A = 0	0	1	1	0
A = 1	0	1	1	1

Group 1 (size 4): the two middle columns, m_1, m_3, m_5, m_7 . A changes and B changes; C = 1 stays $\rightarrow$ **C**. Group 2 (size 2): m_7 and m_6 in row A = 1. C changes; A = 1, B = 1 stay $\rightarrow$ **AB** (m_7 is shared — overlapping is allowed). **F = C + AB**. Check: C + AB is 1 for rows 1, 3, 5, 7 (C = 1) and 6, 7 (AB = 1) = {1, 3, 5, 6, 7}. ✓

(c) Logic diagram: an AND gate with inputs A and B gives AB; an OR gate takes AB and C and gives F.

- (a) First NOT (B'), then AND ($A \cdot B'$), then OR ($+ C$).

(b) Truth table:

A	B	C	B'	A·B'	Y
0	0	0	1	0	0
0	0	1	1	0	1
0	1	0	0	0	0
0	1	1	0	0	1
1	0	0	1	1	1
1	0	1	1	1	1
1	1	0	0	0	0
1	1	1	0	0	1

(c) Logic diagram: input B goes through a NOT gate to give B' . A and B' go into an AND gate to give $A \cdot B'$. $A \cdot B'$ and C go into an OR gate to give Y. (3 gates.)

- Requirement Analysis: meet clients, understand needs, list features; most important phase; deliverable SRS (house: asking the family what rooms they need). System Design: high-level design (architecture), low-level design (database, UI screens), flowcharts; deliverable Design Document (architect draws blueprints). Implementation: write code in Python, Java etc. from the design; deliverable Working Source Code (builders lay bricks). Testing: find and fix bugs using black box and white box testing; deliverable Test Reports / bug-free software (inspector checks the house). Deployment: release to end-users by direct, phased or pilot release; deliverable Live Software (family moves in). Maintenance: support, updates, fixing post-release issues; deliverable Patches / Updated Versions (repairs and extensions).
- Comparison: Flexibility — Waterfall rigid, Agile very flexible. Customer involvement — Waterfall only at start and end, Agile continuous after every sprint. Delivery — Waterfall single delivery at the end, Agile frequent partial deliveries. Testing — Waterfall late in a dedicated phase, Agile continuous in every sprint. Documentation — Waterfall heavy, Agile light. The Al-Noor Library system used Waterfall because its requirements were 100% fixed before coding began, so a simple, well-documented linear process fitted. The Al-Noor Student App used Agile because teachers, parents and students kept requesting new features, so short sprints with continuous feedback were needed.
- OSI (ISO, 1984), top to bottom: 7 Application — network services to user applications (HTTP, HTTPS, FTP, SMTP, DNS); 6 Presentation — translation, encryption, compression (SSL/TLS, JPEG, MP3, ASCII); 5 Session — opens, maintains, closes sessions (NetBIOS, RPC); 4 Transport — reliable end-to-end delivery, error checking, port numbers (TCP, UDP); 3 Network — logical IP addressing and routing (IP, ICMP, routers); 2 Data Link — physical MAC addressing and error detection in frames (Ethernet, switches); 1 Physical — raw bits over cables/wireless (cables, hubs, Wi-Fi radio). Mnemonic bottom to top: "Please Do Not Throw Sausage Pizza Away". TCP/IP mapping: Application = OSI 7, 6, 5; Transport = 4; Internet = 3; Network Access = 2, 1.

Self-assessment: I can...

- ☐ ...tell discrete from continuous quantities and analog from digital signals, and draw both waves.
- ☐ ...evaluate AND, OR and NOT expressions and follow the order of precedence.
- ☐ ...draw all seven gate symbols and write their truth tables from memory.
- ☐ ...write the SOP (minterms) and POS (maxterms) from a truth table.
- ☐ ...simplify expressions with 2- and 3-variable K-maps, including overlap and wrap-around groups.
- ☐ ...explain the six SDLC phases and choose between Waterfall and Agile for a project.
- ☐ ...list four advantages of digital systems.
- ☐ ...build a complete truth table for 2 or 3 inputs without missing a row.
- ☐ ...explain why NAND and NOR are universal gates.
- ☐ ...draw a logic diagram from an expression.
- ☐ ...build and test a simple circuit in LogiSim and read the wire colours.
- ☐ ...name the 7 OSI layers in order, state their functions, and map them to the 4 TCP/IP layers.

CHAPTER 2

Computational Thinking & Algorithm

This chapter teaches you how to think like a computer scientist: break a problem into parts, spot patterns, ignore what does not matter, and write clear step-by-step algorithms. You will then learn four famous algorithms — Bubble Sort, Selection Sort, Linear Search and Binary Search — and how to judge and choose between them.

اس باب میں آپ سیکھیں گے کہ کسی مسئلے کو کمپیوٹر سائنس دان کی طرح کیسے سوچ کر حل کیا جاتا ہے: مسئلے کو چھوٹے حصوں میں توڑنا، پیٹرن پہچاننا، غیر ضروری باتوں کو نظر انداز کرنا اور مرحلہ وار الگورتھم لکھنا۔ اس کے بعد آپ ترتیب دینے (Sorting) اور تلاش کرنے (Searching) کے چار اہم الگورتھم سیکھیں گے۔

What you will learn

- Define computational thinking and name its four parts: decomposition, pattern recognition, abstraction and algorithms.
- Compare an algorithm with pseudocode on at least five points.
- Dry-run Bubble Sort and Selection Sort pass by pass on a given list, and write them in pseudocode and Python.
- List the advantages and disadvantages of each sorting and searching algorithm.
- Evaluate an algorithm for correctness (using a trace table), efficiency and clarity.
- Define an algorithm and state five reasons why algorithms are important.
- Apply decomposition, pattern recognition and abstraction to real-life problems.
- Trace Linear Search step by step and Binary Search using a low / mid / high table.
- State the best-case and worst-case time complexity of the four algorithms.
- Choose the right algorithm for a situation and justify your choice.

ACADEMY CALENDAR

Academy calendar: 13 topics · 6 Golden · **11 classes of 90 minutes** + one 40-minute weekly test after this chapter.

Class	Topics	Kind	Board focus
Class 01	Computational Thinking	Single · 90 min	Computational Thinking (CT) is a systematic approach to solving problems.
Class 02	Algorithm	★ Golden · 90 min	An algorithm is a step-by-step logical procedure used to solve a problem.
Class 03	Algorithm vs Pseudocode	★ Golden · 90 min	Both algorithms and pseudocode are used in problem-solving, but they serve different...
Class 04	Decomposition	★ Golden · 90 min	Decomposition is a problem-solving technique in which a complex task or system is broken...
Class 05	Pattern Recognition + Abstraction	Paired · 90 min	Pattern recognition is the process of identifying regularities, repetitions or rules in...
Class 06	Sorting and Searching Algorithms	Single · 90 min	Sorting and searching are both fundamental techniques of computer science.
Class 07	Sorting Algorithms: Bubble Sort	★ Golden · 90 min	Bubble Sort is an elementary sorting algorithm that works by repeatedly comparing...
Class 08	Sorting Algorithms: Selection Sort	★ Golden · 90 min	Selection Sort is a simple sorting algorithm that works by repeatedly selecting the...
Class 09	Searching Algorithms: Linear Search	Single · 90 min	Linear Search, also known as sequential search, works by examining each element in the...
Class 10	Searching Algorithms: Binary Search	★ Golden · 90 min	Binary Search is a highly efficient search algorithm that works by repeatedly dividing...
Class 11	Evaluation Criteria of Algorithm + How to Decide Which Algorithm to Use	Paired · 90 min	Many algorithms can solve the same problem.

Weekly test: 15 MCQ from this chapter + two 5-mark Golden questions. Mark to the recipes. Re-teach any Golden below 60% in the next starter.

گولڈن موضوع پوری کلاس لیتا ہے۔ ہفتہ وار ٹیسٹ کے بعد کمزور گولڈن دوبارہ پڑھائیں۔

2.1 Computational Thinking

ACADEMY SESSION

Session 1 of 11 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Computational Thinking (CT) is a systematic approach to solving problems.

Error clinic: Students sometimes think computational thinking means "writing code".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Computational Thinking**. Write: Computational Thinking (CT) is a systematic approach to solving problems.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Pattern recognition — identifying things that repeat or follow a rule. (2) Abstraction — hiding (ignoring) details that do not matter. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Computational Thinking (CT) is a systematic approach to solving problems. "Systematic" means you follow a fixed, organised method instead of guessing. CT involves four activities:

- **Decomposition** — breaking a big problem down into smaller parts.
- **Pattern recognition** — identifying things that repeat or follow a rule.
- **Abstraction** — hiding (ignoring) details that do not matter.
- **Algorithms** — developing clear step-by-step instructions to solve the problem.

CT is not "thinking like a computer". It is thinking in a way that lets *you* describe a solution so clearly that a computer (or another person) could carry it out.

Problem → Decomposition → Pattern recognition → Abstraction → Algorithm → Program

You already use computational thinking in daily life. When you plan your exam preparation, you split the syllabus into chapters (decomposition), notice that every chapter needs the same routine of reading, making notes and practising (pattern recognition), ignore things that are not in the syllabus (abstraction), and make a day-by-day timetable (algorithm).

LEARN IT

Did you know? Pseudocode is a human-readable representation of an algorithm using plain English and structured programming keywords. It is the bridge between human logic and machine code. You will study it in detail in section 2.2.2.

REMEMBER IT

Remember the four parts of CT with the phrase **"Don't Pick Any Apple"**: Decomposition, Pattern recognition, Abstraction, Algorithm.

COMMON MISTAKE

Students sometimes think computational thinking means "writing code". It does not. CT happens *before* coding. You can do all four steps with pen and paper, without a computer.

اردو میں سمجھیں

کمپیوٹیشنل تھنکنگ (Computational Thinking) مسائل حل کرنے کا ایک منظم طریقہ ہے۔ اس کے چار حصے ہیں: مسئلے کو چھوٹے حصوں میں توڑنا (Decomposition)، دہرائی جانے والی باتوں کو پہچاننا (Pattern Recognition)، غیر ضروری تفصیلات کو چھپانا (Abstraction) اور مرحلہ وار حل لکھنا (Algorithm)۔ یہ سوچنے کا طریقہ ہے، کوڈ لکھنا نہیں۔

CHECK YOURSELF

1. Name the four parts of computational thinking.
2. Is computational thinking done before or after writing code?
3. What is pseudocode called a "bridge" between?

Answers: 1. Decomposition, pattern recognition, abstraction, algorithms. 2. Before coding (it is planning the solution). 3. Between human logic and machine code.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name the four parts of computational thinking.

3 marks. Explain Computational Thinking with two clear points and one example.

5 marks. Write a 5-mark answer on Computational Thinking: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Decomposition, pattern recognition, abstraction, algorithms 3. Pattern recognition — identifying things that repeat or follow a rule.; Abstraction — hiding (ignoring) details that do not matter. 5. Use the recipe in the blue box. Model opening: Computational Thinking (CT) is a systematic approach to solving problems.

BATCH HOMEWORK

Write a 5-mark answer on **Computational Thinking** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.2 Algorithm ★ Golden

ACADEMY SESSION

Session 2 of 11 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: An algorithm is a step-by-step logical procedure used to solve a problem.

Error clinic: Do not write "an algorithm is a program".

Exam wording to train: Very common short question: "Define algorithm and write its importance." Write the definition word for word — a step-by-step logical procedure used to solve a...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Algorithm**. Write: An algorithm is a step-by-step logical procedure used to solve a problem.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Clear steps — each step has only one meaning. (2) A definite end — it must finish after a limited number of steps. — + example.

5 marks: 3-mark structure + table: Reason / What it means for you + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

An **algorithm** is a step-by-step logical procedure used to solve a problem. It is **conceptual** in nature (it is an idea, a plan) and completely **independent of any programming language**. The same algorithm can be written later in Python, C++ or Java.

A good algorithm has:

- **Input** — the data it starts with.
- **Clear steps** — each step has only one meaning.
- **A definite end** — it must finish after a limited number of steps.
- **Output** — the result it produces.

WORKED EXAMPLE

Algorithm to find the larger of two numbers

Step 1: Start

Step 2: Read A and B

Step 3: If $A > B$, print "A is larger"

Step 4: Else print "B is larger or equal"

Step 5: End

Notice: there is no Python or C++ here. Anyone — even a non-programmer — can follow these steps. That is what "language-independent" means.

2.2.1 Importance of Algorithms

Reason	What it means for you
Structured approach	Algorithms provide a structured approach to problem-solving, making complex tasks manageable.
Optimisation	They optimise time and memory usage, which is crucial for large-scale applications (for example, searching millions of records).
Reusability	They can be reused for similar problems, saving time and effort. A sorting algorithm for marks can also sort prices.
Accuracy and consistency	They ensure accuracy and consistency, reducing human error. The same steps always give the same result.
Blueprint	They act as a blueprint (a plan) before actual code implementation, just like an architect's map before building a house.

REMEMBER IT

Remember the five reasons as **S-O-R-A-B**: **S**tructured, **O**ptimised, **R**eusable, **A**ccurate, **B**lueprint.

COMMON MISTAKE

Do not write "an algorithm is a program". A program is the algorithm *written in a programming language* so that a computer can run it. The algorithm itself is only the logic.

اردو میں سمجھیں

الگورتھم (Algorithm) کسی مسئلے کو حل کرنے کا مرحلہ وار منطقی طریقہ ہے۔ یہ ایک تصور ہے اور کسی بھی پروگرامنگ زبان پر منحصر نہیں۔ الگورتھم کام کو منظم بناتے ہیں، وقت اور میموری بچاتے ہیں، دوبارہ استعمال ہو سکتے ہیں، غلطیاں کم کرتے ہیں اور کوڈ لکھنے سے پہلے نقشے کا کام دیتے ہیں۔

EXAM TIP

Very common short question: "Define algorithm and write its importance." Write the definition word for word — *a step-by-step logical procedure used to solve a problem; conceptual and independent of any programming language* — then list at least four of the five importance points. If asked to "write an algorithm", always begin with **Step 1: Start** and finish with **End**, and number every step.

CHECK YOURSELF

1. Why is an algorithm called "language-independent"?
2. Give two reasons why algorithms are important.
3. Write a 5-step algorithm to find the sum of two numbers.

Answers: 1. Because it describes only the logic; it is not tied to Python, C++ or any other language. 2. Any two: structured approach, optimise time/memory, reusable, accurate and consistent, blueprint before coding. 3. Step 1: Start; Step 2: Read A and B; Step 3: SUM = A + B; Step 4: Print SUM; Step 5: End.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Why is an algorithm called "language-independent"?

3 marks. Explain Algorithm with two clear points and one example.

5 marks. Very common short question: "Define algorithm and write its importance." Write the definition word for word — *a step-by-step logical procedure used to solve a problem; conceptual and independent of...*

8 marks. Algorithm: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. Because it describes only the logic; it is not tied to Python, C++ or any other language 3. Clear steps — each step has only one meaning.; A definite end — it must finish after a limited number of steps. 5. Use the recipe in the blue box. Model opening: An algorithm is a step-by-step logical procedure used to solve a problem. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Algorithm** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.2.2 Algorithm vs Pseudocode ★ Golden

ACADEMY SESSION

Session 3 of 11 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Both algorithms and pseudocode are used in problem-solving, but they serve different purposes in the design phase.

Error clinic: Pseudocode is not executable.

Exam wording to train: "Differentiate between algorithm and pseudocode" is a favourite 4–5 mark question.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Algorithm vs Pseudocode**. Write: Both algorithms and pseudocode are used in problem-solving, but they serve different purposes in the design phase.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The algorithm says what must be done. (2) The pseudocode shows how it could be implemented, using programming-like keywords such as IF, FOR and WHILE, but it still cannot be run on... — + example.

5 marks: 3-mark structure + table: Point / Algorithm / Pseudocode + the worked example from this topic.

8–10 marks: 5-mark structure + the full comparison table with every cell filled + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Both algorithms and pseudocode are used in problem-solving, but they serve different purposes in the design phase. The **algorithm** says *what* must be done. The **pseudocode** shows *how* it could be implemented, using programming-like keywords such as IF, FOR and WHILE, but it still cannot be run on a computer.

Point	Algorithm	Pseudocode
Definition	A step-by-step logical procedure to solve a problem.	A human-readable representation of an algorithm using plain English & keywords.
Nature	Conceptual and language-independent.	Semi-formal and structured, but not executable code.
Purpose	To define what needs to be done logically.	To present how it can be implemented in a readable format.
Form	Usually described in plain steps, bullets or numbered points.	Written using structured constructs (IF, FOR, WHILE) like programming.
Focus	Focuses on the logic and steps of the problem.	Focuses on representing steps clearly before coding.
Audience	For anyone trying to understand the logic (including non-programmers).	Mainly for programmers or students preparing for coding.
Format rules	No fixed format; can be informal.	Follows standard pseudocode conventions for clarity.

WORKED EXAMPLE

The same problem written both ways: print whether a number is even or odd.

Algorithm

Step 1: Start
Step 2: Read a number N
Step 3: Divide N by 2 and find the remainder
Step 4: If the remainder is 0, print "Even",
otherwise print "Odd"
Step 5: End

Pseudocode

```
START
INPUT N
SET R TO N MOD 2
IF R = 0 THEN
    PRINT "Even"
ELSE
    PRINT "Odd"
END IF
END
```

The equivalent Python program (real, executable code):

```
n = 7
if n % 2 == 0:
    print("Even")
else:
    print("Odd")
```

OUTPUT

Odd

Problem → Algorithm (what) → Pseudocode (how) → Program (code) → Output

REMEMBER IT

Teacher's analogy: an **algorithm** is like a recipe ("Bake a cake at 350 degrees"). **Pseudocode** is like a structured kitchen manual using standard verbs (SET temperature TO 350; WHILE cake is not baked, WAIT). The program is the oven actually doing it.

COMMON MISTAKE

Pseudocode is **not** executable. If you type pseudocode into Python, it will give errors. Also, do not mix exact Python syntax (colons, brackets) into pseudocode answers unless asked — use keywords like IF ... THEN ... END IF.

اردو میں سمجھیں

الگورتھم بتاتا ہے کہ کیا کرنا ہے، جبکہ سوڈو کوڈ (Pseudocode) بتاتا ہے کہ اسے کیسے کیا جا سکتا ہے۔ الگورتھم سادہ مرحلوں میں لکھا جاتا ہے اور ہر کوئی اسے سمجھ سکتا ہے۔ سوڈو کوڈ میں IF، FOR، WHILE جیسے الفاظ استعمال ہوتے ہیں اور یہ زیادہ تر پروگرامرز کے لیے ہوتا ہے، لیکن اسے کمپیوٹر پر چلایا نہیں جا سکتا۔

EXAM TIP

"Differentiate between algorithm and pseudocode" is a favourite 4–5 mark question. Draw a two-column table and give at least **five** points (definition, nature, purpose, form, audience). Adding the recipe vs kitchen-manual analogy and one small example of each earns full marks.

CHECK YOURSELF

1. Which one — algorithm or pseudocode — uses keywords like FOR and WHILE?
2. Which one is meant for non-programmers too?
3. Can pseudocode be executed by a computer?

Answers: 1. Pseudocode. 2. Algorithm. 3. No; it is semi-formal and not executable.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which one — algorithm or pseudocode — uses keywords like FOR and WHILE?

3 marks. Explain Algorithm vs Pseudocode with two clear points and one example.

5 marks. "Differentiate between algorithm and pseudocode" is a favourite 4–5 mark question. Draw a two-column table and give at least five points (definition, nature, purpose, form, audience). Adding the...

8 marks. Algorithm vs Pseudocode: 5-mark answer plus the full comparison table with every cell filled.

Answers: 1. Pseudocode 3. The algorithm says what must be done.; The pseudocode shows how it could be implemented, using programming-like keywords such as IF, FOR and WHILE, but it still cannot be run on... 5. Use the recipe in the blue box. Model opening: Both algorithms and pseudocode are used in problem-solving, but they serve different purposes in the design phase. 8. Same 5-mark body + the full comparison table with every cell filled + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Algorithm vs Pseudocode** using the recipe in this topic. Include the full comparison table with every cell filled. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.3.1 Decomposition ★ Golden

ACADEMY SESSION

Session 4 of 11 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Decomposition is a problem-solving technique in which a complex task or system is broken down into smaller, manageable parts.

Error clinic: Do not break a problem into random pieces.

Exam wording to train: Expect "Define decomposition with a real-life example" or "Explain the benefits of decomposition".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Decomposition**. Write: Decomposition is a problem-solving technique in which a complex task or system is broken down into smaller, manageable parts.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) By dividing a big problem into simpler steps, it becomes easier to understand, develop and solve. (2) Each small part is called a sub-task (or sub-problem). — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.


8–10 marks: 5-mark structure + the layer table with one protocol or device on each layer + a one-line conclusion. Method marks are awarded for working.

2.3 Algorithmic Strategies for Problem Solving. An **algorithmic strategy** is a general method that helps you design an algorithm. The three strategies in your syllabus are decomposition, pattern recognition and abstraction.

LEARN IT

Decomposition is a problem-solving technique in which a complex task or system is broken down into smaller, manageable parts. By dividing a big problem into simpler steps, it becomes easier to understand, develop and solve.

Each small part is called a **sub-task** (or sub-problem). You solve each sub-task separately, then join the solutions to solve the whole problem.



Decomposition: one complex problem is split into smaller sub-tasks.

WORKED EXAMPLE

Real-life example: Learning a new language

"Learn English" (or any language) is too big to do in one go. Decompose it:

Sub-task	Description
Learn vocabulary	Learn the words for people, actions and things (e.g., "I", "eat", "apple").
Grammar rules	Learn the sentence structure: Subject → Verb → Object.
Learn tenses	Present, past, future (e.g., "I eat" vs. "I ate").
Sentence building	Combine words using the rules to create valid sentences: "I ate an apple."

Vocabulary → Grammar rules → Tenses → Sentence building

WORKED EXAMPLE

Computing example: a "Student Result" program

Problem: read the marks of a student in 5 subjects and print the total, percentage and grade.

- Sub-task 1: Input marks of 5 subjects.
- Sub-task 2: Calculate total = sum of the 5 marks.
- Sub-task 3: Calculate percentage = $\text{total} \div 500 \times 100$.
- Sub-task 4: Decide the grade from the percentage.
- Sub-task 5: Print the result card.

Each sub-task is now so small that you can write it in two or three lines of code.

Why is decomposition useful?

- **Reduces complexity:** you focus on one piece at a time.
- **Helps in debugging:** you can find exactly where the mistake is (e.g., in the language example, is the error in the verb tense or the word order?).
- **Promotes reusability:** once you learn or build a small part, you can apply it elsewhere (the "calculate percentage" part can be reused in an attendance program).

REMEMBER IT

Think of eating a big *roti*: you cannot eat it in one bite, so you break it into small pieces. Decomposition = "break the *roti*".

COMMON MISTAKE

Do not break a problem into random pieces. Each sub-task must be a meaningful, clear job, and all sub-tasks together must solve the *whole* problem. If one part is missing (e.g., "print result"), the solution is incomplete.

اردو میں سمجھیں

ڈیکمپوزیشن (Decomposition) کا مطلب ہے کسی بڑے اور پیچیدہ مسئلے کو چھوٹے اور آسان حصوں میں تقسیم کرنا۔ مثلاً نئی زبان سیکھنے کو الفاظ، گرامر، زمانے (Tenses) اور جملہ سازی میں تقسیم کیا جا سکتا ہے۔ اس سے پیچیدگی کم ہوتی ہے، غلطی ڈھونڈنا آسان ہوتا ہے اور حصے دوبارہ استعمال ہو سکتے ہیں۔

EXAM TIP

Expect "Define decomposition with a real-life example" or "Explain the benefits of decomposition". Give the definition, draw the small tree (Complex Problem → Sub-task 1, 2, 3), show the language-learning table, and list the three benefits: reduces complexity, helps debugging, promotes reusability.

CHECK YOURSELF

1. What is each smaller part of a decomposed problem called?
2. Decompose "Making a school timetable" into three sub-tasks.
3. State the three benefits of decomposition.

Answers: 1. A sub-task (sub-problem). 2. Example: list subjects and teachers; decide periods per subject per week; place periods in days so no teacher has two classes at once. 3. Reduces complexity, helps in debugging, promotes reusability.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is each smaller part of a decomposed problem called?

3 marks. Explain Decomposition with two clear points and one example.

5 marks. Expect "Define decomposition with a real-life example" or "Explain the benefits of decomposition". Give the definition, draw the small tree (Complex Problem → Sub-task 1, 2, 3), show the...

8 marks. Decomposition: 5-mark answer plus the layer table with one protocol or device on each layer.

Answers: 1. A sub-task (sub-problem) 3. By dividing a big problem into simpler steps, it becomes easier to understand, develop and solve.; Each small part is called a sub-task (or sub-problem). 5. Use the recipe in the blue box. Model opening: Decomposition is a problem-solving technique in which a complex task or system is broken down into smaller, manageable parts. 8. Same 5-mark body + the layer table with one protocol or device on each layer + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Decomposition** using the recipe in this topic. Include the layer table with one protocol or device on each layer. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.3.2 Pattern Recognition

ACADEMY SESSION

Session 5 of 11 · 45 minutes (first half) · paired with Abstraction.

10–45 min — this topic. Lock the definition and table for **Pattern Recognition**. Starter (0–10) is from last class. Second half is Abstraction.

On the board: Pattern recognition is the process of identifying regularities, repetitions or rules in data.

Error clinic: Do not generalise from too few cases.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Pattern Recognition**. Write: Pattern recognition is the process of identifying regularities, repetitions or rules in data.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) What changes in a predictable way? (2) Can I generalise this (write one rule that works for every case)? — + example.

5 marks: 3-mark structure + table: Row / Stars + the worked example from this topic.

LEARN IT

Pattern recognition is the process of identifying regularities, repetitions or rules in data. It helps in reducing the overall complexity of an algorithm and forms the foundation of concepts such as **loops**.

How it works — ask yourself three questions:

- What is repeating?
- What changes in a predictable way?
- Can I generalise this (write one rule that works for every case)?

WORKED EXAMPLE

Example: Triangle of stars

OUTPUT

```

*
**
***
****
*****

```

Step 1 — What repeats? Every row prints stars.

Step 2 — What changes predictably? Each row adds 1 star to the previous row's count.

Row	Stars
1	1
2	2
3	3
...	...
N	N

Step 3 — Generalise: Row N = N stars. Recognising this pattern lets us write one generic loop instead of 5 separate print statements.

Without the pattern (5 statements)

```

print("*")
print("**")
print("***")
print("****")
print("*****")

```

With the pattern (one loop)

```

n = 5
for row in range(1, n + 1):
    print("*" * row)

```

Both programs print exactly the same triangle. But if you want 100 rows, the loop version needs only one change ($n = 100$), while the first version needs 100 lines.

REMEMBER IT

Whenever you see "the same thing again and again, with a small change each time", think **loop**. Pattern recognition is the habit of spotting that.

COMMON MISTAKE

Do not generalise from too few cases. Check your rule on several rows (or items) before trusting it. "Row N = N stars" is correct here; a different triangle (1, 3, 5, 7 stars) follows the rule "Row N = $2N - 1$ stars".

اردو میں سمجھیں

پیٹرن ریکگنیشن (Pattern Recognition) کا مطلب ہے ڈیٹا میں دہرائی جانے والی چیزوں یا اصولوں کو پہچاننا۔ ستاروں کی تکون میں ہر قطار میں پچھلی قطار سے ایک ستارہ زیادہ ہے، یعنی قطار N میں N ستارے۔ یہ پیٹرن پہچان کر ہم پانچ الگ پرنٹ کے بجائے ایک لوپ (Loop) لکھ سکتے ہیں۔

CHECK YOURSELF

1. Which programming concept is based on pattern recognition?
2. How many stars will row 8 of the triangle have?
3. Find the rule: 2, 4, 6, 8, ...

Answers: 1. Loops. 2. 8 stars (Row N = N stars). 3. Term N = $2 \times N$ (each term adds 2).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which programming concept is based on pattern recognition?

3 marks. Explain Pattern Recognition with two clear points and one example.

5 marks. Write a 5-mark answer on Pattern Recognition: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Loops 3. What changes in a predictable way?; Can I generalise this (write one rule that works for every case)?
5. Use the recipe in the blue box. Model opening: Pattern recognition is the process of identifying regularities, repetitions or rules in data.

BATCH HOMEWORK

Write a 5-mark answer on **Pattern Recognition** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.3.3 Abstraction

ACADEMY SESSION

Session 5 of 11 · 45 minutes (second half) · paired with Pattern Recognition.

45–75 min — this topic. Board working for **Abstraction**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Abstraction means hiding unnecessary features and focusing only on the essential ones needed to solve a problem.

Error clinic: Do not confuse abstraction with decomposition.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Abstraction**. Write: Abstraction means hiding unnecessary features and focusing only on the essential ones needed to solve a problem.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Changes based on the situation — these become variables (inputs) in the algorithm. (2) Abstraction items (noise) — details you can ignore completely. — + example.

5 marks: 3-mark structure + table: 1. Necessary steps (core logic) / 2. Changes based on situation (variables) / 3. Abstraction items (ignore / noise) + the worked example from this topic.

LEARN IT

Abstraction means hiding unnecessary features and focusing only on the essential ones needed to solve a problem. It reduces complexity by ignoring what is not important (the **noise**).

When you apply abstraction you sort details into three groups:

- **Necessary steps** — the core logic that never changes.
- **Changes based on the situation** — these become **variables** (inputs) in the algorithm.
- **Abstraction items (noise)** — details you can ignore completely.


WORKED EXAMPLE

Example: applying abstraction to "Making Tea"

To make an algorithm for tea, we separate the necessary steps from the situational changes and the noise.

1. Necessary steps (core logic)	2. Changes based on situation (variables)	3. Abstraction items (ignore / noise)
1. Boil water 2. Add tea leaves/bag 3. Steep for a few minutes 4. Pour into cup 5. Serve	Ingredients (black, green, milk) Additions (sugar, lemon) Tools (stove vs kettle)	Brand of kettle Cup colour or design Where tea is made (kitchen, office)

The core abstracted logic, independent of cup colour or kettle brand:



This one algorithm now works for green tea in an office kettle and for milk tea on a kitchen stove. The middle column simply becomes inputs: `tea_type`, `addition`, `tool`.

Computers use abstraction everywhere. When you call `print("Hello")` in Python, you do not think about how the screen lights up each pixel — those details are hidden from you. A map of Karachi shows roads and landmarks but hides every tree and car: it is an abstraction of the city.

REMEMBER IT

Abstraction = **"Keep the skeleton, drop the decoration."** Ask: "If I remove this detail, does the solution still work?" If yes, it is noise.

COMMON MISTAKE

Do not confuse abstraction with decomposition. Decomposition *splits* a problem into parts. Abstraction *removes* unimportant details. Also, do not throw away details that really matter — "boil water" can never be ignored, but kettle brand can.

اردو میں سمجھیں

ایبسٹریکشن (Abstraction) کا مطلب ہے غیر ضروری تفصیلات کو چھپا کر صرف ضروری باتوں پر توجہ دینا۔ چائے بنانے کی مثال میں پانی ابالنا، پتی ڈالنا، دم دینا، کپ میں ڈالنا اور پیش کرنا ضروری مراحل ہیں؛ چائے کی قسم یا چینی متغیرات (Variables) ہیں؛ جبکہ کیتلی کا برانڈ یا کپ کا رنگ فالتو باتیں (Noise) ہیں جنہیں نظر انداز کیا جاتا ہے۔

CHECK YOURSELF

1. What is "noise" in abstraction?
2. In the tea example, is "sugar or lemon" a necessary step, a variable, or noise?
3. How is abstraction different from decomposition?

Answers: 1. Unnecessary details that do not affect the solution. 2. A variable (it changes with the situation). 3. Decomposition breaks a problem into parts; abstraction hides details that are not important.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is "noise" in abstraction?

3 marks. Explain Abstraction with two clear points and one example.

5 marks. Write a 5-mark answer on Abstraction: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Unnecessary details that do not affect the solution 3. Changes based on the situation — these become variables (inputs) in the algorithm.; Abstraction items (noise) — details you can ignore completely. 5. Use the recipe in the blue box. Model opening: Abstraction means hiding unnecessary features and focusing only on the essential ones needed to solve a problem.

BATCH HOMEWORK

Write a 5-mark answer on **Abstraction** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.4 Sorting and Searching Algorithms

ACADEMY SESSION

Session 6 of 11 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Sorting and searching are both fundamental techniques of computer science.

Error clinic: Position 1 in the textbook algorithm is index 0 in Python.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Sorting and Searching Algorithms**. Write: Sorting and searching are both fundamental techniques of computer science.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) They work on lists of the same data type (for example, a list of all integers or a list of all names). (2) SortingSearching Arranging a collection of items in an order. — + example.

5 marks: 3-mark structure + table: Sorting / Searching + the worked example from this topic.

LEARN IT

Sorting and searching are both fundamental techniques of computer science. They work on **lists of the same data type** (for example, a list of all integers or a list of all names).

Sorting	Searching
Arranging a collection of items in an order. The order may be ascending (0–9, A–Z) or descending (9–0, Z–A). Used to organise data.	Locating a specific element within a list to find its position or check its existence (is it there or not?).
Examples: Bubble Sort, Selection Sort	Examples: Linear Search, Binary Search
Real life: merit list arranged from highest to lowest marks.	Real life: finding your roll number in the merit list.

Notation you will see

- **DATA** — the list (array). `DATA[1]` is the 1st element in the textbook algorithms (counting starts at 1).
- In **pseudocode and Python** counting starts at **0**: `DATA[0]` is the 1st element. This is called an **index**.
- **N** — the number of elements in the list.
- **PTR** (pointer) — a variable that holds the current position.
- **temp** — a temporary variable used to **swap** (exchange) two values.
- **Pass** — one complete run of the inner loop over the list.

WORKED EXAMPLE

How a swap works with temp. Suppose $A = 8$ and $B = 4$. To exchange them:

`temp = A (temp = 8)` → `A = B (A = 4)` → `B = temp (B = 8)`

Without `temp`, writing `A = B` first would destroy the 8. In Python you may also write `a, b = b, a`.

COMMON MISTAKE

Position 1 in the textbook algorithm is index 0 in Python. In exams, if a question uses `DATA[1]`, count from 1; if it uses Python, count from 0. State clearly which one you use.

اردو میں سمجھیں

سارٹنگ (Sorting) کا مطلب ہے ڈیٹا کو صعودی (چھوٹے سے بڑے) یا نزولی (بڑے سے چھوٹے) ترتیب میں رکھنا۔ سرچنگ (Searching) کا مطلب ہے فہرست میں کسی خاص چیز کو تلاش کرنا تاکہ اس کی جگہ یا موجودگی معلوم ہو سکے۔ دونوں ایک ہی قسم کے ڈیٹا کی فہرست پر کام کرتے ہیں۔

CHECK YOURSELF

1. Arrange C, A, D, B in descending order.
2. What is the purpose of the variable `temp`?

Answers: 1. D, C, B, A. 2. It temporarily holds one value so that two values can be swapped without losing either.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Arrange C, A, D, B in descending order.

3 marks. Explain Sorting and Searching Algorithms with two clear points and one example.

5 marks. Write a 5-mark answer on Sorting and Searching Algorithms: definition, two points, a labelled diagram or table, and one example.

Answers: 1. D, C, B, A 3. They work on lists of the same data type (for example, a list of all integers or a list of all names).; SortingSearching Arranging a collection of items in an order. 5. Use the recipe in the blue box. Model opening: Sorting and searching are both fundamental techniques of computer science.

BATCH HOMEWORK

Write a 5-mark answer on **Sorting and Searching Algorithms** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.4.1 Sorting Algorithms: Bubble Sort ★ Golden

ACADEMY SESSION

Session 7 of 11 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Bubble Sort is an elementary sorting algorithm that works by repeatedly comparing adjacent (side-by-side) elements and swapping them if they are in the wrong order.

Error clinic: The slides say the time grows "exponentially".

Exam wording to train: The most common question: "Sort the list ... using Bubble Sort."

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Sorting Algorithms: Bubble Sort**. Write: Bubble Sort is an elementary sorting algorithm that works by repeatedly comparing adjacent (side-by-side) elements and swapping them if they are in the wrong order.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) In each pass, the largest remaining value "bubbles up" to the end of the list, like an air bubble rising to the top of water. (2) So after pass 1 the largest value is in the last place, after pass 2 the second largest is in second-last place, and so on. — + example.

5 marks: 3-mark structure + table: Comparison / Pair / Left > Right? / Action / List after + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Bubble Sort is an elementary sorting algorithm that works by repeatedly comparing **adjacent** (side-by-side) elements and swapping them if they are in the wrong order.

In each pass, the largest remaining value "bubbles up" to the end of the list, like an air bubble rising to the top of water. So after pass 1 the largest value is in the last place, after pass 2 the second largest is in second-last place, and so on. A list of N items needs **$N - 1$ passes**, and pass K makes **$N - K$ comparisons**.



Algorithm (textbook)

```
Step 1: Start
Step 2: Set DATA := {8,4,1,9,3}
Step 3: Set N := 5
Step 4: Repeat Step 5 and 6 for
        K = 1 to N-1
Step 5: Set PTR := 1
Step 6: Repeat while PTR ≤ N-K:
    a: If DATA[PTR] > DATA[PTR+1]:
        1. Set temp = DATA[PTR]
        2. Set DATA[PTR] = DATA[PTR+1]
        3. Set DATA[PTR+1] = temp
    b: Set PTR := PTR + 1
Step 7: End
```

Pseudocode

```
Start
DATA = {8,4,1,9,3}
N = 5
For outer = 0 to N-1
    For inner = 0 to N-2-outer
        IF DATA[inner] > DATA[inner+1]
            Temp = DATA[inner]
            DATA[inner] = DATA[inner+1]
            DATA[inner+1] = Temp
        End If
    End For
End For
End
```


WORKED EXAMPLE

Worked example: sort 8, 4, 1, 9, 3 in ascending order. The pair in brackets [] is being compared. Positions are counted from 1.

Pass 1 (K = 1, 4 comparisons)

Comparison	Pair	Left > Right?	Action	List after
1st vs 2nd	[8, 4], 1, 9, 3	8 > 4 Yes	Swap	4, 8, 1, 9, 3
2nd vs 3rd	4, [8, 1], 9, 3	8 > 1 Yes	Swap	4, 1, 8, 9, 3
3rd vs 4th	4, 1, [8, 9], 3	8 > 9 No	No change	4, 1, 8, 9, 3
4th vs 5th	4, 1, 8, [9, 3]	9 > 3 Yes	Swap	4, 1, 8, 3, 9

9 is now at its correct (final) place.

Pass 2 (K = 2, 3 comparisons)

Comparison	Pair	Left > Right?	Action	List after
1st vs 2nd	[4, 1], 8, 3, 9	4 > 1 Yes	Swap	1, 4, 8, 3, 9
2nd vs 3rd	1, [4, 8], 3, 9	4 > 8 No	No change	1, 4, 8, 3, 9
3rd vs 4th	1, 4, [8, 3], 9	8 > 3 Yes	Swap	1, 4, 3, 8, 9

Pass 3 (K = 3, 2 comparisons)

Comparison	Pair	Left > Right?	Action	List after
1st vs 2nd	[1, 4], 3, 8, 9	1 > 4 No	No change	1, 4, 3, 8, 9
2nd vs 3rd	1, [4, 3], 8, 9	4 > 3 Yes	Swap	1, 3, 4, 8, 9

Pass 4 (K = 4, 1 comparison)

Comparison	Pair	Left > Right?	Action	List after
1st vs 2nd	[1, 3], 4, 8, 9	1 > 3 No	No change	1, 3, 4, 8, 9

Sorted list: 1, 3, 4, 8, 9. Totals: $4 + 3 + 2 + 1 = 10$ comparisons and **6 swaps**.

Pass	List after pass	Fixed at the end
Start	8, 4, 1, 9, 3	—
1	4, 1, 8, 3, 9	9
2	1, 4, 3, 8, 9	8, 9
3	1, 3, 4, 8, 9	4, 8, 9
4	1, 3, 4, 8, 9	all

WORKED EXAMPLE

Bubble Sort in Python (follows the pseudocode exactly; Python indexes start at 0):

```
data = [8, 4, 1, 9, 3]
n = len(data)
for outer in range(n - 1):
    for inner in range(n - 1 - outer):
        if data[inner] > data[inner + 1]:
            temp = data[inner]
            data[inner] = data[inner + 1]
            data[inner + 1] = temp
    print("After pass", outer + 1, ":", data)
print("Sorted list:", data)
```

OUTPUT

```
After pass 1 : [4, 1, 8, 3, 9]
After pass 2 : [1, 4, 3, 8, 9]
After pass 3 : [1, 3, 4, 8, 9]
After pass 4 : [1, 3, 4, 8, 9]
Sorted list: [1, 3, 4, 8, 9]
```

`range(n - 1 - outer)` gives `inner = 0 ... N-2-outer`, exactly as in the pseudocode. Notice the list was already sorted after pass 3, but the plain algorithm still does pass 4.

Advantages and disadvantages

Advantages	Disadvantages
Easiest algorithm to visualise and explain.	Uses nested loops, so the time grows very fast as the list grows (about N^2 comparisons).
Does not need extra memory (in-place sorting).	Performs a massive number of swaps.
Stable (equal items stay in their original order).	Useless for real-world "Big Data".

REMEMBER IT

Bubble = neighbours. Bubble Sort only ever compares *neighbours* (j and $j+1$). Each pass pushes the biggest bubble to the end. For **descending** order, just change `>` to `<` in the comparison.

COMMON MISTAKE

The slides say the time grows "exponentially". Strictly, Bubble Sort's time grows **quadratically**: for N items it makes $N(N-1)/2$ comparisons, which is $O(N^2)$. Doubling the list makes it about 4 times slower — bad, but not exponential. Another common mistake: students forget that pass K does only $N - K$ comparisons; the sorted tail is never compared again.

اردو میں سمجھیں

بل سارٹ (Bubble Sort) میں ساتھ ساتھ موجود دو عناصر کا موازنہ کیا جاتا ہے اور اگر وہ غلط ترتیب میں ہوں تو ان کی جگہ بدل دی جاتی ہے۔ ہر پاس (Pass) کے بعد سب سے بڑا عدد آخر میں پہنچ جاتا ہے۔ N عناصر کے لیے $N-1$ پاس درکار ہوتے ہیں۔ یہ سمجھنے میں آسان اور مستحکم (Stable) ہے لیکن بڑے ڈیٹا کے لیے بہت سست ہے۔

EXAM TIP

The most common question: "Sort the list ... using Bubble Sort. Show each pass." Draw one table per pass with columns *Pair*, *Compare*, *Action*, *List after*. Mark the element fixed at the end after every pass. Also be ready to write the algorithm (with PTR and K) or the pseudocode (with outer/inner), and to list two advantages and two disadvantages.

CHECK YOURSELF

1. How many passes and comparisons does Bubble Sort need for 6 elements?
2. Show the list 5, 1, 4 after pass 1 of Bubble Sort.
3. Sort 2, 9, 4, 7 in descending order with Bubble Sort: give the list after each pass.

Answers: 1. 5 passes; $5 + 4 + 3 + 2 + 1 = 15$ comparisons. 2. (5,1) swap $\rightarrow$ 1, 5, 4; (5,4) swap $\rightarrow$ 1, 4, 5. 3. Pass 1: 9, 4, 7, 2; Pass 2: 9, 7, 4, 2; Pass 3: 9, 7, 4, 2.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. How many passes and comparisons does Bubble Sort need for 6 elements?

3 marks. Explain Sorting Algorithms: Bubble Sort with two clear points and one example.

5 marks. The most common question: "Sort the list ... using Bubble Sort. Show each pass." Draw one table per pass with columns Pair, Compare, Action, List after. Mark the element fixed at the end after every...

8 marks. Sorting Algorithms: Bubble Sort: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. 5 passes; $5 + 4 + 3 + 2 + 1 = 15$ comparisons 3. In each pass, the largest remaining value "bubbles up" to the end of the list, like an air bubble rising to the top of water.; So after pass 1 the largest value is in the last place, after pass 2 the second largest is in second-last place,... 5. Use the recipe in the blue box. Model opening: Bubble Sort is an elementary sorting algorithm that works by repeatedly comparing adjacent (side-by-side) elements and swapping them if they are in the wrong... 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Sorting Algorithms: Bubble Sort** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.4.1 Sorting Algorithms: Selection Sort ★ Golden

ACADEMY SESSION

Session 8 of 11 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Selection Sort is a simple sorting algorithm that works by repeatedly selecting the smallest element from the unsorted portion of the list and moving it to its correct position at the front.

Error clinic: In the textbook method, the comparison is always with the fixed position DATA[K] (Pos1 in pass 1, Pos2 in pass 2), not with the neighbour.

Exam wording to train: Typical questions: "Sort ... using Selection Sort, showing all steps", "Differentiate between Bubble Sort and Selection Sort" and "Why is Selection Sort not..."

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Sorting Algorithms: Selection Sort**. Write: Selection Sort is a simple sorting algorithm that works by repeatedly selecting the smallest element from the unsorted portion of the list and moving it to its correct position at the front.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Think of it as filling seats from the front: first find who belongs in position 1, then position 2, and so on. (2) In the textbook version, the element at position K is compared with every element after it; whenever a smaller one is found, the two are... — + example.

5 marks: 3-mark structure + table: Compare / List / Pos1 > PosX? / Action / List after + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Selection Sort is a simple sorting algorithm that works by repeatedly **selecting the smallest element** from the unsorted portion of the list and moving it to its correct position at the front.

Think of it as filling seats from the front: first find who belongs in position 1, then position 2, and so on. In the textbook version, the element at position K is compared with every element after it; whenever a smaller one is found, the two are swapped. So at the end of pass K, the K-th smallest value sits in position K.



Algorithm (textbook)

```
Step 1: Start
Step 2: Set DATA := {8,4,1,9,3}
Step 3: Set N := 5
Step 4: Repeat Step 5 and 6 for
        K = 1 to N
Step 5: Set PTR := K+1
Step 6: Repeat while PTR ≤ N:
    a: If DATA[K] > DATA[PTR]:
        1. Set temp = DATA[K]
        2. Set DATA[K] = DATA[PTR]
        3. Set DATA[PTR] = temp
    b: Set PTR := PTR + 1
Step 7: End
```

Pseudocode

```
Start
DATA = {8,4,1,9,3}
N = 5
For outer = 0 to N-1
    For inner = outer+1 to N-1
        IF DATA[outer] > DATA[inner]
            Temp = DATA[outer]
            DATA[outer] = DATA[inner]
            DATA[inner] = Temp
        End If
    End For
End For
End
```

REMEMBER IT

Teacher's tip — spot the difference: in Selection Sort the inner loop starts at `outer + 1` and compares with the *fixed* position `DATA[outer]`. In Bubble Sort the inner loop always starts at `0` and compares *neighbours* `DATA[inner]` and `DATA[inner+1]`. Bubble pushes the largest to the **end**; Selection brings the smallest to the **front**.

WORKED EXAMPLE

Worked example: sort 8, 4, 1, 9, 3 in ascending order (textbook method). The two positions in brackets are being compared.

Pass 1 — find the smallest for Position 1

Compare	List	Pos1 > PosX?	Action	List after
Pos1 vs Pos2	[8], [4], 1, 9, 3	8 > 4 Yes	Swap	4, 8, 1, 9, 3
Pos1 vs Pos3	[4], 8, [1], 9, 3	4 > 1 Yes	Swap	1, 8, 4, 9, 3
Pos1 vs Pos4	[1], 8, 4, [9], 3	1 > 9 No	No change	1, 8, 4, 9, 3
Pos1 vs Pos5	[1], 8, 4, 9, [3]	1 > 3 No	No change	1 , 8, 4, 9, 3

1 is now permanently in Position 1.

Pass 2 — find the smallest for Position 2

Compare	List	Pos2 > PosX?	Action	List after
Pos2 vs Pos3	1, [8], [4], 9, 3	8 > 4 Yes	Swap	1, 4, 8, 9, 3
Pos2 vs Pos4	1, [4], 8, [9], 3	4 > 9 No	No change	1, 4, 8, 9, 3
Pos2 vs Pos5	1, [4], 8, 9, [3]	4 > 3 Yes	Swap	1, 3 , 8, 9, 4

Pass 3 — find the smallest for Position 3

Compare	List	Pos3 > PosX?	Action	List after
Pos3 vs Pos4	1, 3, [8], [9], 4	8 > 9 No	No change	1, 3, 8, 9, 4
Pos3 vs Pos5	1, 3, [8], 9, [4]	8 > 4 Yes	Swap	1, 3, 4 , 9, 8

Pass 4 — find the smallest for Position 4

Compare	List	Pos4 > PosX?	Action	List after
Pos4 vs Pos5	1, 3, 4, [9], [8]	9 > 8 Yes	Swap	1, 3, 4, 8, 9

Sorted list: 1, 3, 4, 8, 9. Totals: 4 + 3 + 2 + 1 = **10 comparisons, 6 swaps** in this textbook method.

Pass	List after pass	Fixed at the front
Start	8, 4, 1, 9, 3	—
1	1, 8, 4, 9, 3	1
2	1, 3, 8, 9, 4	1, 3
3	1, 3, 4, 9, 8	1, 3, 4
4	1, 3, 4, 8, 9	all

WORKED EXAMPLE

Selection Sort in Python (follows the textbook pseudocode):

```
data = [8, 4, 1, 9, 3]
n = len(data)
for outer in range(n - 1):
    for inner in range(outer + 1, n):
        if data[outer] > data[inner]:
            temp = data[outer]
            data[outer] = data[inner]
            data[inner] = temp
    print("After pass", outer + 1, ":", data)
print("Sorted list:", data)
```

OUTPUT

```
After pass 1 : [1, 8, 4, 9, 3]
After pass 2 : [1, 3, 8, 9, 4]
After pass 3 : [1, 3, 4, 9, 8]
After pass 4 : [1, 3, 4, 8, 9]
Sorted list: [1, 3, 4, 8, 9]
```

WORKED EXAMPLE

The "classic" Selection Sort (one swap per pass). Many books first *find the position of the smallest value* in the unsorted part, and swap only once at the end of each pass. The result is the same; only the swaps are fewer.

```
data = [8, 4, 1, 9, 3]
n = len(data)
for outer in range(n - 1):
    smallest = outer
    for inner in range(outer + 1, n):
        if data[inner] < data[smallest]:
            smallest = inner
    data[outer], data[smallest] = data[smallest], data[outer]
    print("After pass", outer + 1, ":", data)
```

OUTPUT

```
After pass 1 : [1, 4, 8, 9, 3]
After pass 2 : [1, 3, 8, 9, 4]
After pass 3 : [1, 3, 4, 9, 8]
After pass 4 : [1, 3, 4, 8, 9]
```

Here only 4 swaps are made (at most $N - 1$). This is why Selection Sort is said to perform fewer swaps than Bubble Sort. In exams, use the textbook method unless the question asks otherwise.

Advantages and disadvantages

Advantages	Disadvantages
Very easy to code.	Time grows very fast with list size (nested loops, about N^2 comparisons).
Performs fewer swaps overall compared to Bubble Sort.	Must finish every single loop — it is "blind" to an already sorted list.
Does not need extra memory.	Not stable (it might change the relative positions of equal items).

WORKED EXAMPLE

Why "not stable"? Take two equal marks, 5_a (Ali) and 5_b (Bilal), in the list $5_a, 5_b, 2$. Pass 1 compares 5_a with 5_b (no swap), then 5_a with $2 \rightarrow \text{swap} \rightarrow 2, 5_b, 5_a$. Now Bilal is before Ali, although Ali came first originally. Bubble Sort never does this, because it swaps only neighbours that are strictly out of order.

COMMON MISTAKE

In the textbook method, the comparison is always with the **fixed position** DATA[K] (Pos1 in pass 1, Pos2 in pass 2), not with the neighbour. Students often mix this up with Bubble Sort and compare neighbours. Also, after a swap, the *new* value at Pos K is used for the next comparison.

اردو میں سمجھیں

سلیکشن سارٹ (Selection Sort) میں فہرست کے غیر ترتیب شدہ حصے سے سب سے چھوٹا عدد چن کر اسے سامنے اس کی درست جگہ پر رکھا جاتا ہے۔ ہر پاس میں ایک مقررہ جگہ (Position) کا موازنہ اس کے بعد والے تمام عناصر سے ہوتا ہے۔ اس کا کوڈ آسان ہے اور ببل سارٹ سے کم تبادلے (Swaps) ہوتے ہیں، لیکن یہ مستحکم (Stable) نہیں اور ترتیب شدہ فہرست پر بھی پورے لوپ چلاتا ہے۔

EXAM TIP

Typical questions: "Sort ... using Selection Sort, showing all steps", "Differentiate between Bubble Sort and Selection Sort" and "Why is Selection Sort not stable?" In the difference question mention: what is compared (neighbours vs fixed position), where the inner loop starts (0 vs outer+1), where items settle (end vs front), stability, and number of swaps.

CHECK YOURSELF

1. In Selection Sort, where does the inner loop start?
2. Using the textbook method, show 7, 2, 5 after pass 1.
3. Which of the two sorts is stable?

Answers: 1. At outer + 1 (PTR = K + 1). 2. Pos1 vs Pos2: $7 > 2 \rightarrow \text{swap} \rightarrow 2, 7, 5$; Pos1 vs Pos3: $2 > 5$ no $\rightarrow 2, 7, 5$. 3. Bubble Sort.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. In Selection Sort, where does the inner loop start?

3 marks. Explain Sorting Algorithms: Selection Sort with two clear points and one example.

5 marks. Typical questions: "Sort ... using Selection Sort, showing all steps", "Differentiate between Bubble Sort and Selection Sort" and "Why is Selection Sort not stable?" In the difference question mention:...

8 marks. Sorting Algorithms: Selection Sort: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. At outer + 1 (PTR = K + 1) 3. Think of it as filling seats from the front: first find who belongs in position 1, then position 2, and so on.; In the textbook version, the element at position K is compared with every element after it; whenever a smaller one is found,... 5. Use the recipe in the blue box. Model opening: Selection Sort is a simple sorting algorithm that works by repeatedly selecting the smallest element from the unsorted portion of the list and moving it to its... 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Sorting Algorithms: Selection Sort** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.4.2 Searching Algorithms: Linear Search

ACADEMY SESSION

Session 9 of 11 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Linear Search, also known as sequential search, works by examining each element in the list one by one, from the start, until the target is found (or the list ends).

Error clinic: Do not print "Not Found" inside the loop after every mismatch — that would print it many times.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Searching Algorithms: Linear Search**. Write: Linear Search, also known as sequential search, works by examining each element in the list one by one, from the start, until the target is found (or the list ends).

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It works on both sorted and unsorted data. (2) A flag variable (here ValueFound) starts at 0 and becomes 1 when the item is found. — + example.

5 marks: 3-mark structure + table: Step / Element checked / Condition ($== 7$) / Result + the worked example from this topic.

LEARN IT

Linear Search, also known as **sequential search**, works by examining each element in the list one by one, from the start, until the target is found (or the list ends). It works on both **sorted and unsorted** data.

A **flag** variable (here `ValueFound`) starts at 0 and becomes 1 when the item is found. After the loop, the flag tells us whether to print the item or "Not Found".

PTR = first → DATA[PTR] = FindValue? → Yes: ValueFound = 1, exit → No: PTR = PTR + 1 →

List ended? print "Not Found"

Algorithm (textbook)

```
Step 1: Start
Step 2: DATA := {8,3,6,1,7,2,4,5}
Step 3: N := 8
Step 4: FindValue := 7
Step 5: ValueFound := 0
Step 6: Repeat for PTR = 1 to N
Step 7:   If DATA[PTR] = FindValue:
           a. ValueFound = 1
           b. Goto Step 8
Step 8: If ValueFound = 1:
           Print DATA[PTR]
       Else:
           Print "Not Found"
Step 9: End
```

Pseudocode

```
Start
DATA = {8, 3, 6, 1, 7, 2, 4, 5}
N = 8
FindValue = 7
ValueFound = 0
For PTR = 0 to N-1
    If DATA[PTR] = FindValue then
        ValueFound = 1
        Exit Loop
    End If
End For
If ValueFound = 1 then
    Print DATA[PTR]
Else
    Print "Data Not Found"
End If
End
```

WORKED EXAMPLE

Worked example. Data list: 8, 3, 6, 1, 7, 2, 4, 5. Searching item: 7.

Step	Element checked	Condition (== 7)	Result
1	8	8 == 7 ?	Not found
2	3	3 == 7 ?	Not found
3	6	6 == 7 ?	Not found
4	1	1 == 7 ?	Not found
5	7	7 == 7 ?	Found! (Exit loop)

7 is found at position 5 (index 4) after 5 comparisons. The remaining items 2, 4, 5 are never checked.

If the item is missing — e.g., search for 9 — all 8 elements are checked, the flag stays 0, and "Data Not Found" is printed. This is the **worst case**: N comparisons.

WORKED EXAMPLE

Linear Search in Python

```
data = [8, 3, 6, 1, 7, 2, 4, 5]
find_value = 7
value_found = 0
for ptr in range(len(data)):
    print("Step", ptr + 1, ": checking", data[ptr])
    if data[ptr] == find_value:
        value_found = 1
        break
if value_found == 1:
    print("Found", data[ptr], "at position", ptr + 1)
else:
    print("Data Not Found")
```

OUTPUT

```
Step 1 : checking 8
Step 2 : checking 3
Step 3 : checking 6
Step 4 : checking 1
Step 5 : checking 7
Found 7 at position 5
```

break is Python's "Exit Loop".

Advantages and disadvantages

Advantages	Disadvantages
Does not care whether data is scrambled or sorted.	If the target is at the end of 1 million items, it does 1 million checks.
Extremely simple code (one loop, one if statement).	Time grows linearly (double the list = double the time).
Faster for very small lists (no setup time, such as sorting).	Inefficient if you need to search the same list thousands of times.
Does not require any extra space.	

REMEMBER IT

Linear Search is like looking for your friend in a queue by checking every face from the front. Best case: 1 check (first person). Worst case: N checks (last person or not there).

COMMON MISTAKE

Do not print "Not Found" inside the loop after every mismatch — that would print it many times. Decide only **after** the loop ends, using the flag. And remember to **exit the loop** once the item is found, or you waste comparisons.

اردو میں سمجھیں

لینیئر سرچ (Linear Search) کو ترتیب وار تلاش (Sequential Search) بھی کہتے ہیں۔ اس میں فہرست کے ہر عنصر کو شروع سے ایک ایک کر کے چیک کیا جاتا ہے جب تک مطلوبہ چیز نہ مل جائے۔ یہ ترتیب شدہ اور غیر ترتیب شدہ دونوں قسم کے ڈیٹا پر کام کرتی ہے اور بہت سادہ ہے، لیکن بڑی فہرست میں بہت وقت لیتی ہے۔

CHECK YOURSELF

1. What is another name for Linear Search?
2. In 8, 3, 6, 1, 7, 2, 4, 5, how many comparisons are needed to find 2?
3. What is the purpose of the variable ValueFound?

Answers: 1. Sequential search. 2. 6 comparisons (2 is in position 6). 3. It is a flag: 0 means not found yet, 1 means found; it decides what to print after the loop.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is another name for Linear Search?

3 marks. Explain Searching Algorithms: Linear Search with two clear points and one example.

5 marks. Write a 5-mark answer on Searching Algorithms: Linear Search: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Sequential search 3. It works on both sorted and unsorted data.; A flag variable (here ValueFound) starts at 0 and becomes 1 when the item is found. 5. Use the recipe in the blue box. Model opening: Linear Search, also known as sequential search, works by examining each element in the list one by one, from the start, until the target is found (or the list...

BATCH HOMEWORK

Write a 5-mark answer on **Searching Algorithms: Linear Search** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.4.2 Searching Algorithms: Binary Search ★ Golden

ACADEMY SESSION

Session 10 of 11 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Binary Search is a highly efficient search algorithm that works by repeatedly dividing the search interval in half.

Error clinic: The slide's pseudocode writes the loop condition as $BEG = 0$; the check should simply be "LOC is not NULL" (or, with $LOC = 0$ meaning not found, " $LOC > 0$ ").

Exam wording to train: You will usually be given a sorted list and an item and asked to "search using Binary Search, showing all steps".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Searching Algorithms: Binary Search**. Write: Binary Search is a highly efficient search algorithm that works by repeatedly dividing the search interval in half.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) END (high) — last position of the current part. (2) $MID = INT((BEG + END) / 2)$ — the middle position. INT means "drop the decimal part". — + example.

5 marks: 3-mark structure + table: Step / BEG (low) / END (high) / MID / DATA[MID] / Compare + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Binary Search is a highly efficient search algorithm that works by repeatedly dividing the search interval in half.

Crucial limitation: it only works on a SORTED list.


Three variables mark the part of the list still being searched:

- **BEG** (low) — first position of the current part.
- **END** (high) — last position of the current part.
- **MID** = $INT((BEG + END) / 2)$ — the middle position. INT means "drop the decimal part".

At each step compare the item with DATA[MID]:

- Equal → found, stop.
- Item < DATA[MID] → the item can only be in the **left** half: set $END = MID - 1$.
- Item > DATA[MID] → the item can only be in the **right** half: set $BEG = MID + 1$.

If BEG becomes greater than END, the part is empty and the item is **not in the list**.



Algorithm (textbook summary)

```

Step 1: Start
Step 2: DATA := {1,2,3,4,5,6,7,8,9}
         (Sorted)
Step 3: BEG = 1, END = 9
Step 4: MID = INT((BEG+END)/2)
Step 5: Item = 7
Step 6: LOC = 0
Step 7: Repeat while BEG ≤ END AND
        DATA[MID] ≠ Item
Step 8:   If Item < DATA[MID]:
            END = MID - 1
        Else:
            BEG = MID + 1
Step 9:   MID = INT((BEG+END)/2)
Step 10: [End loop]
Step 11: If DATA[MID] = Item:
            LOC = MID
        Else:
            LOC = 0
Step 12: Print result based on LOC
Step 13: End
  
```

Pseudocode

```

Start
DATA = {1,2,3,4,5,6,7,8,9}
BEG = 1, END = 9
MID = INT((BEG+END)/2)
Item = 7
LOC = NULL
While BEG ≤ END AND DATA[MID] ≠ Item
  If Item < DATA[MID] then
    END = MID - 1
  Else
    BEG = MID + 1
  End If
  MID = INT((BEG+END)/2)
End While
If DATA[MID] = Item then
  LOC = MID
Else
  LOC = NULL
End If
If LOC ≠ NULL then
  Print DATA[MID]
Else
  Print "Not Found"
End If
End
  
```

COMMON MISTAKE

The slide's pseudocode writes the loop condition as `BEG ≤ END OR DATA[MID] ≠ Item`. That is a slip: with OR the loop would never stop once the item is found while `BEG ≤ END`. The textbook algorithm (Step 7) correctly uses **AND** — keep going only while the part is not empty *and* the item is not yet found. Likewise, the slide sets `LOC = NULL` but then tests "`LOC ≥ 0`"; the check should simply be "`LOC is not NULL`" (or, with `LOC = 0` meaning not found, "`LOC > 0`"). The pseudocode above shows the corrected form.

WORKED EXAMPLE

Worked example 1 (textbook algorithm). DATA = 1, 2, 3, 4, 5, 6, 7, 8, 9; Item = 7. Positions 1 to 9.

Step	BEG (low)	END (high)	MID	DATA[MID]	Compare	Action
1	1	9	INT(10/2) = 5	5	7 > 5	BEG = 6 (go right)
2	6	9	INT(15/2) = 7	7	7 = 7	Found, LOC = 7

Only **2 comparisons**. Linear Search would need 7.

WORKED EXAMPLE

Worked example 2 (slide example). Sorted list: 1, 2, 3, 4, 5, 6, 7, 8. Searching item: 3.

Step	BEG (low)	END (high)	MID	DATA[MID]	Compare	Action
1	1	8	$\text{INT}(9/2) = 4$	4	$3 < 4$	END = 3 (go left)
2	1	3	$\text{INT}(4/2) = 2$	2	$3 > 2$	BEG = 3 (go right)
3	3	3	$\text{INT}(6/2) = 3$	3	$3 = 3$	FOUND at position 3

Picture the list shrinking (the highlighted cell is MID):

Step	1	2	3	4	5	6	7	8
1	1	2	3	4	5	6	7	8
2	1	2	3					
3			3					

The slide describes the same steps using the size of each sub-list: Step 1 $\text{MID} = 8/2 = 4$ (value 4), $3 < 4$, go left; Step 2 sub-list [1, 2, 3], middle = $3/2 = 1.5 \rightarrow$ 2nd item (value 2), $3 > 2$, go right; Step 3 sub-list [3], middle = 1st item (value 3), FOUND. Both ways land on the same values $4 \rightarrow 2 \rightarrow 3$.

WORKED EXAMPLE

Binary Search in Python (index starts at 0, so positions 1–8 become indexes 0–7):

```
data = [1, 2, 3, 4, 5, 6, 7, 8]
item = 3
beg = 0
end = len(data) - 1
loc = -1
step = 0
while beg ≤ end:
    mid = (beg + end) // 2
    step = step + 1
    print("Step", step, ": beg =", beg, "mid =", mid, "end =", end, "value =", data[mid])
    if data[mid] == item:
        loc = mid
        break
    elif item < data[mid]:
        end = mid - 1
    else:
        beg = mid + 1
if loc ≥ 0:
    print("Found", item, "at index", loc)
else:
    print("Not Found")
```

OUTPUT

```
Step 1 : beg = 0 mid = 3 end = 7 value = 4
Step 2 : beg = 0 mid = 1 end = 2 value = 2
Step 3 : beg = 2 mid = 2 end = 2 value = 3
Found 3 at index 2
```

// is integer division, the same as `INT()`. Index 2 is position 3. Here `loc = -1` means "not found", so the test `loc ≥ 0` is correct.

Why is it so fast?

Every comparison throws away half of the remaining list. $1,000,000 \rightarrow 500,000 \rightarrow 250,000 \rightarrow \dots \rightarrow 1$ takes about 20 halvings, because $2^{20} = 1,048,576$. So Binary Search finds an item among 1 million elements in at most about **20 steps**, while Linear Search may need 1,000,000.

Advantages and disadvantages

Advantages	Disadvantages
Extremely fast for "Big Data": finds an item in 1M elements in just ~20 steps.	The list must be sorted first; it fails on scrambled data.
Massive time savings for static lists that are searched repeatedly.	Requires random access to elements (works on arrays, not easily on linked lists).
	More complex code, prone to logic errors (off-by-one).

REMEMBER IT

Binary Search is how you find a word in a dictionary: open the middle, decide "before or after?", and throw away half the book each time. **"Sorted first, then split."**

COMMON MISTAKE

Common errors: (1) using Binary Search on an unsorted list — the answer will be wrong; (2) setting $END = MID$ instead of $MID - 1$ (or $BEG = MID$ instead of $MID + 1$), which can cause an infinite loop — this is the "off-by-one" error; (3) forgetting INT , so MID becomes a decimal like 4.5.

اردو میں سمجھیں

بائنری سرچ (Binary Search) ایک تیز رفتار طریقہ ہے جو ہر قدم پر تلاش کے حصے کو آدھا کر دیتا ہے۔ یہ صرف ترتیب شدہ (Sorted) فہرست پر کام کرتا ہے۔ درمیانی عنصر (MID) سے موازنہ کیا جاتا ہے: اگر مطلوبہ چیز چھوٹی ہو تو بائیں آدھے حصے میں، اور بڑی ہو تو دائیں آدھے حصے میں تلاش جاری رہتی ہے۔ دس لاکھ عناصر میں بھی تقریباً بیس قدموں میں نتیجہ مل جاتا ہے۔

EXAM TIP

You will usually be given a sorted list and an item and asked to "search using Binary Search, showing all steps". Always draw a table with **BEG, END, MID, DATA[MID], comparison, action**. Show the INT calculation for MID . If the item is absent, continue until $BEG > END$ and write "Not Found". Also learn: "Why must the list be sorted?" and "Compare Linear and Binary Search".

CHECK YOURSELF

1. What is the crucial condition for Binary Search to work?
2. $BEG = 6$, $END = 9$. What is MID ?
3. In 1, 2, 3, 4, 5, 6, 7, 8 (positions 1–8), list the MID values visited when searching for 8.

Answers: 1. The list must be sorted. 2. $INT(15/2) = 7$. 3. $MID = 4$ (value 4, go right, $BEG = 5$) $\rightarrow MID = INT(13/2) = 6$ (value 6, go right, $BEG = 7$) $\rightarrow MID = INT(15/2) = 7$ (value 7, go right, $BEG = 8$) $\rightarrow MID = 8$ (value 8, found). Four comparisons.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is the crucial condition for Binary Search to work?

3 marks. Explain Searching Algorithms: Binary Search with two clear points and one example.

5 marks. You will usually be given a sorted list and an item and asked to "search using Binary Search, showing all steps". Always draw a table with BEG, END, MID, DATA[MID], comparison, action. Show the INT...

8 marks. Searching Algorithms: Binary Search: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. The list must be sorted 3. END (high) — last position of the current part.; $MID = INT((BEG + END) / 2)$ — the middle position. INT means "drop the decimal part". 5. Use the recipe in the blue box. Model opening: Binary Search is a highly efficient search algorithm that works by repeatedly dividing the search interval in half. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Searching Algorithms: Binary Search** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.5 Evaluation Criteria of Algorithm

ACADEMY SESSION

Session 11 of 11 · 45 minutes (first half) · paired with How to Decide Which Algorithm to Use.

10–45 min — this topic. Lock the definition and table for **Evaluation Criteria of Algorithm**. Starter (0–10) is from last class. Second half is How to Decide Which Algorithm to Use.

On the board: Many algorithms can solve the same problem.

Error clinic: Testing only "normal" inputs is not enough to prove correctness.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Evaluation Criteria of Algorithm**. Write: Many algorithms can solve the same problem.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Many algorithms can solve the same problem. (2) To judge which is better, we evaluate them on three criteria: correctness, efficiency and clarity. — + example.

5 marks: 3-mark structure + table: Input / Operation (divide by 2, find remainder) / Remainder == 0? / Result + the worked example from this topic.

LEARN IT

Many algorithms can solve the same problem. To judge which is better, we evaluate them on three criteria: **correctness, efficiency and clarity.**

2.5.1 Correctness

An algorithm is **correct** if:

- its output matches the expected outcomes;
- it handles **edge cases** gracefully (unusual inputs such as an empty list, 0, a negative number, or an item that is not present);
- it is guaranteed to finish — no infinite loops.

We test correctness with a **trace table** (dry run): we feed sample inputs and record every value by hand, then compare the result with what we expect.

WORKED EXAMPLE

Trace table example: Even/Odd checker. Rule: divide the number by 2; if the remainder is 0 it is Even, otherwise Odd.

Input	Operation (divide by 2, find remainder)	Remainder == 0?	Result
3	3 / 2 (Quotient = 1, Remainder = 1)	No	Odd
6	6 / 2 (Quotient = 3, Remainder = 0)	Yes	Even
15	15 / 2 (Quotient = 7, Remainder = 1)	No	Odd

All three results match what we expect, so the algorithm is correct for these inputs. The same check in Python:

```
for number in [3, 6, 15]:
    remainder = number % 2
    if remainder == 0:
        print(number, "remainder", remainder, "→ Even")
    else:
        print(number, "remainder", remainder, "→ Odd")
```

OUTPUT

```
3 remainder 1 → Odd
6 remainder 0 → Even
15 remainder 1 → Odd
```

A good tester would also try the edge case 0 (remainder 0 → Even, which is correct).

2.5.2 Efficiency

We measure algorithm efficiency through **time** (speed) and **space** (memory). The key question is: how fast does it run as the input size grows — does it **scale** well?

Computer scientists describe growth with **Big O notation**. It counts roughly how many steps are needed for N items:

- **O(1)** — constant: same time, whatever N is.
- **O(log N)** — logarithmic: grows very slowly (Binary Search).
- **O(N)** — linear: double N, double the time (Linear Search).
- **O(N²)** — quadratic: double N, four times the time (Bubble and Selection Sort).

WORKED EXAMPLE

How the worst-case number of comparisons grows

N (items)	Linear Search (N)	Binary Search (about $\log_2 N$)	Bubble/Selection Sort $N(N-1)/2$
10	10	4	45
100	100	7	4,950
1,000	1,000	10	499,500
1,000,000	1,000,000	20	499,999,500,000

This is why Binary Search is called excellent for Big Data and the simple sorts are called useless for it.

2.5.3 Clarity (Readability)

An algorithm must be easy to read, understand and modify. It should use **clear steps**, **meaningful variable names** and **good indentation**.

Unclear

```
a=[3,6,15]
for x in a:
    if x%2==0:print(x,"E")
    else:print(x,"O")
```

Clear

```
numbers = [3, 6, 15]
for number in numbers:
    if number % 2 == 0:
        print(number, "Even")
    else:
        print(number, "Odd")
```

Both work, but the second is far easier for another person (or you, a month later) to understand and change.

REMEMBER IT

Remember **C-E-C**: **C**orrect (right answer, always finishes), **E**fficient (fast and light), **C**lear (easy to read).

COMMON MISTAKE

Testing only "normal" inputs is not enough to prove correctness. Always include edge cases in your trace table, e.g., the first item, the last item, a missing item, or an empty list in a search.

اردو میں سمجھیں

کسی الگورتھم کو تین معیارات پر پرکھا جاتا ہے: درستگی (Correctness) یعنی درست نتیجہ دے، غیر معمولی صورتوں کو سنبھالے اور ہمیشہ ختم ہو؛ کارکردگی (Efficiency) یعنی کم وقت اور کم میموری استعمال کرے؛ اور وضاحت (Clarity) یعنی پڑھنے، سمجھنے اور تبدیل کرنے میں آسان ہو۔ درستگی جانچنے کے لیے ٹریس ٹیبل (Trace Table) بنایا جاتا ہے۔

CHECK YOURSELF

1. Name the three evaluation criteria of an algorithm.
2. Give one example of an edge case for a search algorithm.
3. Efficiency is measured in terms of which two resources?

Answers: 1. Correctness, efficiency, clarity. 2. The item is not in the list (or the list is empty, or the item is the last element). 3. Time (speed) and space (memory).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name the three evaluation criteria of an algorithm.

3 marks. Explain Evaluation Criteria of Algorithm with two clear points and one example.

5 marks. Write a 5-mark answer on Evaluation Criteria of Algorithm: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Correctness, efficiency, clarity 3. Many algorithms can solve the same problem.; To judge which is better, we evaluate them on three criteria: correctness, efficiency and clarity. 5. Use the recipe in the blue box. Model opening: Many algorithms can solve the same problem.

BATCH HOMEWORK

Write a 5-mark answer on **Evaluation Criteria of Algorithm** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.6 How to Decide Which Algorithm to Use

ACADEMY SESSION

Session 11 of 11 · 45 minutes (second half) · paired with Evaluation Criteria of Algorithm.

45–75 min — this topic. Board working for **How to Decide Which Algorithm to Use**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Before choosing an algorithm, ask three questions: What is the input size?

Error clinic: "Binary Search is always better" is wrong.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **How to Decide Which Algorithm to Use**. Write: Before choosing an algorithm, ask three questions: What is the input size?

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Is the data sorted? (2) Do we need speed or memory efficiency? — + example.

5 marks: 3-mark structure + table: Algorithm / Type / Best case / Worst case / Extra memory / Needs sorted data? + the worked example from this topic.


LEARN IT

Before choosing an algorithm, ask three questions:

- **What is the input size?** (10 items or 10 million?)
- **Is the data sorted?**
- **Do we need speed or memory efficiency?**

Simple decision guide:

- If searching on **unsorted** data → use **Linear Search**.
- If searching on **sorted** data → use **Binary Search**.
- If data needs **ordering** → use a **sorting** algorithm.



Comparison of the four algorithms

Algorithm	Type	Best case	Worst case	Extra memory	Needs sorted data?	Stable?
Bubble Sort	Sorting	$O(N^2)$ as written; $O(N)$ with an early-stop check	$O(N^2)$	None — $O(1)$	—	Yes
Selection Sort	Sorting	$O(N^2)$	$O(N^2)$	None — $O(1)$	—	No
Linear Search	Searching	$O(1)$ (first item)	$O(N)$ (last item / absent)	None — $O(1)$	No	—
Binary Search	Searching	$O(1)$ (item at first MID)	$O(\log N)$	None — $O(1)$	Yes	—

Point	Bubble Sort	Selection Sort
What is compared	Adjacent elements (j and $j+1$)	Fixed position K with every later element
Inner loop starts at	0	outer + 1
After each pass	Largest moves to the end	Smallest moves to the front
Swaps	Many	Fewer
Stable	Yes	No

Point	Linear Search	Binary Search
Method	Checks one by one	Splits the list in half each step
Data required	Sorted or unsorted	Sorted only
Worst case (1M items)	1,000,000 checks	About 20 checks
Code	Very simple	More complex, off-by-one risk
Best for	Small or unsorted lists, one-off searches	Large, sorted lists searched many times

WORKED EXAMPLE

Choosing in practice

- **A shopkeeper's list of 15 items, written in random order, searched once:** Linear Search — the list is unsorted and tiny; sorting first would waste time.
- **NADRA looking up a CNIC number among millions of sorted records, thousands of times a day:** Binary Search — data is sorted, huge, and searched repeatedly.
- **A teacher arranging 40 students' marks into a merit list:** a sorting algorithm; for 40 items even Bubble or Selection Sort is acceptable.
- **An unsorted list of 1 million records that will be searched thousands of times:** sort it once, then use Binary Search for every search.

REMEMBER IT

Two keywords decide most exam answers: "**sorted?**" and "**how big?**". Unsorted or small → Linear. Sorted and big → Binary.

COMMON MISTAKE

"Binary Search is always better" is wrong. On unsorted data it does not work at all, and for a single search on a small unsorted list, sorting first costs more than a simple Linear Search.

اردو میں سمجھیں

الگورتھم چننے سے پہلے دیکھیں کہ ڈیٹا کتنا بڑا ہے، ترتیب شدہ ہے یا نہیں، اور ہمیں رفتار چاہیے یا میموری کی بچت۔ غیر ترتیب شدہ ڈیٹا میں تلاش کے لیے لینیئر سرچ، ترتیب شدہ ڈیٹا میں تلاش کے لیے بائنری سرچ، اور ڈیٹا کو ترتیب دینے کے لیے سارٹنگ الگورتھم استعمال کریں۔

CHECK YOURSELF

1. Which search would you use on an unsorted list of phone contacts?
2. What is the worst-case time complexity of Binary Search?
3. Which sort has the same time complexity in its best and worst case?

Answers: 1. Linear Search. 2. $O(\log N)$. 3. Selection Sort ($O(N^2)$ in both).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which search would you use on an unsorted list of phone contacts?

3 marks. Explain How to Decide Which Algorithm to Use with two clear points and one example.

5 marks. Write a 5-mark answer on How to Decide Which Algorithm to Use: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Linear Search 3. Is the data sorted?; Do we need speed or memory efficiency? 5. Use the recipe in the blue box. Model opening: Before choosing an algorithm, ask three questions: What is the input size?

BATCH HOMEWORK

Write a 5-mark answer on **How to Decide Which Algorithm to Use** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Chapter 2 Review

Chapter summary

- **Computational thinking** is systematic problem solving using decomposition, pattern recognition, abstraction and algorithms.
- An **algorithm** is a step-by-step logical procedure to solve a problem; it is conceptual and language-independent.
- Algorithms give structure, optimise time and memory, are reusable, ensure accuracy and act as a blueprint for code.
- **Pseudocode** is a human-readable, structured representation of an algorithm using keywords like IF, FOR and WHILE; it is not executable.
- An algorithm defines *what* to do; pseudocode shows *how* to implement it.
- **Decomposition** breaks a big problem into smaller sub-tasks; it reduces complexity, helps debugging and promotes reusability.
- **Pattern recognition** finds repetitions and rules (Row N = N stars) and is the foundation of loops.
- **Abstraction** hides noise and keeps only essential steps; situational details become variables.
- Sorting arranges data (ascending or descending); searching locates an element's position or existence.
- **Bubble Sort** compares and swaps adjacent elements; the largest value moves to the end each pass; N – 1 passes; stable; $O(N^2)$.
- **Selection Sort** brings the smallest remaining value to the front each pass; inner loop starts at outer + 1; fewer swaps; not stable; $O(N^2)$.
- **Linear Search** checks items one by one; works on unsorted data; $O(N)$ worst case.
- **Binary Search** halves the search range using BEG, MID and END; needs sorted data; $O(\log N)$ — about 20 steps for 1 million items.
- Algorithms are evaluated on **correctness** (checked with trace tables and edge cases), **efficiency** (time and space) and **clarity**.
- Choose by asking: input size, sorted or not, speed or memory? Unsorted → Linear; sorted → Binary; needs order → sort.

Key terms

Term	Meaning	اردو
Computational thinking	A systematic approach to solving problems using decomposition, patterns, abstraction and algorithms.	کمپیوٹیشنل سوچ
Algorithm	A step-by-step logical procedure to solve a problem, independent of any language.	الگورتھم، مرحلہ وار طریقہ حل
Pseudocode	A human-readable, structured but non-executable representation of an algorithm.	سوڈو کوڈ، فرضی کوڈ
Decomposition	Breaking a complex problem into smaller, manageable parts.	تقسیم کاری
Sub-task	One small part of a decomposed problem.	ذیلی کام
Pattern recognition	Identifying regularities, repetitions or rules in data.	نمونے کی پہچان
Abstraction	Hiding unnecessary details and focusing on essentials.	تجريد، غير ضروری تفصیل چھپانا
Noise	Details that do not affect the solution and can be ignored.	فالتو تفصیلات
Sorting	Arranging items in ascending or descending order.	ترتیب دینا
Searching	Locating an element in a list to find its position or existence.	تلاش کرنا
Ascending order	Smallest to largest (0–9, A–Z).	صعودی ترتیب
Descending order	Largest to smallest (9–0, Z–A).	نزولی ترتیب
Bubble Sort	Sort that repeatedly compares and swaps adjacent elements.	ببل سارٹ
Selection Sort	Sort that repeatedly selects the smallest element and puts it at the front.	سلیکشن سارٹ
Pass	One full run of the inner loop through the list.	ایک چکر
Swap	Exchanging the values of two positions, usually with a temp variable.	جگہ کا تبادلہ
In-place sorting	Sorting without needing extra memory for another list.	اضافی میموری کے بغیر ترتیب

Term	Meaning	اردو
Stable sort	A sort that keeps equal items in their original order.	مستحکم ترتیب
Linear (sequential) search	Checking each element one by one until the target is found.	ترتیب وار تلاش
Binary search	Search that halves a sorted list at each step.	دو حصی تلاش
BEG / MID / END	First, middle and last positions of the part being searched in Binary Search.	آغاز / درمیان / اختتام
Flag	A variable (like ValueFound) that records whether something has happened.	نشان دہی کرنے والا متغیر
Correctness	Giving expected output, handling edge cases and always finishing.	درستگی
Efficiency	How well an algorithm uses time and memory as input grows.	کارکردگی
Clarity	How easy an algorithm is to read, understand and modify.	وضاحت
Trace table	A table recording values step by step during a dry run.	ٹریس ٹیبل، جانچ جدول
Edge case	An unusual or extreme input used to test an algorithm.	انتہائی صورت
Time complexity (Big O)	A measure of how the number of steps grows with input size, e.g. $O(N)$, $O(\log N)$.	وقتی پیچیدگی

Practice: multiple choice

1. An algorithm is best defined as:
 - a. a programming language
 - b. a step-by-step logical procedure to solve a problem
 - c. a type of computer hardware
 - d. compiled machine code
2. Pseudocode is:
 - a. executable machine code
 - b. a symbol used in flowcharts
 - c. a Python library
 - d. a human-readable representation of an algorithm using plain English and keywords
3. Breaking a complex problem into smaller, manageable parts is called:
 - a. decomposition
 - b. abstraction
 - c. pattern recognition
 - d. compilation
4. In the "making tea" example, ignoring the brand of the kettle is an example of:
 - a. decomposition
 - b. sorting
 - c. abstraction
 - d. searching
5. Pattern recognition forms the foundation of:
 - a. variables
 - b. loops
 - c. comments
 - d. input devices
6. Bubble Sort works by comparing:
 - a. the first and last elements
 - b. every element with the middle element
 - c. adjacent elements
 - d. random pairs of elements
7. After the first pass of Bubble Sort (ascending) on 8, 4, 1, 9, 3, the list is:
 - a. 1, 3, 4, 8, 9
 - b. 4, 8, 1, 9, 3
 - c. 1, 8, 4, 9, 3
 - d. 4, 1, 8, 3, 9
8. Binary Search works only on a list that is:
 - a. sorted
 - b. unsorted
 - c. stored in a linked list
 - d. of strings only
9. Linear Search is also known as:
 - a. binary search
 - b. sequential search
 - c. bubble search
 - d. random search
10. How many passes does Bubble Sort need to sort N elements?
 - a. N
 - b. N + 1
 - c. N - 1
 - d. 2N
11. In Selection Sort pseudocode, the inner loop starts at:
 - a. 0
 - b. N - 1
 - c. outer - 1
 - d. outer + 1
12. The worst-case time complexity of Binary Search is:
 - a. $O(\log N)$
 - b. $O(N)$
 - c. $O(N^2)$
 - d. $O(1)$
13. About how many steps does Binary Search need, at most, to find an item among 1 million sorted elements?
 - a. 2
 - b. 20
 - c. 1,000
 - d. 1,000,000
14. Which sorting algorithm is NOT stable?
 - a. Bubble Sort
 - b. Both are stable
 - c. Selection Sort
 - d. Neither sorts data
15. Which of the following is NOT an evaluation criterion of an algorithm?
 - a. Correctness
 - b. Efficiency
 - c. Clarity
 - d. Popularity

Practice: short questions

1. Define computational thinking and name its four components.
2. Write any four points on the importance of algorithms.
3. Give three differences between an algorithm and pseudocode.
4. What is decomposition? Explain it with the example of learning a new language.
5. What three questions should you ask during pattern recognition? Apply them to the triangle of stars.
6. Define abstraction. In the "making tea" example, name two variables and two noise items.
7. Differentiate between sorting and searching.
8. Why does Binary Search require a sorted list? State two disadvantages of Binary Search.
9. Give two differences between Bubble Sort and Selection Sort.
10. Name the three evaluation criteria of an algorithm. What is a trace table used for?

Practice: long / problem questions

1. Sort the list **5, 2, 7, 1, 6** in ascending order using Bubble Sort. Show every comparison of every pass in a table, and state the total number of comparisons and swaps. Then write the Python code for Bubble Sort.
2. Sort the list **6, 2, 9, 5, 1** in ascending order using Selection Sort (textbook method). Show every comparison of every pass and count the swaps. Also state why Selection Sort is called "blind" to an already sorted list.
3. The sorted list is **3, 8, 12, 17, 23, 31, 40, 52, 66** (Python indexes 0–8). Using Binary Search, show a low / mid / high table to search for (a) 40 and (b) 20. For each, state how many comparisons Linear Search would need.
4. Write the algorithm and pseudocode for Linear Search. Dry-run it on **8, 3, 6, 1, 7, 2, 4, 5** for FindValue = 2 and for FindValue = 9, and give two advantages and two disadvantages of Linear Search.
5. A school wants a program that reads the marks of 5 subjects for every student and prints each student's total, percentage and grade. Apply decomposition, pattern recognition and abstraction to this problem, and write a short algorithm.
6. A library has 50,000 book IDs stored in sorted order, and the librarian searches it hundreds of times a day. (a) Which search algorithm should be used and why? (b) What is the maximum number of comparisons for Linear and for Binary Search? (c) Explain the three evaluation criteria you would use to judge the chosen program.

Answer key

Multiple choice

1. b
2. d
3. a
4. c
5. b
6. c
7. d
8. a
9. b
10. c
11. d
12. a
13. b
14. c
15. d

Short questions — model answers

1. Computational thinking is a systematic approach to solving problems. Its four components are decomposition (breaking down), pattern recognition (finding repetitions), abstraction (hiding unnecessary details) and algorithms (writing step-by-step solutions).
2. Algorithms (1) provide a structured approach that makes complex tasks manageable; (2) optimise time and memory usage, crucial for large applications; (3) can be reused for similar problems; (4) ensure accuracy and consistency, reducing human error; (5) act as a blueprint before coding. (Any four.)
3. (1) An algorithm is a step-by-step logical procedure; pseudocode is a human-readable representation of it using English and keywords. (2) An algorithm is conceptual and language-independent; pseudocode is semi-formal and structured but not executable. (3) An algorithm has no fixed format and is for anyone; pseudocode uses IF/FOR/WHILE, follows conventions and is mainly for programmers.
4. Decomposition is breaking a complex task into smaller, manageable parts. Learning a language is decomposed into: vocabulary (words like "I", "eat", "apple"), grammar rules (Subject → Verb → Object), tenses ("I eat" vs "I ate") and sentence building (combining words with rules).
5. Ask: What is repeating? What changes in a predictable way? Can I generalise this? For the star triangle: stars repeat in every row; each row has one more star than the previous; generalisation: Row $N = N$ stars, so one loop can print it.
6. Abstraction means hiding unnecessary features and focusing on the essential ones. Variables: type of tea (black, green, milk), additions (sugar, lemon), tool (stove or kettle) — any two. Noise: brand of kettle, cup colour or design, where tea is made — any two.
7. Sorting arranges a collection of items in ascending or descending order to organise data (e.g., Bubble Sort, Selection Sort). Searching locates a specific element in a list to find its position or whether it exists (e.g., Linear Search, Binary Search).
8. Binary Search decides to go left or right by comparing with the middle value; this decision is only valid if all smaller values are on the left and larger on the right, i.e., the list is sorted. Disadvantages: needs sorted data; needs random access (arrays, not linked lists); code is more complex and prone to off-by-one errors. (Any two.)
9. (1) Bubble Sort compares adjacent elements; Selection Sort compares a fixed position with all later elements. (2) Bubble Sort moves the largest to the end each pass; Selection Sort moves the smallest to the front. Also: Bubble Sort is stable, Selection Sort is not; Selection Sort makes fewer swaps.
10. Correctness, efficiency (time and space) and clarity (readability). A trace table records the values of variables step by step during a dry run, so we can check that the output matches the expected result and so prove correctness.

Long questions — model answers

1. Bubble Sort on 5, 2, 7, 1, 6

Pass	Pair	Left > Right?	List after
1	[5, 2]	Yes, swap	2, 5, 7, 1, 6
1	[5, 7]	No	2, 5, 7, 1, 6
1	[7, 1]	Yes, swap	2, 5, 1, 7, 6
1	[7, 6]	Yes, swap	2, 5, 1, 6, 7
2	[2, 5]	No	2, 5, 1, 6, 7
2	[5, 1]	Yes, swap	2, 1, 5, 6, 7
2	[5, 6]	No	2, 1, 5, 6, 7
3	[2, 1]	Yes, swap	1, 2, 5, 6, 7
3	[2, 5]	No	1, 2, 5, 6, 7
4	[1, 2]	No	1, 2, 5, 6, 7

Total comparisons = 4 + 3 + 2 + 1 = 10; total swaps = 3 + 1 + 1 + 0 = 5. Sorted list: 1, 2, 5, 6, 7.

```
data = [5, 2, 7, 1, 6]
n = len(data)
for outer in range(n - 1):
    for inner in range(n - 1 - outer):
        if data[inner] > data[inner + 1]:
            temp = data[inner]
            data[inner] = data[inner + 1]
            data[inner + 1] = temp
print(data)
```

OUTPUT

```
[1, 2, 5, 6, 7]
```

2. Selection Sort (textbook method) on 6, 2, 9, 5, 1

Pass	Compare	Values	Action	List after
1	Pos1 vs Pos2	6 > 2	Swap	2, 6, 9, 5, 1
1	Pos1 vs Pos3	2 > 9	No	2, 6, 9, 5, 1
1	Pos1 vs Pos4	2 > 5	No	2, 6, 9, 5, 1
1	Pos1 vs Pos5	2 > 1	Swap	1, 6, 9, 5, 2
2	Pos2 vs Pos3	6 > 9	No	1, 6, 9, 5, 2
2	Pos2 vs Pos4	6 > 5	Swap	1, 5, 9, 6, 2
2	Pos2 vs Pos5	5 > 2	Swap	1, 2, 9, 6, 5
3	Pos3 vs Pos4	9 > 6	Swap	1, 2, 6, 9, 5
3	Pos3 vs Pos5	6 > 5	Swap	1, 2, 5, 9, 6
4	Pos4 vs Pos5	9 > 6	Swap	1, 2, 5, 6, 9

10 comparisons, 7 swaps. Sorted list: 1, 2, 5, 6, 9. (With the classic one-swap-per-pass method the passes give 1, 2, 9, 5, 6 → 1, 2, 9, 5, 6 → 1, 2, 5, 9, 6 → 1, 2, 5, 6, 9.)

Selection Sort is "blind" to a sorted list because its loops have fixed limits: it always makes all $N(N-1)/2$ comparisons, even if the list is already in order. It has no way to notice that no swaps were needed and stop early.

3. (a) Search for 40

Step	low	high	mid	data[mid]	Compare	Action
1	0	8	$(0+8)//2 = 4$	23	$40 > 23$	low = 5
2	5	8	$(5+8)//2 = 6$	40	$40 = 40$	Found at index 6

Binary: 2 comparisons. Linear Search: 40 is the 7th item, so 7 comparisons.

(b) Search for 20

Step	low	high	mid	data[mid]	Compare	Action
1	0	8	4	23	$20 < 23$	high = 3
2	0	3	$(0+3)//2 = 1$	8	$20 > 8$	low = 2
3	2	3	$(2+3)//2 = 2$	12	$20 > 12$	low = 3
4	3	3	3	17	$20 > 17$	low = 4
—	4	3	low > high, so the loop stops: Not Found			

Binary: 4 comparisons. Linear Search must check all 9 items before saying "Not Found".

4. Algorithm and pseudocode: as in section 2.4.2 (Start; DATA, N, FindValue, ValueFound := 0; repeat for PTR = 1 to N: if DATA[PTR] = FindValue then ValueFound = 1 and exit; after the loop print DATA[PTR] if ValueFound = 1, else "Not Found"; End).

FindValue = 2:

Step	1	2	3	4	5	6
Element	8	3	6	1	7	2
== 2?	No	No	No	No	No	Yes — exit

Found at position 6 after 6 comparisons; ValueFound = 1; prints 2.

FindValue = 9: 8, 3, 6, 1, 7, 2, 4, 5 are all checked (8 comparisons), none equals 9, ValueFound stays 0, so "Data Not Found" is printed.

Advantages: works on sorted and unsorted data; very simple code; fast for small lists; no extra space. Disadvantages: up to N checks (1 million for 1 million items); time grows linearly; inefficient if the same list is searched thousands of times. (Any two of each.)

5. **Decomposition:** (1) input a student's 5 marks; (2) calculate total; (3) calculate percentage = $\text{total} \div 500 \times 100$; (4) decide grade; (5) print result; (6) repeat for the next student.

Pattern recognition: the same steps repeat for every student, and the same "add a mark" step repeats for every subject — so use a loop over students and a loop over subjects.

Abstraction: keep only roll number, marks, total, percentage and grade; ignore noise such as the student's address, uniform or the colour of the result card. The number of students can be a variable.

Algorithm: Step 1: Start. Step 2: Read number of students S. Step 3: Repeat Steps 4–8 for each student. Step 4: TOTAL = 0. Step 5: Repeat 5 times: read MARK, TOTAL = TOTAL + MARK. Step 6: PER = TOTAL / 500 × 100. Step 7: If PER ≥ 80 grade "A1", else if PER ≥ 70 "A", else if PER ≥ 60 "B", else if PER ≥ 50 "C", else "Fail" (school's own grading scale). Step 8: Print TOTAL, PER, GRADE. Step 9: End.

6. (a) **Binary Search**, because the data is already sorted, it is large (50,000 items) and it is searched many times a day, so the time saved per search adds up; Linear Search would be far slower.

(b) Linear Search worst case: 50,000 comparisons. Binary Search worst case: 16 comparisons, because $2^{15} = 32,768 < 50,000 \leq 2^{16} = 65,536$, so 16 halvings are enough to reduce 50,000 items to one.

(c) **Correctness:** it must return the right position for IDs that exist, say "Not Found" for missing IDs (edge cases: first ID, last ID, missing ID), and always stop. **Efficiency:** time $O(\log N)$ and no extra memory ($O(1)$). **Clarity:** meaningful names like low, mid, high, clear steps and good indentation so another programmer can maintain it.

Self-assessment: I can...

- ☐ define computational thinking and name its four parts.
- ☐ draw a table comparing algorithm and pseudocode on at least five points.
- ☐ find a pattern in data and turn it into a loop.
- ☐ dry-run Bubble Sort pass by pass and count comparisons and swaps.
- ☐ trace Linear Search with a step table, including the "not found" case.
- ☐ state best and worst time complexity for all four algorithms.
- ☐ define an algorithm and give five reasons it is important.
- ☐ decompose a real-life problem into sub-tasks and explain three benefits.
- ☐ separate necessary steps, variables and noise using abstraction.
- ☐ dry-run Selection Sort pass by pass and explain why it is not stable.
- ☐ trace Binary Search with a BEG / MID / END table and explain why it needs sorted data.
- ☐ evaluate an algorithm for correctness, efficiency and clarity, and choose the right algorithm for a situation.

CHAPTER 3

Programming Fundamentals

In this chapter you start writing real programs in Python. You will learn how programs store data, take input, make decisions, repeat work, use ready-made libraries, and how to find and fix your own mistakes.

اس باب میں آپ پائتھن (Python) میں حقیقی پروگرام لکھنا سیکھیں گے۔ آپ جانیں گے کہ پروگرام ڈیٹا کیسے محفوظ کرتا ہے، فیصلے کیسے کرتا ہے، کام کو کیسے دہراتا ہے، اور غلطیاں کیسے تلاش کی جاتی ہیں۔

What you will learn

- Define a program and a programming language, and compare low-, mid- and high-level languages.
- Describe the features of an IDE and the main parts of the VS Code window.
- Take input with `input()`, convert it with `int()` / `float()`, and display output with `print()` and f-strings.
- Use sequence, selection (`if`, `if-else`, `if-elif-else`, nested `if`) and repetition (`for`, `while`, `range()`, `break`, `continue`, nested loops).
- Identify syntax, runtime and logical errors and read a traceback to fix a bug.
- Name career areas where Python is used.
- Write Python programs that use comments, correct indentation, valid variable names and the main data types.
- Evaluate expressions with arithmetic, assignment, relational, logical, membership and bitwise operators, including binary working.
- Import and use built-in libraries (`math`, `random`, `datetime`) and install third-party libraries with `pip`.

ACADEMY CALENDAR

Academy calendar: 24 topics · 12 Golden · **20 classes of 90 minutes** + one 40-minute weekly test after this chapter.

Class	Topics	Kind	Board focus
Class 01	Programming + Programming Language Types	Paired · 90 min	Computers are "dumb" machines.
Class 02	Career Growth with Python + Integrated Development Environment (IDE)	Paired · 90 min	Python is one of the most in-demand languages in the world.
Class 03	Visual Studio Code (VS Code)	Single · 90 min	VS Code is a free, lightweight and powerful code editor made by Microsoft and widely used...
Class 04	Fundamentals of Python Programming	★ Golden · 90 min	The basic structure of a Python program is simple and clear.
Class 05	Variables	★ Golden · 90 min	A variable is a named space in computer memory used to store data.
Class 06	Data Types in Python	★ Golden · 90 min	A data type specifies the kind of data a variable holds — a whole number, a decimal,...
Class 07	Input and Output Handling	Single · 90 min	Output — the print() function.
Class 08	Operators and Operands: Arithmetic and Assignment	★ Golden · 90 min	An operand is the value or variable being worked on.
Class 09	Relational, Logical and Membership Operators	★ Golden · 90 min	3.
Class 10	Bitwise Operators	★ Golden · 90 min	6.
Class 11	Control Structures	★ Golden · 90 min	Control structures decide the order in which statements are executed in a program (the...
Class 12	Sequence	Single · 90 min	Sequence means statements are executed one after another, strictly from top to bottom, in...
Class 13	Selection Statements: if and if-else	★ Golden · 90 min	Selection changes the flow of a program based on a condition — an expression that is...
Class 14	Selection Statements: if-elif-else and Nested if	★ Golden · 90 min	3.

Class	Topics	Kind	Board focus
Class 15	Repetition Statements: the for Loop and range()	★ Golden · 90 min	A repetition statement (loop) lets a block of code run again and again.
Class 16	The while Loop, break and continue	★ Golden · 90 min	2.
Class 17	Nested Loops and for vs while	★ Golden · 90 min	A nested loop is a loop inside another loop.
Class 18	Practical Activity: Shopping Bill Calculator + Libraries in Python	Paired · 90 min	This program combines all three control structures: sequence (steps in order), selection...
Class 19	Built-in Libraries + Third-Party Libraries	Paired · 90 min	Built-in libraries come pre-installed with Python.
Class 20	Debugging Code in Python	Single · 90 min	Debugging is the process of identifying, tracing and fixing bugs so a program works...

Weekly test: 15 MCQ from this chapter + two 5-mark Golden questions. Mark to the recipes. Re-teach any Golden below 60% in the next starter.

گولڈن موضوع پوری کلاس لیتا ہے۔ ہفتہ وار ٹیسٹ کے بعد کمزور گولڈن دوبارہ پڑھائیں۔

3.1 Programming

ACADEMY SESSION

Session 1 of 20 · 45 minutes (first half) · paired with Programming Language Types.

10–45 min — this topic. Lock the definition and table for **Programming**. Starter (0–10) is from last class. Second half is Programming Language Types.

On the board: Computers are "dumb" machines.

Error clinic: Students often think the computer "understands" what they want.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Programming**. Write: Computers are "dumb" machines.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The language used to write these instructions is called a programming language. (2) Writing programs is called programming, and the person who writes them is a programmer. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Computers are "dumb" machines. They are very fast, but they cannot think or do anything on their own. They need exact, step-by-step **instructions**.

- A set of instructions given to a computer is called a **program**.
- The language used to write these instructions is called a **programming language**.
- Writing programs is called **programming**, and the person who writes them is a **programmer**.

Think of a recipe. A cook follows the recipe line by line: "boil water, add rice, wait 15 minutes". A computer follows a program in the same way, one instruction at a time, without guessing what you meant.

WORKED EXAMPLE

A tiny program. Here is a complete Python program with one instruction. It tells the computer to show a message on the screen.

```
print("Hello")
```

OUTPUT
Hello

The word `print` is the instruction; `"Hello"` is the data it works on.

REMEMBER IT

Program = recipe, programmer = recipe writer, computer = cook who follows every line exactly. If the recipe is wrong, the food is wrong. The cook does not fix it for you.

COMMON MISTAKE

Students often think the computer "understands" what they want. It does not. If you type `Print("Hello")` with a capital P, Python stops with an error, because it only knows `print`. Be exact.

اردو میں سمجھیں

کمپیوٹر خود سے کچھ نہیں سوچ سکتا۔ اسے کام کرنے کے لیے ہدایات چاہئیں۔ ہدایات کے مجموعے کو پروگرام (Program) کہتے ہیں، اور جس زبان میں یہ ہدایات لکھی جاتی ہیں اسے پروگرامنگ لینگویج (Programming Language) کہتے ہیں۔

CHECK YOURSELF

1. What is a program?
2. Why do we say computers are "dumb" machines?

Answers: 1. A set of instructions given to a computer to perform a task. 2. Because they cannot think or do anything without instructions; they only follow exactly what they are told.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is a program?

3 marks. Explain Programming with two clear points and one example.

5 marks. Write a 5-mark answer on Programming: definition, two points, a labelled diagram or table, and one example.

Answers: 1. A set of instructions given to a computer to perform a task. 3. The language used to write these instructions is called a programming language.; Writing programs is called programming, and the person who writes them is a programmer. 5. Use the recipe in the blue box. Model opening: Computers are "dumb" machines.

BATCH HOMEWORK

Write a 5-mark answer on **Programming** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.1.1 Programming Language Types

ACADEMY SESSION

Session 1 of 20 · 45 minutes (second half) · paired with Programming.

45–75 min — this topic. Board working for **Programming Language Types**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Programming languages are classified into three main types, depending on how close they are to the computer's own language (binary 0s and 1s) or to human language.

Error clinic: "Low level" does not mean "bad" or "weak".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Programming Language Types**. Write: Programming languages are classified into three main types, depending on how close they are to the computer's own language (binary 0s and 1s) or to human language.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).


3 marks: definition + two points — (1) Programming languages are classified into three main types, depending on how close they are to the computer's own language (binary 0s and... (2) Second distinct point (not a repeat of the definition) — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

Programming languages are classified into **three main types**, depending on how close they are to the computer's own language (binary 0s and 1s) or to human language.

Type	Description	Examples
Low level	Closest to the native language of the computer (binary 0s and 1s). Very difficult for humans to read and write.	Machine language (binary)
Mid level	Bridges the gap. It can access hardware but is easier to read than binary because it uses short words called mnemonics (e.g. <code>MOV</code> , <code>ADD</code>).	Assembly language
High level	Designed to be easy for humans to read and write. Uses English-like words.	C++, Java, Python



The three levels of programming languages, with a sample line from each.

Common high-level languages

Language	Key idea	Used for
C++	Powerful and closer to hardware.	System software, operating systems, high-performance computer games.
Java	"Write once, run anywhere."	Large enterprise applications, Android mobile apps, server programming.
Python	Simple, readable syntax.	Data Science, Artificial Intelligence, Web Development, and learning to program.

WORKED EXAMPLE

Same task, three levels. Suppose you want to copy a value.

- Machine language: a pattern like `01010101` — you would need a chart to know what it means.
- Assembly: `MOV AX, BX` — "move the value in register BX into register AX". Shorter words, but you still need to know the hardware.
- Python: `a = b` — you simply say "a gets the value of b".

The higher the level, the less you need to know about the hardware and the faster you can write the program.

REMEMBER IT

"Low = Like the machine, High = Human." Mid level sits in the Middle and uses Mnemonics (both start with M).

COMMON MISTAKE

"Low level" does not mean "bad" or "weak". Low-level code runs very fast and controls hardware directly. It is just harder for humans to write.

اردو میں سمجھیں

پروگرامنگ زبانوں کی تین اقسام ہیں: لو لیول (Low Level) جو بائری 0 اور 1 میں ہوتی ہے، مڈ لیول (Mid Level) یعنی اسمبلی جو مختصر الفاظ (Mnemonics) استعمال کرتی ہے، اور ہائی لیول (High Level) جیسے پائتھن، جاوا اور سی پلس پلس جو انگریزی جیسے الفاظ استعمال کرتی ہیں اور انسانوں کے لیے آسان ہیں۔

CHECK YOURSELF

1. Which level is `MOV AX, BX` ?
2. Which high-level language is famous for "write once, run anywhere"?
3. Give one use of C++.

Answers: 1. Mid level (assembly language). 2. Java. 3. Any one: system software, operating systems, high-performance games.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which level is `MOV AX, BX`?

3 marks. Explain Programming Language Types with two clear points and one example.

5 marks. Write a 5-mark answer on Programming Language Types: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Mid level (assembly language) 3. Programming languages are classified into three main types, depending on how close they are to the computer's own language (binary 0s and... 5. Use the recipe in the blue box. Model opening: Programming languages are classified into three main types, depending on how close they are to the computer's own language (binary 0s and 1s) or to human...

BATCH HOMEWORK

Write a 5-mark answer on **Programming Language Types** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.2 Career Growth with Python

ACADEMY SESSION

Session 2 of 20 · 45 minutes (first half) · paired with Integrated Development Environment (IDE).

10–45 min — this topic. Lock the definition and table for **Career Growth with Python**. Starter (0–10) is from last class. Second half is Integrated Development Environment (IDE).

On the board: Python is one of the most in-demand languages in the world.

Error clinic: Django and Flask are web frameworks (for websites), not AI tools.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Career Growth with Python**. Write: Python is one of the most in-demand languages in the world.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Data Science and Data Analysis: analyse data, create reports and make predictions. (2) Artificial Intelligence and Machine Learning: develop intelligent systems, chatbots and recommendation algorithms (like "videos you may... — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Python is one of the most in-demand languages in the world. Learning it opens many career paths:

- **Software Development:** build desktop and web applications.
- **Data Science and Data Analysis:** analyse data, create reports and make predictions.
- **Artificial Intelligence and Machine Learning:** develop intelligent systems, chatbots and recommendation algorithms (like "videos you may like").
- **Web Development:** use frameworks such as **Django** and **Flask** to build websites.
- **Automation and Scripting:** automate repetitive office or lab tasks (renaming 500 files, filling spreadsheets).
- **Cybersecurity and Networking:** write security tools and analyse network data.

Why Python? Python lets you focus on **problem-solving and logic** instead of memorising complex syntax rules. Compare printing a message in Python with C++:

```
# Python
print("Hello")
```

```
// C++
#include <iostream>
int main() {
    std::cout << "Hello";
    return 0;
}
```

WORKED EXAMPLE

Automation example. A school clerk must write "Roll No. 1" to "Roll No. 5" on a list. Python does it in two lines:

```
for n in range(1, 6):
    print("Roll No.", n)
```

OUTPUT

```
Roll No. 1
Roll No. 2
Roll No. 3
Roll No. 4
Roll No. 5
```

Change 6 to 501 and it writes 500 lines just as fast. (You will learn loops in 3.5.3.)

REMEMBER IT

Six careers — remember **"S-D-A-W-A-C"**: **S**oftware, **D**ata, **A**I, **W**eb, **A**utomation, **C**ybersecurity.

COMMON MISTAKE

Django and Flask are **web frameworks** (for websites), not AI tools. AI/ML uses libraries such as TensorFlow and PyTorch (see 3.6.2).

اردو میں سمجھیں

پائتھن سیکھ کر آپ سافٹ ویئر ڈیولپمنٹ، ڈیٹا سائنس، مصنوعی ذہانت (AI)، ویب ڈیولپمنٹ، آٹومیشن اور سائبر سیکیورٹی جیسے شعبوں میں کیریئر بنا سکتے ہیں۔ پائتھن کا آسان انداز آپ کو مشکل اصول یاد کرنے کے بجائے مسئلہ حل کرنے پر توجہ دینے دیتا ہے۔

CHECK YOURSELF

1. Name two Python web frameworks.
2. Which career area builds chatbots and recommendation systems?

Answers: 1. Django and Flask. 2. Artificial Intelligence and Machine Learning.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name two Python web frameworks.

3 marks. Explain Career Growth with Python with two clear points and one example.

5 marks. Write a 5-mark answer on Career Growth with Python: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Django and Flask 3. Data Science and Data Analysis: analyse data, create reports and make predictions.; Artificial Intelligence and Machine Learning: develop intelligent systems, chatbots and recommendation algorithms (like "videos you may... 5. Use the recipe in the blue box. Model opening: Python is one of the most in-demand languages in the world.

BATCH HOMEWORK

Write a 5-mark answer on **Career Growth with Python** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.3 Integrated Development Environment (IDE)

ACADEMY SESSION

Session 2 of 20 · 45 minutes (second half) · paired with Career Growth with Python.

45–75 min — this topic. Board working for **Integrated Development Environment (IDE)**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: An IDE (Integrated Development Environment) is a software tool that helps programmers write, run and manage code in one place.

Error clinic: An IDE does not write the program for you and does not catch logical mistakes.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Integrated Development Environment (IDE)**. Write: An IDE (Integrated Development Environment) is a software tool that helps programmers write, run and manage code in one place.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Syntax Highlighting: colours different parts of the code (keywords, strings, numbers) to make it easier to read. (2) Auto-completion: suggests code while you type (type pri and it offers print). — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

An **IDE (Integrated Development Environment)** is a software tool that helps programmers **write, run and manage code in one place**. It is a complete workspace for programming. "Integrated" means many tools are joined together in one window.

Key features of an IDE:

- **Code Editor:** where you write and edit code.
- **Syntax Highlighting:** colours different parts of the code (keywords, strings, numbers) to make it easier to read.
- **Auto-completion:** suggests code while you type (type `pri` and it offers `print`).
- **Run/Execute Tool:** runs the program with one click.
- **Debugger:** helps you find and fix errors, for example by pausing the program at a chosen line.

WORKED EXAMPLE

Without vs with an IDE. Without an IDE you would write code in Notepad, save it, open a terminal and type `python file.py`, then go back to Notepad to fix mistakes. With an IDE you write, run (press the ► Run button) and debug in the same window, and errors are underlined while you type.

REMEMBER IT

IDE features — **"E-S-A-R-D"**: Editor, Syntax highlighting, Auto-completion, Run, Debugger.

COMMON MISTAKE

An IDE does not write the program for you and does not catch logical mistakes. It only makes writing, running and debugging easier.

اردو میں سمجھیں

آئی ڈی ای (IDE) ایک ایسا سافٹ ویئر ہے جس میں کوڈ لکھنا، چلانا اور غلطیاں درست کرنا ایک ہی جگہ ممکن ہوتا ہے۔ اس کی اہم خصوصیات میں کوڈ ایڈیٹر، رنگین کوڈ (Syntax Highlighting)، خودکار تجاویز (Auto completion)، رن بٹن اور ڈیبیگر شامل ہیں۔

CHECK YOURSELF

1. What does "integrated" mean in IDE?
2. Which IDE feature suggests code while you type?

Answers: 1. Many programming tools (editor, runner, debugger) are combined in one program. 2. Auto-completion.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does "integrated" mean in IDE?

3 marks. Explain Integrated Development Environment (IDE) with two clear points and one example.

5 marks. Write a 5-mark answer on Integrated Development Environment (IDE): definition, two points, a labelled diagram or table, and one example.

Answers: 1. Many programming tools (editor, runner, debugger) are combined in one program. 3. Syntax Highlighting: colours different parts of the code (keywords, strings, numbers) to make it easier to read.; Auto-completion: suggests code while you type (type `pri` and it offers `print`). 5. Use the recipe in the blue box. Model opening: An IDE (Integrated Development Environment) is a software tool that helps programmers write, run and manage code in one place.

BATCH HOMEWORK

Write a 5-mark answer on **Integrated Development Environment (IDE)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.3.1 Visual Studio Code (VS Code)

ACADEMY SESSION

Session 3 of 20 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: VS Code is a free, lightweight and powerful code editor made by Microsoft and widely used for Python.

Error clinic: Always save Python files with the .py extension (e.g.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Visual Studio Code (VS Code)**. Write: VS Code is a free, lightweight and powerful code editor made by Microsoft and widely used for Python.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) VS Code is a free, lightweight and powerful code editor made by Microsoft and widely used for Python. (2) By default it is not a full IDE, but it becomes one when you install extensions (add-ons), such as the Python extension by Microsoft. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

VS Code is a **free, lightweight and powerful code editor** made by Microsoft and widely used for Python. By default it is **not a full IDE**, but it becomes one when you install **extensions** (add-ons), such as the **Python extension by Microsoft**.

VS Code interface elements

Element	Description
1. Top Menu Bar	Control over files, editing, navigation and workspace (File, Edit, Selection, View, Go, Run).
2. Side Bar	Contains the core tools: Explorer, Search, Source Control, Run & Debug and Extensions.
3. Explorer	Shows project files and folders. Helps you create, open and manage your Python files.
4. Search	Finds and replaces text in the open file or across the whole project.
5. Source Control	Connects with Git (a version control system) to track changes, undo mistakes and collaborate.
6. Run & Debug	Runs code, finds errors, pauses at specific lines and lets you inspect variables.
7. Extensions	Like an App Store for VS Code. Add features such as the Python extension, Prettier or Python Debugger.



A simplified VS Code window: menu bar, side bar, Explorer and the code editor.

WORKED EXAMPLE

Setting up and running your first program in VS Code:



```
print("Hello, World!")
```

OUTPUT

```
Hello, World!
```

The output appears in the **Terminal** panel at the bottom of the window.

REMEMBER IT

Extensions are the **"App Store"** of VS Code: just as apps give your phone new abilities, extensions give VS Code new abilities.

COMMON MISTAKE

Always save Python files with the `.py` extension (e.g. `hello.py`). Without it, VS Code does not know the file is Python, so there is no syntax highlighting and no Run button.

اردو میں سمجھیں

وی ایس کوڈ (VS Code) ایک مفت اور ہلکا پھلکا کوڈ ایڈیٹر ہے۔ یہ اپنے آپ میں مکمل آئی ڈی ای نہیں، لیکن ایکسٹینشنز (Extensions) لگانے سے آئی ڈی ای بن جاتا ہے۔ اس کے اہم حصے مینو بار، سائیڈ بار، ایکسپلورر، سرچ، سورس کنٹرول، رن اینڈ ڈیبگ اور ایکسٹینشنز ہیں۔

CHECK YOURSELF

1. Which VS Code element connects to Git?
2. Is VS Code a full IDE by default? How does it become one?
3. Where do you see and manage your project's files?

Answers: 1. Source Control. 2. No; it becomes an IDE by installing extensions (e.g. the Python extension). 3. Explorer.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which VS Code element connects to Git?

3 marks. Explain Visual Studio Code (VS Code) with two clear points and one example.

5 marks. Write a 5-mark answer on Visual Studio Code (VS Code): definition, two points, a labelled diagram or table, and one example.

Answers: 1. Source Control 3. VS Code is a free, lightweight and powerful code editor made by Microsoft and widely used for Python.; By default it is not a full IDE, but it becomes one when you install extensions (add-ons), such as the Python extension by Microsoft. 5. Use the recipe in the blue box. Model opening: VS Code is a free, lightweight and powerful code editor made by Microsoft and widely used for Python.

BATCH HOMEWORK

Write a 5-mark answer on **Visual Studio Code (VS Code)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.4 Fundamentals of Python Programming ★ Golden

ACADEMY SESSION

Session 4 of 20 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The basic structure of a Python program is simple and clear.

Error clinic: IndentationError?

Exam wording to train: Common questions: "What is the purpose of comments?", "Why is indentation important in Python?", "How is Python different from C++/Java in defining blocks?"...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Fundamentals of Python Programming**. Write: The basic structure of a Python program is simple and clear.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) A program takes data, processes it using statements, and finally shows output. (2) Python runs the statements top to bottom, one after another (sequentially). — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

8–10 marks: 5-mark structure + a complete truth table and a labelled gate / logic diagram + a one-line conclusion. Method marks are awarded for working.

LEARN IT

The basic structure of a Python program is simple and clear. A program takes data, **processes it using statements**, and finally **shows output**. Python runs the statements **top to bottom, one after another** (sequentially).

A **statement** is one complete instruction, usually written on one line, such as `print("Hi")` or `x = 5`.

1. Comments (#) — Comments are notes written in the code **for humans**. They start with the `#` symbol. The Python interpreter completely **ignores** them. Use them to explain what your code does.

2. Indentation (spaces) — C++ and Java use curly brackets `{ }` to mark a **block** of code (a group of statements that belong together). Python instead uses **indentation**: spaces at the beginning of a line. Indentation is **mandatory** in Python. The standard is **4 spaces** (or 1 tab).

```
# This is a comment. It explains the code below.
print("Hello, World!")
if 5 > 2:
    # The space before 'print' is the indentation
    print("Five is greater than two!")
```

OUTPUT

```
Hello, World!
Five is greater than two!
```

WORKED EXAMPLE

Reading the program line by line:

1. Line 1 starts with #, so Python skips it.
2. Line 2 prints Hello, World!.
3. Line 3 asks a question: is 5 greater than 2? The colon : says "a block follows".
4. Line 4 is a comment inside the block (ignored).
5. Line 5 is indented by 4 spaces, so it belongs to the if block. Because 5 > 2 is true, it runs.

What happens if you forget the indentation?

```
if 5 > 2:
print("Five is greater than two!")
```

OUTPUT

```
File "indent.py", line 2
    print("Five is greater than two!")
    ^
IndentationError: expected an indented block after 'if' statement on line 1
```

Python refuses to run the program and points to line 2. Add 4 spaces before print to fix it.

REMEMBER IT

Think of indentation like the points and sub-points in your notebook. Sub-points are written a little to the right to show they "belong" to the main point. A colon : at the end of a line always means "indent the next line".

COMMON MISTAKE

IndentationError? Check your spaces. **Mixing tabs and spaces** can break a Python program even when the code looks lined up. Choose 4 spaces and use them everywhere (VS Code inserts 4 spaces when you press Tab in a .py file).

اردو میں سمجھیں

پائتھن پروگرام اوپر سے نیچے ترتیب سے چلتا ہے۔ # سے شروع ہونے والی لائن تبصرہ (Comment) ہوتی ہے جسے پائتھن نظر انداز کر دیتا ہے۔ پائتھن میں کوڈ کے بلاک کو بریکٹ کے بجائے انڈینٹیشن (Indentation) یعنی لائن کے شروع میں چار خالی جگہوں سے ظاہر کیا جاتا ہے، اور یہ لازمی ہے۔

EXAM TIP

Common questions: "What is the purpose of comments?", "Why is indentation important in Python?", "How is Python different from C++/Java in defining blocks?" Write: comments start with # and are ignored by the interpreter; Python uses indentation (4 spaces) instead of { }; wrong indentation gives an IndentationError. Always give a 3–4 line code example.

CHECK YOURSELF

1. Predict the output:

```
# print("A")
print("B")
if 3 > 7:
    print("C")
print("D")
```

2. What is the standard amount of indentation in Python?

Answers: 1. B then D on separate lines (line 1 is a comment; $3 > 7$ is false so C is skipped). 2. 4 spaces (or 1 tab).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Predict the output:

3 marks. Explain Fundamentals of Python Programming with two clear points and one example.

5 marks. Common questions: "What is the purpose of comments?", "Why is indentation important in Python?", "How is Python different from C++/Java in defining blocks?" Write: comments start with # and are...

8 marks. Fundamentals of Python Programming: 5-mark answer plus a complete truth table and a labelled gate / logic diagram.

Answers: 1. B then D on separate lines (line 1 is a comment; $3 > 7$ is false so C is skipped) 3. A program takes data, processes it using statements, and finally shows output.; Python runs the statements top to bottom, one after another (sequentially). 5. Use the recipe in the blue box. Model opening: The basic structure of a Python program is simple and clear. 8. Same 5-mark body + a complete truth table and a labelled gate / logic diagram + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Fundamentals of Python Programming** using the recipe in this topic. Include a complete truth table and a labelled gate / logic diagram. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.4.1 Variables ★ Golden

ACADEMY SESSION

Session 5 of 20 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A variable is a named space in computer memory used to store data.

Error clinic: = is not "equals" in the maths sense.

Exam wording to train: A favourite question: "Which of these variable names are valid?"

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Variables**. Write: A variable is a named space in computer memory used to store data.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Must start with a letter or underscore, NOT a number (1name is invalid). (2) Are case-sensitive: age and Age are two completely different variables. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **variable** is a **named space in computer memory used to store data**. Think of it as a labelled container (a box with a name written on it). You put a value in it with the **assignment operator** `=`, which means "store", not "equals".

In Python you **do not need to declare the type** of a variable. Python figures it out automatically from the value. This is called **dynamic typing**: the same variable can later hold a different type.

Rules for naming variables:

- Can contain **letters, numbers and underscores** (`_`) only — no spaces or symbols like `-`, `@`, `$`.
- **Must start with a letter or underscore**, NOT a number (`1name` is invalid).
- Are **case-sensitive**: `age` and `Age` are two completely different variables.
- Cannot be a Python **keyword** (a reserved word such as `if`, `for`, `while`, `else`, `True`).

Valid names ✓

```
name = "Ali"
age = 16
my_height = 5.7
score1 = 100
```

Invalid names ✗

```
1name = "Ali"    # starts with a number
my height = 5.7  # contains a space
if = 100         # keyword used
```

WORKED EXAMPLE

Using variables and case-sensitivity:

```
name = "Ali"
age = 16
my_height = 5.7
score1 = 100
print(name, age, my_height, score1)

Age = 17          # a different variable from age
print(age, Age)
```

OUTPUT

```
Ali 16 5.7 100
16 17
```

Dynamic typing — the type follows the value. `type()` tells you the type:

```
x = 5
print(x, type(x))
x = "five"
print(x, type(x))
```

OUTPUT

```
5 <class 'int'>
five <class 'str'>
```

What Python says about an invalid name:

```
1name = "Ali"
```

OUTPUT

```
File "names.py", line 1
  1name = "Ali"
    ^
SyntaxError: invalid decimal literal
```

REMEMBER IT

Choose **meaningful names**: `total_marks` is far clearer than `tm` or `x`. Use lowercase words joined by underscores (this style is called **snake_case**).

COMMON MISTAKE

`=` is **not** "equals" in the maths sense. `x = x + 1` is not a false equation; it means "take the value of `x`, add 1, and store the result back in `x`". To **compare** two values you use `==` (see 3.4.3).

اردو میں سمجھیں

ویری ایبل (Variable) میموری میں ایک نام والی جگہ ہے جس میں ڈیٹا رکھا جاتا ہے، بالکل ایک لیبل لگے ڈبے کی طرح۔ پائتھن میں ٹائپ بتانے کی ضرورت نہیں ہوتی۔ نام حرف یا انڈر سکور سے شروع ہونا چاہیے، اس میں خالی جگہ نہیں ہو سکتی، یہ کیس سینسیٹیو (Case-sensitive) ہوتا ہے اور کوئی کی ورڈ (Keyword) نہیں ہو سکتا۔

EXAM TIP

A favourite question: "Which of these variable names are valid? Give reasons." Check each name against all four rules and state the rule broken, e.g. "2nd_place — invalid, starts with a digit". Remember that `While` (capital W) is **valid** because keywords are lowercase and Python is case-sensitive.

CHECK YOURSELF

1. Valid or invalid? `_total`, `roll-no`, `class`, `marks2026`, `2marks`

2. Predict the output:

```
city = "Karachi"
City = "Hyderabad"
print(city)
```

Answers: 1. `_total` valid; `roll-no` invalid (hyphen); `class` invalid (keyword); `marks2026` valid; `2marks` invalid (starts with a digit). 2. `Karachi` — `city` and `City` are different variables.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Valid or invalid? `_total`, `roll-no`, `class`, `marks2026`, `2marks`

3 marks. Explain Variables with two clear points and one example.

5 marks. A favourite question: "Which of these variable names are valid? Give reasons." Check each name against all four rules and state the rule broken, e.g. "2nd_place — invalid, starts with a digit"....

8 marks. Variables: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. `_total` valid; `roll-no` invalid (hyphen); `class` invalid (keyword); `marks2026` valid; `2marks` invalid (starts with a digit) 3. Must start with a letter or underscore, NOT a number (1name is invalid).; Are case-sensitive: `age` and `Age` are two completely different variables. 5. Use the recipe in the blue box. Model opening: A variable is a named space in computer memory used to store data. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Variables** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.4.1 Data Types in Python ★ Golden

ACADEMY SESSION

Session 6 of 20 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A data type specifies the kind of data a variable holds — a whole number, a decimal, text, True/False, or a collection of items.

Error clinic: True and False must start with a capital letter.

Exam wording to train: Expect: "Name any four data types with examples" or "Differentiate list and tuple".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Data Types in Python**. Write: A data type specifies the kind of data a variable holds — a whole number, a decimal, text, True/False, or a collection of items.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The type decides what you can do with the data (you can divide numbers, but not names). (2) Python has several built-in data types: — + example.

5 marks: 3-mark structure + table: Name / Type / Description / Example + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **data type** specifies the **kind of data** a variable holds — a whole number, a decimal, text, True/False, or a collection of items. The type decides what you can do with the data (you can divide numbers, but not names). Python has several built-in data types:

Name	Type	Description	Example
Integer	<code>int</code>	Whole numbers without decimals (positive, negative or zero).	<code>age = 16</code>
Floating point	<code>float</code>	Numbers with a decimal point.	<code>height = 5.7</code>
String	<code>str</code>	Text data, enclosed in quotes (" " or ' ').	<code>name = "Sammy"</code> or <code>year = "2026"</code>
Boolean	<code>bool</code>	Logical value: <code>True</code> or <code>False</code> (capital T / F).	<code>is_student = True</code>
List	<code>list</code>	Ordered, changeable collection in square brackets [].	<code>marks = [85, 90, 75]</code>
Tuple	<code>tuple</code>	Ordered, unchangeable sequence in parentheses ().	<code>coords = (10, 20)</code>
Dictionary	<code>dict</code>	Key : value pairs in curly braces { }.	<code>student = {"name": "Ahmed", "age": 16}</code>
Set	<code>set</code>	Unordered collection of unique items (no duplicates).	<code>vowels = {'a', 'e', 'i'}</code>

Note: the slide abbreviates tuple as "tup"; the real Python type name is `tuple`, as the program below shows. The slides describe dictionaries as unordered; since Python 3.7 a dictionary remembers the order in which keys were added, but you always look items up **by key**, not by position.

WORKED EXAMPLE

Checking every type with `type()` :

```
age = 16
height = 5.7
name = "Sammy"
year = "2026"
is_student = True
marks = [85, 90, 75]
coords = (10, 20)
student = {"name": "Ahmed", "age": 16}
vowels = {'a', 'e', 'i'}

print(type(age))
print(type(height))
print(type(name), type(year))
print(type(is_student))
print(type(marks))
print(type(coords))
print(type(student))
print(type(vowels))
```

OUTPUT

```
<class 'int'>
<class 'float'>
<class 'str'> <class 'str'>
<class 'bool'>
<class 'list'>
<class 'tuple'>
<class 'dict'>
<class 'set'>
```

Notice that `year = "2026"` is a **string**, not a number, because it is inside quotes.

Working with the collection types:

```
marks = [85, 90, 75]
marks[0] = 88          # lists are changeable
marks.append(60)
print(marks)

coords = (10, 20)
print(coords[0])       # read item at position 0

student = {"name": "Ahmed", "age": 16}
print(student["name"]) # look up by key

nums = {1, 2, 2, 3, 3, 3} # duplicates are removed
print(nums)
print(len(nums))
```

OUTPUT

```
[88, 90, 75, 60]
10
Ahmed
{1, 2, 3}
3
```

Positions (called **indexes**) start at **0**, so `coords[0]` is the first item. Trying to change a tuple causes an error:

```
coords = (10, 20)
coords[0] = 50
```

OUTPUT

```
Traceback (most recent call last):
  File "tuple_test.py", line 2, in <module>
    coords[0] = 50
    ~~~~~^
TypeError: 'tuple' object does not support item assignment
```

REMEMBER IT

Brackets decide the collection: `[]` List (changeable), `()` Tuple (locked), `{ }` with **key:value** = Dictionary, `{ }` with single items = Set (unique). Think: a **list** is a shopping list you can edit; a **tuple** is your date of birth — it never changes.

COMMON MISTAKE

True and False must start with a capital letter. `true` is not a Boolean; Python treats it as an unknown variable name and gives a `NameError`. Also, `"16"` (string) and `16` (int) are different: `"16" + "1"` gives `"161"`, while `16 + 1` gives `17`.

اردو میں سمجھیں

ڈیٹا ٹائپ (Data Type) بتاتی ہے کہ ویری ایبل میں کس قسم کا ڈیٹا ہے۔ `int` مکمل اعداد، `float` اعشاریہ والے اعداد، `str` متن، اور `bool` صرف `True` یا `False` کے لیے ہے۔ لسٹ (List) تبدیل ہو سکتی ہے، ٹپل (Tuple) تبدیل نہیں ہو سکتا، ڈکشنری (Dictionary) کی اور ویلیو کے جوڑے ہوتے ہیں، اور سیٹ (Set) میں کوئی چیز دہرائی نہیں جاتی۔

EXAM TIP

Expect: "Name any four data types with examples" or "Differentiate list and tuple". For a difference question, use a two-column table: list — `[ ]`, changeable, e.g. `marks = [85, 90]`; tuple — `( )`, unchangeable, e.g. `coords = (10, 20)`.

CHECK YOURSELF

1. What is the data type of each? `3.0`, `"3"`, `3`, `False`, `[3]`
2. Predict the output: `print(len({5, 5, 6, 6, 6}))`
3. Which type should store a student's CNIC/B-Form number such as `"42101-1234567-1"`? Why?

Answers: 1. float, str, int, bool, list. 2. 2 (the set keeps only 5 and 6). 3. str, because it contains hyphens and you never do arithmetic on it.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is the data type of each? `3.0`, `"3"`, `3`, `False`, `[3]`

3 marks. Explain Data Types in Python with two clear points and one example.

5 marks. Expect: "Name any four data types with examples" or "Differentiate list and tuple". For a difference question, use a two-column table: list — `[ ]`, changeable, e.g. `marks = [85, 90]`; tuple — `( )`,...

8 marks. Data Types in Python: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. float, str, int, bool, list 3. The type decides what you can do with the data (you can divide numbers, but not names).; Python has several built-in data types: 5. Use the recipe in the blue box. Model opening: A data type specifies the kind of data a variable holds — a whole number, a decimal, text, True/False, or a collection of items. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Data Types in Python** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.4.2 Input and Output Handling

ACADEMY SESSION

Session 7 of 20 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Output — the `print()` function.

Error clinic: If the user types letters where a number is expected, `int()` crashes with `ValueError: invalid literal for int() with base 10` (see 3.7).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Input and Output Handling**. Write: Output — the `print()` function.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Items separated by commas are printed with one space between them. (2) An f-string (a string with `f` before the quote) lets you put variables directly inside `{ }`. It is the fastest and most readable way to... — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Output — the `print()` function. A **function** is a named, ready-made piece of code that does a job when you call it with brackets. `print()` displays information on the screen.

- Items separated by commas are printed with one space between them.
- An **f-string** (a string with `f` before the quote) lets you put variables directly inside `{ }`. It is the fastest and most readable way to format output.

Input — the `input()` function. It shows a message (a **prompt**), **pauses the program** and waits for the user to type something and press Enter. Whatever the user types is **always a string** by default.

Type casting means converting a value from one type to another: `int()` converts to an integer, `float()` to a decimal number, `str()` to a string.

```
# 1. Print only a string
print("Hello Class!")

# 2. Print a string and a variable (comma separates them)
name = "Ali"
print("Welcome,", name)

# 3. f-strings (fastest and most readable way to format)
age = 16
print(f"My name is {name} and I am {age} years old.")
```

OUTPUT

```
Hello Class!
Welcome, Ali
My name is Ali and I am 16 years old.
```

Two useful extras: `sep` changes the separator between items, and `end` changes what is printed at the end (normally a new line).

```
print("10", "09", "2026", sep="-")
print("Loading", end="...")
print("done")
print(f"Total: {7 * 3}")
```

OUTPUT

```
10-09-2026
Loading...done
Total: 21
```

WORKED EXAMPLE

Taking input with type casting.

```
# Taking text input
user_name = input("Enter your name: ")
# Type casting: converting string input to an integer (int)
age = int(input("Enter your age: "))
# Type casting: converting string input to a decimal (float)
height = float(input("Enter your height: "))
print(f"Hello {user_name}! Next year you will be {age + 1}.")
print("Height:", height, "feet")
```

Sample run (the user types Sara, 16 and 5.4):

OUTPUT

```
Enter your name: Sara
Enter your age: 16
Enter your height: 5.4
Hello Sara! Next year you will be 17.
Height: 5.4 feet
```

Why type casting matters. Without `int()`, the numbers stay as text and `+` joins them:

```
a = input("First number: ")
b = input("Second number: ")
print(a + b)
print(int(a) + int(b))
```

OUTPUT

```
First number: 5
Second number: 3
53
8
```

"5" + "3" joins two strings into "53" (called **concatenation**). 5 + 3 adds numbers to give 8.

REMEMBER IT

"input() always gives a string." If you plan to do maths, wrap it: `int(input(...))` for whole numbers, `float(input(...))` for decimals. Read it from the inside out: first `input`, then convert.

COMMON MISTAKE

If the user types letters where a number is expected, `int()` crashes with `ValueError: invalid literal for int() with base 10` (see 3.7). Also, `int("5.4")` fails — use `float()` for decimal input.

`print()` اسکرین پر معلومات دکھاتا ہے اور `input()` صارف سے معلومات لیتا ہے۔ یاد رکھیں کہ `input()` ہمیشہ اسٹرنگ (String) دیتا ہے، اس لیے حساب کے لیے اسے `int()` یا `float()` سے تبدیل کرنا ضروری ہے۔ اسے ٹائپ کاسٹنگ (Type Casting) کہتے ہیں۔ ایف اسٹرنگ (f-string) سے ویری ایبلز کو جملے کے اندر آسانی سے لکھا جا سکتا ہے۔

CHECK YOURSELF

1. Predict the output:

```
a = "3"
b = 4
print(a * b)
print(int(a) * b)
```

2. Find the error: the user types 21 but the output is 2121, not 42.

```
num = input("Enter a number: ")
print(num * 2)
```

Answers: 1. 3333 then 12 (a string times a number repeats the string). 2. `input()` returns the string "21", and a string times 2 repeats it. Fix: `num = int(input("Enter a number: "))`.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Predict the output:

3 marks. Explain Input and Output Handling with two clear points and one example.

5 marks. Write a 5-mark answer on Input and Output Handling: definition, two points, a labelled diagram or table, and one example.

Answers: 1. 3333 then 12 (a string times a number repeats the string) 3. Items separated by commas are printed with one space between them.; An f-string (a string with f before the quote) lets you put variables directly inside { }. It is the fastest and most readable way to... 5. Use the recipe in the blue box. Model opening: Output — the `print()` function.

BATCH HOMEWORK

Write a 5-mark answer on **Input and Output Handling** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.4.3 Operators and Operands: Arithmetic and Assignment ★ Golden

ACADEMY SESSION

Session 8 of 20 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: An operand is the value or variable being worked on.

Error clinic: ^ is not power in Python — it is bitwise XOR (see bitwise operators).

Exam wording to train: You will be asked to evaluate expressions such as `17 // 5`, `17 % 5`, `2 ** 4` or to trace compound assignment.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Operators and Operands: Arithmetic and Assignment**. Write: An operand is the value or variable being worked on.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) An operator is the symbol that performs the action. (2) Together they form an expression, which Python evaluates to a single value. — + example.

5 marks: 3-mark structure + table: Operator / Purpose / Example / Result + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

An **operand** is the value or variable being worked on. An **operator** is the symbol that performs the action. Together they form an **expression**, which Python evaluates to a single value.

In `10 + 20`: **10** is an operand, **+** is the operator, **20** is an operand, and the result is **30**.

1. Arithmetic operators do maths:

Operator	Purpose	Example	Result
<code>+</code>	Addition	<code>5 + 3</code>	8
<code>-</code>	Subtraction	<code>10 - 4</code>	6
<code>*</code>	Multiplication	<code>4 * 2</code>	8
<code>/</code>	Division (result is always a float)	<code>9 / 2</code>	4.5
<code>//</code>	Floor division (drops the decimal part)	<code>9 // 2</code>	4
<code>%</code>	Modulus (remainder)	<code>9 % 2</code>	1
<code>**</code>	Exponentiation (power)	<code>2 ** 3</code>	8

```
print(5 + 3)
print(10 - 4)
print(4 * 2)
print(9 / 2)
print(9 // 2)
print(9 % 2)
print(2 ** 3)
print(8 / 2)
```

OUTPUT

```
8
6
8
4.5
4
1
8
4.0
```

Notice the last line: `8 / 2` gives `4.0`, not `4`, because `/` always gives a float.

Order of operations (precedence). Python follows the same order as maths (like BODMAS): brackets first, then `**`, then `*` `/` `//` `%` (left to right), then `+` `-` (left to right). `**` is the exception: it works right to left.

```
print(2 + 3 * 4)
print((2 + 3) * 4)
print(2 ** 3 ** 2)
print(10 - 4 - 3)
print(-9 // 2)
print(17 % 5, 17 // 5)
```

OUTPUT

```
14
20
512
3
-5
2 3
```

`2 ** 3 ** 2 = 2 ** 9 = 512` (right to left). `-9 // 2` is `-5` because floor division always rounds **down** to the smaller whole number (`-4.5 → -5`).

2. Assignment operators store a value in a variable, often updating it. The short forms are called **compound assignment**.

Operator	Example	Equivalent to
<code>=</code>	<code>x = 5</code>	Assign 5 to x
<code>+=</code>	<code>x += 2</code>	<code>x = x + 2</code>
<code>-=</code>	<code>x -= 1</code>	<code>x = x - 1</code>
<code>*=</code>	<code>x *= 3</code>	<code>x = x * 3</code>
<code>/=</code> , <code>/=</code> , <code>%=</code> , <code>**=</code>	<code>x /= 2</code>	<code>x = x / 2</code> (and so on)

WORKED EXAMPLE

Tracing assignment operators. Follow the value of `x` line by line:

```
x = 5
x += 2    # x = 5 + 2
print(x)
x -= 1    # x = 7 - 1
print(x)
x *= 3    # x = 6 * 3
print(x)
x /= 2    # x = 18 / 2
print(x)
```

OUTPUT

```
7
6
18
9.0
```

Using `%` and `//` to split digits. `% 10` gives the last digit; `// 10` removes it.

```
n = 357
last = n % 10    # remainder after dividing by 10
rest = n // 10   # drop the last digit
print("Last digit:", last)
print("Remaining:", rest)
```

OUTPUT

```
Last digit: 7
Remaining: 35
```

`357 ÷ 10 = 35` remainder `7`. So `357 // 10 = 35` and `357 % 10 = 7`.

REMEMBER IT

Three kinds of division: `/` = exact answer (float), `//` = quotient only ("floor"), `%` = remainder only. A number is even when `n % 2 == 0`.

COMMON MISTAKE

`^` is **not** power in Python — it is bitwise XOR (see bitwise operators). `2 ^ 3` gives 1, not 8. For power, always use `**`.

اردو میں سمجھیں

آپرینڈ (Operand) وہ ویلیو ہے جس پر عمل ہوتا ہے اور آپریٹر (Operator) وہ علامت ہے جو عمل کرتی ہے۔ `/` ہمیشہ اعشاریہ والا جواب دیتا ہے، `//` صرف حاصل تقسیم دیتا ہے، `%` باقی دیتا ہے اور `**` طاقت (Power) نکالتا ہے۔ `x += 2` کا مطلب ہے `x = x + 2`۔

EXAM TIP

You will be asked to evaluate expressions such as `17 // 5`, `17 % 5`, `2 ** 4` or to trace compound assignment. Show each step and write the final value with its type (e.g. `9.0` is a float, so write the `.0`).

CHECK YOURSELF

1. Predict the output:

```
x = 7
y = 2
print(x // y, x % y, x / y)
print(x ** y)
```

2. Predict the output:

```
x = 10
x += 5
x /= 4
print(x)
```

Answers: 1. 3 1 3.5 then 49. 2. 3 (10 + 5 = 15; 15 // 4 = 3).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Predict the output:

3 marks. Explain Operators and Operands: Arithmetic and Assignment with two clear points and one example.

5 marks. You will be asked to evaluate expressions such as `17 // 5`, `17 % 5`, `2 ** 4` or to trace compound assignment. Show each step and write the final value with its type (e.g. `9.0` is a float, so write the...).

8 marks. Operators and Operands: Arithmetic and Assignment: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. 3 1 3.5 then 49. 3. An operator is the symbol that performs the action.; Together they form an expression, which Python evaluates to a single value. 5. Use the recipe in the blue box. Model opening: An operand is the value or variable being worked on. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Operators and Operands: Arithmetic and Assignment** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.4.3 Relational, Logical and Membership Operators ★ Golden

ACADEMY SESSION

Session 9 of 20 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: 3.

Error clinic: Do not confuse = (assignment, "store") with == (comparison, "is it equal?").

Exam wording to train: Typical: "Evaluate $a > b$ and $b > 3$ for $a = 10$, $b = 5$ " or "Write the truth table of and/or".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Relational, Logical and Membership Operators**. Write: 3.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Relational (comparison) operators compare two values and return a Boolean (True or False). (2) They are used in conditions. — + example.

5 marks: 3-mark structure + table: Op / Description / Example ($a = 10$, $b = 5$) / Result + the worked example from this topic.

8–10 marks: 5-mark structure + a complete truth table and a labelled gate / logic diagram + a one-line conclusion. Method marks are awarded for working.

LEARN IT

3. Relational (comparison) operators compare two values and return a **Boolean** (True or False). They are used in conditions.

Op	Description	Example ($a = 10$, $b = 5$)	Result
<code>=</code>	Equal to	<code>a == b</code>	False
<code>≠</code>	Not equal to	<code>a != b</code>	True
<code>></code>	Greater than	<code>a > b</code>	True
<code><</code>	Less than	<code>a < b</code>	False
<code>≥</code>	Greater than or equal to	<code>a ≥ 10</code>	True
<code>≤</code>	Less than or equal to	<code>a ≤ b</code>	False


```

a = 10
b = 5
print(a == b)
print(a != b)
print(a > b)
print(a < b)
print(a >= 10)
print(a <= b)

```

OUTPUT

```

False
True
True
False
True
False

```

4. Logical operators combine several conditions:

A	B	A and B	A or B	not A
False	False	False	False	True
False	True	False	True	True
True	False	False	True	False
True	True	True	True	False

- **and** — True **only if both** conditions are true.
- **or** — True if **at least one** condition is true.
- **not** — **reverses** the result (True becomes False, False becomes True).

```

a = 10
b = 5
print(a > 5 and b > 5)
print(a > 5 or b > 5)
print(not a > 5)

```

OUTPUT

```

False
True
False

```

5. Membership operators check whether a value exists inside a sequence (such as a string or list): **in** and **not in**.

```

name = "Python"
print("P" in name)
print("z" not in name)
print("p" in name)
marks = [85, 90, 75]
print(90 in marks)

```

OUTPUT

```

True
True
False
True

```

"p" in name is False because strings are case-sensitive: the word has a capital P.

WORKED EXAMPLE

Real-life conditions. A person can apply for a CNIC if they are 18 or older **and** have the documents. Marks are invalid if they are below 0 **or** above 100.

```
age = 20
has_cnic = True
print(age ≥ 18 and has_cnic)
marks = 45
print(marks < 0 or marks > 100)
```

OUTPUT

```
True
False
```

Step by step: $20 \geq 18$ is True, has_cnic is True, True and True = **True**. For marks: $45 < 0$ is False, $45 > 100$ is False, False or False = **False** (the marks are valid).

REMEMBER IT

AND is strict, OR is generous. AND is like a teacher who needs both homework and attendance; OR is like a shop that accepts cash **or** card. Order of evaluation: **not** first, then **and**, then **or**.

COMMON MISTAKE

Do not confuse = (assignment, "store") with == (comparison, "is it equal?"). Writing `if x = 5:` is a **syntax error**; the correct form is `if x == 5:`.

اردو میں سمجھیں

ریشنل آپریٹرز (Relational Operators) دو ویلیوز کا موازنہ کر کے True یا False دیتے ہیں۔ لاجیکل آپریٹرز میں **and** تب True دیتا ہے جب دونوں شرطیں درست ہوں، **or** تب جب کم از کم ایک درست ہو، اور **not** نتیجہ الٹ دیتا ہے۔ **in** اور **not in** دیکھتے ہیں کہ کوئی چیز اسٹرینگ یا لسٹ میں موجود ہے یا نہیں۔

EXAM TIP

Typical: "Evaluate $a > b$ and $b > 3$ for $a = 10$, $b = 5$ " or "Write the truth table of **and** / **or**". Write each sub-condition's value first, then combine. Remember: `=` compares, `=` assigns.

CHECK YOURSELF

1. Predict the output:

```
print(True and False or True)
print(not (5 > 3) or 2 == 2.0)
```

2. Find the error:

```
x = 5
if x = 5:
    print("five")
```

Answers: 1. True and True. (True and False = False; False or True = True. not True = False; $2 == 2.0$ is True; False or True = True.) 2. = is assignment; a comparison needs ==. Python reports SyntaxError: invalid syntax. Maybe you meant '=' or '==' instead of '='? Fix: `if x == 5:`

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Predict the output:

3 marks. Explain Relational, Logical and Membership Operators with two clear points and one example.

5 marks. Typical: "Evaluate $a > b$ and $b > 3$ for $a = 10, b = 5$ " or "Write the truth table of and/or". Write each sub-condition's value first, then combine. Remember: $==$ compares, $=$ assigns.

8 marks. Relational, Logical and Membership Operators: 5-mark answer plus a complete truth table and a labelled gate / logic diagram.

Answers: 1. True and True. (True and False = False; False or True = True. not True = False; $2 == 3$. Relational (comparison) operators compare two values and return a Boolean (True or False).; They are used in conditions. 5. Use the recipe in the blue box. Model opening: 3. 8. Same 5-mark body + a complete truth table and a labelled gate / logic diagram + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Relational, Logical and Membership Operators** using the recipe in this topic. Include a complete truth table and a labelled gate / logic diagram. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.4.3 Bitwise Operators ★ Golden

ACADEMY SESSION

Session 10 of 20 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: 6.

Error clinic: Do not mix up the logical and bitwise operators: and/or/not work on True/False conditions, while $\&/\|/\sim$ work on the bits of integers.

Exam wording to train: Exams ask you to "evaluate $12 \& 10, 12 \mid 10, 12 \wedge 10, \sim 5, 7 >> 1$ showing binary working".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Bitwise Operators**. Write: 6.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) OR ($\mid$) — gives 1 if at least one bit is 1. (2) XOR ($\wedge$) — gives 1 if the bits are different, 0 if they are the same. — + example.

5 marks: 3-mark structure + table: Bit A / Bit B / $A \& B$ / $A \mid B$ / $A \wedge B$ / $\sim A$ + the worked example from this topic.

8–10 marks: 5-mark structure + a complete truth table and a labelled gate / logic diagram + a one-line conclusion. Method marks are awarded for working.

LEARN IT

6. Bitwise operators treat numbers as **binary digits** (bits: 0s and 1s) and work on them **bit by bit**, column by column. Think of each bit as a switch that is ON (1) or OFF (0). Python's `bin()` function shows the binary form of a number (it starts with `0b`).

- **AND (&)** — gives 1 **only if both** bits are 1, otherwise 0.
- **OR (|)** — gives 1 if **at least one** bit is 1.
- **XOR (^)** — gives 1 if the bits are **different**, 0 if they are the **same**.
- **NOT (~)** — inverts all bits (0 → 1, 1 → 0). In Python the result is the number made negative, minus 1: $\sim x = -(x + 1)$. So ~ 10 gives -11 .
- **Left shift (<<)** — moves bits left and adds 0s on the right. Each shift **multiplies by 2**.
- **Right shift (>>)** — moves bits right and removes the rightmost bits. Each shift **divides by 2** (floor division).

Bit A	Bit B	A & B	A B	A ^ B	~A
0	0	0	0	0	1
0	1	0	1	1	1
1	0	0	1	1	0
1	1	1	1	0	0

WORKED EXAMPLE

Worked example: a = 10, b = 6. First convert to binary using place values 8, 4, 2, 1: $10 = 8 + 2 = \mathbf{1010}$; $6 = 4 + 2 = \mathbf{0110}$. Then work column by column.

	8	4	2	1	Decimal
a = 10	1	0	1	0	10
b = 6	0	1	1	0	6
a & b	0	0	1	0	2
a b	1	1	1	0	14
a ^ b	1	1	0	0	12

- AND: only the "2" column has 1 in both → $0010 = \mathbf{2}$.
- OR: columns 8, 4 and 2 have at least one 1 → $1110 = 8 + 4 + 2 = \mathbf{14}$.
- XOR: columns 8 and 4 are different; column 2 is the same (both 1) → $1100 = 8 + 4 = \mathbf{12}$.
- NOT: $\sim 10 = -(10 + 1) = \mathbf{-11}$.

```
a = 10
b = 6
print(bin(a), bin(b))
print(a & b)
print(a | b)
print(a ^ b)
print(~a)
```

OUTPUT

```
0b1010 0b110
2
14
12
-11
```

Worked example: shifts. 5 in 8 bits is **0000 0101**.

Expression	Binary	Decimal	What happened
5	0000 0101	5	start
5 << 1	0000 1010	10	add one 0 on the right (5 × 2)
5 << 2	0001 0100	20	add 00 on the right (5 × 4)
20 >> 1	0000 1010	10	remove the rightmost bit (20 ÷ 2)
20 >> 2	0000 0101	5	remove two bits (20 ÷ 4)

```
a = 5          # Binary: 0000 0101
print(a << 1)   # 0000 1010
print(a << 2)   # 0001 0100
b = 20         # Binary: 0001 0100
print(b >> 1)   # 0000 1010
print(b >> 2)   # 0000 0101
print(bin(20 >> 2))
```

OUTPUT

```
10
20
10
5
0b101
```

REMEMBER IT

Shortcuts: $x \ll n = x \times 2^n$, $x \gg n = x // 2^n$, $\sim x = -x - 1$. For AND/OR/XOR always write both numbers in binary, one under the other, with the same number of bits.

COMMON MISTAKE

Do not mix up the logical and bitwise operators: `and` / `or` / `not` work on True/False conditions, while `&` / `|` / `~` work on the bits of integers. Also remember `bin(6)` prints `0b110`, without the leading zero — add zeros yourself when lining up columns.

اردو میں سمجھیں

بٹ وائز آپریٹرز (Bitwise Operators) اعداد کو بائری میں بدل کر ہر بٹ پر الگ الگ کام کرتے ہیں۔ `&` تب 1 دیتا ہے جب دونوں بٹ 1 ہوں، `|` تب جب کوئی ایک بھی 1 ہو، اور `^` تب جب دونوں بٹ مختلف ہوں۔ `~` تمام بٹ الٹ دیتا ہے، اس لیے `~10` کا جواب -11 ہے۔ لیفٹ شفٹ عدد کو 2 سے ضرب دیتا ہے اور رائٹ شفٹ 2 سے تقسیم کرتا ہے۔

EXAM TIP

Exams ask you to "evaluate $12 \& 10$, $12 | 10$, $12 \wedge 10$, ~ 5 , $7 \gg 1$ showing binary working". Marks are given for the binary conversion and column working, not just the final number. Always draw the column table.

CHECK YOURSELF

1. Predict the output (show the binary working):

```
print(12 & 10, 12 | 10, 12 ^ 10)
print(~5, 7 >> 1, 3 << 3)
```

2. What does `bin(13)` print?

Answers: 1. 8 14 6 and -6 3 24. $12 = 1100$, $10 = 1010$: AND = $1000 = 8$, OR = $1110 = 14$, XOR = $0110 = 6$. $\sim 5 = -(5 + 1) = -6$. $7 = 111 \rightarrow 11 = 3$. $3 = 11 \rightarrow 11000 = 24$ (3×8). 2. `0b1101` ($8 + 4 + 1$).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Predict the output (show the binary working):

3 marks. Explain Bitwise Operators with two clear points and one example.

5 marks. Exams ask you to "evaluate $12 \& 10$, $12 | 10$, $12 \wedge 10$, ~ 5 , $7 \gg 1$ showing binary working". Marks are given for the binary conversion and column working, not just the final number. Always draw the...

8 marks. Bitwise Operators: 5-mark answer plus a complete truth table and a labelled gate / logic diagram.

Answers: 1. 8 14 6 and -6 3 24. $12 = 1100$, $10 = 1010$: AND = $1000 = 8$, OR = $1110 = 14$, XOR = $0110 = 6$. $\sim 5 = -(5 + 1) = -6$. $7 = 111 \rightarrow 11 = 3$. $3 = 11 \rightarrow 11000 = 24$ (3×8). 3. OR (`|`) — gives 1 if at least one bit is 1.; XOR (`^`) — gives 1 if the bits are different, 0 if they are the same. 5. Use the recipe in the blue box. Model opening: 6. 8. Same 5-mark body + a complete truth table and a labelled gate / logic diagram + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Bitwise Operators** using the recipe in this topic. Include a complete truth table and a labelled gate / logic diagram. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.5 Control Structures ★ Golden

ACADEMY SESSION

Session 11 of 20 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Control structures decide the order in which statements are executed in a program (the "flow of control").

Error clinic: Selection and repetition both use conditions, but they are different: selection runs a block at most once; repetition can run a block many times.

Exam wording to train: "Name and explain the three basic control structures" is a very common short question.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Control Structures**. Write: Control structures decide the order in which statements are executed in a program (the "flow of control").

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Selection — choose a path depending on a condition (if, else). (2) Repetition — repeat steps (loops: for, while). — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Control structures decide the **order in which statements are executed** in a program (the "flow of control"). Almost every program is built from just three basic structures:

1. **Sequence** — do the steps one after another, top to bottom.
2. **Selection** — choose a path depending on a condition (if, else).
3. **Repetition** — repeat steps (loops: for, while).

WORKED EXAMPLE

Morning routine as control structures:

- Sequence: wake up → brush teeth → have breakfast.
- Selection: **if** it is raining, take an umbrella; **else** take a cap.
- Repetition: **while** the bus has not come, keep waiting.

REMEMBER IT

Remember **"S-S-R"**: Sequence, Selection, Repetition — "Step, Select, Repeat".

COMMON MISTAKE

Selection and repetition both use conditions, but they are different: selection runs a block **at most once**; repetition can run a block **many times**.

اردو میں سمجھیں

کنٹرول اسٹرکچرز (Control Structures) طے کرتے ہیں کہ پروگرام کی ہدایات کس ترتیب سے چلیں گی۔ تین بنیادی اسٹرکچر ہیں: سیکوئنس (ترتیب وار)، سلیکشن (شرط کی بنیاد پر انتخاب) اور ریپیٹیشن (دہرانا یعنی لوپ)۔

EXAM TIP

"Name and explain the three basic control structures" is a very common short question. Give a one-line definition and a two-line Python example for each.

CHECK YOURSELF

1. Name the three basic control structures.
2. Which structure is used for "keep asking for the password until it is correct"?

Answers: 1. Sequence, selection, repetition. 2. Repetition (a while loop).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name the three basic control structures.

3 marks. Explain Control Structures with two clear points and one example.

5 marks. "Name and explain the three basic control structures" is a very common short question. Give a one-line definition and a two-line Python example for each.

8 marks. Control Structures: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. Sequence, selection, repetition 3. Selection — choose a path depending on a condition (if, else).; Repetition — repeat steps (loops: for, while). 5. Use the recipe in the blue box. Model opening: Control structures decide the order in which statements are executed in a program (the "flow of control"). 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Control Structures** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.5.1 Sequence

ACADEMY SESSION

Session 12 of 20 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Sequence means statements are executed one after another, strictly from top to bottom, in the exact order they are written.

Error clinic: Order matters.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Sequence**. Write: Sequence means statements are executed one after another, strictly from top to bottom, in the exact order they are written.


2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) This is the default behaviour of Python. (2) No statement is skipped or repeated. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

Sequence means statements are executed **one after another, strictly from top to bottom**, in the exact order they are written. This is the **default behaviour** of Python. No statement is skipped or repeated.



Sequence: control flows straight down from one statement to the next.

WORKED EXAMPLE

Input → Process → Output in sequence.

```
print("Enter two numbers")
a = int(input("Enter first number: ")) # Step 1: Input
b = int(input("Enter second number: ")) # Step 2: Input
total = a + b # Step 3: Process
print("Sum =", total) # Step 4: Output
```

Sample run (user types 7 and 5):

```
OUTPUT
Enter two numbers
Enter first number: 7
Enter second number: 5
Sum = 12
```

Each line runs exactly once, in order. If you moved line 4 (`total = a + b`) above the input lines, Python would stop with a `NameError` because `a` and `b` would not exist yet.

REMEMBER IT

Sequence is like reading a page: line 1, then line 2, then line 3. Most programs follow the pattern **Input → Process → Output**.

COMMON MISTAKE

Order matters. A variable must be given a value **before** it is used. Using it first causes `NameError: name '...' is not defined`.

اردو میں سمجھیں

سیکوئنس (Sequence) کا مطلب ہے کہ ہدایات بالکل اسی ترتیب سے ایک کے بعد ایک اوپر سے نیچے چلتی ہیں جس ترتیب سے لکھی گئی ہیں۔ یہ پائنتھن کا عام طریقہ ہے۔ کسی ویری ایبل کو استعمال کرنے سے پہلے اس میں ویلیو رکھنا ضروری ہے۔

CHECK YOURSELF

1. Predict the output:

```
x = 4
y = x * 2
x = 10
print(x, y)
```

2. What is the default control structure in Python?

Answers: 1. 10 8 — y was calculated when x was still 4; changing x later does not change y. 2. Sequence.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Predict the output:

3 marks. Explain Sequence with two clear points and one example.

5 marks. Write a 5-mark answer on Sequence: definition, two points, a labelled diagram or table, and one example.

Answers: 1. 10 8 — y was calculated when x was still 4; changing x later does not change y. 3. This is the default behaviour of Python.; No statement is skipped or repeated. 5. Use the recipe in the blue box. Model opening: Sequence means statements are executed one after another, strictly from top to bottom, in the exact order they are written.

BATCH HOMEWORK

Write a 5-mark answer on **Sequence** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.5.2 Selection Statements: if and if-else ★ Golden

ACADEMY SESSION

Session 13 of 20 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Selection changes the flow of a program based on a condition — an expression that is either True or False.

Error clinic: Common mistakes: forgetting the colon (SyntaxError: expected ':'), writing a condition after else (else age < 18: is wrong), and not indenting else at the same...

Exam wording to train: Asked as: "Write a program that inputs a number and prints whether it is even or odd / positive or negative / pass or fail." Write the full program with...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Selection Statements: if and if-else**. Write: Selection changes the flow of a program based on a condition — an expression that is either True or False.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It helps a program respond intelligently to different situations. (2) The if statement executes a block of code only if the condition is True. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a fully labelled diagram copied from the board + a one-line conclusion. Method marks are awarded for working.

LEARN IT


Selection changes the flow of a program based on a **condition** — an expression that is either True or False. It helps a program respond intelligently to different situations.

1. The if statement executes a block of code **only if** the condition is True. If the condition is False, the block is completely skipped.

```
if condition:
    statement(s)    # runs only when condition is True
```

2. The if-else statement provides **two paths**: if the condition is true, do this; **else** (otherwise), do that. Exactly one of the two blocks always runs.

```
if condition:
    block A         # condition True
else:
    block B         # condition False
```



An if-else statement: one diamond (condition), two paths, then the paths join again.

WORKED EXAMPLE

The if statement.

```
age = int(input("Enter your age: "))
if age >= 18:
    print("You are an Adult.")    # runs only if age >= 18
print("Program continues...")    # runs every time
```

Run 1 (user types 20):

```
OUTPUT
Enter your age: 20
You are an Adult.
Program continues...
```

Run 2 (user types 15):

```
OUTPUT
Enter your age: 15
Program continues...
```

The last line is not indented, so it is outside the `if` block and runs every time.

The if-else statement.

```
age = int(input("Enter your age: "))
if age ≥ 18:
    print("Apply for CNIC.")
else:
    print("Apply for CRC (B-Form).")
```

Sample run (user types 16):

OUTPUT

```
Enter your age: 16
Apply for CRC (B-Form).
```

Even or odd — a classic if-else program:

```
n = 7
if n % 2 == 0:
    print(n, "is even")
else:
    print(n, "is odd")
```

OUTPUT

```
7 is odd
```

7 % 2 = 1, and 1 == 0 is False, so the `else` block runs.

REMEMBER IT

Formatting rule: put a **colon (:)** after `if` and `else`, and **indent** the code inside the blocks. `else` never has a condition of its own.

COMMON MISTAKE

Common mistakes: forgetting the colon (`SyntaxError: expected ':'`), writing a condition after `else` (`else age < 18: is wrong`), and not indenting `else` at the same level as its `if`.

اردو میں سمجھیں

سلیکشن (Selection) میں پروگرام شرط کی بنیاد پر فیصلہ کرتا ہے۔ `if` کا بلاک صرف تب چلتا ہے جب شرط درست (True) ہو۔ `if-else` میں دو راستے ہوتے ہیں: شرط درست ہو تو پہلا بلاک، ورنہ `else` والا بلاک چلتا ہے۔ `if` اور `else` کے بعد کولن (:) اور اندر کے کوڈ کی انڈینٹیشن ضروری ہے۔

EXAM TIP

Asked as: "Write a program that inputs a number and prints whether it is even or odd / positive or negative / pass or fail." Write the full program with `int(input())`, the condition, both blocks, and a sample run.

CHECK YOURSELF

1. Predict the output when `marks = 32`:

```
marks = 32
if marks ≥ 33:
    print("Pass")
else:
    print("Fail")
print("Done")
```

2. Find the two errors:

```
n = 5
if n > 0
    print("Positive")
else n ≤ 0:
    print("Not positive")
```

Answers: 1. Fail then Done . 2. Missing colon after `if n > 0`; `else` must not have a condition — write `else:` .

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Predict the output when `marks = 32`:

3 marks. Explain Selection Statements: `if` and `if-else` with two clear points and one example.

5 marks. Asked as: "Write a program that inputs a number and prints whether it is even or odd / positive or negative / pass or fail." Write the full program with `int(input())`, the condition, both blocks, and...

8 marks. Selection Statements: `if` and `if-else`: 5-mark answer plus a fully labelled diagram copied from the board.

Answers: 1. Fail then Done 3. It helps a program respond intelligently to different situations.; The `if` statement executes a block of code only if the condition is True. 5. Use the recipe in the blue box. Model opening: Selection changes the flow of a program based on a condition — an expression that is either True or False. 8. Same 5-mark body + a fully labelled diagram copied from the board + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Selection Statements: `if` and `if-else`** using the recipe in this topic. Include a fully labelled diagram copied from the board. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.5.2 Selection Statements: `if-elif-else` and Nested `if` ★ Golden

ACADEMY SESSION

Session 14 of 20 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: 3.

Error clinic: Wrong order gives wrong answers.

Exam wording to train: Grade-calculator programs (`if-elif-else`) and "largest of three numbers" are very common long questions.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Selection Statements: if-elif-else and Nested if**. Write: 3.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) (elif is short for "else if".) Python checks the conditions from top to bottom. (2) As soon as it finds a True condition, it runs that block and ignores all the rest. — + example.

5 marks: 3-mark structure + table: marks / ≥ 80 ? / ≥ 70 ? / ≥ 60 ? / Output + the worked example from this topic.

8–10 marks: 5-mark structure + a complete truth table and a labelled gate / logic diagram + a one-line conclusion. Method marks are awarded for working.

LEARN IT

3. The if-elif-else statement handles **many conditions**. (elif is short for "else if".) Python checks the conditions **from top to bottom**. As soon as it finds a True condition, it runs that block and **ignores all the rest**. If none is True, the else block runs.

4. Nested if is an if inside another if. It is used when a decision needs to pass **several levels of checks**: the inner check happens only if the outer check passed.

WORKED EXAMPLE

Grading with if-elif-else.

```
marks = int(input("Enter marks: "))
if marks ≥ 80:
    print("A-1 Grade")
elif marks ≥ 70:
    print("A Grade")
elif marks ≥ 60:
    print("B Grade")
else:
    print("Fail or below B")
```

Sample run (user types 75):

OUTPUT

```
Enter marks: 75
A Grade
```

Trace for different marks:

marks	≥ 80 ?	≥ 70 ?	≥ 60 ?	Output
92	True	(not checked)	(not checked)	A-1 Grade
75	False	True	(not checked)	A Grade
60	False	False	True	B Grade
41	False	False	False	Fail or below B

Loan approval with nested if.

```

age = 20
salary = 35000
if age ≥ 18:
    # passed first check
    if salary ≥ 30000:
        # passed second check
        print("Loan APPROVED!")
    else:
        print("Salary too low for loan.")
else:
    print("Too young for loan.")

```

OUTPUT

Loan APPROVED!

age	salary	Outer check (age ≥ 18)	Inner check (salary ≥ 30000)	Output
20	35000	True	True	Loan APPROVED!
20	25000	True	False	Salary too low for loan.
16	35000	False	(never checked)	Too young for loan.

When you only need a yes/no answer, two levels can often be joined with `and` — but then you lose the separate messages:

```

age = 20
salary = 25000
if age ≥ 18 and salary ≥ 30000:
    print("Loan APPROVED!")
else:
    print("Loan not approved.")

```

OUTPUT

Loan not approved.

REMEMBER IT

In an `if-elif-else` ladder, put the **strictest condition first** (highest marks first). Think of a ladder: you step off at the first rung that fits.

COMMON MISTAKE

Wrong order gives wrong answers. Here 85 marks gets "B Grade", because `85 ≥ 60` is True first and the other conditions are ignored:

```

marks = 85
if marks ≥ 60:
    print("B Grade")
elif marks ≥ 70:
    print("A Grade")
elif marks ≥ 80:
    print("A-1 Grade")

```

OUTPUT

B Grade

This is a **logical error**: no crash, just a wrong result. Fix it by checking `≥ 80` first.

if-elif-else میں کئی شرطیں اوپر سے نیچے ترتیب سے دیکھی جاتی ہیں، اور جو شرط سب سے پہلے درست ہو اسی کا بلاک چلتا ہے، باقی سب چھوڑ دی جاتی ہیں۔ نیسٹڈ ایف (Nested if) میں ایک if دوسرے if کے اندر ہوتا ہے، اور اندر والی شرط تب ہی دیکھی جاتی ہے جب باہر والی شرط درست ہو۔

EXAM TIP

Grade-calculator programs (if-elif-else) and "largest of three numbers" are very common long questions. Check conditions in the right order, indent nested blocks carefully (8 spaces for the inner block), and give a sample run. Tracing tables like the ones above earn full marks in "predict the output" questions.

CHECK YOURSELF

1. Predict the output:

```
temp = 30
if temp > 35:
    print("Hot")
elif temp > 25:
    print("Warm")
elif temp > 15:
    print("Pleasant")
else:
    print("Cold")
```

2. Predict the output:

```
x = 15
if x > 10:
    if x > 20:
        print("A")
    else:
        print("B")
else:
    print("C")
```

Answers: 1. Warm (30 > 35 is False; 30 > 25 is True, so the rest are skipped even though 30 > 15 is also True). 2. B (outer check 15 > 10 passes; inner check 15 > 20 fails).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Predict the output:

3 marks. Explain Selection Statements: if-elif-else and Nested if with two clear points and one example.

5 marks. Grade-calculator programs (if-elif-else) and "largest of three numbers" are very common long questions. Check conditions in the right order, indent nested blocks carefully (8 spaces for the inner...

8 marks. Selection Statements: if-elif-else and Nested if: 5-mark answer plus a complete truth table and a labelled gate / logic diagram.

Answers: 1. Warm (30 > 35 is False; 30 > 25 is True, so the rest are skipped even though 30 > 15 is also True) 3. (elif is short for "else if".) Python checks the conditions from top to bottom.; As soon as it finds a True condition, it runs that block and ignores all the rest. 5. Use the recipe in the blue box. Model opening: 3. 8. Same 5-mark body + a complete truth table and a labelled gate / logic diagram + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Selection Statements: if-elif-else and Nested if** using the recipe in this topic. Include a complete truth table and a labelled gate / logic diagram. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.5.3 Repetition Statements: the for Loop and range() ★ Golden

ACADEMY SESSION

Session 15 of 20 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A repetition statement (loop) lets a block of code run again and again.

Error clinic: Writing `range(1, 10)` to print 1 to 10 misses 10 — an "off-by-one" logical error.

Exam wording to train: Expect "predict the output" questions on `range()` with a step, and programs such as "print a table", "sum of first n numbers", "even numbers from 1 to 20".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Repetition Statements: the for Loop and range()**. Write: A repetition statement (loop) lets a block of code run again and again.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) This greatly reduces the need to write the same code many times. (2) Each single run of the loop body is called an iteration. — + example.

5 marks: 3-mark structure + table: Syntax / How it works / Example / Values produced + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **repetition statement (loop)** lets a block of code run **again and again**. This greatly reduces the need to write the same code many times. Each single run of the loop body is called an **iteration**.

1. The for loop is used when the **exact number of iterations is known**. It takes each value from a sequence one by one and stores it in the **loop variable** (e.g. `i`).

The `range()` function generates the sequence of numbers for the loop:

Syntax	How it works	Example	Values produced
<code>range(stop)</code>	From 0 up to, but not including , stop.	<code>range(3)</code>	0 1 2
<code>range(start, stop)</code>	From start up to, but not including, stop.	<code>range(2, 5)</code>	2 3 4
<code>range(start, stop, step)</code>	From start towards stop, jumping by step.	<code>range(1, 6, 2)</code>	1 3 5

```
for i in range(3):  
    print(i)
```

OUTPUT

```
0  
1  
2
```

```
for i in range(1, 6, 2):  
    print(i)
```

OUTPUT

```
1  
3  
5
```

```
for i in range(2, 5):  
    print(i)
```

OUTPUT

```
2  
3  
4
```

```
for i in range(0, 6, 2):  
    print("Even:", i)
```

OUTPUT

```
Even: 0  
Even: 2  
Even: 4
```

You can see all the values of a range at once by converting it to a list. A negative step counts **down**; if start equals stop, the range is empty:

```
print(list(range(5)))  
print(list(range(2, 5)))  
print(list(range(1, 6, 2)))  
print(list(range(10, 0, -2)))  
print(list(range(5, 5)))
```

OUTPUT

```
[0, 1, 2, 3, 4]  
[2, 3, 4]  
[1, 3, 5]  
[10, 8, 6, 4, 2]  
[]
```

WORKED EXAMPLE

Multiplication table of 7:

```
for i in range(1, 6):  
    print(f"7 x {i} = {7 * i}")
```

OUTPUT

```
7 x 1 = 7  
7 x 2 = 14  
7 x 3 = 21  
7 x 4 = 28  
7 x 5 = 35
```

Adding numbers with an accumulator. An **accumulator** is a variable that starts at 0 and collects a running total.

```
total = 0
for i in range(1, 11):
    total += i
print("Sum of 1 to 10 =", total)
```

OUTPUT

Sum of 1 to 10 = 55

i	1	2	3	4	5	...	10
total after	1	3	6	10	15	...	55

Looping over a string or list. A `for` loop can also take items directly from any sequence:

```
for ch in "Sindh":
    print(ch, end=" ")
print()
for m in [85, 90, 75]:
    print(m + 5)
```

OUTPUT

S i n d h
90
95
80

REMEMBER IT

range stops one short: `range(1, 11)` gives 1 to **10**. To include a number `n`, write `range(..., n + 1)`.
Number of values in `range(a, b)` = `b - a`.

COMMON MISTAKE

Writing `range(1, 10)` to print 1 to 10 misses 10 — an "off-by-one" logical error. Also, the loop body must be indented; a `for` line without an indented block gives `IndentationError: expected an indented block after 'for' statement`.

اردو میں سمجھیں

لوپ (Loop) کوڈ کے ایک بلاک کو بار بار چلاتا ہے۔ `for` لوپ تب استعمال ہوتا ہے جب پہلے سے معلوم ہو کہ کتنی بار دہرانا ہے۔
`range(start, stop, step)` سے، اور `range(start, stop)` سے شروع ہوتا ہے، `start` اور `stop` کے درمیان ہر `step` کے برابر چھلانگ لگاتا ہے۔ آخری عدد (`stop`) کبھی شامل نہیں ہوتا۔

EXAM TIP

Expect "predict the output" questions on `range()` with a step, and programs such as "print a table", "sum of first `n` numbers", "even numbers from 1 to 20". Always state what range produces before tracing.

CHECK YOURSELF

1. Predict the output:

```
for i in range(10, 0, -3):  
    print(i, end=" ")
```

2. Predict the output:

```
s = 0  
for k in range(2, 11, 2):  
    s += k  
print(s)
```

3. Find the error:

```
for i in range(3):  
print(i)
```

Answers: 1. 10 7 4 1 2. 30 (2 + 4 + 6 + 8 + 10). 3. The body is not indented: IndentationError. Indent print(i) by 4 spaces.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Predict the output:

3 marks. Explain Repetition Statements: the for Loop and range() with two clear points and one example.

5 marks. Expect "predict the output" questions on range() with a step, and programs such as "print a table", "sum of first n numbers", "even numbers from 1 to 20". Always state what range produces before...

8 marks. Repetition Statements: the for Loop and range(): 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. 10 7 4 1 3. This greatly reduces the need to write the same code many times.; Each single run of the loop body is called an iteration. 5. Use the recipe in the blue box. Model opening: A repetition statement (loop) lets a block of code run again and again. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Repetition Statements: the for Loop and range()** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.5.3 The while Loop, break and continue ★ Golden

ACADEMY SESSION

Session 16 of 20 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: 2.

Error clinic: Infinite loop — find the error: count = 1 while count <= 5: print(count) count is never updated, so count <= 5 stays True and the program prints 1 forever.

Exam wording to train: "Differentiate break and continue with examples" and "What is an infinite loop?" are frequent.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **The while Loop, break and continue**. Write: 2.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) **break** — exits (stops) the loop entirely and immediately. (2) **continue** — skips the rest of the current iteration and jumps to the next one. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.


LEARN IT

2. The while loop repeats a block of code **as long as a condition remains True**. It is used when the exact number of iterations is **not known in advance** (for example, "keep asking until the password is correct").

A while loop needs three parts: (1) **initialise** a variable before the loop, (2) **test** the condition, (3) **update** the variable inside the loop. If you forget the update, the condition never becomes False and the loop never stops — an **infinite loop**.

Loop control statements change the normal flow of a loop:

- **break** — exits (stops) the loop **entirely and immediately**.
- **continue** — **skips the rest of the current iteration** and jumps to the next one.



A while loop: test the condition, run the body, go back and test again.

```
count = 1
while count ≤ 3:
    print(count)
    count += 1  # VERY IMPORTANT: update the condition!
```

OUTPUT

```
1
2
3
```

WORKED EXAMPLE

Trace of the while loop above:

count	count <= 3?	Printed	count after update
1	True	1	2
2	True	2	3
3	True	3	4
4	False	—	loop ends

Sum of digits — we do not know how many digits the number has, so `while` fits well:

```
n = 4072
total = 0
while n > 0:
    digit = n % 10
    total += digit
    n = n // 10
print("Sum of digits =", total)
```

```
OUTPUT
Sum of digits = 13
```

Digits taken: 2, 7, 0, 4 → 2 + 7 + 0 + 4 = 13. `n` becomes 407, 40, 4, 0, and then the loop stops.

Password check — repeat until the user gets it right:

```
password = input("Enter password: ")
while password != "sindh123":
    print("Wrong password, try again.")
    password = input("Enter password: ")
print("Welcome!")
```

Sample run (user types `abc`, `sindh`, `sindh123`):

```
OUTPUT
Enter password: abc
Wrong password, try again.
Enter password: sindh
Wrong password, try again.
Enter password: sindh123
Welcome!
```

break and continue side by side:

```
for i in range(5):
    if i == 3:
        break
    print(i)
print("Loop ended")
```

```
OUTPUT
0
1
2
Loop ended
```

```
for i in range(5):
    if i == 3:
        continue
    print(i)
```

```
OUTPUT
0
1
2
4
```

At `i = 3` the loop stops completely, so 3 and 4 are never printed.

At `i = 3` only that iteration is skipped; the loop carries on with 4.

while True with break — a loop that runs "forever" until `break` stops it:

```
n = 1
while True:
    if n * n > 50:
        break
    n += 1
print("First number whose square is more than 50:", n)
```

```
OUTPUT
First number whose square is more than 50: 8
```

REMEMBER IT

break = "exit the room"; **continue** = "skip this turn". For every **while** loop, check the **I-T-U** rule: **I**nitialise, **T**est, **U**pdate.

COMMON MISTAKE

Infinite loop — find the error:

```
count = 1
while count ≤ 5:
    print(count)
```

`count` is never updated, so `count ≤ 5` stays True and the program prints 1 forever. Fix: add `count += 1` inside the loop. (To stop a running program in the terminal, press **Ctrl + C**.)

اردو میں سمجھیں

while لوپ اس وقت تک چلتا رہتا ہے جب تک شرط درست (True) رہے، اور یہ تب استعمال ہوتا ہے جب پہلے سے معلوم نہ ہو کہ کتنی بار دہرانا ہے۔ لوپ کے اندر ویری ایبل کو اپڈیٹ کرنا لازمی ہے ورنہ لوپ کبھی ختم نہیں ہوگا (Infinite Loop)۔ **break** لوپ کو فوراً مکمل طور پر روک دیتا ہے، جبکہ **continue** صرف موجودہ چکر چھوڑ کر اگلے چکر پر چلا جاتا ہے۔

EXAM TIP

"Differentiate **break** and **continue** with examples" and "What is an infinite loop?" are frequent. Use the two side-by-side programs above with their outputs — examiners like seeing the difference in the output (0 1 2 vs 0 1 2 4).

CHECK YOURSELF

1. Predict the output:

```
n = 1
while n < 20:
    n = n * 3
    print(n)
```

2. Predict the output:

```
for i in range(1, 8):
    if i % 3 == 0:
        continue
    if i == 7:
        break
    print(i, end=" ")
```

Answers: 1. 27 (n: 1 → 3 → 9 → 27; 27 < 20 is False, so the loop stops). 2. 1 2 4 5 (3 and 6 are skipped by **continue**; at 7 the loop breaks).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Predict the output:

3 marks. Explain The while Loop, break and continue with two clear points and one example.

5 marks. "Differentiate break and continue with examples" and "What is an infinite loop?" are frequent. Use the two side-by-side programs above with their outputs — examiners like seeing the difference in the...

8 marks. The while Loop, break and continue: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. 27 (n: 1 → 3 → 9 → 27; 27 < 20 is False, so the loop stops) 3. **break** — exits (stops) the loop entirely and immediately; **continue** — skips the rest of the current iteration and jumps to the next one. 5. Use the recipe in the blue box. Model opening: 2. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **The while Loop, break and continue** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.5.3 Nested Loops and for vs while ★ Golden

ACADEMY SESSION

Session 17 of 20 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A nested loop is a loop inside another loop.

Error clinic: Indentation decides which loop a line belongs to.

Exam wording to train: "Differentiate between for and while loops" (give three points and an example of each) and "How many times will the inner statement run?" (multiply the counts)...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Nested Loops and for vs while**. Write: A nested loop is a loop inside another loop.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The inner loop runs completely, from start to finish, for every single iteration of the outer loop. (2) If the outer loop runs 2 times and the inner loop runs 3 times, the inner body runs $2 \times 3 = 6$ times. — + example.

5 marks: 3-mark structure + table: for loop / while loop + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **nested loop** is a loop inside another loop. The **inner loop runs completely, from start to finish, for every single iteration of the outer loop**. If the outer loop runs 2 times and the inner loop runs 3 times, the inner body runs $2 \times 3 = 6$ times.

```
for outer in range(1, 3):          # runs 2 times (1, 2)
    for inner in range(1, 4):      # runs 3 times per outer (1, 2, 3)
        print(f"Outer: {outer}, Inner: {inner}")
```

OUTPUT

```
Outer: 1, Inner: 1
Outer: 1, Inner: 2
Outer: 1, Inner: 3
Outer: 2, Inner: 1
Outer: 2, Inner: 2
Outer: 2, Inner: 3
```


WORKED EXAMPLE

A star triangle. The outer loop chooses the row; the inner loop prints that many stars on the same line (end=""), and the empty print() moves to the next line.

```
for row in range(1, 5):
    for col in range(row):
        print("*", end="")
    print()
```

OUTPUT

```
*
**
***
****
```

Row 1: inner loop runs once → *. Row 2: twice → **. And so on up to row 4.

for loop vs while loop

for loop	while loop
Used when the number of iterations is known .	Used when the number of iterations is unknown (condition-based).
Automatically updates the loop variable.	Requires a manual update of the counter (risk of an infinite loop).
Cleaner and shorter for counting tasks.	Better for dynamic situations (like "keep playing until the user says Stop").
<code>for i in range(1, 4): print(i)</code>	<code>i = 1 / while i ≤ 3: / print(i) / i += 1</code>

REMEMBER IT

Ask yourself: "Do I know **how many times**?" Yes → `for`. "Do I only know **when to stop**?" → `while`.
Nested loops are like a clock: the minute hand (inner loop) goes all the way round for each step of the hour hand (outer loop).

COMMON MISTAKE

Indentation decides which loop a line belongs to. In the triangle program, if `print()` were indented under the inner loop, every star would go on its own line.

اردو میں سمجھیں

نیسٹڈ لوپ (Nested Loop) میں ایک لوپ دوسرے لوپ کے اندر ہوتا ہے، اور باہر والے لوپ کے ہر چکر میں اندر والا لوپ شروع سے آخر تک مکمل چلتا ہے۔ جب دہرانے کی تعداد معلوم ہو تو `for` لوپ، اور جب صرف رکنے کی شرط معلوم ہو تو `while` لوپ بہتر ہے۔

EXAM TIP

"Differentiate between for and while loops" (give three points and an example of each) and "How many times will the inner statement run?" (multiply the counts) are typical. For pattern programs, explain what the outer and inner loops each control.

CHECK YOURSELF

1. Predict the output:

```
count = 0
for i in range(3):
    for j in range(2):
        count += 1
print(count)
```

2. Which loop would you use to keep reading numbers until the user enters 0?

Answers: 1. 6 (3×2). 2. A `while` loop, because the number of inputs is not known in advance.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Predict the output:

3 marks. Explain Nested Loops and `for` vs `while` with two clear points and one example.

5 marks. "Differentiate between `for` and `while` loops" (give three points and an example of each) and "How many times will the inner statement run?" (multiply the counts) are typical. For pattern programs,...

8 marks. Nested Loops and `for` vs `while`: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. 6 (3×2) 3. The inner loop runs completely, from start to finish, for every single iteration of the outer loop.; If the outer loop runs 2 times and the inner loop runs 3 times, the inner body runs $2 \times 3 = 6$ times. 5. Use the recipe in the blue box. Model opening: A nested loop is a loop inside another loop. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Nested Loops and `for` vs `while`** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Practical Activity: Shopping Bill Calculator

ACADEMY SESSION

Session 18 of 20 · 45 minutes (first half) · paired with Libraries in Python.

10–45 min — this topic. Lock the definition and table for **Practical Activity: Shopping Bill Calculator**. Starter (0–10) is from last class. Second half is Libraries in Python.

On the board: This program combines all three control structures: sequence (steps in order), selection (checking "done", checking the price, checking for a discount) and repetition (a `while` loop that keeps adding...

Error clinic: total and count must be set to 0 before the loop.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Practical Activity: Shopping Bill Calculator**. Write: This program combines all three control structures: sequence (steps in order), selection (checking "done", checking the price, checking for a discount) and repetition (a while loop that keeps adding...

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It uses a flag — a Boolean variable (shopping) that controls when the loop stops. (2) `item.lower()` converts the text to lowercase so that "done", "Done" and "DONE" all work. — + example.

5 marks: 3-mark structure + table: Step / item / price / total / count + the worked example from this topic.

LEARN IT

This program combines all three control structures: **sequence** (steps in order), **selection** (checking "done", checking the price, checking for a discount) and **repetition** (a `while` loop that keeps adding items). It uses a **flag** — a Boolean variable (`shopping`) that controls when the loop stops.

`item.lower()` converts the text to lowercase so that "done", "Done" and "DONE" all work.

```
print("==== SHOPPING BILL ====")
total = 0.0
count = 0
shopping = True

# REPETITION: keep adding items
while shopping:
    item = input("Enter Item Name (or 'done' to stop): ")
    # SELECTION: check if user wants to stop
    if item.lower() == "done":
        shopping = False
    else:
        price = float(input(f"Enter Price of {item}: "))
        # SELECTION: validate price
        if price <= 0:
            print("Invalid price!")
        else:
            total += price
            count += 1

# Summary and discount
if total >= 5000:
    discount = total * 0.20 # 20% off
else:
    discount = 0

final = total - discount
print(f"Total Items: {count}")
print(f"Total Bill: {total}")
print(f"Final to Pay: {final}")
```

WORKED EXAMPLE

Sample run. The user buys Rice for 3000, types a wrong price -50 for Soap, buys Oil for 2500, then types DONE :

OUTPUT

```
===== SHOPPING BILL =====
Enter Item Name (or 'done' to stop): Rice
Enter Price of Rice: 3000
Enter Item Name (or 'done' to stop): Soap
Enter Price of Soap: -50
Invalid price!
Enter Item Name (or 'done' to stop): Oil
Enter Price of Oil: 2500
Enter Item Name (or 'done' to stop): DONE
Total Items: 2
Total Bill: 5500.0
Final to Pay: 4400.0
```

Step	item	price	total	count
1	Rice	3000.0	3000.0	1
2	Soap	-50.0 (invalid, not added)	3000.0	1
3	Oil	2500.0	5500.0	2
4	DONE → shopping = False	—	5500.0	2

After the loop: $5500.0 \geq 5000$, so discount = $5500.0 \times 0.20 = 1100.0$, and final = $5500.0 - 1100.0 = 4400.0$.

REMEMBER IT

Label the parts of any program with comments, as here: # REPETITION , # SELECTION . It helps you, your teacher and the examiner see the structure.

COMMON MISTAKE

total and count must be set to 0 **before** the loop. If you put total = 0.0 inside the loop, it resets on every item and the bill is wrong.

اردو میں سمجھیں

یہ شاپنگ بل پروگرام تینوں کنٹرول اسٹرکچرز کو ملا کر بنایا گیا ہے: while لوپ سے اشیاء بار بار شامل ہوتی ہیں، if-else سے غلط قیمت روکی جاتی ہے اور 5000 یا زیادہ کے بل پر 20 فیصد رعایت دی جاتی ہے۔

CHECK YOURSELF

1. What will "Final to Pay" be if the user buys one item for 4000 and then types done ?
2. What is the purpose of the variable shopping ?

Answers: 1. Final to Pay: 4000.0 (4000 is less than 5000, so no discount). 2. It is a flag that keeps the while loop running; setting it to False stops the loop.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What will "Final to Pay" be if the user buys one item for 4000 and then types done?

3 marks. Explain Practical Activity: Shopping Bill Calculator with two clear points and one example.

5 marks. Write a 5-mark answer on Practical Activity: Shopping Bill Calculator: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Final to Pay: 4000.0 (4000 is less than 5000, so no discount) 3. It uses a flag — a Boolean variable (shopping) that controls when the loop stops.; item.lower() converts the text to lowercase so that "done", "Done" and "DONE" all work. 5. Use the recipe in the blue box. Model opening: This program combines all three control structures: sequence (steps in order), selection (checking "done", checking the price, checking for a discount) and...

BATCH HOMEWORK

Write a 5-mark answer on **Practical Activity: Shopping Bill Calculator** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.6 Libraries in Python

ACADEMY SESSION

Session 18 of 20 · 45 minutes (second half) · paired with Practical Activity: Shopping Bill Calculator.

45–75 min — this topic. Board working for **Libraries in Python**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: A library (also called a module) is a collection of pre-written code that offers ready-made functions.

Error clinic: from math import * dumps every name into your program.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Libraries in Python**. Write: A library (also called a module) is a collection of pre-written code that offers ready-made functions.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Instead of writing a square-root algorithm from scratch, you import math and call math.sqrt(). (2) Libraries save time, reduce bugs and let you stand on other programmers' work. — + example.

5 marks: 3-mark structure + table: Method / Syntax / How you call the function + the worked example from this topic.

LEARN IT

A **library** (also called a **module**) is a collection of pre-written code that offers ready-made functions. Instead of writing a square-root algorithm from scratch, you import `math` and call `math.sqrt()`. Libraries save time, reduce bugs and let you stand on other programmers' work.

There are five common ways to import a library. Method 3 (import only what you need) is the best habit: it is clearer and uses less memory than `from math import *`.

Method	Syntax	How you call the function
1. Entire module	<code>import math</code>	<code>math.sqrt(25)</code>
2. Alias (nickname)	<code>import math as m</code>	<code>m.sqrt(16)</code>
3. Specific function	<code>from math import sqrt</code>	<code>sqrt(36)</code>
4. Several functions	<code>from math import sqrt, pi</code>	<code>sqrt(9), pi</code>
5. Everything (*)	<code>from math import *</code>	<code>sqrt(64)</code> — avoid this

WORKED EXAMPLE

Five imports, one result each:

```
import math
print(math.sqrt(25))
import math as m
print(m.sqrt(16))
from math import sqrt
print(sqrt(36))
from math import sqrt, pi
print(pi)
from math import *
print(sqrt(64))
```

OUTPUT

```
5.0
4.0
6.0
3.141592653589793
8.0
```

COMMON MISTAKE

`from math import *` dumps every name into your program. If you later write a function called `sqrt`, you silently overwrite the library one. Prefer methods 1–4.

اردو میں سمجھیں

لائبریری پہلے سے لکھا ہوا کوڈ ہے جسے `import` سے پروگرام میں لایا جاتا ہے۔ سب سے اچھا طریقہ یہ ہے کہ صرف وہ فنکشن درآمد کریں جس کی ضرورت ہو، ستارہ `*` سے سب کچھ نہ کھینچیں۔

CHECK YOURSELF

1. Write the line that lets you call `ceil` without writing `math.` in front.
2. Why is an alias such as `import pandas as pd` useful?

Answers: 1. `from math import ceil`. 2. The library name is long; a short nickname keeps later lines short and is a community convention.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Write the line that lets you call `ceil` without writing `math.` in front.

3 marks. Explain Libraries in Python with two clear points and one example.

5 marks. Write a 5-mark answer on Libraries in Python: definition, two points, a labelled diagram or table, and one example.

Answers: 1. `from math import ceil` 3. Instead of writing a square-root algorithm from scratch, you import `math` and call `math.sqrt()`; Libraries save time, reduce bugs and let you stand on other programmers' work. 5. Use the recipe in the blue box. Model opening: A library (also called a module) is a collection of pre-written code that offers ready-made functions.

BATCH HOMEWORK

Write a 5-mark answer on **Libraries in Python** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.6.1 Built-in Libraries

ACADEMY SESSION

Session 19 of 20 · 45 minutes (first half) · paired with Third-Party Libraries.

10–45 min — this topic. Lock the definition and table for **Built-in Libraries**. Starter (0–10) is from last class. Second half is Third-Party Libraries.

On the board: Built-in libraries come pre-installed with Python.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Built-in Libraries**. Write: Built-in libraries come pre-installed with Python.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) You only import them; you do not run pip. (2) Three that every Class XI student must know are math, random and datetime. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Built-in libraries come pre-installed with Python. You only import them; you do not run pip. Three that every Class XI student must know are math, random and datetime.

math

```
import math
print(math.pi)
print(math.ceil(4.3))
print(math.floor(4.9))
print(math.pow(2, 4))
print(math.sqrt(81))
```

OUTPUT

```
3.141592653589793
5
4
16.0
9.0
```

random and datetime

```
import random
print(random.randint(1, 1))
print(0.0 ≤ random.random() < 1.0)

import datetime
now = datetime.datetime(2026, 9, 27, 11, 59, 40)
print(now.strftime("%d-%m-%Y"))
```

OUTPUT

```
1
True
27-09-2026
```

`randint(a, b)` includes both ends. `random()` is a float in `[0.0, 1.0)`. `strftime` formats a date; `%d-%m-%Y` is day-month-year.

REMEMBER IT

`ceil` always rounds **up** (ceiling); `floor` always rounds **down**. `round()` (built-in, not in `math`) goes to the nearest integer and is a different function.

اردو میں سمجھیں

`math` حساب کے لیے، `random` بے ترتیب عدد کے لیے اور `datetime` تاریخ وقت کے لیے بنی ہوئی لائبریریاں ہیں۔ انہیں انسٹال نہیں کرنا پڑتا، صرف `import` کافی ہے۔

CHECK YOURSELF

1. What does `math.ceil(4.0)` return?
2. Write a line that prints a random integer from 1 to 6 (a dice).

Answers: 1. 4 (already an integer). 2. `print(random.randint(1, 6))` after `import random`.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does `math.ceil(4.0)` return?

3 marks. Explain Built-in Libraries with two clear points and one example.

5 marks. Write a 5-mark answer on Built-in Libraries: definition, two points, a labelled diagram or table, and one example.

Answers: 1. 4 (already an integer) 3. You only import them; you do not run `pip`.; Three that every Class XI student must know are `math`, `random` and `datetime`. 5. Use the recipe in the blue box. Model opening: Built-in libraries come pre-installed with Python.

BATCH HOMEWORK

Write a 5-mark answer on **Built-in Libraries** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.6.2 Third-Party Libraries

ACADEMY SESSION

Session 19 of 20 · 45 minutes (second half) · paired with Built-in Libraries.

45–75 min — this topic. Board working for **Third-Party Libraries**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Third-party libraries are written by the community.

Error clinic: `pip` is a terminal command, not a Python statement.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Third-Party Libraries**. Write: Third-party libraries are written by the community.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Third-party libraries are written by the community. (2) They are not bundled with Python, so you install them from a terminal with `pip install library_name` and then import them as usual. — + example.

5 marks: 3-mark structure + table: Library / Primary use + the worked example from this topic.

LEARN IT

Third-party libraries are written by the community. They are **not** bundled with Python, so you install them from a terminal with `pip install library_name` and then import them as usual.

Library	Primary use
NumPy	Heavy numerical computing and large arrays
Pandas	Data analysis; table-like data (CSV / Excel)
Matplotlib	Data visualisation — graphs and charts
TensorFlow / PyTorch	Artificial intelligence and machine learning

WORKED EXAMPLE

Installing and importing Pandas (you will use this in Class XII):

```
pip install pandas
import pandas as pd
```

COMMON MISTAKE

`pip` is a **terminal** command, not a Python statement. Do not type `pip install pandas` inside a `.py` file. In VS Code, open the Terminal panel.

اردو میں سمجھیں

تھرڈ پارٹی لائبریریاں پائتھن کے ساتھ نہیں آتیں، انہیں `pip install` سے انسٹال کیا جاتا ہے۔ نمپائی، پینڈا، میٹپلاٹ لیب اور ٹینسر فلو اسی قسم کی ہیں۔

CHECK YOURSELF

1. Which library would you choose to draw a bar chart of class marks?

2. Is `math` a third-party library?

Answers: 1. Matplotlib. 2. No — `math` is built-in.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which library would you choose to draw a bar chart of class marks?

3 marks. Explain Third-Party Libraries with two clear points and one example.

5 marks. Write a 5-mark answer on Third-Party Libraries: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Matplotlib 3. Third-party libraries are written by the community.; They are not bundled with Python, so you install them from a terminal with `pip install library_name` and then import them as usual. 5. Use the recipe in the blue box. Model opening: Third-party libraries are written by the community.

BATCH HOMEWORK

Write a 5-mark answer on **Third-Party Libraries** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.7 Debugging Code in Python

ACADEMY SESSION

Session 20 of 20 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Debugging is the process of identifying, tracing and fixing bugs so a program works correctly.

Error clinic: A logical error is the most dangerous because Python reports nothing.

Exam wording to train: Examiners love "identify the error type" questions.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Debugging Code in Python**. Write: Debugging is the process of identifying, tracing and fixing bugs so a program works correctly.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Every program you write will have bugs. (2) The skill is not "never make a mistake"; it is "find the mistake quickly". — + example.

5 marks: 3-mark structure + table: Type / When it appears / What you notice / Example + the worked example from this topic.

LEARN IT

Debugging is the process of identifying, tracing and fixing bugs so a program works correctly. Every program you write will have bugs. The skill is not "never make a mistake"; it is "find the mistake quickly".

Python errors fall into three families:

Type	When it appears	What you notice	Example
Syntax error	Before the program even starts	Python refuses to run	<code>print("Hello" — missing)</code>
Runtime error (exception)	While the program is running	It crashes with a traceback	<code>x = 10 / 0 → ZeroDivisionError</code>
Logical error	Program finishes "successfully"	The output is wrong	<code>area = length + width</code> instead of <code>*</code>

WORKED EXAMPLE

Reading a traceback. When Python crashes it prints a roadmap: the file, the line number, and the error type.

```
x = int("abc")
```

OUTPUT

```
Traceback (most recent call last):
  File "debug_program.py", line 1, in <module>
    x = int("abc")
ValueError: invalid literal for int() with base 10: 'abc'
```

Diagnosis: on **line 1** we tried to convert the letters "abc" into an integer, which raised a `ValueError`.

EXAM TIP

Examiners love "identify the error type" questions. Ask: (1) Does it refuse to start? → syntax. (2) Does it crash mid-run? → runtime. (3) Does it run but give a wrong answer? → logical. Write the name of the error **and** how to fix it.

REMEMBER IT

Fix syntax errors first (the program cannot start). Then run it. Then check the output against a hand-worked example to catch logical errors.

COMMON MISTAKE

A logical error is the most dangerous because Python reports nothing. Always test with values whose answer you already know (for a rectangle 3 by 4, area must be 12, not 7).

اردو میں سمجھیں

ڈیبگنگ یعنی غلطی ڈھونڈ کر ٹھیک کرنا۔ نحوی غلطی پر پروگرام چلتا ہی نہیں، رن ٹائم پر چلتے چلتے رک جاتا ہے، منطقی غلطی پر چل تو جاتا ہے مگر جواب غلط دیتا ہے — یہ سب سے خطرناک ہے۔

CHECK YOURSELF

1. `print("Hi"` — which error type?
2. A program that should add two numbers multiplies them instead. Which error type?
3. `int("12.5")` raises which named exception?

Answers: 1. Syntax error. 2. Logical error. 3. `ValueError` (runtime).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. `print("Hi"` — which error type?

3 marks. Explain Debugging Code in Python with two clear points and one example.

5 marks. Examiners love "identify the error type" questions. Ask: (1) Does it refuse to start? → syntax. (2) Does it crash mid-run? → runtime. (3) Does it run but give a wrong answer? → logical. Write the...

Answers: 1. Syntax error 3. Every program you write will have bugs.; The skill is not "never make a mistake"; it is "find the mistake quickly". 5. Use the recipe in the blue box. Model opening: Debugging is the process of identifying, tracing and fixing bugs so a program works correctly.

BATCH HOMEWORK

Write a 5-mark answer on **Debugging Code in Python** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Chapter 3 Review

Chapter summary

- A program is a set of instructions; programming languages are low-level (close to hardware) or high-level (close to English). Python is a high-level, interpreted, readable language.
- Python is widely used in web development, data science, AI and automation — skills that grow a career in Pakistan and abroad.
- An IDE (such as VS Code plus the Python extension) combines an editor, a terminal, a debugger and syntax highlighting.
- Variables store values; Python types are dynamic. Core types: `int`, `float`, `str`, `bool`, `list`, `dict`.
- `print()` displays output; `input()` always returns a **string** — convert with `int()` or `float()` before arithmetic.
- Operators: arithmetic (`+` `-` `*` `/` `//` `%` `**`), assignment (`=` `+=` `...`), relational, logical (`and` `or` `not`), membership (`in`), bitwise (`&` `|` `^` `~` `<<` `>>`).
- Control structures: sequence (top to bottom), selection (`if` / `if-else` / `if-elif-else` / nested), repetition (`for` / `while`).
- `range(stop)` goes 0 ... stop-1; `range(start, stop, step)` jumps by step. `break` leaves a loop; `continue` skips one iteration.
- Use `for` when the count is known; use `while` when you wait for a condition (and always update that condition).
- Libraries extend Python. Built-in: `math`, `random`, `datetime`. Third-party (need `pip`): NumPy, Pandas, Matplotlib, TensorFlow.
- Errors: syntax (grammar, will not run), runtime (crash, traceback), logical (runs, wrong answer).

Key terms

Term	Meaning	اردو
Program	A set of instructions a computer can follow.	پروگرام
High-level language	A language close to English (Python, Java, C++).	اعلیٰ سطحی زبان
Interpreter	Runs a program line by line without a separate compile step.	انٹریپرٹر
IDE	Software that combines editor, terminal and debugger.	انٹیگریٹڈ ڈویلپمنٹ انوائرنمنٹ
Variable	A named box that holds a value.	متغیر
Data type	The kind of value: int, float, str, bool, list, dict.	ڈیٹا کی قسم
Operator	A symbol that performs an operation on operands.	عامل
Operand	A value an operator works on.	معمول
Sequence	Instructions executed from top to bottom.	تسلسل
Selection	Choosing a path with <code>if / else</code> .	انتخاب
Repetition / loop	Repeating a block with <code>for</code> or <code>while</code> .	تکرار / لوپ
Nested	A structure placed inside another of the same kind.	تو در تو
Library / module	A collection of ready-made functions.	لائبریری / ماڈیول
pip	The tool that installs third-party Python libraries.	پپ
Syntax error	A grammar mistake; the program will not start.	نحوی غلطی
Runtime error	A crash while the program is running (exception).	رن ٹائم غلطی
Logical error	The program runs but the result is wrong.	منطقی غلطی
Traceback	Python's report of where a crash happened.	ٹریس بیک
Flag	A Boolean variable that controls a loop or decision.	فلیگ
Integer division	<code>//</code> division that drops the fraction.	صحیح تقسیم

Practice: multiple choice

1. Python is best described as a:
 - a. low-level compiled language
 - b. high-level interpreted language
 - c. machine language
 - d. hardware description language
2. `input("Age: ")` always returns a:
 - a. int
 - b. float
 - c. str
 - d. bool
3. The value of `17 // 5` is:
 - a. 3.4
 - b. 2
 - c. 3
 - d. 3.0
4. The value of `17 % 5` is:
 - a. 2
 - b. 3
 - c. 3.4
 - d. 0
5. `2 ** 3` equals:
 - a. 6
 - b. 8
 - c. 9
 - d. 5
6. Which operator is bitwise AND?
 - a. `and`
 - b. `&&`
 - c. `&`
 - d. `^`
7. `list(range(2, 5))` is:
 - a. `[2, 3, 4, 5]`
 - b. `[2, 3, 4]`
 - c. `[2, 5]`
 - d. `[0, 1, 2, 3, 4]`
8. A `while` loop is preferred when:
 - a. you know the exact number of repeats
 - b. you must wait for a condition
 - c. you never need a counter
 - d. the body must run exactly once
9. `break` inside a loop:
 - a. skips one iteration
 - b. restarts the loop
 - c. leaves the loop immediately
 - d. pauses for input
10. `from math import sqrt` lets you write:
 - a. `math.sqrt(9)` only
 - b. `sqrt(9)`
 - c. `import.sqrt(9)`
 - d. `m.sqrt(9)`
11. Which library is built-in?
 - a. Pandas
 - b. NumPy
 - c. random
 - d. Matplotlib
12. `print("Hi")` is a:
 - a. syntax error
 - b. runtime error
 - c. logical error
 - d. warning only
13. `10 / 0` is a:
 - a. syntax error
 - b. runtime error
 - c. logical error
 - d. style error
14. `area = length + width` when you meant to multiply is a:
 - a. syntax error
 - b. runtime error
 - c. logical error
 - d. import error
15. `math.ceil(4.3)` is:
 - a. 4
 - b. 4.0
 - c. 5
 - d. 4.3

Practice: short questions

1. Differentiate between a compiler and an interpreter.
2. Why must the result of `input()` often be converted with `int()`?
3. State the difference between `/` and `//` with one example each.
4. Write the truth table of the logical operator `and` for two Boolean values.
5. Explain `if-elif-else`. Why is the order of conditions important?
6. Differentiate between a `for` loop and a `while` loop.
7. What do `break` and `continue` do?
8. Name two built-in and two third-party Python libraries and their uses.
9. Differentiate between syntax, runtime and logical errors with one example each.
10. What three pieces of information does a Python traceback give you?

Practice: long / problem questions

1. Write a complete Python program that reads a student's marks (0–100) and prints the grade: 80+ A-1, 70–79 A, 60–69 B, otherwise Fail. Include input conversion and a sample run.
2. Write a program that prints all even numbers from 0 to 10 using `range`, then rewrite it with a `while` loop. Dry-run both.
3. Trace this nested loop and write every line of output:

```
for o in range(1, 3):
    for i in range(1, 4):
        print(o, i)
```
4. A shop gives 20% discount if the bill is 5000 or more. Write a program that keeps reading item prices until the user types 0, prints the total, the discount and the amount to pay. Show a sample run with prices 3000, 2500, 0.
5. Classify each bug and write the corrected line:
 - (a) `print("Total is", total`
 - (b) `avg = total / 0` when there are no items
 - (c) `discount = total + 0.20` when 20% off was intended.
6. Explain how you would use `math`, `random` and `datetime` in a small "lucky student of the day" program for a class of 40. Write the code.

Answer key

Multiple choice

1. b
2. c
3. c
4. a
5. b
6. c
7. b
8. b
9. c
10. b
11. c
12. a
13. b
14. c
15. c

Short questions — model answers

1. A compiler translates the whole program into machine code before it runs (C, C++). An interpreter translates and runs line by line (Python). Compiled programs often run faster; interpreted ones are easier to test.
2. `input()` always returns a string. Adding strings concatenates them (`"2"+"3"` is `"23"`), so numeric work needs `int()` or `float()`.
3. `/` is true division: `17/5` is `3.4`. `//` is integer (floor) division: `17//5` is `3`.
4. $F \text{ and } F \rightarrow F$; $F \text{ and } T \rightarrow F$; $T \text{ and } F \rightarrow F$; $T \text{ and } T \rightarrow T$. Output is True only when both operands are True.
5. Python tests conditions from the top. The first True block runs and the rest are skipped. If you put `marks >= 60` above `marks >= 80`, an 85 would match the weaker condition first and get the wrong grade.
6. `for`: known count, counter updates automatically, good with `range`. `while`: unknown count, you must update the condition yourself or you get an infinite loop.
7. `break` leaves the loop immediately. `continue` skips the rest of this iteration and starts the next one.
8. Built-in: `math` (roots, ceil/floor), `random` (random integers). Third-party: Pandas (tables), Matplotlib (charts). (NumPy and TensorFlow also accepted.)
9. Syntax: missing bracket, will not run. Runtime: `10/0`, crashes. Logical: `area = l + w`, runs but answer is wrong.
10. The error type (e.g. `ValueError`), the file name, and the line number that caused the crash.

Long questions — model answers

```
1. marks = int(input("Enter marks: "))
if marks ≥ 80:
    print("A-1 Grade")
elif marks ≥ 70:
    print("A Grade")
elif marks ≥ 60:
    print("B Grade")
else:
    print("Fail or below B")
```

Sample: input 85 → A-1 Grade; input 72 → A Grade; input 40 → Fail or below B.

```
2. for i in range(0, 11, 2):
    print(i)
n = 0
while n ≤ 10:
    print(n)
    n += 2
```

Both print 0, 2, 4, 6, 8, 10.

3. Output (six lines): 1 1 / 1 2 / 1 3 / 2 1 / 2 2 / 2 3. The inner loop runs fully for each value of the outer loop.

```
4. total = 0.0
while True:
    p = float(input("Price (0 to stop): "))
    if p == 0:
        break
    if p > 0:
        total += p
    discount = total * 0.20 if total ≥ 5000 else 0
    print("Total", total)
    print("Discount", discount)
    print("Pay", total - discount)
```

Sample: 3000 + 2500 = 5500; discount 1100; pay 4400.

5. (a) Syntax — add `)`: `print("Total is", total)`. (b) Runtime `ZeroDivisionError` — only divide when the count of items is not 0. (c) Logical — 20% of total is `total * 0.20`, not `total + 0.20`.

```
6. import random, datetime, math
n = random.randint(1, 40)
today = datetime.datetime.now().strftime("%d-%m-%Y")
print("Lucky roll", n, "on", today)
print("Root of roll", math.sqrt(n))
```

`random` picks the student number, `datetime` stamps the date, `math` shows a sample extra calculation.

Self-assessment: I can...

- | | |
|--|--|
| ☐ classify a language as high-level or low-level and explain why Python is popular. | ☐ declare variables and identify int, float, str, bool, list and dict values. |
| ☐ read input, convert types, and print formatted output. | ☐ evaluate arithmetic, relational, logical and bitwise expressions by hand. |
| ☐ write if, if-else, if-elif-else and nested selections. | ☐ write for and while loops, including range, break and continue. |
| ☐ import built-in libraries (math, random, datetime) in more than one style. | ☐ name pip and at least two third-party libraries. |
| ☐ classify a bug as syntax, runtime or logical and read a traceback. | ☐ combine sequence, selection and repetition in a small complete program. |

CHAPTER 4

Data and Analysis

This chapter teaches you how raw facts become organised information in a database, how tables are linked with keys, how to draw an ER diagram, and how to build tables, forms, queries and charts in Microsoft Access. Banks, NADRA, college libraries and fee offices all run on these ideas.

اس باب میں آپ سیکھیں گے کہ خام حقائق کو ڈیٹا بیس میں کیسے منظم کیا جاتا ہے، ٹیبلز کو کیسے جوڑا جاتا ہے، ای آر خاکہ کیسے بنتا ہے، اور مائیکروسافٹ ایکسیس میں ٹیبل، فارم، کوئری اور چارٹ کیسے بنائے جاتے ہیں۔

What you will learn

- Distinguish data, information and a database, and explain what a DBMS does.
- Choose candidate, primary, alternate and foreign keys and state integrity rules.
- Explain referential integrity, Cascade Update and Cascade Delete with before/after tables.
- Develop the college-library case study from requirements to the final ER schema.
- Create tables in Access (Datasheet and Design view) and pick data types.
- Identify tables, records and fields in a given example.
- Draw ER diagrams (entities, attributes, relationships) and give cardinality 1:1, 1:M, M:N.
- Write a relational schema and resolve an M:N relationship with a junction table.
- State the job of tables, forms, queries and reports.
- Build a form with the Form Wizard and a SELECT query with criteria, AND/OR, totals and charts.

ACADEMY CALENDAR

Academy calendar: 15 topics · 4 Golden · **11 classes of 90 minutes** + one 40-minute weekly test after this chapter.

Class	Topics	Kind	Board focus
Class 01	Data, Information and Database + Database Management System (DBMS)	Paired · 90 min	Data are unprocessed facts, figures or observations.
Class 02	Database Components (Tables, Records, Fields)	Single · 90 min	The basic structure is a table (also called a relation): rows and columns, like a...
Class 03	Keys and Integrity Constraints	★ Golden · 90 min	A key is a field (or a set of fields) that uniquely identifies records and links tables.
Class 04	Relational Database Management System (RDBMS)	Single · 90 min	An RDBMS stores data in several tables and uses primary and foreign keys to keep...

Class	Topics	Kind	Board focus
Class 05	Entity Relationship Model (ER-Model)	★ Golden · 90 min	The ER model is the architect's blueprint: you draw what will be stored and how it...
Class 06	Referential Integrity	★ Golden · 90 min	Referential integrity means every foreign-key value in a child table must match an...
Class 07	Relational Schema Development + Case Study — Library Management System	Paired · 90 min	A relational schema is the formal written design of the database: table names, fields,...
Class 08	Database Objects (Tables, Forms, Queries, Reports) + Creation of Tables in Microsoft Access	Paired · 90 min	Four objects you will meet in Access.
Class 09	Designing Forms for Data Manipulation	Single · 90 min	A form is the screen people actually type into.
Class 10	Creating Queries in MS Access	★ Golden · 90 min	A query retrieves, filters and analyses data without changing the original tables.
Class 11	Data Summarization and Statistical Analysis + Data Visualization in MS Access (Charts)	Paired · 90 min	Grouping combines rows that share a value (all CS students together) and then an...

Weekly test: 15 MCQ from this chapter + two 5-mark Golden questions. Mark to the recipes. Re-teach any Golden below 60% in the next starter.

گولڈن موضوع پوری کلاس لیتا ہے۔ ہفتہ وار ٹیسٹ کے بعد کمزور گولڈن دوبارہ پڑھائیں۔

4.1.1 Data, Information and Database

ACADEMY SESSION

Session 1 of 11 · 45 minutes (first half) · paired with Database Management System (DBMS).

10–45 min — this topic. Lock the definition and table for **Data, Information and Database**. Starter (0–10) is from last class. Second half is Database Management System (DBMS).

On the board: Data are unprocessed facts, figures or observations.

Error clinic: Do not call a jumble of WhatsApp numbers a database.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Data, Information and Database**. Write: Data are unprocessed facts, figures or observations.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) They can be quantitative (numbers: 80, 75, 90) or qualitative (descriptions: the colours of cars in a parking lot). (2) Data on its own is not very useful — a list of marks does not yet tell you whether the class is strong. — + example.

5 marks: 3-mark structure + table: Aspect / Data / Information + the worked example from this topic.

LEARN IT

Data are unprocessed facts, figures or observations. They can be **quantitative** (numbers: 80, 75, 90) or **qualitative** (descriptions: the colours of cars in a parking lot). Data on its own is not very useful — a list of marks does not yet tell you whether the class is strong.

When you organise, process and interpret data, it becomes **information**. Information has meaning and supports a decision. Example: "The class average is 80%, so we can move to the next chapter."

A **database** is an organised collection of **related** data, stored in a structured way so it can be accessed, managed and updated easily. Paper registers and loose files make searching painful; a database is built for search, update and sharing.



Aspect	Data	Information
Definition	Raw facts and figures	Processed, meaningful data
Example	85, 90, 75	Average marks = 83.3%
Usefulness	Little, on its own	Useful for decisions

WORKED EXAMPLE

Five CS XI marks: 80, 75, 90, 70, 85. Sum = 400. Average = $400 \div 5 = 80\%$. The numbers are data; "the class average is 80%" is information; a **Student** table holding every student's marks is a database.

REMEMBER IT

Exam line: *Data is raw; information is processed data used for decision-making.* Always add one pair of examples.

COMMON MISTAKE

Do not call a jumble of WhatsApp numbers a database. Related + structured + easy to update is what makes it a database.

اردو میں سمجھیں

ڈیٹا خام حقائق ہیں، معلومات وہی حقائق ہیں جب انہیں ترتیب دے کر معنی دے دیا جائے۔ ڈیٹا بیس متعلقہ ڈیٹا کا منظم ذخیرہ ہے جسے آسانی سے تلاش اور تبدیل کیا جا سکتا ہے۔

CHECK YOURSELF

1. Is "Nadia, Class 11, 72 marks" data or information?
2. Why is a stack of unmarked answer sheets not a database?

Answers: 1. Data (raw facts about one student). 2. It is not organised in a structured, searchable, updatable collection of related records.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Is "Nadia, Class 11, 72 marks" data or information?

3 marks. Explain Data, Information and Database with two clear points and one example.

5 marks. Write a 5-mark answer on Data, Information and Database: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Data (raw facts about one student) 3. They can be quantitative (numbers: 80, 75, 90) or qualitative (descriptions: the colours of cars in a parking lot).; Data on its own is not very useful — a list of marks does not yet tell you whether the class is strong. 5. Use the recipe in the blue box. Model opening: Data are unprocessed facts, figures or observations.

BATCH HOMEWORK

Write a 5-mark answer on **Data, Information and Database** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.1.2 Database Management System (DBMS)

ACADEMY SESSION

Session 1 of 11 · 45 minutes (second half) · paired with Data, Information and Database.

45–75 min — this topic. Board working for **Database Management System (DBMS)**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: A DBMS is software that lets you create, manage and interact with databases.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Database Management System (DBMS)**. Write: A DBMS is software that lets you create, manage and interact with databases.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Consistency. Change a phone number once; every screen that uses it shows the new number. (2) Security. Only authorised users see sensitive fields (an admin sees marks; office staff see names). — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

A **DBMS** is software that lets you create, manage and interact with databases. It sits between the user and the stored files. You never edit raw data files by hand — you talk to the DBMS (Access, MySQL, Oracle, SQLite) and it handles storage, security and consistency.

Advantages you must be able to list:

- **Less redundancy.** The department name is stored once, not in every student row.
- **Consistency.** Change a phone number once; every screen that uses it shows the new number.
- **Security.** Only authorised users see sensitive fields (an admin sees marks; office staff see names).
- **Integrity.** Rules stop duplicate roll numbers and empty primary keys.

WORKED EXAMPLE

In a paper register, Ali's address is written on the admission page, the fee page and the sports page. If he moves house, two of the three pages stay wrong. In a DBMS, Address lives in one **Student** table. Every form and report reads that single field.

اردو میں سمجھیں

ڈی بی ایم ایس وہ سافٹ ویئر ہے جو صارف اور ڈیٹا بیس کے درمیان پل کا کام کرتا ہے۔ اس سے تکرار کم ہوتی ہے، ڈیٹا ایک جیسا رہتا ہے، صرف مجاز افراد دیکھ سکتے ہیں، اور غلط اندراج رک جاتی ہے۔

CHECK YOURSELF

1. Name two DBMS programs.
2. Which advantage stops two students sharing the same roll number?

Answers: 1. MS Access, MySQL (Oracle, SQLite also). 2. Integrity (unique / primary-key constraint).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name two DBMS programs.

3 marks. Explain Database Management System (DBMS) with two clear points and one example.

5 marks. Write a 5-mark answer on Database Management System (DBMS): definition, two points, a labelled diagram or table, and one example.

Answers: 1. MS Access, MySQL (Oracle, SQLite also) 3. Consistency. Change a phone number once; every screen that uses it shows the new number.; Security. Only authorised users see sensitive fields (an admin sees marks; office staff see names). 5. Use the recipe in the blue box. Model opening: A DBMS is software that lets you create, manage and interact with databases.

BATCH HOMEWORK

Write a 5-mark answer on **Database Management System (DBMS)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.2 Database Components (Tables, Records, Fields)

ACADEMY SESSION

Session 2 of 11 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The basic structure is a table (also called a relation): rows and columns, like a spreadsheet, holding facts about one kind of thing (Students, Teachers, Books).

Error clinic: Do not mix two entities in one table (students and library books together).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Database Components (Tables, Records, Fields)**. Write: The basic structure is a table (also called a relation): rows and columns, like a spreadsheet, holding facts about one kind of thing (Students, Teachers, Books).

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) A record (row, tuple) is one complete instance — everything about Ali. (2) A field (column, attribute) is one kind of fact — the whole Name column, or the whole Grade column. — + example.

5 marks: 3-mark structure + table: Roll No / Name / Course / Grade + the worked example from this topic.

LEARN IT

The basic structure is a **table** (also called a relation): rows and columns, like a spreadsheet, holding facts about one kind of thing (Students, Teachers, Books).

A **record** (row, tuple) is one complete instance — everything about Ali. A **field** (column, attribute) is one kind of fact — the whole Name column, or the whole Grade column.

Roll No	Name	Course	Grade
101	Ali	CS	A
102	Sara	IT	B+
103	Ahmed	CS	A

The row 101 | Ali | CS | A is one **record**. The Name column is one **field**.

REMEMBER IT

Memory: **row = record = one person. column = field = one question on the admission form.**

COMMON MISTAKE

Do not mix two entities in one table (students and library books together). Each entity gets its own table; keys will link them later.

اردو میں سمجھیں

ٹیبل قطاروں اور کالموں میں ڈیٹا رکھتا ہے۔ ایک قطار ایک ریکارڈ (مثلاً علی کی پوری معلومات) ہے، ایک کالم ایک فیلڈ (مثلاً صرف نام) ہے۔

CHECK YOURSELF

1. How many records and how many fields are in the table above?
2. Is "CS" a record or a field value?

Answers: 1. 3 records, 4 fields. 2. A value stored in the Course field.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. How many records and how many fields are in the table above?

3 marks. Explain Database Components (Tables, Records, Fields) with two clear points and one example.

5 marks. Write a 5-mark answer on Database Components (Tables, Records, Fields): definition, two points, a labelled diagram or table, and one example.

Answers: 1. 3 records, 4 fields 3. A record (row, tuple) is one complete instance — everything about Ali.; A field (column, attribute) is one kind of fact — the whole Name column, or the whole Grade column. 5. Use the recipe in the blue box. Model opening: The basic structure is a table (also called a relation): rows and columns, like a spreadsheet, holding facts about one kind of thing (Students, Teachers,...

BATCH HOMEWORK

Write a 5-mark answer on **Database Components (Tables, Records, Fields)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.3.1 Keys and Integrity Constraints ★ Golden

ACADEMY SESSION

Session 3 of 11 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A key is a field (or a set of fields) that uniquely identifies records and links tables.

Error clinic: A phone number is a bad PK: people change numbers, two siblings may share one, and some students have none (NULL).

Exam wording to train: Board questions: “Differentiate primary and foreign key” (table of 4 points) and “Why can a PK not be NULL?” Because a NULL would mean “this row has no...”

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Keys and Integrity Constraints**. Write: A key is a field (or a set of fields) that uniquely identifies records and links tables.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Integrity constraints are the rules that keep those keys honest. (2) Any field (or combination) that could uniquely identify a row. — + example.

5 marks: 3-mark structure + table: Table / Field / Role + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **key** is a field (or a set of fields) that uniquely identifies records and links tables. Integrity constraints are the rules that keep those keys honest.

Candidate key. Any field (or combination) that *could* uniquely identify a row. A table may have several. In an Employee table: EmpID, EmpLicense# and EmpPassport are all candidate keys.

Primary key (PK). The one candidate you actually choose. Rules: unique, never NULL, only one PK per table (it may be a **composite** of two columns). Example: EmpID.

Alternate key. The leftover candidate keys. After EmpID is chosen, EmpLicense# and EmpPassport become alternate keys — still unique, just not “the” identifier.

Foreign key (FK). A field in this table that refers to the PK of another table. It *may* contain duplicates (many employees in one department) and, in some designs, NULL.

WORKED EXAMPLE

Classroom analogy. Roll Number, B-Form number and phone number can all identify a student (candidate keys). The school picks Roll Number as the primary key. B-Form and phone become alternate keys. In a **Result** table, RollNo is a foreign key pointing back to Student.

Table	Field	Role
Student	RollNo	Primary key
Student	BFormNo	Alternate key
Result	RollNo	Foreign key → Student.RollNo
Result	ExamID + RollNo	Could be a composite primary key

EXAM TIP

Board questions: "Differentiate primary and foreign key" (table of 4 points) and "Why can a PK not be NULL?" Because a NULL would mean "this row has no identity", so the DBMS could not tell rows apart.

COMMON MISTAKE

A phone number is a bad PK: people change numbers, two siblings may share one, and some students have none (NULL). Roll numbers are issued by the school and stay unique.

اردو میں سمجھیں

کینڈیڈٹ کی وہ فیلڈ ہے جو ریکارڈ کی شناخت کر سکے۔ پرائمری کی منتخب شدہ شناخت ہے — منفرد اور خالی نہیں۔ جو بچ جائیں وہ آئرنیٹ کیز ہیں۔ فارن کی دوسرے ٹیبل کی پرائمری کی طرف اشارہ کرتی ہے اور ٹیبلز کو جوڑتی ہے۔

CHECK YOURSELF

1. Can a table have two primary keys?
2. Can a foreign key have duplicate values?

Answers: 1. No — only one PK (it may be composite). 2. Yes — many child rows may point to the same parent.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Can a table have two primary keys?

3 marks. Explain Keys and Integrity Constraints with two clear points and one example.

5 marks. Board questions: "Differentiate primary and foreign key" (table of 4 points) and "Why can a PK not be NULL?" Because a NULL would mean "this row has no identity", so the DBMS could not tell rows...

8 marks. Keys and Integrity Constraints: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. No — only one PK (it may be composite) 3. Integrity constraints are the rules that keep those keys honest.; Any field (or combination) that could uniquely identify a row. 5. Use the recipe in the blue box. Model opening: A key is a field (or a set of fields) that uniquely identifies records and links tables. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Keys and Integrity Constraints** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.3 Relational Database Management System (RDBMS)

ACADEMY SESSION

Session 4 of 11 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: An RDBMS stores data in several tables and uses primary and foreign keys to keep relationships.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Relational Database Management System (RDBMS)**. Write: An RDBMS stores data in several tables and uses primary and foreign keys to keep relationships.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Supports many users at once, with permissions. (2) Is queried with SQL (Structured Query Language) — a standard language of SELECT, INSERT, UPDATE, DELETE. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

An **RDBMS** stores data in several tables and uses primary and foreign keys to keep relationships. Banks, universities and NADRA use RDBMS software. Extra strengths on top of a plain DBMS:

- Reduces redundancy by splitting data into related tables.
- Supports many users at once, with permissions.
- Is queried with **SQL** (Structured Query Language) — a standard language of SELECT, INSERT, UPDATE, DELETE.

WORKED EXAMPLE

Instead of one giant spreadsheet of students-and-departments, an RDBMS has Department(DeptID, DeptName) and Student(RollNo, Name, DeptID FK). CS is stored once. SQL: SELECT Name FROM Student WHERE DeptID = 1;

اردو میں سمجھیں

آر ڈی بی ایم ایس کئی ٹیبلز میں ڈیٹا رکھتا ہے اور کیڑ سے ان کے تعلقات برقرار رکھتا ہے۔ ایس کیو ایل سے سوال پوچھے جاتے ہیں۔ اس سے تکرار کم اور کئی صارفین محفوظ طریقے سے کام کر سکتے ہیں۔

CHECK YOURSELF

1. What language do you use to query an RDBMS?

2. Why split Department out of the Student table?

Answers: 1. SQL. 2. To store the department name once (less redundancy) and update it in one place.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What language do you use to query an RDBMS?

3 marks. Explain Relational Database Management System (RDBMS) with two clear points and one example.

5 marks. Write a 5-mark answer on Relational Database Management System (RDBMS): definition, two points, a labelled diagram or table, and one example.

Answers: 1. SQL 3. Supports many users at once, with permissions.; Is queried with SQL (Structured Query Language) — a standard language of SELECT, INSERT, UPDATE, DELETE. 5. Use the recipe in the blue box. Model opening: An RDBMS stores data in several tables and uses primary and foreign keys to keep relationships.

BATCH HOMEWORK

Write a 5-mark answer on **Relational Database Management System (RDBMS)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.4 Entity Relationship Model (ER-Model) ★ Golden

ACADEMY SESSION

Session 5 of 11 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The ER model is the architect's blueprint: you draw what will be stored and how it connects before you create tables in Access.

Error clinic: The M:N rule.

Exam wording to train: Always state cardinality on the diagram (1 and M at the ends of the line).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Entity Relationship Model (ER-Model)**. Write: The ER model is the architect's blueprint: you draw what will be stored and how it connects before you create tables in Access.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The ER model is the architect's blueprint: you draw what will be stored and how it connects before you create tables in Access. (2) Second distinct point (not a repeat of the definition) — + example.


5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a labelled ER diagram (rectangle / oval / diamond) or the relational schema + a one-line conclusion. Method marks are awarded for working.

LEARN IT

The **ER model** is the architect's blueprint: you draw what will be stored and how it connects *before* you create tables in Access. Three building blocks:

Component	Meaning	Symbol	Example
Entity	A real-world object we store data about	Rectangle	STUDENT, TEACHER, COURSE
Attribute	A property of an entity. PK is underlined	Oval	StudentID, Name, Class
Relationship	How two entities are connected	Diamond	Enrolls, Teaches, Has



Rectangle = entity, diamond = relationship, oval = attribute. Underline the primary-key attribute.

Cardinality (types of relationship)

Type	Meaning	Example
One-to-One (1:1)	One record $\leftrightarrow$ exactly one record. Rare; often for security.	One student has one ID card.
One-to-Many (1:M)	One record in A $\leftrightarrow$ many in B. The most common type.	One teacher teaches many students.
Many-to-Many (M:N)	Many in A $\leftrightarrow$ many in B.	Many students enrol in many classes.

COMMON MISTAKE

The M:N rule. A relational database cannot store M:N directly — it duplicates data. Break it into two 1:M relationships with a **junction table** (also called a bridge or associative table). Example: Enrollment(StudentID, ClassID, Date).

EXAM TIP

Always state cardinality on the diagram (1 and M at the ends of the line). For M:N, the long question is “how do you resolve it?” — draw the junction entity with two foreign keys.

اردو میں سمجھیں

ای آر ماڈل ڈیٹا بیس کا خاکہ ہے۔ مستطیل ہستی، بیضوی صفت، لوزی تعلق۔ تعلقات 1:1، M:1 یا M:N ہوتے ہیں۔ M:N کو دو M:1 میں توڑنے کے لیے جنکشن ٹیبل بنانا پڑتا ہے۔

CHECK YOURSELF

1. What symbol is used for a relationship?
2. A hospital: one patient, many appointments. Cardinality?

Answers: 1. Diamond. 2. 1:M (Patient 1 — has — M Appointment).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What symbol is used for a relationship?

3 marks. Explain Entity Relationship Model (ER-Model) with two clear points and one example.

5 marks. Always state cardinality on the diagram (1 and M at the ends of the line). For M:N, the long question is “how do you resolve it?” — draw the junction entity with two foreign keys.

8 marks. Entity Relationship Model (ER-Model): 5-mark answer plus a labelled ER diagram (rectangle / oval / diamond) or the relational schema.

Answers: 1. Diamond 3. The ER model is the architect’s blueprint: you draw what will be stored and how it connects before you create tables in Access. 5. Use the recipe in the blue box. Model opening: The ER model is the architect’s blueprint: you draw what will be stored and how it connects before you create tables in Access. 8. Same 5-mark body + a labelled ER diagram (rectangle / oval / diamond) or the relational schema + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Entity Relationship Model (ER-Model)** using the recipe in this topic. Include a labelled ER diagram (rectangle / oval / diamond) or the relational schema. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.5 Referential Integrity ★ Golden

ACADEMY SESSION

Session 6 of 11 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Referential integrity means every foreign-key value in a child table must match an existing primary-key value in the parent — or be NULL if the design allows it.

Error clinic: Cascade Delete is powerful and dangerous.

Exam wording to train: Write: definition, why it matters (no orphans), then one numbered example of Cascade Update and one of Cascade Delete.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Referential Integrity**. Write: Referential integrity means every foreign-key value in a child table must match an existing primary-key value in the parent — or be NULL if the design allows it.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) If Result.StudentID is a FK to Student.StudentID, you cannot type Result for student 999 if 999 is not in Student. (2) You also cannot delete student 101 while results for 101 still exist — unless you first handle those child rows. — + example.

5 marks: 3-mark structure + table: ID / Name + the worked example from this topic.

8–10 marks: 5-mark structure + a labelled ER diagram (rectangle / oval / diamond) or the relational schema + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Referential integrity means every foreign-key value in a child table must match an existing primary-key value in the parent — or be NULL if the design allows it. It stops **orphan records**.

If Result.StudentID is a FK to Student.StudentID, you cannot type Result for student 999 if 999 is not in Student. You also cannot delete student 101 while results for 101 still exist — unless you first handle those child rows.

Parent — STUDENT

ID	Name
101	Ali
102	Sara

Child — RESULT

ID	Grade
101	A
999	F — rejected

Cascade operations

Cascade Update. Change the PK in the parent, and every matching FK in the child changes automatically. Ali's ID 101 → 201 updates Enrollments too. Nothing is left pointing at a vanished 101.

Cascade Delete. Delete the parent, and related child rows are deleted too. If Sara (102) leaves school, her Enrolment and Result rows disappear. That prevents "ghost" marks for a student who is gone.

WORKED EXAMPLE

Before Cascade Update

Student.ID	Enrol.StudentID
101	101

After changing 101 → 201 with Cascade Update ON

Student.ID	Enrol.StudentID
201	201

If Cascade Update were OFF, Access would refuse the change, or (in a sloppy file) leave Enrol stuck on 101 — an orphan.

COMMON MISTAKE

Cascade Delete is powerful and dangerous. Deleting one parent can wipe years of child history. In a real school, you more often **archive** a student (a Status field) than delete them.

EXAM TIP

Write: definition, why it matters (no orphans), then one numbered example of Cascade Update and one of Cascade Delete. Mention parent vs child.

اردو میں سمجھیں

ریفرنشل انٹیگریٹی کا مطلب ہے بچہ ٹیبل کی فارن کی ہمیشہ والدین کی موجود پرائمری کی طرف اشارہ کرے۔ کیسکیڈ اپ ڈیٹ والدین کی کی بدلنے پر بچوں کو خود بدل دیتی ہے؛ کیسکیڈ ڈیلیٹ والدین مٹانے پر متعلقہ بچے ریکارڈ بھی مٹا دیتی ہے۔

CHECK YOURSELF

1. What is an orphan record?
2. Cascade Delete: parent Teacher is removed. What happens to that teacher's Class rows?

Answers: 1. A child row whose FK value does not exist in the parent. 2. They are deleted automatically (if Cascade Delete is on).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is an orphan record?

3 marks. Explain Referential Integrity with two clear points and one example.

5 marks. Write: definition, why it matters (no orphans), then one numbered example of Cascade Update and one of Cascade Delete. Mention parent vs child.

8 marks. Referential Integrity: 5-mark answer plus a labelled ER diagram (rectangle / oval / diamond) or the relational schema.

Answers: 1. A child row whose FK value does not exist in the parent. 3. If Result.StudentID is a FK to Student.StudentID, you cannot type Result for student 999 if 999 is not in Student.; You also cannot delete student 101 while results for 101 still exist — unless you first handle those child rows. 5. Use the recipe in the blue box. Model opening: Referential integrity means every foreign-key value in a child table must match an existing primary-key value in the parent — or be NULL if the design allows... 8. Same 5-mark body + a labelled ER diagram (rectangle / oval / diamond) or the relational schema + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Referential Integrity** using the recipe in this topic. Include a labelled ER diagram (rectangle / oval / diamond) or the relational schema. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.6 Relational Schema Development

ACADEMY SESSION

Session 7 of 11 · 45 minutes (first half) · paired with Case Study — Library Management System.

10–45 min — this topic. Lock the definition and table for **Relational Schema Development**. Starter (0–10) is from last class. Second half is Case Study — Library Management System.

On the board: A relational schema is the formal written design of the database: table names, fields, primary keys, foreign keys and how tables relate.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Relational Schema Development**. Write: A relational schema is the formal written design of the database: table names, fields, primary keys, foreign keys and how tables relate.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) You write it before clicking around in Access. (2) It defines (1) how data is split into tables, (2) which columns each table has, (3) which fields are PK/FK, (4) the relationships. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

A **relational schema** is the formal written design of the database: table names, fields, primary keys, foreign keys and how tables relate. You write it *before* clicking around in Access.

It defines (1) how data is split into tables, (2) which columns each table has, (3) which fields are PK/FK, (4) the relationships. Benefits: less redundancy, integrity planned in advance, easier to grow later.

WORKED EXAMPLE

Written schema for a tiny college:

```
Department (DeptID PK, DeptName)
Student    (RollNo PK, Name, Class, DeptID FK → Department)
Course     (CourseID PK, Title, Credit, DeptID FK → Department)
```

REMEMBER IT

Skipping the schema is like building a house without a drawing. You get messy, broken structures that are painful to repair.

ریلیشنل اسکیم ڈیٹا بیس کا لکھا ہوا نقشہ ہے: کون سے ٹیبل، کون سے فیلڈ، کون سی کیز، کون سے تعلقات۔ سافٹ ویئر کھولنے سے پہلے یہ بنانا چاہیے۔

CHECK YOURSELF

1. Name two things a schema must show.
2. Give one reason to write a schema before opening Access.

Answers: 1. Tables/fields and keys/relationships. 2. It reduces redundancy and mistakes (any valid benefit).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name two things a schema must show.

3 marks. Explain Relational Schema Development with two clear points and one example.

5 marks. Write a 5-mark answer on Relational Schema Development: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Tables/fields and keys/relationships 3. You write it before clicking around in Access.; It defines (1) how data is split into tables, (2) which columns each table has, (3) which fields are PK/FK, (4) the relationships. 5. Use the recipe in the blue box. Model opening: A relational schema is the formal written design of the database: table names, fields, primary keys, foreign keys and how tables relate.

BATCH HOMEWORK

Write a 5-mark answer on **Relational Schema Development** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.7 Case Study — Library Management System

ACADEMY SESSION

Session 7 of 11 · 45 minutes (second half) · paired with Relational Schema Development.

45–75 min — this topic. Board working for **Case Study — Library Management System**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: A college library needs a database.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Case Study — Library Management System**. Write: A college library needs a database.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Walk the seven steps examiners expect. (2) A book has ID, title, author, publisher. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

A college library needs a database. Walk the seven steps examiners expect.

Step 1 — Requirements. A book has ID, title, author, publisher. A member (student/teacher) has ID, name, contact. A member can borrow many books; a book can be borrowed by different members over time. Record Issue Date and Return Date.

Step 2 — Entities. Book, Member. (Borrowing will need a third entity in step 6.)

Step 3 — Attributes. Book: BookID (PK), Title, Author, Publisher. Member: MemberID (PK), Name, ContactInfo.

Step 4 — Relationship. Member *borrow*s Book.

Step 5 — Cardinality. One member borrows many books over time; one book is borrowed by many members over time → **M:N**.

Step 6 — Resolve M:N. Add junction entity **BorrowRecord**: BorrowID (PK), MemberID (FK), BookID (FK), IssueDate, ReturnDate. Now Member 1—M BorrowRecord M—1 Book (two 1:M links).

Step 7 — Final schema.

```
Member      (MemberID PK, Name, ContactInfo)
Book         (BookID PK, Title, Author, Publisher)
BorrowRecord (BorrowID PK, MemberID FK, BookID FK, IssueDate, ReturnDate)
```



Final library ER: two 1:M relationships through the BorrowRecord junction table.

WORKED EXAMPLE

Sample rows after Sara borrows "Khushwant" on 5 Oct 2026:

BorrowID	MemberID	BookID	IssueDate	ReturnDate
5001	102	B-17	2026-10-05	

The same book can later be borrowed by Ali as BorrowID 5002 — no duplicated book title, no duplicated member address.

اردو میں سمجھیں

لائبریری میں ممبر اور کتاب کا تعلق بہت-سے-بہت-سے ہے، اس لیے بورو ریکارڈ نامی پل ٹیبل بناتے ہیں جس میں دونوں کی فارن کیز اور اجراء/واپسی کی تاریخ ہوتی ہے۔

CHECK YOURSELF

1. Why is BorrowRecord needed?

2. Where do IssueDate and ReturnDate belong, and why not on Book?

Answers: 1. To break M:N into two 1:M links. 2. On BorrowRecord — they belong to a *transaction*, not to the book itself (a book is issued many times).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Why is BorrowRecord needed?

3 marks. Explain Case Study — Library Management System with two clear points and one example.

5 marks. Write a 5-mark answer on Case Study — Library Management System: definition, two points, a labelled diagram or table, and one example.

Answers: 1. To break M:N into two 1:M links 3. Walk the seven steps examiners expect.; A book has ID, title, author, publisher. 5. Use the recipe in the blue box. Model opening: A college library needs a database.

BATCH HOMEWORK

Write a 5-mark answer on **Case Study — Library Management System** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.8 Database Objects (Tables, Forms, Queries, Reports)

ACADEMY SESSION

Session 8 of 11 · 45 minutes (first half) · paired with Creation of Tables in Microsoft Access.

10–45 min — this topic. Lock the definition and table for **Database Objects (Tables, Forms, Queries, Reports)**. Starter (0–10) is from last class. Second half is Creation of Tables in Microsoft Access.

On the board: Four objects you will meet in Access.

Error clinic: A query does not copy the table into a second storage place.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Database Objects (Tables, Forms, Queries, Reports)**. Write: Four objects you will meet in Access.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Four objects you will meet in Access. (2) Learn the one-line jobs cold: — + example.

5 marks: 3-mark structure + table: Object / Job / You ... + the worked example from this topic.

LEARN IT

Four objects you will meet in Access. Learn the one-line jobs cold:

Object	Job	You ...
Table	Stores the data (foundation; every other object depends on it)	keep the actual records here
Form	Friendly screen for enter / edit / view (text boxes, drop-downs)	type data in; fewer mistakes than a raw grid
Query	Ask a question: filter, sort, calculate	e.g. "students above 80%"
Report	Formatted output for printing or sharing	read only — never type into a report

REMEMBER IT

Store → Enter → Search → Print. Tables, Forms, Queries, Reports.

COMMON MISTAKE

A query does not copy the table into a second storage place. It is a saved question. Change the table, re-run the query, and the answer updates.

اردو میں سمجھیں

ٹیبل ڈیٹا رکھتی ہے، فارم سے اندراج ہوتا ہے، کوئری سوال پوچھ کر چھاننتی ہے، رپورٹ چھپائی کے لیے سنواری ہوئی پیشکش ہے — اس میں ڈیٹا بھرا نہیں جاتا۔

CHECK YOURSELF

1. Which object would you use for a printed fee slip?
2. Which object actually holds the fee amount?

Answers: 1. Report. 2. Table.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which object would you use for a printed fee slip?

3 marks. Explain Database Objects (Tables, Forms, Queries, Reports) with two clear points and one example.

5 marks. Write a 5-mark answer on Database Objects (Tables, Forms, Queries, Reports): definition, two points, a labelled diagram or table, and one example.

Answers: 1. Report 3. Four objects you will meet in Access.; Learn the one-line jobs cold: 5. Use the recipe in the blue box. Model opening: Four objects you will meet in Access.

BATCH HOMEWORK

Write a 5-mark answer on **Database Objects (Tables, Forms, Queries, Reports)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.9 Creation of Tables in Microsoft Access

ACADEMY SESSION

Session 8 of 11 · 45 minutes (second half) · paired with Database Objects (Tables, Forms, Queries, Reports).

45–75 min — this topic. Board working for **Creation of Tables in Microsoft Access**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Plan first (4.9.1): purpose, field list, data type of each field, which field is the PK.

Error clinic: Phone numbers look numeric but are Short Text.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Creation of Tables in Microsoft Access**. Write: Plan first (4.9.1): purpose, field list, data type of each field, which field is the PK.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) A blank grid appears. (2) Double-click Field1, Field2, ... to rename. — + example.

5 marks: 3-mark structure + table: Data type / Use it for + the worked example from this topic.

LEARN IT

Plan first (4.9.1): purpose, field list, data type of each field, which field is the PK.

Datasheet View (4.9.2) — fast, spreadsheet-like, good for beginners, weak on rules.

1. Create tab → Table.
2. A blank grid appears.
3. Double-click Field1, Field2, ... to rename.
4. Type data; Access guesses the data type.

Limitation: you cannot easily say “Marks cannot exceed 100”. Professionals use Design View.

Design View (4.9.3) — full control before any data is typed.

1. Create tab → Table Design.
2. Type each Field Name (StudentID, Name, ...).
3. Pick the Data Type from the dropdown.
4. Right-click the unique field → Primary Key (key icon).
5. Save the table.

Data type	Use it for
Short Text	Names, addresses, phone numbers (you do not add phone numbers). Up to 255 characters.
Number	Values you calculate with: Age, Marks, Quantity.
Date/Time	Date of birth, admission date, appointment time.
Currency	Fees, salary.
AutoNumber	Access fills a unique sequential number — excellent PK.

COMMON MISTAKE

Phone numbers look numeric but are Short Text. Leading zeros (0333...) would vanish in a Number field, and you never sum two phone numbers.

اردو میں سمجھیں

پہلے ٹیبل کا منصوبہ بنائیں۔ ڈیٹا شیٹ ویو تیز لیکن کمزور ہے؛ ڈیزائن ویو میں فیلڈ، ڈیٹا ٹائپ اور پرائمری کی خود منتخب کرتے ہیں۔ فون نمبر شارٹ ٹیکسٹ رکھیں۔

CHECK YOURSELF

1. Best data type for StudentID if you want Access to generate it?
2. Best data type for FeeAmount?

Answers: 1. AutoNumber. 2. Currency.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Best data type for StudentID if you want Access to generate it?

3 marks. Explain Creation of Tables in Microsoft Access with two clear points and one example.

5 marks. Write a 5-mark answer on Creation of Tables in Microsoft Access: definition, two points, a labelled diagram or table, and one example.

Answers: 1. AutoNumber 3. A blank grid appears.; Double-click Field1, Field2, ... to rename. 5. Use the recipe in the blue box. Model opening: Plan first (4.9.1): purpose, field list, data type of each field, which field is the PK.

BATCH HOMEWORK

Write a 5-mark answer on **Creation of Tables in Microsoft Access** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.10 Designing Forms for Data Manipulation

ACADEMY SESSION

Session 9 of 11 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A form is the screen people actually type into.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Designing Forms for Data Manipulation**. Write: A form is the screen people actually type into.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Select the table (e.g. Student). (2) Move fields with > (one) or >> (all). — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

A form is the screen people actually type into. It cuts errors and can show validation messages. Every form **must** have a data source — a table or a query. A form with no source has nowhere to save.

Form Wizard (the exam method):

1. Create tab → Form Wizard.
2. Select the table (e.g. Student).
3. Move fields with > (one) or >> (all).
4. Choose layout. **Columnar** = one record at a time, best for data entry.
5. Name it ("Student Registration") → Finish.

WORKED EXAMPLE

A Student Registration form shows Student ID (AutoNumber, locked), Full Name, Class, Department as labelled boxes, plus Save. The clerk never sees the raw datasheet and cannot accidentally overwrite the next row.

اردو میں سمجھیں

فارم اندراج کی سادہ اسکرین ہے۔ ہر فارم کسی ٹیبل یا کوئری سے جڑا ہوتا ہے۔ فارم وزرڈ سے ٹیبل چنائیں، فیلڈز منتخب کریں، کالم نما لے آؤٹ بہتر ہے، نام دے کر ختم کریں۔

CHECK YOURSELF

1. Can a form exist without a table or query?
2. Which layout is best for entering one student at a time?

Answers: 1. No — it needs a data source. 2. Columnar.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Can a form exist without a table or query?

3 marks. Explain Designing Forms for Data Manipulation with two clear points and one example.

5 marks. Write a 5-mark answer on Designing Forms for Data Manipulation: definition, two points, a labelled diagram or table, and one example.

Answers: 1. No — it needs a data source 3. Select the table (e.g. Student).; Move fields with > (one) or >> (all). 5. Use the recipe in the blue box. Model opening: A form is the screen people actually type into.

BATCH HOMEWORK

Write a 5-mark answer on **Designing Forms for Data Manipulation** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.11 Creating Queries in MS Access ★ Golden

ACADEMY SESSION

Session 10 of 11 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A query retrieves, filters and analyses data without changing the original tables.

Error clinic: Text criteria need quotes: "IT".

Exam wording to train: Remember: AND = same row in the grid; OR = different rows.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Creating Queries in MS Access**. Write: A query retrieves, filters and analyses data without changing the original tables.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Show Table → add Student → Close. (2) Double-click the fields you want; they drop into the grid. — + example.

5 marks: 3-mark structure + table: Goal / Where to type / Example + the worked example from this topic.

8–10 marks: 5-mark structure + the full comparison table with every cell filled + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A query retrieves, filters and analyses data **without changing the original tables**. A simple SELECT query:

1. Create tab → Query Design.
2. Show Table → add Student → Close.
3. Double-click the fields you want; they drop into the grid.
4. Red Run (!) button executes it.

Criteria restrict rows. Type a value in the Criteria row under a field.

Goal	Where to type	Example
Single criterion	Criteria row, one column	Department → "Computer Science"
AND (both must match)	Same Criteria row, two columns	Name "Ali" and Department "Computer Science"
OR (either may match)	Criteria row and the or: row	Department "IT" or "Computer Science"

Wildcards in Access: * = any characters, ? = one character. Like "A*" finds Ali, Ahmed, Ayesha.

WORKED EXAMPLE

Equivalent SQL (what Access writes behind the grid):

```
SELECT StudentName, Department
FROM Student
WHERE Department = "Computer Science";

SELECT StudentName, Department
FROM Student
WHERE StudentName = "Ali" AND Department = "Computer Science";

SELECT StudentName, Department
FROM Student
WHERE Department = "IT" OR Department = "Computer Science";
```

EXAM TIP

Remember: AND = same row in the grid; OR = different rows. Examiners draw a blank grid and ask you to fill Criteria and or:.

COMMON MISTAKE

Text criteria need quotes: "IT". Numbers do not: ≥ 80 . Mixing these is a common cause of empty results.

اردو میں سمجھیں

کوئری ٹیبل کو بدلے بغیر سوال پوچھتی ہے۔ ایک شرط Criteria قطار میں، AND ایک ہی قطار کی دو کالموں میں، OR الگ قطار (or) میں۔ وائلڈ کارڈ * کئی حروف، ? ایک حرف۔

CHECK YOURSELF

1. Criteria for marks at least 80?
2. You want CS or IT. Same row or two rows?

Answers: 1. ≥ 80 under Marks. 2. Two rows (OR).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Criteria for marks at least 80?

3 marks. Explain Creating Queries in MS Access with two clear points and one example.

5 marks. Remember: AND = same row in the grid; OR = different rows. Examiners draw a blank grid and ask you to fill Criteria and or:.

8 marks. Creating Queries in MS Access: 5-mark answer plus the full comparison table with every cell filled.

Answers: 1. ≥ 80 under Marks 3. Show Table → add Student → Close.; Double-click the fields you want; they drop into the grid. 5. Use the recipe in the blue box. Model opening: A query retrieves, filters and analyses data without changing the original tables. 8. Same 5-mark body + the full comparison table with every cell filled + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Creating Queries in MS Access** using the recipe in this topic. Include the full comparison table with every cell filled. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.11.4 Data Summarization and Statistical Analysis

ACADEMY SESSION

Session 11 of 11 · 45 minutes (first half) · paired with Data Visualization in MS Access (Charts).

10–45 min — this topic. Lock the definition and table for **Data Summarization and Statistical Analysis**. Starter (0–10) is from last class. Second half is Data Visualization in MS Access (Charts).

On the board: Grouping combines rows that share a value (all CS students together) and then an aggregate calculates a number for the group.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Data Summarization and Statistical Analysis**. Write: Grouping combines rows that share a value (all CS students together) and then an aggregate calculates a number for the group.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Grouping combines rows that share a value (all CS students together) and then an aggregate calculates a number for the group. (2) In Access click Totals (Σ) to reveal the Total row in the grid. — + example.

5 marks: 3-mark structure + table: Function / What it calculates + the worked example from this topic.

LEARN IT

Grouping combines rows that share a value (all CS students together) and then an **aggregate** calculates a number for the group. In Access click Totals (Σ) to reveal the Total row in the grid.

Function	What it calculates
COUNT()	How many records (students in IT)
SUM()	Total of a number field (fees collected)
AVG()	Mean
MAX() / MIN()	Highest / lowest in the group

WORKED EXAMPLE

Average marks per department: add Department and Marks; Totals Σ ; Department $\rightarrow$ Group By; Marks $\rightarrow$ Avg; Run.

Department	Avg of Marks
Computer Science	82.5
IT	76.0

Check: CS marks 80, 85 $\rightarrow$ average $(80+85)/2 = 82.5$. IT 70, 82 $\rightarrow 76.0$.

```
SELECT Department, AVG(Marks) AS AvgOfMarks
FROM Student
GROUP BY Department;
```

اردو میں سمجھیں

گروپ بائی ایک جیسے ریکارڈ جوڑتا ہے، پھر COUNT, SUM, AVG, MAX, MIN سے خلاصہ نکلتا ہے۔ ایکسیس میں Σ بٹن Total قطار کھولتا ہے۔

CHECK YOURSELF

1. Which Total setting goes under Department?
2. Which function counts how many books each member has borrowed?

Answers: 1. Group By. 2. COUNT (of BorrowID or BookID) grouped by MemberID.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which Total setting goes under Department?

3 marks. Explain Data Summarization and Statistical Analysis with two clear points and one example.

5 marks. Write a 5-mark answer on Data Summarization and Statistical Analysis: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Group By 3. Grouping combines rows that share a value (all CS students together) and then an aggregate calculates a number for the group.; In Access click Totals (Σ) to reveal the Total row in the grid. 5. Use the recipe in the blue box. Model opening: Grouping combines rows that share a value (all CS students together) and then an aggregate calculates a number for the group.

BATCH HOMEWORK

Write a 5-mark answer on **Data Summarization and Statistical Analysis** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.11.6 Data Visualization in MS Access (Charts)

ACADEMY SESSION

Session 11 of 11 · 45 minutes (second half) · paired with Data Summarization and Statistical Analysis.

45–75 min — this topic. Board working for **Data Visualization in MS Access (Charts)**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Charts turn numbers into a picture so a pattern jumps out.

Exam wording to train: “Which chart?” — line for time, pie for composition, bar/column for comparing categories.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Data Visualization in MS Access (Charts)**. Write: Charts turn numbers into a picture so a pattern jumps out.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).


3 marks: definition + two points — (1) Charts turn numbers into a picture so a pattern jumps out. (2) Pick the chart that matches the question: — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

Charts turn numbers into a picture so a pattern jumps out. Pick the chart that matches the question:

Chart	Shape	Best for
Bar (horizontal)	Bars sideways	Categories with long names (English, Mathematics, ...)
Column (vertical)	Bars standing	Side-by-side comparison (2024 / 2025 / 2026 admissions)
Pie	Slices of a circle	Parts of one whole (percent of CS vs IT vs Eng). Few slices.
Line	Dots joined	A trend over time (visitors per month)



Column = compare categories. Pie = share of a total. Line = change over time.

EXAM TIP

"Which chart?" — line for time, pie for composition, bar/column for comparing categories. Mention one reason.

اردو میں سمجھیں

بار لمبے ناموں والی اقسام، کالم سادہ موازنہ، پائی حصوں کا تناسب، لائن وقت کے ساتھ رجحان۔ چارٹ کوٹری یا ٹیبل کے اعداد کو تصویر بناتا ہے۔

CHECK YOURSELF

1. Website visitors each month — which chart?
2. Share of boys vs girls in one class — which chart?

Answers: 1. Line. 2. Pie (two parts of a whole).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Website visitors each month — which chart?

3 marks. Explain Data Visualization in MS Access (Charts) with two clear points and one example.

5 marks. "Which chart?" — line for time, pie for composition, bar/column for comparing categories. Mention one reason.

Answers: 1. Line 3. Charts turn numbers into a picture so a pattern jumps out.; Pick the chart that matches the question: 5. Use the recipe in the blue box. Model opening: Charts turn numbers into a picture so a pattern jumps out.

BATCH HOMEWORK

Write a 5-mark answer on **Data Visualization in MS Access (Charts)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Chapter 4 Review

Chapter summary

- Data = raw facts; information = processed data used for decisions; a database stores related data in a structured, updatable way.
- A DBMS is the software layer that provides less redundancy, consistency, security and integrity.
- Table = rows (records) and columns (fields). One table, one entity.
- Candidate keys could identify a row; the primary key is the one you choose (unique, not NULL); leftover candidates are alternate keys; a foreign key points at another table's PK.
- An RDBMS keeps several related tables and is queried with SQL.
- ER symbols: rectangle entity, oval attribute, diamond relationship. Cardinality 1:1, 1:M, M:N. M:N needs a junction table.
- Referential integrity forbids orphan FKs. Cascade Update copies a changed PK into children; Cascade Delete removes children with the parent.
- Write a relational schema before building. Library case: Member and Book are M:N, resolved by BorrowRecord.
- Objects: tables store, forms enter, queries search, reports print.
- Access Design View sets field names, data types and the PK. Phone numbers are Short Text; money is Currency; auto IDs are AutoNumber.
- Forms need a table/query source; Wizard + columnar layout for data entry.
- Query criteria: one value; AND on the same row; OR on two rows. Totals Σ for Group By / Count / Sum / Avg / Max / Min.
- Bar/column compare categories, pie shows parts of a whole, line shows a trend over time.

Key terms

Term	Meaning	اردو
Data	Raw facts and figures.	ڈیٹا / خام حقائق
Information	Processed data that supports a decision.	معلومات
Database	Organised collection of related data.	ڈیٹا بیس
DBMS	Software that creates and manages databases.	ڈیٹا بیس مینجمنٹ سسٹم
Table	Rows and columns about one entity.	ٹیبل
Record	One row — one instance.	ریکارڈ
Field	One column — one attribute.	فیلڈ
Primary key	Chosen unique, non-empty identifier.	پرائمری کی
Foreign key	Field that refers to another table's PK.	فارن کی
Candidate key	Any field(s) that could be the PK.	کینڈیڈیٹ کی
Alternate key	A candidate not chosen as PK.	آلٹرنیٹ کی
RDBMS	DBMS that stores related tables linked by keys.	ریلیشنل ڈی بی ایم ایس
SQL	Language to query relational databases.	ساختمہ استفساری زبان
Entity	Object we store data about (ER rectangle).	ہستی
Attribute	Property of an entity (ER oval).	صفت
Relationship	Link between entities (ER diamond).	تعلق
Cardinality	1:1, 1:M or M:N.	عددییت
Junction table	Bridge table that splits an M:N into two 1:M.	جنکشن ٹیبل
Referential integrity	Every FK matches a live PK (no orphans).	حوالہ جاتی درستگی
Cascade Update	Parent PK change copied to child FKs.	کیسکیڈ اپ ڈیٹ
Cascade Delete	Deleting the parent deletes related children.	کیسکیڈ ڈیلیٹ
Schema	Written blueprint of tables, keys, relationships.	اسکیما / نقشہ
Form	Screen for entering data.	فارم
Query	Saved question that filters/calculates data.	کوئری
Report	Formatted printable output.	رپورٹ
AutoNumber	Access-generated unique integer, often the PK.	آٹو نمبر

Practice: multiple choice

1. Processed data used for a decision is called:
 - a. a field
 - b. information
 - c. a query
 - d. redundancy
2. A complete row about one student is a:
 - a. field
 - b. report
 - c. record
 - d. schema
3. A primary key cannot contain:
 - a. numbers
 - b. text
 - c. NULL
 - d. an AutoNumber
4. EmpLicense# after EmpID is chosen as PK is an:
 - a. foreign key
 - b. alternate key
 - c. orphan
 - d. report
5. A foreign key:
 - a. must be unique in the child table
 - b. may contain duplicates
 - c. cannot exist in an RDBMS
 - d. is always AutoNumber
6. The ER symbol for a relationship is a:
 - a. rectangle
 - b. oval
 - c. diamond
 - d. circle
7. The most common cardinality is:
 - a. 1:1
 - b. 1:M
 - c. M:N stored as-is
 - d. 0:0
8. M:N is stored in an RDBMS by:
 - a. duplicating both tables
 - b. a junction table
 - c. deleting one entity
 - d. using a pie chart
9. A child row whose StudentID is not in Student is:
 - a. a candidate key
 - b. an orphan record
 - c. a form
 - d. a primary key
10. Changing parent ID 101 → 201 and seeing the child follow is:
 - a. Cascade Delete
 - b. Cascade Update
 - c. a SELECT query
 - d. a pie chart
11. Which Access object is for printing a report card?
 - a. Table
 - b. Form
 - c. Query
 - d. Report
12. Phone numbers should be stored as:
 - a. Number
 - b. Currency
 - c. Short Text
 - d. Date/Time
13. AND criteria go:
 - a. on two different rows of the grid
 - b. on the same Criteria row
 - c. in a report header
 - d. only in SQL Server
14. To average marks per department you set Department to:
 - a. Sum
 - b. Where
 - c. Group By
 - d. Expression
15. The best chart for admissions in 2024, 2025, 2026 is a:
 - a. pie chart
 - b. column chart
 - c. junction table
 - d. foreign key

Practice: short questions

1. Differentiate data and information with one example each.
2. List four advantages of a DBMS.
3. Define record and field with reference to a Student table.
4. Differentiate primary key and foreign key (four points).
5. Why can a relational database not store M:N directly?
6. What is referential integrity? Give one rejected-insert example.
7. Differentiate Cascade Update and Cascade Delete.
8. State the four Access objects and the job of each in one line.
9. Why are phone numbers Short Text, not Number?
10. How do you express OR in Query Design?

Practice: long / problem questions

1. Draw a complete ER diagram for Student–Course enrolment (M:N). Resolve it with a junction entity. Write the relational schema with keys marked.
2. A Result table uses StudentID as a foreign key. Explain referential integrity, then show before/after tables for (a) Cascade Update of ID 101 → 201 and (b) Cascade Delete of student 102.
3. Work through the library case study: requirements, entities, attributes, relationship, cardinality, junction table, final schema. Include two sample BorrowRecord rows.
4. Write step-by-step how to create a Student table in Access Design View (fields RollNo Number PK, Name Short Text, Marks Number, Fee Currency, AdmDate Date/Time) and then a columnar form with the Wizard.
5. Write the Query Design settings and the SQL to list CS students with Marks ≥ 80 , sorted by Name. Then write a totals query that shows COUNT of students and AVG(Marks) for each Department.
6. A principal wants to see (i) fee collected per class, (ii) the share of each class in total enrolment, (iii) enrolment over five years. Which chart for each, and why?

Answer key

Multiple choice

1. b
2. c
3. c
4. b
5. b
6. c
7. b
8. b
9. b
10. b
11. d
12. c
13. b
14. c
15. b

Short questions — model answers

1. Data = raw facts (80, 75, 90). Information = processed meaning ("average is 81.7%, the class is ready").
2. Less redundancy, consistency, security (authorised access), integrity (valid, unique keys). (Sharing / backup also accepted.)
3. Record = one student's full row (101, Ali, CS, A). Field = one column such as Name.
4. PK uniquely identifies a row, cannot be NULL, one per table, lives in the parent. FK refers to a PK, may duplicate, may be NULL, lives in the child, creates the relationship.
5. It would duplicate attributes of both entities. Split into two 1:M links with a junction table that holds both FKs plus extra attributes (dates).
6. Every FK must match an existing parent PK. Inserting Result.StudentID = 999 is rejected if 999 is not in Student — that would have been an orphan.
7. Cascade Update copies a changed parent PK into child FKs. Cascade Delete removes child rows when the parent is deleted.
8. Table stores; form enters; query searches/filters; report prints.
9. They are identifiers, not quantities; leading zeros would vanish; you never add two numbers of a phone.
10. Put one value on the Criteria row and the other on the or: row of the same field (or of different fields if that is the question).

Long questions — model answers

1. Entities STUDENT and COURSE, relationship Enrolls (M:N). Junction ENROLLMENT(EnrollID PK, StudentID FK, CourseID FK, Date). Schema: Student(StudentID PK, Name, Class); Course(CourseID PK, Title); Enrollment as above. Diagram: 1 — M — M — 1 through the junction.
2. (a) Parent 101 Ali → 201 Ali; child Result rows that said 101 now say 201. (b) Delete parent 102 Sara; all Result and Enrolment rows with 102 disappear. Integrity definition: FK must match a live PK; this stops orphans and keeps reports true.
3. Follow steps 1–7 in the chapter. Sample: (5001, 102, B-17, 2026-10-05, NULL); (5002, 101, B-17, 2026-10-12, 2026-10-20) — same book, two members, no duplicated titles.
4. Create → Table Design; enter the five fields and types; right-click RollNo → Primary Key; Save as Student. Create → Form Wizard → Student → >> all fields → Columnar → name Student Registration → Finish.
5. Grid: Name, Department, Marks. Criteria under Department: "CS" (or "Computer Science"); Criteria under Marks: ≥ 80 (same row = AND); Sort under Name: Ascending. SQL: `SELECT Name, Department, Marks FROM Student WHERE Department="CS" AND Marks  $\geq 80$  ORDER BY Name`; Totals query: Department Group By, StudentID Count, Marks Avg.
6. (i) Column or bar — compare categories (classes). (ii) Pie — each class is a part of one whole enrolment. (iii) Line — a trend over years.

Self-assessment: I can...

- | | |
|--|---|
| ☐ explain data vs information vs database vs DBMS. | ☐ point at records and fields in a table. |
| ☐ choose PK / FK / candidate / alternate keys correctly. | ☐ draw ER symbols and label 1:1, 1:M, M:N. |
| ☐ resolve M:N with a junction table. | ☐ explain referential integrity and both cascade operations with examples. |
| ☐ write a relational schema including the library case study. | ☐ match tables, forms, queries and reports to a task. |
| ☐ create a table in Design View and pick data types. | ☐ build a Wizard form and a criteria query (AND, OR, totals). |
| ☐ choose bar, column, pie or line for a given question. | |

Application and Impacts of Computing

This chapter shows you how computing technologies such as Artificial Intelligence, the Internet of Things and Data Analytics are changing life in Pakistan — in cities, hospitals, farms and classrooms. You will also learn how to judge information sources, weigh the good and bad effects of computing, and see how assistive technologies give everyone an equal chance.

اس باب میں آپ سیکھیں گے کہ مصنوعی ذہانت (AI)، انٹرنیٹ آف تھنگز (IoT) اور ڈیٹا اینالیٹکس ہماری روزمرہ زندگی کو کیسے بدل رہے ہیں۔ آپ معلومات کے ذرائع کو پرکھنا، کمپیوٹنگ کے مثبت اور منفی اثرات سمجھنا، اور معذور افراد کی مدد کرنے والی ٹیکنالوجی کے بارے میں بھی جانیں گے۔

What you will learn

- Explain what Artificial Intelligence (AI) is and give everyday examples of it.
- Name and explain the six components of an IoT system, with examples of each.
- Compare IoT, AI and Data Analytics by definition, purpose, type of work and output.
- Discuss the uses, benefits and challenges of AI in education in Pakistan.
- Analyse positive and negative impacts of computing in five fields, and practise responsible use.
- Describe how IoT, Data Analytics and AI work together in a smart system.
- List the five components of Data Analytics in the correct order.
- Describe uses of IoT in smart cities, industry, healthcare, education, homes and farming.
- Classify information sources as primary, secondary or tertiary, and judge when a source is unreliable.
- Explain the four categories of assistive technologies, their importance, and related careers.

ACADEMY CALENDAR

Academy calendar: 13 topics · 4 Golden · **10 classes of 90 minutes** + one 40-minute weekly test after this chapter.

Class	Topics	Kind	Board focus
Class 01	Introduction to Computing Impacts	Single · 90 min	Computing means using computers and computer-based devices to store, process and share...
Class 02	Artificial Intelligence (AI)	★ Golden · 90 min	Artificial Intelligence (AI) is the ability of a computer system to perform tasks that...
Class 03	Internet of Things (IoT) & Components	★ Golden · 90 min	The Internet of Things (IoT) is a system in which physical devices are connected to the...
Class 04	Data Analytics & Components + Comparison: IoT vs AI vs Data Analytics	Paired · 90 min	Data Analytics is the process of collecting, organising, cleaning, studying and...
Class 05	Uses of IoT in Different Areas + Scope of AI in Education in Pakistan	Paired · 90 min	IoT improves efficiency (doing more with less effort), saves time, and enhances the...
Class 06	Career Connection in IoT and AI	Single · 90 min	Learning computing skills opens doors to many employers in Pakistan: software houses (e.g.
Class 07	Information Sources (Primary, Secondary, Tertiary)	★ Golden · 90 min	Information sources are ways to find knowledge and data.
Class 08	Impacts of Computing in Various Fields	Single · 90 min	Computing has drastically changed society.
Class 09	Assistive Technologies	★ Golden · 90 min	Assistive technologies are devices, software and systems that help people with...
Class 10	Importance of Assistive Technologies + Career Connection in Assistive Tech	Paired · 90 min	Assistive technologies are important for three main reasons: Equal access to education:...

Weekly test: 15 MCQ from this chapter + two 5-mark Golden questions. Mark to the recipes. Re-teach any Golden below 60% in the next starter.

گولڈن موضوع پوری کلاس لیتا ہے۔ ہفتہ وار ٹیسٹ کے بعد کمزور گولڈن دوبارہ پڑھائیں۔

5.1 Introduction to Computing Impacts

ACADEMY SESSION

Session 1 of 10 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Computing means using computers and computer-based devices to store, process and share information.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Introduction to Computing Impacts**. Write: Computing means using computers and computer-based devices to store, process and share information.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Hospitals — computerised patient records, digital X-rays, online appointment systems. (2) Banks — ATMs, mobile banking apps, Raast instant payments, JazzCash and Easypaisa wallets. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Computing means using computers and computer-based devices to store, process and share information. Today computing is an important part of your daily life. You use computers, mobile phones, the internet and smart devices almost everywhere — at home, in college and on the road.

In Pakistan, computing is becoming **vital** (very necessary) in:

- **Schools and colleges** — online admissions, e-books, online results of the Sindh boards.
- **Hospitals** — computerised patient records, digital X-rays, online appointment systems.
- **Banks** — ATMs, mobile banking apps, Raast instant payments, JazzCash and Easypaisa wallets.
- **Farms** — weather forecasts on mobile phones, soil sensors, tube-well control.
- **Industries** — automatic machines in textile mills in Karachi, Hyderabad and Faisalabad.

An **impact** is the effect something has on people and society. Computing has **positive impacts** (speed, convenience, new jobs) and **negative impacts** (privacy risks, addiction, job loss). In this chapter you will study three key technologies first — AI, IoT and Data Analytics — and then their uses and impacts.

WORKED EXAMPLE

A day in Sara's life in Karachi — spot the computing:

Step 1. 7:00 am — Her phone unlocks by recognising her face (AI).

Step 2. 7:30 am — She books a ride on a ride-hailing app; GPS shows the car's location (internet + location data).

Step 3. 9:00 am — College attendance is marked by a biometric (fingerprint) machine (IoT).

Step 4. 2:00 pm — She pays her fee through a mobile banking app (computing in business).

Step 5. 8:00 pm — YouTube suggests a physics lecture based on what she watched yesterday (AI).

Conclusion: in a single day, Sara uses computing in at least five different fields without even thinking about it.

اردو میں سمجھیں

کمپیوٹنگ آج ہماری روزمرہ زندگی کا اہم حصہ بن چکی ہے۔ پاکستان میں اسکول، اسپتال، بینک، کھیت اور صنعتیں سب کمپیوٹر اور انٹرنیٹ پر انحصار کرنے لگے ہیں۔ کمپیوٹنگ کے فائدے بھی ہیں اور نقصانات بھی، جنہیں ہم اس باب میں سمجھیں گے۔

CHECK YOURSELF

1. Name four places in Pakistan where computing has become vital.

2. What is meant by the "impact" of computing?

Answers: 1. Any four of: schools, hospitals, banks, farms, industries. 2. The effect computing has on people and society — it can be positive or negative.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name four places in Pakistan where computing has become vital.

3 marks. Explain Introduction to Computing Impacts with two clear points and one example.

5 marks. Write a 5-mark answer on Introduction to Computing Impacts: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Any four of: schools, hospitals, banks, farms, industries 3. Hospitals — computerised patient records, digital X-rays, online appointment systems.; Banks — ATMs, mobile banking apps, Raast instant payments, JazzCash and Easypaisa wallets. 5. Use the recipe in the blue box. Model opening: Computing means using computers and computer-based devices to store, process and share information.

BATCH HOMEWORK

Write a 5-mark answer on **Introduction to Computing Impacts** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.1.1 Artificial Intelligence (AI) ★ Golden

ACADEMY SESSION

Session 2 of 10 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Artificial Intelligence (AI) is the ability of a computer system to perform tasks that normally need human thinking, such as recognising faces, understanding language and making decisions.

Error clinic: Mistake: "AI means robots." Fix: Most AI is just software — YouTube suggestions, spam filters and face unlock have no robot body.

Exam wording to train: Common questions: "Define AI and give two examples" (2–3 marks), and "Explain how AI, IoT and Data Analytics work together" (4–5 marks).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Artificial Intelligence (AI)**. Write: Artificial Intelligence (AI) is the ability of a computer system to perform tasks that normally need human thinking, such as recognising faces, understanding language and making decisions.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Intelligence — it can perform tasks that require thinking. (2) Face recognition on a mobile phone to unlock the screen. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

8–10 marks: 5-mark structure + a complete truth table and a labelled gate / logic diagram + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Artificial Intelligence (AI) is the ability of a computer system to perform tasks that normally need human thinking, such as recognising faces, understanding language and making decisions.

Understand the name in two parts:

- **Artificial** — it is *created by humans*; it is not natural.
- **Intelligence** — it can perform tasks that *require thinking*.

AI systems **use data to make decisions**. The more good data an AI system sees, the better it becomes at recognising patterns (repeating features) and predicting what to do.

Examples from the source:

1. **Face recognition** on a mobile phone to unlock the screen.
2. **YouTube suggesting videos** based on your interests.
3. **Chatbots** answering questions on a website (for example, a bank's help chat).

More Pakistani examples: Google Maps predicting traffic on Shahrah-e-Faisal, Urdu voice typing on your phone, banks flagging a suspicious card transaction, and AI tools that translate English into Urdu.

AI in smart systems

AI rarely works alone. It often acts as the **"brain"** of a system, working together with the **Internet of Things (IoT)** and **Data Analytics**:

- **IoT devices gather data** — they are the "eyes" (sensors).
- **Analytics sorts the data** — it organises and studies it.
- **AI makes the final decision** — it is the "brain".
- An **action** follows — something happens in the real world.

IoT (Eyes) — collects data → Analytics — sorts data → AI (Brain) — decides → Action

WORKED EXAMPLE

Smart air-conditioner in a hot Hyderabad room — trace the system:

Step 1 (IoT – eyes). A temperature sensor reads the room temperature: 36 °C.

Step 2 (Analytics). The readings of the last 10 minutes are organised: 34, 35, 35, 36 °C — the room is getting hotter.

Step 3 (AI – brain). The AI compares this with the comfortable limit (say 26 °C) and with the fact that a person is in the room (motion sensor). Decision: "Turn the AC on."

Step 4 (Action). A switch turns the AC on automatically.

No human pressed a button — the system sensed, thought and acted.

REMEMBER IT

Eyes – Sort – Brain – Do. IoT is the *eyes*, Analytics *sorts*, AI is the *brain*, and the actuator *does* the action. Think of a cricket fielder: his eyes see the ball (IoT), he judges speed and direction (analytics), decides to dive (AI), and his body moves (action).

COMMON MISTAKE

Mistake: "AI means robots." **Fix:** Most AI is just *software* — YouTube suggestions, spam filters and face unlock have no robot body. A robot may *use* AI, but AI itself is the thinking software.

مصنوعی ذہانت (AI) کو "مصنوعی" اس لیے کہتے ہیں کہ اسے انسانوں نے بنایا ہے، اور "ذہانت" اس لیے کہ یہ ایسے کام کر سکتی ہے جن کے لیے سوچنا پڑتا ہے۔ AI ڈیٹا کی مدد سے فیصلے کرتی ہے، جیسے چہرہ پہچان کر فون کھولنا یا یوٹیوب پر ویڈیوز تجویز کرنا۔ ایک اسمارٹ سسٹم میں IoT آنکھوں کا کام کرتا ہے اور AI دماغ کا۔

EXAM TIP

Common questions: "Define AI and give two examples" (2–3 marks), and "Explain how AI, IoT and Data Analytics work together" (4–5 marks).

To score full marks: (1) write the two-part meaning of the name — *artificial* = *made by humans*, *intelligence* = *can think/decide*; (2) say "AI uses data to make decisions"; (3) give at least two examples; (4) for the "together" question, draw the flow IoT → Analytics → AI → Action and explain it with the room-AC example.

CHECK YOURSELF

1. Why is AI called "artificial"?
2. In a smart system, which technology is the "brain" and which is the "eyes"?
3. Is a spam filter in Gmail an example of AI? Why?

Answers: 1. Because it is created by humans. 2. AI is the brain; IoT is the eyes. 3. Yes — it uses data (past spam emails) to decide whether a new email is spam, a task that needs "thinking".

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Why is AI called "artificial"?

3 marks. Explain Artificial Intelligence (AI) with two clear points and one example.

5 marks. Common questions: "Define AI and give two examples" (2–3 marks), and "Explain how AI, IoT and Data Analytics work together" (4–5 marks). To score full marks: (1) write the two-part meaning of the...

8 marks. Artificial Intelligence (AI): 5-mark answer plus a complete truth table and a labelled gate / logic diagram.

Answers: 1. Because it is created by humans 3. Intelligence — it can perform tasks that require thinking.; Face recognition on a mobile phone to unlock the screen. 5. Use the recipe in the blue box. Model opening: Artificial Intelligence (AI) is the ability of a computer system to perform tasks that normally need human thinking, such as recognising faces, understanding... 8. Same 5-mark body + a complete truth table and a labelled gate / logic diagram + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Artificial Intelligence (AI)** using the recipe in this topic. Include a complete truth table and a labelled gate / logic diagram. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.1.2 Internet of Things (IoT) & Components ★ Golden

ACADEMY SESSION

Session 3 of 10 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The Internet of Things (IoT) is a system in which physical devices are connected to the Internet and can collect and share data to perform tasks automatically.

Error clinic: Mistake: Calling a fan controller or water valve a "sensor".

Exam wording to train: "Define IoT and explain its components" is one of the most frequent long questions.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Internet of Things (IoT) & Components**. Write: The Internet of Things (IoT) is a system in which physical devices are connected to the Internet and can collect and share data to perform tasks automatically.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The "things" are ordinary objects — watches, cameras, cars, fans, water pumps — that have been given sensors and an internet connection so... (2) Source example: A smartwatch collects your heart-rate data and sends it to your mobile phone, where it is displayed. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a fully labelled diagram copied from the board + a one-line conclusion. Method marks are awarded for working.

LEARN IT

The **Internet of Things (IoT)** is a system in which **physical devices are connected to the Internet** and can **collect and share data** to perform tasks **automatically**.

The "things" are ordinary objects — watches, cameras, cars, fans, water pumps — that have been given sensors and an internet connection so they can "talk" to each other and to us.

Source example: A **smartwatch** collects your heart-rate data and sends it to your mobile phone, where it is displayed.

Components of IoT systems

IoT relies on **six foundational components** to work properly.

#	Component	What it does	Examples
1	Sensors	Devices that collect information from the physical world. They are the "eyes and ears" of the system.	Temperature sensor, motion sensor, fingerprint sensor, smoke sensor, soil moisture sensor


#	Component	What it does	Examples
2	Actuators	Devices that perform physical actions in response to system commands. They convert digital signals into physical movement.	Electric motor, switch, automatic door opener, water valve, fan controller
3	Connectivity	The connection that allows devices to send and receive data . Without it, sensors can't talk to the system.	Wi-Fi, Bluetooth, ZigBee, 4G/5G
4	Data Processing	Changing raw data into useful information . Steps: collecting, organising, analysing and deciding.	Checking if the room temperature is too hot to trigger the AC
5	Cloud Computing	Storing data and using services over the internet instead of local hard drives. Handles massive IoT data.	Google Drive, iCloud, online LMS
6	User Interface (UI)	The component that enables interaction between the user and the device . Helps users see information and give commands.	Mobile apps, touch screens, voice commands

Understanding each component

- **Sensors** turn something in the real world (heat, movement, a fingerprint, smoke, wetness of soil) into data. A smoke sensor in a Karachi shopping mall "smells" smoke and reports it.
- **Actuators** do the opposite: they take a digital command and make something *move* or *change*. The water valve that opens, the motor that turns, the door that slides open at a bank entrance.
- **Connectivity** is the "road" for data. Short distances use Bluetooth (watch to phone); a house uses Wi-Fi; low-power sensor networks use **ZigBee**; devices far away in fields use mobile networks (4G/5G from Jazz, Zong, Telenor/Ufone).
- **Data processing** is where raw numbers ("36") become meaning ("too hot — turn on AC"). Its four steps are *collect* → *organise* → *analyse* → *decide*.
- **Cloud computing** stores and processes the huge amount of data that thousands of sensors produce every second — far more than a single small device can hold.
- **User Interface** is how *you* see the data and give orders — an app on your phone, a touch screen on a smart fridge, or saying "Hey Google, turn off the lights".

How the components connect





The six IoT components working as one system (data processing happens inside the cloud).

WORKED EXAMPLE

Smart fire alarm in a Karachi factory — identify all six components:

Step 1 — Sensor: A smoke sensor detects smoke near the machines.

Step 2 — Connectivity: It sends the reading over the factory Wi-Fi.

Step 3 — Cloud computing: The reading is stored on an online server along with the history of all sensors.

Step 4 — Data processing: The software checks: "Is the smoke level above the safe limit?" Yes → decide "Fire risk!"

Step 5 — Actuator: Water valves of the sprinklers open and the alarm bell switch turns on.

Step 6 — User interface: The manager's mobile app shows a red alert: "Smoke detected – Hall 3".

REMEMBER IT

Sensor senses, Actuator acts. Both words give you the answer: **sensor** = **see**/sense (input), **actuator** = **act** (output). Remember the six components with "**Some Ants Carry Data Carefully Up**" — Sensors, Actuators, Connectivity, Data processing, Cloud, UI.

COMMON MISTAKE

Mistake: Calling a fan controller or water valve a "sensor". **Fix:** Ask "does it *measure* something or *do* something?" A valve opens and closes — it *does*, so it is an **actuator**. A soil moisture sensor only *measures*, so it is a **sensor**.

اردو میں سمجھیں

انٹرنیٹ آف تھنگز (IoT) ایک ایسا نظام ہے جس میں مختلف آلات (جیسے گھڑیاں، کیمرے، گاڑیاں) انٹرنیٹ سے جڑے ہوتے ہیں اور خودکار طریقے سے ڈیٹا جمع اور شیئر کرتے ہیں۔ اس کے چھ بنیادی اجزاء ہیں: سینسرز (معلومات جمع کرتے ہیں)، ایکچویٹرز (جسمانی کام انجام دیتے ہیں جیسے موٹر چلانا یا دروازہ کھولنا)، کنیکٹیویٹی (وائی فائی، بلوٹوتھ)، ڈیٹا پروسیسنگ، کلاؤڈ کمپیوٹنگ، اور یوزر انٹرفیس (موبائل ایپ)۔

EXAM TIP

"Define IoT and explain its components" is one of the most frequent long questions. Write the definition with the three key ideas — *physical devices, connected to the internet, collect and share data automatically*. Then list all **six** components, each with a one-line meaning and one example. A labelled flow diagram (Sensor → Wi-Fi → Cloud → Actuator → App) earns extra credit.

Short questions often ask: "Differentiate between a sensor and an actuator" — sensor collects data (input, eyes and ears), actuator performs physical action (output, converts digital signals into movement).

CHECK YOURSELF

1. Classify as sensor or actuator: (a) fingerprint scanner, (b) automatic door opener, (c) motion detector, (d) electric motor.
2. Name four types of connectivity used in IoT.
3. Why is cloud computing needed in IoT?

Answers: 1. (a) sensor, (b) actuator, (c) sensor, (d) actuator. 2. Wi-Fi, Bluetooth, ZigBee, 4G/5G. 3. Because IoT devices produce massive amounts of data; the cloud stores and processes it over the internet instead of on small local hard drives.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Classify as sensor or actuator: (a) fingerprint scanner, (b) automatic door opener, (c) motion detector, (d) electric motor.

3 marks. Explain Internet of Things (IoT) & Components with two clear points and one example.

5 marks. "Define IoT and explain its components" is one of the most frequent long questions. Write the definition with the three key ideas — physical devices, connected to the internet, collect and share data...

8 marks. Internet of Things (IoT) & Components: 5-mark answer plus a fully labelled diagram copied from the board.

Answers: 1. (a) sensor, (b) actuator, (c) sensor, (d) actuator 3. The "things" are ordinary objects — watches, cameras, cars, fans, water pumps — that have been given sensors and an internet connection so...; Source example: A smartwatch collects your heart-rate data and sends it to your mobile phone,... 5. Use the recipe in the blue box. Model opening: The Internet of Things (IoT) is a system in which physical devices are connected to the Internet and can collect and share data to perform tasks automatically. 8. Same 5-mark body + a fully labelled diagram copied from the board + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Internet of Things (IoT) & Components** using the recipe in this topic. Include a fully labelled diagram copied from the board. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.1.3 Data Analytics & Components

ACADEMY SESSION

Session 4 of 10 · 45 minutes (first half) · paired with Comparison: IoT vs AI vs Data Analytics.

10–45 min — this topic. Lock the definition and table for **Data Analytics & Components**. Starter (0–10) is from last class. Second half is Comparison: IoT vs AI vs Data Analytics.

On the board: Data Analytics is the process of collecting, organising, cleaning, studying and presenting data to find useful information.

Error clinic: Mistake: Skipping cleaning and going straight to analysis.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Data Analytics & Components**. Write: Data Analytics is the process of collecting, organising, cleaning, studying and presenting data to find useful information.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It helps people make better decisions. (2) Data means raw facts and figures (for example, "72, 45, 88"). — + example.

5 marks: 3-mark structure + table: Roll No / Name / Marks (raw) + the worked example from this topic.

LEARN IT

Data Analytics is the process of **collecting, organising, cleaning, studying and presenting data** to find useful information. It helps people make better decisions.

Data means raw facts and figures (for example, "72, 45, 88"). **Information** is data that has been processed so it has meaning ("Ali scored 72%; he passed"). Data Analytics is the bridge from data to information.

Source example: A college collects exam marks, calculates percentages, and identifies which students need extra help. This entire process is Data Analytics.

Components of Data Analytics

Data Analytics comprises **five key components**, which happen in order like a pipeline:

1. Collection → 2. Storage → 3. Cleaning → 4. Analysis → 5. Visualization

- 1. Data Collection** — Gathering raw information from multiple sources: websites, surveys, sensors, hospital records, bank transactions.
- 2. Data Storage** — Storing data safely and properly after collection. It can be stored in files, databases, spreadsheets or the cloud.
- 3. Data Cleaning** — Identifying and correcting errors in data. Raw data may contain:
 - **Duplication** of records (the same student entered twice),
 - **Incorrect values** (typos, e.g. marks "870" instead of "87"),
 - **Missing** files or records (a student's marks not entered),
 - **Improper formats** (dates written as 05/10/2026 in one place and "5 Oct 26" in another).
- 4. Data Analysis** — Studying the clean data to identify patterns, trends and relevant information for problem-solving (e.g. finding out which subjects students failed the most).
- 5. Data Visualization** — Creating visual representations of data (plots, charts, graphs) to provide valuable insights at a glance (e.g. a pie chart showing pass vs fail percentage).

WORKED EXAMPLE

A college in Sukkur analyses Physics test results (out of 50) for 6 students.

Step 1 — Collection: Marks are gathered from the teacher's register.

Roll No	Name	Marks (raw)
1	Ayesha	42
2	Bilal	18
3	Hina	35
3	Hina	35
4	Kashif	250
5	Sana	(missing)

Step 2 — Storage: The marks are typed into a spreadsheet saved on Google Drive (cloud).

Step 3 — Cleaning: Hina's record is a *duplicate* → delete one copy. Kashif's 250 is an *incorrect value* (more than 50) → the register shows 25, so correct it. Sana's marks are *missing* → ask the teacher; she was absent, so mark her "absent".

Step 4 — Analysis: Clean marks: 42, 18, 35, 25. Pass mark is 17 (33% of 50 = 16.5, rounded up). All 4 passed. Percentages: Ayesha 84%, Bilal 36%, Hina 70%, Kashif 50%. Average = $(42 + 18 + 35 + 25) \div 4 = 120 \div 4 = 30$ marks = 60%. Bilal is closest to failing → needs extra help.

Step 5 — Visualization: A bar chart shows each student's percentage; Bilal's short bar makes the problem visible at a glance.

REMEMBER IT

"Cows Sit Calmly And Vote" — Collection, Storage, Cleaning, Analysis, Visualization. Or think of cooking daal: buy the lentils (collect), keep them in a jar (store), pick out stones (clean), cook (analyse), serve beautifully on a plate (visualise).

COMMON MISTAKE

Mistake: Skipping cleaning and going straight to analysis. **Fix:** Dirty data gives wrong answers. In the example, Kashif's wrong "250" would have made the average $(42 + 18 + 35 + 250) \div 4 = 86.25$ — more than 50, which is impossible. Always clean first.

اردو میں سمجھیں

ڈیٹا اینالٹکس ڈیٹا کو جمع کرنے، ترتیب دینے، صاف کرنے، اس کا مطالعہ کرنے اور پیش کرنے کا عمل ہے تاکہ مفید معلومات حاصل ہوں اور بہتر فیصلے کیے جا سکیں۔ اس کے پانچ اجزاء ہیں: ڈیٹا جمع کرنا، محفوظ کرنا، صاف کرنا (غلطیاں اور دہرائے گئے ریکارڈ ہٹانا)، تجزیہ کرنا، اور چارٹ یا گراف کی صورت میں دکھانا۔

CHECK YOURSELF

1. List the five components of Data Analytics in order.
2. Name four kinds of errors removed during data cleaning.
3. A pie chart of pass/fail percentage belongs to which component?

Answers: 1. Collection, Storage, Cleaning, Analysis, Visualization. 2. Duplicate records, incorrect values (typos), missing records, improper formats. 3. Data Visualization.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. List the five components of Data Analytics in order.

3 marks. Explain Data Analytics & Components with two clear points and one example.

5 marks. Write a 5-mark answer on Data Analytics & Components: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Collection, Storage, Cleaning, Analysis, Visualization 3. It helps people make better decisions.; Data means raw facts and figures (for example, "72, 45, 88"). 5. Use the recipe in the blue box. Model opening: Data Analytics is the process of collecting, organising, cleaning, studying and presenting data to find useful information.

BATCH HOMEWORK

Write a 5-mark answer on **Data Analytics & Components** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Comparison: IoT vs AI vs Data Analytics

ACADEMY SESSION

Session 4 of 10 · 45 minutes (second half) · paired with Data Analytics & Components.

45–75 min — this topic. Board working for **Comparison: IoT vs AI vs Data Analytics**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: These three technologies are often used together, so students mix them up.

Error clinic: Mistake: Writing that IoT "makes decisions".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Comparison: IoT vs AI vs Data Analytics**. Write: These three technologies are often used together, so students mix them up.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) These three technologies are often used together, so students mix them up. (2) The table below, from the source, compares them on four aspects. — + example.

5 marks: 3-mark structure + table: Aspect / IoT / Artificial Intelligence (AI) / Data Analytics + the worked example from this topic.

LEARN IT

These three technologies are often used together, so students mix them up. The table below, from the source, compares them on four aspects.

Aspect	IoT	Artificial Intelligence (AI)	Data Analytics
Definition	Network of physical devices connected to the internet.	Technology enabling machines to think and decide.	Process of examining data to find patterns.
Main purpose	Data collection and automation.	Intelligent decision making and predictions.	Extracting meaningful insights.
Type of work	Works with physical devices (hardware).	Works with smart software systems.	Works with data (numbers, records).
Output	Raw data from the environment.	Smart decisions or actions.	Reports, graphs, insights.
Role in a smart system	Eyes and hands	Brain	Organiser / reporter
Pakistani example	Safe City cameras in Lahore/Karachi capturing traffic	Software recognising a car's number plate for an e-challan	Monthly report showing which roads have the most violations

WORKED EXAMPLE

One problem, three technologies — a K-Electric smart meter:

IoT: The smart electricity meter measures units used every 15 minutes and sends them over the mobile network. Output: raw readings.

Data Analytics: The company cleans and studies a month of readings and draws a graph showing that most electricity is used between 7 pm and 11 pm. Output: report/graph.

AI: Software learns each area's pattern, predicts tomorrow's demand, and decides how to plan load management. Output: smart decision.

REMEMBER IT

Ask "What is the output?" Raw readings → IoT. Charts and reports → Data Analytics. A decision or prediction → AI.

COMMON MISTAKE

Mistake: Writing that IoT "makes decisions". **Fix:** In the comparison table IoT's main purpose is *data collection and automation*; the *intelligent decision* belongs to AI.

اردو میں سمجھیں

IoT جسمانی آلات (ہارڈویئر) کا نیٹ ورک ہے جو ماحول سے خام ڈیٹا جمع کرتا ہے۔ AI ذہین سافٹ ویئر ہے جو فیصلے اور پیش گوئیاں کرتا ہے۔ ڈیٹا اینالٹکس ڈیٹا کا جائزہ لے کر رپورٹس اور گراف بناتا ہے۔ تینوں مل کر ایک اسمارٹ نظام بناتے ہیں۔

CHECK YOURSELF

1. Which of the three works mainly with hardware?

2. What is the output of Data Analytics?

Answers: 1. IoT. 2. Reports, graphs and insights.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which of the three works mainly with hardware?

3 marks. Explain Comparison: IoT vs AI vs Data Analytics with two clear points and one example.

5 marks. Write a 5-mark answer on Comparison: IoT vs AI vs Data Analytics: definition, two points, a labelled diagram or table, and one example.

Answers: 1. IoT 3. These three technologies are often used together, so students mix them up.; The table below, from the source, compares them on four aspects. 5. Use the recipe in the blue box. Model opening: These three technologies are often used together, so students mix them up.

BATCH HOMEWORK

Write a 5-mark answer on **Comparison: IoT vs AI vs Data Analytics** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.2 Uses of IoT in Different Areas

ACADEMY SESSION

Session 5 of 10 · 45 minutes (first half) · paired with Scope of AI in Education in Pakistan.

10–45 min — this topic. Lock the definition and table for **Uses of IoT in Different Areas**. Starter (0–10) is from last class. Second half is Scope of AI in Education in Pakistan.

On the board: IoT improves efficiency (doing more with less effort), saves time, and enhances the overall quality of life.

Error clinic: Mistake: Giving only the name of the area ("smart cities") in an exam answer.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Uses of IoT in Different Areas**. Write: IoT improves efficiency (doing more with less effort), saves time, and enhances the overall quality of life.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It plays a significant role in developing modern infrastructure (the basic systems of a country — roads, power, water, hospitals). (2) The source lists six areas. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

IoT **improves efficiency** (doing more with less effort), **saves time**, and **enhances the overall quality of life**. It plays a significant role in developing modern **infrastructure** (the basic systems of a country — roads, power, water, hospitals). The source lists six areas.

1. Smart Cities

- **Traffic management:** Sensors adjust traffic signals automatically to reduce congestion (crowding). Example: signals on a busy Karachi road stay green longer for the direction with more cars.
- **Street lighting:** Lights turn ON/OFF based on daylight or movement, saving electricity.
- **Parking:** Sensors guide drivers to empty parking spaces, e.g. in a large shopping mall car park.
- **Waste management:** Smart bins send alerts when full, so trucks collect only full bins instead of driving to every bin.

2. Industrial Automation

- Sensors check machine **temperature and vibration** to prevent breakdowns (called predictive maintenance).
- Automated machines perform repeated tasks precisely.
- Quality-control sensors check products during manufacturing — for example, in the **textile industries of Sindh**, cameras and sensors spot faults in cloth as it is woven.

3. Healthcare (Smart Health)

- **Smartwatches** continuously measure heart rate and vital signs (pulse, oxygen level).
- **Remote monitoring devices** send patient data directly to doctors — vital for **rural areas of Pakistan**, where a specialist may be hundreds of kilometres away (e.g. a heart patient in Tharparkar monitored by a doctor in Karachi).
- **Emergency alert devices** inform hospitals instantly, for example when an elderly person falls.

4. Education (Smart Learning)

- **Smart classrooms:** digital boards and connected projectors.
- **Attendance systems:** biometric automated attendance for students and teachers (used in many Sindh government schools and colleges).
- **Resource management:** automated classroom lighting and AC control — off when the room is empty.

5. Home Automation


- **Smart lighting:** controlled remotely via mobile apps.
- **Security:** real-time monitoring via Wi-Fi cameras — you can watch your house gate on your phone.
- **Voice control:** using assistants (like Alexa or Google Assistant) to control TVs and appliances.

6. Smart Farming

Smart farming is **crucial for agriculture in Pakistan** (especially Sindh and Punjab) to **save water** and **improve yields** (the amount of crop produced).

- **Soil moisture sensors:** check if crops actually need water.
- **Automated irrigation:** turns water pumps ON/OFF based on soil data.
- **Drones:** monitor crop health from above, spotting disease or dry patches.

Smart farming process:



WORKED EXAMPLE

A cotton farmer near Nawabshah uses smart irrigation:

Step 1. A soil moisture sensor in the field reads 18% moisture.

Step 2. It sends the reading over the 4G network to a cloud service.

Step 3. The cloud AI checks: cotton needs at least 25% moisture, and the weather forecast shows no rain → decision "Needs water: YES".

Step 4. The actuator (pump switch) turns the tube-well ON.

Step 5. When moisture reaches 30%, the AI decides "enough" and the pump turns OFF.

Result: water is used only when needed — important because Sindh faces water shortages — and the farmer sees everything on his phone app.

REMEMBER IT

Remember the six areas with **"CHIEF H"**: **C**ities, **H**ealth, **I**ndustry, **E**ducation, **F**arming, **H**omes.

COMMON MISTAKE

Mistake: Giving only the name of the area ("smart cities") in an exam answer. **Fix:** Always add *what* IoT does there — e.g. "smart bins send alerts when full" — and, if possible, a Pakistani example.

IoT کارکردگی بہتر بناتا ہے، وقت بچاتا ہے اور زندگی کا معیار بلند کرتا ہے۔ اسمارٹ شہروں میں ٹریفک سگنل اور اسٹریٹ لائٹس خود کار ہوتی ہیں، اسپتالوں میں مریضوں کا ڈیٹا براہ راست ڈاکٹر تک پہنچتا ہے، اور کھیتوں میں مٹی کی نمی کے سینسر بتاتے ہیں کہ فصل کو پانی چاہیے یا نہیں، جس سے سندھ اور پنجاب میں پانی کی بچت ہوتی ہے۔

CHECK YOURSELF

1. How do smart bins help waste management?
2. Why is remote health monitoring especially useful in Pakistan?
3. In smart farming, which device is the actuator?

Answers: 1. They send alerts when full, so only full bins are emptied. 2. Rural areas lack doctors; devices send patient data directly to doctors far away. 3. The water pump (its switch).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. How do smart bins help waste management?

3 marks. Explain Uses of IoT in Different Areas with two clear points and one example.

5 marks. Write a 5-mark answer on Uses of IoT in Different Areas: definition, two points, a labelled diagram or table, and one example.

Answers: 1. They send alerts when full, so only full bins are emptied. 3. It plays a significant role in developing modern infrastructure (the basic systems of a country — roads, power, water, hospitals).; The source lists six areas. 5. Use the recipe in the blue box. Model opening: IoT improves efficiency (doing more with less effort), saves time, and enhances the overall quality of life.

BATCH HOMEWORK

Write a 5-mark answer on **Uses of IoT in Different Areas** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.2.1 Scope of AI in Education in Pakistan

ACADEMY SESSION

Session 5 of 10 · 45 minutes (second half) · paired with Uses of IoT in Different Areas.

45–75 min — this topic. Board working for **Scope of AI in Education in Pakistan**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Artificial Intelligence is gradually becoming an important part of Pakistan's education system, improving teaching, learning and administration (managing the school: admissions, records, timetables).

Error clinic: Mistake: Writing that AI will replace teachers.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Scope of AI in Education in Pakistan**. Write: Artificial Intelligence is gradually becoming an important part of Pakistan's education system, improving teaching, learning and administration (managing the school: admissions, records, timetables).

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Automated grading and digital testing — MCQ tests marked instantly by computer. (2) AI-based career counselling — software that studies a student's marks and interests and suggests suitable fields. — + example.

5 marks: 3-mark structure + table: Practical uses / Benefits / Challenges + the worked example from this topic.

LEARN IT

Artificial Intelligence is gradually becoming an important part of Pakistan's education system, improving **teaching, learning** and **administration** (managing the school: admissions, records, timetables).

Practical uses:

- **Learning Management Systems (LMS)** — online platforms (e.g. Google Classroom, Moodle) where teachers post lessons and assignments; AI features can recommend lessons to each student.
- **Automated grading and digital testing** — MCQ tests marked instantly by computer.
- **AI-based career counselling** — software that studies a student's marks and interests and suggests suitable fields.

Benefits:

- Helps students learn **at their own speed**.
- **Identifies students who need extra help**.
- Supports students with disabilities (**Assistive AI**), e.g. text-to-speech for a visually impaired student.

Major challenges in Pakistan:

- Limited **internet access in rural areas**.
- Lack of **computers and digital devices** for all students.
- Need for proper **teacher training** to use AI tools.
- **Data privacy and security** issues — students' personal data must be protected.

Practical uses	Benefits	Challenges
LMS	Learn at own speed	Limited rural internet
Automated grading & digital testing	Identifies students needing help	Lack of computers/devices
AI career counselling	Supports students with disabilities	Teacher training needed
—	—	Data privacy & security

WORKED EXAMPLE

Scenario — Fatima in Larkana and an AI tutor app:

Step 1. Fatima takes a 10-question online maths quiz on the college LMS. It is graded instantly (automated grading).

Step 2. The AI notices she got all 3 trigonometry questions wrong.

Step 3. It recommends two short videos and five easy practice questions on trigonometry — she learns at her own speed.

Step 4. Her teacher's dashboard flags "Fatima – needs help in trigonometry" (identifies students who need help).

Challenge: At home Fatima's village has weak 3G signals, so the videos buffer — showing the rural internet challenge.

COMMON MISTAKE

Mistake: Writing that AI will replace teachers. **Fix:** The source says AI *improves* teaching and needs *teacher training* — teachers use AI as a tool; they are not replaced.

اردو میں سمجھیں

پاکستان کے تعلیمی نظام میں مصنوعی ذہانت آہستہ آہستہ اہم کردار ادا کر رہی ہے، جیسے لرننگ مینجمنٹ سسٹم (LMS)، خودکار جانچ اور کیریئر کونسلنگ۔ اس سے طلبہ اپنی رفتار سے سیکھ سکتے ہیں اور کمزور طلبہ کی نشاندہی ہوتی ہے۔ لیکن دیہی علاقوں میں انٹرنیٹ کی کمی، کمپیوٹرز کی قلت، اساتذہ کی تربیت اور ڈیٹا کی حفاظت بڑے چیلنج ہیں۔

CHECK YOURSELF

1. Give three practical uses of AI in education.
2. State any two challenges of AI in education in Pakistan.

Answers: 1. LMS, automated grading and digital testing, AI-based career counselling. 2. Any two: limited rural internet, lack of devices, need for teacher training, data privacy and security.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Give three practical uses of AI in education.

3 marks. Explain Scope of AI in Education in Pakistan with two clear points and one example.

5 marks. Write a 5-mark answer on Scope of AI in Education in Pakistan: definition, two points, a labelled diagram or table, and one example.

Answers: 1. LMS, automated grading and digital testing, AI-based career counselling 3. Automated grading and digital testing — MCQ tests marked instantly by computer.; AI-based career counselling — software that studies a student's marks and interests and suggests suitable fields. 5. Use the recipe in the blue box. Model opening: Artificial Intelligence is gradually becoming an important part of Pakistan's education system, improving teaching, learning and administration (managing the...

BATCH HOMEWORK

Write a 5-mark answer on **Scope of AI in Education in Pakistan** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.2.2 Career Connection in IoT and AI

ACADEMY SESSION

Session 6 of 10 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Learning computing skills opens doors to many employers in Pakistan: software houses (e.g.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Career Connection in IoT and AI**. Write: Learning computing skills opens doors to many employers in Pakistan: software houses (e.g.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Data Analyst: analyses the data generated by IoT systems and produces reports. (2) Programming — Python, C++. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Learning computing skills opens doors to many employers in Pakistan: **software houses** (e.g. in Karachi, Lahore and Islamabad technology parks), **telecom companies** (Jazz, Telenor), **banks**, and **government IT departments** (e.g. NADRA, provincial IT boards).

- **IoT Engineer:** designs smart systems and connected devices (e.g. a smart irrigation kit).
- **Data Analyst:** analyses the data generated by IoT systems and produces reports.

Key skills needed:

- **Programming** — Python, C++.
- **Networking** — Wi-Fi, protocols (rules for how devices communicate).
- **Electronics** — sensors and circuits.
- **Problem-solving.**

REMEMBER IT

Skills = **"PNEP"**: Programming, Networking, Electronics, Problem-solving. You start building the first one this year when you learn Python!

اردو میں سمجھیں

کمپیوٹنگ کی مہارتیں سیکھ کر آپ سافٹ ویئر ہاؤسز، ٹیلی کام کمپنیوں (جیسے جاز، ٹیلی نار)، بینکوں اور سرکاری آئی ٹی محکموں میں کام کر سکتے ہیں۔ IoT انجینئر اسمارٹ آلات بناتا ہے اور ڈیٹا اینالسٹ ان سے پیدا ہونے والے ڈیٹا کا تجزیہ کرتا ہے۔ اس کے لیے پروگرامنگ، نیٹ ورکنگ، الیکٹرانکس اور مسئلہ حل کرنے کی صلاحیت ضروری ہے۔

CHECK YOURSELF

1. What does an IoT Engineer do?
2. Name the four key skills for IoT/AI careers.

Answers: 1. Designs smart systems and connected devices. 2. Programming (Python, C++), networking, electronics, problem-solving.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does an IoT Engineer do?

3 marks. Explain Career Connection in IoT and AI with two clear points and one example.

5 marks. Write a 5-mark answer on Career Connection in IoT and AI: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Designs smart systems and connected devices 3. Data Analyst: analyses the data generated by IoT systems and produces reports.; Programming — Python, C++. 5. Use the recipe in the blue box. Model opening: Learning computing skills opens doors to many employers in Pakistan: software houses (e.g.

BATCH HOMEWORK

Write a 5-mark answer on **Career Connection in IoT and AI** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.3 Information Sources (Primary, Secondary, Tertiary) ★ Golden

ACADEMY SESSION

Session 7 of 10 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Information sources are ways to find knowledge and data.

Error clinic: Mistake: Thinking "primary" means "most important" or "tertiary" means "useless".

Exam wording to train: Typical questions: "Differentiate between primary, secondary and tertiary sources with two examples each" (long/short), "Classify the following sources..."...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Information Sources (Primary, Secondary, Tertiary)**. Write: Information sources are ways to find knowledge and data.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The internet has vast information, but not all of it is accurate. (2) Sources are divided into three main categories. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a four-row comparison table and one rewritten survey question + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Information sources are ways to find knowledge and data. The internet has vast information, but **not all of it is accurate**. Sources are divided into three main categories.

1. Primary sources give **original, firsthand information** straight from people, events or official records. They are **highly authentic** (genuine).


Examples: interviews, photographs, diaries, NADRA official records.

2. Secondary sources contain information that has **already been collected and explained by someone else**. They **summarise or analyse primary data**.

Examples: textbooks, news reports, research papers, Pakistan Bureau of Statistics reports.

3. Tertiary sources provide **highly summarised and organised information** derived from both primary and secondary sources. They are used for **quick reference**.

Examples: encyclopedias, Wikipedia, dictionaries, handbooks.



The information pyramid: primary data is the base; each higher level is built from the levels below it and is more summarised.

Many examples, sorted

Primary (firsthand)	Secondary (explained by others)	Tertiary (summarised, quick reference)
Interview with a flood victim in Dadu	Newspaper report on the 2022 floods	Encyclopedia entry "Floods in Pakistan"
Photograph taken at an event	Textbook chapter explaining the event	Wikipedia article
Personal diary or letter	Biography written by a historian	Dictionary
NADRA official records (CNIC data)	Pakistan Bureau of Statistics report analysing census data	Handbook / almanac of facts
Original survey responses	Research paper analysing the survey	Index or list of research papers
Sensor readings from an IoT weather station	TV news analysis of the weather	A school "fact sheet" on climate
Quaid-e-Azam's original speech recording	Article discussing the speech	Encyclopedia summary of his life

When do sources become unreliable?

In the digital age you must check facts carefully. A source is **unreliable** (cannot be trusted) if:

Source type	Reasons for unreliability
Primary	Information is incomplete, data is recorded incorrectly, or false information was deliberately provided.
Secondary	The information is outdated, lacks proper references/citations, or has not been verified by an expert.
Tertiary	Comes from an unknown/unverified website, or the information is oversimplified and misses key facts.

REMEMBER IT

Rule of thumb (Author – Date – References): If an online article does not state the **author's name**, the **date of publication**, or list its **references**, it should not be trusted for academic work. Remember "**ADR**" — like checking a bus has a driver, a route and a ticket before you board.

WORKED EXAMPLE

Classify these — worked solutions:

(a) **Your grandfather's handwritten diary from 1947.** Written by a person who lived through the event → firsthand → **Primary**.

(b) **A Dawn newspaper article analysing the budget.** A journalist collected facts and explained them → **Secondary**.

(c) **An Oxford English–Urdu dictionary.** Organised, summarised reference built from many sources → **Tertiary**.

(d) **A Bureau of Statistics report on literacy in Sindh.** It analyses census (primary) data → **Secondary**.

(e) **A photo you took of a road accident.** Original record of the event → **Primary**.

Method: Ask (1) "Was the creator *there* / is it the original record?" → Primary. (2) "Is someone *explaining or analysing* original data?" → Secondary. (3) "Is it a *quick-reference summary* of many sources?" → Tertiary.

CHECK YOURSELF

Exercise — classify these as Primary (P), Secondary (S) or Tertiary (T):

1. A video interview with a cricketer after a match.
2. Your Computer Science textbook.
3. Wikipedia page on "Mohenjo-daro".
4. A birth certificate issued by the union council.
5. A research paper reviewing ten studies on smog in Lahore.
6. A handbook of physics formulas.
7. Original exam answer sheets of students.
8. A TV news report summarising a court decision.

Answers: 1. P 2. S 3. T 4. P 5. S 6. T 7. P 8. S

COMMON MISTAKE

Mistake: Thinking "primary" means "most important" or "tertiary" means "useless". **Fix:** The names describe *how far the information is from the original event*. Primary = straight from the source; tertiary = summarised summary. Each is useful for a different job. Also, Wikipedia is **tertiary** — not primary — because it summarises other sources.

اردو میں سمجھیں

معلومات کے ذرائع علم اور ڈیٹا تلاش کرنے کے طریقے ہیں، جنہیں تین اقسام میں تقسیم کیا جاتا ہے۔ پرائمری ذرائع براہ راست اور اصل معلومات دیتے ہیں (جیسے انٹرویو، تصاویر، نادرا کا ریکارڈ)۔ سیکنڈری ذرائع وہ ہیں جن میں کسی اور نے پرائمری معلومات کی وضاحت یا تجزیہ کیا ہو (جیسے درسی کتابیں، خبریں)۔ ٹرشییری ذرائع خلاصہ شدہ معلومات دیتے ہیں جیسے انسائیکلوپیڈیا، وکی پیڈیا اور لغت۔ جس آن لائن مضمون میں مصنف کا نام، تاریخ یا حوالہ جات نہ ہوں اس پر بھروسہ نہ کریں۔

EXAM TIP

Typical questions: "Differentiate between primary, secondary and tertiary sources with two examples each" (long/short), "Classify the following sources..." (MCQ/short), and "When does a source become unreliable?"

Write the definition key phrase for each — *firsthand/original, collected and explained by someone else, highly summarised for quick reference* — plus two examples each. Draw the pyramid with primary at the base. For unreliability, give one reason for each type and quote the author–date–references rule.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. A video interview with a cricketer after a match.

3 marks. Explain Information Sources (Primary, Secondary, Tertiary) with two clear points and one example.

5 marks. Typical questions: "Differentiate between primary, secondary and tertiary sources with two examples each" (long/short), "Classify the following sources..." (MCQ/short), and "When does a source become..."

8 marks. Information Sources (Primary, Secondary, Tertiary): 5-mark answer plus a four-row comparison table and one rewritten survey question.

Answers: 1. P 3. The internet has vast information, but not all of it is accurate.; Sources are divided into three main categories. 5. Use the recipe in the blue box. Model opening: Information sources are ways to find knowledge and data. 8. Same 5-mark body + a four-row comparison table and one rewritten survey question + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Information Sources (Primary, Secondary, Tertiary)** using the recipe in this topic. Include a four-row comparison table and one rewritten survey question. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.4 Impacts of Computing in Various Fields

ACADEMY SESSION

Session 8 of 10 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Computing has drastically changed society.

Error clinic: Mistake: Writing only positive impacts in a "discuss the impacts" question.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Impacts of Computing in Various Fields**. Write: Computing has drastically changed society.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It makes life faster and more connected, but it also brings challenges like privacy risks and technology addiction. (2) For every field, think of both sides. — + example.

5 marks: 3-mark structure + table: Field / Positive impact (+) / Negative impact (–) + the worked example from this topic.

LEARN IT

Computing has drastically changed society. It makes life **faster and more connected**, but it also brings challenges like **privacy risks** and **technology addiction**. For every field, think of both sides.

Field	Positive impact (+)	Negative impact (–)
Education	Online classes, e-books and learning apps make studying highly flexible and accessible.	Excessive screen time reduces attention spans and causes physical health issues (eye strain, back pain).
Communication	Emails and video calls allow instant, global communication at almost zero cost (e.g. a WhatsApp video call to a relative in Dubai).	People interact less in person, leading to social isolation and reduced face-to-face skills.
Business	Online shopping, digital banking and automation dramatically improve speed and efficiency.	Traditional manual jobs are lost to machines; risk of severe cyber-attacks on banks.
Healthcare	Digital patient records and telemedicine allow doctors to treat remote patients accurately.	Patient data privacy is at risk if hospital servers are hacked.
Agriculture	Smart irrigation and weather forecasting massively increase crop yields.	Poor internet access in rural areas means many farmers cannot use these tools.

Smart and responsible use

- **Protect personal information** and use **strong passwords** (long, with letters, numbers and symbols; never share your OTP or CNIC details with callers).
- **Do not share fake news** or unverified WhatsApp forwards.
- **Balance screen time** with physical sports and activities.

WORKED EXAMPLE

Scenario analysis — a bank in Karachi moves to mobile banking:

Step 1 — Identify the field: Business (banking).

Step 2 — Positive: Customers transfer money in seconds from home; no queue at the branch; the bank processes more transactions with fewer staff (speed and efficiency).

Step 3 — Negative: Some cashier jobs are no longer needed (job loss); hackers may attempt cyber-attacks or phishing SMS to steal accounts.

Step 4 — Responsible use: Customers should use strong passwords, never share OTPs, and report suspicious messages.

REMEMBER IT

For the five fields, remember **"E-C-B-H-A"** — **E**ducation, **C**ommunication, **B**usiness, **H**ealthcare, **A**griculture — and always write one + and one – for each.

COMMON MISTAKE

Mistake: Writing only positive impacts in a "discuss the impacts" question. **Fix:** "Impact" means *both* sides. Examiners expect a balanced answer: advantages, disadvantages, and how to use technology responsibly.

کمپیوٹنگ نے معاشرے کو بہت بدل دیا ہے۔ تعلیم، مواصلات، کاروبار، صحت اور زراعت میں اس نے کام تیز اور آسان بنائے ہیں، لیکن اس کے ساتھ اسکرین کی لت، سماجی تنہائی، ملازمتوں کا خاتمہ، بیکنگ اور پرائیویسی کے خطرات بھی پیدا ہوئے ہیں۔ ذمہ دارانہ استعمال کے لیے مضبوط پاس ورڈ رکھیں، جعلی خبریں نہ پھیلائیں، اور کھیل کود کے ساتھ اسکرین ٹائم میں توازن رکھیں۔

CHECK YOURSELF

1. Give one positive and one negative impact of computing in healthcare.
2. Why can't many farmers in Pakistan benefit from smart agriculture tools?
3. State three rules of smart and responsible use.

Answers: 1. + Digital records and telemedicine help treat remote patients; – patient data privacy is at risk if servers are hacked. 2. Poor internet access in rural areas. 3. Protect personal information/use strong passwords; do not share fake news; balance screen time with physical activity.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Give one positive and one negative impact of computing in healthcare.

3 marks. Explain Impacts of Computing in Various Fields with two clear points and one example.

5 marks. Write a 5-mark answer on Impacts of Computing in Various Fields: definition, two points, a labelled diagram or table, and one example.

Answers: 1. + Digital records and telemedicine help treat remote patients; – patient data privacy is at risk if servers are hacked. 3. It makes life faster and more connected, but it also brings challenges like privacy risks and technology addiction.; For every field, think of both sides. 5. Use the recipe in the blue box. Model opening: Computing has drastically changed society.

BATCH HOMEWORK

Write a 5-mark answer on **Impacts of Computing in Various Fields** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.5 Assistive Technologies ★ Golden

ACADEMY SESSION

Session 9 of 10 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Assistive technologies are devices, software and systems that help people with disabilities or functional limitations (difficulty in seeing, hearing, moving, speaking, remembering, etc.).

Error clinic: Mistake: Putting text-to-speech and screen readers in the same category every time.

Exam wording to train: Expect: "What are assistive technologies?"

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Assistive Technologies**. Write: Assistive technologies are devices, software and systems that help people with disabilities or functional limitations (difficulty in seeing, hearing, moving, speaking, remembering, etc.).

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) They allow more people to participate equally in school, work and society. (2) There are four categories: — + example.

5 marks: 3-mark structure + table: Category / Purpose / Examples + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Assistive technologies are **devices, software and systems** that help people with **disabilities or functional limitations** (difficulty in seeing, hearing, moving, speaking, remembering, etc.). They allow more people to **participate equally** in school, work and society.

There are **four categories**:

Category	Purpose	Examples
1. Mobility aids	Help people move from one place to another.	Smart wheelchairs, stair lifts
2. Sensory aids	Support vision and hearing to improve interaction.	Hearing aids, screen readers (VoiceOver), Braille displays
3. Communication aids	Assist individuals with speech difficulties to express themselves.	Speech-generating devices, text-to-speech apps
4. Cognitive / learning aids	Help people with memory, reading and understanding.	Audiobooks, spell-checkers, digital reminder apps

Mobility · Sensory · Communication · Cognitive

- A **screen reader** is software that reads aloud the text on a screen, so a blind person can use a phone or computer. **VoiceOver** is Apple's screen reader; Android has TalkBack.
- A **Braille display** is a device with small pins that rise and fall to form Braille dots, so a blind user can read screen text with their fingers.
- A **speech-generating device** speaks out words that a person types or selects on a screen.
- A **smart wheelchair** can be controlled by a joystick, voice or head movement and may avoid obstacles with sensors.

WORKED EXAMPLE

Scenario — choose the right assistive technology:

(a) Ahmed, a student in Hyderabad, is blind and wants to read his e-textbook. → **Sensory aid**: a screen reader or Braille display.

(b) Mrs Rashida cannot climb the stairs of her house after a knee operation. → **Mobility aid**: stair lift (or smart wheelchair).

(c) Zain cannot speak clearly due to a medical condition but can type. → **Communication aid**: text-to-speech app or speech-generating device.

(d) Nani often forgets to take her medicine. → **Cognitive aid**: digital reminder app.

(e) Usman has dyslexia (difficulty reading). → **Cognitive/learning aid**: audiobooks and spell-checkers.

Method: identify the *limitation* (moving, seeing/hearing, speaking, memory/reading) → choose the matching category.

REMEMBER IT

Four categories = "**My Small Cat Cries**": **M**obility, **S**ensory, **C**ommunication, **C**ognitive. Link each to a body function: *legs* (mobility), *eyes/ears* (sensory), *mouth* (communication), *mind* (cognitive).

COMMON MISTAKE

Mistake: Putting text-to-speech and screen readers in the same category every time. **Fix:** In the source, the **screen reader** is a *sensory aid* (supports vision), while a **text-to-speech app** is listed as a *communication aid* (helps a person with speech difficulty express themselves). Decide by *whose problem* it solves.

اردو میں سمجھیں

معاون ٹیکنالوجیز (Assistive Technologies) وہ آلات، سافٹ ویئر اور نظام ہیں جو معذور افراد کی مدد کرتے ہیں تاکہ وہ اسکول، کام اور معاشرے میں برابر حصہ لے سکیں۔ ان کی چار اقسام ہیں: نقل و حرکت میں مدد (اسمارٹ ویبل چیئر)، حسی مدد (سماعتی آلہ، اسکرین ریڈر، بریل ڈسپلے)، گفتگو میں مدد (اسپیج جنریٹنگ ڈیوائس) اور ذہنی و تعلیمی مدد (آڈیو بکس، اسپیل چیکر، یاد دہانی ایپس)۔

EXAM TIP

Expect: "What are assistive technologies? Explain their categories with examples" (long), "Name two sensory aids" (short), or "A screen reader is an example of ___" (MCQ).

For full marks write the definition (devices, software and systems; help people with disabilities; equal participation), then all **four** categories each with purpose + two examples. Finish with one line on importance (equal access, independence, inclusion).

CHECK YOURSELF

1. Which category does a hearing aid belong to?
2. Give two examples of cognitive/learning aids.
3. Define assistive technologies in one sentence.

Answers: 1. Sensory aids. 2. Any two: audiobooks, spell-checkers, digital reminder apps. 3. Devices, software and systems that help people with disabilities or functional limitations participate equally in school, work and society.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which category does a hearing aid belong to?

3 marks. Explain Assistive Technologies with two clear points and one example.

5 marks. Expect: "What are assistive technologies? Explain their categories with examples" (long), "Name two sensory aids" (short), or "A screen reader is an example of ___" (MCQ). For full marks write the...

8 marks. Assistive Technologies: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. Sensory aids 3. They allow more people to participate equally in school, work and society.; There are four categories: 5. Use the recipe in the blue box. Model opening: Assistive technologies are devices, software and systems that help people with disabilities or functional limitations (difficulty in seeing, hearing, moving,... 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Assistive Technologies** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.5.1 Importance of Assistive Technologies

ACADEMY SESSION

Session 10 of 10 · 45 minutes (first half) · paired with Career Connection in Assistive Tech.

10–45 min — this topic. Lock the definition and table for **Importance of Assistive Technologies**. Starter (0–10) is from last class. Second half is Career Connection in Assistive Tech.

On the board: Assistive technologies are important for three main reasons: Equal access to education: Screen readers allow blind students to read digital textbooks equally with their peers (classmates).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Importance of Assistive Technologies**. Write: Assistive technologies are important for three main reasons: Equal access to education: Screen readers allow blind students to read digital textbooks equally with their peers (classmates).

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Independence in daily life: Mobility aids reduce the need for constant human assistance — a person in a smart wheelchair can go to the... (2) Social inclusion: They break down barriers, allowing individuals to work, study and socialise confidently. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Assistive technologies are important for three main reasons:

1. **Equal access to education:** Screen readers allow blind students to read digital textbooks equally with their peers (classmates).
2. **Independence in daily life:** Mobility aids reduce the need for constant human assistance — a person in a smart wheelchair can go to the market without someone pushing.
3. **Social inclusion:** They break down barriers, allowing individuals to work, study and socialise confidently.

Equal Access → Independence → Inclusion

WORKED EXAMPLE

How one tool changes a life: A visually impaired student in Karachi uses a screen reader on her laptop.

Equal access — she reads the same e-books as her class. **Independence** — she no longer needs someone to read to her. **Inclusion** — she joins the class WhatsApp group, takes online tests and later gets a job, contributing to society.

REMEMBER IT

Remember **"All"**: Access, Independence, Inclusion.

اردو میں سمجھیں

معاون ٹیکنالوجیز کی اہمیت تین باتوں میں ہے: تعلیم تک برابر رسائی (ناہینا طلبہ اسکرین ریڈر سے کتابیں پڑھ سکتے ہیں)، روزمرہ زندگی میں خود مختاری (کسی کی مسلسل مدد کی ضرورت کم ہوتی ہے)، اور سماجی شمولیت (لوگ اعتماد کے ساتھ پڑھ، کام اور میل جول کر سکتے ہیں)۔

CHECK YOURSELF

1. State three reasons why assistive technologies are important.

2. How do mobility aids support independence?

Answers: 1. Equal access to education, independence in daily life, social inclusion. 2. They reduce the need for constant human assistance.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. State three reasons why assistive technologies are important.

3 marks. Explain Importance of Assistive Technologies with two clear points and one example.

5 marks. Write a 5-mark answer on Importance of Assistive Technologies: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Equal access to education, independence in daily life, social inclusion 3. Independence in daily life: Mobility aids reduce the need for constant human assistance — a person in a smart wheelchair can go to the...; Social inclusion: They break down barriers, allowing individuals to work, study and socialise... 5. Use the recipe in the blue box. Model opening: Assistive technologies are important for three main reasons: Equal access to education: Screen readers allow blind students to read digital textbooks equally...

BATCH HOMEWORK

Write a 5-mark answer on **Importance of Assistive Technologies** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.5.2 Career Connection in Assistive Tech

ACADEMY SESSION

Session 10 of 10 · 45 minutes (second half) · paired with Importance of Assistive Technologies.

45–75 min — this topic. Board working for **Career Connection in Assistive Tech**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Designing assistive technology is a highly rewarding career path — you earn a living while improving people's lives.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Career Connection in Assistive Tech**. Write: Designing assistive technology is a highly rewarding career path — you earn a living while improving people's lives.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) CareerWhat they do Assistive Software DeveloperCreates tools such as speech-to-text software (e.g. Urdu voice typing for people who cannot use a keyboard). — + example.

5 marks: 3-mark structure + table: Career / What they do + the worked example from this topic.

LEARN IT

Designing assistive technology is a **highly rewarding career path** — you earn a living while improving people's lives.

Career	What they do
Assistive Software Developer	Creates tools such as speech-to-text software (e.g. Urdu voice typing for people who cannot use a keyboard).
Biomedical Engineer	Designs artificial limbs and hearing aids.
UX/UI Accessibility Expert	Ensures websites are easy to navigate for visually impaired users (e.g. adding text descriptions to images so screen readers can read them).

UX means *user experience* (how easy and pleasant a product is to use); **UI** means *user interface* (the screens and buttons you interact with). **Accessibility** means designing so that *everyone*, including people with disabilities, can use it.

اردو میں سمجھیں

معاون ٹیکنالوجی بنانا ایک قابلِ قدر پیشہ ہے۔ اسسٹو سافٹ ویئر ڈویلپر اسپیشل ٹو ٹیکسٹ جیسے ٹولز بناتا ہے، بائیو میڈیکل انجینئر مصنوعی اعضاء اور سماعتی آلات تیار کرتا ہے، اور UX/UI ایکسیسبیلٹی ماہر یقینی بناتا ہے کہ ویب سائٹس نابینا افراد کے لیے بھی آسانی سے استعمال ہو سکیں۔

CHECK YOURSELF

1. Who designs artificial limbs and hearing aids?

2. What does a UX/UI accessibility expert ensure?

Answers: 1. A biomedical engineer. 2. That websites are easy to navigate for visually impaired users.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Who designs artificial limbs and hearing aids?

3 marks. Explain Career Connection in Assistive Tech with two clear points and one example.

5 marks. Write a 5-mark answer on Career Connection in Assistive Tech: definition, two points, a labelled diagram or table, and one example.

Answers: 1. A biomedical engineer 3. CareerWhat they do Assistive Software DeveloperCreates tools such as speech-to-text software (e.g.; Urdu voice typing for people who cannot use a keyboard). 5. Use the recipe in the blue box. Model opening: Designing assistive technology is a highly rewarding career path — you earn a living while improving people's lives.

BATCH HOMEWORK

Write a 5-mark answer on **Career Connection in Assistive Tech** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Chapter 5 Review

Chapter summary

- Computing is vital in Pakistan's schools, hospitals, banks, farms and industries; it has both positive and negative impacts.
- **AI** is "artificial" (made by humans) and "intelligent" (does tasks needing thinking); it uses data to learn, recognise patterns and make decisions.
- In smart systems, IoT is the "eyes" that gather data, Analytics sorts it, and AI is the "brain" that decides the action.
- **IoT** is a system of physical devices connected to the internet that collect and share data to perform tasks automatically.
- The six IoT components are sensors (collect), actuators (act), connectivity, data processing, cloud computing and user interface.
- **Data Analytics** is a pipeline: collection → storage → cleaning → analysis → visualization.
- Data cleaning removes duplicates, incorrect values, missing records and improper formats.
- IoT outputs raw data (hardware); AI outputs smart decisions (software); Data Analytics outputs reports, graphs and insights (data).
- IoT is used in smart cities, industrial automation, healthcare, education, home automation and smart farming.
- Smart farming (soil sensor → cloud AI → water pump) saves water and improves yields in Sindh and Punjab.
- AI in Pakistani education: LMS, automated grading, career counselling; challenges are rural internet, lack of devices, teacher training and data privacy.
- IoT/AI careers (IoT engineer, data analyst) need programming, networking, electronics and problem-solving.
- Information sources: primary (firsthand/original), secondary (collected and explained by others), tertiary (summarised for quick reference).
- Do not trust an online article that lacks an author, a publication date or references.
- Computing helps education, communication, business, healthcare and agriculture but risks screen addiction, isolation, job loss, cyber-attacks and privacy loss.
- **Assistive technologies** — mobility, sensory, communication and cognitive aids — give equal access, independence and social inclusion to people with disabilities.

Key terms

Term	Meaning	اردو
Computing	Using computers and digital devices to store, process and share information.	کمپیوٹنگ
Artificial Intelligence (AI)	Human-made technology that lets machines think, learn and decide using data.	مصنوعی ذہانت
Internet of Things (IoT)	Physical devices connected to the internet that collect and share data to work automatically.	انٹرنیٹ آف تھنگز، اشیاء کا انٹرنیٹ
Sensor	Device that collects information from the physical world.	حساس آلہ (سینسر)
Actuator	Device that performs a physical action in response to a command.	عمل کار آلہ (ایکچوٹر)
Connectivity	The link (Wi-Fi, Bluetooth, ZigBee, 4G/5G) that lets devices send and receive data.	رابطہ کاری
Data processing	Changing raw data into useful information.	ڈیٹا کی پروسیسنگ
Cloud computing	Storing data and using services over the internet instead of local drives.	کلاؤڈ کمپیوٹنگ
User interface (UI)	The part that lets a user see information and give commands to a device.	صارف انٹرفیس
Data Analytics	Collecting, storing, cleaning, analysing and presenting data to find useful information.	ڈیٹا کا تجزیہ
Data cleaning	Finding and correcting errors such as duplicates and missing values.	ڈیٹا کی صفائی
Data visualization	Showing data as charts, plots or graphs.	ڈیٹا کی بصری پیشکش
Smart city	City using IoT for traffic, lighting, parking and waste.	اسمارٹ شہر
Smart farming	Using sensors, automated irrigation and drones in agriculture.	اسمارٹ کاشتکاری
Learning Management System (LMS)	Online platform for lessons, assignments and tests.	آن لائن تعلیمی نظام
Telemedicine	Treating patients remotely using computing and communication.	دور دراز علاج
Primary source	Original, firsthand information.	بنیادی ذریعہ

Term	Meaning	اردو
Secondary source	Information collected and explained by someone else.	ثانوی ذریعہ
Tertiary source	Highly summarised information for quick reference.	ثالثی ذریعہ
Reliability	How far a source can be trusted.	قابلِ اعتماد ہونا
Privacy	Keeping personal information safe from others.	رازداری
Cyber-attack	An attempt by hackers to damage or steal from computer systems.	سائبر حملہ
Assistive technology	Devices, software and systems that help people with disabilities.	معاون ٹیکنالوجی
Screen reader	Software that reads screen text aloud for blind users.	اسکرین ریڈر
Braille display	Device with raised pins showing text as Braille dots.	بریل ڈسپلے
Accessibility	Designing so everyone, including people with disabilities, can use a product.	رسائی پذیری

Practice: multiple choice

1. AI is called "artificial" because it:
 - a. runs only on electricity
 - b. is created by humans
 - c. is always wrong
 - d. works without data
2. Which of the following is an actuator?
 - a. Temperature sensor
 - b. Motion sensor
 - c. Water valve
 - d. Wi-Fi router
3. ZigBee is an example of which IoT component?
 - a. Connectivity
 - b. Sensor
 - c. User interface
 - d. Actuator
4. Google Drive and iCloud are examples of:
 - a. Sensors
 - b. Data cleaning
 - c. Actuators
 - d. Cloud computing
5. Removing duplicate student records belongs to which component of Data Analytics?
 - a. Data collection
 - b. Data storage
 - c. Data cleaning
 - d. Data visualization
6. A pie chart showing pass vs fail percentage is an example of:
 - a. Data collection
 - b. Data storage
 - c. Data cleaning
 - d. Data visualization
7. According to the comparison table, the output of IoT is:
 - a. Raw data from the environment
 - b. Smart decisions
 - c. Reports and graphs
 - d. Printed documents
8. In a smart system, AI acts as the:
 - a. eyes
 - b. brain
 - c. hands
 - d. wires
9. NADRA's official records are a:
 - a. tertiary source
 - b. secondary source
 - c. primary source
 - d. unreliable source
10. Wikipedia is classified as a:
 - a. primary source
 - b. tertiary source
 - c. secondary source
 - d. firsthand record
11. Smart bins that send alerts when full are a use of IoT in:
 - a. smart farming
 - b. healthcare
 - c. home automation
 - d. smart cities
12. A system in which a soil sensor tells the cloud AI to switch on a water pump is used in:
 - a. smart farming
 - b. industrial automation
 - c. smart classrooms
 - d. traffic management
13. A screen reader such as VoiceOver is a:
 - a. mobility aid
 - b. communication aid
 - c. sensory aid
 - d. cognitive aid
14. A speech-generating device is a:
 - a. mobility aid
 - b. cognitive aid
 - c. sensory aid
 - d. communication aid
15. An online article should NOT be trusted for academic work if it lacks:
 - a. colourful pictures
 - b. the author's name, publication date or references
 - c. a long title
 - d. advertisements

Practice: short questions

1. Define Artificial Intelligence and give two examples from daily life.
2. Define the Internet of Things (IoT) with one example.
3. Differentiate between a sensor and an actuator with two examples of each.
4. What is the role of cloud computing in an IoT system?
5. List the five components of Data Analytics. What kinds of errors are removed in data cleaning?
6. Give two uses of IoT in smart cities and two in healthcare.
7. State two benefits and two challenges of AI in education in Pakistan.
8. Differentiate between primary and secondary sources with two examples each.
9. When does a secondary source become unreliable?
10. Give one positive and one negative impact of computing on (a) communication and (b) business.

Practice: long / problem questions

1. Define IoT. Explain its six components with an example of each. Draw a diagram showing how they connect.
2. Compare IoT, AI and Data Analytics in a table (definition, purpose, type of work, output). Then explain, with an example, how the three work together in a smart system.
3. A college in Mirpurkhas wants to find out why many students are failing Mathematics. Explain how it would use each of the five components of Data Analytics to solve this problem.
4. Explain the three types of information sources with examples. Classify the following: (i) a school textbook, (ii) a photograph of an event, (iii) an encyclopedia, (iv) an interview, (v) a Bureau of Statistics report, (vi) a dictionary. When does each type become unreliable?
5. What are assistive technologies? Explain their four categories with examples, state their importance, and name two related careers.
6. "Computing has both positive and negative impacts on society." Discuss with reference to education, healthcare and agriculture, and suggest three rules for smart and responsible use.

Answer key

Multiple choice

1. b
2. c
3. a
4. d
5. c
6. d
7. a
8. b
9. c
10. b
11. d
12. a
13. c
14. d
15. b

Short questions — model answers

1. AI is human-made ("artificial") technology that can perform tasks requiring thinking ("intelligence"); it uses data to make decisions. Examples: face recognition to unlock a phone; YouTube suggesting videos; chatbots answering questions.
2. IoT is a system in which physical devices are connected to the internet and can collect and share data to perform tasks automatically. Example: a smartwatch collects heart-rate data and sends it to a mobile phone for display.
3. A sensor collects information from the physical world (input; the "eyes and ears"), e.g. temperature sensor, motion sensor. An actuator performs a physical action in response to a command, converting digital signals into movement (output), e.g. electric motor, automatic door opener.
4. Cloud computing stores IoT data and provides processing services over the internet instead of local hard drives, so it can handle the massive amounts of data produced by many devices. Examples: Google Drive, iCloud, online LMS.
5. Collection, storage, cleaning, analysis, visualization. Cleaning removes duplicated records, incorrect values (typos), missing files/records, and improper formats.
6. Smart cities: sensors adjust traffic signals to reduce congestion; smart bins send alerts when full (also street lighting, parking). Healthcare: smartwatches measure heart rate and vitals; remote monitoring devices send patient data to doctors (also emergency alerts).
7. Benefits: students learn at their own speed; AI identifies students who need extra help (also supports students with disabilities). Challenges: limited internet access in rural areas; lack of computers/devices (also teacher training, data privacy).
8. Primary sources give original, firsthand information from people, events or official records (e.g. interviews, NADRA records). Secondary sources contain information already collected and explained by someone else, summarising or analysing primary data (e.g. textbooks, news reports).
9. When the information is outdated, lacks proper references/citations, or has not been verified by an expert.
10. (a) Communication: + emails and video calls give instant, global communication at almost no cost; – less in-person interaction causes social isolation. (b) Business: + online shopping, digital banking and automation improve speed and efficiency; – manual jobs are lost to machines and banks face cyber-attacks.

Long questions — model answers

1. **Definition:** IoT is a system in which physical devices are connected to the internet and collect and share data to perform tasks automatically. **Components:** (1) Sensors — collect information from the physical world, e.g. temperature, motion, fingerprint, smoke, soil moisture sensors. (2) Actuators — perform physical actions in response to commands, converting digital signals to movement, e.g. motor, switch, door opener, water valve, fan controller. (3) Connectivity — lets devices send/receive data, e.g. Wi-Fi, Bluetooth, ZigBee, 4G/5G. (4) Data processing — changes raw data into useful information through collecting, organising, analysing and deciding, e.g. checking if a room is too hot to switch on the AC. (5) Cloud computing — stores data and provides services over the internet, handles massive data, e.g. Google Drive, iCloud, LMS. (6) User interface — lets users see information and give commands, e.g. mobile apps, touch screens, voice commands. **Diagram:** Sensor (collects) → Wi-Fi → Cloud (processes) → Actuator (acts) → User App (UI).
2. **Table:** IoT — network of physical devices connected to the internet; purpose: data collection and automation; works with hardware; output: raw data from environment. AI — technology enabling machines to think and decide; purpose: intelligent decisions and predictions; works with smart software; output: smart decisions or actions. Data Analytics — process of examining data to find patterns; purpose: extracting meaningful insights; works with data (numbers, records); output: reports, graphs, insights. **Working together:** IoT is the eyes that gather data, Analytics sorts it, AI is the brain that decides. Example: a temperature sensor reads 36 °C (IoT) → recent readings are organised showing the room is heating up (Analytics) → AI decides the room is too hot (AI) → a switch turns on the AC (action).
3. (1) **Collection:** gather marks of all Maths tests, attendance and survey responses from students. (2) **Storage:** keep them safely in a spreadsheet or database, e.g. on the cloud. (3) **Cleaning:** remove duplicate records, correct typing errors (e.g. 120 out of 100), fill or mark missing records, and make formats (dates, roll numbers) consistent. (4) **Analysis:** study the clean data to find patterns — e.g. which chapters most students got wrong, whether low attendance links to failing. (5) **Visualization:** present results in bar charts or a pie chart of pass vs fail so the principal sees the problem at a glance and plans extra classes for weak chapters.
4. **Primary:** original, firsthand, highly authentic (interviews, photographs, diaries, NADRA records). **Secondary:** collected and explained by someone else, summarises/analyses primary data (textbooks, news reports, research papers, Bureau of Statistics reports). **Tertiary:** highly summarised and organised from primary and secondary sources for quick reference (encyclopedias, Wikipedia, dictionaries, handbooks). **Classification:** (i) secondary, (ii) primary, (iii) tertiary, (iv) primary, (v) secondary, (vi) tertiary. **Unreliability:** primary — incomplete, recorded incorrectly, or deliberately false; secondary — outdated, no references/citations, not verified by an expert; tertiary — unknown/unverified website, or oversimplified and missing key facts. Rule: do not trust an article without author, date or references.
5. **Definition:** devices, software and systems that help people with disabilities or functional limitations participate equally in school, work and society. **Categories:** (1) Mobility aids — help people move; smart wheelchairs, stair lifts. (2) Sensory aids — support vision and hearing; hearing aids, screen readers (VoiceOver), Braille displays. (3) Communication aids — help people with speech difficulties express themselves; speech-generating devices, text-to-speech apps. (4) Cognitive/learning aids — help with memory, reading, understanding; audiobooks, spell-checkers, reminder apps. **Importance:** equal access to education (screen readers let blind students read digital textbooks), independence in daily life (mobility aids reduce need for constant help), social inclusion (people work, study and socialise confidently). **Careers:** any two of assistive software developer (speech-to-text tools), biomedical engineer (artificial limbs, hearing aids), UX/UI accessibility expert (websites usable by visually impaired users).
6. **Introduction:** computing makes life faster and more connected but brings privacy risks and addiction. **Education:** + online classes, e-books and learning apps make study flexible and accessible; – excessive screen time reduces attention span and harms physical health. **Healthcare:** + digital patient records and telemedicine let doctors treat remote patients accurately (e.g. rural Sindh); – patient data privacy is at risk if hospital servers are hacked. **Agriculture:** + smart irrigation and weather forecasting greatly increase yields; – poor rural internet means many farmers cannot use these tools. **Responsible use:** protect personal information and use strong passwords; do not share fake news or unverified forwards; balance screen time with sports and physical activity. **Conclusion:** benefits are large if technology is used wisely.

Self-assessment: I can...

- ☐ define AI and explain why it is called "artificial intelligence".
- ☐ define IoT and name its six components with examples.
- ☐ list the five components of Data Analytics in order and describe data cleaning.
- ☐ describe IoT uses in smart cities, industry, healthcare, education, homes and farms.
- ☐ classify any source as primary, secondary or tertiary and judge its reliability.
- ☐ explain the four categories of assistive technologies and their importance.
- ☐ explain how IoT, Data Analytics and AI work together (eyes → sort → brain → action).
- ☐ tell the difference between a sensor and an actuator.
- ☐ compare IoT, AI and Data Analytics in a table.
- ☐ state uses, benefits and challenges of AI in education in Pakistan.
- ☐ discuss positive and negative impacts of computing in five fields.
- ☐ name careers linked to IoT, AI and assistive technology and the skills they need.

CHAPTER 6

Digital Literacy

This chapter teaches you how to find, collect, organise and present information using digital tools, safely and responsibly. You will learn about types of data, ways to collect it, and how to turn it into a useful report, presentation or infographic. At the end you will follow a complete research project from the first question to the final product.

اس باب میں آپ سیکھیں گے کہ ڈیجیٹل آلات کی مدد سے معلومات کو محفوظ اور ذمہ دارانہ طریقے سے کیسے تلاش کیا جائے، جمع کیا جائے، ترتیب دیا جائے اور پیش کیا جائے۔ آخر میں آپ ایک مکمل تحقیقی منصوبہ (Digital Inquiry Project) شروع سے آخر تک دیکھیں گے۔

What you will learn

- Define digital literacy and explain why it matters in the Information Age.
- Describe five data-collection strategies: interviews, surveys, prototypes, observation and simulations.
- Compare primary and secondary data by source, examples, purpose and control.
- Use spreadsheet formulas such as `=SUM()`, `=AVERAGE()` and `=COUNTIF()` to analyse data.
- Use advanced search operators (" " , `filetype:` , `site:`) and evaluate the reliability of a source.
- Distinguish between qualitative and quantitative data and give examples of each.
- Write clear, unbiased survey questions and recognise badly written ones.
- List the eight steps for designing a data-collection approach, including ethics and consent.
- Choose a suitable digital tool (spreadsheet, presentation, infographic, report, dashboard) to present findings.
- Carry out all 12 steps of a digital inquiry project and produce a final digital artefact.

ACADEMY CALENDAR

Academy calendar: 17 topics · 11 Golden · **15 classes of 90 minutes** + one 40-minute weekly test after this chapter.

Class	Topics	Kind	Board focus
Class 01	Introduction to Digital Literacy + Digital Literacy in the Information Age	Paired · 90 min	Digital literacy is the ability to understand and use digital devices, the internet, and...
Class 02	Types of Data	★ Golden · 90 min	Data means facts, numbers, words or observations that we collect.
Class 03	Data-Collection Strategies	★ Golden · 90 min	Digital literacy is not limited to finding information that already exists on the...
Class 04	Interviews and Surveys	★ Golden · 90 min	An interview is a planned conversation used to gather information directly from a person.
Class 05	Prototypes, Observation and Simulations	★ Golden · 90 min	A prototype is a simple early version of a product, model or solution.
Class 06	Primary and Secondary Data	★ Golden · 90 min	Whenever you use data, it is important to know where it came from.
Class 07	Designing a Data-Collection Approach + Presenting Data Using Digital Tools: 6.7.1 Spreadsheets and 6.7.2 Presentations	Paired · 90 min	Before collecting data, a researcher must have a plan.
Class 08	Infographics and Reports	Single · 90 min	An infographic (information + graphic) is a visual way of presenting information, facts...
Class 09	Case Study: Digital Inquiry Project	★ Golden · 90 min	This case study shows how to apply all the ideas of this chapter to solve a real-world...
Class 10	Steps 1 – 3: Advanced Search and Methodology	★ Golden · 90 min	Students first search for background information using search engines (such as Google or...
Class 11	Steps 4 – 6: Survey Preparation and Primary Data Collection	★ Golden · 90 min	Design clear, unbiased questions.

Class	Topics	Kind	Board focus
Class 12	Steps 7 – 9: Secondary Data and Spreadsheet Organisation	★ Golden · 90 min	Students include a reliable online article stating that "excessive screen time lowers...
Class 13	Steps 10 – 12: Data Analysis, Conclusion and Recommendations	★ Golden · 90 min	To analyse means to study the data carefully to find patterns and trends.
Class 14	The Final Digital Artefact	★ Golden · 90 min	A digital artefact is a final product created using digital technologies.
Class 15	Careers in Digital Research	Single · 90 min	The skills in this chapter lead to real jobs: CareerWhat they doChapter skill used Market...

Weekly test: 15 MCQ from this chapter + two 5-mark Golden questions. Mark to the recipes. Re-teach any Golden below 60% in the next starter.

گولڈن موضوع پوری کلاس لیتا ہے۔ ہفتہ وار ٹیسٹ کے بعد کمزور گولڈن دوبارہ پڑھائیں۔

6.1 Introduction to Digital Literacy

ACADEMY SESSION

Session 1 of 15 · 45 minutes (first half) · paired with Digital Literacy in the Information Age.

10–45 min — this topic. Lock the definition and table for **Introduction to Digital Literacy**. Starter (0–10) is from last class. Second half is Digital Literacy in the Information Age.

On the board: Digital literacy is the ability to understand and use digital devices, the internet, and online tools in a safe, effective, and responsible manner.

Error clinic: Mistake: "Digital literacy means knowing how to use a computer." Fix: Using a computer is only the start.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Introduction to Digital Literacy**. Write: Digital literacy is the ability to understand and use digital devices, the internet, and online tools in a safe, effective, and responsible manner.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Effective – you get the job done well (for example, you find the right information quickly). (2) Responsible – you use information honestly and fairly (for example, you do not copy someone else's work or spread false news). — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Digital literacy is the ability to understand and use digital devices, the internet, and online tools in a **safe**, **effective**, and **responsible** manner.

Look at the three key words:

- **Safe** – you protect yourself and others online (for example, you do not share passwords or private details).
- **Effective** – you get the job done well (for example, you find the right information quickly).
- **Responsible** – you use information honestly and fairly (for example, you do not copy someone else's work or spread false news).

In our increasingly digital world, digital literacy is essential for **everyone**, not only for computer experts. It enables you to:

- **find** information,
- **communicate** with others,
- **produce** digital content, and
- **solve problems** through technology.

Did you know? Digital literacy is not only *using devices*; it is *using digital information safely and wisely*. A digitally literate student can:

Locate information → Organise it properly → Turn it into something useful → Share it responsibly

WORKED EXAMPLE

Is this student digitally literate?

Ali can type fast and plays games on his phone all day. When his teacher asks him to find the population of Karachi, he copies the first number he sees on a random website and does not check where it came from.

Step 1 – Can he use devices? Yes. He has basic skills.

Step 2 – Can he locate and judge information? No. He did not check whether the website was reliable.

Step 3 – Conclusion: Ali has *computer skills* but is not yet fully *digitally literate*. A digitally literate student would compare two or three trusted sources (for example, the Pakistan Bureau of Statistics website) before using the number.

REMEMBER IT

Remember the four verbs of a digitally literate student: **Locate – Organise – Create – Share** ("**LOCS**": think of a *lock* that keeps your digital life safe).

COMMON MISTAKE

Mistake: "Digital literacy means knowing how to use a computer." **Fix:** Using a computer is only the start. Digital literacy also means finding, judging, creating and sharing information safely and responsibly.

اردو میں سمجھیں

ڈیجیٹل خواندگی (Digital Literacy) سے مراد ڈیجیٹل آلات، انٹرنیٹ اور آن لائن ٹولز کو محفوظ، مؤثر اور ذمہ دارانہ طریقے سے سمجھنا اور استعمال کرنا ہے۔ ایک ڈیجیٹل خواندہ طالب علم معلومات تلاش کر سکتا ہے، انہیں ترتیب دے سکتا ہے، ان سے کوئی مفید چیز بنا سکتا ہے اور انہیں ذمہ داری سے دوسروں تک پہنچا سکتا ہے۔

CHECK YOURSELF

1. Write the definition of digital literacy in one sentence.
2. Name the four things digital literacy enables you to do.

Answers: 1. The ability to understand and use digital devices, the internet and online tools in a safe, effective and responsible manner. 2. Find information, communicate, produce digital content, and solve problems through technology.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Write the definition of digital literacy in one sentence.

3 marks. Explain Introduction to Digital Literacy with two clear points and one example.

5 marks. Write a 5-mark answer on Introduction to Digital Literacy: definition, two points, a labelled diagram or table, and one example.

Answers: 1. The ability to understand and use digital devices, the internet and online tools in a safe, effective and responsible manner 3. Effective – you get the job done well (for example, you find the right information quickly).; Responsible – you use information honestly and fairly (for example, you do not copy someone else's work or spread false news). 5. Use the recipe in the blue box. Model opening: Digital literacy is the ability to understand and use digital devices, the internet, and online tools in a safe, effective, and responsible manner.

BATCH HOMEWORK

Write a 5-mark answer on **Introduction to Digital Literacy** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.2 Digital Literacy in the Information Age

ACADEMY SESSION

Session 1 of 15 · 45 minutes (second half) · paired with Introduction to Digital Literacy.

45–75 min — this topic. Board working for **Digital Literacy in the Information Age**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: The Information Age is the period we live in now, where vast amounts of data are produced, shared and accessed instantly through the internet, mobile devices and digital platforms (websites, apps,...)

Error clinic: Mistake: Thinking that "more information" automatically means "better information".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Digital Literacy in the Information Age**. Write: The Information Age is the period we live in now, where vast amounts of data are produced, shared and accessed instantly through the internet, mobile devices and digital platforms (websites, apps,...)

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Simply having access to technology is not enough. (2) Owning a smartphone does not make you good at using information. — + example.

5 marks: 3-mark structure + table: Ability / What it means / Example + the worked example from this topic.

LEARN IT

The **Information Age** is the period we live in now, where vast amounts of data are **produced**, **shared** and **accessed instantly** through the internet, mobile devices and digital platforms (websites, apps, social media).

Simply **having access** to technology is **not enough**. Owning a smartphone does not make you good at using information. You must develop the skills to **understand**, **manage** and **use** information wisely.

Digital literacy goes beyond basic computer skills. It involves three kinds of ability:

Ability	What it means	Example
Technical	Knowing how to operate devices and software.	Creating a Google Form; using a spreadsheet.
Cognitive (thinking)	Thinking critically about information.	Checking whether a news story is true before believing it.
Social	Communicating and behaving well with others online.	Being polite in a class WhatsApp group; respecting privacy.

Together these abilities help you function successfully in a **digital society**.

WORKED EXAMPLE

Applying the three abilities. A video claims "Drinking hot water cures dengue." What does a digitally literate student do?

Technical: Uses a search engine to search `dengue treatment site:.gov`.

Cognitive: Notices the video has no doctor or source, and that official health websites do not support the claim. Concludes it is false.

Social: Does not forward the video, and politely tells the family group that it is not reliable.

REMEMBER IT

Three abilities = **"Tech, Think, Talk"**: Technical, Cognitive (think), Social (talk with others).

COMMON MISTAKE

Mistake: Thinking that "more information" automatically means "better information". **Fix:** In the Information Age the problem is not finding *some* information; it is choosing the *right, reliable* information from too much.

اردو میں سمجھیں

معلوماتی دور (Information Age) میں انٹرنیٹ اور موبائل کے ذریعے بے پناہ معلومات فوراً تیار اور شیئر ہوتی ہیں۔ صرف ٹیکنالوجی تک رسائی کافی نہیں؛ معلومات کو سمجھنے، سنبھالنے اور دانشمندی سے استعمال کرنے کی مہارت ضروری ہے۔ ڈیجیٹل خواندگی میں تکنیکی، ذہنی (Cognitive) اور سماجی صلاحیتیں شامل ہیں۔

CHECK YOURSELF

1. What is the Information Age?
2. Name the three types of ability that digital literacy involves.

Answers: 1. A period in which vast amounts of data are produced, shared and accessed instantly through the internet, mobile devices and digital platforms. 2. Technical, cognitive and social abilities.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is the Information Age?

3 marks. Explain Digital Literacy in the Information Age with two clear points and one example.

5 marks. Write a 5-mark answer on Digital Literacy in the Information Age: definition, two points, a labelled diagram or table, and one example.

Answers: 1. A period in which vast amounts of data are produced, shared and accessed instantly through the internet, mobile devices and digital platforms 3. Simply having access to technology is not enough.; Owning a smartphone does not make you good at using information. 5. Use the recipe in the blue box. Model opening: The Information Age is the period we live in now, where vast amounts of data are produced, shared and accessed instantly through the internet, mobile devices...

BATCH HOMEWORK

Write a 5-mark answer on **Digital Literacy in the Information Age** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.3 Types of Data ★ Golden

ACADEMY SESSION

Session 2 of 15 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Data means facts, numbers, words or observations that we collect.

Error clinic: Mistake: Thinking that any data containing a number is quantitative.

Exam wording to train: Common questions: "Differentiate between qualitative and quantitative data" (4–5 marks) or "Classify the following data".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Types of Data**. Write: Data means facts, numbers, words or observations that we collect.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The data gathered through a survey, an investigation or a classroom project can be described in two ways: qualitatively or quantitatively. (2) Knowing the difference is critical, because each type is analysed in a different way. — + example.

5 marks: 3-mark structure + table: Type of data / Nature / Examples / Best used for + the worked example from this topic.

8–10 marks: 5-mark structure + a four-row comparison table and one rewritten survey question + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Data means facts, numbers, words or observations that we collect. The data gathered through a survey, an investigation or a classroom project can be described in two ways: **qualitatively** or **quantitatively**. Knowing the difference is critical, because each type is analysed in a different way.

6.3.1 Qualitative Data

Qualitative data describes what people **think, feel, notice or experience**. It is **non-numerical** and **descriptive**: it is made of words, not numbers. The word comes from *quality* (what something is like).

Examples: students' opinions about online classes; descriptions of study habits; observation notes ("The students looked bored after 20 minutes").

6.3.2 Quantitative Data

Quantitative data deals with **numbers**. The word comes from *quantity* (how much or how many). It is useful when you need to **count, measure, compare, calculate averages, or display results in charts**.

Examples: number of students using the internet daily; marks obtained in a test; time spent online in hours.

6.3.3 Comparing Qualitative and Quantitative Data

Type of data	Nature	Examples	Best used for
Qualitative	Descriptive, non-numerical	Opinions, reasons, behaviour	Understanding why and how something happens
Quantitative	Numerical, countable or measurable	Hours, scores, percentages, totals	Comparing results and making graphs/charts

LEARN IT

Going a little further (background). Quantitative data is sometimes split into two kinds:

- **Discrete** data can only take separate, countable values, e.g. number of students in a class (35, 36 – never 35.5).
- **Continuous** data can take any value in a range and is *measured*, e.g. height (162.4 cm) or time online (2.75 hours).

Also note: a question with fixed categories (e.g. "Which activity do you use your phone for most? Lectures / Notes / Social media / Games") gives **categories** that you can **count**. In this chapter's case study such answers are treated as **quantitative (categories)**, because you count how many students chose each option.

WORKED EXAMPLE

Classify each piece of data.

Data	Type	Reason
"I like online classes because I can replay lectures."	Qualitative	An opinion with a reason, in words.
Ayesha scored 78 out of 100.	Quantitative	A score – a number you can compare.
28 out of 40 students use the internet daily.	Quantitative	A count (and gives 70%).
Observer notes: "Students chat during the last period."	Qualitative	A description of behaviour.
Bilal spends 3.5 hours online per day.	Quantitative	A measurement of time.

Quick test: ask "Can I calculate an average of this?" If yes, it is quantitative. If the answer is words, it is qualitative.

REMEMBER IT

QUALitative = **QUAL**ity = words and feelings. **QUANT**itative = **QUANT**ity = numbers and counts. Qualitative answers **why/how**; quantitative answers **how many/how much**.

COMMON MISTAKE

Mistake: Thinking that any data containing a number is quantitative. A phone number or a roll number is a *label*, not a quantity – averaging roll numbers is meaningless. **Fix:** Data is quantitative only if the number measures or counts something.

اردو میں سمجھیں

کیفیتی ڈیٹا (Qualitative Data) الفاظ پر مشتمل ہوتا ہے اور بتاتا ہے کہ لوگ کیا سوچتے، محسوس کرتے یا تجربہ کرتے ہیں، جیسے آن لائن کلاسز کے بارے میں رائے۔ مقداری ڈیٹا (Quantitative Data) اعداد پر مشتمل ہوتا ہے، جیسے ٹیسٹ کے نمبر یا آن لائن گزارے گئے گھنٹے۔ کیفیتی ڈیٹا "کیوں اور کیسے" سمجھنے کے لیے، جبکہ مقداری ڈیٹا موازنہ کرنے اور چارٹ بنانے کے لیے بہترین ہے۔

EXAM TIP

Common questions: "Differentiate between qualitative and quantitative data" (4–5 marks) or "Classify the following data". Write the answer as a **table** with four rows: **nature, examples, best used for**, plus a one-line definition of each. Always give **two examples** of each type. The source's table (Nature / Examples / Best used for) is exactly what examiners expect.

CHECK YOURSELF

1. Is "time spent online in hours" qualitative or quantitative?
2. Which type of data is best for understanding *why* something happens?
3. Classify: "The canteen food is too oily."

Answers: 1. Quantitative (measurable number). 2. Qualitative. 3. Qualitative (an opinion in words).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Is "time spent online in hours" qualitative or quantitative?

3 marks. Explain Types of Data with two clear points and one example.

5 marks. Common questions: "Differentiate between qualitative and quantitative data" (4–5 marks) or "Classify the following data". Write the answer as a table with four rows: nature, examples, best used for,...

8 marks. Types of Data: 5-mark answer plus a four-row comparison table and one rewritten survey question.

Answers: 1. Quantitative (measurable number) 3. The data gathered through a survey, an investigation or a classroom project can be described in two ways: qualitatively or quantitatively.; Knowing the difference is critical, because each type is analysed in a different way. 5. Use the recipe in the blue box. Model opening: Data means facts, numbers, words or observations that we collect. 8. Same 5-mark body + a four-row comparison table and one rewritten survey question + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Types of Data** using the recipe in this topic. Include a four-row comparison table and one rewritten survey question. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.4 Data-Collection Strategies ★ Golden

ACADEMY SESSION

Session 3 of 15 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Digital literacy is not limited to finding information that already exists on the internet.

Exam wording to train: "List and explain the data-collection strategies" is a frequent long question.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Data-Collection Strategies**. Write: Digital literacy is not limited to finding information that already exists on the internet.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) You should also learn how to gather original (new) information yourself. (2) A data-collection strategy is a planned method for gathering this information. — + example.

5 marks: 3-mark structure + table: Strategy / How it works (one line) / Usual data type / Best when... + the worked example from this topic.

8–10 marks: 5-mark structure + a one-page canvas: problem, user, riskiest assumption, test + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Digital literacy is not limited to finding information that **already exists** on the internet. You should also learn how to gather **original** (new) information yourself. A **data-collection strategy** is a planned method for gathering this information.

The five common strategies are:

Interviews · Surveys · Prototypes · Observation · Simulations

Strategy	How it works (one line)	Usual data type	Best when...
Interview	Planned conversation with a person or small group	Mostly qualitative	You need deep, detailed answers from a few people
Survey	Same questions asked to many people	Quantitative and qualitative	You need answers from many people quickly
Prototype	Users test an early version and give feedback	Both	You want to improve a product or solution
Observation	Watch and record; no questions asked	Notes (qualitative) or counts (quantitative)	You want to see what people actually do
Simulation	Computer model; change variables and see what happens	Mostly quantitative	Real experiments are costly, risky or difficult

REMEMBER IT

Mnemonic for the five strategies: "**I S P O S**" – "**I** **S**aw **P**eople **O**n **S**creens": Interviews, Surveys, Prototypes, Observation, Simulations.

اردو میں سمجھیں

ڈیجیٹل خواندگی صرف موجود معلومات تلاش کرنے تک محدود نہیں، بلکہ نئی معلومات خود جمع کرنا بھی اس کا حصہ ہے۔
ڈیٹا جمع کرنے کے پانچ عام طریقے یہ ہیں: انٹرویو، سروے، پروٹوٹائپ، مشاہدہ (Observation) اور سمیولیشن (Simulation)۔

EXAM TIP

"List and explain the data-collection strategies" is a frequent long question. Name all **five**, give a one-sentence definition and **one example** for each, and say what type of data each gives. Detailed notes on each follow in the next two topics.

CHECK YOURSELF

1. Name the five data-collection strategies.
2. What does "original information" mean?

Answers: 1. Interviews, surveys, prototypes, observation, simulations. 2. New information that you gather yourself, rather than information that already exists.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name the five data-collection strategies.

3 marks. Explain Data-Collection Strategies with two clear points and one example.

5 marks. "List and explain the data-collection strategies" is a frequent long question. Name all five, give a one-sentence definition and one example for each, and say what type of data each gives. Detailed...

8 marks. Data-Collection Strategies: 5-mark answer plus a one-page canvas: problem, user, riskiest assumption, test.

Answers: 1. Interviews, surveys, prototypes, observation, simulations 3. You should also learn how to gather original (new) information yourself.; A data-collection strategy is a planned method for gathering this information. 5. Use the recipe in the blue box. Model opening: Digital literacy is not limited to finding information that already exists on the internet. 8. Same 5-mark body + a one-page canvas: problem, user, riskiest assumption, test + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Data-Collection Strategies** using the recipe in this topic. Include a one-page canvas: problem, user, riskiest assumption, test. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.4.1 – 6.4.2 Interviews and Surveys ★ Golden

ACADEMY SESSION

Session 4 of 15 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: An interview is a planned conversation used to gather information directly from a person.

Error clinic: Mistake: Writing only open-ended questions in a survey for 100 people.

Exam wording to train: You may be asked to "differentiate between an interview and a survey" or to "identify what is wrong with this survey question and rewrite it".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Interviews and Surveys**. Write: An interview is a planned conversation used to gather information directly from a person.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Questions are planned in advance, so you do not forget anything important. (2) Answers are usually qualitative (opinions, reasons, experiences). — + example.

5 marks: 3-mark structure + table: Question type / What it looks like / Data it gives + the worked example from this topic.

8–10 marks: 5-mark structure + a four-row comparison table and one rewritten survey question + a one-line conclusion. Method marks are awarded for working.

6.4.1 Interviews

LEARN IT

An **interview** is a **planned conversation** used to gather information **directly from a person**.

- It may be **one-to-one** (you and one person) or in a **small group**.
- Questions are **planned in advance**, so you do not forget anything important.
- Answers are usually **qualitative** (opinions, reasons, experiences).

Strength: you get deep, detailed answers and can ask follow-up questions ("Why do you say that?").

Weakness: it takes a lot of time, so you can only interview a few people.

6.4.2 Surveys / Questionnaires

LEARN IT

A **survey** (or **questionnaire**) is useful when the **same set of questions** needs to be asked to **many people**.

- It may be on **paper** or created with **digital tools** such as **Google Forms** or **Microsoft Forms**.
- **Note:** online survey tools **automatically collect responses** and **display basic charts**, which makes data analysis much easier.

Types of survey and interview questions

Question type	What it looks like	Data it gives
Closed: Yes/No	Do you study with your phone nearby? (Yes / No)	Countable (quantitative)
Closed: Multiple choice	Which activity do you use your phone for most? (Lectures / Notes / Social media / Games)	Categories you can count
Number / scale	How many hours do you use your phone daily? ____	Quantitative
Rating scale	"My phone helps me study." 1 = Strongly disagree ... 5 = Strongly agree	Quantitative (you can average the ratings)
Open-ended	How does your phone help you in studies?	Qualitative (free text)

Good questions vs bad questions

A good question is **clear, short, unbiased** (it does not push the person towards one answer) and asks about **one thing at a time**.

Problem	Bad question	Better question
Leading / biased – suggests the "right" answer	Don't you agree that phones waste students' time?	How do phones affect your study time? (Helps a lot / Helps a little / No effect / Harms a little / Harms a lot)
Double-barrelled – two questions in one	Do you use your phone for lectures and games?	Split into two: "Do you use your phone for lectures?" and "Do you use your phone for games?"
Vague – unclear words	Do you use your phone a lot?	How many hours do you use your phone on a normal school day?
Overlapping options	1–3 hrs / 3–5 hrs / 5+ hrs (where does exactly 3 go?)	Less than 3 hrs / 3 to less than 5 hrs / 5 hrs or more
Sensitive / too personal	What is your father's monthly income?	Leave it out unless it is truly needed for the study.

WORKED EXAMPLE

Building a short Google Form, step by step. Research question: "How do Class XI students travel to college?"

Step 1: Open Google Forms → Blank form → Title: "Travel to College Survey". Add a description: "This survey is anonymous and for a class project. Do you agree to take part? (Yes/No)" – this is your **consent** question.

Step 2: Q1 (multiple choice): "How do you usually travel to college?" Walk / Bus / Rickshaw / Motorbike / Car / Other.

Step 3: Q2 (number): "How many minutes does your journey take?"

Step 4: Q3 (open-ended): "What is the biggest problem you face while travelling?"

Step 5: Click *Send* and share the link in the class group. Responses appear in the *Responses* tab with automatic pie/bar charts, and can be opened in Google Sheets.

Result: Q1 and Q2 give quantitative data; Q3 gives qualitative data.

REMEMBER IT

Interview = In-depth with few. Survey = Same questions to many. Think of a doctor talking to one patient (interview) vs a census form sent to every house (survey).

COMMON MISTAKE

Mistake: Writing only open-ended questions in a survey for 100 people. You will get 100 paragraphs that are very hard to analyse. **Fix:** Use mostly closed or number questions in a large survey, and only one or two open-ended questions.

اردو میں سمجھیں

انٹرویو ایک منصوبہ بند گفتگو ہے جس میں کسی ایک فرد یا چھوٹے گروہ سے براہ راست معلومات حاصل کی جاتی ہیں؛ اس کے جوابات عموماً کیفیتی ہوتے ہیں۔ سروے میں ایک ہی سوالات بہت سے لوگوں سے پوچھے جاتے ہیں، کاغذ پر یا گوگل فارمز (Google Forms) جیسے ڈیجیٹل ٹولز کے ذریعے، جو جوابات خودکار طور پر جمع کر کے چارٹ بھی دکھاتے ہیں۔ اچھا سوال واضح، مختصر، غیر جانبدار اور ایک وقت میں ایک ہی بات کے بارے میں ہوتا ہے۔

EXAM TIP

You may be asked to "differentiate between an interview and a survey" or to "identify what is wrong with this survey question and rewrite it". For rewriting, name the problem (leading, double-barrelled, vague, overlapping) and give the corrected version.

CHECK YOURSELF

1. Name two digital tools for creating surveys.
2. What is wrong with: "Do you enjoy maths and physics?"
3. Are interview answers usually qualitative or quantitative?

Answers: 1. Google Forms and Microsoft Forms. 2. It is double-barrelled (two subjects in one question); ask about each subject separately. 3. Usually qualitative.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name two digital tools for creating surveys.

3 marks. Explain Interviews and Surveys with two clear points and one example.

5 marks. You may be asked to "differentiate between an interview and a survey" or to "identify what is wrong with this survey question and rewrite it". For rewriting, name the problem (leading,...

8 marks. Interviews and Surveys: 5-mark answer plus a four-row comparison table and one rewritten survey question.

Answers: 1. Google Forms and Microsoft Forms 3. Questions are planned in advance, so you do not forget anything important.; Answers are usually qualitative (opinions, reasons, experiences). 5. Use the recipe in the blue box. Model opening: An interview is a planned conversation used to gather information directly from a person. 8. Same 5-mark body + a four-row comparison table and one rewritten survey question + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Interviews and Surveys** using the recipe in this topic. Include a four-row comparison table and one rewritten survey question. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.4.3 – 6.4.5 Prototypes, Observation and Simulations ★ Golden

ACADEMY SESSION

Session 5 of 15 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A prototype is a simple early version of a product, model or solution.

Error clinic: Mistake: Saying that observation involves asking people questions.

Exam wording to train: Scenario questions are popular: "Which data-collection method is most suitable for ... ?"

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Prototypes, Observation and Simulations**. Write: A prototype is a simple early version of a product, model or solution.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It allows an idea to be tested before time and effort are spent on the final version. (2) Users try the prototype and give feedback, and this feedback becomes useful data for improvement. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

8–10 marks: 5-mark structure + a one-page canvas: problem, user, riskiest assumption, test + a one-line conclusion. Method marks are awarded for working.

6.4.3 Prototypes

LEARN IT

A **prototype** is a **simple early version** of a product, model or solution. It allows an idea to be **tested before** time and effort are spent on the final version. Users **try** the prototype and give **feedback**, and this feedback becomes useful **data for improvement**.

Example: Before building a full school app, you draw the screens on paper (or make a few clickable screens in a design tool) and ask five classmates to try "finding the timetable". You note where they get confused.

6.4.4 Observation

LEARN IT

In **observation**, the researcher **watches** what people do or what happens in a situation and **records the results carefully**. **No direct questions are asked**.

The data may be **qualitative** (written notes, e.g. "students push in the queue") or **quantitative** (counts, e.g. "42 students bought samosas in 10 minutes").

Why use it? People sometimes say one thing and do another. Observation shows what really happens.

6.4.5 Simulations

LEARN IT

A **simulation** is a **computer-based model of a real situation**. **Variables** (the things that can change, like speed, temperature or number of people) can be changed to see what happens.

Simulations are highly useful when **real experiments are costly, risky or difficult** to perform.

Examples: a flight simulator for training pilots (real crashes are dangerous); a traffic simulation to test what happens if a new signal is added (changing real roads is costly); a weather model to predict a cyclone (you cannot experiment with real weather).

WORKED EXAMPLE

Choosing the right method. Which method would you use?

(a) "How many cars cross an intersection at 8 AM?" → **Observation**. Stand at the corner from 8:00 to 8:15 and tally each car. Asking drivers would be impossible and unnecessary; you just count.

(b) "How do students feel about the new cafeteria food?" → **Survey or interview**. Feelings are inside people's heads, so you must ask them. Use a survey for many students, or interviews for deeper reasons.

(c) "Will a new college website menu be easy to use?" → **Prototype**. Build a rough version and let users try it.

(d) "What happens to traffic if the bridge is closed for repairs?" → **Simulation**. Closing a real bridge to test is costly and disruptive.

REMEMBER IT

Watch it → Observation. **Ask** it → Survey/Interview. **Try** it → Prototype. **Model** it → Simulation.

COMMON MISTAKE

Mistake: Saying that observation involves asking people questions. **Fix:** In observation, **no direct questions** are asked – the researcher only watches and records. Also, a prototype is *not* the finished product; it is an early test version.

اردو میں سمجھیں

پروٹوٹائپ کسی پروڈکٹ یا حل کا ابتدائی سادہ نمونہ ہے جسے صارفین آزما کر رائے دیتے ہیں تاکہ اسے بہتر بنایا جاسکے۔ مشاہدے (Observation) میں محقق کوئی سوال نہیں پوچھتا بلکہ صرف دیکھ کر نتائج درج کرتا ہے۔ سمیولیشن کسی حقیقی صورتحال کا کمپیوٹر ماڈل ہے، جو اس وقت مفید ہے جب حقیقی تجربہ مہنگا، خطرناک یا مشکل ہو۔

EXAM TIP

Scenario questions are popular: "Which data-collection method is most suitable for ... ? Give a reason." Always name the method **and** justify it using its key feature (e.g. "Simulation, because a real experiment would be risky").

CHECK YOURSELF

1. Why would an engineer use a simulation instead of a real test?
2. Can observation produce quantitative data? Give an example.
3. What becomes the "data" when using a prototype?

Answers: 1. Because the real experiment may be costly, risky or difficult. 2. Yes – for example, counting the number of cars passing a point. 3. The feedback users give after trying the prototype.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Why would an engineer use a simulation instead of a real test?

3 marks. Explain Prototypes, Observation and Simulations with two clear points and one example.

5 marks. Scenario questions are popular: "Which data-collection method is most suitable for ... ? Give a reason." Always name the method and justify it using its key feature (e.g. "Simulation, because a real...

8 marks. Prototypes, Observation and Simulations: 5-mark answer plus a one-page canvas: problem, user, riskiest assumption, test.

Answers: 1. Because the real experiment may be costly, risky or difficult 3. It allows an idea to be tested before time and effort are spent on the final version.; Users try the prototype and give feedback, and this feedback becomes useful data for improvement. 5. Use the recipe in the blue box. Model opening: A prototype is a simple early version of a product, model or solution. 8. Same 5-mark body + a one-page canvas: problem, user, riskiest assumption, test + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Prototypes, Observation and Simulations** using the recipe in this topic. Include a one-page canvas: problem, user, riskiest assumption, test. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.5 Primary and Secondary Data ★ Golden

ACADEMY SESSION

Session 6 of 15 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Whenever you use data, it is important to know where it came from.

Error clinic: Mistake: Thinking data from a website is always primary because "I found it myself".

Exam wording to train: "Differentiate between primary and secondary data" is one of the most-asked questions in this chapter.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Primary and Secondary Data**. Write: Whenever you use data, it is important to know where it came from.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Whenever you use data, it is important to know where it came from. (2) The source affects how much control the researcher had over collecting it, and how confidently the results can be used. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a four-row comparison table and one rewritten survey question + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Whenever you use data, it is important to know **where it came from**. The source affects how much **control** the researcher had over collecting it, and how **confidently** the results can be used.

6.5.1 Primary Data

Primary data is collected **first-hand** by the researcher for a **particular purpose**. It is gathered **directly** from people, events or situations, rather than taken from an already published source.

Sources: interviews, surveys, observations, experiments.

6.5.2 Secondary Data

Secondary data has **already been collected by someone else** and is being used again for a **new purpose**. It is taken from existing archives (stored collections of information).

Sources: books, research articles, official reports, web statistics, online databases.



Primary data is collected by you; secondary data was collected by others.

6.5.3 Difference Between Primary and Secondary Data

Aspect	Primary Data	Secondary Data
Source	Collected directly by the researcher.	Already collected by others.
Examples	Survey responses, interviews, observations.	Reports, articles, websites, databases.
Purpose	Prepared for a specific study.	Reused for a new purpose.
Control	High control over questions and collection process.	Limited control because the data already exists.

WORKED EXAMPLE

Primary or secondary? Hira is researching "Internet use among students in Hyderabad".

(a) She sends a Google Form to 50 students in her college. → **Primary** (she collected it herself, for this study).

(b) She uses a PTA (Pakistan Telecommunication Authority) report on the number of broadband users in Pakistan. → **Secondary** (PTA collected it for its own purpose; Hira reuses it).

(c) She counts how many students use phones in the library during one hour. → **Primary** (her own observation).

(d) She quotes a statistic from a research article. → **Secondary**.

Why use both? Her primary data tells her about *her own* college; the secondary data lets her **compare** it with the national picture.

REMEMBER IT

Primary = "1st hand" (you collect it first). Secondary = "2nd hand" (like a second-hand book – someone else used it first).

COMMON MISTAKE

Mistake: Thinking data from a website is always primary because "I found it myself". **Fix:** What matters is *who collected* the data. If someone else collected it and you only found it, it is secondary.

اردو میں سمجھیں

بنیادی ڈیٹا (Primary Data) محقق خود کسی خاص مقصد کے لیے براہ راست جمع کرتا ہے، مثلاً سروے، انٹرویو یا مشاہدہ۔ ثانوی ڈیٹا (Secondary Data) پہلے ہی کسی اور نے جمع کیا ہوتا ہے اور اسے نئے مقصد کے لیے دوبارہ استعمال کیا جاتا ہے، جیسے کتابیں، رپورٹس اور آن لائن ڈیٹا بیس۔ بنیادی ڈیٹا پر محقق کا کنٹرول زیادہ اور ثانوی ڈیٹا پر کم ہوتا ہے۔

EXAM TIP

"Differentiate between primary and secondary data" is one of the most-asked questions in this chapter. Draw the four-row table: **Source, Examples, Purpose, Control**. Learn it exactly. Add one example from each side to secure full marks.

CHECK YOURSELF

1. Which type of data gives the researcher high control?
2. Is a government census report primary or secondary data for your project?
3. Give two sources of primary data.

Answers: 1. Primary data. 2. Secondary (someone else collected it). 3. Any two: interviews, surveys, observations, experiments.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which type of data gives the researcher high control?

3 marks. Explain Primary and Secondary Data with two clear points and one example.

5 marks. "Differentiate between primary and secondary data" is one of the most-asked questions in this chapter. Draw the four-row table: Source, Examples, Purpose, Control. Learn it exactly. Add one example...

8 marks. Primary and Secondary Data: 5-mark answer plus a four-row comparison table and one rewritten survey question.

Answers: 1. Primary data 3. Whenever you use data, it is important to know where it came from.; The source affects how much control the researcher had over collecting it, and how confidently the results can be used. 5. Use the recipe in the blue box. Model opening: Whenever you use data, it is important to know where it came from. 8. Same 5-mark body + a four-row comparison table and one rewritten survey question + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Primary and Secondary Data** using the recipe in this topic. Include a four-row comparison table and one rewritten survey question. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.6 Designing a Data-Collection Approach

ACADEMY SESSION

Session 7 of 15 · 45 minutes (first half) · paired with Presenting Data Using Digital Tools: 6.7.1 Spreadsheets and 6.7.2 Presentations.

10–45 min — this topic. Lock the definition and table for **Designing a Data-Collection Approach**. Starter (0–10) is from last class. Second half is Presenting Data Using Digital Tools: 6.7.1 Spreadsheets and 6.7.2 Presentations.

On the board: Before collecting data, a researcher must have a plan.

Error clinic: Mistake: Starting to collect data before writing a clear research question.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Designing a Data-Collection Approach**. Write: Before collecting data, a researcher must have a plan.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Decide the type of data needed: quantitative, qualitative, or both. (2) Select suitable methods (survey, interview, observation). — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Before collecting data, a researcher must have a **plan**. A plan makes sure that the information gathered is **accurate, relevant** (related to the question) and **useful**. Follow these eight steps in order:

1. **Define the research question clearly.** What exactly do you want to find out?
2. **Decide the type of data needed:** quantitative, qualitative, or both.
3. **Select suitable methods** (survey, interview, observation).
4. **Choose the sample or target group** – the people who will give you data.
5. **Prepare the tools** such as forms, questions and observation sheets.
6. **Collect the data** carefully and accurately.
7. **Store the data digitally** in a spreadsheet and **keep a backup**.
8. **Follow ethical practice and respect privacy. Consent is mandatory** (you must get permission).



WORKED EXAMPLE

Applying the eight steps. Topic: water wastage in your college.

1. **Question:** "How much water is wasted at the college taps during break time, and why?"
2. **Data type:** Both – quantitative (number of taps left running, minutes) and qualitative (reasons students give).
3. **Methods:** Observation (count running taps) + a short survey (ask about habits).
4. **Sample:** All 12 taps in the college; 30 students from different classes for the survey.
5. **Tools:** An observation sheet with columns *Tap no. / Time / Left running? (Y/N) / Minutes*; a Google Form with 5 questions.
6. **Collect:** Observe during break for five days; send the form link.
7. **Store:** Enter the observation counts into Google Sheets; download a copy to a USB drive as backup.
8. **Ethics:** Ask the principal's permission; tell students the survey is anonymous and voluntary; do not record names.

REMEMBER IT

Remember the steps with: "Quiet Teachers **M**ake Students **T**hink, **C**heck, **S**ave **E**thically" → Question, Type, Method, Sample, Tools, Collect, Store, Ethics.

COMMON MISTAKE

Mistake: Starting to collect data before writing a clear research question. You then collect lots of data that does not answer anything. **Fix:** Always write the question first. Another mistake: keeping data in only one place – if the file is lost, the project is lost. Always keep a backup.

اردو میں سمجھیں

ڈیٹا جمع کرنے سے پہلے منصوبہ بندی ضروری ہے: تحقیقی سوال واضح کریں، ڈیٹا کی قسم طے کریں، مناسب طریقہ چنیں، نمونہ (Sample) منتخب کریں، فارم اور سوالات تیار کریں، احتیاط سے ڈیٹا جمع کریں، اسے اسپریڈشیٹ میں محفوظ کر کے بیک اپ رکھیں، اور اخلاقیات کا خیال رکھیں۔ اجازت (Consent) لینا لازمی ہے۔

CHECK YOURSELF

1. What is the first step in designing a data-collection approach?
2. Which step says "consent is mandatory"?
3. Where should collected data be stored?

Answers: 1. Define the research question clearly. 2. Step 8 – follow ethical practice and respect privacy. 3. Digitally, in a spreadsheet, with a backup copy.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is the first step in designing a data-collection approach?

3 marks. Explain Designing a Data-Collection Approach with two clear points and one example.

5 marks. Write a 5-mark answer on Designing a Data-Collection Approach: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Define the research question clearly 3. Decide the type of data needed: quantitative, qualitative, or both.; Select suitable methods (survey, interview, observation). 5. Use the recipe in the blue box. Model opening: Before collecting data, a researcher must have a plan.

BATCH HOMEWORK

Write a 5-mark answer on **Designing a Data-Collection Approach** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.7 Presenting Data Using Digital Tools: 6.7.1 Spreadsheets and 6.7.2 Presentations

ACADEMY SESSION

Session 7 of 15 · 45 minutes (second half) · paired with Designing a Data-Collection Approach.

45–75 min — this topic. Board working for **Presenting Data Using Digital Tools: 6.7.1 Spreadsheets and 6.7.2 Presentations**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Collecting data is only one part of the work.

Error clinic: Mistake: Typing a result by hand (e.g.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Presenting Data Using Digital Tools: 6.7.1 Spreadsheets and 6.7.2 Presentations**. Write: Collecting data is only one part of the work.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) You must also present your findings so that others can understand them quickly and easily. (2) Digital tools make this much easier. — + example.

5 marks: 3-mark structure + table: Formula / What it does + the worked example from this topic.

LEARN IT

Collecting data is only **one part** of the work. You must also **present** your findings so that others can understand them **quickly and easily**. Digital tools make this much easier. The four main tools are spreadsheets, presentations, infographics and reports.

6.7.1 Spreadsheets

LEARN IT

Spreadsheets such as **MS Excel**, **Google Sheets** and **Apple Numbers** arrange information in **rows** (horizontal, numbered 1, 2, 3...) and **columns** (vertical, lettered A, B, C...). The box where a row and column meet is a **cell**, named by its column and row, e.g. **B2**. With a spreadsheet you can:

- **Enter data** systematically (one record per row).
- **Calculate** totals, averages and percentages.
- **Sort** (arrange in order) and **filter** (show only some rows) records.
- **Create charts and graphs** automatically.

A **formula** always starts with = . A **range** such as B2:B4 means "cells B2 to B4".

Formula	What it does
=SUM(B2:B4)	Adds all values in B2 to B4.
=AVERAGE(B2:B4)	Mean: sum ÷ number of values.
=MAX(B2:B4) / =MIN(B2:B4)	Largest / smallest value.
=MEDIAN(B2:B4)	Middle value when sorted.
=COUNT(B2:B4)	Counts cells containing numbers.
=COUNTA(C2:C4)	Counts cells that are not empty (text or numbers).
=COUNTIF(C2:C4, "Yes")	Counts cells that match a condition.

WORKED EXAMPLE

Analysing the case-study spreadsheet. The data from the 6.8 case study (Step 8) is entered like this:

	A	B	C	D	E
1	Student	Hours	Study Use	Main Activity	Distracted?
2	1	3	Yes	Lectures	Sometimes
3	2	5	No	Social Media	Yes
4	3	2	Yes	Notes	No

Step 1 – Total hours: =SUM(B2:B4) → 3 + 5 + 2 = **10**.

Step 2 – Average hours: =AVERAGE(B2:B4) → 10 ÷ 3 = **3.33** hours (to 2 decimal places).

Step 3 – Most and least: =MAX(B2:B4) → **5**; =MIN(B2:B4) → **2**.

Step 4 – Median: sorted values 2, 3, 5 → middle = **3**. =MEDIAN(B2:B4) gives 3.

Step 5 – How many use the phone for study? =COUNTIF(C2:C4, "Yes") → **2**.

Step 6 – Percentage: =COUNTIF(C2:C4, "Yes")/COUNTA(C2:C4) → 2 ÷ 3 = 0.667; format the cell as % → **66.7%**.

Step 7 – How many said "Yes" to distracted? =COUNTIF(E2:E4, "Yes") → **1** (only "Yes" matches; "Sometimes" does not).

Step 8 – Sort: select the data → Data → Sort by column B (largest to smallest) → order becomes Student 2 (5), Student 1 (3), Student 3 (2).

6.7.2 Presentations

LEARN IT

Presentation software such as **PowerPoint**, **Google Slides** and **Canva** helps you explain findings to an **audience** in an organised way. Good practice:

- Begin with a clear **title** and the **research question**.
- Use **short bullet points** instead of long paragraphs.
- Include **tables, charts and key findings**.
- Keep the design **simple and readable** (large font, few colours).

Spreadsheets and presentations work together: you make a chart from the spreadsheet data and insert it into the slides.

Spreadsheet data → Chart / Graph → Insert → Slides

REMEMBER IT

Presentation rule of thumb: **one idea per slide**, and no more than about **six short bullet points**. If you are reading long sentences off the slide, the slide has too much text.

COMMON MISTAKE

Mistake: Typing a result by hand (e.g. writing "3.33" in a cell) instead of using a formula. If the data changes, the typed result becomes wrong. **Fix:** Always use formulas like =AVERAGE(B2:B4) so results update automatically. Also remember every formula must begin with =.

اردو میں سمجھیں

ڈیٹا جمع کرنے کے بعد اسے پیش کرنا بھی ضروری ہے۔ اسپریڈشیت (جیسے ایکسل اور گوگل شیٹس) میں ڈیٹا قطاروں اور کالموں میں ترتیب دیا جاتا ہے، اور =SUM() اور =AVERAGE() جیسے فارمولوں سے مجموعہ، اوسط اور فیصد نکالے جاتے ہیں۔ پریزنٹیشن سافٹ ویئر (جیسے پاور پوائنٹ) میں مختصر نکات، چارٹس اور سادہ ڈیزائن کے ساتھ نتائج سامعین کے سامنے پیش کیے جاتے ہیں۔

CHECK YOURSELF

1. Write the formula to find the average of cells D2 to D20.
2. Name three spreadsheet programs.
3. Give two rules for a good presentation.

Answers: 1. =AVERAGE(D2:D20) . 2. MS Excel, Google Sheets, Apple Numbers. 3. Any two: start with a clear title and research question; use short bullet points; include tables/charts/key findings; keep design simple and readable.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Write the formula to find the average of cells D2 to D20.

3 marks. Explain Presenting Data Using Digital Tools: 6.7.1 Spreadsheets and 6.7.2 Presentations with two clear points and one example.

5 marks. Write a 5-mark answer on Presenting Data Using Digital Tools: 6.7.1 Spreadsheets and 6.7.2 Presentations: definition, two points, a labelled diagram or table, and one example.

Answers: 1. =AVERAGE(D2:D20) 3. You must also present your findings so that others can understand them quickly and easily.; Digital tools make this much easier. 5. Use the recipe in the blue box. Model opening: Collecting data is only one part of the work.

BATCH HOMEWORK

Write a 5-mark answer on **Presenting Data Using Digital Tools: 6.7.1 Spreadsheets and 6.7.2 Presentations** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.7.3 – 6.7.4 Infographics and Reports

ACADEMY SESSION

Session 8 of 15 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: An infographic (information + graphic) is a visual way of presenting information, facts or data so that people can understand the main idea quickly and easily.

Error clinic: Mistake: Making a chart look more dramatic than the data – for example, starting the bar-chart axis at 18 instead of 0 so that 20 looks twice as big as 19.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Infographics and Reports**. Write: An infographic (information + graphic) is a visual way of presenting information, facts or data so that people can understand the main idea quickly and easily.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Highlight the most important findings and results. (2) Use clear visuals, limited text and accurate information. — + example.

5 marks: 3-mark structure + table: Situation / Best tool / Why + the worked example from this topic.

6.7.3 Infographics

LEARN IT

An **infographic** (information + graphic) is a **visual way** of presenting information, facts or data so that people can understand the main idea **quickly and easily**. Tools such as **Canva**, **Power BI** or **Tableau** can be used. A good infographic should:

- **Simplify** complex concepts.
- **Highlight** the most important findings and results.
- Use **clear visuals**, **limited text** and **accurate** information.

6.7.4 Reports

LEARN IT

Reports are **structured documents** used to present collected data, findings, analysis and conclusions. Tools like **MS Word** or **Google Docs** are standard. A good report should:

- Start with a clear **title**, **introduction** and **purpose**.
- Present the collected data using **tables or charts**.
- Explain findings in **simple language**.
- Include **conclusions and recommendations** based on the data.

Optional: you may use AI tools carefully to improve wording, but **always review for accuracy**. AI can make mistakes or invent facts, and you are responsible for what you submit.

LEARN IT

Visual rule of thumb: a good chart or infographic can explain complex data **faster** than a long paragraph. However, visuals must always be **accurate** and based strictly on the **real data collected** – never exaggerated.

WORKED EXAMPLE

Which tool should you choose?

Situation	Best tool	Why
You must calculate the average marks of 40 students.	Spreadsheet	Formulas calculate instantly.
You will explain results to the class in assembly.	Presentation	Designed for a live audience.
You want a one-page poster for the notice board.	Infographic	Main result understood at a glance.
The principal wants the full study with method and recommendations.	Report	Detailed, structured document.

REMEMBER IT

Match tool to job: **Spreadsheet = Calculate**, **Presentation = Tell**, **Infographic = Show quickly**, **Report = Explain fully**.

COMMON MISTAKE

Mistake: Making a chart look more dramatic than the data – for example, starting the bar-chart axis at 18 instead of 0 so that 20 looks twice as big as 19. **Fix:** Start bar-chart axes at 0, label axes, and show real numbers only.

انفوگرافک معلومات کو تصویری انداز میں پیش کرنے کا طریقہ ہے تاکہ اصل بات جلدی سمجھ آ جائے؛ اس کے لیے کینوا (Canva) اور پاور بی آئی (Power BI) جیسے ٹولز استعمال ہوتے ہیں۔ رپورٹ ایک منظم دستاویز ہے جس میں عنوان، تعارف، ڈیٹا، نتائج، اختتامیہ اور سفارشات شامل ہوتی ہیں۔ تصاویر اور چارٹس ہمیشہ اصل ڈیٹا کے مطابق اور درست ہونے چاہئیں، مبالغہ آمیز نہیں۔

CHECK YOURSELF

1. Name two tools for making infographics.
2. What must you always do if you use AI to improve your report's wording?
3. What should a report end with?

Answers: 1. Any two: Canva, Power BI, Tableau. 2. Review it carefully for accuracy. 3. Conclusions and recommendations based on the data.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name two tools for making infographics.

3 marks. Explain Infographics and Reports with two clear points and one example.

5 marks. Write a 5-mark answer on Infographics and Reports: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Any two: Canva, Power BI, Tableau 3. Highlight the most important findings and results.; Use clear visuals, limited text and accurate information. 5. Use the recipe in the blue box. Model opening: An infographic (information + graphic) is a visual way of presenting information, facts or data so that people can understand the main idea quickly and easily.

BATCH HOMEWORK

Write a 5-mark answer on **Infographics and Reports** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.8 Case Study: Digital Inquiry Project ★ Golden

ACADEMY SESSION

Session 9 of 15 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: This case study shows how to apply all the ideas of this chapter to solve a real-world problem from start to finish.

Exam wording to train: Expect a long question: "Describe the steps of a digital inquiry project using the example of mobile phone use." Write the research question first, then the 12...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Case Study: Digital Inquiry Project**. Write: This case study shows how to apply all the ideas of this chapter to solve a real-world problem from start to finish.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) An inquiry is an investigation to find the answer to a question. (2) Research question: "How does daily mobile phone use affect the study habits of students?" Scenario: Students notice classmates using phones... — + example.

5 marks: 3-mark structure + table: Workflow stage / Steps + the worked example from this topic.

8–10 marks: 5-mark structure + the full comparison table with every cell filled + a one-line conclusion. Method marks are awarded for working.

LEARN IT

This case study shows how to apply **all** the ideas of this chapter to solve a real-world problem from start to finish. An **inquiry** is an investigation to find the answer to a question.

Research question: "How does daily mobile phone use affect the study habits of students?"

Scenario: Students notice classmates using phones during free periods and while studying. Some say phones **help** them learn; others say phones **waste time**. The class must investigate whether phone use helps or harms study habits.

The digital inquiry workflow

1 Question → 2 Search → 3 Collect → 4 Analyse → 5 Create

The project is carried out in **12 steps** that fit into this five-stage workflow:

Workflow stage	Steps
Question & Search	1 Advanced searches · 2 Identify data types · 3 Select methods
Collect	4 Prepare the survey · 5 Choose the sample · 6 Collect primary data ethically · 7 Use secondary data
Analyse	8 Organise in a spreadsheet · 9 Create charts · 10 Analyse results
Create	11 Write the conclusion · 12 Recommendations → final digital artefact

REMEMBER IT

Workflow in five words: **Ask → Search → Collect → Analyse → Create**. Every research project you ever do will follow this pattern.

اردو میں سمجھیں

اس کیس اسٹڈی میں تحقیقی سوال یہ ہے: "روزانہ موبائل فون کا استعمال طلبہ کی پڑھائی کی عادات پر کیسے اثر ڈالتا ہے؟" تحقیق پانچ مراحل میں ہوتی ہے: سوال، تلاش، ڈیٹا جمع کرنا، تجزیہ اور آخری پروڈکٹ بنانا۔ یہ کام بارہ قدموں میں مکمل کیا جاتا ہے۔

EXAM TIP

Expect a long question: "Describe the steps of a digital inquiry project using the example of mobile phone use." Write the research question first, then the 12 steps with one or two lines each, and finish with the artefact. Learn the five-stage workflow as your skeleton.

CHECK YOURSELF

1. What is the research question in the case study?
2. Name the five stages of the digital inquiry workflow.

Answers: 1. "How does daily mobile phone use affect the study habits of students?" 2. Question, Search, Collect, Analyse, Create.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is the research question in the case study?

3 marks. Explain Case Study: Digital Inquiry Project with two clear points and one example.

5 marks. Expect a long question: "Describe the steps of a digital inquiry project using the example of mobile phone use." Write the research question first, then the 12 steps with one or two lines each, and...

8 marks. Case Study: Digital Inquiry Project: 5-mark answer plus the full comparison table with every cell filled.

Answers: 1. "How does daily mobile phone use affect the study habits of students?" 3. An inquiry is an investigation to find the answer to a question.; Research question: "How does daily mobile phone use affect the study habits of students?" Scenario: Students notice classmates using phones... 5. Use the recipe in the blue box. Model opening: This case study shows how to apply all the ideas of this chapter to solve a real-world problem from start to finish. 8. Same 5-mark body + the full comparison table with every cell filled + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Case Study: Digital Inquiry Project** using the recipe in this topic. Include the full comparison table with every cell filled. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.8 Steps 1 – 3: Advanced Search and Methodology ★ Golden

ACADEMY SESSION

Session 10 of 15 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Students first search for background information using search engines (such as Google or Bing).

Error clinic: Mistake: Assuming the first search result is the most reliable.

Exam wording to train: "Explain any three advanced search operators with examples" is a likely short question.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Steps 1 – 3: Advanced Search and Methodology**. Write: Students first search for background information using search engines (such as Google or Bing).

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) They use advanced search operators – special symbols or words typed into the search box – to narrow down results and find reliable... (2) Suggested queryOperator usedWhat it does "mobile phone use" "study habits" students" " (quotes)Finds the exact phrases "mobile phone use"... — + example.

5 marks: 3-mark structure + table: Suggested query / Operator used / What it does + the worked example from this topic.

8–10 marks: 5-mark structure + a four-row comparison table and one rewritten survey question + a one-line conclusion. Method marks are awarded for working.

The **methodology** is the plan of methods a researcher uses to answer the question.

Step 1: Perform advanced searches

LEARN IT

Students first search for **background information** using search engines (such as Google or Bing). They use **advanced search operators** – special symbols or words typed into the search box – to **narrow down** results and find **reliable secondary data**.

Suggested query	Operator used	What it does
"mobile phone use" "study habits" students	" " (quotes)	Finds the exact phrases "mobile phone use" and "study habits", not the words scattered randomly.
"academic performance" filetype:pdf	filetype:	Finds only PDF documents (often official reports and research papers).
digital distraction site:.edu	site:	Searches only educational websites (addresses ending in .edu).

Other useful operators (background): - (minus) excludes a word, e.g. phone addiction -game; OR finds either word, e.g. smartphone OR mobile; site:.gov.pk searches only Pakistani government websites.

LEARN IT

Source evaluation checklist. Before trusting a source, ask:

- | | |
|---|--|
| ☐ Is the author/organisation clearly mentioned? | ☐ Is the information recent ? |
| ☐ Is the website reliable (.edu, .gov, research-based)? | ☐ Does the source provide facts/references , or is it biased (one-sided, trying to sell something)? |

WORKED EXAMPLE

Building a search query step by step. You want official PDF reports about screen time of students on Pakistani government websites.

Step 1 – Plain search: `screen time students` → millions of results, many blogs and adverts.

Step 2 – Exact phrase: `"screen time" students` → results must contain the exact phrase.

Step 3 – Only PDFs: `"screen time" students filetype:pdf` → mostly reports and papers.

Step 4 – Only government sites: `"screen time" students filetype:pdf site:.gov.pk` → a small number of highly relevant, reliable results.

Step 5 – Evaluate: open a result and check the checklist: author named? year recent? references given?

Step 2: Identify data types

LEARN IT

Students decide what kind of **primary data** they will collect:

- **Quantitative:** number of hours used daily; percentage who feel distracted.
- **Qualitative:** opinions on why they get distracted; suggestions for better use.

Step 3: Select data-collection methods

LEARN IT

Because they need to ask the **same questions to many students**, a **survey/questionnaire** (via Google Forms or on paper) is the **most efficient** method. Interviews would take too long for so many people, and observation could not reveal opinions.

REMEMBER IT

Three operators, three jobs: `" "` = **exact**, `filetype:` = **format**, `site:` = **where**. Note: there is **no space** after the colon (`site:.edu`, not `site: .edu`).

COMMON MISTAKE

Mistake: Assuming the first search result is the most reliable. Search results can be adverts or popular blogs.
Fix: Always apply the source evaluation checklist. A website ending in `.edu` or `.gov` is usually more reliable, but you should still check the date and author.

اردو میں سمجھیں

پہلے قدم میں طلبہ سرچ انجن پر جدید سرچ آپریٹرز (Advanced Search Operators) استعمال کرتے ہیں: کوئیشن مارکس (" ") بالکل وہی جملہ تلاش کرتے ہیں، `filetype:pdf` صرف پی ڈی ایف فائلیں اور `site:.edu` صرف تعلیمی ویب سائٹس دکھاتا ہے۔ ہر ذریعے کو مصنف، تاریخ، قابل اعتماد ویب سائٹ اور حوالوں کی بنیاد پر پرکھا جاتا ہے۔ پھر ڈیٹا کی اقسام طے کی جاتی ہیں اور بہت سے طلبہ سے سوال کرنے کے لیے سروے کو بہترین طریقہ چنا جاتا ہے۔

EXAM TIP

"Explain any three advanced search operators with examples" is a likely short question. For each, write the operator, an example query, and what it does. Also learn the four-point source evaluation checklist.

CHECK YOURSELF

1. Write a query that finds the exact phrase "online learning" only on educational websites.
2. Why was a survey chosen in Step 3?
3. Give one quantitative and one qualitative data item from Step 2.

Answers: 1. "online learning" site:.edu . 2. Because the same questions had to be asked to many students, and a survey is the most efficient way to do that. 3. Quantitative: hours used daily (or % who feel distracted). Qualitative: opinions on why they get distracted (or suggestions for better use).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Write a query that finds the exact phrase "online learning" only on educational websites.

3 marks. Explain Steps 1 – 3: Advanced Search and Methodology with two clear points and one example.

5 marks. "Explain any three advanced search operators with examples" is a likely short question. For each, write the operator, an example query, and what it does. Also learn the four-point source evaluation...

8 marks. Steps 1 – 3: Advanced Search and Methodology: 5-mark answer plus a four-row comparison table and one rewritten survey question.

Answers: 1. "online learning" site:.edu 3. They use advanced search operators – special symbols or words typed into the search box – to narrow down results and find reliable...; Suggested queryOperator usedWhat it does "mobile phone use" "study habits" students" " (quotes)Finds the... 5. Use the recipe in the blue box. Model opening: Students first search for background information using search engines (such as Google or Bing). 8. Same 5-mark body + a four-row comparison table and one rewritten survey question + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Steps 1 – 3: Advanced Search and Methodology** using the recipe in this topic. Include a four-row comparison table and one rewritten survey question. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.8 Steps 4 – 6: Survey Preparation and Primary Data Collection ★ Golden

ACADEMY SESSION

Session 11 of 15 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Design clear, unbiased questions.

Error clinic: Mistake: Thinking a bigger sample is always enough.

Exam wording to train: Questions often ask: "What ethical guidelines should be followed when collecting data?" List all five points.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Steps 4 – 6: Survey Preparation and Primary Data Collection**. Write: Design clear, unbiased questions.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Design clear, unbiased questions. (2) Each question is linked to the type of data it produces: QuestionType of data How many hours do you use your phone daily?Quantitative Which... — + example.

5 marks: 3-mark structure + table: Question / Type of data + the worked example from this topic.

8–10 marks: 5-mark structure + a four-row comparison table and one rewritten survey question + a one-line conclusion. Method marks are awarded for working.

Step 4: Prepare the survey

LEARN IT

Design **clear, unbiased** questions. Each question is linked to the type of data it produces:

Question	Type of data
How many hours do you use your phone daily?	Quantitative
Which activity do you use your phone for the most?	Quantitative (categories)
How does your phone help you in studies?	Qualitative
Suggest one way to use phones responsibly.	Qualitative

Step 5: Choose the sample

LEARN IT

The **sample** is the group of people who provide the data. It is usually impossible to ask everyone (the whole **population**), so a smaller group is chosen. The students decide to survey **40 Class XI students from different sections** to get a **representative** mix of habits. "Representative" means the sample looks like the whole group – it includes different kinds of students, not just your friends.

Step 6: Collect primary data (ethically)

LEARN IT

Ethics means doing what is morally right. When conducting the survey, students must follow strict ethical guidelines:

- Ask **permission** before collecting responses (**consent**).
- Avoid collecting **sensitive personal information**.
- Do **not record names** unless absolutely necessary (**anonymity**).
- Keep the responses **private**.
- Use the data **only for educational purposes**.

WORKED EXAMPLE

Why "different sections" matters. Suppose the group surveyed only the 40 students of the Pre-Engineering section who sit in the front rows.

Problem: these students might study more than average, so the results would show less phone distraction than is true for the whole class.

Fix: pick students from every section (e.g. 10 each from Pre-Medical, Pre-Engineering, Computer Science and Commerce). Now the sample better represents all Class XI students.

Ethical opening text for the form: "This survey is for a class project on phone use and study habits. It is anonymous – do not write your name. Your answers will be kept private and used only for this project. Do you agree to take part? ☐ Yes ☐ No"

REMEMBER IT

Ethics in five words: **Consent, No-Sensitive, Anonymous, Private, Educational** – "C-NAPE". Think: "Cover the person's nape (neck) – protect them."

COMMON MISTAKE

Mistake: Thinking a bigger sample is always enough. A sample of 200 students all from one section is still biased. **Fix:** A sample must be **representative**, not just large.

اردو میں سمجھیں

چوتھے قدم میں واضح اور غیر جانبدار سوالات تیار کیے جاتے ہیں۔ پانچویں قدم میں نمونہ (Sample) چنا جاتا ہے: مختلف سیکشنز کے چالیس طلبہ تاکہ نتائج پوری جماعت کی نمائندگی کریں۔ چھٹے قدم میں اخلاقی اصولوں کے ساتھ ڈیٹا جمع کیا جاتا ہے: اجازت لیں، حساس معلومات نہ لیں، نام نہ لکھیں (گمنامی)، جوابات کو راز میں رکھیں اور صرف تعلیمی مقصد کے لیے استعمال کریں۔

EXAM TIP

Questions often ask: "What ethical guidelines should be followed when collecting data?" List all five points. Use the words **consent** and **anonymity** – examiners look for them. You may also be asked to classify the four survey questions by data type.

CHECK YOURSELF

1. What is a sample?
2. What does anonymity mean in a survey?
3. What type of data does "Suggest one way to use phones responsibly" give?

Answers: 1. The group of people who provide the data. 2. Not recording the names of participants (unless absolutely necessary). 3. Qualitative.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is a sample?

3 marks. Explain Steps 4 – 6: Survey Preparation and Primary Data Collection with two clear points and one example.

5 marks. Questions often ask: "What ethical guidelines should be followed when collecting data?" List all five points. Use the words consent and anonymity – examiners look for them. You may also be asked to...

8 marks. Steps 4 – 6: Survey Preparation and Primary Data Collection: 5-mark answer plus a four-row comparison table and one rewritten survey question.

Answers: 1. The group of people who provide the data 3. Design clear, unbiased questions.; Each question is linked to the type of data it produces: QuestionType of data How many hours do you use your phone daily?Quantitative Which... 5. Use the recipe in the blue box. Model opening: Design clear, unbiased questions. 8. Same 5-mark body + a four-row comparison table and one rewritten survey question + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Steps 4 – 6: Survey Preparation and Primary Data Collection** using the recipe in this topic. Include a four-row comparison table and one rewritten survey question. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.8 Steps 7 – 9: Secondary Data and Spreadsheet Organisation ★ Golden

ACADEMY SESSION

Session 12 of 15 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Students include a reliable online article stating that "excessive screen time lowers concentration." They will compare this secondary data with their own primary survey results.

Error clinic: Mistake: Using overlapping groups like "1–3" and "3–5": a student who uses the phone for exactly 3 hours could be counted twice or put in the wrong bar.

Exam wording to train: You may get the spreadsheet table and be asked to "write formulas to find the total and average hours" or "count students who use the phone for study".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Steps 7 – 9: Secondary Data and Spreadsheet Organisation**. Write: Students include a reliable online article stating that "excessive screen time lowers concentration." They will compare this secondary data with their own primary survey results.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) If both agree, the conclusion is stronger. (2) If they disagree, the students must think about why (for example, a different age group or country). — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a four-row comparison table and one rewritten survey question + a one-line conclusion. Method marks are awarded for working.

Step 7: Use secondary data

LEARN IT

Students include a reliable online article stating that "**excessive screen time lowers concentration.**" They will **compare** this secondary data with their own primary survey results. If both agree, the conclusion is stronger. If they disagree, the students must think about why (for example, a different age group or country).

Step 8: Organise data in a spreadsheet

LEARN IT

Responses are entered into **MS Excel** or **Google Sheets** to **sort, calculate totals** and **find averages**. Each row is one student; each column is one question.


Student	Hours	Study Use	Main Activity	Distracted?
1	3	Yes	Lectures	Sometimes
2	5	No	Social Media	Yes
3	2	Yes	Notes	No

(The full sheet has 40 rows, one per student. The formulas for this table are worked out in topic 6.7.1.)

Step 9: Create charts and graphs

LEARN IT

The spreadsheet data is converted into **visuals** to make it easy to digest. In the source, the "Daily Phone Use (Hours)" bar chart groups the 40 students into three bars: 1–3 hrs, 3–5 hrs and 5+ hrs, with the 3–5 hrs bar the tallest.



Bar chart of daily phone use for 40 students. The counts (12, 21, 7) are estimated from the bar heights in the source chart.

WORKED EXAMPLE

Making the chart in Google Sheets.

Step 1 – Count each group. If the hours are in B2:B41, use `=COUNTIF(B2:B41, "<3")` for under 3 hrs, `=COUNTIFS(B2:B41, ">=3", B2:B41, "<5")` for 3 to under 5 hrs, and `=COUNTIF(B2:B41, ">=5")` for 5 hrs or more. (This gives non-overlapping groups.)

Step 2 – Check the total. $12 + 21 + 7 = 40$ ✓ – every student is counted exactly once.

Step 3 – Percentages. $12 \div 40 = 30\%$; $21 \div 40 = 52.5\%$; $7 \div 40 = 17.5\%$. Total = 100% ✓.

Step 4 – Insert chart. Select the group labels and counts → Insert → Chart → choose *Column chart*. Add the title "Daily Phone Use (Hours)" and label the axes.

Step 5 – Choose the right chart. Bar/column chart to compare groups; pie chart to show parts of a whole (e.g. % in each group); line chart to show change over time.

REMEMBER IT

Chart chooser: **Bar = Compare**, **Pie = Parts of a whole**, **Line = Change over time**.

COMMON MISTAKE

Mistake: Using overlapping groups like "1–3" and "3–5": a student who uses the phone for exactly 3 hours could be counted twice or put in the wrong bar. **Fix:** Define groups clearly, e.g. "under 3", "3 to under 5", "5 or more", and check that the group counts add up to the sample size.

اردو میں سمجھیں

ساتویں قدم میں ایک قابلِ اعتماد آن لائن مضمون کا ثانوی ڈیٹا ("زیادہ اسکرین ٹائم توجہ کم کرتا ہے") اپنے سروے کے بنیادی ڈیٹا سے موازنہ کرنے کے لیے لیا جاتا ہے۔ آٹھویں قدم میں جوابات ایکسل یا گوگل شیٹس میں درج کر کے ترتیب، مجموعہ اور اوسط نکالی جاتی ہے۔ نویں قدم میں اسپریڈشیٹ کے ڈیٹا سے چارٹ اور گراف بنائے جاتے ہیں تاکہ نتائج آسانی سے سمجھ آئیں۔

EXAM TIP

You may get the spreadsheet table and be asked to "write formulas to find the total and average hours" or "count students who use the phone for study". Write the full formula with =, the correct range, and the result.

CHECK YOURSELF

1. What is the secondary data used in Step 7?
2. Which formula counts how many students answered "Yes" in column C, rows 2 to 41?
3. Which type of chart is best for comparing the three hour-groups?

Answers: 1. A reliable online article stating "excessive screen time lowers concentration". 2. =COUNTIF(C2:C41, "Yes") . 3. A bar (column) chart.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is the secondary data used in Step 7?

3 marks. Explain Steps 7 – 9: Secondary Data and Spreadsheet Organisation with two clear points and one example.

5 marks. You may get the spreadsheet table and be asked to "write formulas to find the total and average hours" or "count students who use the phone for study". Write the full formula with =, the correct...

8 marks. Steps 7 – 9: Secondary Data and Spreadsheet Organisation: 5-mark answer plus a four-row comparison table and one rewritten survey question.

Answers: 1. A reliable online article stating "excessive screen time lowers concentration" 3. If both agree, the conclusion is stronger.; If they disagree, the students must think about why (for example, a different age group or country). 5. Use the recipe in the blue box. Model opening: Students include a reliable online article stating that "excessive screen time lowers concentration." They will compare this secondary data with their own... 8. Same 5-mark body + a four-row comparison table and one rewritten survey question + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Steps 7 – 9: Secondary Data and Spreadsheet Organisation** using the recipe in this topic. Include a four-row comparison table and one rewritten survey question. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.8 Steps 10 – 12: Data Analysis, Conclusion and Recommendations ★ Golden

ACADEMY SESSION

Session 13 of 15 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: To analyse means to study the data carefully to find patterns and trends.

Error clinic: Mistake: Writing a conclusion that is not based on the data, e.g.

Exam wording to train: You may be asked to "write a conclusion and two recommendations" for given data.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Steps 10 – 12: Data Analysis, Conclusion and Recommendations**. Write: To analyse means to study the data carefully to find patterns and trends.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Half use it for educational purposes (lectures/notes). (2) A clear trend: students who use phones mostly for entertainment report much higher distraction levels than those who use them for study. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

8–10 marks: 5-mark structure + full working plus a one-line conclusion + a one-line conclusion. Method marks are awarded for working.

Step 10: Analyse the results

LEARN IT

To **analyse** means to study the data carefully to find **patterns** and **trends**. By looking at the spreadsheet and charts, the group identifies:

- **Most students** (the majority) use phones for **3–5 hours daily**.
- **Half** use it for **educational purposes** (lectures/notes).
- **A clear trend:** students who use phones mostly for **entertainment** report much **higher distraction** levels than those who use them for study.

Step 11: Write the conclusion

LEARN IT

A **conclusion** answers the research question using the evidence:

"The research shows mobile phones have both positive and negative effects. They provide access to learning materials. However, excessive use of social media and gaming reduces concentration. Therefore, phones should not be banned, but managed wisely."

Step 12: Recommendations

LEARN IT

Recommendations are practical suggestions based on the data. The students recommend:

- Turn off **social media notifications** while studying.
- Set **daily screen-time limits**.
- Take **physical breaks** from screens to protect health.

WORKED EXAMPLE

From numbers to a finding. Using the estimated chart counts (12, 21, 7 out of 40):

Step 1: $21 \div 40 = 52.5\%$. Since $52.5\% > 50\%$, the statement "most students use phones for 3–5 hours" is supported.

Step 2: "Half use it for educational purposes" means about 20 of the 40 students chose Lectures or Notes as their main activity ($20 \div 40 = 50\%$). Formula: `=COUNTIF(D2:D41, "Lectures")+COUNTIF(D2:D41, "Notes")`.

Step 3 – Compare groups: filter the sheet to show only Social Media/Games users and count how many said "Yes" to distracted; then do the same for Lectures/Notes users. If the entertainment group has a much higher share of "Yes", that is the trend.

Step 4 – Link to secondary data: the article said excessive screen time lowers concentration; the survey agrees, so the conclusion is stronger.

REMEMBER IT

Conclusion formula: "**The data shows ... However ... Therefore ...**" – state the main finding, mention the other side, then give the overall answer.

COMMON MISTAKE

Mistake: Writing a conclusion that is not based on the data, e.g. "Phones should be banned" when the data showed phones also help learning. **Fix:** Every sentence in the conclusion and recommendations must be supported by your findings. Also, a trend between two things (entertainment use and distraction) shows a *link*; be careful before claiming one definitely *causes* the other.

اردو میں سمجھیں

دسویں قدم میں چارٹس اور اسپریڈشیٹ سے رجحانات تلاش کیے جاتے ہیں: زیادہ تر طلبہ روزانہ تین سے پانچ گھنٹے فون استعمال کرتے ہیں، نصف اسے تعلیم کے لیے استعمال کرتے ہیں، اور تفریح کے لیے استعمال کرنے والے زیادہ توجہ بٹنے کی شکایت کرتے ہیں۔ گیارہویں قدم میں نتیجہ لکھا جاتا ہے کہ فون پر پابندی نہیں بلکہ اس کا دانشمندانہ استعمال ہونا چاہیے۔ بارہویں قدم میں سفارشات دی جاتی ہیں: پڑھائی کے دوران نوٹیفکیشن بند کریں، اسکرین ٹائم کی حد مقرر کریں اور وقفے لیں۔

EXAM TIP

You may be asked to "write a conclusion and two recommendations" for given data. Use the "shows ... however ... therefore" pattern and make sure each recommendation follows from a finding.

CHECK YOURSELF

1. According to Step 10, which group reported higher distraction?
2. Should phones be banned according to the conclusion?
3. Give two of the students' recommendations.

Answers: 1. Students who use phones mostly for entertainment. 2. No – they should not be banned but managed wisely. 3. Any two: turn off social media notifications while studying; set daily screen-time limits; take physical breaks from screens.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. According to Step 10, which group reported higher distraction?

3 marks. Explain Steps 10 – 12: Data Analysis, Conclusion and Recommendations with two clear points and one example.

5 marks. You may be asked to "write a conclusion and two recommendations" for given data. Use the "shows ... however ... therefore" pattern and make sure each recommendation follows from a finding.

8 marks. Steps 10 – 12: Data Analysis, Conclusion and Recommendations: 5-mark answer plus full working plus a one-line conclusion.

Answers: 1. Students who use phones mostly for entertainment. 3. Half use it for educational purposes (lectures/notes).; A clear trend: students who use phones mostly for entertainment report much higher distraction levels than those who use them for study. 5. Use the recipe in the blue box. Model opening: To analyse means to study the data carefully to find patterns and trends. 8. Same 5-mark body + full working plus a one-line conclusion + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Steps 10 – 12: Data Analysis, Conclusion and Recommendations** using the recipe in this topic. Include full working plus a one-line conclusion. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.8 The Final Digital Artefact ★ Golden

ACADEMY SESSION

Session 14 of 15 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A digital artefact is a final product created using digital technologies.

Error clinic: Mistake: Spending all your time on colours and animations and forgetting evidence.

Exam wording to train: Learn the four artefact options with tools and purpose (a table question), and the ten-part structure in order.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **The Final Digital Artefact**. Write: A digital artefact is a final product created using digital technologies.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Students must create one final artefact that answers the original research question. (2) It is not just a decorated file; it must present evidence and conclusions. — + example.

5 marks: 3-mark structure + table: Artefact option / Suitable digital tools / Main purpose + the worked example from this topic.

8–10 marks: 5-mark structure + a four-row comparison table and one rewritten survey question + a one-line conclusion.

Method marks are awarded for working.

LEARN IT

A **digital artefact** is a final product created using digital technologies. Students must create **one final artefact** that answers the original research question. It is **not just a decorated file**; it must present **evidence** and **conclusions**.

Artefact option	Suitable digital tools	Main purpose
Digital Report	MS Word, Google Docs	Explain the full study in a structured text document.
Presentation	PowerPoint, Canva, Slides	Share key findings with a live audience.
Infographic	Canva, Adobe Express	Show the main results visually and quickly on one page.
Dashboard	Power BI, Tableau	Explore data through interactive charts and filters.

A **dashboard** is an interactive screen of charts; the viewer can click filters (e.g. "show only Commerce students") and the charts update.

Standard artefact structure

1. Title
2. Research Question
3. Introduction
4. Method of Data Collection
5. Primary Data Findings
6. Secondary Data Summary
7. Charts and Graphs
8. Conclusion
9. Recommendations
10. References

WORKED EXAMPLE

Planning a 10-slide presentation artefact for the phone study (one slide per structure item):

Slide 1 Title: "Phones and Study Habits – Class XI Survey". **Slide 2** Research question. **Slide 3** Introduction: why the class investigated this. **Slide 4** Method: Google Form survey, 40 students, different sections, anonymous with consent. **Slide 5** Primary findings: 52.5% use phones 3–5 hours; half use for study. **Slide 6** Secondary data: article on screen time and concentration. **Slide 7** The bar chart of daily phone use. **Slide 8** Conclusion: "manage wisely, don't ban". **Slide 9** Three recommendations. **Slide 10** References: the article's title, author, website and date.

REMEMBER IT

The structure follows the inquiry itself: **What** (title, question, intro) → **How** (method) → **Found** (primary, secondary, charts) → **So what** (conclusion, recommendations) → **Credit** (references).

COMMON MISTAKE

Mistake: Spending all your time on colours and animations and forgetting evidence. **Fix:** An artefact is judged on whether it answers the research question with evidence. Also never skip **References** – listing your secondary sources is honest and avoids plagiarism.

اردو میں سمجھیں

ڈیجیٹل آرٹیفیکٹ (Digital Artefact) ڈیجیٹل ٹیکنالوجی سے بنائی گئی آخری پروڈکٹ ہے جو تحقیقی سوال کا جواب ثبوت اور نتائج کے ساتھ پیش کرتی ہے؛ یہ صرف سچی ہوئی فائل نہیں۔ اس کی چار صورتیں ہیں: رپورٹ، پریزنٹیشن، انفوگرافک اور ڈیش بورڈ۔ معیاری ساخت میں عنوان، تحقیقی سوال، تعارف، طریقہ کار، بنیادی و ثانوی ڈیٹا، چارٹس، نتیجہ، سفارشات اور حوالہ جات شامل ہیں۔

EXAM TIP

Learn the four artefact options with tools and purpose (a table question), and the ten-part structure in order. "What is a digital artefact?" – stress that it must present **evidence and conclusions**, not just decoration.

CHECK YOURSELF

1. Which artefact lets viewers explore data with interactive filters?
2. What is the last item in the standard artefact structure?
3. Name two tools for making an infographic artefact.

Answers: 1. A dashboard (Power BI, Tableau). 2. References. 3. Canva and Adobe Express.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which artefact lets viewers explore data with interactive filters?

3 marks. Explain The Final Digital Artefact with two clear points and one example.

5 marks. Learn the four artefact options with tools and purpose (a table question), and the ten-part structure in order. "What is a digital artefact?" – stress that it must present evidence and conclusions,...

8 marks. The Final Digital Artefact: 5-mark answer plus a four-row comparison table and one rewritten survey question.

Answers: 1. A dashboard (Power BI, Tableau) 3. Students must create one final artefact that answers the original research question.; It is not just a decorated file; it must present evidence and conclusions. 5. Use the recipe in the blue box. Model opening: A digital artefact is a final product created using digital technologies. 8. Same 5-mark body + a four-row comparison table and one rewritten survey question + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **The Final Digital Artefact** using the recipe in this topic. Include a four-row comparison table and one rewritten survey question. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Careers in Digital Research

ACADEMY SESSION

Session 15 of 15 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The skills in this chapter lead to real jobs: CareerWhat they doChapter skill used Market Research AnalystDesigns surveys to collect primary data to guide business decisions.Surveys, primary data UX...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Careers in Digital Research**. Write: The skills in this chapter lead to real jobs: CareerWhat they doChapter skill used Market Research AnalystDesigns surveys to collect primary data to guide business decisions.Surveys, primary data UX...

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The skills in this chapter lead to real jobs: CareerWhat they doChapter skill used Market Research AnalystDesigns surveys to collect... (2) Second distinct point (not a repeat of the definition) — + example.

5 marks: 3-mark structure + table: Career / What they do / Chapter skill used + the worked example from this topic.

LEARN IT

The skills in this chapter lead to real jobs:

Career	What they do	Chapter skill used
Market Research Analyst	Designs surveys to collect primary data to guide business decisions.	Surveys, primary data
UX (User Experience) Researcher	Gathers qualitative and quantitative data to improve app and website designs.	Prototypes, interviews, observation
Data Journalist	Uses advanced search skills to research stories and presents them via infographics.	Advanced search, infographics
Digital Marketing Specialist	Collects audience data and presents results through dashboards and reports.	Dashboards, reports

WORKED EXAMPLE

A day for a UX researcher. A Karachi food-delivery app wants to redesign its checkout. The UX researcher (1) builds a clickable **prototype**, (2) **observes** 8 users trying it and counts how many seconds each takes (quantitative), (3) **interviews** them about what confused them (qualitative), and (4) presents a short **report** with recommendations to the design team.

REMEMBER IT

Link each career to one tool: Market Researcher → **Survey**; UX Researcher → **Prototype**; Data Journalist → **Search + Infographic**; Digital Marketer → **Dashboard**.

اردو میں سمجھیں

اس باب کی مہارتوں سے کئی کیریئر بنتے ہیں: مارکیٹ ریسرچ اینالسٹ کاروباری فیصلوں کے لیے سروے بناتا ہے، یو ایکس (UX) ریسرچر ایپس اور ویب سائٹس بہتر بنانے کے لیے ڈیٹا جمع کرتا ہے، ڈیٹا جرنلسٹ جدید سرچ اور انفوگرافکس استعمال کرتا ہے، اور ڈیجیٹل مارکیٹنگ اسپیشلسٹ ڈیش بورڈز اور رپورٹس کے ذریعے نتائج پیش کرتا ہے۔

CHECK YOURSELF

1. Which career designs surveys to guide business decisions?
2. What does UX stand for?

Answers: 1. Market Research Analyst. 2. User Experience.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which career designs surveys to guide business decisions?

3 marks. Explain Careers in Digital Research with two clear points and one example.

5 marks. Write a 5-mark answer on Careers in Digital Research: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Market Research Analyst 3. The skills in this chapter lead to real jobs: CareerWhat they doChapter skill used
Market Research AnalystDesigns surveys to collect... 5. Use the recipe in the blue box. Model opening: The skills in this chapter lead to real jobs: CareerWhat they doChapter skill used Market Research AnalystDesigns surveys to collect primary data to guide...

BATCH HOMEWORK

Write a 5-mark answer on **Careers in Digital Research** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Chapter 6 Review

Chapter summary

- **Digital literacy** is the ability to understand and use digital devices, the internet and online tools safely, effectively and responsibly – not just using devices, but finding, evaluating and creating information.
- In the **Information Age**, access to technology is not enough; digital literacy needs technical, cognitive and social abilities.
- **Qualitative data** is descriptive and non-numerical (opinions, reasons, behaviour) and explains why/how.
- **Quantitative data** is numerical, countable or measurable (hours, scores, percentages) and is used for comparing and charting.
- The five **data-collection strategies** are interviews, surveys, prototypes, observation and simulations.
- **Interviews** are planned conversations giving mostly qualitative data; **surveys** ask the same questions to many people, on paper or with Google/Microsoft Forms.
- Good survey questions are clear, short, unbiased and ask about one thing; avoid leading, double-barrelled, vague and overlapping questions.
- A **prototype** is an early version tested for feedback; **observation** records what happens without asking questions; a **simulation** is a computer model used when real experiments are costly, risky or difficult.
- **Primary data** is collected first-hand (high control); **secondary data** was collected by others and reused (limited control).
- Designing a data-collection approach has eight steps: question, data type, method, sample, tools, collect, store with backup, and ethics (consent is mandatory).
- **Spreadsheets** organise and calculate (e.g. `=SUM()`, `=AVERAGE()`, `=COUNTIF()`); **presentations** deliver to an audience; **infographics** give quick visual summaries; **reports** give detailed structure.
- Visuals must always be accurate and based strictly on real data, never exaggerated.
- **Advanced search operators** such as `" "`, `filetype:pdf` and `site:.edu` help find reliable sources efficiently; sources must be evaluated for author, date, reliability and bias.
- **Ethics:** get consent, avoid sensitive information, keep anonymity, keep responses private, and use data only for educational purposes.
- The **digital inquiry project** follows Question → Search → Collect → Analyse → Create in 12 steps.
- A **digital artefact** (report, presentation, infographic or dashboard) answers the research question using evidence and visuals, following a ten-part structure ending in references.

Key terms

Term	Meaning	اردو
Digital literacy	Ability to understand and use digital devices, the internet and online tools safely, effectively and responsibly.	ڈیجیٹل خواندگی
Information Age	Period in which vast amounts of data are produced, shared and accessed instantly.	معلوماتی دور
Data	Facts, numbers, words or observations collected for study.	مواد / ڈیٹا
Qualitative data	Descriptive, non-numerical data about thoughts, feelings and experiences.	کیفیتی ڈیٹا
Quantitative data	Numerical data that can be counted or measured.	مقداری ڈیٹا
Interview	Planned conversation to gather information directly from a person or small group.	انٹرویو / بالمشافہ گفتگو
Survey / Questionnaire	Same set of questions asked to many people.	سروے / سوالنامہ
Prototype	Simple early version of a product used to test an idea and get feedback.	ابتدائی نمونہ
Observation	Watching and recording what happens without asking questions.	مشاہدہ
Simulation	Computer-based model of a real situation in which variables can be changed.	نقلی ماڈل (سمیولیشن)
Variable	A factor that can be changed or measured.	متغیر
Primary data	Data collected first-hand by the researcher for a specific purpose.	بنیادی ڈیٹا
Secondary data	Data already collected by someone else and reused for a new purpose.	ثانوی ڈیٹا
Research question	The clear question an investigation tries to answer.	تحقیقی سوال
Sample	The group of people who provide the data.	نمونہ
Representative sample	A sample that reflects the mix of the whole group.	نمائندہ نمونہ
Consent	Permission given by a person before their data is collected.	رضامندی / اجازت

Term	Meaning	اردو
Anonymity	Not recording people's names so they cannot be identified.	گمنامی
Ethics	Rules of right and fair behaviour when collecting and using data.	اخلاقیات
Spreadsheet	Software that arranges data in rows and columns and performs calculations.	اسپریڈشیٹ / حسابی جدول
Formula	A spreadsheet instruction starting with = that calculates a result.	فارمولا
Infographic	A visual presentation of information so the main idea is understood quickly.	تصویری معلومات (انفوگرافک)
Report	Structured document presenting data, findings, analysis and conclusions.	رپورٹ
Dashboard	Interactive screen of charts and filters for exploring data.	ڈیش بورڈ
Advanced search operator	Special symbol or word (e.g. " ", filetype:, site:) that narrows search results.	جدید تلاش آپریٹر
Methodology	The plan of methods used to answer a research question.	طریقہ کار
Digital artefact	Final product made with digital technology that answers the research question with evidence.	ڈیجیٹل آرٹیفیکٹ / ڈیجیٹل تخلیق
Recommendation	A practical suggestion based on the findings.	سفارش

Practice: multiple choice

1. Digital literacy is best described as the ability to:
 - a. type quickly on a keyboard
 - b. understand and use digital devices, the internet and online tools safely, effectively and responsibly
 - c. repair computer hardware
 - d. write computer programs
2. Which of the following is qualitative data?
 - a. Marks obtained in a test
 - b. Number of hours spent online
 - c. Students' opinions about online classes
 - d. Percentage of students using the internet
3. Which method is most suitable when the same questions must be asked to many people?
 - a. Survey
 - b. Interview
 - c. Prototype
 - d. Simulation
4. Simulations are especially useful when:
 - a. you want people's opinions
 - b. the data already exists in a report
 - c. you want to watch people without asking questions
 - d. real experiments are costly, risky or difficult
5. To find out how many cars cross an intersection at 8 AM, the best method is:
 - a. Interview
 - b. Observation
 - c. Survey
 - d. Prototype
6. Which of these is primary data?
 - a. Responses to a Google Form you created for your project
 - b. An official government report
 - c. A published research article
 - d. Web statistics from a website
7. A researcher has limited control over:
 - a. their own interviews
 - b. their own survey questions
 - c. their own observations
 - d. secondary data
8. The first step in designing a data-collection approach is to:
 - a. collect the data
 - b. choose the sample
 - c. define the research question clearly
 - d. store the data with a backup
9. Which spreadsheet formula finds the mean of cells B2 to B6?
 - a. `=AVERAGE(B2:B6)`
 - b. `=SUM(B2:B6)`
 - c. `=COUNT(B2:B6)`
 - d. `=MAX(B2:B6)`
10. The search query `digital distraction site:.edu` will:
 - a. find only PDF files
 - b. search only educational websites
 - c. find the exact phrase "digital distraction" only
 - d. exclude educational websites
11. The operator `filetype:pdf` is used to:
 - a. search for an exact phrase
 - b. search only government websites
 - c. convert a web page into PDF
 - d. find only PDF documents
12. "Do not record names unless absolutely necessary" describes the principle of:
 - a. consent
 - b. accuracy
 - c. anonymity
 - d. sampling
13. In the case study, how many Class XI students were surveyed?
 - a. 20
 - b. 40
 - c. 50
 - d. 100
14. Which tools are suggested for a dashboard artefact?
 - a. Power BI, Tableau
 - b. MS Word, Google Docs
 - c. PowerPoint, Google Slides
 - d. Google Forms, Microsoft Forms
15. A prototype is:
 - a. the final finished product
 - b. a published report
 - c. a type of survey question
 - d. a simple early version of a product used to test an idea

Practice: short questions

1. Define digital literacy. Name the three kinds of ability it involves.
2. Why is simply having access to technology not enough in the Information Age?
3. Differentiate between qualitative and quantitative data, giving two examples of each.
4. How is an interview different from a survey?
5. What is a prototype, and how does it produce useful data?
6. When is a simulation used? Give one example.
7. Compare primary and secondary data in terms of purpose and control.
8. List any four ethical guidelines to follow when collecting primary data.
9. Explain three advanced search operators with an example of each.
10. What is a digital artefact? Name its four options with one suitable tool each.

Practice: long / problem questions

1. Explain the eight steps of designing a data-collection approach. Apply each step to the research question: "How much water is wasted at the college taps during break time, and why?"
2. **Design a survey for** finding out how Class XI students in your college travel to college and how long the journey takes. Write a consent statement and at least six questions (mixing closed, number, rating and open-ended types), state the data type of each question, describe your sample, and explain how you will keep the data ethical.
3. Ten students recorded their daily phone use (hours) in cells B2 to B11: 2, 4, 3, 5, 6, 4, 3, 4, 1, 4. (a) Write the spreadsheet formulas and give the results for the total, mean, median, mode, maximum and minimum. (b) Write a formula to count students using the phone for more than 4 hours, and find the percentage. (c) Group the data into "1–2 hrs", "3–4 hrs" and "5+ hrs" and name a suitable chart.
4. Describe all 12 steps of the Digital Inquiry Project on the question "How does daily mobile phone use affect the study habits of students?", including the final digital artefact and its structure.
5. **Design a survey for** investigating "How do Class XI students use AI tools for homework?" Then explain which secondary sources you would search for (with advanced search queries), and which artefact you would create to present your findings to the principal, with reasons.

Answer key

Multiple choice

1. b
2. c
3. a
4. d
5. b
6. a
7. d
8. c
9. a
10. b
11. d
12. c
13. b
14. a
15. d

Short questions — model answers

1. Digital literacy is the ability to understand and use digital devices, the internet and online tools in a safe, effective and responsible manner. It involves technical, cognitive and social abilities.
2. In the Information Age vast amounts of data are produced and shared instantly. Owning a device does not mean you can judge or use this information well. Users must develop skills to understand, manage and use information wisely, and to tell reliable information from unreliable.
3. Qualitative data is descriptive and non-numerical; it explains why and how (e.g. students' opinions about online classes; observation notes). Quantitative data is numerical, countable or measurable; it is used for comparing and making charts (e.g. marks in a test; hours spent online).
4. An interview is a planned conversation with one person or a small group, giving mostly qualitative, in-depth answers. A survey asks the same set of questions to many people (on paper or via Google/Microsoft Forms) and is efficient for large groups; online surveys also collect responses and make charts automatically.
5. A prototype is a simple early version of a product, model or solution. Users try it and give feedback; this feedback is data used to improve the product before time and effort are spent on the final version.
6. A simulation is used when real experiments are costly, risky or difficult. Example: a flight simulator to train pilots, or a traffic simulation to test the effect of closing a road.
7. Purpose: primary data is prepared for a specific study; secondary data is reused for a new purpose. Control: the researcher has high control over primary data (questions and process) and limited control over secondary data because it already exists.
8. Any four: ask permission (consent); avoid sensitive personal information; do not record names unless necessary (anonymity); keep responses private; use data only for educational purposes.
9. Quotes " " find an exact phrase, e.g. "study habits" students. filetype: finds a file format, e.g. "academic performance" filetype:pdf gives only PDFs. site: limits to a type of website, e.g. digital distraction site:.edu searches only educational sites.
10. A digital artefact is a final product created with digital technology that answers the research question with evidence and conclusions. Options: digital report (MS Word/Google Docs), presentation (PowerPoint/Canva/Slides), infographic (Canva/Adobe Express), dashboard (Power BI/Tableau).

Long questions — model answers

- 1. Eight steps applied to water wastage.** (1) **Define the question:** "How much water is wasted at the college taps during break time, and why?" (2) **Data type:** both – quantitative (number of taps left running, minutes running) and qualitative (students' reasons). (3) **Methods:** observation to count running taps; a short survey to learn habits and reasons. (4) **Sample:** all 12 taps observed over 5 break times; 30 students from different classes surveyed. (5) **Tools:** an observation sheet (Tap no., Time, Left running Y/N, Minutes) and a Google Form. (6) **Collect** carefully, at the same time each day, recording accurately. (7) **Store** data in Google Sheets and keep a backup copy (download or USB). (8) **Ethics:** get the principal's permission; the survey is voluntary and anonymous with a consent question; data used only for the project.
- 2. Survey on travel to college (model).** *Consent:* "This anonymous survey is for a Class XI project on travel to college. Do not write your name. Answers will be kept private and used only for this project. Do you agree to take part? Yes / No." *Questions:* Q1 How do you usually travel to college? Walk / Bus / Rickshaw / Motorbike / Car / Other – quantitative (categories). Q2 How many minutes does your journey usually take? ____ – quantitative. Q3 How many days a week are you late because of travel? 0 / 1 / 2 / 3 or more – quantitative. Q4 "My journey to college is safe." 1 (strongly disagree) to 5 (strongly agree) – quantitative (rating). Q5 Do you travel alone? Yes / No – quantitative (count). Q6 What is the biggest problem you face while travelling? – qualitative. Q7 Suggest one way the college could make travel easier. – qualitative. Questions are unbiased, ask one thing each, and options do not overlap. *Sample:* about 40 Class XI students, roughly 10 from each section, to be representative. *Ethics:* consent, no sensitive information (no home address), no names (anonymity), private storage, educational use only. Data is collected through Google Forms and exported to Google Sheets for analysis.
- 3. Spreadsheet problem.** (a) $\text{=SUM(B2:B11)} \rightarrow 2+4+3+5+6+4+3+4+1+4 = 36$. $\text{=AVERAGE(B2:B11)} \rightarrow 36 \div 10 = 3.6$ hours. Sorted: 1, 2, 3, 3, 4, 4, 4, 4, 5, 6; $\text{=MEDIAN(B2:B11)} \rightarrow (4 + 4) \div 2 = 4$. $\text{=MODE(B2:B11)} \rightarrow 4$ (appears 4 times). $\text{=MAX(B2:B11)} \rightarrow 6$; $\text{=MIN(B2:B11)} \rightarrow 1$. (b) $\text{=COUNTIF(B2:B11, ">4")}$ $\rightarrow$ values 5 and 6 $\rightarrow 2$ students; percentage $\text{=COUNTIF(B2:B11, ">4")}/\text{COUNT(B2:B11)} \rightarrow 2 \div 10 = 20\%$. (c) 1–2 hrs: 2 students (2, 1); 3–4 hrs: 6 students (4, 3, 4, 3, 4, 4); 5+ hrs: 2 students (5, 6). Check: $2 + 6 + 2 = 10 \checkmark$. A **bar/column chart** is suitable for comparing the groups (or a pie chart to show 20%, 60%, 20%).
- 4. Twelve steps.** (1) Advanced searches with operators such as "mobile phone use" "study habits" students, "academic performance" filetype:pdf, digital distraction site:.edu; evaluate sources (author, recent, reliable site, facts/bias). (2) Identify data types: quantitative (hours daily, % distracted) and qualitative (reasons, suggestions). (3) Select method: survey via Google Forms/paper, because the same questions go to many students. (4) Prepare the survey: hours daily (quantitative), main activity (quantitative categories), how the phone helps (qualitative), one responsible-use suggestion (qualitative). (5) Sample: 40 Class XI students from different sections. (6) Collect ethically: consent, no sensitive data, anonymity, privacy, educational use only. (7) Secondary data: an article saying excessive screen time lowers concentration, to compare with results. (8) Organise in Excel/Google Sheets (Student, Hours, Study Use, Main Activity, Distracted?), sort, total, average. (9) Charts: bar chart of daily phone use (1–3, 3–5, 5+ hrs). (10) Analyse: majority use 3–5 hours; half use for education; entertainment users report more distraction. (11) Conclusion: phones have positive and negative effects; should be managed wisely, not banned. (12) Recommendations: turn off social media notifications, set screen-time limits, take physical breaks. **Artefact:** one of report, presentation, infographic or dashboard, structured as Title, Research Question, Introduction, Method, Primary Findings, Secondary Summary, Charts, Conclusion, Recommendations, References.
- 5. AI tools for homework (model).** *Survey:* consent statement (anonymous, voluntary, educational use only). Q1 Have you used an AI tool (e.g. ChatGPT, Gemini) for homework? Yes / No – quantitative. Q2 How many times a week? 0 / 1–2 / 3–5 / 6 or more – quantitative (non-overlapping categories). Q3 What do you use it for most? Explaining topics / Checking answers / Writing assignments / Translation / Other – quantitative (categories). Q4 "AI tools help me understand my subjects better." 1–5 rating – quantitative. Q5 Do you check AI answers against your textbook? Always / Sometimes / Never – quantitative. Q6 Describe one problem you have faced with AI answers. – qualitative. *Sample:* about 40 Class XI students from all sections. *Secondary sources:* "generative AI" students homework filetype:pdf; "AI in education" site:.edu; "artificial intelligence" policy site:.gov.pk; evaluate each for author, date, reliability and bias. *Artefact:* a **digital report** (MS Word/Google Docs) because the principal needs the full study – method, findings, charts, conclusion, recommendations and references – in a structured document; a one-page infographic could be attached as a quick summary. Charts would be made in Google Sheets from the form responses, and every visual must match the real data.

Self-assessment: I can...

- ☐ define digital literacy and explain why it matters in the Information Age.
- ☐ name and explain the five data-collection strategies and choose the right one for a scenario.
- ☐ compare primary and secondary data by source, examples, purpose and control.
- ☐ follow ethical rules: consent, anonymity, privacy and educational use.
- ☐ use advanced search operators and evaluate whether a source is reliable.
- ☐ describe the 12 steps of the digital inquiry project.
- ☐ classify data as qualitative or quantitative and explain the difference in a table.
- ☐ write clear, unbiased survey questions and fix leading, double-barrelled or vague ones.
- ☐ list the eight steps for designing a data-collection approach.
- ☐ use spreadsheet formulas such as `=SUM()`, `=AVERAGE()` and `=COUNTIF()` and calculate results correctly.
- ☐ choose a suitable tool (spreadsheet, presentation, infographic, report, dashboard) to present findings.
- ☐ plan a digital artefact using the ten-part standard structure.

FINAL REVISION

One-page recaps and a mock paper

Use these pages in the last week before the exam. Read one recap, close the booklet, and say it aloud. Then sit the mock paper in 2 hours 30 minutes with no notes.

امتحان سے ایک ہفتہ پہلے یہ خلاصے زبانی دہرائیں، پھر ماک پیپر بغیر نوٹس کے حل کریں۔

Chapter 1 recap — Computer Systems

- Discrete = counted (stairs). Continuous = measured (ramp). Digital systems use bits 0 and 1; they are reliable, accurate, easy to design and programmable.
- Analog signal = smooth sine wave. Digital signal = square wave HIGH/LOW. Digital data resists noise.
- AND · output 1 only if all inputs 1. OR + output 1 if any input 1. NOT ' inverts. NAND = NOT-AND, NOR = NOT-OR (universal). XOR 1 when inputs differ. XNOR 1 when inputs same.
- Truth table rows = 2^n . SOP = sum of minterms where output is 1. POS = product of maxterms where output is 0.
- K-map: group 1, 2, 4, 8 adjacent 1s (power of 2, wrap-around allowed). Each group drops the variables that change.
- SDLC: requirement → design → implementation → testing → deployment → maintenance. Waterfall = sequential; Agile = short sprints and feedback.
- OSI 7: Physical, Data Link, Network, Transport, Session, Presentation, Application. Mnemonic: Please Do Not Throw Sausage Pizza Away. TCP/IP 4: Network Access, Internet, Transport, Application.

Chapter 2 recap — Computational Thinking & Algorithm

- CT pillars: decomposition, pattern recognition, abstraction, algorithms.
- Algorithm = finite, ordered, unambiguous steps. Pseudocode = structured English, not a programming language.
- Bubble Sort: compare neighbours, swap if out of order; largest "bubbles" to the end each pass. $O(n^2)$.
- Selection Sort: find the minimum in the unsorted part and swap it to the front. $O(n^2)$.
- Linear Search: check one by one. Works on unsorted data. $O(n)$.
- Binary Search: list MUST be sorted. Repeatedly test the middle. $O(\log n)$. Trace with low / mid / high.
- Judge an algorithm on correctness, efficiency (time and space) and clarity. Prefer binary search on large sorted lists; linear search on small or unsorted lists.

Chapter 3 recap — Programming Fundamentals

- Python: high-level, interpreted. Variables are names; types int, float, str, bool, list, dict. `input()` returns str.
- Arithmetic `+` `-` `*` `/` `//` `%` `**`. Relational. Logical `and` `or` `not`. Bitwise `&` `|` `^` `~` `<<` `>>`.
- Selection: `if` / `if-else` / `if-elif-else` / nested. Test from the top; first True wins.
- `for` = known count + `range`. `while` = unknown count; always update the condition. `break` leaves; `continue` skips one.
- Libraries: `import math` / `random` / `datetime`. Third-party via `pip`: NumPy, Pandas, Matplotlib.
- Syntax = will not run. Runtime = crash + traceback. Logical = runs, wrong answer.

Chapter 4 recap — Data and Analysis

- Data = raw facts. Information = processed data used for decisions. Database = organised related data. DBMS = software that manages it (reduces redundancy, improves security, sharing, integrity).
- Table / relation; row / record / tuple; column / field / attribute. Primary key uniquely identifies a row. Foreign key refers to another table's primary key.
- ER model: entity (rectangle), attribute (oval), relationship (diamond), cardinality 1:1, 1:M, M:N.
- Referential integrity: you cannot orphan a child row. Cascade Update / Cascade Delete copy or remove matching child rows.
- Access objects: tables, forms, queries, reports. Queries filter with criteria, wildcards (`*`, `?`), AND/OR. Totals: Count, Sum, Avg, Group By. Charts visualise the result.

Chapter 5 recap — Application and Impacts of Computing

- IoT = connected devices. Six parts: sensor, actuator, connectivity, processing, cloud, UI. AI = machines that learn and decide. Analytics = collect → store → clean → analyse → visualise.
- Together: IoT (eyes) → Analytics (sort) → AI (brain) → actuator (action).
- Sources: primary (firsthand), secondary (explained by others), tertiary (summaries). No author / date / references → do not trust.
- Assistive tech: mobility, sensory, communication, cognitive. Goal: equal access, independence, inclusion.

Chapter 6 recap — Digital Literacy

- Digital literacy = find, evaluate, create and share information with digital tools, safely.
- Qualitative = words/descriptions. Quantitative = numbers. Strategies: interview, survey, prototype, observation, simulation.
- Primary data you collect; secondary data already exists. Good survey questions are clear, single-idea, unbiased.
- Present with spreadsheets (formulas such as `=AVERAGE()`), slides, infographics and reports. Cite sources. Follow the 12-step inquiry project from question to artefact.

ACADEMY SESSION

Academy exam week — 7 days × 90 minutes.

Days 1–6: one chapter recap as an error clinic. Starter test from that chapter's Golden topics. Two students write a 5-mark answer on the board using the recipe.

Day 7: sit the mock paper in 2 hours 30 minutes, academy hall conditions. No notes, no phones. Invigilate as the board will.

چھ دن خلاصے اور ایئر کلینک، ساتویں دن ماک پیپر بغیر نوٹس کے کرائیں۔

BATCH HOMEWORK

After the mock, students mark with the key in this book. Each student lists every Golden topic they missed. Those topics become the last two 90-minute revision classes.

Collect the list next class. Re-teach any Golden that more than a third of the batch missed.

FULL-MARK ANSWER RECIPE

Mark the mock to the same 1 / 3 / 5 / 8–10 recipes used all year. An answer with no working, no diagram, or no example cannot score full marks.

Mock paper — Computer Science XI

Time: 2 hours 30 minutes | Total: 75 marks | Answer all questions. Calculators allowed. Write Python with correct indentation.

Section A — Multiple choice (15 × 1 = 15)

1. Which quantity is discrete?
 - a. Room temperature
 - b. Number of desks
 - c. Car speed
 - d. Time of day
2. NAND is called universal because:
 - a. it has two inputs
 - b. any gate can be built from it
 - c. its output is always 1
 - d. it is faster than AND
3. The Boolean expression for XOR is:
 - a. $A \cdot B$
 - b. $A + B$
 - c. $A \oplus B$
 - d. $(A \cdot B)'$
4. OSI layer that chooses the best path (IP addresses) is:
 - a. Transport
 - b. Network
 - c. Data Link
 - d. Session
5. Which SDLC model delivers working software in short sprints?
 - a. Waterfall
 - b. Agile
 - c. Spiral only
 - d. Big Bang
6. Binary Search requires the list to be:
 - a. unsorted
 - b. sorted
 - c. all unique and unsorted
 - d. of even length
7. Worst-case time of Bubble Sort is:
 - a. $O(n)$
 - b. $O(\log n)$
 - c. $O(n^2)$
 - d. $O(1)$
8. `input()` in Python returns a:
 - a. int
 - b. str
 - c. float
 - d. bool
9. `17 // 5` equals:
 - a. 3.4
 - b. 3
 - c. 2
 - d. 3.0
10. A program that runs but prints the wrong total has a:
 - a. syntax error
 - b. runtime error
 - c. logical error
 - d. hardware fault
11. A field that uniquely identifies each record is a:
 - a. foreign key
 - b. primary key
 - c. composite description
 - d. query
12. An actuator in IoT:
 - a. collects temperature
 - b. opens a water valve
 - c. stores cloud files
 - d. draws a chart
13. Wikipedia is a:
 - a. primary source
 - b. secondary source
 - c. tertiary source
 - d. sensor
14. Marks out of 100 are:
 - a. qualitative data
 - b. quantitative data
 - c. tertiary data
 - d. metadata only
15. Which Access object is best for printing a formatted class list?
 - a. Table
 - b. Form
 - c. Query
 - d. Report

Section B — Short questions (10 × 3 = 30)

1. Differentiate analog and digital signals with one example of each.
2. Draw the symbol and truth table of a 2-input NOR gate.
3. List the four pillars of computational thinking in one sentence each.
4. Why can you not use Binary Search on an unsorted attendance list?
5. Write a Python `if-elif-else` that prints Pass if marks ≥ 40 , else Fail.
6. Define primary key and foreign key.
7. Name the six components of IoT.
8. Classify: (a) a photograph you took, (b) a textbook, (c) an encyclopedia.
9. Give two good and two bad survey questions about mobile-phone use in college.
10. State three advantages of a DBMS over paper files.

Section C — Long questions (3 × 10 = 30). Attempt any three.

1. Simplify $F(A,B,C) = \Sigma(1,3,5,7)$ using a 3-variable K-map. Show the grouping and the final expression. Draw the logic diagram.
2. Dry-run Bubble Sort on the list [5, 1, 4, 2]. Show every pass. Then search for 4 using Binary Search on the sorted result, with a low/mid/high table.
3. Write a complete Python program that reads n subject marks, prints the average, and prints "A" if average ≥ 80 , "B" if ≥ 70 , "C" if ≥ 60 , else "D". Include a sample run of four marks: 80, 70, 90, 60.
4. Design an ER diagram and relational schema for a school library (Student, Book, Issue). Mark keys. Write one Access/SQL query that lists all books issued to roll number 101.
5. Explain how IoT, Data Analytics and AI work together on a Sindh farm. Then discuss two positive and two negative impacts of computing on education in Pakistan.

Mock paper — answers

Section A

1. b
2. b
3. c
4. b
5. b
6. b
7. c
8. b
9. b
10. c
11. b
12. b
13. c
14. b
15. d

Section B

1. Analog: continuous, sine wave, e.g. human voice. Digital: two levels 0/1, square wave, e.g. computer data. Digital resists noise.
2. NOR symbol: OR-gate shape with a bubble on the output. $Y = (A+B)'$. Truth: 00→1, 01→0, 10→0, 11→0.
3. Decomposition = split a problem. Pattern recognition = reuse similarities. Abstraction = ignore extra detail. Algorithms = write ordered steps.
4. Binary Search repeatedly halves a sorted range. If the list is unsorted, the middle value does not tell you which half to keep, so the method is invalid.
5. `m = int(input("Marks: ")) then if m ≥ 40: print("Pass") else print("Fail").`
6. Primary key: unique identifier of a row (e.g. StudentID). Foreign key: a field that refers to the primary key of another table (e.g. StudentID in Issuance).
7. Sensors, actuators, connectivity, data processing, cloud computing, user interface.
8. (a) primary (b) secondary (c) tertiary.
9. Good: "How many hours per day do you use a phone for study?" / "Which apps do you use for class notes?" Bad: "Don't you agree phones are destroying students?" (leading) / "Do you like phones and also use laptops?" (double-barrelled).
10. Less redundancy, easier search and update, better security and multi-user access, integrity constraints. (Any three.)

Section C — outline

1. K-map 1s at m1, m3, m5, m7 form one group of 4 covering B=1 (or C=1 depending on labelling — with standard ABC order the 1s are all cells where C=1). $F = C$. Diagram: a single wire C to output (or a buffer). Show the map with the group circled.
2. Pass 1: [1,4,2,5]; Pass 2: [1,2,4,5]; Pass 3: already sorted. Sorted [1,2,4,5]. Search 4: low=0 high=3 mid=1 (2<4) → low=2; mid=2 (4=4) found at index 2.
3. Read n, loop n times adding `float(input())`, $avg = total/n$, then if-elif for A/B/C/D. Sample: total 300, avg 75.0, grade B.
4. Entities Student(StudentID PK, Name, Class), Book(BookID PK, Title, Author), Issue(IssueID PK, StudentID FK, BookID FK, Date). Query: `SELECT Book.Title FROM Issue INNER JOIN Book ON Issue.BookID = Book.BookID WHERE StudentID = 101;`
5. Soil sensor (IoT) → cloud spreadsheet of moisture (Analytics) → model decides "too dry" (AI) → pump (actuator). Education +: LMS, remote classes. Education -: screen addiction, urban/rural device gap.

COACHING ACADEMY EDITION

Computer Science XII

For coaching academies — 90-minute batch plans, full-mark recipes, timed drills with answers, and batch homework.

Bilingual support: English + اردو

کوچنگ اکیڈمی کے لیے — 90 منٹ کلاس، مکمل نمبر، ڈرل اور ہوم ورک

01 Computer Systems (HCI)

02 Computational Thinking & Algorithms

03 Programming Fundamentals

04 Data and Analysis

05 Application and Impacts of Computing

06 Entrepreneurship in the Digital Age

XII

Contents

Chapter 1: Computer Systems (HCI)

- 1.1 Fundamentals of Human-Computer Interaction
 - 1.1.1 Traditional Interaction and 1.1.2 Natural Interaction
 - 1.2 Applications of HCI (Domains of Life)
 - Types of User Interaction
 - 1.4 Importance of HCI
 - 1.6 Need Analysis for Interface Design
 - 1.8 Methods for Improving HCI
 - 1.9.3–1.9.5 Wireframing, Figma and Prototypes
 - 1.11.2 Testing Methods (Usability, A/B, Automated)
 - 1.3 Components of HCI
 - Interface Types, Environment and Feedback
 - 1.5 Accessibility Principles
 - 1.7 Human-Computer Interaction Problems
 - 1.9 User Interface Design (UI vs UX)
 - 1.11 Test and Evaluate HCI (Evaluation Methods)
 - Career Opportunities in UI/UX
-

Chapter 2: Computational Thinking & Algorithms

- 2.1 Analyze algorithms for correctness
 - 2.1.1 Trace Tables
 - 2.1.2 Stepwise Reasoning
 - 2.1.3 Comparing Trace Tables and Stepwise Reasoning
 - 2.2 Evaluating the Clarity of an Algorithm
 - 2.2.1 Modularity
 - 2.2.2 Readability
 - 2.3 Assess Algorithm Efficiency
 - 2.3.1 Number of Steps (Big O Notation)
 - 2.3.2 Number of Conditions
 - 2.3.3 Number of Repetitions
 - 2.3.4 The Efficiency Evaluation Framework
 - 2.4 Refinements to improve clarity and efficiency
 - 2.5 Concept of Data Structure
 - 2.5.1 Linear Data Structures: Array
 - Linear Data Structures: Stack
 - Linear Data Structures: Linked List
 - Linear Data Structures: Queue
 - 2.5.2 Non-Linear Data Structures: Tree
 - Non-Linear Data Structures: Graph
 - 2.5.3 Operations on Data Structures
 - 2.6 Identify data structures in problem scenarios
 - 2.7 Trace data retrieval in Array, List and Queue
 - Career Opportunities in Algorithms
-

Chapter 3: Programming Fundamentals

- 3.1 Data Structures in Python
 - 3.1.1 Lists (Ordered, Mutable, Methods)
 - 3.1.2 Tuples (Ordered, Immutable)
 - 3.1.3 Sets (Unordered, Unique, Math Operations)
 - 3.1.4 Dictionaries (Key-Value Pairs)
 - 3.1.5 Common Built-in Functions (min, max, len, sum)
 - 3.1.6 Activity: Student Attendance System
 - 3.1.7 Activity: Word Frequency Counter
 - 3.2 Functions in Python
 - 3.2.1 Types of Functions (Built-in vs User-defined)
 - 3.2.2 Functions with Return Values
 - 3.2.3 Activity: Arithmetic Calculator Using Functions
 - 3.2.4 Scope of Local and Global Variables
 - 3.3 & 3.4 File Handling and Operations (Modes r, w, a)
 - 3.6 The with Statement (Context Manager)
 - 3.8 Errors and Exceptions (Try-Except)
 - 3.9 Mini File Handling Project: Grade Tracker
 - Career Opportunities
-

Chapter 4: Data and Analysis

- 4.1 Concept of Data Analysis
- 4.2 Creating a SQLite Database in Python
- 4.3.3 Handling Missing Values (NaN)
- 4.5 Data Visualization and Types of Graphs
- Career Opportunities
- 4.1.1 – 4.1.2 Data Sources and Database Connection
- 4.3 Pandas and DataFrames
- 4.4 Data Organization and Representation
- 4.6 Descriptive Statistics

Chapter 5: Application and Impacts of Computing

- 5.1 Machine Learning, Neural Networks and Deep Learning
- 5.1.2 Neural Networks (NN)
- 5.1.4 Components of Neural Networks
- Future of AI, NN and DL in Pakistan
- 5.3.1 Secure Collaboration (Authentication, MFA, Access Control)
- 5.4.1 Common Security Threats (Malware, Phishing, DoS)
- 5.4.3 Apply Mitigation Techniques
- 5.5.1 Functions of Equity and Equal Access
- Career Opportunities
- 5.1.1 Machine Learning (ML)
- 5.1.3 Deep Learning (DL)
- 5.1.5 Components of Deep Learning
- 5.2 Applications of Neural Networks and Deep Learning
- 5.3.2 Data Protection (Encryption, Passwords, Backup, Firewall)
- 5.4.2 Identifying Security Threats
- 5.5 Equity and Equal Access in Digital Collaboration
- 5.5.2 Collaboration Tools

Chapter 6: Entrepreneurship in the Digital Age

- 6.1 Entrepreneur and Entrepreneurship
- Local Examples of Digital Entrepreneurship (Table 6.1)
- 6.4 Prototype
- 6.6 Prototype Development Cycle
- 6.8 Minimum Viable Product (MVP)
- 6.10 Identifying the Riskiest Assumption
- 6.12 Case Study: MVP for a Canteen Pre-Order System
- 6.14 Beachhead Market
- 6.16 Ethical and Safe Use of Digital Tools
- 6.2 Entrepreneurship in the Digital Age
- 6.3 From Problem to Business Idea
- 6.5 Types of Prototypes
- 6.7 Class Activity: Create a Prototype
- 6.9 Difference between Prototype and MVP
- 6.11 Developing an MVP
- 6.13 Testing an MVP
- 6.15 Complete Student Project
- Career Opportunities

Final Revision: one-page summaries, mock paper and answers

How to run this Coaching Academy Edition

This book is for a **coaching academy batch** (not a 40-minute school period). A standard academy class is **90 minutes**. Golden topics (★) get a full class. Other topics pair into one class. Every topic below the notes has a full-mark recipe, an academy drill with answers, and batch homework.

یہ کتاب کوچنگ اکیڈمی کے بیچ کے لیے ہے۔ ایک کلاس 90 منٹ کی ہے۔ گولڈن موضوع پوری کلاس لیتا ہے۔ ہر موضوع پر نمبر بنانے کا طریقہ، ڈرل اور ہوم ورک ہے۔

The 90-minute academy class

1. **0–10 min — Starter test.** Three oral or written 1-mark questions from last class. Marks go in the batch register.
2. **10–35 min — Concept lock.** Write the definition, table and diagram on the whiteboard. Students copy. No phones.
3. **35–55 min — Board working.** Do the worked example. Then hide it. Two students redo it on the board.
4. **55–75 min — Academy drill.** Timed. 1-mark then 3-mark then 5-mark. Mark at once with the recipe in this book.
5. **75–85 min — Error clinic.** Collect the three most common wrong answers. Correct them in one box on the board.
6. **85–90 min — Homework out.** One 5-mark question + one drawing/code/trace. Collect next class and mark to the scheme.

How academy answers score marks

- **1 mark:** one exact definition or one named fact.
- **2 marks:** definition + one example (preferably local: JazzCash, school portal, NADRA, load-shedding).
- **3 marks:** definition + two clear points + example.
- **5 marks:** definition, a four-point table or explanation, example, and a labelled diagram if the topic has one.
- **8–10 marks:** 5-mark structure + full working (trace, K-map, code, ER diagram) + a one-line conclusion.

Train this wording in every class: *Define. Explain. Example. Diagram. Working.* Examiners award method marks. An answer with no working is a half-answer.

What the extra academy boxes mean

ACADEMY SESSION

How to run this topic in a 90-minute batch: board, drill, error clinic.

FULL-MARK ANSWER RECIPE

The sentence pattern that scores 1, 3, 5 and 8 marks.

ACADEMY DRILL

Timed extra questions with answers — for class, not homework peeking.

BATCH HOMEWORK

What the batch takes home, and how you will mark it tomorrow.

ACADEMY CALENDAR

Chapter session calendar and weekly test.

GOLDEN TOPIC

★ **Golden** — never skip, never rush, test it every week until the exam.

CHAPTER 1

Computer Systems (HCI)

This chapter teaches you Human-Computer Interaction (HCI): how people and computers talk to each other, how to design screens that are easy and fair to use, and how to test those designs before they go live. You will apply every idea to things you already use in Pakistan — a bank ATM, JazzCash, and a school portal.

اس باب میں آپ ہیومن کمپیوٹر انٹرایکشن (HCI) سیکھیں گے: انسان اور کمپیوٹر آپس میں کیسے بات کرتے ہیں، اسکرینیں کیسے آسان اور منصفانہ بنائی جاتی ہیں، اور انہیں عوام تک پہنچانے سے پہلے کیسے جانچا جاتا ہے۔

What you will learn

- Define HCI (also called CHI and MMI) and name the five sensory channels of interaction.
- Describe HCI applications in health care, banking, education, and networking.
- Explain environment and the two kinds of feedback.
- Carry out a need analysis before designing an interface.
- Differentiate UI from UX, and compare wireframes, Figma work and prototypes.
- Differentiate traditional interaction from natural interaction with local examples.
- Name the components of HCI and classify types of user interaction and interface.
- State why HCI is important and apply five accessibility principles.
- Identify common HCI problems and methods for improving HCI.
- Choose evaluation and testing methods (SUS, NPS, usability, A/B, automated audits).

ACADEMY CALENDAR

Academy calendar: 16 topics · 5 Golden · **12 classes of 90 minutes** + one 40-minute weekly test after this chapter.

Class	Topics	Kind	Board focus
Class 01	Fundamentals of Human-Computer Interaction + Traditional Interaction and 1.1.2 Natural Interaction	Paired · 90 min	Human-Computer Interaction (HCI) is the study and design of technology so that it serves...
Class 02	Applications of HCI (Domains of Life)	★ Golden · 90 min	HCI is used to design and develop interactive systems such as desktop applications,...
Class 03	Components of HCI + Types of User Interaction	Paired · 90 min	HCI relies on several primary components that work together.
Class 04	Interface Types, Environment and Feedback	Single · 90 min	Components v–vii complete the HCI picture: the look of the controls, the place where you...
Class 05	Importance of HCI	★ Golden · 90 min	HCI ensures that machines are approachable and usable, turning complex technology into...
Class 06	Accessibility Principles + Need Analysis for Interface Design	Paired · 90 min	Accessibility principles are HCI guidelines that ensure digital systems are usable by all...
Class 07	Human-Computer Interaction Problems	★ Golden · 90 min	HCI problems are common difficulties that stop users from using technology smoothly.
Class 08	Methods for Improving HCI	Single · 90 min	Once you can name an HCI problem, you fix it with a matching method.

Class	Topics	Kind	Board focus
Class 09	User Interface Design (UI vs UX)	★ Golden · 90 min	UI design is the process of creating and organizing the visual elements of a software...
Class 10	Wireframing, Figma and Prototypes + Test and Evaluate HCI (Evaluation Methods)	Paired · 90 min	1.9.3 Wireframing is creating a basic visual outline or blueprint of a user interface...
Class 11	Testing Methods (Usability, A/B, Automated)	★ Golden · 90 min	Testing involves observing how the system behaves under specific conditions.
Class 12	Career Opportunities in UI/UX	Single · 90 min	The same HCI skills you practised on ATMs, JazzCash and school portals are real jobs.

Weekly test: 15 MCQ from this chapter + two 5-mark Golden questions. Mark to the recipes. Re-teach any Golden below 60% in the next starter.

گولڈن موضوع پوری کلاس لیتا ہے۔ ہفتہ وار ٹیسٹ کے بعد کمزور گولڈن دوبارہ پڑھائیں۔

1.1 Fundamentals of Human-Computer Interaction

ACADEMY SESSION

Session 1 of 12 · 45 minutes (first half) · paired with Traditional Interaction and 1.1.2 Natural Interaction.

10–45 min — this topic. Lock the definition and table for **Fundamentals of Human-Computer Interaction**. Starter (0–10) is from last class. Second half is Traditional Interaction and 1.1.2 Natural Interaction.

On the board: Human-Computer Interaction (HCI) is the study and design of technology so that it serves people.

Error clinic: Mistake: Writing "HCI is only about computer hardware" or mixing up Voice with Hearing.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Fundamentals of Human-Computer Interaction**. Write: Human-Computer Interaction (HCI) is the study and design of technology so that it serves people.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) An HCI system is easy to use, efficient, and responsive to human needs. (2) HCI is also known as CHI (Computer-Human Interface) or MMI (Man-Machine Interaction). — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

Human-Computer Interaction (HCI) is the study and design of technology so that it **serves people**. An HCI system is easy to use, efficient, and responsive to human needs. HCI is also known as **CHI** (Computer-Human Interface) or **MMI** (Man-Machine Interaction). The three names mean the same idea: the meeting point of a person and a machine.


HCI is not only "making a pretty screen". It asks: Can a student in Hyderabad find results on the school portal in 30 seconds? Can a grandmother send JazzCash without help? Can a person standing at an outdoor ATM in bright sunlight read the buttons?

Sensory channels of interaction

Humans and computers communicate through **sensory channels**. A sensory channel is a path that carries information to (or from) one of the human senses. Computers must send and receive signals on the same channels, or the conversation breaks.

Channel	How humans use it	How computers respond
Sight (بصارت)	Look at screens, graphics or videos.	Displays visuals on monitors and screens.
Touch (چھونا)	Tap, type or swipe.	Responds with clicks or vibrations (haptics).
Hearing (سننا)	Listen to sounds or voices.	Provides audio feedback via speakers.
Voice (آواز)	Speak commands (for example, "Alexa").	Processes speech and replies.
Spatial (مکانی)	Move in physical space.	Tracks position or body movement (for example, VR).

Haptics means physical feedback you can feel, such as a phone vibrating when a JazzCash payment succeeds. **Spatial** interaction means the system notices where your body is, as in a VR headset or a Kinect camera.



Five sensory channels meet at the human. HCI design must support the channels the user actually needs.

WORKED EXAMPLE

Worked example: map a JazzCash payment to channels. Sara in Sukkur sends Rs 500 to her brother.

1. **Sight:** she looks at the JazzCash home screen and the amount field.
2. **Touch:** she taps "Send Money" and types the mobile number.
3. **Voice (optional):** she could say "JazzCash, send five hundred rupees" if voice commands are on.
4. **Hearing + haptics:** a beep and a short vibration confirm "Payment successful".

If the app showed no tick, no sound and no vibration, Sara would not know whether the money left. That is an HCI failure, not a banking failure.

REMEMBER IT

Remember the three names: HCI = CHI = MMI. Think "Human meets Machine." Five channels: **S-T-H-V-S** — Sight, Touch, Hearing, Voice, Spatial. "See The Handy Voice in Space."

COMMON MISTAKE

Mistake: Writing "HCI is only about computer hardware" or mixing up Voice with Hearing.

Fix: HCI is about the *design of the conversation* between people and machines. Hearing is what you *listen to* (speakers). Voice is what you *speak* (microphone + speech software).

اردو میں سمجھیں

ہیومن کمپیوٹر انٹرایکشن (HCI) کا مطلب ہے ٹیکنالوجی کو اس طرح ڈیزائن کرنا کہ وہ انسانوں کے لیے فائدہ مند، آسان اور مؤثر ہو۔ اسے CHI یا MMI بھی کہتے ہیں۔ انسان اور کمپیوٹر پانچ حسی راستوں سے بات کرتے ہیں: بصارت، چھونا، سنا، آواز اور مکانی حرکت۔ ہپٹکس (Haptics) وہ ارتعاش ہے جو آپ کو چھو کر محسوس ہوتا ہے۔

CHECK YOURSELF

1. Give two other names for HCI.
2. Which channel tracks body movement in VR?
3. Is a phone vibration sight, touch (haptics), or voice?

Answers: 1. CHI (Computer-Human Interface) and MMI (Man-Machine Interaction). 2. Spatial. 3. Touch / haptics.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Give two other names for HCI.

3 marks. Explain Fundamentals of Human-Computer Interaction with two clear points and one example.

5 marks. Write a 5-mark answer on Fundamentals of Human-Computer Interaction: definition, two points, a labelled diagram or table, and one example.

Answers: 1. CHI (Computer-Human Interface) and MMI (Man-Machine Interaction) 3. An HCI system is easy to use, efficient, and responsive to human needs.; HCI is also known as CHI (Computer-Human Interface) or MMI (Man-Machine Interaction). 5. Use the recipe in the blue box. Model opening: Human-Computer Interaction (HCI) is the study and design of technology so that it serves people.

BATCH HOMEWORK

Write a 5-mark answer on **Fundamentals of Human-Computer Interaction** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.1.1 Traditional Interaction and 1.1.2 Natural Interaction

ACADEMY SESSION

Session 1 of 12 · 45 minutes (second half) · paired with Fundamentals of Human-Computer Interaction.

45–75 min — this topic. Board working for **Traditional Interaction and 1.1.2 Natural Interaction**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: 1.1.1 Traditional interaction is the basic way people use everyday devices.

Error clinic: Mistake: "Touchscreens are always natural interaction." Fix: Ordinary tapping and swiping on a phone is still listed as traditional in this chapter.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Traditional Interaction and 1.1.2 Natural Interaction**. Write: 1.1.1 Traditional interaction is the basic way people use everyday devices.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Smartphone (traditional use): tapping and swiping on a touchscreen; output via screen lighting and vibrations. (2) Voice: speaking commands into a device (for example, "Alexa, play a song"). — + example.

5 marks: 3-mark structure + table: Feature / Traditional / Natural + the worked example from this topic.

LEARN IT

1.1.1 Traditional interaction is the basic way people use everyday devices. It relies on standard input and output: a mouse, a keyboard, a keypad, a monitor, speakers, or a simple touchscreen tap and swipe.

- **Computer:** moving a mouse and typing on a keyboard; output via monitor and speakers.
- **Smartphone (traditional use):** tapping and swiping on a touchscreen; output via screen lighting and vibrations.

1.1.2 Natural interaction is advanced, smart technology that lets people interact **without a mouse or keyboard**. It feels more human — you speak, move, or show your face, and the system understands.

- **Voice:** speaking commands into a device (for example, "Alexa, play a song").
- **Body and gesture:** facial recognition to unlock a phone, or playing VR games by waving hands.

Feature	Traditional	Natural
Main input	Mouse, keyboard, keypad, simple tap/swipe	Voice, face, hand/body gesture, movement
Feels like	Operating a machine	Talking or moving as you do with people
Examples	TV remote, ATM keypad, school-portal login typed on a PC	FaceID, Siri, Kinect games, "Hey Google"
Typical output	Screen, speakers, vibration	Spoken reply, unlock, tracking of the body in VR

WORKED EXAMPLE

Worked example: sort today's tools. List three traditional and three natural interfaces you might use in one day in Sindh.

Traditional: (1) HBL ATM keypad to withdraw cash. (2) College computer lab: mouse + keyboard to open the school portal. (3) Television remote at home.

Natural: (1) Unlocking a phone with FaceID. (2) Asking Google Assistant "Call Aslam". (3) A VR science demo in which you pick a molecule by waving your hand.

Notice: the *same smartphone* can be traditional (you type a PIN) or natural (the camera reads your face). The classification depends on **how you interact**, not on the brand of the device.

REMEMBER IT

Test sentence: If you must press keys or tap labelled buttons, it is traditional. If the machine understands speech, face or body movement, it is natural.

COMMON MISTAKE

Mistake: "Touchscreens are always natural interaction."

Fix: Ordinary tapping and swiping on a phone is still listed as traditional in this chapter. Natural interaction starts when the system understands voice, face, or full-body gesture without a mouse or keyboard.

اردو میں سمجھیں

روایتی تعامل (Traditional Interaction) میں ماؤس، کی بورڈ، کی پیڈ یا عام ٹیپ اور سوائپ استعمال ہوتے ہیں، جیسے اے ٹی ایم کی پیڈ۔ قدرتی تعامل (Natural Interaction) میں آواز، چہرہ یا جسم کی حرکت سے کام ہوتا ہے، جیسے فیس آئی ڈی (FaceID) یا "الیکسا، گانا چلاؤ"۔ درجہ بندی آلے کی نہیں، تعامل کے طریقے کی ہوتی ہے۔

CHECK YOURSELF

1. Is an ATM keypad traditional or natural?
2. Give one voice example of natural interaction from the source.
3. Why can one smartphone be both traditional and natural?

Answers: 1. Traditional. 2. "Alexa, play a song" (or any spoken command). 3. Because typing a PIN is traditional, while FaceID or a voice assistant on the same phone is natural — it depends on the method, not the device.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Is an ATM keypad traditional or natural?

3 marks. Explain Traditional Interaction and 1.1.2 Natural Interaction with two clear points and one example.

5 marks. Write a 5-mark answer on Traditional Interaction and 1.1.2 Natural Interaction: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Traditional 3. Smartphone (traditional use): tapping and swiping on a touchscreen; output via screen lighting and vibrations.; Voice: speaking commands into a device (for example, "Alexa, play a song"). 5. Use the recipe in the blue box. Model opening: 1.1.1 Traditional interaction is the basic way people use everyday devices.

BATCH HOMEWORK

Write a 5-mark answer on **Traditional Interaction and 1.1.2 Natural Interaction** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.2 Applications of HCI (Domains of Life) ★ Golden

ACADEMY SESSION

Session 2 of 12 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: HCI is used to design and develop interactive systems such as desktop applications, websites and mobile apps.

Error clinic: Mistake: Listing brand names only ("WhatsApp, JazzCash, Zoom") without saying the domain and the user benefit.

Exam wording to train: Very common 5–8 mark question: "Explain applications of HCI in different domains of life with examples." Draw a four-row table (Health care, Banking,...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Applications of HCI (Domains of Life)**. Write: HCI is used to design and develop interactive systems such as desktop applications, websites and mobile apps.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) These are human-centred solutions built to meet user needs across many domains of life. (2) A domain is an area of daily activity — health, money, school, talking to people. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.


8–10 marks: 5-mark structure + a labelled wireframe and one accessibility fix + a one-line conclusion. Method marks are awarded for working.

LEARN IT

HCI is used to design and develop interactive systems such as **desktop applications, websites and mobile apps**. These are **human-centred solutions** built to meet user needs across many domains of life. A domain is an area of daily activity — health, money, school, talking to people.

When you design for a domain, you design for that domain's **users, tasks and risks**. A mistake on a games app is annoying. A mistake on a medical or banking screen can harm a person or lose money. That is why examiners treat this topic as golden.

Domain	Application examples	User benefit
Health care	Patient portals, telemedicine apps, assistive technologies	Improves access to medical services remotely
Banking	Mobile banking apps, secure ATM interfaces	Enables quick transactions and secure financial management
Education	E-learning platforms (LMS), online exam portals	Enhances teaching, learning and student engagement
Networking and communication	Social media, messaging apps (WhatsApp), Zoom	Connects people globally through collaboration tools



HCI sits at the centre of four everyday domains: healthcare, banking, education and networking.

WORKED EXAMPLE

Worked example: the same HCI idea in three Pakistani systems.

Step 1 — ATM (banking). You insert a card, the screen shows large buttons (Fast Cash, Balance, Other), you enter a PIN on the keypad, and you take cash. HCI benefit: a quick, secure transaction without a human teller.

Step 2 — JazzCash (banking + communication). You log in with a PIN or fingerprint, choose Send Money, type a number and amount, confirm, and see "Successful" with a JazzCash SMS. HCI benefit: money moves in seconds from a shop in Larkana to a student in Karachi.

Step 3 — School portal (education). A Grade XII student opens the college LMS, taps "Download date sheet", and submits a leave form. HCI benefit: learning and admin tasks happen without standing in a queue at the office.

Step 4 — Compare the user benefit. Banking HCI saves time and keeps money safe. Education HCI raises engagement. Health HCI (a Sehat/telemedicine app) brings a doctor to a village phone. Networking HCI (WhatsApp, Zoom) keeps a family in Dubai in touch with parents in Sukkur.

REMEMBER IT

Exam mnemonic H-BEN: Health, Banking, Education, Networking. For each, write: one application + one user benefit. That structure scores full marks on "applications of HCI".

COMMON MISTAKE

Mistake: Listing brand names only ("WhatsApp, JazzCash, Zoom") without saying the *domain* and the *user benefit*.

Fix: Always write three parts: domain → example → what the user gains. "Banking: JazzCash mobile app — enables quick, secure transfers."

اردو میں سمجھیں

ایچ سی آئی کی ایپلیکیشنز صحت، بینکنگ، تعلیم اور نیٹ ورکنگ کے شعبوں میں انسانی ضروریات پوری کرتی ہیں۔ صحت میں مریض پورٹل اور ٹیلی میڈیسن دور سے علاج دیتے ہیں، بینکنگ میں موبائل ایپ اور اے ٹی ایم تیز اور محفوظ لین دین دیتے ہیں، تعلیم میں ای لرننگ اور آن لائن امتحان مشغولیت بڑھاتے ہیں، اور وائس ایپ یا زوم لوگوں کو جوڑتے ہیں۔

EXAM TIP

Very common 5–8 mark question: "Explain applications of HCI in different domains of life with examples." Draw a four-row table (Health care, Banking, Education, Networking & communication). Each row: one or two application names + the user benefit from the source. Add a local line (ATM / JazzCash / school portal) to show you can apply the idea. Do not write a story about only one app.

CHECK YOURSELF

1. Name the four domains of HCI given in the source.
2. What user benefit does HCI bring in banking?
3. Give one education application and one networking application.

Answers: 1. Health care, banking, education, networking and communication. 2. Quick transactions and secure financial management. 3. Education: LMS or online exam portal. Networking: social media, WhatsApp or Zoom.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name the four domains of HCI given in the source.

3 marks. Explain Applications of HCI (Domains of Life) with two clear points and one example.

5 marks. Very common 5–8 mark question: "Explain applications of HCI in different domains of life with examples." Draw a four-row table (Health care, Banking, Education, Networking & communication). Each row:...

8 marks. Applications of HCI (Domains of Life): 5-mark answer plus a labelled wireframe and one accessibility fix.

Answers: 1. Health care, banking, education, networking and communication 3. These are human-centred solutions built to meet user needs across many domains of life.; A domain is an area of daily activity — health, money, school, talking to people. 5. Use the recipe in the blue box. Model opening: HCI is used to design and develop interactive systems such as desktop applications, websites and mobile apps. 8. Same 5-mark body + a labelled wireframe and one accessibility fix + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Applications of HCI (Domains of Life)** using the recipe in this topic. Include a labelled wireframe and one accessibility fix. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.3 Components of HCI

ACADEMY SESSION

Session 3 of 12 · 45 minutes (first half) · paired with Types of User Interaction.

10–45 min — this topic. Lock the definition and table for **Components of HCI**. Starter (0–10) is from last class. Second half is Types of User Interaction.

On the board: HCI relies on several primary components that work together.

Error clinic: Mistake: Calling the bank manager an "end user" of the ATM, or saying a task has only one property (difficulty).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Components of HCI**. Write: HCI relies on several primary components that work together.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).


3 marks: definition + two points — (1) If one component is weak, the whole interaction feels broken. (2) The first four are the people, the machine, the conversation, and the job to be done. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

HCI relies on several primary components that work together. If one component is weak, the whole interaction feels broken. The first four are the people, the machine, the conversation, and the job to be done.

	Component	Meaning
i	User (صارف)	Any individual or group that interacts with a computer system to achieve defined goals. Two categories: end users (people who directly operate the system, from beginners to experts) and stakeholders (people with an interest in the outcome, such as managers and clients).
ii	Computer system (کمپیوٹر سسٹم)	The platform where humans and computers communicate through input, output and feedback using an interface. It connects human actions with machine responses.
iii	User interaction (صارف کا تعامل)	The process through which a user communicates with a system by performing actions (clicking, tapping, typing, speaking). It transforms user intent into system responses.
iv	Task (کام)	The specific action users perform (for example, booking a ticket). It has three characteristics: task complexity (filling a form vs designing a 3D model), user knowledge (basic typing vs advanced programming), and time requirement (ATM withdrawal vs online passport application).



The user performs a task through interaction with a computer system. All four parts must fit together.

WORKED EXAMPLE

Worked example: label the four components of an HBL ATM withdrawal.

1. **User:** end user = the account holder standing at the machine; stakeholder = the bank that owns the ATM and must keep it safe and working.
2. **Computer system:** the ATM hardware plus the bank's software; it takes PIN input, shows a screen, and dispenses notes (output and feedback).
3. **User interaction:** insert card → type PIN → choose "Cash" → type amount → confirm. Intent ("I want Rs 5,000") becomes a machine response (cash + receipt).
4. **Task:** withdraw cash. Complexity: low (a few buttons). User knowledge: basic (PIN and amounts). Time: about one minute — much shorter than an online passport application.

REMEMBER IT

U-C-I-T: User, Computer system, Interaction, Task. "U Can Interact with Tasks." Then add three task questions: How hard? What skill? How long?

COMMON MISTAKE

Mistake: Calling the bank manager an "end user" of the ATM, or saying a task has only one property (difficulty).

Fix: The manager is usually a **stakeholder**. The person pressing the keys is the **end user**. A task always has complexity, knowledge and time — mention all three in long answers.

اردو میں سمجھیں

ایچ سی آئی کے چار بنیادی اجزاء ہیں: صارف (اینڈ یوزر جو خود سسٹم چلاتا ہے اور اسٹیک ہولڈر جس کا نتیجے میں مفاد ہے)، کمپیوٹر سسٹم (ان پٹ، آؤٹ پٹ اور فیڈبیک کا پلیٹ فارم)، صارف کا تعامل (کلک، ٹیپ، ٹائپ، بولنا) اور کام (ٹاسک) جس کی پیچیدگی، مطلوبہ مہارت اور وقت مختلف ہوتا ہے۔ اے ٹی ایم سے رقم نکالنا آسان اور مختصر کام ہے؛ پاسپورٹ کی آن لائن درخواست لمبا کام ہے۔

CHECK YOURSELF

1. What is the difference between an end user and a stakeholder?
2. Name the three characteristics of a task.
3. In a school portal, who is a stakeholder?

Answers: 1. End users directly operate the system; stakeholders have an interest in the outcome (managers, clients) but may not click the buttons. 2. Task complexity, user knowledge, time requirement. 3. The principal, IT admin or board office — they care about results even if students are the end users.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is the difference between an end user and a stakeholder?

3 marks. Explain Components of HCI with two clear points and one example.

5 marks. Write a 5-mark answer on Components of HCI: definition, two points, a labelled diagram or table, and one example.

Answers: 1. End users directly operate the system; stakeholders have an interest in the outcome (managers, clients) but may not click the buttons. 3. If one component is weak, the whole interaction feels broken.; The first four are the people, the machine, the conversation, and the job to be done. 5. Use the recipe in the blue box. Model opening: HCI relies on several primary components that work together.

BATCH HOMEWORK

Write a 5-mark answer on **Components of HCI** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Types of User Interaction

ACADEMY SESSION

Session 3 of 12 · 45 minutes (second half) · paired with Components of HCI.

45–75 min — this topic. Board working for **Types of User Interaction**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: User interaction can happen in many different ways depending on the technology used.

Error clinic: Mistake: Treating "voice interaction" and "conversational" as identical, or calling a dropdown menu "command-based".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Types of User Interaction**. Write: User interaction can happen in many different ways depending on the technology used.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) User interaction can happen in many different ways depending on the technology used. (2) Learn every type with one clean example — board questions often ask you to "list and explain" five or more. — + example.

5 marks: 3-mark structure + table: Interaction type / Description / Examples + the worked example from this topic.

LEARN IT

User interaction can happen in many different ways depending on the technology used. Learn every type with one clean example — board questions often ask you to "list and explain" five or more.

Interaction type	Description	Examples
Direct manipulation	Handling digital objects on a screen exactly like physical objects.	Dragging files, zooming images with fingers
Command-based	Giving precise instructions through typed text commands.	MS-DOS, Linux terminal (<code>dir</code> , <code>cd ..</code>)
Menu-driven	Selecting from predefined lists or options instead of typing.	Clicking "Start Test" or "Download" on a portal

Interaction type	Description	Examples
Form fill	Entering structured data into blank text fields.	Sign-up forms, ticket booking screens
Conversational	Communicating with systems using natural human language (text or voice).	Chatbots, ChatGPT, Google Assistant
Gesture-based	Using body or hand movements to control systems.	Swiping touchscreens, VR hand gestures
Voice interaction	Speaking commands directly to the system.	"Call Aslam" on a smartphone
Context-aware	Systems sense the environment and act automatically without a prompt.	Smart lighting turning on when you enter a room
Biometric	Using biological features for interaction and authentication.	Fingerprint unlock, FaceID
Haptic and tactile	Providing physical feedback to confirm actions.	Phone vibration when typing
Multimodal	Combining two or more interaction types together.	Voice + touch (speak a search, then tap)

WORKED EXAMPLE

Worked example: a full JazzCash "Send Money" session, labelled by type.

1. Open the app with a fingerprint → **biometric**.
2. Home screen shows Send Money, Bill Payment, Load → you tap Send Money → **menu-driven**.
3. Type the receiver's mobile number and the amount → **form fill**.
4. The keypad vibrates on each tap → **haptic**.
5. Optional: say "Send five hundred to Ali" then tap Confirm → **multimodal** (voice + touch).

Same idea on a **school portal**: menu-driven ("Date Sheet", "Fee Challan"), form fill (leave application), conversational (a chatbot "When is the chemistry practical?").

REMEMBER IT

Group them: hands on screen (direct, gesture, haptic) · words (command, conversational, voice) · lists and blanks (menu, form) · automatic/body (context-aware, biometric) · mix (multimodal).

COMMON MISTAKE

Mistake: Treating "voice interaction" and "conversational" as identical, or calling a dropdown menu "command-based".

Fix: Voice is spoken commands only. Conversational includes typed chat (ChatGPT) as well as voice. Command-based means you type precise codes such as `dir`, not clicking a menu.

اردو میں سمجھیں

تعامل کی اقسام میں براہ راست ہیرا پھیری، کمانڈ، مینو، فارم، گفتگو (چیٹ بوٹ)، اشارہ، آواز، سیاق و سباق سے آگاہ نظام، بایومیٹرک، بیپٹک اور ملٹی موڈل شامل ہیں۔ جاز کیش میں فنگر پرنٹ بایومیٹرک ہے، "رقم بھیجیں" مینو ہے، نمبر لکھنا فارم ہے، اور آواز کے ساتھ ٹیپ ملٹی موڈل ہے۔

CHECK YOURSELF

1. Which type is a Linux `cd ..` command?
2. Smart lighting that turns on when you enter a room is which type?
3. Why is speaking a search and then tapping a result called multimodal?

Answers: 1. Command-based. 2. Context-aware. 3. Because it combines two or more types (voice + touch) in one task.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which type is a Linux `cd ..` command?

3 marks. Explain Types of User Interaction with two clear points and one example.

5 marks. Write a 5-mark answer on Types of User Interaction: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Command-based 3. User interaction can happen in many different ways depending on the technology used.; Learn every type with one clean example — board questions often ask you to "list and explain" five or more. 5. Use the recipe in the blue box. Model opening: User interaction can happen in many different ways depending on the technology used.

BATCH HOMEWORK

Write a 5-mark answer on **Types of User Interaction** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Interface Types, Environment and Feedback

ACADEMY SESSION

Session 4 of 12 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Components v–vii complete the HCI picture: the look of the controls, the place where you use them, and the signals that tell you "it worked" or "try again".

Error clinic: Mistake: Mixing up system feedback with user feedback, or saying "environment" means only the software theme (dark mode).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Interface Types, Environment and Feedback**. Write: Components v–vii complete the HCI picture: the look of the controls, the place where you use them, and the signals that tell you "it worked" or "try again".

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Command-Line Interface (CLI): text-based typing (MS-DOS, Linux terminal). (2) Touch interface: tapping, swiping, pinching (smartphones, tablets). — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Components v–vii complete the HCI picture: the look of the controls, the place where you use them, and the signals that tell you "it worked" or "try again".

v) User interface (UI)

The **user interface** is the medium through which humans interact with computer systems.

- **Graphical User Interface (GUI):** visual elements such as windows, icons and menus (Windows OS, Android).
- **Command-Line Interface (CLI):** text-based typing (MS-DOS, Linux terminal).
- **Touch interface:** tapping, swiping, pinching (smartphones, tablets).
- **Voice User Interface (VUI):** spoken commands (smart speakers).
- **Natural User Interface (NUI):** gestures, body movements or immersive environments (VR headsets, Microsoft Kinect).

vi) Environment

The **environment** is the real-world setting where a person uses a computer system. It is shaped by:

- **Physical conditions** — an ATM outdoors in sunlight, heat, noise, rain.
- **Social conditions** — a quiet classroom, a crowded bazaar, privacy at a PIN pad.
- **Technical hardware** — slow college Wi-Fi, a cracked phone screen, an old browser.

vii) Feedback

Feedback is the signal or response given to confirm or guide actions.

System feedback

Response from the computer: a "Loading..." bar, a "Message Sent!" tick, or an error sound.

User feedback

Input from the user to the system: tapping a "Submit" button, giving a 5-star rating.

WORKED EXAMPLE

Worked example: environment and feedback at a roadside ATM in Hyderabad.

Physical: noon sunlight washes out a dim screen — the GUI must use high contrast.

Social: people stand in a queue; the user needs a privacy shield around the PIN pad.

Technical: the printer may be out of paper, so on-screen "Take your cash" plus a beep still has to confirm the transaction.

System feedback: "Please wait", cash coming out, a printed or SMS receipt.

User feedback: the user presses Confirm, or later rates the bank's app 4 stars.

On a **school portal** during board-exam week, hundreds of students on weak Wi-Fi need a visible "Loading results..." bar. Silence after clicking "View marks" is poor system feedback.

REMEMBER IT

GUI vs CLI vs NUI: GUI = pictures you click. CLI = words you type. NUI = body you move. VUI = voice you speak. Touch = fingers on glass.

Feedback rule: **system talks back; user talks in.**

COMMON MISTAKE

Mistake: Mixing up system feedback with user feedback, or saying "environment" means only the software theme (dark mode).

Fix: A tick mark is system feedback. A 5-star rating is user feedback. Environment is the *real world* around the user — sun, noise, hardware — not the colour of the app (though a good UI will adapt to that world).

اردو میں سمجھیں

یوزر انٹرفیس وہ واسطہ ہے جس سے انسان سسٹم سے بات کرتا ہے: GUI تصاویر اور مینو، CLI لکھی کمانڈ، ٹچ، آواز (VUI) اور قدرتی اشارے (NUI)۔ ماحول وہ حقیقی جگہ ہے جہاں سسٹم استعمال ہوتا ہے — دھوپ میں اے ٹی ایم، خاموش کلاس روم، کمزور وائی فائی۔ سسٹم فیڈبیک مشین کا جواب ہے ("بھیج دیا گیا")؛ صارف کا فیڈبیک صارف کا ان پٹ ہے (سمٹ بٹن یا پانچ ستارے)۔

CHECK YOURSELF

1. Name five types of user interface given in the source.
2. Give one physical and one social example of environment.
3. Is a "Message Sent" tick system feedback or user feedback?

Answers: 1. GUI, CLI, Touch, VUI, NUI. 2. Physical: ATM in sunlight. Social: a quiet classroom. 3. System feedback.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name five types of user interface given in the source.

3 marks. Explain Interface Types, Environment and Feedback with two clear points and one example.

5 marks. Write a 5-mark answer on Interface Types, Environment and Feedback: definition, two points, a labelled diagram or table, and one example.

Answers: 1. GUI, CLI, Touch, VUI, NUI 3. Command-Line Interface (CLI): text-based typing (MS-DOS, Linux terminal).; Touch interface: tapping, swiping, pinching (smartphones, tablets). 5. Use the recipe in the blue box. Model opening: Components v–vii complete the HCI picture: the look of the controls, the place where you use them, and the signals that tell you "it worked" or "try again".

BATCH HOMEWORK

Write a 5-mark answer on **Interface Types, Environment and Feedback** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.4 Importance of HCI ★ Golden

ACADEMY SESSION

Session 5 of 12 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: HCI ensures that machines are approachable and usable, turning complex technology into everyday tools.

Error clinic: Mistake: Writing only "HCI is important because it makes apps look nice." Fix: Looks are a tiny part of UI.

Exam wording to train: Typical wording: "Why is HCI important?"

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Importance of HCI**. Write: HCI ensures that machines are approachable and usable, turning complex technology into everyday tools.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Good design makes technology simple and enjoyable (touchscreens). (2) Poor design causes confusion and risks (unclear buttons on medical devices). — + example.

5 marks: 3-mark structure + table: Implication / Description + the worked example from this topic.

8–10 marks: 5-mark structure + a labelled wireframe and one accessibility fix + a one-line conclusion. Method marks are awarded for working.

LEARN IT

HCI ensures that machines are approachable and usable, turning complex technology into everyday tools.

Good design makes technology simple and enjoyable (touchscreens). **Poor design** causes confusion and risks (unclear buttons on medical devices).

This is why HCI is not optional decoration. A confusing JazzCash confirm button can send money to the wrong number. A confusing school-portal "Submit" can lock a student out of an online exam. Importance questions in the board exam expect the five implications below, each with a sentence of explanation.

Implication	Description
1. Enhance productivity	Well-designed interfaces help users work faster, make fewer mistakes, and achieve goals efficiently.
2. Promotes inclusivity	Accessibility features (screen readers, voice commands) empower marginalized groups and ensure equal use of technology for everyone.
3. Drives innovation	Emerging tech such as AR/VR, AI and IoT rely strictly on solid HCI principles for people to actually adopt and use them.
4. Economic impact	User-friendly products gain higher adoption rates, customer loyalty and market success, driving profits.
5. Ethical responsibility	Responsible design ensures technology respects user privacy, reduces bias and supports human well-being.

WORKED EXAMPLE

Worked example: good vs poor HCI, same task.

Task: send Rs 2,000 through JazzCash to a parent.

Good HCI: large "Send Money" button, amount shown in words and numbers, last 4 digits of the number repeated, fingerprint confirm, green "Successful" plus SMS. Result: fast, few mistakes, the user trusts the app (productivity + economic loyalty + ethics of clear consent).

Poor HCI: tiny grey buttons, no amount-in-words, no confirm screen, no tick. Result: wrong number, no idea if it worked, user deletes the app and goes back to a bank queue.

Medical contrast from the source: unclear buttons on a medical device are not just ugly — they are dangerous. That is why ethical responsibility sits in this table.

REMEMBER IT

P-I-I-E-E: Productivity, Inclusivity, Innovation, Economic impact, Ethics. Sentence: "Please Include Innovative, Ethical Earnings."

COMMON MISTAKE

Mistake: Writing only "HCI is important because it makes apps look nice."

Fix: Looks are a tiny part of UI. Importance answers must name productivity, inclusivity, innovation, money and ethics. Quote the medical-device warning if you have time.

اردو میں سمجھیں

اچھا ایچ سی آئی پیچیدہ ٹیکنالوجی کو روزمرہ کا آسان اوزار بناتا ہے؛ برا ڈیزائن الجھن اور خطرہ پیدا کرتا ہے، جیسے طبی آلے پر غیر واضح بٹن۔ پانچ مضمرات: پیداوری بڑھتی ہے، شمولیت آتی ہے، جدت اپنائی جاتی ہے، معیشت مضبوط ہوتی ہے، اور رازداری و انصاف کی اخلاقی ذمہ داری پوری ہوتی ہے۔

EXAM TIP

Typical wording: "Why is HCI important? Discuss its implications." (8 marks) Write a short opening (good design vs poor design) then five numbered points with one example each. Local examples that earn marks: ATM PIN privacy (ethics), screen reader on a school portal (inclusivity), JazzCash one-tap send (productivity), a bank's app beating a rival because it is easier (economic), AR classroom app that students actually use (innovation). Do not skip ethics — examiners look for privacy and well-being.

CHECK YOURSELF

1. Give one example of poor design mentioned in the source.
2. Which implication is about screen readers and equal use?
3. How does HCI create economic impact?

Answers: 1. Unclear buttons on medical devices. 2. Promotes inclusivity. 3. User-friendly products get higher adoption, loyalty and profits.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Give one example of poor design mentioned in the source.

3 marks. Explain Importance of HCI with two clear points and one example.

5 marks. Typical wording: "Why is HCI important? Discuss its implications." (8 marks) Write a short opening (good design vs poor design) then five numbered points with one example each. Local examples that...

8 marks. Importance of HCI: 5-mark answer plus a labelled wireframe and one accessibility fix.

Answers: 1. Unclear buttons on medical devices 3. Good design makes technology simple and enjoyable (touchscreens).; Poor design causes confusion and risks (unclear buttons on medical devices). 5. Use the recipe in the blue box. Model opening: HCI ensures that machines are approachable and usable, turning complex technology into everyday tools. 8. Same 5-mark body + a labelled wireframe and one accessibility fix + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Importance of HCI** using the recipe in this topic. Include a labelled wireframe and one accessibility fix. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.5 Accessibility Principles

ACADEMY SESSION

Session 6 of 12 · 45 minutes (first half) · paired with Need Analysis for Interface Design.

10–45 min — this topic. Lock the definition and table for **Accessibility Principles**. Starter (0–10) is from last class. Second half is Need Analysis for Interface Design.

On the board: Accessibility principles are HCI guidelines that ensure digital systems are usable by all individuals, including people with diverse physical, sensory and cognitive abilities.

Error clinic: Mistake: "Accessibility is only for people with disabilities, so our class portal does not need it." Fix: The source says usable by all individuals.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Accessibility Principles**. Write: Accessibility principles are HCI guidelines that ensure digital systems are usable by all individuals, including people with diverse physical, sensory and cognitive abilities.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) They remove barriers to create equal access. (2) Accessibility is not a "special extra". — + example.

5 marks: 3-mark structure + table: Principle / What it means / Example + the worked example from this topic.

LEARN IT

Accessibility principles are HCI guidelines that ensure digital systems are usable by **all** individuals, including people with diverse physical, sensory and cognitive abilities. They remove barriers to create equal access.

Accessibility is not a "special extra". It is how you make sure a student with low vision, a shopkeeper who cannot use a mouse, or a colour-blind driver can still complete the task.

Principle	What it means	Example
1. High contrast (واضح رنگ)	Make text and pictures stand out clearly against the background.	Black text on a white background in a railway app, readable in bright sunlight.
2. Readable fonts (پڑھنے میں آسان تحریر)	Clear, simple fonts with proper size and spacing.	A school website using large Calibri so homework instructions are easy to read.
3. Colour-blind friendly design (رنگوں کی پہچان)	Do not depend <i>only</i> on colours; also use symbols or text labels.	A traffic app showing a red circle with a "STOP" label, not just a red colour.
4. Inclusive navigation (آسان نیویگیشن)	Give users different ways to move around a system.	A website that lets you use the Tab key to jump between buttons if you cannot use a mouse.
5. Multimodal detection (متعدد حسی ذرائع)	Present information in different formats (sight, sound, touch).	A video with text captions, or a phone vibrating to alert a user.

WORKED EXAMPLE

Worked example: audit a school portal against the five principles.

1. **Contrast:** are result PDFs pale grey on white? Fail — use dark text.
2. **Fonts:** is the fee-challan note in 9-point decorative script? Fail — large Calibri (or a similar simple font), as the source recommends.
3. **Colour:** is "fail" only a red row with no word "Fail"? Fail — add the word, for colour-blind students.
4. **Navigation:** can a student who cannot use a mouse reach "Download date sheet" with Tab + Enter? If not, fail.
5. **Multimodal:** does the principal's video assembly have captions, and does a fee-due alert vibrate as well as flash? If not, deaf or busy students miss it.

The same five checks apply to an outdoor ATM (sunlight contrast) and to JazzCash (large numerals, Urdu labels, vibration on success).

REMEMBER IT

C-F-C-N-M: Contrast, Fonts, Colour-blind, Navigation, Multimodal. "Can Friends Catch New Messages?"

COMMON MISTAKE

Mistake: "Accessibility is only for people with disabilities, so our class portal does not need it."

Fix: The source says usable by **all** individuals. High contrast also helps in sunlight; captions help in a noisy bus; large fonts help tired eyes during board exams.

اردو میں سمجھیں

رسائی پذیری (Accessibility) کے اصول یقینی بناتے ہیں کہ ہر انسان سسٹم استعمال کر سکے، بشمول مختلف جسمانی، حسی اور ذہنی صلاحیتوں والے افراد۔ پانچ اصول: اونچا تضاد (کنٹراسٹ)، پڑھنے میں آسان فونٹ، صرف رنگ پر انحصار نہ کرنا، کی بورڈ سمیت متبادل نیویگیشن، اور معلومات کو نظر، آواز اور لمس کئی شکلوں میں دینا۔

CHECK YOURSELF

1. Why is a red-only "STOP" sign a problem?
2. Which principle does the Tab key support?
3. Give the source's school-website font example.

Answers: 1. Colour-blind users may not see the meaning if there is no symbol or "STOP" text. 2. Inclusive navigation. 3. Large Calibri on a school website for homework instructions.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Why is a red-only "STOP" sign a problem?

3 marks. Explain Accessibility Principles with two clear points and one example.

5 marks. Write a 5-mark answer on Accessibility Principles: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Colour-blind users may not see the meaning if there is no symbol or "STOP" text. 3. They remove barriers to create equal access.; Accessibility is not a "special extra". 5. Use the recipe in the blue box. Model opening: Accessibility principles are HCI guidelines that ensure digital systems are usable by all individuals, including people with diverse physical, sensory and...

BATCH HOMEWORK

Write a 5-mark answer on **Accessibility Principles** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.6 Need Analysis for Interface Design

ACADEMY SESSION

Session 6 of 12 · 45 minutes (second half) · paired with Accessibility Principles.

45–75 min — this topic. Board working for **Need Analysis for Interface Design**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Need analysis is the process of identifying the gap between the existing situation and the desired outcome.

Error clinic: Mistake: Starting in Figma on day one, then "asking users later".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Need Analysis for Interface Design**. Write: Need analysis is the process of identifying the gap between the existing situation and the desired outcome.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) In HCI it is done before designing a UI, so that you understand users' goals, tasks, abilities and expectations. (2) If you skip need analysis, you guess. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Need analysis is the process of identifying the gap between the **existing situation** and the **desired outcome**. In HCI it is done **before** designing a UI, so that you understand users' goals, tasks, abilities and expectations.

If you skip need analysis, you guess. Guessing is how a school portal ends up with 40 menus and no "Download date sheet" button on the home screen.

Steps in need analysis:



- 1. Identify the users:** who exactly will use the system? (elderly people, teenagers, ...)
- 2. Information collection:** gather data using interviews, questionnaires or observations.
- 3. Analyse user needs:** identify the core problems, goals and requirements.
- 4. Prioritise needs:** decide which features are the most critical to build first.
- 5. Develop solutions:** design a system that meets those verified needs.

WORKED EXAMPLE

Case study from the source: mobile banking app. Before building the app, the team interviews customers and discovers:

- Users want secure login via Fingerprint / FaceID.
- Elderly users need large buttons and simple navigation.
- Users want support for both English and local languages.

Result: the UI is designed around these proven needs, which makes success more likely.

Apply the five steps to a college portal in Sindh.

1. Users: Grade XI–XII students, parents, clerks, teachers. Not "everyone in Pakistan".
2. Collect: interview 20 students; questionnaire to parents; watch a queue at the office on fee day.
3. Analyse: students cannot find date sheets; parents cannot read English-only fee notices; clerks re-type the same form.
4. Prioritise: (1) date sheet on home screen, (2) Urdu/Sindhi fee notice, (3) online leave form. Fancy animations wait.
5. Solution: a simple portal with those three features, large buttons, bilingual labels.

REMEMBER IT

Need analysis = gap finding. Write: Existing = what hurts now. Desired = what "done" looks like. The UI must close that gap, not decorate it.

COMMON MISTAKE

Mistake: Starting in Figma on day one, then "asking users later".

Fix: Need analysis comes **before** UI design. Features you did not hear from users are guesses. Guessed features waste time and fail in exams when the question is "why do we analyse needs?"

اردو میں سمجھیں

نیڈ اینالیسس موجودہ صورتحال اور مطلوبہ نتیجے کے فرق کو یو آئی بنانے سے پہلے تلاش کرتا ہے۔ پانچ قدم: صارفین کی پہچان، انٹرویو یا مشاہدے سے معلومات، ضروریات کا تجزیہ، اہم خصوصیات کو ترجیح، پھر تصدیق شدہ ضرورتوں پر حل۔ موبائل بینکنگ کی مثال: فنگر پرنٹ لاگ ان، بڑے بٹن، اور انگریزی کے ساتھ مقامی زبان۔

CHECK YOURSELF

1. When in the design process is need analysis done?
2. List the five steps in order.
3. Name three needs found in the mobile-banking case study.

Answers: 1. Before designing the UI. 2. Identify users; collect information; analyse needs; prioritise; develop solutions. 3. Fingerprint/FaceID login; large buttons and simple navigation for elderly users; English plus local languages.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. When in the design process is need analysis done?

3 marks. Explain Need Analysis for Interface Design with two clear points and one example.

5 marks. Write a 5-mark answer on Need Analysis for Interface Design: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Before designing the UI. 3. In HCI it is done before designing a UI, so that you understand users' goals, tasks, abilities and expectations.; If you skip need analysis, you guess. 5. Use the recipe in the blue box. Model opening: Need analysis is the process of identifying the gap between the existing situation and the desired outcome.

BATCH HOMEWORK

Write a 5-mark answer on **Need Analysis for Interface Design** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.7 Human-Computer Interaction Problems ★ Golden

ACADEMY SESSION

Session 7 of 12 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: HCI problems are common difficulties that stop users from using technology smoothly.

Error clinic: Mistake: Writing "the app is bad" as an HCI problem, or mixing up cognitive load with compatibility.

Exam wording to train: Common 8-mark question: "Describe problems of HCI with examples." Aim for at least six of the eight, each in the pattern Name → one-line meaning → example.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Human-Computer Interaction Problems**. Write: HCI problems are common difficulties that stop users from using technology smoothly.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) They happen when systems fail to meet human needs or cognitive limits. (2) Cognitive limits means the mind can only hold and process so much at once — if an app asks you to remember three SMS codes at the same... — + example.

5 marks: 3-mark structure + table: Problem / Explanation and example + the worked example from this topic.

8–10 marks: 5-mark structure + a labelled wireframe and one accessibility fix + a one-line conclusion. Method marks are awarded for working.

LEARN IT

HCI problems are common difficulties that stop users from using technology smoothly. They happen when systems fail to meet human needs or cognitive limits. **Cognitive limits** means the mind can only hold and process so much at once — if an app asks you to remember three SMS codes at the same time, it has gone past that limit.

Board answers score well when you name the problem, explain it in one line, and give a concrete example (the source examples are safe; a matching local example is even better).

Problem	Explanation and example
Interface complexity	Too many options or a confusing layout. Example: a shopping app with so many menus you cannot find the checkout button.
Poor feedback	The system does not show if an action worked or failed. Example: clicking Submit and the screen freezes with no confirmation.
Inconsistency	Different parts of the app look or act differently. Example: a magnifying-glass icon for Search on one page, a binocular icon on another.
Accessibility gaps	Design ignores people with disabilities. Example: a video tutorial platform without captions for deaf users.
Compatibility issues	Interface fails on different devices or browsers. Example: a website that works on a laptop but crashes on a mobile browser.
Contextual neglect	The system does not adjust to the user's situation. Example: a map app with no dark mode, blinding the driver at night.
High cognitive load	Users must memorize too much or follow overly complex steps. Example: a registration system forcing you to remember three different SMS codes at once.
Trust deficiency	The system feels unsafe or hides security cues. Example: an online store asking for credit cards but lacking an SSL/HTTPS lock icon.

WORKED EXAMPLE

Worked example: diagnose three local systems.

ATM: six tiny unmarked buttons beside the screen and no "Cash is coming" message → interface complexity + poor feedback. A user walks away while cash is still coming out.

JazzCash: "Send" is green on the home screen but orange on the confirm screen, and there is no padlock on the payment page → inconsistency + trust deficiency.

School portal: works in Chrome on a lab PC, blank on a student's Android browser; exam instructions are a caption-free video; login needs a portal password, an email OTP and an SMS OTP on the same screen → compatibility, accessibility gap, high cognitive load.

Once you can name the problem, Section 1.8 tells you how to fix it.

REMEMBER IT

Eight problems in two families: (1) Screen problems — complexity, inconsistency, accessibility, compatibility, context. (2) Mind-and-trust problems — poor feedback, cognitive load, trust. If the user is lost, look at the screen family. If the user is scared or exhausted, look at the mind family.

COMMON MISTAKE

Mistake: Writing "the app is bad" as an HCI problem, or mixing up cognitive load with compatibility.

Fix: Use the exact names from the table. Cognitive load is "too much to remember". Compatibility is "breaks on another device or browser".

ایچ سی آئی مسائل وہ رکاوٹیں ہیں جو سسٹم کو انسانی ضرورت یا ذہنی حد کے مطابق نہ ہونے پر پیدا ہوتی ہیں۔ آٹھ مسائل: انٹرفیس کی پیچیدگی، کمزور فیڈبیک، عدم مطابقت (ایک جیسا نہ ہونا)، رسائی کی کمی، آلہ/براؤزر سے ناسازگاری، سیاق کو نظرانداز کرنا، زیادہ ذہنی بوجھ، اور اعتماد کی کمی (جیسے HTTPS) کے بغیر کارڈ مانگنا)۔

EXAM TIP

Common 8-mark question: "Describe problems of HCI with examples." Aim for at least six of the eight, each in the pattern Name → one-line meaning → example. Memorise the source examples (checkout buried in menus, frozen Submit, binocular vs magnifying glass, no captions, laptop-only site, no dark mode, three SMS codes, missing HTTPS lock). Adding ATM / JazzCash / portal examples shows application and often gains the last marks.

CHECK YOURSELF

1. Which problem is a missing HTTPS lock on a payment page?
2. Why are three SMS codes at once an HCI problem?
3. A site works on a laptop but crashes on a phone. Name the problem.

Answers: 1. Trust deficiency. 2. High cognitive load — users must memorize too much. 3. Compatibility issues.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which problem is a missing HTTPS lock on a payment page?

3 marks. Explain Human-Computer Interaction Problems with two clear points and one example.

5 marks. Common 8-mark question: "Describe problems of HCI with examples." Aim for at least six of the eight, each in the pattern Name → one-line meaning → example. Memorise the source examples (checkout...).

8 marks. Human-Computer Interaction Problems: 5-mark answer plus a labelled wireframe and one accessibility fix.

Answers: 1. Trust deficiency 3. They happen when systems fail to meet human needs or cognitive limits.; Cognitive limits means the mind can only hold and process so much at once — if an app asks you to remember three SMS codes at the same... 5. Use the recipe in the blue box. Model opening: HCI problems are common difficulties that stop users from using technology smoothly. 8. Same 5-mark body + a labelled wireframe and one accessibility fix + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Human-Computer Interaction Problems** using the recipe in this topic. Include a labelled wireframe and one accessibility fix. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.8 Methods for Improving HCI

ACADEMY SESSION

Session 8 of 12 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Once you can name an HCI problem, you fix it with a matching method.

Error clinic: Mistake: Naming methods without saying what they change ("we will improve HCI" is not an answer).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Methods for Improving HCI**. Write: Once you can name an HCI problem, you fix it with a matching method.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Strengthen accessibility: support disabilities (captions on videos). (2) Ensure consistency: keep layouts uniform (the same "Save" button everywhere). — + example.

5 marks: 3-mark structure + table: Problem (1.7) / Method (1.8) + the worked example from this topic.

LEARN IT

Once you can name an HCI problem, you fix it with a matching method. The source lists eight methods. Learn each with its tiny example — they pair almost one-to-one with Section 1.7.

- **Enhance usability:** simplify navigation (a clear "Buy Now" button).
- **Strengthen accessibility:** support disabilities (captions on videos).
- **Ensure consistency:** keep layouts uniform (the same "Save" button everywhere).
- **Provide clear feedback:** show action results ("Payment Successful" popup).
- **Improve adaptability:** responsive design (the website scales to mobile screens).
- **Apply user-centred design (UCD):** focus on real user goals and pilot-test.
- **Use multimodal interaction:** allow touch, voice or gesture inputs combined.
- **Continuous testing:** regularly update based on user feedback.

User-centred design (UCD) means the real user's goals drive every decision, and you trial (pilot-test) the design with those users instead of guessing in an office.

Responsive design means the layout rearranges itself for phone, tablet and PC, instead of staying a laptop-only page.

WORKED EXAMPLE

Worked example: match each JazzCash / portal problem to a fix.

Problem (1.7)	Method (1.8)
Cannot find "Send Money"	Enhance usability — one clear button
No captions on help video	Strengthen accessibility
Search icon changes from page to page	Ensure consistency
Submit freezes with no message	Clear feedback — "Payment Successful"
Portal crashes on mobile	Improve adaptability — responsive layout
Built features nobody asked for	UCD — interview, then pilot-test
Elderly user cannot type a long number	Multimodal — voice + touch
Complaints ignored after launch	Continuous testing and updates

REMEMBER IT

Think "problem → method" as a pair. Complexity ↔ usability. No captions ↔ accessibility. Different icons ↔ consistency. Freeze ↔ feedback. Phone crash ↔ adaptability. Guessing ↔ UCD. One input only ↔ multimodal. Launch and forget ↔ continuous testing.

COMMON MISTAKE

Mistake: Naming methods without saying *what they change* ("we will improve HCI" is not an answer).

Fix: Always attach the source example: "Provide clear feedback, for example a Payment Successful popup."

اردو میں سمجھیں

ایچ سی آئی بہتر بنانے کے طریقے: نیویگیشن آسان کرنا، رسائی بڑھانا (کیپشن)، ایک جیسا لے آؤٹ، واضح فیڈبیک ("ادائیگی کامیاب")، ریسپانسیو ڈیزائن، صارف مرکز ڈیزائن (UCD) اور پائلٹ ٹیسٹ، ملٹی موڈل ان پٹ، اور مسلسل جانچ۔ ہر مسئلے کا ایک جوڑی دار حل یاد رکھیں۔

CHECK YOURSELF

1. What does UCD stand for, and what extra step does it include?
2. Which method stops a website from failing on a phone?
3. Give the source's example of clear feedback.

Answers: 1. User-Centred Design; focus on real user goals and pilot-test. 2. Improve adaptability (responsive design). 3. A "Payment Successful" popup.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does UCD stand for, and what extra step does it include?

3 marks. Explain Methods for Improving HCI with two clear points and one example.

5 marks. Write a 5-mark answer on Methods for Improving HCI: definition, two points, a labelled diagram or table, and one example.

Answers: 1. User-Centred Design; focus on real user goals and pilot-test 3. Strengthen accessibility: support disabilities (captions on videos).; Ensure consistency: keep layouts uniform (the same "Save" button everywhere). 5. Use the recipe in the blue box. Model opening: Once you can name an HCI problem, you fix it with a matching method.

BATCH HOMEWORK

Write a 5-mark answer on **Methods for Improving HCI** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.9 User Interface Design (UI vs UX) ★ Golden

ACADEMY SESSION

Session 9 of 12 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: UI design is the process of creating and organizing the visual elements of a software application so users can interact with it easily and efficiently.

Error clinic: Mistake: Writing "UI and UX are the same" or "UX is just colours".

Exam wording to train: Highest-yield short question in the chapter: "Differentiate between UI and UX with an example." Write: (1) the two definitions, (2) the sentence "UI is what..."

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **User Interface Design (UI vs UX)**. Write: UI design is the process of creating and organizing the visual elements of a software application so users can interact with it easily and efficiently.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) 1.9.1 Components of a user interface ComponentRole ButtonsClickable elements that perform actions (Submit, Cancel). (2) MenusLists of options for navigating the system. — + example.

5 marks: 3-mark structure + table: Component / Role + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

UI design is the process of creating and organizing the **visual elements** of a software application so users can interact with it easily and efficiently.

1.9.1 Components of a user interface

Component	Role
Buttons	Clickable elements that perform actions (Submit, Cancel).
Menus	Lists of options for navigating the system.
Icons	Small symbols representing tools or actions.
Text fields	Boxes where users type information (passwords, search).
Checkboxes / radio buttons	Selecting options in a form. Checkboxes allow several choices; radio buttons allow only one in a group.
Sliders	Adjusting values along a bar (volume, brightness).

1.9.2 User experience (UX)

UX is the overall experience a user has while interacting with a system — how smooth, comfortable and satisfying it feels.

UI is what you see; UX is how it feels.

WORKED EXAMPLE

Source example: food-delivery app. The UI is the nice pictures of burgers and the red buttons. The UX is that the app loads fast, tracking works, and the food arrives without the user getting frustrated.

Local walk-through: JazzCash.

- **UI:** green Send button, JazzCash logo, amount text field, fingerprint icon, menu of Bill / Load / Send.
- **UX:** login in two seconds, no crash in a weak-signal bazaar, money arrives, SMS comes, the user feels safe and finished — or, if it hangs with no tick, the UX is bad even if the buttons look pretty.

School portal: UI = logo, "Login" button, date-sheet menu icon. UX = a student finds the chemistry practical date in under a minute on a phone, without calling the clerk.

Pretty UI + slow, confusing flow = poor UX. Plain UI + fast, clear flow = good UX.

REMEMBER IT

Clothes vs day out. UI is the outfit (colours, buttons, icons). UX is the whole day (Did you arrive on time? Did you get wet? Were you stressed?). Examiners love the line: *UI is what you see; UX is how it feels.*

COMMON MISTAKE

Mistake: Writing "UI and UX are the same" or "UX is just colours".

Fix: UI = visual components (buttons, menus, icons, fields, checkboxes, sliders). UX = overall smoothness, comfort and satisfaction, including speed and whether the task succeeds.

اردو میں سمجھیں

یو آئی ڈیزائن بصری عناصر — بٹن، مینو، آئیکن، ٹیکسٹ فیلڈ، چیک باکس/ریڈیو، سلائیڈر — کو ترتیب دینا ہے۔ یو ایکس پورا تجربہ ہے: کتنا ہموار، آرام دہ اور اطمینان بخش لگا۔ یو آئی وہ ہے جو آپ دیکھتے ہیں؛ یو ایکس وہ ہے جو آپ محسوس کرتے ہیں۔ کھانے کی ڈیلیوری ایپ میں برگر کی خوبصورت تصویر یو آئی ہے، تیز لوڈنگ اور وقت پر کھانا یو ایکس ہے۔

EXAM TIP

Highest-yield short question in the chapter: "Differentiate between UI and UX with an example." Write: (1) the two definitions, (2) the sentence "UI is what you see; UX is how it feels", (3) the food-delivery example from the source, (4) optionally JazzCash or the school portal. For 5 marks also list four UI components. Do not spend the answer describing Figma — that is the next topic.

CHECK YOURSELF

1. List six UI components from the source.
2. In the food-delivery example, what is UX?
3. Complete: "UI is what you see; UX is ____."

Answers: 1. Buttons, menus, icons, text fields, checkboxes/radio buttons, sliders. 2. The app loads fast, tracking works, food arrives without frustration. 3. how it feels.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. List six UI components from the source.

3 marks. Explain User Interface Design (UI vs UX) with two clear points and one example.

5 marks. Highest-yield short question in the chapter: "Differentiate between UI and UX with an example." Write: (1) the two definitions, (2) the sentence "UI is what you see; UX is how it feels", (3) the...

8 marks. User Interface Design (UI vs UX): 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. Buttons, menus, icons, text fields, checkboxes/radio buttons, sliders 3. 1.9.1 Components of a user interface ComponentRole ButtonsClickable elements that perform actions (Submit, Cancel).; MenusLists of options for navigating the system. 5. Use the recipe in the blue box. Model opening: UI design is the process of creating and organizing the visual elements of a software application so users can interact with it easily and efficiently. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **User Interface Design (UI vs UX)** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.9.3–1.9.5 Wireframing, Figma and Prototypes

ACADEMY SESSION

Session 10 of 12 · 45 minutes (first half) · paired with Test and Evaluate HCI (Evaluation Methods).

10–45 min — this topic. Lock the definition and table for **Wireframing, Figma and Prototypes**. Starter (0–10) is from last class. Second half is Test and Evaluate HCI (Evaluation Methods).

On the board: 1.9.3 Wireframing is creating a basic visual outline or blueprint of a user interface before the final design.

Error clinic: Mistake: Colouring a Lo-Fi wireframe, or thinking a Figma prototype is the finished coded app.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Wireframing, Figma and Prototypes**. Write: 1.9.3 Wireframing is creating a basic visual outline or blueprint of a user interface before the final design.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It plans the structure without focusing on colours or detailed graphics. (2) Low-fidelity wireframes (Lo-Fi) A simple black-and-white sketch showing basic layout (boxes and lines). — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

1.9.3 Wireframing is creating a basic visual outline or blueprint of a user interface **before** the final design. It plans the structure without focusing on colours or detailed graphics.


Low-fidelity wireframes (Lo-Fi)

A simple black-and-white sketch showing basic layout (boxes and lines). Used early to test and share ideas quickly. Focuses purely on structure and flow.


High-fidelity prototypes (Hi-Fi)

A detailed version that looks almost exactly like the final product. Includes real colours, fonts, images and interactive clickable buttons. Used for final user testing.

Lo-Fi sketch → Add details → Hi-Fi prototype



→
add colour



A school-portal login: Lo-Fi boxes and labels on the left; a coloured, realistic Hi-Fi prototype on the right.

1.10 What is Figma?

Figma is a popular, free, web-based tool used to design and collaborate on UI and prototypes. It works directly in a web browser — you do not have to install a heavy program on the college lab PCs.

Creating a low-fidelity design in Figma

1. **Sign up:** access the Figma workspace online.
2. **Create frames:** select the Frame tool (for example an iPhone-sized frame) to act as your screen canvas.
3. **Add shapes:** draw basic rectangles for buttons and circles for avatars.
4. **Add text:** use the text tool to label buttons (for example, "Sign Up").
5. **Duplicate and edit:** copy the frame to create the next screen (for example, the Home Screen).

1.9.5 Prototype design

A **prototype** is an early interactive model used to test design ideas **before writing actual code**. In Figma you use the Prototype tab to link screens together.

- Set a **Trigger** (for example, "On Tap").
- Set an **Action** (for example, "Navigate to Home Screen").

Real users can then click through the fake app to see if the navigation makes sense.

WORKED EXAMPLE

Worked example: JazzCash-style "Send Money" in Figma, without writing code.

1. Lo-Fi on paper or in Figma: three frames — Home (boxes: Send, Bills, Load), Amount (text field + Next), Success (tick + Done).
2. Show the sketch to two classmates. If they cannot find Send, move that box to the top. This is the point of Lo-Fi: cheap changes.
3. In Figma, add a phone frame, rectangles, and labels. Duplicate the frame for Home, Amount and Success.
4. Prototype tab: Trigger = On Tap of the Send rectangle; Action = Navigate to Amount. On Tap of Next → Success.
5. Hand the laptop to a student. If they tap Bills by mistake, the navigation is still wrong — fix it before any programmer writes Java or Kotlin.

REMEMBER IT

Lo-Fi = boxes. Hi-Fi = almost the real app. Prototype = clickable. Figma can hold all three stages. Trigger = what the user does. Action = where the fake app goes.

COMMON MISTAKE

Mistake: Colouring a Lo-Fi wireframe, or thinking a Figma prototype is the finished coded app.

Fix: Lo-Fi stays black-and-white on purpose so people discuss structure, not taste in colours. A prototype tests ideas before code; developers still have to build the real system afterwards.

اردو میں سمجھیں

وائر فریم یو آئی کا بنیادی خاکہ ہے، رنگوں سے پہلے۔ لو فائی سیاہ و سفید ڈبے ہیں؛ ہائی فائی تقریباً حتمی شکل ہے، رنگ، فونٹ اور کلک ہونے والے بٹن کے ساتھ۔ فگما (Figma) مفت ویب ٹول ہے: فریم بناؤ، شکل اور متن ڈالو، فریم کاپی کرو۔ پروٹوٹائپ کوڈ سے پہلے کا چلنے والا نمونہ ہے جس میں ٹرگر (On Tap) اور ایکشن (اگلی اسکرین) جوڑے جاتے ہیں۔

CHECK YOURSELF

1. What does a Lo-Fi wireframe deliberately leave out?
2. Where does Figma run?
3. In Figma prototyping, what is a trigger? Give the source example.

Answers: 1. Colours and detailed graphics (it is structure only). 2. Directly in a web browser. 3. The user event that starts a move between screens, e.g. "On Tap".

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does a Lo-Fi wireframe deliberately leave out?

3 marks. Explain Wireframing, Figma and Prototypes with two clear points and one example.

5 marks. Write a 5-mark answer on Wireframing, Figma and Prototypes: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Colours and detailed graphics (it is structure only) 3. It plans the structure without focusing on colours or detailed graphics.; Low-fidelity wireframes (Lo-Fi) A simple black-and-white sketch showing basic layout (boxes and lines). 5. Use the recipe in the blue box. Model opening: 1.9.3 Wireframing is creating a basic visual outline or blueprint of a user interface before the final design.

BATCH HOMEWORK

Write a 5-mark answer on **Wireframing, Figma and Prototypes** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.11 Test and Evaluate HCI (Evaluation Methods)

ACADEMY SESSION

Session 10 of 12 · 45 minutes (second half) · paired with Wireframing, Figma and Prototypes.

45–75 min — this topic. Board working for **Test and Evaluate HCI (Evaluation Methods)**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Testing checks if the product works properly (finding bugs).

Error clinic: Mistake: Saying testing and evaluation are the same, or mixing formative with summative.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Test and Evaluate HCI (Evaluation Methods)**. Write: Testing checks if the product works properly (finding bugs).

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Evaluation determines whether it meets users' needs (usability). (2) Together they improve the product before release. — + example.

5 marks: 3-mark structure + table: Method / Description + the worked example from this topic.

LEARN IT

Testing checks if the product works properly (finding bugs). **Evaluation** determines whether it meets users' needs (usability). Together they improve the product before release.

A school portal can be "bug-free" (testing passed) and still unusable if students cannot find the date sheet (evaluation failed). You need both.

1.11.1 Evaluation methods

Method	Description
SUS (System Usability Scale)	A standard 10-item questionnaire used to calculate a score for how usable a system is.
NPS (Net Promoter Score)	Asks users: "How likely are you to recommend this app to a friend?" Measures user loyalty.
Formative evaluation	Done during development to collect early feedback and improve the design continuously.
Summative evaluation	Done at the end of development to measure overall success against the original goals.
Expert reviews	Usability specialists review the app against established design standards (heuristics).

Heuristics are agreed rules of good design (for example "show system status", "be consistent"). An expert review checks the product against those rules without waiting for a huge user survey.

WORKED EXAMPLE

Worked example: when to use each method on a school portal.

1. Week 2 of building: show the Lo-Fi to five students, change the menu. That is **formative** evaluation.
2. A teacher who has studied HCI checks the screens against standard rules (Is feedback visible? Are labels consistent?). That is an **expert review**.
3. After the portal is "finished", 30 students fill the 10 SUS questions. A low score means it is still hard to use, even if there are no crashes.
4. Ask: "On a scale of 0–10, would you recommend this portal to a friend in another college?" That is **NPS** (loyalty).
5. Compare the finished portal with the original goals (date sheet in one tap, bilingual fee notice). That is **summative** evaluation.

REMEMBER IT

Formative = forming it (during). Summative = summing it up (end). SUS = 10 questions on usability. NPS = "Would you recommend it?" Expert = specialist vs heuristics.

COMMON MISTAKE

Mistake: Saying testing and evaluation are the same, or mixing formative with summative.

Fix: Testing = bugs. Evaluation = does it meet human needs. Formative is during; summative is at the end against original goals.

ٹیسٹنگ یہ دیکھتی ہے کہ پروڈکٹ ٹھیک چلتا ہے (بگز)؛ ایویلیوایشن یہ دیکھتی ہے کہ صارف کی ضرورت پوری ہوئی۔ SUS دس سوالوں والا استعمال کا اسکور ہے، NPS پوچھتا ہے کہ آپ یہ ایپ دوست کو کتنی تجویز کریں گے۔ فارمیٹو جانچ ترقی کے دوران ہوتی ہے، سمیٹو آخر میں اہداف کے خلاف۔ ماہر جائزہ ہیورسٹکس (Heuristics) پر ہوتا ہے۔

CHECK YOURSELF

1. What is the difference between testing and evaluation?
2. How many items are on the SUS questionnaire?
3. When is summative evaluation done?

Answers: 1. Testing finds bugs / checks the product works; evaluation checks it meets users' needs (usability). 2. 10. 3. At the end of development, against the original goals.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is the difference between testing and evaluation?

3 marks. Explain Test and Evaluate HCI (Evaluation Methods) with two clear points and one example.

5 marks. Write a 5-mark answer on Test and Evaluate HCI (Evaluation Methods): definition, two points, a labelled diagram or table, and one example.

Answers: 1. Testing finds bugs / checks the product works; evaluation checks it meets users' needs (usability) 3. Evaluation determines whether it meets users' needs (usability).; Together they improve the product before release. 5. Use the recipe in the blue box. Model opening: Testing checks if the product works properly (finding bugs).

BATCH HOMEWORK

Write a 5-mark answer on **Test and Evaluate HCI (Evaluation Methods)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

1.11.2 Testing Methods (Usability, A/B, Automated)

★ Golden

ACADEMY SESSION

Session 11 of 12 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Testing involves observing how the system behaves under specific conditions.

Error clinic: Mistake: Calling A/B testing "showing both designs to the same user and asking which is prettier".

Exam wording to train: Golden 8-mark question: "Explain testing methods used in HCI." Write seven short paragraphs or a seven-row table.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Testing Methods (Usability, A/B, Automated)**. Write: Testing involves observing how the system behaves under specific conditions.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Task-based testing: assigning a specific task (for example, "Find a product and add it to cart") and strictly measuring completion time,... (2) Automated audits: software bots scan websites to detect technical issues such as broken links, slow loading speeds or low colour contrast. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Testing involves observing how the system behaves under specific conditions. Learn all seven methods. The three named in the heading — usability, A/B and automated — are the ones examiners ask most, but a complete answer also names the others.

1. **Usability testing:** observing real users while they perform realistic tasks, to measure efficiency and satisfaction. If the user gets stuck, designers know where to fix the UI.
2. **Task-based testing:** assigning a specific task (for example, "Find a product and add it to cart") and strictly measuring **completion time**, **success rate** and **number of errors**.
3. **Automated audits:** software bots scan websites to detect technical issues such as broken links, slow loading speeds or low colour contrast.
4. **A/B testing:** comparing two versions of an interface (A and B). Half the users see A, half see B. The one with more clicks or sign-ups wins.
5. **Compatibility testing:** verifying the system on different browsers (Chrome, Safari), devices (mobiles, tablets, PCs) and operating systems.
6. **Performance and load testing:** simulating high traffic (for example 10,000 users logging in at once) to see if speed drops or the server crashes.
7. **Keyboard and screen-reader walkthroughs:** navigating using *only* the keyboard (Tab/Enter) or assistive technologies, to check accessibility for users with disabilities.

Task-based

"Add to cart"

Time: 12 s

Success: Yes

A/B test

Version A | Version B

half / half users

more clicks wins

Automated audit

Bot scanning...

3 broken links

Low contrast

Three golden testing pictures: timed tasks, A versus B, and a bot that finds broken links and weak contrast.

WORKED EXAMPLE

Worked example: test JazzCash "Send Money" and a school portal with numbers.

Usability testing. Sit beside five students. Task: "Send Rs 100 to this test number." Do not help. Note where they pause. If three people look for Confirm at the bottom and it is at the top, that is your UI fix.

Task-based testing (numbers). Same task for 10 students.

- Success: 8 of 10 finish = success rate $(8 \div 10) \times 100 = 80\%$.
- Times: 12, 14, 11, 40, 13, 12, 15, 50, 14, 12 seconds. The two slow times (40, 50) are the students who got stuck — they also made errors.
- Errors: extra taps, wrong field. Count them. High errors + high time = poor HCI, even if most people eventually succeed.

A/B testing. Version A: green "Send" at the top. Version B: large orange "Send" under the amount. 200 users each. If B gets 140 completed payments and A gets 90, B wins. You keep B.

Automated audit. A bot reports 3 broken "Fee challan" links and low contrast on the portal's grey-on-grey marks table. Fix those before the board-exam rush.

Load testing. On result day, 10,000 students log in at 9:00 a.m. If the server crashes, performance testing failed — the UI never even appears.

Keyboard walkthrough. Unplug the mouse. Can a student Tab to "Download date sheet" and press Enter? If focus jumps randomly, accessibility testing failed.

REMEMBER IT

Task-based three numbers: Time, Success, Errors. **A/B:** two versions, split users, the higher clicks/sign-ups win. **Bot:** links, speed, contrast. **Load:** many users at once. **Keyboard:** Tab and Enter only.

COMMON MISTAKE

Mistake: Calling A/B testing "showing both designs to the same user and asking which is prettier".

Fix: Half the users see only A, half see only B. You measure behaviour (clicks, sign-ups), not a taste vote. Also: an automated audit does not replace watching real users — bots cannot see that a student is confused.

اردو میں سمجھیں

سات ٹیسٹنگ طریقے: یوزیبلٹی (حقیقی صارف کو کام کرتے دیکھنا)، ٹاسک بیسڈ (وقت، کامیابی، غلطیاں ناپنا)، خودکار آڈٹ (بوت ٹوٹے لنک، سست رفتار، کم کنٹراسٹ ڈھونڈنے)، اے/بی ٹیسٹ (آدھا صارف اے، آدھا بی؛ زیادہ کلک والا جیتے)، کمپیٹیبلٹی (براؤزر اور آلہ)، لوڈ ٹیسٹ (مثلاً دس ہزار لاگ ان)، اور صرف کی بورڈ یا اسکرین ریڈر سے چل کر رسائی کی جانچ۔

EXAM TIP

Golden 8-mark question: "Explain testing methods used in HCI." Write seven short paragraphs or a seven-row table. For full marks, define usability testing (observe real users on realistic tasks), give the three task-based measures, describe automated audits with the three bot findings (broken links, slow load, low contrast), explain A/B with the half-and-half rule, then add compatibility, load (10,000 users), and keyboard/screen-reader walkthroughs. If the paper asks only "usability, A/B and automated", go deep on those three and still mention the rest in one closing line.

CHECK YOURSELF

1. Name the three measurements in task-based testing.
2. In A/B testing, who sees version A?
3. Give two issues an automated audit can detect.

Answers: 1. Completion time, success rate, number of errors. 2. Half of the users (the other half see B). 3. Any two of: broken links, slow loading, low colour contrast.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name the three measurements in task-based testing.

3 marks. Explain Testing Methods (Usability, A/B, Automated) with two clear points and one example.

5 marks. Golden 8-mark question: "Explain testing methods used in HCI." Write seven short paragraphs or a seven-row table. For full marks, define usability testing (observe real users on realistic tasks),...

8 marks. Testing Methods (Usability, A/B, Automated): 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. Completion time, success rate, number of errors. 3. Task-based testing: assigning a specific task (for example, "Find a product and add it to cart") and strictly measuring completion time,...; Automated audits: software bots scan websites to detect technical issues such as broken links, slow... 5. Use the recipe in the blue box. Model opening: Testing involves observing how the system behaves under specific conditions. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Testing Methods (Usability, A/B, Automated)** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Career Opportunities in UI/UX

ACADEMY SESSION

Session 12 of 12 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The same HCI skills you practised on ATMs, JazzCash and school portals are real jobs.

Error clinic: Mistake: "UI designer and UX designer are one job." Fix: In small teams one person may wear both hats, but the source lists them separately: UX researches...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Career Opportunities in UI/UX**. Write: The same HCI skills you practised on ATMs, JazzCash and school portals are real jobs.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The same HCI skills you practised on ATMs, JazzCash and school portals are real jobs. (2) Each role uses a different slice of this chapter. — + example.

5 marks: 3-mark structure + table: Career / What the person does + the worked example from this topic.

LEARN IT

The same HCI skills you practised on ATMs, JazzCash and school portals are real jobs. Each role uses a different slice of this chapter.

Career	What the person does
UX designer	Researches user needs to ensure the app is intuitive and satisfying.
UI designer	Designs the visual layout (colours, typography, buttons) using tools such as Figma.
Interaction designer	Focuses on the flow between screens, animations and gestures.
Usability researcher	Runs SUS/NPS tests and A/B tests with real users to find flaws.
Accessibility specialist	Ensures products meet inclusive standards for people with disabilities.

WORKED EXAMPLE

Worked example: who does which JazzCash task?

- "Interview shopkeepers about sending money" → **UX designer**.
- "Pick the green, the typeface and the Send button in Figma" → **UI designer**.
- "On Tap Send, slide to Confirm, then Success" → **interaction designer**.
- "Run SUS and an A/B test of two Send buttons" → **usability researcher**.
- "Check contrast, captions and Tab order" → **accessibility specialist**.

REMEMBER IT

UI looks; UX asks; interaction connects screens; research measures; accessibility includes everyone.

COMMON MISTAKE

Mistake: "UI designer and UX designer are one job."

Fix: In small teams one person may wear both hats, but the source lists them separately: UX researches needs and satisfaction; UI draws the visual layout in tools like Figma.

اردو میں سمجھیں

اس باب سے ملازمتیں: یو ایکس ڈیزائنر صارف کی ضرورت تحقیق کرتا ہے، یو آئی ڈیزائنر فگما میں رنگ اور بٹن بناتا ہے، انٹریکشن ڈیزائنر اسکرینوں کا بہاؤ سنبھالتا ہے، یوزیبیلیٹی ریسرچر SUS، NPS اور اے/بی ٹیسٹ چلاتا ہے، اور ایکسیسیبیلیٹی ماہر سب کے لیے رسائی یقینی بناتا ہے۔

CHECK YOURSELF

1. Who runs SUS, NPS and A/B tests?
2. Which career uses Figma for colours, type and buttons?

Answers: 1. Usability researcher. 2. UI designer.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Who runs SUS, NPS and A/B tests?

3 marks. Explain Career Opportunities in UI/UX with two clear points and one example.

5 marks. Write a 5-mark answer on Career Opportunities in UI/UX: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Usability researcher 3. The same HCI skills you practised on ATMs, JazzCash and school portals are real jobs.; Each role uses a different slice of this chapter. 5. Use the recipe in the blue box. Model opening: The same HCI skills you practised on ATMs, JazzCash and school portals are real jobs.

BATCH HOMEWORK

Write a 5-mark answer on **Career Opportunities in UI/UX** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Chapter 1 Review

Chapter summary

- **HCI** (also CHI, MMI) designs technology to be easy, efficient and responsive to people, using five sensory channels: sight, touch (haptics), hearing, voice and spatial.
- **Traditional interaction** uses mouse, keyboard, keypad or simple tap/swipe; **natural interaction** uses voice, face or body gesture without a mouse or keyboard.
- HCI applications cover **health care, banking, education, and networking/communication**, each with a clear user benefit (remote care, quick secure money, better learning, global connection).
- Four core components: **user** (end user vs stakeholder), **computer system**, **user interaction**, and **task** (complexity, knowledge, time).
- Interaction types include direct manipulation, command-based, menu-driven, form fill, conversational, gesture, voice, context-aware, biometric, haptic and multimodal.
- Interfaces: GUI, CLI, touch, VUI, NUI. **Environment** is physical, social and technical. **System feedback** is the machine's reply; **user feedback** is what the person sends in.
- HCI matters for productivity, inclusivity, innovation, economic impact and ethical responsibility. Poor design (unclear medical buttons) creates risk.
- Five accessibility principles: high contrast, readable fonts, colour-blind friendly labels, inclusive navigation, multimodal presentation.
- **Need analysis** finds the gap before UI design: identify users, collect data, analyse, prioritise, develop solutions (banking case: FaceID, large buttons, local language).
- Eight HCI problems: complexity, poor feedback, inconsistency, accessibility gaps, compatibility, contextual neglect, high cognitive load, trust deficiency.
- Improve HCI with usability, accessibility, consistency, clear feedback, adaptability (responsive design), UCD and pilot tests, multimodal input, and continuous testing.
- **UI** is the visual components (buttons, menus, icons, fields, checkboxes, sliders); **UX** is how the whole experience feels. UI is what you see; UX is how it feels.
- Lo-Fi wireframes plan structure; Hi-Fi prototypes look real; **Figma** is a free browser tool; prototypes use Trigger (On Tap) and Action (navigate) before code.
- Evaluation (SUS, NPS, formative, summative, expert/heuristic reviews) checks needs; testing (usability, task-based, automated, A/B, compatibility, load, keyboard/screen-reader) checks behaviour under conditions.

Key terms

Term	Meaning	اردو
HCI	Human-Computer Interaction; designing technology that is easy, efficient and responsive to people. Also called CHI or MMI.	انسان اور کمپیوٹر کا باہمی تعامل
Haptics	Physical feedback you can feel, such as a vibration.	لمسی / ارتعاشی جواب
Traditional interaction	Using standard input/output such as mouse, keyboard, keypad or simple tap and swipe.	روایتی تعامل
Natural interaction	Interacting without mouse or keyboard, using voice, face or body gesture.	قدرتی تعامل
End user	A person who directly operates the system.	حتمی صارف
Stakeholder	A person or group with an interest in the system's outcome (manager, client).	فریق مفاد
GUI	Graphical User Interface using windows, icons and menus.	تصویری صارف انٹرفیس
CLI	Command-Line Interface using typed text commands.	کمانڈ لائن انٹرفیس
NUI	Natural User Interface using gestures, body movement or immersive environments (VR, Kinect).	قدرتی صارف انٹرفیس
System feedback	The computer's response that confirms or guides an action.	نظام کا جواب
User feedback	Input the user sends to the system (Submit click, star rating).	صارف کی رائے / ان پٹ
Accessibility	Making digital systems usable by all, including people with diverse abilities.	رسائی پذیری
Need analysis	Finding the gap between the current situation and the desired outcome before designing a UI.	ضروریات کا تجزیہ
Cognitive load	How much the user must remember or process at once.	ذہنی بوجھ
UCD	User-Centred Design: focus on real user goals and pilot-test.	صارف مرکز ڈیزائن
UI	The visual elements of an application (buttons, menus, icons, fields, sliders).	صارف انٹرفیس

Term	Meaning	اردو
UX	The overall smoothness, comfort and satisfaction of using a system.	صارف کا تجربہ
Wireframe	A basic outline of a UI that plans structure without colours or detailed graphics.	انٹرفیس کا خاکہ
Lo-Fi	Low-fidelity sketch of boxes and lines used early to test ideas.	کم تفصیل والا خاکہ
Hi-Fi	High-fidelity prototype that looks almost like the final product.	زیادہ تفصیل والا نمونہ
Prototype	An early interactive model used to test design ideas before writing code.	ابتدائی چلنے والا نمونہ
Figma	A free, web-based tool for UI design and prototypes.	فگما (ویب پر یو آئی ٹول)
SUS	System Usability Scale: a 10-item questionnaire that scores how usable a system is.	نظام کی استعمال پذیری کا پیمانہ
NPS	Net Promoter Score: how likely a user is to recommend the app to a friend.	تجویز کا درجہ (وفاداری)
Formative evaluation	Evaluation during development to improve the design continuously.	دورانِ تعمیر جانچ
Summative evaluation	Evaluation at the end, measured against original goals.	اختتامی جانچ
A/B testing	Showing version A to half the users and version B to the other half; the better-performing version wins.	اے/بی موازنہ ٹیسٹ
Automated audit	Bots scanning for broken links, slow pages or low contrast.	خودکار جانچ
Heuristic	An established design standard used in expert reviews.	مستند ڈیزائن اصول

Practice: multiple choice

1. HCI is also known as:
 - a. CPU and ALU
 - b. CHI or MMI
 - c. HTTP or HTML
 - d. GUI only
2. Which sensory channel tracks body movement in VR?
 - a. Sight
 - b. Hearing
 - c. Spatial
 - d. Voice
3. Unlocking a phone with FaceID is an example of:
 - a. natural interaction
 - b. command-based interaction only
 - c. traditional interaction
 - d. CLI
4. Which domain of HCI includes patient portals and telemedicine?
 - a. Banking
 - b. Education
 - c. Networking
 - d. Health care
5. A bank manager who never uses the ATM but cares that it works is a:
 - a. stakeholder
 - b. end user
 - c. haptic device
 - d. wireframe
6. Typing `dir` in MS-DOS is:
 - a. menu-driven
 - b. command-based
 - c. context-aware
 - d. biometric
7. A "Message Sent!" tick mark is:
 - a. user feedback
 - b. a stakeholder
 - c. need analysis
 - d. system feedback
8. Unclear buttons on a medical device mainly show that poor HCI:
 - a. only affects game apps
 - b. is a colour preference
 - c. causes confusion and risk
 - d. improves load testing
9. Not depending only on colour, but adding a "STOP" label, is:
 - a. colour-blind friendly design
 - b. load testing
 - c. CLI design
 - d. A/B testing
10. Need analysis for a UI should be done:
 - a. after the product is sold
 - b. before designing the UI
 - c. only by programmers
 - d. instead of testing
11. An online store that asks for a credit card but shows no HTTPS lock has:
 - a. high contrast
 - b. natural interaction
 - c. summative evaluation
 - d. trust deficiency
12. "UI is what you see; UX is how it feels" means:
 - a. UI and UX are identical
 - b. UX is only the logo colour
 - c. UI is code and UX is hardware
 - d. UI is visual elements; UX is the overall experience
13. A Lo-Fi wireframe should focus on:
 - a. final photographs and brand colours
 - b. structure and flow using boxes and lines
 - c. server load of 10,000 users
 - d. writing the finished Python code
14. The System Usability Scale (SUS) is:
 - a. a 10-item questionnaire that scores usability
 - b. a bot that finds broken links
 - c. a type of ATM keypad
 - d. a Figma trigger
15. In A/B testing:
 - a. every user sees both versions at once and votes for the prettier one
 - b. only experts review heuristics
 - c. half the users see A, half see B, and the version with more clicks or sign-ups wins
 - d. the server is crashed on purpose

Practice: short questions

1. Define HCI. Give two other names for it and list the five sensory channels.
2. Differentiate traditional interaction from natural interaction with one example of each from daily Pakistani use.
3. State four domains of HCI. For each, give one application and one user benefit.
4. Name the four primary HCI components. Distinguish end user from stakeholder, and list the three characteristics of a task.
5. Define GUI, CLI, VUI and NUI, with one example of each.
6. Write five implications of the importance of HCI.
7. List the five accessibility principles with one example each.
8. What is need analysis? Write its five steps and three findings from the mobile-banking case study.
9. Differentiate UI from UX using the food-delivery example. Name six UI components.
10. What is A/B testing? How is it different from an automated audit?

Practice: long / problem questions

1. Explain the components of HCI (user, computer system, user interaction, task, interface types, environment, feedback). Illustrate every part with a labelled walk-through of a person withdrawing cash from an outdoor ATM in Hyderabad.
2. Describe eight HCI problems with examples. Then match each problem to a method of improving HCI. Use JazzCash or a school portal wherever it makes the example clearer.
3. "UI is what you see; UX is how it feels." Explain UI design, its six components, and UX. Then describe Lo-Fi wireframes, Hi-Fi prototypes, the steps of making a low-fidelity design in Figma, and how a Figma prototype uses a trigger and an action. Sketch a Lo-Fi school-portal login.
4. Differentiate testing from evaluation. Explain SUS, NPS, formative evaluation, summative evaluation and expert reviews. Then explain usability testing, task-based testing (including the three measurements), automated audits, A/B testing, compatibility testing, performance/load testing, and keyboard/screen-reader walkthroughs. Apply three of these methods to a college portal on result day.
5. A team is designing a JazzCash-style "Send Money" screen for elderly users in Sukkur who speak Sindhi, stand in bright sunlight, and have never used a CLI. Carry out a need analysis (five steps), list accessibility principles you will apply, choose interaction types, and say which evaluation and testing methods you will use before launch and why.

Answer key

Multiple choice

1. b
2. c
3. a
4. d
5. a
6. b
7. d
8. c
9. a
10. b
11. d
12. d
13. b
14. a
15. c

Short questions — model answers

1. HCI is the design of technology to serve people; systems that are easy to use, efficient and responsive. Also called CHI (Computer-Human Interface) and MMI (Man-Machine Interaction). Channels: sight, touch, hearing, voice, spatial.
2. Traditional uses standard I/O (mouse, keyboard, keypad, simple tap/swipe), e.g. an ATM keypad or typing on a school portal. Natural lets people interact without mouse or keyboard, using voice, face or gesture, e.g. FaceID or "Alexa, play a song".
3. Health care: patient portals / telemedicine — remote access to medical services. Banking: mobile banking and ATMs — quick, secure transactions. Education: LMS and exam portals — better teaching, learning and engagement. Networking: WhatsApp, Zoom, social media — global connection and collaboration.
4. User, computer system, user interaction, task. End users directly operate the system; stakeholders (managers, clients) have an interest in the outcome. Task characteristics: complexity, user knowledge, time requirement.
5. GUI: windows, icons, menus (Windows, Android). CLI: typed commands (MS-DOS, Linux). VUI: spoken commands (smart speakers). NUI: gestures, body, immersive VR/Kinect.
6. Enhance productivity; promote inclusivity; drive innovation (AR/VR, AI, IoT need solid HCI); economic impact (adoption, loyalty, profit); ethical responsibility (privacy, less bias, well-being).
7. High contrast (black text on white in a railway app); readable fonts (large Calibri on a school site); colour-blind friendly (STOP label, not colour alone); inclusive navigation (Tab key); multimodal detection (captions or vibration).
8. Need analysis finds the gap between the existing situation and the desired outcome, before UI design. Steps: identify users; collect information (interviews, questionnaires, observation); analyse needs; prioritise; develop solutions. Banking case: Fingerprint/FaceID login; large buttons and simple navigation for elderly users; English and local languages.
9. UI is the visual elements so people can interact easily; UX is the overall smoothness, comfort and satisfaction. Food app: UI = burger pictures and red buttons; UX = fast load, working tracking, food arrives without frustration. Components: buttons, menus, icons, text fields, checkboxes/radio buttons, sliders.
10. A/B testing shows version A to half the users and version B to the other half; the version with more clicks or sign-ups wins. An automated audit uses bots to scan for technical issues such as broken links, slow loading or low contrast; it does not split users between two designs.

Long questions — model answers

- 1. Components through an outdoor ATM.** User: end user = account holder; stakeholder = bank. Computer system: ATM hardware and bank software linking PIN input to cash output. Interaction: insert card, type PIN, choose Cash, confirm — intent becomes a response. Task: withdraw cash; low complexity, basic knowledge, about one minute (contrast with a long passport application). Interface: GUI on screen + keypad (traditional); possibly fingerprint (biometric). Environment: physical sunlight so contrast must be high; social queue so a privacy shield is needed; technical printer or network may fail. System feedback: "Please wait", cash, receipt/SMS. User feedback: pressing Confirm. If any part is weak (glare, no "cash coming" message), HCI fails even if the bank account is correct.
- 2. Problems and methods.** Interface complexity (buried checkout / hidden Send Money) → enhance usability (clear Buy Now / Send). Poor feedback (frozen Submit) → Payment Successful popup. Inconsistency (magnifying glass vs binoculars, or Send changing colour) → same Save/Send control everywhere. Accessibility gaps (no captions) → strengthen accessibility. Compatibility (laptop-only portal) → responsive/adaptability. Contextual neglect (map with no night mode; ATM unreadable in sun) → design for environment. High cognitive load (three SMS codes) → simplify steps. Trust deficiency (no HTTPS lock on JazzCash-style payment) → show security cues. Also apply UCD with a pilot test, multimodal input (voice + touch for elderly users), and continuous testing after launch.
- 3. UI, UX, wireframe, Figma, prototype.** UI design organises visual elements. Six components: buttons (Submit/Cancel), menus, icons, text fields, checkboxes/radio, sliders. UX = overall experience; UI is what you see, UX is how it feels; food-delivery pictures vs fast delivery. Lo-Fi: black-and-white boxes for structure; Hi-Fi: real colour, type, images, clickable controls for final tests. Figma: sign up in the browser; Frame tool for a phone canvas; rectangles and circles; text labels such as Sign Up; duplicate frames for the next screen. Prototype: before code, Prototype tab, Trigger = On Tap, Action = Navigate to Home. Sketch: header "LOGO / Portal", dashed Username and Password boxes, a LOGIN rectangle, "Forgot password?" — the Lo-Fi login in this chapter.
- 4. Test vs evaluate, then methods.** Testing finds bugs / whether it works; evaluation checks whether it meets user needs. SUS: 10-item usability score. NPS: "recommend to a friend?" (loyalty). Formative: during development. Summative: at the end vs original goals. Expert reviews: specialists vs heuristics. Usability testing: watch real users on realistic tasks. Task-based: time, success rate, errors (e.g. Add to cart in 12 s, success yes). Automated audit: bots find broken links, slow load, low contrast. A/B: half/half, more clicks win. Compatibility: Chrome/Safari, phone/tablet/PC, OS. Load: 10,000 logins at once. Keyboard/screen-reader: Tab/Enter and assistive tech. Result-day portal: load-test the 9:00 a.m. rush; usability-test "find chemistry marks"; automated audit for broken result links and grey-on-grey contrast; optional A/B of two home-screen layouts.
- 5. Send Money for elderly users in Sukkur.** Need analysis: (1) users = elderly Sindhi speakers, not teenagers; (2) collect: interviews and watch them at a JazzCash shop agent; (3) analyse: fear of wrong number, cannot read small English, glare on the phone; (4) prioritise: huge Sindhi "رقم بھیجیں", amount in words, confirm screen, high contrast; (5) solution: that UI, not a CLI. Accessibility: high contrast for sunlight, large simple fonts, not colour-only status, Tab/large targets, vibration + spoken confirm (multimodal). Interaction: menu-driven + form fill + biometric + haptic; optional voice. Evaluate formatively on paper then in Figma; expert review against heuristics; SUS and NPS before launch. Test: usability and task-based ("send Rs 100") measuring time/success/errors; A/B two button sizes; compatibility on cheap Androids; keyboard if a kiosk is used; do not skip a confirm screen — trust and feedback are the main risks.

Self-assessment: I can...

- ☐ define HCI, CHI and MMI and name the five sensory channels.
- ☐ describe HCI in health, banking, education and networking.
- ☐ name the types of user interaction and give an example of each.
- ☐ apply the five accessibility principles and carry out a need analysis.
- ☐ differentiate UI from UX and list six UI components.
- ☐ choose evaluation methods (SUS, NPS, formative, summative, expert).
- ☐ tell traditional interaction from natural interaction with local examples.
- ☐ label user, computer system, interaction, task, UI type, environment and feedback on an ATM, JazzCash or portal.
- ☐ explain why HCI is important using the five implications.
- ☐ name eight HCI problems and the methods that fix them.
- ☐ compare Lo-Fi, Hi-Fi, Figma steps and prototype triggers/actions.
- ☐ explain usability, task-based, automated, A/B, compatibility, load and keyboard tests.

CHAPTER 2

Computational Thinking & Algorithms

Class XI taught you how to write algorithms. This chapter teaches you how to **judge** them: is the algorithm correct, clear and efficient? You will then learn the main **data structures** — array, linked list, stack, queue, tree and graph — so you can store data the smart way and trace how it is retrieved.

گیارہویں جماعت میں آپ نے الگورتھم لکھنا سیکھا۔ اس باب میں آپ سیکھیں گے کہ الگورتھم درست، واضح اور تیز ہے یا نہیں، اور ایرے، لنکڈ لسٹ، سٹیک، کیو، ٹری اور گراف جیسے ڈیٹا سٹرکچرز میں ڈیٹا کیسے رکھا اور نکالا جاتا ہے۔

What you will learn

- Define **correctness** and prove it with a complete **trace table**.
- Evaluate **clarity** using modularity (SRP, coupling, abstraction) and readability (names, flow, consistency).
- Explain how the number of **conditions** and **repetitions** changes efficiency, and apply the three-question efficiency framework.
- Define a **data structure** and classify it as linear or non-linear.
- Draw a tree and a graph, and name the five operations on data structures.
- Apply **stepwise reasoning** and compare it with a trace table on at least four points.
- Define **efficiency** in time and space, and state Big O for $O(1)$, $O(\log n)$, $O(n)$, $O(n \log n)$ and $O(n^2)$ with examples.
- Refine an algorithm for clearer names, modules, comments and fewer wasted steps.
- Draw and trace an array, linked list, stack (PUSH/POP) and queue (ENQUEUE/DEQUEUE).
- Choose a data structure for a real scenario and trace retrieval in an array, a linked list and a queue.

ACADEMY CALENDAR

Academy calendar: 24 topics · 6 Golden · **16 classes of 90 minutes** + one 40-minute weekly test after this chapter.

Class	Topics	Kind	Board focus
Class 01	Analyze algorithms for correctness	Single · 90 min	An algorithm is correct if its output matches the expected results for a given input.
Class 02	Trace Tables	★ Golden · 90 min	A trace table is a technique used to monitor how the values of variables change during...
Class 03	Stepwise Reasoning	Single · 90 min	Stepwise reasoning (also called logic verification) breaks an algorithm into logical...
Class 04	Comparing Trace Tables and Stepwise Reasoning	★ Golden · 90 min	Both methods verify correctness, but they fit different situations depending on the...
Class 05	Evaluating the Clarity of an Algorithm + Modularity	Paired · 90 min	Clarity means an algorithm is easy to read, understand and modify.
Class 06	Readability + Assess Algorithm Efficiency	Paired · 90 min	Readability is how easily another person can understand the purpose and logic of an...
Class 07	Number of Steps (Big O Notation)	★ Golden · 90 min	When we discuss efficiency we ask how performance changes as the input size n increases.
Class 08	Number of Conditions + Number of Repetitions	Paired · 90 min	Conditions (IF statements) are decision points.
Class 09	The Efficiency Evaluation Framework + Refinements to improve clarity and efficiency	Paired · 90 min	To evaluate an algorithm at a conceptual level, ask three questions: Does it scale?
Class 10	Concept of Data Structure	★ Golden · 90 min	A data structure is a systematic way of organising, storing and managing data so that an...
Class 11	Linear Data Structures: Array + Linear Data Structures: Linked List	Paired · 90 min	An array holds a collection of similar items (the same data type) placed next to each...
Class 12	Linear Data Structures: Stack	★ Golden · 90 min	A stack is a linear data structure that works on the LIFO principle: Last-In, First-Out.

Class	Topics	Kind	Board focus
Class 13	Linear Data Structures: Queue	★ Golden · 90 min	A queue organises data on the FIFO principle: First-In, First-Out.
Class 14	Non-Linear Data Structures: Tree + Non-Linear Data Structures: Graph	Paired · 90 min	A tree organises data in a hierarchy.
Class 15	Operations on Data Structures + Identify data structures in problem scenarios	Paired · 90 min	Whatever the shape, you keep meeting the same five operations:
Class 16	Trace data retrieval in Array, List and Queue + Career Opportunities in Algorithms	Paired · 90 min	Tracing data retrieval means following the step-by-step path of how an algorithm finds or...

Weekly test: 15 MCQ from this chapter + two 5-mark Golden questions. Mark to the recipes. Re-teach any Golden below 60% in the next starter.

گولڈن موضوع پوری کلاس لیتا ہے۔ ہفتہ وار ٹیسٹ کے بعد کمزور گولڈن دوبارہ پڑھائیں۔

2.1 Analyze algorithms for correctness

ACADEMY SESSION

Session 1 of 16 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: An algorithm is correct if its output matches the expected results for a given input.

Error clinic: Mistake: testing only one “normal” input and calling the algorithm correct.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Analyze algorithms for correctness**. Write: An algorithm is correct if its output matches the expected results for a given input.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Analysing correctness means showing that the algorithm produces the intended output for all valid inputs, not just one lucky example. (2) Two methods are used in this course: — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

An algorithm is **correct** if its **output matches the expected results** for a given input. Analysing correctness means showing that the algorithm produces the intended output for **all valid inputs**, not just one lucky example.

Two methods are used in this course:

Trace tables



paper execution, line by line



Stepwise reasoning



logic blocks, overall state

You already met the idea of a dry run in Class XI. Here you learn to do it formally, and to choose the method that fits the size of the algorithm.

WORKED EXAMPLE

Worked example: what “correct” means. An algorithm is supposed to count how many of the heights 1.91, 2.01, 1.87, 1.57, 1.48 lie between 1.57 m and 1.91 m inclusive.

Expected output: **3** (1.91, 1.87 and 1.57 qualify; 2.01 is too tall; 1.48 is too short).

If a program prints 4, it **runs** but it is **not correct**. Correctness is about the right answer, not about “no crash”.

REMEMBER IT

Remember: **runs ≠ correct**. A logical error still produces output — just the wrong output. That is why we analyse correctness on paper before we trust the code.

COMMON MISTAKE

Mistake: testing only one “normal” input and calling the algorithm correct.

Fix: also try edge cases (empty list, $N = 0$, the exact boundary values 1.57 and 1.91). The definition says **all valid inputs**.

اردو میں سمجھیں

الگورتھم تب درست (Correct) سمجھا جاتا ہے جب دیے گئے ان پٹ پر اس کا آؤٹ پٹ وہی ہو جو ہونا چاہیے۔ صرف چل جانا کافی نہیں؛ منطقی غلطی سے غلط جواب بھی نکل سکتا ہے۔ درستگی جانچنے کے دو طریقے ہیں: ٹریس ٹیبل (Trace Table) اور مرحلہ وار استدلال (Stepwise Reasoning)۔

CHECK YOURSELF

1. When is an algorithm considered correct?
2. Name the two methods used to analyse correctness in this chapter.
3. Why is “the program ran without an error” not enough?

Answers: 1. When its output matches the expected results for a given input (and does so for all valid inputs). 2. Trace tables and stepwise reasoning. 3. Because a logical error can still produce output — the wrong output.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. When is an algorithm considered correct?

3 marks. Explain Analyze algorithms for correctness with two clear points and one example.

5 marks. Write a 5-mark answer on Analyze algorithms for correctness: definition, two points, a labelled diagram or table, and one example.

Answers: 1. When its output matches the expected results for a given input (and does so for all valid inputs) 3. Analysing correctness means showing that the algorithm produces the intended output for all valid inputs, not just one lucky example.; Two methods are used in this course: 5. Use the recipe in the blue box. Model opening: An algorithm is correct if its output matches the expected results for a given input.

BATCH HOMEWORK

Write a 5-mark answer on **Analyze algorithms for correctness** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.1.1 Trace Tables ★ Golden

ACADEMY SESSION

Session 2 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A trace table is a technique used to monitor how the values of variables change during the execution of an algorithm.

Error clinic: Mistake 1: treating 1.57 or 1.91 as out of range.

Exam wording to train: Very common long question: “Dry-run the given algorithm using a trace table and state the output.” Draw columns for every variable plus a condition column.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Trace Tables**. Write: A trace table is a technique used to monitor how the values of variables change during the execution of an algorithm.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Debugging: find logical errors where the algorithm runs but the output is wrong. (2) Validation: check that the algorithm does what it is intended to do. — + example.

5 marks: 3-mark structure + table: Step / Total / Height / AllHeights (input) / Height between 1.57 and 1.91? / Output + the worked example from this topic.

8–10 marks: 5-mark structure + a filled trace table with every variable on every line + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **trace table** is a technique used to monitor how the values of variables change during the execution of an algorithm. It is a **paper execution** of the code — a manual walkthrough, also called a **dry run**. You act as the computer and fill in one row after another.

Purpose of trace tables

- **Dry running:** execute the algorithm line by line by hand.
- **Debugging:** find logical errors where the algorithm runs but the output is wrong.
- **Validation:** check that the algorithm does what it is intended to do.

Components of a trace table

- **Line / step number** — which line is being executed.
- **Variables** — one column for every variable.
- **Input / output** — user inputs and printed results.
- **Condition check** — True/False for IF, WHILE, FOR, and similar tests.

WORKED EXAMPLE

Worked example: soldiers who meet the height rule. To qualify for training, a soldier's height must be between **1.57 and 1.91 metres, inclusive**.

Inputs: all soldiers' heights. Output: the count of eligible soldiers.

Step 1: Start

Step 2: SET Total = 0

Step 3: Set AllHeights = [1.91, 2.01, 1.87, 1.57, 1.48]

Step 4: FOR EACH height FROM AllHeights DO

Step 5: IF height $\geq$ 1.57 AND height $\leq$ 1.91 THEN

Step 6: SET Total = Total + 1

Step 7: END IF

Step 8: END FOR EACH

Step 9: Print Total

Step 10: End

Inclusive means the two boundary values **count**: 1.57 and 1.91 are eligible.

Step	Total	Height	AllHeights (input)	Height between 1.57 and 1.91?	Output
2	0				
3	0		1.91, 2.01, 1.87, 1.57, 1.48		
4	0	1.91			
5	0	1.91		True	
6	1	1.91			
4	1	2.01			
5	1	2.01		False (skip Step 6)	
4	1	1.87			
5	1	1.87		True	
6	2	1.87			
4	2	1.57			
5	2	1.57		True (boundary)	
6	3	1.57			
4	3	1.48			
5	3	1.48		False (skip Step 6)	
9	3				3

Eligible: 1.91, 1.87, 1.57. Not eligible: 2.01 (above 1.91) and 1.48 (below 1.57). Printed Total = **3**.

```
AllHeights = [1.91, 2.01, 1.87, 1.57, 1.48]
Total = 0
for height in AllHeights:
    if height >= 1.57 and height <= 1.91:
        Total = Total + 1
print(Total)
```

OUTPUT

3

REMEMBER IT

How to fill a trace table without getting lost. Write a new row every time a variable **changes** or a condition is **tested**. Copy unchanged values into the new row so you never guess. Circle the final output.

Mnemonic: **V-I-C-O** — **V**ariables, **I**nter, **C**ondition, **O**utput. If a column is missing, the table is incomplete.

COMMON MISTAKE

Mistake 1: treating 1.57 or 1.91 as out of range. The words “inclusive” and the operators $\geq$ and $\leq$ mean the boundaries **are allowed**.

Mistake 2: updating Total on a False condition. If the IF is False, skip the SET line and leave Total unchanged.

Mistake 3: writing only the last Total. Examiners award marks for the **changing values in the table**, not only for the printed 3.

اردو میں سمجھیں

ٹریس ٹیبل الگورتھم کا کاغذی اجرا (Dry Run) ہے۔ ہر قطار میں لکیر نمبر، متغیرات کی نئی قیمتیں، ان پٹ/آؤٹ پٹ اور شرط کا نتیجہ (True/False) لکھا جاتا ہے۔ فوجیوں کی مثال میں قد 1.57 سے 1.91 میٹر تک ہونا چاہیے، حدود سمیت؛ پانچ قدوں میں سے تین اہل ہیں اس لیے آؤٹ پٹ 3 ہے۔

EXAM TIP

Very common long question: “Dry-run the given algorithm using a trace table and state the output.” Draw columns for **every** variable plus a condition column. Show the loop once per item. Boundary values ($\geq$, $\leq$, empty list) are favourite traps. Short questions ask: purpose of a trace table (dry run / debug / validate) and its components (line, variables, I/O, condition).

CHECK YOURSELF

1. List the four usual columns / components of a trace table.
2. In the soldier example, why is height 1.57 counted but 1.48 not counted?
3. What is printed, and how many times is Step 6 executed?

Answers: 1. Line/step number, variables, input/output, condition check. 2. 1.57 is the lower boundary (inclusive, so True); 1.48 is below 1.57 (False). 3. 3 is printed; Step 6 runs three times (for 1.91, 1.87 and 1.57).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. List the four usual columns / components of a trace table.

3 marks. Explain Trace Tables with two clear points and one example.

5 marks. Very common long question: “Dry-run the given algorithm using a trace table and state the output.” Draw columns for every variable plus a condition column. Show the loop once per item. Boundary...

8 marks. Trace Tables: 5-mark answer plus a filled trace table with every variable on every line.

Answers: 1. Line/step number, variables, input/output, condition check. 3. Debugging: find logical errors where the algorithm runs but the output is wrong.; Validation: check that the algorithm does what it is intended to do. 5. Use the recipe in the blue box. Model opening: A trace table is a technique used to monitor how the values of variables change during the execution of an algorithm. 8. Same 5-mark body + a filled trace table with every variable on every line + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Trace Tables** using the recipe in this topic. Include a filled trace table with every variable on every line. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.1.2 Stepwise Reasoning

ACADEMY SESSION

Session 3 of 16 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Stepwise reasoning (also called logic verification) breaks an algorithm into logical sections and checks the state of the algorithm at each stage.

Error clinic: Mistake: rewriting the whole trace table and calling it stepwise reasoning.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Stepwise Reasoning**. Write: Stepwise reasoning (also called logic verification) breaks an algorithm into logical sections and checks the state of the algorithm at each stage.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Check: does it start in a valid state? (2) Does it handle all possible cases? — + example.

5 marks: 3-mark structure + table: Check / What you verify + the worked example from this topic.

LEARN IT

Stepwise reasoning (also called **logic verification**) breaks an algorithm into logical sections and checks the **state** of the algorithm at each stage. A **state** is a snapshot of what is true about the variables at that moment (for example, "Sum currently holds the total of the numbers seen so far").

You do **not** fill a row for every line. You think through the logic:

1. Analyse each step of the algorithm.
2. Check: does it **start in a valid state**?
3. Does it **handle all possible cases**?
4. Are the **conditions correct**?
5. If the loop is correct at the **start** of an iteration, does it remain correct at the **end**?

WORKED EXAMPLE

Worked example: sum of the numbers from 1 to N.

Step 1: Start
Step 2: Input N
Step 3: SET Sum = 0
Step 4: For i = 1 to N
Step 5: Sum = Sum + i
Step 6: END For
Step 7: Print Sum
Step 8: End

Stepwise reasoning breakdown

Check	What you verify
Initial state	Sum = 0 before the loop. Valid: nothing has been added yet.
Loop boundary	The loop runs exactly from i = 1 to i = N. No missing number, no extra number.
Iteration	Each i is added once: after k iterations, Sum = 1+2+...+k.
Final state	When the loop ends, Sum holds 1+2+...+N, which is the required total.
Edge case N = 0	The loop body never runs, Sum stays 0. Correct (the sum of no numbers is 0).
Check case N = 5	Sum becomes 15, which matches $5 \times 6 / 2 = 15$.

```
N = 5
Sum = 0
for i in range(1, N + 1):
    Sum = Sum + i
print(Sum)
```

OUTPUT
15

```
N = 0
Sum = 0
for i in range(1, N + 1):
    Sum = Sum + i
print(Sum)
```

OUTPUT
0

REMEMBER IT

Think of stepwise reasoning as a **teacher checking a proof**, not as a cashier counting coins one by one. You ask “is this block always true?” instead of “what is Sum when i = 17?”.

COMMON MISTAKE

Mistake: rewriting the whole trace table and calling it stepwise reasoning.

Fix: write short comments about **state** (start, loop, finish, edges). If you listed every i from 1 to 1000, you used the wrong method.

اردو میں سمجھیں

مرحلہ وار استدلال میں الگورتھم کو منطقی حصوں میں توڑ کر ہر مرحلے پر اس کی حالت (State) دیکھی جاتی ہے: کیا شروع درست ہے، کیا تمام صورتیں سنبھلی ہیں، کیا شرط صحیح ہے، اور کیا لوپ کے ہر چکر کے بعد بھی نتیجہ درست رہتا ہے۔ ایک سے N تک جمع کی مثال میں Sum شروع میں 0 ہے، لوپ 1 سے N تک چلتا ہے، اور $N=0$ پر جواب 0 ہی رہتا ہے۔

CHECK YOURSELF

1. What other name is given to stepwise reasoning?
2. For the sum algorithm, why is $\text{Sum} = 0$ a valid start?
3. What happens when $N = 0$, and is that correct?

Answers: 1. Logic verification. 2. Because no numbers have been added yet, so the running total should be zero. 3. The loop does not run and Sum remains 0, which is the correct sum of no numbers.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What other name is given to stepwise reasoning?

3 marks. Explain Stepwise Reasoning with two clear points and one example.

5 marks. Write a 5-mark answer on Stepwise Reasoning: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Logic verification 3. Check: does it start in a valid state?; Does it handle all possible cases? 5. Use the recipe in the blue box. Model opening: Stepwise reasoning (also called logic verification) breaks an algorithm into logical sections and checks the state of the algorithm at each stage.

BATCH HOMEWORK

Write a 5-mark answer on **Stepwise Reasoning** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.1.3 Comparing Trace Tables and Stepwise Reasoning

★ Golden

ACADEMY SESSION

Session 4 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Both methods verify correctness, but they fit different situations depending on the complexity and length of the algorithm.

Error clinic: Mistake: saying one method is “better” in every question.

Exam wording to train: Differentiate questions are almost guaranteed: “Compare a trace table with stepwise reasoning.” Write a four-row table (best for, effort, primary goal,...)

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Comparing Trace Tables and Stepwise Reasoning**. Write: Both methods verify correctness, but they fit different situations depending on the complexity and length of the algorithm.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Both methods verify correctness, but they fit different situations depending on the complexity and length of the algorithm. (2) Second distinct point (not a repeat of the definition) — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a filled trace table with every variable on every line + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Both methods verify correctness, but they fit different situations depending on the **complexity and length** of the algorithm.

Feature	Trace table	Stepwise reasoning
Best for	Small algorithm blocks, complex loops, and beginners learning to track variables.	Large systems, architectural logic, and abstract mathematical proofs.
Effort required	High. Very tedious and impractical if a loop runs 1,000 times.	Moderate. Needs strong logical deduction and abstract thinking.
Primary goal	Catching syntax misinterpretations or specific arithmetic errors line by line.	Catching conceptual or structural flaws in the overall design.
Level	Micro-level (line by line). Checks exact values.	Macro-level (logic blocks). Checks overall state.

Trace table

Micro-level
Line by line
Exact values

Stepwise reasoning

Macro-level
Logic blocks
Overall state

Trace tables zoom in on values; stepwise reasoning zooms out on design.

WORKED EXAMPLE

Worked example: which method would you pick?

1. **A 12-line loop that adds five heights.** Use a **trace table**. The loop is short, you are a beginner, and you need the exact Total.
2. **A billing system with 40 functions.** Use **stepwise reasoning**. You cannot fill 10,000 rows. You check each module's start state, end state and edge cases.
3. **A loop from $i = 1$ to 1,000 that should produce Sum = 500500.** Do **not** write 1,000 rows. Argue: "Sum starts at 0; each i is added once; final Sum = $n(n+1)/2 = 1000 \times 1001/2 = 500500$." That is stepwise reasoning. Then dry-run a tiny N (say 5) with a trace table if you want extra confidence.

REMEMBER IT

Micro vs macro. Trace table = microscope (every cell). Stepwise reasoning = map (whole city). Beginners start with the microscope; designers need the map.

COMMON MISTAKE

Mistake: saying one method is “better” in every question.

Fix: they have different jobs. For a short dry-run in the exam, draw the table. For “explain why the algorithm is correct for any N”, write stepwise reasoning.

اردو میں سمجھیں

ٹریس ٹیبل خرد بینی (Micro) سطح پر کام کرتا ہے: ہر لائن اور ہر قیمت۔ مرحلہ وار استدلال بڑی (Macro) سطح پر ڈیزائن اور حالت چیک کرتا ہے۔ چھوٹے لوپ اور مبتدیوں کے لیے ٹیبل بہتر ہے؛ ہزار بار چلنے والے لوپ یا بڑے سسٹم کے لیے استدلال بہتر ہے۔

EXAM TIP

Differentiate questions are almost guaranteed: “Compare a trace table with stepwise reasoning.” Write a **four-row table** (best for, effort, primary goal, micro/macro). Add one sentence of advice: table for small loops and exact values; reasoning for large systems and proofs. Do not write “trace table is always better”.

CHECK YOURSELF

1. Which method is micro-level and checks exact values?
2. Why is a trace table a poor choice if a loop runs 1,000 times?
3. Which method is better for catching a structural flaw in a large design?

Answers: 1. Trace table. 2. It is very tedious and impractical (too many rows). 3. Stepwise reasoning (macro-level, conceptual / structural flaws).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which method is micro-level and checks exact values?

3 marks. Explain Comparing Trace Tables and Stepwise Reasoning with two clear points and one example.

5 marks. Differentiate questions are almost guaranteed: “Compare a trace table with stepwise reasoning.” Write a four-row table (best for, effort, primary goal, micro/macro). Add one sentence of advice: table...

8 marks. Comparing Trace Tables and Stepwise Reasoning: 5-mark answer plus a filled trace table with every variable on every line.

Answers: 1. Trace table 3. Both methods verify correctness, but they fit different situations depending on the complexity and length of the algorithm. 5. Use the recipe in the blue box. Model opening: Both methods verify correctness, but they fit different situations depending on the complexity and length of the algorithm. 8. Same 5-mark body + a filled trace table with every variable on every line + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Comparing Trace Tables and Stepwise Reasoning** using the recipe in this topic. Include a filled trace table with every variable on every line. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.2 Evaluating the Clarity of an Algorithm

ACADEMY SESSION

Session 5 of 16 · 45 minutes (first half) · paired with Modularity.

10–45 min — this topic. Lock the definition and table for **Evaluating the Clarity of an Algorithm**. Starter (0–10) is from last class. Second half is Modularity.

On the board: Clarity means an algorithm is easy to read, understand and modify.

Error clinic: Mistake: treating a clever one-line trick as “better” than a clear five-line solution.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Evaluating the Clarity of an Algorithm**. Write: Clarity means an algorithm is easy to read, understand and modify.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) In many cases, evaluating clarity is even more important than making the algorithm slightly faster. (2) A clear algorithm is easier to maintain, debug and extend over time. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Clarity means an algorithm is easy to **read, understand and modify**. In many cases, evaluating clarity is even more important than making the algorithm slightly faster. A clear algorithm is easier to **maintain, debug and extend** over time.

The two key aspects of clarity are:

Clarity → Modularity (parts) → Readability (text and flow)

WORKED EXAMPLE

Worked example: speed versus clarity. Algorithm A finds the class average in 8 confusing lines with variables a , b , c . Algorithm B uses two named functions and takes the same number of additions. Both are $O(n)$. Algorithm B is the better school solution because the next person (or you, in three months) can change it without breaking it.

REMEMBER IT

Ask two questions: “**Can I split this into parts?**” (modularity) and “**Can another student read it aloud and understand it?**” (readability).

COMMON MISTAKE

Mistake: treating a clever one-line trick as “better” than a clear five-line solution.

Fix: the source says clarity is often more important than speed. Board answers should praise meaningful names and modules, not compacted code.

وضاحت (Clarity) کا مطلب ہے الگورتھم پڑھنا، سمجھنا اور بدلنا آسان ہو۔ بہت سی صورتوں میں وضاحت رفتار سے بھی اہم ہے۔ اس کے دو حصے ہیں: ماڈیولریٹی (Modularity) یعنی کام کو حصوں میں بانٹنا، اور پڑھائی پن (Readability) یعنی متن اور بہاؤ صاف ہونا۔

CHECK YOURSELF

1. What does clarity mean?
2. Name the two key aspects of clarity.
3. Why can clarity matter more than a small speed gain?

Answers: 1. The algorithm is easy to read, understand and modify. 2. Modularity and readability. 3. Because a clear algorithm is easier to maintain, debug and extend over time.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does clarity mean?

3 marks. Explain Evaluating the Clarity of an Algorithm with two clear points and one example.

5 marks. Write a 5-mark answer on Evaluating the Clarity of an Algorithm: definition, two points, a labelled diagram or table, and one example.

Answers: 1. The algorithm is easy to read, understand and modify. 3. In many cases, evaluating clarity is even more important than making the algorithm slightly faster.; A clear algorithm is easier to maintain, debug and extend over time. 5. Use the recipe in the blue box. Model opening: Clarity means an algorithm is easy to read, understand and modify.

BATCH HOMEWORK

Write a 5-mark answer on **Evaluating the Clarity of an Algorithm** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.2.1 Modularity

ACADEMY SESSION

Session 5 of 16 · 45 minutes (second half) · paired with Evaluating the Clarity of an Algorithm.

45–75 min — this topic. Board working for **Modularity**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Modularity means breaking an algorithm into smaller, independent parts such as functions, classes or modules.

Error clinic: Mistake: copying the 1-based loop for $l = 1$ to n : $total = total + A[l]$ into Python.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Modularity**. Write: Modularity means breaking an algorithm into smaller, independent parts such as functions, classes or modules.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Coupling. Modules should be reusable in different contexts. Good modularity means loose coupling: a change in one part does not smash the... (2) Abstraction. A well-designed algorithm hides complex implementation details. You can call a sorting function without knowing whether it... — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Modularity means breaking an algorithm into smaller, independent parts such as **functions, classes or modules**. This makes the algorithm more organised and easier to work with.

How to evaluate modularity

1. **Single Responsibility Principle (SRP).** Each module should focus on **one** specific task. If a function calculates a sum, prints a report and saves a file, it violates SRP.
2. **Coupling.** Modules should be reusable in different contexts. Good modularity means **loose coupling**: a change in one part does not smash the others. Tight coupling is when two functions share so many hidden details that you cannot reuse one without the other.
3. **Abstraction.** A well-designed algorithm hides complex implementation details. You can call a sorting function without knowing whether it uses Bubble Sort or Selection Sort inside.

WORKED EXAMPLE

Worked example: average of an array.

Poor modularity (monoblock)

All logic sits in one block, so you cannot reuse the sum.

```
Step 1: Start
Step 2: Set A = [1, 2, 3, 4, 5]
Step 3: Set n = 5
Step 4: Set total = 0
Step 5: Set avg = 0
Step 6: For I = 1 to n
Step 7:  total = total + A[I]
Step 8: End For
Step 9: avg = total / n
Step 10: Print avg
Step 11: End
```

Good modularity (functions)

Two clear functions: `CalculateSum()` and `FindAverage()`.

```
Step 1: Start
Step 2: Set A = [1, 2, 3, 4, 5]
Step 3: Set n = 5
Step 4: Print FindAverage(A, n)
Step 5: End
```

```
Function FindAverage(A, n)
  Sum = CalculateSum(A, n)
  Avg = Sum / n
  Return Avg
End Function
```

```
Function CalculateSum(A, n)
  Set Total = 0
  For I = 1 to n
    Total = Total + A[I]
  End For
  Return Total
End Function
```

SRP check: CalculateSum only adds; FindAverage only divides. Loose coupling: you can reuse CalculateSum to find a total without computing an average. Abstraction: the main algorithm just calls FindAverage and does not see the loop.

The source pseudocode numbers array positions from 1. Python numbers them from 0, so the loop is `for i in range(n)`.

```
def calculate_sum(A, n):
    total = 0
    for i in range(n):
        total = total + A[i]
    return total

def find_average(A, n):
    return calculate_sum(A, n) / n

A = [1, 2, 3, 4, 5]
n = 5
print(find_average(A, n))
```

OUTPUT
3.0

REMEMBER IT

SRP in one line: **one function, one job**. If you cannot name the function with a short verb-phrase (CalculateSum, FindAverage), it is doing too much.

COMMON MISTAKE

Mistake: copying the 1-based loop `for I = 1 to n: total = total + A[I]` into Python. Then `A[1]` skips the first item and `A[5]` crashes.

Fix: in Python use `for i in range(n)` so the indices are 0, 1, 2, 3, 4.

اردو میں سمجھیں

ماڈیولریتی کا مطلب الگورتھم کو آزاد حصوں (فنکشن، کلاس، ماڈیول) میں توڑنا ہے۔ جانچ کے تین اصول: واحد ذمہ داری (SRP) یعنی ایک فنکشن ایک کام؛ ڈھیلی جڑت (Loose Coupling) تاکہ ایک حصہ بدلنے سے دوسرے نہ ٹوٹیں؛ اور تجرید (Abstraction) یعنی اندرونی تفصیل چھپا کر صرف کام منگوانا، جیسے سورتھ فنکشن بلائے بغیر یہ جانے کہ بیل ہے یا سلیکشن۔

CHECK YOURSELF

1. What does SRP say each module should do?
2. In the good average algorithm, which function hides the loop?
3. Why is the monoblock harder to reuse?

Answers: 1. One specific task. 2. CalculateSum (FindAverage only divides; the main program only prints). 3. All logic is in one block, so you cannot call "just the sum" from another algorithm.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does SRP say each module should do?

3 marks. Explain Modularity with two clear points and one example.

5 marks. Write a 5-mark answer on Modularity: definition, two points, a labelled diagram or table, and one example.

Answers: 1. One specific task 3. Coupling. Modules should be reusable in different contexts. Good modularity means loose coupling: a change in one part does not smash the...; Abstraction. A well-designed algorithm hides complex implementation details. You can call a sorting... 5. Use the recipe in the blue box. Model opening: Modularity means breaking an algorithm into smaller, independent parts such as functions, classes or modules.

BATCH HOMEWORK

Write a 5-mark answer on **Modularity** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.2.2 Readability

ACADEMY SESSION

Session 6 of 16 · 45 minutes (first half) · paired with Assess Algorithm Efficiency.

10–45 min — this topic. Lock the definition and table for **Readability**. Starter (0–10) is from last class. Second half is Assess Algorithm Efficiency.

On the board: Readability is how easily another person can understand the purpose and logic of an algorithm without running it.

Error clinic: Mistake: dumping a comment on every line (total = total + 1 # add one to total).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Readability**. Write: Readability is how easily another person can understand the purpose and logic of an algorithm without running it.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Self-documentation — the algorithm explains itself, so you need fewer comments. Meaningful names and clean formatting make the purpose... (2) Control-flow simplicity — keep the logic straightforward. Avoid deep nesting (IF inside IF inside IF), limit extra conditions, and keep... — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Readability is how easily another person can understand the purpose and logic of an algorithm **without running it**. It is about how clear the text and the flow are.

How to evaluate readability

- 1. Naming conventions** — consistent rules for names. Good names make an algorithm easier to search and understand.
Bad: $v = d / t$
Good: velocity = distance / time
- 2. Self-documentation** — the algorithm explains itself, so you need fewer comments. Meaningful names and clean formatting make the purpose obvious.
- 3. Control-flow simplicity** — keep the logic straightforward. Avoid deep nesting (IF inside IF inside IF), limit extra conditions, and keep each function on one task.
- 4. Consistency** — one style throughout: indentation, spacing, and casing (camelCase or snake_case). Then the logic stands out instead of the mess.

WORKED EXAMPLE

Worked example: the same formula, two styles.

```
# Hard to read
d = 100
t = 4
s = 20
v = d / t
if v > s:
    if t > 0:
        print(v)
```

OUTPUT
25.0

```
# Readable
distance = 100
time = 4
velocity = distance / time
speed_limit = 20
if time > 0 and velocity > speed_limit:
    print(velocity)
```

OUTPUT
25.0

The second version uses names, avoids an IF nested inside an IF, and keeps one consistent snake_case style. You can understand it without running it. Both print 25.0, but only the second is clear.

REMEMBER IT

Remember readability as **N-S-S-C**: **N**ames, **S**elf-documentation, **S**imple flow, **C**onsistency.

COMMON MISTAKE

Mistake: dumping a comment on every line (`total = total + 1 # add one to total`).

Fix: if the name already says it, skip the comment. Comments should explain **why**, not repeat **what**.

اردو میں سمجھیں

پڑھائی پن یہ ہے کہ دوسرا شخص الگورتھم چلانے بغیر اس کا مقصد سمجھ لے۔ اچھے نام (`velocity = distance / time`)، خود بیان (کم تبصرے)، سادہ کنٹرول فلو (گہری IF کے بغیر) اور ایک جیسا انداز (casing اور indentation) اسے آسان بناتے ہیں۔

CHECK YOURSELF

1. Rewrite `v = d / t` with readable names.
2. What is deep nesting, and why is it a readability problem?
3. Name two style habits that support consistency.

Answers: 1. `velocity = distance / time`. 2. IF inside IF inside IF (or similar); it makes the flow hard to follow. 3. Any two of: consistent indentation, spacing, and casing (camelCase or snake_case).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Rewrite $v = d / t$ with readable names.

3 marks. Explain Readability with two clear points and one example.

5 marks. Write a 5-mark answer on Readability: definition, two points, a labelled diagram or table, and one example.

Answers: 1. velocity = distance / time 3. Self-documentation — the algorithm explains itself, so you need fewer comments. Meaningful names and clean formatting make the purpose...; Control-flow simplicity — keep the logic straightforward. Avoid deep nesting (IF inside IF inside IF),... 5. Use the recipe in the blue box. Model opening: Readability is how easily another person can understand the purpose and logic of an algorithm without running it.

BATCH HOMEWORK

Write a 5-mark answer on **Readability** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.3 Assess Algorithm Efficiency

ACADEMY SESSION

Session 6 of 16 · 45 minutes (second half) · paired with Readability.

45–75 min — this topic. Board working for **Assess Algorithm Efficiency**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Algorithm efficiency is measured in terms of time and space — how fast it runs and how much memory it uses.

Error clinic: Mistake: judging efficiency by how short the code looks.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Assess Algorithm Efficiency**. Write: Algorithm efficiency is measured in terms of time and space — how fast it runs and how much memory it uses.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Number of conditions (IF decisions). (2) Number of repetitions (loops). — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Algorithm efficiency is measured in terms of **time** and **space** — how fast it runs and how much memory it uses.

The key considerations for assessing efficiency are:

1. **Number of steps** (described with **Big O notation**).
2. **Number of conditions** (IF decisions).
3. **Number of repetitions** (loops).

Time (speed) + Space (memory) → Efficiency

WORKED EXAMPLE

Worked example: two ways to find a name in 1,000,000 sorted records.

Linear search checks about 1,000,000 names in the worst case (time grows with n). Binary search checks about 20 names (it halves the list each time). Both can be correct and clear. They are not equally efficient.

REMEMBER IT

Efficiency is always “as the input grows”. An algorithm that feels instant on 10 items can freeze on 10 million items if it is $O(n^2)$.

COMMON MISTAKE

Mistake: judging efficiency by how short the code looks.

Fix: a five-line nested loop can do n^2 work. Count steps, conditions and repetitions — not lines of text.

اردو میں سمجھیں

کارکردگی (Efficiency) وقت (رفتار) اور جگہ (میموری) سے ناپی جاتی ہے۔ تین چیزیں دیکھی جاتی ہیں: قدموں کی تعداد (بگ او)، شرطوں کی تعداد، اور دہرائی (لوپ) کی تعداد۔ چھوٹے ان پٹ پر تیز لگنے والا الگورتھم بڑے ان پٹ پر سست پڑ سکتا ہے۔

CHECK YOURSELF

1. Efficiency is measured in terms of which two resources?
2. List the three key considerations named in the source.

Answers: 1. Time (speed) and space (memory). 2. Number of steps (Big O), number of conditions, number of repetitions.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Efficiency is measured in terms of which two resources?

3 marks. Explain Assess Algorithm Efficiency with two clear points and one example.

5 marks. Write a 5-mark answer on Assess Algorithm Efficiency: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Time (speed) and space (memory) 3. Number of conditions (IF decisions).; Number of repetitions (loops). 5. Use the recipe in the blue box. Model opening: Algorithm efficiency is measured in terms of time and space — how fast it runs and how much memory it uses.

BATCH HOMEWORK

Write a 5-mark answer on **Assess Algorithm Efficiency** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.3.1 Number of Steps (Big O Notation) ★ Golden

ACADEMY SESSION

Session 7 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: When we discuss efficiency we ask how performance changes as the input size n increases.

Error clinic: Mistake 1: writing $O(n)$ for binary search because “there is a loop”.

Exam wording to train: Memorise the five rows of the class table (name, growth, one example, grade).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Number of Steps (Big O Notation)**. Write: When we discuss efficiency we ask how performance changes as the input size n increases.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Big O notation is a mathematical method used to describe how the running time (or memory) grows as n grows. (2) We ignore small constants and keep the most important term: if an algorithm does $3n + 5$ steps we write $O(n)$. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a complete truth table and a labelled gate / logic diagram + a one-line conclusion. Method marks are awarded for working.

LEARN IT

When we discuss efficiency we ask how performance changes as the **input size n** increases. **Big O notation** is a mathematical method used to describe how the running time (or memory) **grows** as n grows. We ignore small constants and keep the most important term: if an algorithm does $3n + 5$ steps we write $O(n)$.

In computer science, **log n** almost always means log base 2 (how many times you can halve n until you reach 1).

Five common classes

Class	Name	What happens when n grows	Typical example	Grade
$O(1)$	Constant	Time stays the same for 10 items or 10 million.	Access <code>arr[0]</code> (or any known index).	Excellent
$O(\log n)$	Logarithmic	Time grows very slowly; the problem is halved each step.	Binary search on a sorted list.	Great
$O(n)$	Linear	If n doubles, time roughly doubles.	Linear search of an unsorted list.	Fair / Good
$O(n \log n)$	Linearithmic	A little worse than linear; much better than n^2 . Common in good sorting.	Merge Sort (split in half, then merge).	Good
$O(n^2)$	Quadratic	Time grows with the square of n . Nested loops. Painful for large n .	Bubble Sort; compare every item with every other item.	Poor

The source stresses $O(1)$, $O(\log n)$, $O(n)$ and $O(n^2)$. $O(n \log n)$ is the class of efficient general-purpose sorts, so you should recognise it when a question says “better than Bubble Sort but more than linear”.


Growth table (log is $\log_2$)

Each cell is the approximate number of operations for that n . Read down a column to see how fast that class explodes.

n	$O(1)$	$O(\log n)$	$O(n)$	$O(n \log n)$	$O(n^2)$
2	1	1	2	2	4
4	1	2	4	8	16
8	1	3	8	24	64
16	1	4	16	64	256
32	1	5	32	160	1,024
1,024	1	10	1,024	10,240	1,048,576
1,000,000	1	~20	1,000,000	~20,000,000	1,000,000,000,000

From $n = 8$ to $n = 1,000,000$, $O(1)$ does not move, $O(\log n)$ only goes from 3 to about 20, $O(n)$ becomes a million, and $O(n^2)$ becomes a million million — which is why nested loops “fail for large datasets”.

Relative work at $n = 16$



Same $n = 16$. Quadratic work is already four times $n \log n$ and sixteen times linear.

WORKED EXAMPLE

Worked example A — $O(1)$: first element of an array. Whether the array holds 10 or 10 million values, `arr[0]` is one jump to a known address.

```
arr = [23, 76, 12, 90, 34, 68]
print(arr[0])
```

OUTPUT
23

Worked example B — $O(n)$: linear search. Each extra item adds one extra check.

```
def linear_search(items, key):
    for i, value in enumerate(items):
        if value == key:
            return i
    return -1

print(linear_search([10, 50, 20, 70, 90, 30], 20))
print(linear_search([10, 50, 20, 70, 90, 30], 99))
```

OUTPUT

2
-1

Worked example C — $O(\log n)$: binary search on a sorted list. Each step throws away half of the remaining items. For 8 sorted numbers the worst case is about 4 comparisons ($\text{floor}(\log_2 8)+1$).

```
def binary_search(arr, key):
    low = 0
    high = len(arr) - 1
    steps = 0
    while low <= high:
        mid = (low + high) // 2
        steps = steps + 1
        if arr[mid] == key:
            return mid, steps
        if arr[mid] < key:
            low = mid + 1
        else:
            high = mid - 1
    return -1, steps

data = [3, 8, 12, 17, 23, 31, 40, 52]
print(binary_search(data, 40))
print(binary_search(data, 3))
```

OUTPUT

(6, 3)
(0, 3)

Key 40 is found at index 6 after 3 comparisons. Key 3 is found at index 0 after 3 comparisons. Never more than a handful of steps, even if the list later grows to a million (about 20 steps).

Worked example D — $O(n \log n)$: Merge Sort idea. To sort 8 items, Merge Sort makes $\log_2 8 = 3$ split-levels, and each level walks all 8 items once, so work $\approx 8 \times 3 = 24$, which matches the growth table. Bubble Sort on 8 items is on the order of $8^2 = 64$ comparisons. That gap becomes enormous at $n = 1,000,000$.

Worked example E — $O(n^2)$: nested loops.

```
n = 4
count = 0
for i in range(n):
    for j in range(n):
        count = count + 1
print(count)
```

OUTPUT

16

Inner body runs $n \times n = 16$ times. That is the pattern of Bubble Sort and of “compare every item with every other item”.

REMEMBER IT

Order from fastest to slowest (for large n): $O(1) \rightarrow O(\log n) \rightarrow O(n) \rightarrow O(n \log n) \rightarrow O(n^2)$.

Mnemonic: **"Constant Logs Never Need Squares"** — Constant, Logarithmic, N, N-log-N, Squares.

COMMON MISTAKE

Mistake 1: writing $O(n)$ for binary search because "there is a loop". The loop runs about $\log n$ times, not n times.

Mistake 2: writing $O(2n)$ or $O(n+5)$. Big O drops constants: both are $O(n)$.

Mistake 3: using binary search on an **unsorted** list. Binary search is $O(\log n)$ only on sorted data.

اردو میں سمجھیں

بگ او (Big O) بتاتا ہے کہ ان پٹ n بڑھنے پر وقت یا میموری کیسے بڑھتی ہے۔ $O(1)$ مستقل (ایرے کا $arr[0]$)، $O(\log n)$ ہر قدم پر آدھا (بائنری سرچ)، $O(n)$ لکیری (لینیئر سرچ)، $O(n \log n)$ اچھے سارٹ جیسے مرچ سارٹ، اور $O(n^2)$ مربع (بل سارٹ، اندرونی لوپ)۔ بڑے n پر $O(n^2)$ ناقابل استعمال ہو جاتا ہے۔

EXAM TIP

Memorise the five rows of the class table (name, growth, one example, grade). Typical MCQ: "Accessing $arr[0]$ is ...?" $\rightarrow O(1)$. "Binary search is ...?" $\rightarrow O(\log n)$. "Nested loops / Bubble Sort ...?" $\rightarrow O(n^2)$. Long questions ask you to fill or interpret a growth table, or to say what happens if n becomes 10 times larger (linear $\rightarrow 10\times$ time; quadratic $\rightarrow 100\times$ time). Always mention that $\log n$ is "halving" and n^2 is "nested loops".

CHECK YOURSELF

1. Give one example each of $O(1)$, $O(\log n)$, $O(n)$ and $O(n^2)$.
2. From the growth table, how many operations does $O(n^2)$ need when $n = 32$?
3. Why is Merge Sort described as $O(n \log n)$?

Answers: 1. $O(1)$ $arr[0]$; $O(\log n)$ binary search; $O(n)$ linear search; $O(n^2)$ Bubble Sort / nested loops. 2. 1,024. 3. It makes about $\log n$ split-levels and does about n work on each level, so $n \times \log n$.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Give one example each of $O(1)$, $O(\log n)$, $O(n)$ and $O(n^2)$.

3 marks. Explain Number of Steps (Big O Notation) with two clear points and one example.

5 marks. Memorise the five rows of the class table (name, growth, one example, grade). Typical MCQ: "Accessing $arr[0]$ is ...?" $\rightarrow O(1)$. "Binary search is ...?" $\rightarrow O(\log n)$. "Nested loops / Bubble Sort ...?" $\rightarrow O(n^2)$

8 marks. Number of Steps (Big O Notation): 5-mark answer plus a complete truth table and a labelled gate / logic diagram.

Answers: 1. $O(1)$ $arr[0]$; $O(\log n)$ binary search; $O(n)$ linear search; $O(n^2)$ Bubble Sort / nested loops. 3. Big O notation is a mathematical method used to describe how the running time (or memory) grows as n grows.; We ignore small constants and keep the most important term: if an algorithm does $3n + 5$ steps we write $O(n)$. 5. Use the recipe in the blue box. Model opening: When we discuss efficiency we ask how performance changes as the input size n increases. 8. Same 5-mark body + a complete truth table and a labelled gate / logic diagram + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Number of Steps (Big O Notation)** using the recipe in this topic. Include a complete truth table and a labelled gate / logic diagram. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.3.2 Number of Conditions

ACADEMY SESSION

Session 8 of 16 · 45 minutes (first half) · paired with Number of Repetitions.

10–45 min — this topic. Lock the definition and table for **Number of Conditions**. Starter (0–10) is from last class. Second half is Number of Repetitions.

On the board: Conditions (IF statements) are decision points.

Error clinic: Mistake: writing a chain of nested IFs when one compound condition would do (as in the velocity example in 2.2.2).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Number of Conditions**. Write: Conditions (IF statements) are decision points.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Nested conditions. IF inside IF often means a brute-force approach. It hurts both readability and speed. (2) Short-circuiting (the optimisation goal). Stop evaluating as soon as the result is known. In a logical AND, if the first part is False the... — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Conditions (IF statements) are decision points. Every condition forces the CPU to evaluate True or False, so excessive branching reduces performance.

- **Computational cost.** Each IF is extra work, even if the rest of the algorithm is simple.
- **Nested conditions.** IF inside IF often means a brute-force approach. It hurts both readability and speed.
- **Short-circuiting** (the optimisation goal). Stop evaluating as soon as the result is known. In a logical AND, if the first part is False the second part is skipped. In a logical OR, if the first part is True the second part is skipped.

WORKED EXAMPLE

Worked example: cheap test first. You only divide if the denominator is not zero. Place the cheap, safe test on the left so Python never evaluates the dangerous part.

```
x = 0
y = 10
if x != 0 and (y / x) > 2:
    print("ratio is large")
else:
    print("skipped safely")
```

OUTPUT

skipped safely

$x \neq 0$ is False, so AND short-circuits and y / x is never attempted. If you wrote the division first, the program would crash. Same idea in the soldier algorithm: a False height test skips Step 6.

REMEMBER IT

Put the **cheapest / most likely False** test first in an AND, and the **most likely True** test first in an OR. That is short-circuiting used on purpose.

COMMON MISTAKE

Mistake: writing a chain of nested IFs when one compound condition would do (as in the velocity example in 2.2.2).

Fix: flatten with AND/OR, and rely on short-circuiting instead of extra layers.

اردو میں سمجھیں

IF پروسیسر سے True/False پوچھتی ہے اس لیے زیادہ شاخیں کارکردگی گھٹاتی ہیں۔ اندرونی IF اکثر brute-force ہوتی ہے۔ شارٹ سرکٹ (Short-circuit) کا مطلب ہے جیسے ہی جواب معلوم ہو جانچ روک دی جائے، مثلاً AND میں پہلی شرط False ہو تو دوسری نہ چلے۔

CHECK YOURSELF

1. Why do extra IF statements reduce performance?
2. What does nested IF often indicate?
3. In $x \neq 0$ and $(y / x) > 2$ with $x = 0$, why is there no division-by-zero?

Answers: 1. Each condition must be evaluated True/False by the CPU. 2. A brute-force approach (and it reduces readability and speed). 3. AND short-circuits: the first part is False, so the division is never evaluated.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Why do extra IF statements reduce performance?

3 marks. Explain Number of Conditions with two clear points and one example.

5 marks. Write a 5-mark answer on Number of Conditions: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Each condition must be evaluated True/False by the CPU. 3. Nested conditions. IF inside IF often means a brute-force approach. It hurts both readability and speed.; Short-circuiting (the optimisation goal). Stop evaluating as soon as the result is known. In a logical AND, if the first part is... 5. Use the recipe in the blue box. Model opening: Conditions (IF statements) are decision points.

BATCH HOMEWORK

Write a 5-mark answer on **Number of Conditions** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.3.3 Number of Repetitions

ACADEMY SESSION

Session 8 of 16 · 45 minutes (second half) · paired with Number of Conditions.

45–75 min — this topic. Board working for **Number of Repetitions**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Repetitions (loops) are the most significant factor in algorithm efficiency.

Error clinic: Mistake: counting the word for and ignoring how the index moves.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Number of Repetitions**. Write: Repetitions (loops) are the most significant factor in algorithm efficiency.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Repetitions (loops) are the most significant factor in algorithm efficiency. (2) The structure of the loop decides how time grows with n . — + example.

5 marks: 3-mark structure + table: Type of repetition / Conceptual impact / Efficiency grade + the worked example from this topic.

LEARN IT

Repetitions (loops) are the most significant factor in algorithm efficiency. The **structure of the loop** decides how time grows with n .

Type of repetition	Conceptual impact	Efficiency grade
Linear loop	Processes each element exactly once. Time grows in proportion to size.	Good — $O(n)$
Logarithmic repetition	Reduces the problem size by half each iteration (binary search). Huge time savings.	Excellent — $O(\log n)$
Nested loops	For each element, process all other elements. Operations explode.	Poor — $O(n^2)$

WORKED EXAMPLE

Worked example: count the inner-body runs.

```
n = 5
linear = 0
for i in range(n):
    linear = linear + 1

nested = 0
for i in range(n):
    for j in range(n):
        nested = nested + 1

print(linear, nested)
```

OUTPUT
5 25

One loop: 5. Nested loops: $25 = 5^2$. For $n = 1,000$ that would be 1,000 versus 1,000,000.

REMEMBER IT

Find the **deepest loop**. One loop $\approx O(n)$. Loop inside a loop $\approx O(n^2)$. A loop that halves $n \approx O(\log n)$.

COMMON MISTAKE

Mistake: counting the word `for` and ignoring how the index moves.

Fix: a loop `while n > 1: n = n // 2` is logarithmic, even though it is still “a loop”.

دہرائی (لوپ) کارکردگی کا سب سے بڑا عامل ہے۔ ایک بار ہر عنصر پر چلنے والا لوپ $O(n)$ (اچھا)، ہر بار مسئلہ آدھا کرنے والا $O(\log n)$ (بہترین)، اور اندرونی لوپ $O(n^2)$ (خراب) ہے۔ اندرونی جسم کے چلنے کی گنتی سے یہ فرق صاف نظر آتا ہے۔

CHECK YOURSELF

1. What grade does the source give nested loops?
2. Why is binary search's loop logarithmic rather than linear?
3. If $n = 5$, how many times does a fully nested n -by- n pair of loops run?

Answers: 1. Poor — $O(n^2)$. 2. Each iteration halves the remaining problem, so the number of iterations is about $\log n$. 3. 25.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What grade does the source give nested loops?

3 marks. Explain Number of Repetitions with two clear points and one example.

5 marks. Write a 5-mark answer on Number of Repetitions: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Poor — $O(n^2)$ 3. Repetitions (loops) are the most significant factor in algorithm efficiency.; The structure of the loop decides how time grows with n . 5. Use the recipe in the blue box. Model opening: Repetitions (loops) are the most significant factor in algorithm efficiency.

BATCH HOMEWORK

Write a 5-mark answer on **Number of Repetitions** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.3.4 The Efficiency Evaluation Framework

ACADEMY SESSION

Session 9 of 16 · 45 minutes (first half) · paired with Refinements to improve clarity and efficiency.

10–45 min — this topic. Lock the definition and table for **The Efficiency Evaluation Framework**. Starter (0–10) is from last class. Second half is Refinements to improve clarity and efficiency.

On the board: To evaluate an algorithm at a conceptual level, ask three questions: Does it scale?

Error clinic: Mistake: always choosing the theoretically fastest Big O.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **The Efficiency Evaluation Framework**. Write: To evaluate an algorithm at a conceptual level, ask three questions: Does it scale?

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) What is the bottleneck? Focus on the most time-consuming section (usually the deepest loop) and try to improve that part. (2) Is the cost worth it? A theoretically faster $O(\log n)$ algorithm can be too complex to code and maintain. For a list of just 50 items, a... — + example.

5 marks: 3-mark structure + table: Situation / Scale / Bottleneck / Worth the cost? / Choice + the worked example from this topic.

LEARN IT

To evaluate an algorithm at a conceptual level, ask three questions:

1. **Does it scale?** If n grows 10 times, does time jump 10 times (linear) or 100 times (quadratic)? Quadratic scaling fails for large datasets.
2. **What is the bottleneck?** Focus on the most time-consuming section (usually the deepest loop) and try to improve that part.
3. **Is the cost worth it?** A theoretically faster $O(\log n)$ algorithm can be too complex to code and maintain. For a list of just 50 items, a simple $O(n)$ linear search is practically better because it is simple.

Does it scale?



Where is the bottleneck?



Is the extra complexity worth it?

WORKED EXAMPLE

Worked example: 50 names versus 1 million names.

Situation	Scale	Bottleneck	Worth the cost?	Choice
50 unsorted class names	Tiny n	A single linear scan	Binary search needs a sort first, which is extra work and extra code	Linear search $O(n)$
1,000,000 sorted account numbers, searched all day	$n \times 10$ compared with 100,000 is already huge; quadratic would be impossible	The search loop	Yes — binary search is standard and well understood	Binary search $O(\log n)$

REMEMBER IT

Framework mnemonic: **S-B-W** — **S**cale, **B**ottleneck, **W**orth it.

COMMON MISTAKE

Mistake: always choosing the theoretically fastest Big O.

Fix: question 3 exists for a reason. For $n = 50$, simple $O(n)$ beats a fragile $O(\log n)$ implementation.

اردو میں سمجھیں

کارکردگی کے تین سوال: کیا الگورتھم بڑے n پر چل سکتا ہے (Scale)؟ سب سے سست جگہ کون سی ہے (Bottleneck، عموماً گہرا لوپ)؟ کیا تیز تر طریقے کی پیچیدگی اس چھوٹے فائدے کے لائق ہے؟ پچاس ناموں کے لیے سادہ $O(n)$ تلاش عملی طور پر بہتر ہو سکتی ہے۔

CHECK YOURSELF

1. If n grows $10\times$, how much slower is a quadratic algorithm?
2. Where do you usually look for the bottleneck?
3. Why might linear search beat binary search for 50 items?

Answers: 1. About $100\times$ slower (10^2). 2. The most time-consuming section, usually the deepest loop. 3. Binary search is more complex to code and maintain, and for $n = 50$ the simplicity of $O(n)$ is practically better.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. If n grows $10\times$, how much slower is a quadratic algorithm?

3 marks. Explain The Efficiency Evaluation Framework with two clear points and one example.

5 marks. Write a 5-mark answer on The Efficiency Evaluation Framework: definition, two points, a labelled diagram or table, and one example.

Answers: 1. About $100\times$ slower (10^2) 3. What is the bottleneck? Focus on the most time-consuming section (usually the deepest loop) and try to improve that part.; Is the cost worth it? A theoretically faster $O(\log n)$ algorithm can be too complex to code and maintain. For a list... 5. Use the recipe in the blue box. Model opening: To evaluate an algorithm at a conceptual level, ask three questions: Does it scale?

BATCH HOMEWORK

Write a 5-mark answer on **The Efficiency Evaluation Framework** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.4 Refinements to improve clarity and efficiency

ACADEMY SESSION

Session 9 of 16 · 45 minutes (second half) · paired with The Efficiency Evaluation Framework.

45–75 min — this topic. Board working for **Refinements to improve clarity and efficiency**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Improving an algorithm means reviewing it step by step: simplifying logic, removing redundant work, and picking smart data structures.

Error clinic: Mistake: “optimising” by renaming variables and thinking that is an efficiency refinement.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Refinements to improve clarity and efficiency**. Write: Improving an algorithm means reviewing it step by step: simplifying logic, removing redundant work, and picking smart data structures.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Break into modules. Divide a massive block into functions, for example separating CalculateSum() from the printing logic. (2) Improve structure and indentation. Packed loops and IF statements confuse the reader. Spacing reduces mental effort. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Improving an algorithm means reviewing it step by step: simplifying logic, removing redundant work, and picking smart data structures. A clear algorithm is easier to follow; an efficient one wastes fewer steps.

2.4.1 Refinements for clarity

1. **Use meaningful names.** Replace vague variables with descriptive ones. Bad: `a = b / c`. Good: `average = totalSum / totalItems`.
2. **Break into modules.** Divide a massive block into functions, for example separating `CalculateSum()` from the printing logic.
3. **Improve structure and indentation.** Packed loops and IF statements confuse the reader. Spacing reduces mental effort.
4. **Add comments.** Keep them short. Explain **why** something is done, not just what is happening, especially for tricky logic.

2.4.2 Refinements for efficiency

1. **Reduce unnecessary steps.** In Bubble Sort, after the first pass the largest value has settled at the end. Ignore that sorted tail on the next pass by shrinking the inner loop, and you save comparisons.
2. **Use better algorithms.** Searching 1 million **sorted** records with Binary Search instead of Linear Search changes the time from seconds to milliseconds.
3. **Avoid re-computing values** (memoization / caching). If a value never changes, compute it once outside the loop, store it, and reuse it.
4. **Use appropriate data structures.** Direct access → array. Hierarchical data → tree. Do not force one structure everywhere.

WORKED EXAMPLE

Worked example 1 — shrinking Bubble Sort's inner loop (n = 5). A naive inner loop always runs $n-1 = 4$ times, for 4 passes: 16 comparisons. The refined inner loop runs 4, then 3, then 2, then 1: 10 comparisons.

```
n = 5
naive = 0
for i in range(n - 1):
    for j in range(n - 1):
        naive = naive + 1

refined = 0
for i in range(n - 1):
    for j in range(n - 1 - i):
        refined = refined + 1

print(naive, refined)
```

OUTPUT

```
16 10
```

Worked example 2 — do not re-compute a constant inside the loop.

```
A = 3
B = 4
N = 5

# BAD: C is recalculated every time
for i in range(1, N + 1):
    C = A + B
    print(C * i)
```

OUTPUT

```
7
14
21
28
35
```

```
A = 3
B = 4
N = 5
# GOOD: compute C once
C = A + B
for i in range(1, N + 1):
    print(C * i)
```

OUTPUT

```
7
14
21
28
35
```

Same output, fewer additions. That is caching: compute once, reuse N times.

REMEMBER IT

Clarity: **N-M-I-C** (Names, Modules, Indentation, Comments). Efficiency: **S-A-C-D** (Shrink steps, Algorithm choice, Cache, Data structure).

COMMON MISTAKE

Mistake: "optimising" by renaming variables and thinking that is an efficiency refinement.

Fix: meaningful names improve **clarity**. Efficiency refinements change the **amount of work** (fewer loop iterations, a better algorithm, no re-compute, a better structure).

اردو میں سمجھیں

وضاحت بہتر کرنے کے لیے معنی خیز نام، ماڈیول، درست indentation اور مختصر تبصرے استعمال کریں۔ کارکردگی کے لیے فضول قدم ہٹائیں (بیل سارٹ میں ترتیب شدہ دم نظر انداز کریں)، بہتر الگورتھم چنیں (لینینر کی جگہ بائنری سرچ)، لوپ کے اندر وہی حساب بار بار نہ کریں (Caching/Memoization)، اور مناسب ڈیٹا سٹرکچر رکھیں۔

CHECK YOURSELF

1. Rewrite $a = b / c$ with meaningful names for an average.
2. After Bubble Sort's first pass, what should the next pass ignore?
3. In the A+B example, where should $C = A + B$ be written?

Answers: 1. average = totalSum / totalItems. 2. The already-sorted largest value at the end (shrink the inner loop). 3. Once, outside the loop, then reuse C inside.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Rewrite $a = b / c$ with meaningful names for an average.

3 marks. Explain Refinements to improve clarity and efficiency with two clear points and one example.

5 marks. Write a 5-mark answer on Refinements to improve clarity and efficiency: definition, two points, a labelled diagram or table, and one example.

Answers: 1. average = totalSum / totalItems 3. Break into modules. Divide a massive block into functions, for example separating CalculateSum() from the printing logic.; Improve structure and indentation. Packed loops and IF statements confuse the reader. Spacing reduces mental effort. 5. Use the recipe in the blue box. Model opening: Improving an algorithm means reviewing it step by step: simplifying logic, removing redundant work, and picking smart data structures.

BATCH HOMEWORK

Write a 5-mark answer on **Refinements to improve clarity and efficiency** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.5 Concept of Data Structure ★ Golden

ACADEMY SESSION

Session 10 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A data structure is a systematic way of organising, storing and managing data so that an algorithm can access, modify and process it efficiently.

Error clinic: Mistake: calling a tree “linear” because you can walk it from top to bottom.

Exam wording to train: Define data structure in full (organise, store, manage; efficient access and processing).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Concept of Data Structure**. Write: A data structure is a systematic way of organising, storing and managing data so that an algorithm can access, modify and process it efficiently.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Books on a shelf are arranged in a set order, so you can find a title quickly. (2) Files in folders are grouped on purpose. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **data structure** is a systematic way of **organising, storing and managing** data so that an algorithm can access, modify and process it efficiently.

Real-life analogy. Books on a shelf are arranged in a set order, so you can find a title quickly. Files in folders are grouped on purpose. Data structures do the same job inside computer memory.

1. Linear data structures

Elements stand in a strict sequence, one after another. Each element (except the first and last) has exactly **one predecessor** and **one successor**.

Examples: Array, Linked List, Stack, Queue.

2. Non-linear data structures

Elements are connected in a hierarchy or a network. One element can connect to **several** others at the same time.


Examples: Tree, Graph.

Linear (sequence)



one after another

Non-linear (branch / net)



Linear: a line of neighbours. Non-linear: a node with more than one connection.

WORKED EXAMPLE

Worked example: classify each everyday picture.

1. Students standing in a single assembly line → **linear** (each has one in front and one behind).
2. A family tree of grandparents, parents and children → **non-linear** (one parent, several children).
3. Roads linking Karachi, Hyderabad, Sukkur and Larkana in many ways → **non-linear** (a network).

REMEMBER IT

Ask: "Does each item have at most one next item?" Yes → linear. "Can one item link to many, or can links form a net?" → non-linear.

COMMON MISTAKE

Mistake: calling a tree "linear" because you can walk it from top to bottom.

Fix: walking is traversal. The **shape** is hierarchical: one parent, many children. That is non-linear.

اردو میں سمجھیں

ڈیٹا سٹرکچر ڈیٹا کو منظم طریقے سے رکھنے کا نظام ہے تاکہ الگورتھم اسے جلدی استعمال کر سکے۔ لکیری ڈھانچوں میں عناصر قطار میں ہوتے ہیں (ایرے، لنکڈ لسٹ، سٹیک، کیو)۔ غیر لکیری میں ایک عنصر کئی سے جڑ سکتا ہے (ٹری، گراف)۔ الماری کی کتابیں اور فولڈرز کی مثال یاد رکھیں۔

EXAM TIP

Define data structure in full (organise, store, manage; efficient access and processing). Then split linear vs non-linear with the "one predecessor and one successor" test, and list the four linear and two non-linear examples. The shelf / folder analogy earns a mark. MCQs: "Which is non-linear?" → Tree or Graph.

CHECK YOURSELF

1. Define data structure.
2. Name four linear and two non-linear examples.
3. What is true of each middle element in a linear structure?

Answers: 1. A systematic way of organising, storing and managing data for efficient access, modification and processing. 2. Linear: array, linked list, stack, queue. Non-linear: tree, graph. 3. It has exactly one predecessor and one successor.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Define data structure.

3 marks. Explain Concept of Data Structure with two clear points and one example.

5 marks. Define data structure in full (organise, store, manage; efficient access and processing). Then split linear vs non-linear with the “one predecessor and one successor” test, and list the four linear...

8 marks. Concept of Data Structure: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. A systematic way of organising, storing and managing data for efficient access, modification and processing. 3. Books on a shelf are arranged in a set order, so you can find a title quickly.; Files in folders are grouped on purpose. 5. Use the recipe in the blue box. Model opening: A data structure is a systematic way of organising, storing and managing data so that an algorithm can access, modify and process it efficiently. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Concept of Data Structure** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.5.1 Linear Data Structures: Array

ACADEMY SESSION

Session 11 of 16 · 45 minutes (first half) · paired with Linear Data Structures: Linked List.

10–45 min — this topic. Lock the definition and table for **Linear Data Structures: Array**. Starter (0–10) is from last class. Second half is Linear Data Structures: Linked List.

On the board: An array holds a collection of similar items (the same data type) placed next to each other in contiguous memory (one continuous block).

Error clinic: Limitation.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Linear Data Structures: Array**. Write: An array holds a collection of similar items (the same data type) placed next to each other in contiguous memory (one continuous block).

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Each item has a position number called an index, usually starting from 0. (2) Because the address of any cell can be calculated from the index, you can jump straight to it. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

An **array** holds a collection of **similar items** (the same data type) placed next to each other in **contiguous memory** (one continuous block).

Each item has a position number called an **index**, usually starting from **0**. Because the address of any cell can be calculated from the index, you can jump straight to it. That is **direct access** (also called random access), and it is $O(1)$.

Array name: A

23	76	12	90	34	68
0	1	2	3	4	5

A[3] = 90 (index starts at 0)

Six integers in contiguous cells. Direct access: A[3] jumps to 90 without walking 23, 76 and 12.

WORKED EXAMPLE

Worked example: read by index.

```
A = [23, 76, 12, 90, 34, 68]
print(A[3])
print(A[0])
```

OUTPUT

```
90
23
```

REMEMBER IT

Index 0 is the first shelf on the row. The third item that humans call "number 4" is index 3. Formula in your head:
position from the left, minus one.

COMMON MISTAKE

Limitation. Arrays are fast to read by index but **inflexible** to grow in the middle. Inserting a new value between 12 and 90 means shifting 90, 34 and 68 one cell to the right. That shift is $O(n)$, so arrays are a poor fit when you insert and delete in the middle all the time.

اردو میں سمجھیں

ایرے ایک جیسے عناصر کو میموری کے لگاتار بلاک میں رکھتا ہے۔ ہر عنصر کا انڈیکس (عموماً 0 سے) ہوتا ہے جس سے براہ راست رسائی $O(1)$ میں مل جاتی ہے، جیسے $A[3] = 90$ ۔ درمیان میں نیا عنصر ڈالنے کے لیے دائیں طرف شفٹ کرنا پڑتا ہے جو سست ہے۔

CHECK YOURSELF

1. What does "contiguous memory" mean?
2. In the diagram, what is A[2]?
3. Why is inserting in the middle of an array inefficient?

Answers: 1. The items sit in one continuous block, next to each other. 2. 12. 3. Later elements must all be shifted right to make room.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does "contiguous memory" mean?

3 marks. Explain Linear Data Structures: Array with two clear points and one example.

5 marks. Write a 5-mark answer on Linear Data Structures: Array: definition, two points, a labelled diagram or table, and one example.

Answers: 1. The items sit in one continuous block, next to each other 3. Each item has a position number called an index, usually starting from 0.; Because the address of any cell can be calculated from the index, you can jump straight to it. 5. Use the recipe in the blue box. Model opening: An array holds a collection of similar items (the same data type) placed next to each other in contiguous memory (one continuous block).

BATCH HOMEWORK

Write a 5-mark answer on **Linear Data Structures: Array** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Linear Data Structures: Linked List

ACADEMY SESSION

Session 11 of 16 · 45 minutes (second half) · paired with Linear Data Structures: Array.

45–75 min — this topic. Board working for **Linear Data Structures: Linked List**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: A linked list stores data as a chain.

Error clinic: Mistake: writing list[3] and calling it linked-list access.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Linear Data Structures: Linked List**. Write: A linked list stores data as a chain.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) the actual data; (2) a link (pointer) holding the memory address of the next node. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT


A **linked list** stores data as a chain. Unlike an array, the items are **not** one continuous block. Each separate piece is a **node** sitting somewhere in memory.

Each node has two parts:

1. the actual **data**;
2. a **link** (pointer) holding the memory address of the **next** node.

The first node is pointed to by **HEAD**. The last node's link is **NULL** (nowhere). To find an item you start at HEAD and follow links one by one — **sequential access**, $O(n)$.

Real-life example: browser history. Clicking Back follows the pointer to the previous page-node.



Follow HEAD → 23 → 76 → 12 → 90 → NULL

Four nodes. The last link is NULL, which ends the chain.

WORKED EXAMPLE

Worked example: walk from HEAD to print every data field.

```
nodes = [23, 76, 12, 90]
for data in nodes:
    print(data, end=" → ")
print("NULL")
```

OUTPUT

23 → 76 → 12 → 90 → NULL

There is no `nodes[2]` jump in a real linked list. The loop above models following each link once. Inserting a new node between 76 and 12 only means changing two pointers — you do not shift the rest of a big block, which is why lists beat arrays for frequent insert/delete.

REMEMBER IT

Array = row of lockers with numbers on the doors. Linked list = treasure hunt: each clue (link) tells you where the next box is.

COMMON MISTAKE

Mistake: writing `list[3]` and calling it linked-list access.

Fix: a true linked list has no index. Python's `list` type is an array-like structure. In this chapter, "linked list" means HEAD-and-pointers.

اردو میں سمجھیں

لنکڈ لسٹ زنجیر کی طرح نوڈز پر مشتمل ہے جو میموری میں بکھرے ہو سکتے ہیں۔ ہر نوڈ میں ڈیٹا اور اگلے نوڈ کا پتہ (Link) ہوتا ہے۔ پہلا نوڈ HEAD سے ملتا ہے، آخری کا لنک NULL ہوتا ہے۔ براؤزر کا Back بٹن پچھلے نوڈ کے پوائنٹر پر چلتا ہے۔ رسائی ترتیب وار ہے، انڈیکس سے چھلانگ نہیں۔

CHECK YOURSELF

1. Name the two parts of a node.
2. What does the last node's link store?
3. Why is browser history a fair analogy?

Answers: 1. Data, and a link/pointer to the next node. 2. NULL (no next node). 3. Back follows the pointer to the previous page-node instead of jumping by index.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name the two parts of a node.

3 marks. Explain Linear Data Structures: Linked List with two clear points and one example.

5 marks. Write a 5-mark answer on Linear Data Structures: Linked List: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Data, and a link/pointer to the next node 3. the actual data;; a link (pointer) holding the memory address of the next node. 5. Use the recipe in the blue box. Model opening: A linked list stores data as a chain.

BATCH HOMEWORK

Write a 5-mark answer on **Linear Data Structures: Linked List** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Linear Data Structures: Stack ★ Golden

ACADEMY SESSION

Session 12 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A stack is a linear data structure that works on the LIFO principle: Last-In, First-Out.

Error clinic: Mistake: POPing from the bottom, or mixing LIFO with FIFO.

Exam wording to train: Define stack + LIFO, define PUSH and POP, mention TOP, give the Undo example, and draw the vertical boxes with TOP labelled.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Linear Data Structures: Stack**. Write: A stack is a linear data structure that works on the LIFO principle: Last-In, First-Out.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) PUSH — add an item to the top. (2) POP — remove the item from the top. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.


8–10 marks: 5-mark structure + a filled trace table with every variable on every line + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **stack** is a linear data structure that works on the **LIFO** principle: **Last-In, First-Out**. The last element added is the first one removed. You cannot pull an item from the bottom or the middle.

- **PUSH** — add an item to the **top**.
- **POP** — remove the item from the **top**.

A **TOP** pointer always names the current top item. **Real-life example:** Undo in a text editor. Every action is piled on the stack; Undo POPs the most recent action first.



PUSH Data1, Data2, Data3 — first POP is Data3

Three PUSH operations. The TOP is Data 3, so the first POP returns Data 3.

WORKED EXAMPLE

Worked example: PUSH / POP trace. Start with an empty stack. Then PUSH Data1, PUSH Data2, PUSH Data3, POP, POP.

Step	Operation	Stack (bottom → top)	TOP	Popped value
0	(empty)	[]	none	
1	PUSH Data1	[Data1]	Data1	
2	PUSH Data2	[Data1, Data2]	Data2	
3	PUSH Data3	[Data1, Data2, Data3]	Data3	
4	POP	[Data1, Data2]	Data2	Data3
5	POP	[Data1]	Data1	Data2

```
stack = []
stack.append("Data1")
stack.append("Data2")
stack.append("Data3")
print("after 3 PUSHes:", stack)
print("POP:", stack.pop())
print("POP:", stack.pop())
print("left:", stack)
```

OUTPUT

```
after 3 PUSHes: ['Data1', 'Data2', 'Data3']
POP: Data3
POP: Data2
left: ['Data1']
```

Python's `list.append` is PUSH and `list.pop()` (no index) is POP from the top.

REMEMBER IT

LIFO = Last In First Out = "last plate washed is first plate used" on a canteen pile. Undo, Redo, Back button and function calls are all stacks.

COMMON MISTAKE

Mistake: POPing from the bottom, or mixing LIFO with FIFO.

Fix: stack = plates (top only). Queue = ticket line (front leaves, rear joins). If the first POP is Data1, you drew a queue, not a stack.

اردو میں سمجھیں

سٹیک LIFO پر چلتا ہے: جو سب سے بعد میں آیا وہ سب سے پہلے نکلے گا۔ اوپر رکھنا PUSH، اوپر سے ہٹانا POP، اور TOP پوائنٹر موجودہ سب سے اوپر عنصر بتاتا ہے۔ انڈو (Undo) کی مثال: ہر عمل ڈھیر پر پڑتا ہے، انڈو سب سے تازہ عمل ہٹاتا ہے۔

EXAM TIP

Define stack + LIFO, define PUSH and POP, mention TOP, give the Undo example, and draw the vertical boxes with TOP labelled. Trace questions: "Show the stack after PUSH A, PUSH B, POP, PUSH C." Work left to right; the first POP must be B. Never remove from the middle.

CHECK YOURSELF

1. Expand LIFO.
2. After PUSH Data1, Data2, Data3, what does the first POP return?
3. Why is Undo modelled as a stack?

Answers: 1. Last-In, First-Out. 2. Data3. 3. Each action is PUSHed; Undo POPs the most recent action first.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Expand LIFO.

3 marks. Explain Linear Data Structures: Stack with two clear points and one example.

5 marks. Define stack + LIFO, define PUSH and POP, mention TOP, give the Undo example, and draw the vertical boxes with TOP labelled. Trace questions: "Show the stack after PUSH A, PUSH B, POP, PUSH C." Work...

8 marks. Linear Data Structures: Stack: 5-mark answer plus a filled trace table with every variable on every line.

Answers: 1. Last-In, First-Out 3. PUSH — add an item to the top.; POP — remove the item from the top. 5. Use the recipe in the blue box. Model opening: A stack is a linear data structure that works on the LIFO principle: Last-In, First-Out. 8. Same 5-mark body + a filled trace table with every variable on every line + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Linear Data Structures: Stack** using the recipe in this topic. Include a filled trace table with every variable on every line. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Linear Data Structures: Queue ★ Golden

ACADEMY SESSION

Session 13 of 16 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A queue organises data on the FIFO principle: First-In, First-Out.

Error clinic: Mistake: DEQUEUEing from the rear, or ENQUEUEing at the front.

Exam wording to train: Define queue + FIFO, define ENQUEUE (rear) and DEQUEUE (front), give the printer example, draw the labelled Front/Rear diagram, and trace a short sequence.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Linear Data Structures: Queue**. Write: A queue organises data on the FIFO principle: First-In, First-Out.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) ENQUEUE — add an element at the Rear (back). (2) DEQUEUE — remove an element from the Front. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.


8–10 marks: 5-mark structure + a filled trace table with every variable on every line + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **queue** organises data on the **FIFO** principle: **First-In, First-Out**. Whoever arrives first is served first. Order truly matters.

- **ENQUEUE** — add an element at the **Rear** (back).
- **DEQUEUE** — remove an element from the **Front**.

Real-life example: several documents sent to a printer. The printer prints the first document received, then the next.



WORKED EXAMPLE

Worked example: ENQUEUE / DEQUEUE trace. Start empty. ENQUEUE 55, 76, 90, then ENQUEUE D, then DEQUEUE.

Step	Operation	Queue (Front → Rear)	Front	Rear	Removed
0	(empty)	[]	—	—	
1	ENQUEUE 55	[55]	55	55	
2	ENQUEUE 76	[55, 76]	55	76	
3	ENQUEUE 90	[55, 76, 90]	55	90	
4	ENQUEUE D	[55, 76, 90, D]	55	D	
5	DEQUEUE	[76, 90, D]	76	D	55

```
from collections import deque
q = deque()
q.append(55)
q.append(76)
q.append(90)
q.append("D")
print("after ENQUEUE D:", list(q))
print("DEQUEUE:", q.popleft())
print("left:", list(q))
```

OUTPUT

```
after ENQUEUE D: [55, 76, 90, 'D']
DEQUEUE: 55
left: [76, 90, 'D']
```

append is ENQUEUE at the rear; popleft is DEQUEUE from the front. The first DEQUEUE is 55 (the oldest), never D.

REMEMBER IT

FIFO = First In First Out = a canteen line. Front = the person being served. Rear = the person who just joined.

COMMON MISTAKE

Mistake: DEQUEUEing from the rear, or ENQUEUEing at the front.

Fix: new items only at Rear; removal only at Front. If your first removal is D, you treated the queue as a stack.

اردو میں سمجھیں

کیو FIFO پر چلتی ہے: جو پہلے آیا وہ پہلے نکلے۔ پیچھے (Rear) شامل کرنا ENQUEUE، آگے (Front) سے ہٹانا DEQUEUE ہے۔ پرنٹر کی قطار: جو فائل پہلے بھیجی گئی وہ پہلے چھپے گی۔ پہلی DEQUEUE ہمیشہ سب سے پرانا عنصر نکالتی ہے۔

EXAM TIP

Define queue + FIFO, define ENQUEUE (rear) and DEQUEUE (front), give the printer example, draw the labelled Front/Rear diagram, and trace a short sequence. Examiners mix stack and queue on the same paper: if they say "first come, first served" write Queue; if they say "Undo" write Stack.

CHECK YOURSELF

1. Expand FIFO. Where is an item added, and where is it removed?
2. After ENQUEUE 55, 76, 90, what does DEQUEUE return?
3. Why is a printer a queue, not a stack?

Answers: 1. First-In, First-Out; added at Rear, removed from Front. 2. 55. 3. Documents must print in the order they arrived (first received, first printed), not last-received first.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Expand FIFO. Where is an item added, and where is it removed?

3 marks. Explain Linear Data Structures: Queue with two clear points and one example.

5 marks. Define queue + FIFO, define ENQUEUE (rear) and DEQUEUE (front), give the printer example, draw the labelled Front/Rear diagram, and trace a short sequence. Examiners mix stack and queue on the same...

8 marks. Linear Data Structures: Queue: 5-mark answer plus a filled trace table with every variable on every line.

Answers: 1. First-In, First-Out; added at Rear, removed from Front. 3. ENQUEUE — add an element at the Rear (back).; DEQUEUE — remove an element from the Front. 5. Use the recipe in the blue box. Model opening: A queue organises data on the FIFO principle: First-In, First-Out. 8. Same 5-mark body + a filled trace table with every variable on every line + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Linear Data Structures: Queue** using the recipe in this topic. Include a filled trace table with every variable on every line. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.5.2 Non-Linear Data Structures: Tree

ACADEMY SESSION

Session 14 of 16 · 45 minutes (first half) · paired with Non-Linear Data Structures: Graph.

10–45 min — this topic. Lock the definition and table for **Non-Linear Data Structures: Tree**. Starter (0–10) is from last class. Second half is Non-Linear Data Structures: Graph.

On the board: A tree organises data in a hierarchy.

Error clinic: Mistake: drawing a tree with two roots, or with an arrow going back up to the Principal from HOD CS (a cycle).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Non-Linear Data Structures: Tree**. Write: A tree organises data in a hierarchy.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Everything branches out from a single starting point called the root. (2) It creates a strict one-to-many (parent-child) relationship. — + example.


5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

A **tree** organises data in a **hierarchy**. Everything branches out from a single starting point called the **root**.

It creates a strict **one-to-many (parent-child)** relationship. That is an excellent way to show how roles flow in an organisation.

Real-life examples: a family tree (grandparents → parents → children) and folders inside folders on a drive.



College tree: one root (Principal), then parent-child branches. No child has two parents in this model.

WORKED EXAMPLE

Worked example: name the relationships.

- Root: Principal.
- Children of the root: Administrative Head, Academic Dean.
- Children of Academic Dean: HOD Math, HOD CS.
- HOD CS has one parent (Academic Dean), not two — that is the tree rule. If HOD CS also reported sideways to Accounts as an equal link, the picture would become a **graph**.

REMEMBER IT

Tree = family / folders / organogram. One root. Branches down. Parent-child, not a web of equals.

COMMON MISTAKE

Mistake: drawing a tree with two roots, or with an arrow going back up to the Principal from HOD CS (a cycle).

Fix: one root, links only parent → child, no loops. Cycles belong to graphs.

اردو میں سمجھیں

ٹری ڈیٹا کو درجہ بندی (Hierarchy) میں رکھتی ہے جو ایک جڑ (Root) سے پھوٹی ہے۔ تعلق والدین-بچہ (ایک سے کئی) ہوتا ہے، جیسے پرنسپل → ڈین → ایچ او ڈی، خاندانی شجرہ، یا فولڈر کے اندر فولڈر۔ دو جڑیں یا چکر ٹری کو گراف بنا دیتے ہیں۔

CHECK YOURSELF

1. What is the starting node of a tree called?
2. What kind of relationship does a tree model?
3. Give two real-life tree examples from the source.

Answers: 1. The root. 2. One-to-many parent-child. 3. A family tree, and folders inside folders (or a college organogram).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is the starting node of a tree called?

3 marks. Explain Non-Linear Data Structures: Tree with two clear points and one example.

5 marks. Write a 5-mark answer on Non-Linear Data Structures: Tree: definition, two points, a labelled diagram or table, and one example.

Answers: 1. The root 3. Everything branches out from a single starting point called the root.; It creates a strict one-to-many (parent-child) relationship. 5. Use the recipe in the blue box. Model opening: A tree organises data in a hierarchy.

BATCH HOMEWORK

Write a 5-mark answer on **Non-Linear Data Structures: Tree** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Non-Linear Data Structures: Graph

ACADEMY SESSION

Session 14 of 16 · 45 minutes (second half) · paired with Non-Linear Data Structures: Tree.

45–75 min — this topic. Board working for **Non-Linear Data Structures: Graph**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: A graph organises data when things connect in a flexible, complex way.

Error clinic: Mistake: using a tree for GPS because “Hyderabad comes under Sindh”.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Non-Linear Data Structures: Graph**. Write: A graph organises data when things connect in a flexible, complex way.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Nodes (vertices) — the items (cities, people). (2) Edges — the connections (roads, friendships). — + example.


5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

A **graph** organises data when things connect in a flexible, complex way. Unlike a tree, there is **no strict hierarchy**: any node can connect to any other node.

- **Nodes (vertices)** — the items (cities, people).
- **Edges** — the connections (roads, friendships).

Examples: Facebook friends; GPS mapping (the fastest route between two cities).



Four vertices A, B, C, D. Edges can form a cycle (A–B–D–C–A). A tree cannot do that.

WORKED EXAMPLE

Worked example: Karachi – Hyderabad – Sukkur – Larkana. Cities are vertices. Roads are edges. You can travel Karachi → Hyderabad → Sukkur or Karachi → Larkana → Sukkur. There is no single “root city”. That is a graph, and GPS uses it to pick a fast route.

REMEMBER IT

Tree $\subset$ Graph in shape-talk: a tree is a special graph with one root and no cycles. If you need cycles or many-to-many links, say **graph**.

COMMON MISTAKE

Mistake: using a tree for GPS because “Hyderabad comes under Sindh”.

Fix: administration can be a tree; **roads** are a graph because you can loop and take alternative paths.

اردو میں سمجھیں

گراف لچکدار روابط کے لیے ہے: کوئی سخت درجہ بندی نہیں، کوئی بھی نوڈ کسی سے جڑ سکتا ہے۔ نوڈز (Vertices) چیزیں ہیں، کنارے (Edges) تعلق۔ فیس بک دوست اور GPS نقشہ کلاسیکی مثالیں ہیں۔ چکر (Cycle) اور کئی راستے گراف کو ٹری سے الگ کرتے ہیں۔

CHECK YOURSELF

1. What are the two parts of a graph?
2. Give two source examples of graphs.
3. State one difference between a tree and a graph.

Answers: 1. Nodes/vertices and edges. 2. Social networks (Facebook friends) and GPS mapping. 3. A tree has a hierarchy and one root; a graph has no strict hierarchy and any node may connect to any other (cycles allowed).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What are the two parts of a graph?

3 marks. Explain Non-Linear Data Structures: Graph with two clear points and one example.

5 marks. Write a 5-mark answer on Non-Linear Data Structures: Graph: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Nodes/vertices and edges 3. Nodes (vertices) — the items (cities, people).; Edges — the connections (roads, friendships). 5. Use the recipe in the blue box. Model opening: A graph organises data when things connect in a flexible, complex way.

BATCH HOMEWORK

Write a 5-mark answer on **Non-Linear Data Structures: Graph** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.5.3 Operations on Data Structures

ACADEMY SESSION

Session 15 of 16 · 45 minutes (first half) · paired with Identify data structures in problem scenarios.

10–45 min — this topic. Lock the definition and table for **Operations on Data Structures**. Starter (0–10) is from last class. Second half is Identify data structures in problem scenarios.

On the board: Whatever the shape, you keep meeting the same five operations:

Error clinic: Mistake: calling a PUSH “sorting” because the stack looks tidy.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Operations on Data Structures**. Write: Whatever the shape, you keep meeting the same five operations:

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Whatever the shape, you keep meeting the same five operations: (2) Second distinct point (not a repeat of the definition) — + example.

5 marks: 3-mark structure + table: Operation / Meaning / Quick picture + the worked example from this topic.

LEARN IT

Whatever the shape, you keep meeting the same five operations:

Operation	Meaning	Quick picture
Insertion	Adding a new item into the structure.	PUSH on a stack; ENQUEUE on a queue; putting 40 into an array.
Deletion	Removing an item that is no longer needed.	POP; DEQUEUE; deleting a node from a list.
Traversal	Going through each item one by one.	Walking HEAD → ... → NULL; visiting every tree node.
Searching	Finding a specific item.	Linear search in an array; following links until 87 is found.
Sorting	Arranging items in a proper order (ascending or descending).	Bubble Sort on an array of marks.

WORKED EXAMPLE

Worked example: name the operation.

- “Print every song from the start of the playlist.” → **Traversal**.
- “Add a print job at the rear.” → **Insertion** (ENQUEUE).
- “Undo the last typing action.” → **Deletion** (POP).
- “Is roll number 87 in the list?” → **Searching**.
- “Arrange heights from shortest to tallest.” → **Sorting**.

REMEMBER IT

Memorise **I-D-T-S-S**: Insert, Delete, Traverse, Search, Sort.

COMMON MISTAKE

Mistake: calling a PUSH "sorting" because the stack looks tidy.

Fix: PUSH is insertion. Sorting means putting values in ascending or descending order.

اردو میں سمجھیں

ہر ڈیٹا سٹرکچر پر پانچ عمل ہوتے ہیں: داخل کرنا (Insertion)، حذف کرنا (Deletion)، ایک ایک کر کے گزرنا (Traversal)، تلاش (Searching) اور ترتیب (Sorting، صعودی یا نزولی)۔

CHECK YOURSELF

1. List the five operations.
2. Which operation is ENQUEUE?
3. Traversal vs searching — one difference?

Answers: 1. Insertion, deletion, traversal, searching, sorting. 2. Insertion (at the rear of a queue). 3. Traversal visits every item; searching stops when the target is found (or the structure ends).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. List the five operations.

3 marks. Explain Operations on Data Structures with two clear points and one example.

5 marks. Write a 5-mark answer on Operations on Data Structures: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Insertion, deletion, traversal, searching, sorting. 3. Whatever the shape, you keep meeting the same five operations: 5. Use the recipe in the blue box. Model opening: Whatever the shape, you keep meeting the same five operations:

BATCH HOMEWORK

Write a 5-mark answer on **Operations on Data Structures** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.6 Identify data structures in problem scenarios

ACADEMY SESSION

Session 15 of 16 · 45 minutes (second half) · paired with Operations on Data Structures.

45–75 min — this topic. Board working for **Identify data structures in problem scenarios**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: To pick a structure, first see how the data is organised.

Error clinic: Mistake: choosing an array for Undo because "actions are stored in a list".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Identify data structures in problem scenarios**. Write: To pick a structure, first see how the data is organised.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Music playlist / browser history → Linked list. Every song knows what comes next. When one finishes, follow the pointer. Frequent... (2) Undo or Redo → Stack (LIFO). Each typing or formatting action is PUSHed. Undo POPs the most recent action. — + example.

5 marks: 3-mark structure + table: If the data... / Then it is... / Recommended structure + the worked example from this topic.

LEARN IT

To pick a structure, first see how the data is organised. If each item has a clear “before and after”, it is **linear**. If it branches or connects to many items, it is **non-linear**.

2.6.1 Linear scenarios

- 1. Storing student grades for a class → Array.** You usually know how many students there are, and all grades are the same type. Indices give rapid lookup.
- 2. Music playlist / browser history → Linked list.** Every song knows what comes next. When one finishes, follow the pointer. Frequent insert/delete is cheap.
- 3. Undo or Redo → Stack (LIFO).** Each typing or formatting action is PUSHed. Undo POPs the most recent action.
- 4. Printer task scheduling → Queue (FIFO).** Documents print in the exact order they were received. First-come, first-served.

2.6.2 Non-linear scenarios

- 1. Organisational chart of a college → Tree.** Principal is the root, then deans, then HODs, then teachers. Clear parent-child links.
- 2. GPS navigation and maps → Graph.** Cities are nodes, roads are edges. No strict top-down hierarchy. Several routes can reach the same destination.

If the data...	Then it is...	Recommended structure
Follows “next” or “previous” logic	Linear	Array, Linked list
Follows “parent” and “child” logic	Non-linear	Tree
Follows “first-come, first-served” logic	Linear	Queue
Follows “connections / relationships” logic	Non-linear	Graph
Needs to be accessed in the reverse order of entry	Linear	Stack

WORKED EXAMPLE

Worked example: match five school problems.

Scenario	Structure	Why (one line)
Store 40 practical marks you already counted	Array	Fixed size, same type, need A[i] lookup.
A playlist where the teacher inserts a nasheed between two songs	Linked list	Insert by moving two pointers, no big shift.
Ctrl+Z after formatting a heading	Stack	Last action must come off first.
Students lining up for the photocopier	Queue	First in line is served first.
Friend links in a class WhatsApp “everyone knows everyone”	Graph	Any student can connect to any other.

REMEMBER IT

Decision order: reverse-of-entry? → stack. First-come? → queue. Parent-child? → tree. Many-to-many routes? → graph. Known list with indexes? → array. Lots of insert/delete in a sequence? → linked list.

COMMON MISTAKE

Mistake: choosing an array for Undo because “actions are stored in a list”.

Fix: the **access rule** matters more than “it is a list”. Undo is reverse order of entry → stack.

اردو میں سمجھیں

اگر ہر عنصر کا واضح اگلا/پچھلا ہے تو ڈھانچہ لکیری ہے؛ اگر شاخیں یا کئی روابط ہیں تو غیر لکیری۔ نمبر: ایرے؛ پلے لسٹ/ہسٹری: لنکڈ لسٹ؛ انڈو: سٹیک؛ پرنٹر: کیو؛ کالج کا چارٹ: ٹری؛ GPS: گراف۔ فیصلے کی جدول یاد کر لیں۔

CHECK YOURSELF

1. Which structure stores a class's grades, and why?
2. Printer jobs: stack or queue? Why?
3. “Needs reverse order of entry” maps to which structure?

Answers: 1. Array — known size, same type, fast index lookup. 2. Queue, because first-come, first-served. 3. Stack.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which structure stores a class's grades, and why?

3 marks. Explain Identify data structures in problem scenarios with two clear points and one example.

5 marks. Write a 5-mark answer on Identify data structures in problem scenarios: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Array — known size, same type, fast index lookup 3. Music playlist / browser history → Linked list. Every song knows what comes next. When one finishes, follow the pointer. Frequent...; Undo or Redo → Stack (LIFO). Each typing or formatting action is PUSHed. Undo POPs the most recent action. 5. Use the recipe in the blue box. Model opening: To pick a structure, first see how the data is organised.

BATCH HOMEWORK

Write a 5-mark answer on **Identify data structures in problem scenarios** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

2.7 Trace data retrieval in Array, List and Queue

ACADEMY SESSION

Session 16 of 16 · 45 minutes (first half) · paired with Career Opportunities in Algorithms.

10–45 min — this topic. Lock the definition and table for **Trace data retrieval in Array, List and Queue**. Starter (0–10) is from last class. Second half is Career Opportunities in Algorithms.

On the board: Tracing data retrieval means following the step-by-step path of how an algorithm finds or accesses data.

Error clinic: Mistake: DEQUEUEing C because “C is the interesting letter”, or reading linked-list node 4 as list[3] without walking.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Trace data retrieval in Array, List and Queue**. Write: Tracing data retrieval means following the step-by-step path of how an algorithm finds or accesses data.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Tracing data retrieval means following the step-by-step path of how an algorithm finds or accesses data. (2) Array, linked list and queue are all linear, but the effort to find an item is very different because of how they are organised inside. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

Tracing data retrieval means following the step-by-step path of how an algorithm finds or accesses data. Array, linked list and queue are all linear, but the **effort** to find an item is very different because of how they are organised inside.

2.7.1 Retrieval in an array

Every element has a fixed index from 0 to $n-1$ pointing at a spot in memory. If the algorithm already knows the index, it does not search: it **jumps** (direct access, $O(1)$).

Array = [10, 50, 20, 70, 90, 30]. Direct access: `Array[2] = 20`.

Loop iteration	Index	Array access	Value
1	0	<code>Array[0]</code>	10
2	1	<code>Array[1]</code>	50
3	2	<code>Array[2]</code>	20

```
Array = [10, 50, 20, 70, 90, 30]
print("Direct Array[2] =", Array[2])
for i in range(3):
    print(i + 1, i, f"Array[{i}]", Array[i])
```

OUTPUT

```
Direct Array[2] = 20
1 0 Array[0] 10
2 1 Array[1] 50
3 2 Array[2] 20
```

2.7.2 Retrieval in a linked list

Linked lists have **no index**. The only way is to start at HEAD and follow links one node at a time (sequential access, $O(n)$).

List: [12] → [98] → [23] → [87] → [56] → NULL. Search key: 87.

Step	Node data	Compare with 87	Action
1	12	$12 \neq 87$	Move next
2	98	$98 \neq 87$	Move next
3	23	$23 \neq 87$	Move next
4	87	$87 == 87$	FOUND — output True

```

nodes = [12, 98, 23, 87, 56]
key = 87
found = False
for i, value in enumerate(nodes, start=1):
    print(f"Step {i}: Check Node {i} ({value}).")
    if value == key:
        found = True
        print("FOUND! Output: True")
        break
    print("Not equal. Move Next.")
print("Result:", found)

```

OUTPUT

```

Step 1: Check Node 1 (12).
Not equal. Move Next.
Step 2: Check Node 2 (98).
Not equal. Move Next.
Step 3: Check Node 3 (23).
Not equal. Move Next.
Step 4: Check Node 4 (87).
FOUND! Output: True
Result: True

```

Key 87 sits at the fourth node, so you paid four checks. An array that already knew index 3 would have paid one jump.

2.7.3 Retrieval in a queue

A queue is FIFO. You **cannot** retrieve from the middle or the rear. The oldest item at the Front is always DEQUEUEEd first.



You cannot pull B until A has left.

Queue A, B, C. ENQUEUE D joins the rear. DEQUEUE must remove A, not C or B.

```

from collections import deque
q = deque(["A", "B", "C"])
q.append("D")
print("after ENQUEUE D:", list(q))
print("DEQUEUE:", q.popleft())
print("now:", list(q))

```

OUTPUT

```

after ENQUEUE D: ['A', 'B', 'C', 'D']
DEQUEUE: A
now: ['B', 'C', 'D']

```

WORKED EXAMPLE

Worked example: three retrievals compared for "get 20 / get 87 / get A".

Structure	Target	Path	Can you jump?
Array [10, 50, 20, ...]	20 at index 2	Array[2] in one step, or scan 10, 50, 20	Yes, if the index is known
Linked list 12→98→23→87→...	87	Must visit 12, 98, 23, then 87	No
Queue A-B-C	A (the only legal retrieval)	DEQUEUE Front	No — never the middle

REMEMBER IT

Array jumps, list walks, queue waits. If the exam asks “why is array retrieval different?”, write **direct access by index** versus **sequential links** versus **Front only**.

COMMON MISTAKE

Mistake: DEQUEUEing C because “C is the interesting letter”, or reading linked-list node 4 as `list[3]` without walking.

Fix: show every hop in the table. Marks are for the path, not only for FOUND.

اردو میں سمجھیں

ایرے میں اگر انڈیکس معلوم ہو تو سیدھی چھلانگ لگتی ہے، جیسے $\text{Array}[2] = 20$ ۔ لنکڈ لسٹ میں HEAD سے ایک ایک نوڈ دیکھنا پڑتا ہے؛ 87 چوتھے نوڈ پر ملا۔ کیوں صرف Front نکلتا ہے، درمیان سے نہیں؛ A, B, C میں DEQUEUE ہمیشہ A ہے۔

CHECK YOURSELF

1. What is $\text{Array}[2]$ in $[10, 50, 20, 70, 90, 30]$?
2. How many nodes are checked before 87 is found in $12 \rightarrow 98 \rightarrow 23 \rightarrow 87 \rightarrow 56$?
3. In queue A, B, C, can you retrieve B without removing A?

Answers: 1. 20. 2. Four (12, 98, 23, 87). 3. No — a queue only DEQUEUEs the Front, so A must leave first.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is $\text{Array}[2]$ in $[10, 50, 20, 70, 90, 30]$?

3 marks. Explain Trace data retrieval in Array, List and Queue with two clear points and one example.

5 marks. Write a 5-mark answer on Trace data retrieval in Array, List and Queue: definition, two points, a labelled diagram or table, and one example.

Answers: 1. 20 3. Tracing data retrieval means following the step-by-step path of how an algorithm finds or accesses data.; Array, linked list and queue are all linear, but the effort to find an item is very different because of how they are organised... 5. Use the recipe in the blue box. Model opening: Tracing data retrieval means following the step-by-step path of how an algorithm finds or accesses data.

BATCH HOMEWORK

Write a 5-mark answer on **Trace data retrieval in Array, List and Queue** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Career Opportunities in Algorithms

ACADEMY SESSION

Session 16 of 16 · 45 minutes (second half) · paired with Trace data retrieval in Array, List and Queue.

45–75 min — this topic. Board working for **Career Opportunities in Algorithms**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: The skills in this chapter — proving correctness, writing clear modules, judging Big O, and choosing data structures — are the daily tools of several computing careers.

Error clinic: Mistake: thinking only “Algorithm Engineer” needs Big O.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Career Opportunities in Algorithms**. Write: The skills in this chapter — proving correctness, writing clear modules, judging Big O, and choosing data structures — are the daily tools of several computing careers.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The skills in this chapter — proving correctness, writing clear modules, judging Big O, and choosing data structures — are the daily tools... (2) Second distinct point (not a repeat of the definition) — + example.

5 marks: 3-mark structure + table: Career / What the person does + the worked example from this topic.

LEARN IT

The skills in this chapter — proving correctness, writing clear modules, judging Big O, and choosing data structures — are the daily tools of several computing careers.

Career	What the person does
Software Engineer	Builds and maintains software that relies on data structures and efficient algorithms to solve logic problems.
Backend Developer	Builds server-side logic where choosing the right structure (array, queue) directly affects web performance.
Algorithm Engineer	Specialises in optimising algorithms for search engines, finance or logistics.
Systems Analyst	Evaluates and improves the efficiency and clarity of existing computer systems in an organisation.
Competitive Programmer	Solves complex algorithmic problems under time limits, a common path into top tech roles.

WORKED EXAMPLE

Worked example: match the task.

1. "Replace an $O(n^2)$ report with an $O(n \log n)$ sort so the payroll finishes overnight." → **Algorithm Engineer** (or a performance-minded Software Engineer).
2. "Put incoming HTTP requests into a FIFO buffer so the first visitor is served first." → **Backend Developer** (queue).
3. "Read a college's old fee software, find the nested-IF bottleneck, and recommend modules." → **Systems Analyst**.

REMEMBER IT

Every career in the table uses the same three tests you learned: **correct, clear, efficient** — plus the right data structure.

COMMON MISTAKE

Mistake: thinking only "Algorithm Engineer" needs Big O.

Fix: a backend developer who puts a nested loop on every page request will take a site down. Efficiency is a shared skill.

اس باب کی مہارتیں سافٹ ویئر انجینئر، بیک اینڈ ڈیولپر، الگورتھم انجینئر، سسٹمز اینالسٹ اور کمپیٹیو پروگرامر کے کام میں روز استعمال ہوتی ہیں: درست منطق، صاف ماڈیول، بگ او اور درست ڈیٹا سٹرکچر۔

CHECK YOURSELF

1. Which career specialises in search-engine or logistics algorithms?
2. Why does a backend developer care about queues and arrays?

Answers: 1. Algorithm Engineer. 2. The choice of structure (array, queue) directly affects web performance.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which career specialises in search-engine or logistics algorithms?

3 marks. Explain Career Opportunities in Algorithms with two clear points and one example.

5 marks. Write a 5-mark answer on Career Opportunities in Algorithms: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Algorithm Engineer 3. The skills in this chapter — proving correctness, writing clear modules, judging Big O, and choosing data structures — are the daily tools... 5. Use the recipe in the blue box. Model opening: The skills in this chapter — proving correctness, writing clear modules, judging Big O, and choosing data structures — are the daily tools of several computing...

BATCH HOMEWORK

Write a 5-mark answer on **Career Opportunities in Algorithms** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Chapter 2 Review

Chapter summary

- **Correctness:** output matches expected results for valid inputs. Test with a trace table (manual dry run) or stepwise reasoning (logic verification).
- A **trace table** is micro-level: line, variables, I/O, conditions. Best for small loops. The soldier heights [1.91, 2.01, 1.87, 1.57, 1.48] print Total = 3.
- **Stepwise reasoning** is macro-level: valid start, all cases, correct conditions, loop stays correct. Sum 1..N starts at 0; N = 0 stays 0; N = 5 becomes 15.
- **Clarity** (read, understand, modify) often beats a tiny speed gain. It has two parts: modularity and readability.
- **Modularity:** SRP (one job), loose coupling, abstraction (call Sort without knowing Bubble vs Selection). Split CalculateSum and FindAverage.
- **Readability:** names (`velocity = distance / time`), self-documentation, simple flow, consistent style.
- **Efficiency** = time + space. Drivers: number of steps (Big O), conditions, repetitions.
- **Big O:** $O(1)$ constant (`arr[0]`), $O(\log n)$ binary search, $O(n)$ linear search, $O(n \log n)$ Merge Sort, $O(n^2)$ nested loops / Bubble Sort. Quadratic fails as n grows.
- **Framework:** Does it scale? What is the bottleneck (deepest loop)? Is the extra complexity worth it? For $n = 50$, simple $O(n)$ can beat fragile $O(\log n)$.
- **Refinements:** meaningful names, modules, indentation, why-comments; shrink Bubble Sort's inner loop; better algorithms; cache constants; pick the right structure.
- **Data structure:** systematic organising of data. Linear (one after another): array, linked list, stack, queue. Non-linear: tree, graph.
- **Array:** contiguous, index from 0, direct access $O(1)$, shifting on mid-insert. **Linked list:** nodes of data+link, HEAD to NULL, sequential access.
- **Stack LIFO:** PUSH/POP at TOP (Undo). **Queue FIFO:** ENQUEUE rear, DEQUEUE front (printer).
- **Tree:** one root, parent-child (college chart). **Graph:** vertices + edges, no strict hierarchy (GPS, friends).
- Five operations: insert, delete, traverse, search, sort. Choose by next/previous, parent/child, FIFO, relationships, or reverse-of-entry.
- **Retrieval:** array can jump to an index; a list walks from HEAD; a queue only removes the Front.

Key terms

Term	Meaning	اردو
Correctness	The algorithm's output matches the expected results for valid inputs.	درستگی
Trace table	A paper dry-run table of steps, variables, I/O and conditions.	ٹریس ٹیبل
Dry run	Executing an algorithm by hand, line by line.	دستی اجرا
Stepwise reasoning	Checking each logic block's state; also called logic verification.	مرحلہ وار استدلال
Clarity	How easy an algorithm is to read, understand and modify.	وضاحت
Modularity	Breaking work into independent functions, classes or modules.	ماڈیولریتی
Single Responsibility Principle	Each module should do one specific task.	واحد ذمہ داری کا اصول
Coupling	How tightly modules depend on each other; loose coupling is the goal.	ماڈیولز کی جڑت
Abstraction	Hiding implementation details so a caller need not know the inner method.	تجربہ
Readability	How easily another person understands the logic without running it.	پڑھائی پن
Efficiency	How well an algorithm uses time (speed) and space (memory).	کارکردگی
Big O notation	A description of how running time or memory grows as n grows.	بگ او نوٹیشن
$O(1)$	Constant time; e.g. accessing <code>arr[0]</code> .	مستقل وقت
$O(\log n)$	Logarithmic time; the problem is halved each step (binary search).	لا جارتھمک وقت
$O(n)$	Linear time; work grows in proportion to n (linear search).	لکیری وقت
$O(n \log n)$	Work about n times log n (Merge Sort).	این لاگ این وقت
$O(n^2)$	Quadratic time; nested loops (Bubble Sort).	مربع وقت
Bottleneck	The slowest, most time-consuming section, often the deepest loop.	رکاوٹ، سب سے سست حصہ

Term	Meaning	اردو
Short-circuiting	Stopping a boolean evaluation as soon as the result is known.	جلدی ختم ہونے والی شرط
Memoization / caching	Computing a fixed value once and reusing it instead of recalculating.	ایک بار حساب، بار بار استعمال
Data structure	A systematic way to organise, store and manage data for efficient use.	ڈیٹا سٹرکچر
Linear structure	A sequence; each middle item has one predecessor and one successor.	لکیری ڈھانچہ
Array	Same-type items in contiguous memory, accessed by index.	ایرے
Linked list	Nodes of data + pointer, starting at HEAD and ending at NULL.	لنکڈ لسٹ
Stack	LIFO structure: PUSH and POP at the TOP.	سٹیک
Queue	FIFO structure: ENQUEUE at Rear, DEQUEUE at Front.	کیو
Tree	Hierarchical non-linear structure with one root and parent-child links.	ٹری
Graph	Nodes (vertices) joined by edges, with no strict hierarchy.	گراف
Traversal	Visiting each item in a structure one by one.	گزرنا، طواف
Direct access	Jumping to an array index without walking earlier items.	براہ راست رسائی

Practice: multiple choice

1. An algorithm is correct when:
 - a. it compiles with no syntax error
 - b. its output matches the expected results for the given input
 - c. it uses Big O notation
 - d. it has no comments
2. A trace table is best described as:
 - a. a paper execution that tracks variables line by line
 - b. a diagram of a tree
 - c. a type of graph edge
 - d. an $O(n^2)$ nested loop
3. Stepwise reasoning mainly checks:
 - a. printer ink levels
 - b. the colour of variable names
 - c. only the last printed line
 - d. the overall state of logic blocks
4. Which method is impractical if a loop runs 1,000 times?
 - a. Abstraction
 - b. A full trace table
 - c. Stepwise reasoning
 - d. Using a function
5. The Single Responsibility Principle says each module should:
 - a. focus on one specific task
 - b. print and save and calculate everything
 - c. avoid meaningful names
 - d. use nested IF only
6. Which assignment is more readable?
 - a. `v = d / t`
 - b. `x1 = a2 / b2`
 - c. `velocity = distance / time`
 - d. `a = b / c`
7. Accessing `arr[0]` is:
 - a. $O(n^2)$
 - b. $O(n \log n)$
 - c. $O(n)$
 - d. $O(1)$
8. Binary search on a sorted list is:
 - a. $O(\log n)$
 - b. $O(n^2)$
 - c. $O(1)$ always for any n
 - d. $O(n)$ because a loop exists
9. Bubble Sort and nested "compare every pair" loops are:
 - a. $O(1)$
 - b. $O(\log n)$
 - c. $O(n)$
 - d. $O(n^2)$
10. If n grows 10 times, a quadratic algorithm's time grows about:
 - a. 2 times
 - b. 10 times
 - c. 100 times
 - d. log 10 times
11. LIFO is the rule of a:
 - a. queue
 - b. graph of cities
 - c. tree root only
 - d. stack
12. ENQUEUE adds an item at the:
 - a. Front of a queue
 - b. TOP of a stack only
 - c. Rear of a queue
 - d. root of a tree
13. A college organogram with a Principal at the top is modelled as a:
 - a. tree
 - b. queue
 - c. stack
 - d. contiguous array of roads
14. GPS maps (cities and roads, many possible routes) need a:
 - a. stack of undo actions
 - b. graph
 - c. strict one-parent tree only
 - d. single array index
15. To retrieve 87 from `HEAD→12→98→23→87→56` you must:
 - a. jump with `Array[87]`
 - b. DEQUEUE the rear
 - c. follow four nodes from HEAD until 87 matches
 - d. POP from the bottom of a stack

Practice: short questions

1. Define correctness of an algorithm. Name the two analysis methods used in this chapter.
2. List the components of a trace table. Why is a dry run useful for debugging?
3. Give four differences between a trace table and stepwise reasoning.
4. What is modularity? Explain SRP, coupling and abstraction in one sentence each.
5. State four ways to evaluate readability, with one example of a bad name and a good name.
6. Define Big O notation. Give one example each of $O(1)$, $O(\log n)$, $O(n)$, $O(n \log n)$ and $O(n^2)$.
7. Write the three questions of the efficiency evaluation framework and answer them for searching 50 unsorted names.
8. List four refinements for clarity and four for efficiency.
9. Define data structure. Distinguish linear from non-linear with examples.
10. Define stack and queue. Include LIFO/FIFO, PUSH/POP, ENQUEUE/DEQUEUE, and one real-life example of each.

Practice: long / problem questions

1. The soldier-eligibility algorithm uses AllHeights = [1.91, 2.01, 1.87, 1.57, 1.48] and counts heights from 1.57 to 1.91 inclusive. (a) Draw a complete trace table. (b) State the printed Total. (c) Explain in stepwise-reasoning style why the boundaries 1.57 and 1.91 are counted. (d) Write equivalent Python and its output.
2. Copy the monoblock average algorithm for A = [1, 2, 3, 4, 5] and rewrite it with CalculateSum and FindAverage. (a) Show that SRP, loose coupling and abstraction are improved. (b) Dry-run both versions to the same average. (c) Give two readability improvements you would still make to the functions.
3. Using the growth table idea, (a) fill n = 8 and n = 32 for $O(1)$, $O(\log_2 n)$, $O(n)$, $O(n \log_2 n)$ and $O(n^2)$. (b) Explain what happens if n becomes 10 times larger for $O(n)$ and for $O(n^2)$. (c) A library has 1,000,000 sorted IDs. Choose linear or binary search using the Scale / Bottleneck / Worth-it framework. (d) Show a 4-by-4 nested loop counts 16 operations in Python.
4. Draw a labelled stack and a labelled queue. Then trace: (a) PUSH Data1, PUSH Data2, PUSH Data3, POP, POP. (b) ENQUEUE 55, 76, 90, D then DEQUEUE. Include Python that matches both traces. (c) Why is Undo a stack and a printer a queue?
5. A college needs structures for: (i) 200 integer marks, (ii) a playlist with frequent insertions, (iii) Undo in the fee-office editor, (iv) photocopier jobs, (v) the Principal-Dean-HOD chart, (vi) roads between Sindh cities. Identify each structure using the decision guide, draw the tree and the graph, and then trace retrieval of 20 from Array = [10, 50, 20, 70, 90, 30] and of 87 from the linked list 12 → 98 → 23 → 87 → 56 → NULL.

Answer key

Multiple choice

1. b
2. a
3. d
4. b
5. a
6. c
7. d
8. a
9. d
10. c
11. d
12. c
13. a
14. b
15. c

Short questions — model answers

1. An algorithm is correct if its output matches the expected results for a given input (and does so for all valid inputs). The two methods are trace tables and stepwise reasoning (logic verification).
2. Components: line/step number, a column per variable, input/output, and a condition-check column. A dry run acts as the computer, so you see logical errors where the program runs but the values go wrong, and you can validate that the intention is met.
3. Trace table: small blocks/complex loops/beginners; high effort (bad for 1,000 iterations); catches arithmetic/line mistakes; micro-level exact values. Stepwise reasoning: large systems and proofs; moderate effort; catches conceptual/structural flaws; macro-level overall state.
4. Modularity is breaking an algorithm into smaller independent parts (functions, classes, modules). SRP: each module does one task. Coupling: modules should be loosely coupled so a change in one does not break others. Abstraction: hide inner details (call Sort without knowing Bubble vs Selection).
5. Naming conventions, self-documentation, simple control flow, consistency of indentation/spacing/casing. Bad: $v = d / t$. Good: `velocity = distance / time`.
6. Big O describes how time or memory grows as n grows. $O(1)$: `arr[0]`; $O(\log n)$: binary search; $O(n)$: linear search; $O(n \log n)$: Merge Sort; $O(n^2)$: Bubble Sort / nested loops.
7. Does it scale? $n = 50$ is tiny, even $O(n)$ is fine. Bottleneck? A single scan of 50 names. Worth it? Binary search needs sorted data and more complex code, so linear search is practically better.
8. Clarity: meaningful names; modules; structure/indentation; short why-comments. Efficiency: reduce extra steps (shrink Bubble Sort's inner loop); better algorithms (binary vs linear on sorted millions); avoid re-computing (cache $C = A+B$ outside the loop); appropriate data structures (array for direct access, tree for hierarchy).
9. A data structure is a systematic way of organising, storing and managing data for efficient access, modification and processing. Linear: sequence with one predecessor and one successor (array, linked list, stack, queue). Non-linear: hierarchical or network links (tree, graph).
10. Stack: LIFO; PUSH adds at TOP; POP removes from TOP; example Undo. Queue: FIFO; ENQUEUE adds at Rear; DEQUEUE removes from Front; example printer jobs.

Long questions — model answers

1. (a) Columns: Step, Total, Height, AllHeights, condition, output. Step 2 sets Total = 0. Step 3 stores the five heights. Then five loop cycles:

- 1.91 → True → Total 1
- 2.01 → False → Total stays 1
- 1.87 → True → Total 2
- 1.57 → True (boundary) → Total 3
- 1.48 → False → Total stays 3

(b) Printed Total = **3**.

(c) The condition is height ≥ 1.57 AND height ≤ 1.91 , so the closed interval includes both ends. 1.57 and 1.91 satisfy the inequalities; 2.01 and 1.48 do not. Initial Total = 0 is valid; each True branch adds one; False skips the add; after five items Total is the count of eligible soldiers.

(d) Python:

```
AllHeights = [1.91, 2.01, 1.87, 1.57, 1.48]
Total = 0
for height in AllHeights:
    if height >= 1.57 and height <= 1.91:
        Total = Total + 1
print(Total)
```

OUTPUT
3

2. (a) Monoblock: one sequence does the loop, the division and the print, so you cannot reuse the sum. Modular version: CalculateSum only adds; FindAverage only divides; main only prints. SRP holds. CalculateSum can be called from another program (loose coupling). Main does not see the loop (abstraction).

(b) Both compute total = 15 and avg = $15/5 = 3.0$.

```
def calculate_sum(A, n):
    total = 0
    for i in range(n):
        total = total + A[i]
    return total

def find_average(A, n):
    return calculate_sum(A, n) / n

print(find_average([1, 2, 3, 4, 5], 5))
```

OUTPUT
3.0

(c) Keep snake_case names; avoid 1-based I in Python; a one-line comment on why you divide by n (empty-list guard could be added later) is enough — do not comment every addition.

3. (a) Growth ($\log_2$):

n	$O(1)$	$O(\log n)$	$O(n)$	$O(n \log n)$	$O(n^2)$
8	1	3	8	24	64
32	1	5	32	160	1,024

(b) $O(n)$: $10\times$ input $\rightarrow$ about $10\times$ time. $O(n^2)$: $10\times$ input $\rightarrow$ about $100\times$ time, which fails for large sets.

(c) Scale: a million IDs; linear worst case is a million checks, binary about 20. Bottleneck: the search. Worth it: the IDs are already sorted and binary search is standard, so choose **binary search $O(\log n)$** .

(d)

```
n = 4
count = 0
for i in range(n):
    for j in range(n):
        count = count + 1
print(count)
```

OUTPUT
16

4. Draw the vertical stack with TOP on Data3 after three PUSHes, and the horizontal queue with FRONT on 55 and REAR on 90 (then D).

(a) Stack: $[] \rightarrow [Data1] \rightarrow [Data1, Data2] \rightarrow [Data1, Data2, Data3] \rightarrow \text{POP Data3} \rightarrow \text{POP Data2} \rightarrow [Data1]$.

```
stack = []
stack.append("Data1")
stack.append("Data2")
stack.append("Data3")
print(stack.pop())
print(stack.pop())
print(stack)
```

OUTPUT
Data3
Data2
['Data1']

(b) Queue: $[55] \rightarrow [55, 76] \rightarrow [55, 76, 90] \rightarrow [55, 76, 90, D] \rightarrow \text{DEQUEUE 55} \rightarrow [76, 90, D]$.

```
from collections import deque
q = deque()
q.append(55)
q.append(76)
q.append(90)
q.append("D")
print(q.popleft())
print(list(q))
```

OUTPUT
55
[76, 90, 'D']

(c) Undo must cancel the most recent action (LIFO $\rightarrow$ stack). A printer must respect arrival order (FIFO $\rightarrow$ queue).

5. (i) Array — known count, same type, index lookup. (ii) Linked list — next-pointer, cheap insert. (iii) Stack — reverse order of entry. (iv) Queue — first-come, first-served. (v) Tree — parent-child from the Principal root (Administrative Head / Academic Dean, then Accounts, HR, HOD Math, HOD CS). (vi) Graph — cities as vertices, roads as edges, alternative routes.

Array retrieval: $\text{Array}[2] = 20$ in one direct access (or after visiting 10 then 50 then 20 if you scan).

List retrieval: Step1 12 $\neq$ 87, Step2 98 $\neq$ 87, Step3 23 $\neq$ 87, Step4 87 = 87 FOUND True.

Self-assessment: I can...

- ☐ prove correctness with a full trace table, including boundary values.
- ☐ judge modularity (SRP, coupling, abstraction) and readability (N-S-S-C).
- ☐ apply the Scale / Bottleneck / Worth-it framework, including the $n = 50$ warning.
- ☐ define a data structure and classify linear vs non-linear.
- ☐ draw a tree and a graph and pick a structure from a scenario using the decision guide.
- ☐ write stepwise reasoning (start, loop, finish, edges) and compare it with a trace table.
- ☐ state $O(1)$, $O(\log n)$, $O(n)$, $O(n \log n)$ and $O(n^2)$ with examples and a growth table.
- ☐ refine an algorithm for names, modules, fewer loop steps and cached values.
- ☐ draw and trace an array, linked list, stack (PUSH/POP) and queue (ENQUEUE/DEQUEUE).
- ☐ trace retrieval: array jump, list walk from HEAD, queue Front only.

CHAPTER 3

Programming Fundamentals

This chapter teaches you how Python stores collections of data, how you write reusable functions, and how you save information in files so it is still there after the program ends. You will build small programs — attendance, a word counter, a calculator, and a grade tracker — that you can type and run yourself.

اس باب میں آپ سیکھیں گے کہ پائتھن (Python) ڈیٹا کو فہرست، ٹیپل، سیٹ اور ڈکشنری میں کیسے رکھتا ہے، فنکشن کیسے لکھے جاتے ہیں، اور فائلوں میں ڈیٹا کیسے محفوظ کیا جاتا ہے تاکہ پروگرام بند ہونے کے بعد بھی وہ موجود رہے۔

What you will learn

- Distinguish primitive types from abstract data structures (list, tuple, set, dictionary).
- Use tuples as ordered, immutable collections, including indexing and the two tuple methods.
- Store and retrieve key-value data with dictionaries, including safe access with `.get()`.
- Write user-defined functions with parameters and `return` values, and contrast them with built-in functions.
- Open text files in modes `r`, `w` and `a`, and close them safely with `with`.
- Create, index, slice, traverse and update lists using the main list methods.
- Build sets of unique items and compute union, intersection, difference and symmetric difference.
- Apply `min()`, `max()`, `len()`, `sum()` and `sorted()` across data structures.
- Explain local and global variable scope with short programs.
- Catch file errors with `try/except` and complete a grade-tracker file project.

ACADEMY CALENDAR

Academy calendar: 18 topics · 6 Golden · **14 classes of 90 minutes** + one 40-minute weekly test after this chapter.

Class	Topics	Kind	Board focus
Class 01	Data Structures in Python	Single · 90 min	A data structure is a way of organising values in a program so you can store them, find...

Class	Topics	Kind	Board focus
Class 02	Lists (Ordered, Mutable, Methods)	★ Golden · 90 min	A list is Python's most versatile built-in data structure.
Class 03	Tuples (Ordered, Immutable)	★ Golden · 90 min	A tuple is an ordered collection that is immutable — once created, you cannot add, remove...
Class 04	Sets (Unordered, Unique, Math Operations)	Single · 90 min	A set stores an unordered, unindexed collection of unique elements.
Class 05	Dictionaries (Key-Value Pairs)	★ Golden · 90 min	A dictionary stores data as key-value pairs.
Class 06	Common Built-in Functions (min, max, len, sum) + Activity: Student Attendance System	Paired · 90 min	Several built-in functions work across lists, tuples, sets and dictionaries.
Class 07	Activity: Word Frequency Counter	Single · 90 min	Count how many times each word appears in a sentence.
Class 08	Functions in Python	★ Golden · 90 min	When the same instructions are written again and again, that is duplicate code.
Class 09	Types of Functions (Built-in vs User-defined) + Functions with Return Values	Paired · 90 min	There are two main types of functions in Python.
Class 10	Activity: Arithmetic Calculator Using Functions + Scope of Local and Global Variables	Paired · 90 min	Each arithmetic operation is a separate function.
Class 11	& 3.4 File Handling and Operations (Modes r, w, a)	★ Golden · 90 min	File handling is a program's ability to create, read, write, update and delete files on...
Class 12	The with Statement (Context Manager)	★ Golden · 90 min	It is easy to forget .close().
Class 13	Errors and Exceptions (Try-Except) + Mini File Handling Project: Grade Tracker	Paired · 90 min	An exception is an error raised while the program is running — for example opening a file...

Class	Topics	Kind	Board focus
Class 14	Career Opportunities	Single · 90 min	The skills in this chapter — data structures, functions and files — are the same skills...

Weekly test: 15 MCQ from this chapter + two 5-mark Golden questions. Mark to the recipes. Re-teach any Golden below 60% in the next starter.

گولڈن موضوع پوری کلاس لیتا ہے۔ ہفتہ وار ٹیسٹ کے بعد کمزور گولڈن دوبارہ پڑھائیں۔

3.1 Data Structures in Python

ACADEMY SESSION

Session 1 of 14 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A data structure is a way of organising values in a program so you can store them, find them and change them.

Error clinic: Do not call a list a “variable type” and stop there.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Data Structures in Python**. Write: A data structure is a way of organising values in a program so you can store them, find them and change them.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Primitive data structures — the basic types that hold one value. Examples: integers (int), floating-point numbers (float), and booleans... (2) Abstract data structures — higher-level containers built from primitive types so you can hold many values and run richer operations.... — + example.

5 marks: 3-mark structure + table: Category / Description / Examples + the worked example from this topic.

LEARN IT

A **data structure** is a way of organising values in a program so you can store them, find them and change them. Every useful program is built on data structures. Python gives you two layers:

- **Primitive data structures** — the basic types that hold **one** value. Examples: integers (`int`), floating-point numbers (`float`), and booleans (`bool`).
- **Abstract data structures** — higher-level containers built from primitive types so you can hold **many** values and run richer operations. Examples: **lists, tuples, sets, dictionaries**.

Python has these four abstract structures built in. You do not install anything extra. That is why collecting marks, names or settings is simpler in Python than in many other languages.

Category	Description	Examples
Primitive	Basic types that represent a single value.	<code>int</code> , <code>float</code> , <code>bool</code>
Abstract	Higher-level structures for collections and complex operations.	Lists, tuples, sets, dictionaries

WORKED EXAMPLE

One value versus a collection. A student's age is one integer. That student's three test marks need a list.

```
age = 17
height = 5.8
passed = True
marks = [80, 75, 90]
print(type(age))
print(type(height))
print(type(passed))
print(type(marks))
```

OUTPUT

```
<class 'int'>
<class 'float'>
<class 'bool'>
<class 'list'>
```

`type()` tells you which structure a value has. `age` is a primitive integer. `marks` is an abstract list that holds three integers together.

REMEMBER IT

Primitive = one piece. Abstract = a box of pieces. Think of a single rupee coin (primitive) versus a wallet that can hold many coins (list, tuple, set or dictionary).

COMMON MISTAKE

Do not call a list a “variable type” and stop there. A list is a **structure**: it has an order, methods, and rules. The four abstract structures look similar at first (they all hold several values) but they follow different rules. Learn those rules one by one in 3.1.1–3.1.4.

اردو میں سمجھیں

ڈیٹا سٹرکچر (Data Structure) پروگرام میں ڈیٹا کو ترتیب دینے کا طریقہ ہے۔ پرائمیٹو اقسام جیسے عدد (int) صرف ایک قیمت رکھتی ہیں، جبکہ فہرست، ٹیبل، سیٹ اور ڈکشنری کئی قیمتیں ایک ساتھ سنبھالتی ہیں۔ پائنتھن میں یہ چاروں سٹرکچرز پہلے سے موجود ہیں، اس لیے ڈیٹا جمع کرنا دوسری زبانوں کے مقابلے میں آسان ہے۔

CHECK YOURSELF

1. Name two primitive types and two abstract data structures in Python.
2. Why is a list called an abstract data structure rather than a primitive type?

Answers: 1. Primitive: any two of int, float, bool. Abstract: any two of list, tuple, set, dictionary. 2. Because it is a higher-level container built from primitive values, holding many items and supporting operations such as append and slice.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name two primitive types and two abstract data structures in Python.

3 marks. Explain Data Structures in Python with two clear points and one example.

5 marks. Write a 5-mark answer on Data Structures in Python: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Primitive: any two of int, float, bool. Abstract: any two of list, tuple, set, dictionary 3. Primitive data structures — the basic types that hold one value. Examples: integers (int), floating-point numbers (float), and booleans...; Abstract data structures — higher-level containers built from primitive types so you can hold many... 5. Use the recipe in the blue box. Model opening: A data structure is a way of organising values in a program so you can store them, find them and change them.

BATCH HOMEWORK

Write a 5-mark answer on **Data Structures in Python** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.1.1 Lists (Ordered, Mutable, Methods) ★ Golden

ACADEMY SESSION

Session 2 of 14 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A list is Python's most versatile built-in data structure.

Error clinic: Mistake 1: `.remove('apple')` deletes every apple.

Exam wording to train: Lists appear every year: "What is a list?", "List four methods with one line each", "Differentiate list and tuple", "Write a program to search an element",...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Lists (Ordered, Mutable, Methods)**. Write: A list is Python's most versatile built-in data structure.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It stores an ordered collection of items in a single variable. (2) Lists are mutable (you can change them after you create them) and they are written with square brackets `[]`. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **list** is Python's most versatile built-in data structure. It stores an **ordered** collection of items in a single variable. Lists are **mutable** (you can change them after you create them) and they are written with **square brackets** `[]`.

Why use a list? One variable can hold thousands of values. You can mix types if you need to. You can add, remove and sort items as the program runs.


```
numbers = [10, 2, 15, 14, 3, 33]      # list of integers
names = ["Hassan", "Qasim", "Malika"] # list of strings
mixed = [1, "Python", 3.14, True]    # mixed data types
print(numbers)
print(names)
print(mixed)
```

OUTPUT

```
[10, 2, 15, 14, 3, 33]
['Hassan', 'Qasim', 'Malika']
[1, 'Python', 3.14, True]
```

List indexing (positive and negative)

Each item sits in a numbered slot called an **index**. Numbering starts at **0** from the left. Python also supports **negative indexing** from the right: **-1** is the last item, **-2** is the second last, and so on.



Positive indices count left to right from 0. Negative indices count right to left from -1.

```
fruits = ["apple", "mango", "banana", "grape", "kiwi"]
print(fruits[0])    # first item
print(fruits[4])    # last item (when you know the length)
print(fruits[-1])   # last item (works even if the list grows)
print(fruits[-5])   # first item, counted from the right
```

OUTPUT

```
apple
kiwi
kiwi
apple
```

REMEMBER IT

Always remember [-1]. If a list has 10,000 items and you do not want to compute `len(list) - 1`, write `list[-1]`. It grabs the last item in one step.

Slicing a list

Slicing copies a portion of a list into a **new** list. The original is not changed.

Syntax: `list[start:stop:step]`

- **start** — first index to include (default 0).
- **stop** — first index to **exclude**. The slice goes up to, but does **not** include, this index.
- **step** — jump size (default 1). A step of **-1** walks backwards.

```
nums = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
print(nums[2:6])
print(nums[:4])
print(nums[6:])
print(nums[:2])
print(nums[::-1])
```

OUTPUT

```
[2, 3, 4, 5]
[0, 1, 2, 3]
[6, 7, 8, 9]
[0, 2, 4, 6, 8]
[9, 8, 7, 6, 5, 4, 3, 2, 1, 0]
```

Trace of `nums[2:6]`: start at index 2 (value 2), take 3, 4, 5, and stop **before** index 6. Result `[2, 3, 4, 5]`. `nums[::-1]` is the standard way to reverse a list without changing the original (it returns a new reversed list).

Traversal

Traversal means visiting each element, one by one, in order. Use a `for` loop (the usual Python style) or a `while` loop with an index.

```
numsList = [10, 20, 30]
for num in numsList:
    print(num)
```

OUTPUT

```
10
20
30
```

```
numsList = [10, 20, 30]
index = 0
while index < len(numsList):
    print(numsList[index])
    index += 1
```

OUTPUT

```
10
20
30
```

The `for` loop gives you each value directly. The `while` loop needs a counter, a test `index < len(numsList)`, and `index += 1` so the loop ends.

Built-in list methods

Because a list is mutable, Python gives you methods that change it in place. `len()` is listed with them in many notes, but it is a **built-in function**: you write `len(fruits)`, not `fruits.len()`.

Operation	What it does
<code>len(list)</code>	Returns the number of items.
<code>.append(value)</code>	Adds an item at the end .
<code>.insert(index, value)</code>	Inserts an item at a chosen position (later items shift right).
<code>.remove(value)</code>	Removes the first matching value. Raises <code>ValueError</code> if it is missing.
<code>.clear()</code>	Removes every item. The list becomes <code>[]</code> .
<code>.count(value)</code>	How many times a value appears.
<code>.index(value)</code>	Index of the first occurrence.
<code>.sort()</code>	Sorts the list in place, ascending. Use <code>reverse=True</code> for descending.
<code>.reverse()</code>	Reverses the list in place (does not sort).

WORKED EXAMPLE

Worked example: methods change the same list step by step.

```
fruits = ['apple', 'banana', 'apple']
print(fruits)
fruits.append('grape')
print(fruits)
fruits.remove('apple')
print(fruits)
fruits.sort()
print(fruits)
```

OUTPUT

```
['apple', 'banana', 'apple']
['apple', 'banana', 'apple', 'grape']
['banana', 'apple', 'grape']
['apple', 'banana', 'grape']
```

After this line	List in memory
create	['apple', 'banana', 'apple']
.append('grape')	['apple', 'banana', 'apple', 'grape']
.remove('apple')	['banana', 'apple', 'grape'] — only the first apple goes
.sort()	['apple', 'banana', 'grape']

More methods on numbers:

```
nums = [10, 20, 30]
print(len(nums))
nums.insert(1, 15)
print(nums)
print(nums.count(20))
print(nums.index(30))
nums.reverse()
print(nums)
nums.clear()
print(nums)
```

OUTPUT

```
3
[10, 15, 20, 30]
1
3
[30, 20, 15, 10]
[]
```

`insert(1, 15)` places 15 at index 1, so 20 and 30 shift right. After that, 30 sits at index 3. `reverse()` flips the current order; it does not sort. `clear()` leaves an empty list `[]`, not the value `None`.

You can also replace an item by index, because lists are mutable:

```
numbers = [10, 2, 15]
numbers[0] = 99
print(numbers)
```

OUTPUT

```
[99, 2, 15]
```

Advantages of lists

- **Mutable** — add, remove or replace items as the program runs.
- **Organised** — thousands of values live in one variable instead of `n1`, `n2`, `n3`...
- **Flexible** — integers, strings, booleans and even other lists can sit in the same list.

Activity: searching an element in a list

This program combines a list, user input, a `for` loop, an `if` test and a **flag** (a Boolean that remembers whether the search succeeded).

```
numbers = [5, 10, 15, 20, 25]
search = int(input("Enter number to search: "))
found = False
for num in numbers:
    if num == search:
        found = True
        break
if found:
    print("Number found in the list.")
else:
    print("Number NOT found in the list.")
```

Execution 1 — the user types 15, which is at index 2. The loop sets `found = True` and `break` stops the scan at once.

OUTPUT

```
Enter number to search: 15
Number found in the list.
```

Execution 2 — the user types 99. The loop finishes without a match, so the flag stays `False`.

OUTPUT

```
Enter number to search: 99
Number NOT found in the list.
```

Why `break`? If the value is found at index 1 in a list of 10,000 items, there is no need to check the remaining 9,998. `break` makes linear search cheaper as soon as it succeeds.

REMEMBER IT

LIST — Lots of items, Indexed from 0, Square brackets, Tweakable (mutable). Slice memory trick: "start is in, stop is out."

COMMON MISTAKE

Mistake 1: `.remove('apple')` deletes every apple. **Fix:** it deletes only the first match. Call it again if you need the next one, or use a loop.

Mistake 2: `.sort()` and `sorted()` are the same. **Fix:** `.sort()` is a list method that changes the original and returns `None`. `sorted()` is a function that works on many structures and returns a **new** list (see 3.1.5).

Mistake 3: `fruits[5]` on a five-item list. Valid positive indices are 0 to 4. Use `[-1]` for the last item.

اردو میں سمجھیں

فہرست (List) مربع بریکٹ [] میں لکھی جاتی ہے، ترتیب برقرار رکھتی ہے اور تبدیل کی جا سکتی ہے (Mutable)۔ انڈیکس صفر سے شروع ہوتا ہے، اور [1-] آخری عنصر دیتا ہے۔ `.append()` آخر میں جوڑتا ہے، `.remove()` پہلی مشابہ قیمت ہٹاتا ہے، اور `.sort()` اصل فہرست کو ترتیب دیتا ہے۔ تلاش کرتے وقت `break` مل جانے کے بعد لوپ روک دیتا ہے۔

EXAM TIP

Lists appear every year: "What is a list?", "List four methods with one line each", "Differentiate list and tuple", "Write a program to search an element", "Predict the output of a slice." Write: ordered, mutable, [], index from 0, [-1] for last. For a slice, always say the stop index is excluded. For .remove(), say "first occurrence only." Keep a short program ready that uses append, remove and sort with the printed list after each line.

CHECK YOURSELF

1. What does `nums[2:6]` return if `nums = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]`?
2. After `fruits = ['apple', 'banana', 'apple']` then `fruits.remove('apple')`, what is `fruits`?
3. Why does the search program use `break`?

Answers: 1. [2, 3, 4, 5] 2. ['banana', 'apple'] (only the first apple is removed). 3. To stop scanning once the value is found, so the rest of a long list is not checked.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does `nums[2:6]` return if `nums = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]`?

3 marks. Explain Lists (Ordered, Mutable, Methods) with two clear points and one example.

5 marks. Lists appear every year: "What is a list?", "List four methods with one line each", "Differentiate list and tuple", "Write a program to search an element", "Predict the output of a slice." Write:...

8 marks. Lists (Ordered, Mutable, Methods): 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. [2, 3, 4, 5] 3. It stores an ordered collection of items in a single variable.; Lists are mutable (you can change them after you create them) and they are written with square brackets []. 5. Use the recipe in the blue box. Model opening: A list is Python's most versatile built-in data structure. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Lists (Ordered, Mutable, Methods)** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.1.2 Tuples (Ordered, Immutable) ★ Golden

ACADEMY SESSION

Session 3 of 14 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A tuple is an ordered collection that is immutable — once created, you cannot add, remove or replace items.

Error clinic: One-item trap: (5) is just the integer 5 with extra parentheses.

Exam wording to train: Expect "Differentiate list and tuple" (at least four points: brackets, mutability, methods, speed/protection), "Why use a tuple?", and "What happens if you..."

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Tuples (Ordered, Immutable)**. Write: A tuple is an ordered collection that is immutable — once created, you cannot add, remove or replace items.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Think of it as a read-only list. (2) Tuples use parentheses (). — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **tuple** is an ordered collection that is **immutable** — once created, you cannot add, remove or replace items. Think of it as a **read-only list**. Tuples use **parentheses ()**. Like lists, they allow duplicates, mixed types, and indexing from 0 (including negative indices).

List []

Can add / remove / replace

Tuple ()

LOCKED — read-only

A list is an open box you can refill. A tuple is a sealed box you may only look into.

```
t = (10, 20, 30, 40, 50)
print(t[0])
print(t[-1])
print(t[1:4])
print(t[::-1])
```

OUTPUT

```
10
50
(20, 30, 40)
(50, 40, 30, 20, 10)
```

Slicing a tuple returns a **new tuple**, not a list. Negative indexing and `[::-1]` work exactly as they do for lists.

Immutability

You cannot assign to an index of a tuple. Python raises `TypeError`.

```
t = (1, 2, 3)
t[0] = 99
```

OUTPUT

```
Traceback (most recent call last):
  File "tuple.py", line 2, in <module>
    t[0] = 99
TypeError: 'tuple' object does not support item assignment
```

Exception: if a tuple contains a **mutable object** (a list inside the tuple), that inner object's contents can still change. The tuple still holds the same two list objects; you changed a list, not the tuple's structure.

```
t = ([1, 2], [3, 4])
t[0].append(99)
print(t)
```

```
OUTPUT
([1, 2, 99], [3, 4])
```

`t[0] = [9, 9]` would still be illegal, because that would replace the tuple's first item. `t[0].append(99)` is legal because it mutates the list that already lives at index 0.

Traversal and methods

Traverse a tuple with `for`, just as you do a list. You are only reading, which is the usual reason to choose a tuple.

```
student = ("Ali", 20, "Computer Science")
for item in student:
    print(item)
```

```
OUTPUT
Ali
20
Computer Science
```

Because a tuple cannot grow or shrink, it has only **two** methods:

Method	Meaning
<code>.count(value)</code>	How many times the value appears.
<code>.index(value)</code>	Index of the first occurrence.

```
t = (10, 20, 10, 30, 10)
print(t.count(10))
print(t.index(20))
```

```
OUTPUT
3
1
```

Advantages of tuples

- **Protection** — coordinates, identity-card numbers or settings cannot be changed by accident.
- **Speed** — a fixed-size tuple is processed slightly faster than a list.
- **Hashable keys** — a tuple of immutables can be used as a dictionary key; a list cannot. (You will use dictionaries in 3.1.4.)

WORKED EXAMPLE

When to choose a tuple. A student's roll number, name and class form a record that should not be edited in place:

```
record = ("XII-CS-07", "Ayesha", "Computer Science")
print(record[0])
print(len(record))
```

```
OUTPUT
XII-CS-07
3
```

If later you need to change the class, you build a **new** tuple. You do not assign to `record[2]`.

REMEMBER IT

Tuple = locked lunchbox. You can see what is inside; you cannot swap the sandwich. Memory: “Tuple is Tight (immutable), written with round brackets that look like a hug holding the data still.”

COMMON MISTAKE

One-item trap: (5) is just the integer 5 with extra parentheses. A one-item tuple needs a trailing comma: (5,).

```
t1 = (5)
t2 = (5,)
print(type(t1), t1)
print(type(t2), t2)
```

OUTPUT

```
<class 'int'> 5
<class 'tuple'> (5,)
```

An empty tuple is ().

اردو میں سمجھیں

ٹیپل (Tuple) گول بریکٹ () میں لکھا جاتا ہے، ترتیب رکھتا ہے مگر تبدیل نہیں ہو سکتا (Immutable)۔ انڈیکس اور سلائس فہرست جیسی ہیں، لیکن `t[0] = 99` سے `TypeError` آتا ہے۔ صرف دو میتھڈز ہیں: `count()` اور `index()`۔ حساس ڈیٹا کے لیے ٹیپل محفوظ ہے۔ اگر ٹیپل کے اندر فہرست ہو تو اس فہرست کے اندر کی اشیاء بدل سکتی ہیں۔

EXAM TIP

Expect “Differentiate list and tuple” (at least four points: brackets, mutability, methods, speed/protection), “Why use a tuple?”, and “What happens if you write `t[0] = 1`?” Quote the `TypeError` wording. Mention the inner-list exception if the question is a 6-mark “explain with example.” A one-item tuple (5,) is a favourite trick question.

CHECK YOURSELF

1. Name the two tuple methods.
2. What error does `t[0] = 99` raise for a tuple?
3. After `t = ([1, 2], [3, 4]); t[0].append(99)`, what is `t`?

Answers: 1. `count` and `index`. 2. `TypeError: 'tuple' object does not support item assignment`. 3. `([1, 2, 99], [3, 4])`.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name the two tuple methods.

3 marks. Explain Tuples (Ordered, Immutable) with two clear points and one example.

5 marks. Expect “Differentiate list and tuple” (at least four points: brackets, mutability, methods, speed/protection), “Why use a tuple?”, and “What happens if you write `t[0] = 1`?” Quote the `TypeError`...

8 marks. Tuples (Ordered, Immutable): 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. `count` and `index`. 3. Think of it as a read-only list.; Tuples use parentheses (). 5. Use the recipe in the blue box. Model opening: A tuple is an ordered collection that is immutable — once created, you cannot add, remove or replace items. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Tuples (Ordered, Immutable)** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.1.3 Sets (Unordered, Unique, Math Operations)

ACADEMY SESSION

Session 4 of 14 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A set stores an unordered, unindexed collection of unique elements.

Error clinic: `myset[0]` raises `TypeError` because sets are unindexed.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Sets (Unordered, Unique, Math Operations)**. Write: A set stores an unordered, unindexed collection of unique elements.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It is inspired by mathematical sets. (2) You write a set with curly braces `{}`. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT

A **set** stores an **unordered, unindexed** collection of **unique** elements. It is inspired by mathematical sets. You write a set with **curly braces** `{}`. Duplicates are removed as soon as the set is created. Because there is no index, `myset[0]` is illegal.

The set itself is **mutable** (you can add and remove items). Each item inside must be **immutable** (numbers, strings, tuples of immutables — not lists).

```
nums = {1, 4, 3, 3, 2, 2}
print(nums)
```

OUTPUT

```
{1, 2, 3, 4}
```

The two 3s and two 2s collapse to one each. Do not depend on the printed order: a set is unordered. CPython often prints small integers in a tidy way, but that is not a language promise.

Adding and removing

Method	Description
<code>.add(value)</code>	Adds one element.
<code>.update(values)</code>	Adds many elements from a list, tuple or set.
<code>.remove(value)</code>	Removes the value. Raises <code>KeyError</code> if it is missing.
<code>.discard(value)</code>	Removes the value. Does not crash if it is missing.
<code>.clear()</code>	Removes every element. Result is <code>set()</code> .

```
s = {1, 2, 3}
s.add(4)
print(s)
s.update([5, 6])
print(s)
s.discard(99)
print(s)
s.remove(1)
print(s)
s.clear()
print(s)
```

```
OUTPUT
{1, 2, 3, 4}
{1, 2, 3, 4, 5, 6}
{1, 2, 3, 4, 5, 6}
{2, 3, 4, 5, 6}
set()
```

`discard(99)` quietly does nothing. After `clear()` Python prints `set()`, not `{}`, because `{}` already means an empty dictionary.

Compare with `.remove(99)` on a set that does not contain 99:


```
s = {1, 2, 3}
s.remove(99)
```

```
OUTPUT
Traceback (most recent call last):
  File "set_remove.py", line 2, in <module>
    s.remove(99)
  KeyError: 99
```

Prefer `.discard()` when the item might not be there, so a missing value does not crash the program.

Mathematical operations

Sets are built for union, intersection, difference and symmetric difference.



Overlap {3, 4} is the intersection. Left-only {1, 2} is A - B. Right-only {5, 6} is B - A.

Operation	Meaning	Syntax	Result for A, B above
Union	All unique items from both	A B or A.union(B)	{1, 2, 3, 4, 5, 6}
Intersection	Items in both	A & B or A.intersection(B)	{3, 4}
Difference	In A, not in B	A - B or A.difference(B)	{1, 2}
Symmetric difference	In either, but not both	A ^ B or A.symmetric_difference(B)	{1, 2, 5, 6}

```
A = {1, 2, 3, 4}
B = {3, 4, 5, 6}
print(A | B)
print(A & B)
print(A - B)
print(A ^ B)
```

OUTPUT

```
{1, 2, 3, 4, 5, 6}
{3, 4}
{1, 2}
{1, 2, 5, 6}
```

$B - A$ would be $\{5, 6\}$ — difference is not symmetric. Symmetric difference $A \oplus B$ is $(A - B) \cup (B - A)$.

Set traversal

There is no index, so you loop with `for`. Print order is not guaranteed. Use `sorted()` when you need a stable alphabetical or numerical order (it returns a list).

```
colors = {"red", "green", "blue"}
for color in sorted(colors):
    print(color)
```

OUTPUT

```
blue
green
red
```

WORKED EXAMPLE

Deduplication. A teacher types roll numbers and some are repeated. A set keeps each roll once:

```
rolls = [12, 5, 12, 8, 5, 19]
unique = set(rolls)
print(unique)
print(sorted(unique))
```

OUTPUT

```
{8, 19, 12, 5}
[5, 8, 12, 19]
```

`set(rolls)` drops duplicates. `sorted(unique)` gives a list in numeric order for a register.

REMEMBER IT

SET = Same-item Eaten Twice-never. Empty set is `set()`, never `{}`. Safe delete = `discard`; angry delete = `remove`.

COMMON MISTAKE

`myset[0]` raises `TypeError` because sets are unindexed. Convert with `list(myset)` only if you accept that the order is arbitrary. Do not put a list inside a set — lists are mutable, so they cannot be set elements.

سیٹ (Set) منفرد عناصر کا بغیر ترتیب اور بغیر انڈیکس مجموعہ ہے، جو $\{ \}$ میں لکھا جاتا ہے۔ دہرائی ہوئی قیمتیں خود بخود ختم ہو جاتی ہیں۔ $\text{add}()$ اور $\text{update}()$ عناصر جوڑتے ہیں، $\text{discard}()$ محفوظ طریقے سے ہٹاتا ہے جبکہ $\text{remove}()$ غیر موجود عنصر پر KeyError دیتا ہے۔ اجتماع (Union) $|$ ، اشتراک (Intersection) $\&$ ، فرق $-$ اور متوازی فرق $\wedge$ ریاضی کی کارروائیاں ہیں۔

CHECK YOURSELF

1. What is printed by `print({1, 4, 3, 3, 2, 2})` ?
2. Why prefer `.discard()` over `.remove()` ?
3. If $A = \{1, 2, 3, 4\}$ and $B = \{3, 4, 5, 6\}$, what is $A \wedge B$?

Answers: 1. $\{1, 2, 3, 4\}$ (duplicates removed; order may vary). 2. `discard` does not raise `KeyError` if the value is missing. 3. $\{1, 2, 5, 6\}$.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is printed by `print({1, 4, 3, 3, 2, 2})`?

3 marks. Explain Sets (Unordered, Unique, Math Operations) with two clear points and one example.

5 marks. Write a 5-mark answer on Sets (Unordered, Unique, Math Operations): definition, two points, a labelled diagram or table, and one example.

Answers: 1. $\{1, 2, 3, 4\}$ (duplicates removed; order may vary) 3. It is inspired by mathematical sets.; You write a set with curly braces $\{ \}$. 5. Use the recipe in the blue box. Model opening: A set stores an unordered, unindexed collection of unique elements.

BATCH HOMEWORK

Write a 5-mark answer on **Sets (Unordered, Unique, Math Operations)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.1.4 Dictionaries (Key-Value Pairs) ★ Golden

ACADEMY SESSION

Session 5 of 14 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A dictionary stores data as key–value pairs.

Error clinic: Older notes (and the chapter summary in some slides) still call dictionaries “unordered.” From Python 3.7 onwards insertion order is preserved, so you may...

Exam wording to train: High-yield: definition of a dictionary, difference between `d[key]` and `d.get(key)`, “what if a key is repeated?”, traversal with `.items()`, and a full comparison...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Dictionaries (Key-Value Pairs)**. Write: A dictionary stores data as key–value pairs.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Mutable: you can add, change and delete pairs. (2) Keys are unique: if you repeat a key, the last value silently overwrites the earlier one. Values may repeat. — + example.


5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **dictionary** stores data as **key–value pairs**. It works like a real dictionary: you look up a word (the **key**) to find its meaning (the **value**). Write a dictionary with curly braces, and put a **colon** between each key and value.

- **Ordered** (Python 3.7+): insertion order is kept.
- **Mutable**: you can add, change and delete pairs.
- **Keys are unique**: if you repeat a key, the last value silently overwrites the earlier one. Values may repeat.



You never search a dictionary by position. You search by key.

A school analogue: a **roll number** (key) can point to only one student (value). If you assign that roll number to someone else, the old link is gone.

Adding, changing and deleting

```
d = {"name": "Alice", "age": 30}
print(d)
d["age"] = 31
print(d)
d["city"] = "NYC"
print(d)
del d["city"]
print(d)
```

OUTPUT

```
{'name': 'Alice', 'age': 30}
{'name': 'Alice', 'age': 31}
{'name': 'Alice', 'age': 31, 'city': 'NYC'}
{'name': 'Alice', 'age': 31}
```

Assigning to an existing key updates the value. Assigning to a new key adds a pair. `del d["city"]` removes that pair.

The duplicate-keys rule. Python does not crash. The last assignment wins.


```
d = {"a": 1, "a": 2, "a": 3}
print(d)
```

OUTPUT

```
{'a': 3}
```

Accessing values safely

1. Direct brackets (risky)

`dict[key]` works if the key exists. If it is missing, the program crashes with `KeyError`.

2. `.get()` (safe)

`dict.get(key)` returns `None` if the key is missing. You may pass a default: `dict.get(key, 0)`.

```
person = {"name": "Alice", "age": 30}
print(person["name"])
print(person.get("salary"))
print(person.get("salary", 0))
print("name" in person)
print("salary" in person)
```

OUTPUT

```
Alice
None
0
True
False
```

The operator `in` tests **keys**, not values. `"Alice" in person` would be `False`.

```
person = {"name": "Alice", "age": 30}
print(person["salary"])
```

OUTPUT

```
Traceback (most recent call last):
  File "keyerror.py", line 2, in <module>
    print(person["salary"])
KeyError: 'salary'
```

Dictionary views and traversal

Three view methods return live objects. If the dictionary changes, the view reflects the change immediately.

Method	Returns
<code>.keys()</code>	All keys.
<code>.values()</code>	All values.
<code>.items()</code>	Key–value pairs as tuples.

```
d = {"a": 1}
keys = d.keys()
print(keys)
d["b"] = 2
print(keys)
```

OUTPUT

```
dict_keys(['a'])
dict_keys(['a', 'b'])
```

The variable `keys` was not rebuilt. The view updated itself.

```
inventory = {"apple": 50, "banana": 30, "cherry": 20}
print(list(inventory.keys()))
print(list(inventory.values()))
print(list(inventory.items()))
for key in inventory:
    print(key)
for val in inventory.values():
    print(val)
for key, val in inventory.items():
    print(f"{key} costs {val}")
```

OUTPUT

```
['apple', 'banana', 'cherry']
[50, 30, 20]
[('apple', 50), ('banana', 30), ('cherry', 20)]
apple
banana
cherry
50
30
20
apple costs 50
banana costs 30
cherry costs 20
```

A plain `for key in inventory` loops over keys (the default). `.items()` is the most useful form because you get both sides at once.

Comparison: list, tuple, set, dictionary

Feature	List	Tuple	Set	Dictionary
Written with	[]	()	{ }	{key: value}
Ordered	Yes	Yes	No	Yes (Python 3.7+)
Mutable	Yes	No	Yes (items must be immutable)	Yes
Duplicates	Allowed	Allowed	Removed	Duplicate keys not allowed (last value wins)
Access by	Index 0, 1, 2...	Index 0, 1, 2...	No index	Key
Empty value	[]	()	set()	{}
Typical use	Changing sequences	Fixed records	Unique items, set maths	Look-up tables

WORKED EXAMPLE

Same data, four structures. Three subject marks:

- List `[80, 70, 90]` — easy to append a fourth test.
- Tuple `(80, 70, 90)` — a frozen result slip.
- Set `{80, 70, 90}` — unique scores only; two papers of 80 would become one 80.
- Dictionary `{"math": 80, "eng": 70, "cs": 90}` — you ask “What is CS?” and get 90 without remembering an index.

REMEMBER IT

Keys are unique, like roll numbers. Values are the student records and may repeat (two students can both score 80). Memory: “**get** is gentle, brackets can **break**.”

COMMON MISTAKE

Older notes (and the chapter summary in some slides) still call dictionaries “unordered.” From Python 3.7 onwards insertion order is preserved, so you may write “ordered since 3.7.” Keys must be immutable: a list cannot be a key; a tuple of numbers can. Do not write `{}` when you want an empty set.

اردو میں سمجھیں

ڈکشنری (Dictionary) کلید اور قدر (Key-Value) کے جوڑوں میں ڈیٹا رکھتی ہے۔ کلید منفرد ہوتی ہے، دہرائی ہوئی کلید پر آخری قدر رہ جاتی ہے۔ `d[key]` غیر موجود کلید پر `KeyError` دیتا ہے، جبکہ `d.get(key, default)` محفوظ ہے۔ `.values()`، `.keys()` اور `.items()` سے گھما جا سکتا ہے۔ فہرست انڈیکس سے، ڈکشنری کلید سے پہچانی جاتی ہے۔

EXAM TIP

High-yield: definition of a dictionary, difference between `d[key]` and `d.get(key)`, “what if a key is repeated?”, traversal with `.items()`, and a full comparison table of the four structures. Memorise the comparison table in this section — it is a complete 8-mark answer if you add one example row. Always mention that `in` checks keys.

CHECK YOURSELF

1. What does `{"a": 1, "a": 2, "a": 3}` print?
2. What does `person.get("salary", 0)` return if `salary` is missing?
3. Which structure has no index and no duplicate items?

Answers: 1. `{'a': 3}`. 2. `0`. 3. A set.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does `{"a": 1, "a": 2, "a": 3}` print?

3 marks. Explain Dictionaries (Key-Value Pairs) with two clear points and one example.

5 marks. High-yield: definition of a dictionary, difference between `d[key]` and `d.get(key)`, “what if a key is repeated?”, traversal with `.items()`, and a full comparison table of the four structures. Memorise...

8 marks. Dictionaries (Key-Value Pairs): 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. `{'a': 3}` 3. Mutable: you can add, change and delete pairs.; Keys are unique: if you repeat a key, the last value silently overwrites the earlier one. Values may repeat. 5. Use the recipe in the blue box. Model opening: A dictionary stores data as key-value pairs. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Dictionaries (Key-Value Pairs)** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.1.5 Common Built-in Functions (min, max, len, sum)

ACADEMY SESSION

Session 6 of 14 · 45 minutes (first half) · paired with Activity: Student Attendance System.

10–45 min — this topic. Lock the definition and table for **Common Built-in Functions (min, max, len, sum)**. Starter (0–10) is from last class. Second half is Activity: Student Attendance System.

On the board: Several built-in functions work across lists, tuples, sets and dictionaries.

Error clinic: `sum()` needs numbers.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Common Built-in Functions (min, max, len, sum)**. Write: Several built-in functions work across lists, tuples, sets and dictionaries.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Several built-in functions work across lists, tuples, sets and dictionaries. (2) You do not call them with a dot on the object (except when a type also has its own method, such as `list.sort()`). — + example.

5 marks: 3-mark structure + table: Function / Purpose / Works on + the worked example from this topic.

LEARN IT

Several built-in functions work across lists, tuples, sets and dictionaries. You do not call them with a dot on the object (except when a type also has its own method, such as `list.sort()`).

Function	Purpose	Works on
<code>min()</code>	Smallest element (numeric or alphabetical)	List, tuple, set, dictionary keys
<code>max()</code>	Largest element	List, tuple, set, dictionary keys
<code>len()</code>	Number of elements (for a dict: number of keys)	List, tuple, set, dictionary
<code>sum()</code>	Adds numeric elements	List, tuple, set, dictionary values via <code>sum(d.values())</code>
<code>sorted()</code>	Returns a new sorted list ; original unchanged	List, tuple, set, dictionary keys

```
s = {5, 1, 9, 3, 7}
print(len(s))
print(min(s))
print(max(s))
print(sum(s))
print(sorted(s))
```

OUTPUT

```
5
1
9
25
[1, 3, 5, 7, 9]
```

$5 + 1 + 9 + 3 + 7 = 25$. `sorted(s)` always returns a **list**, even when the input is a set.

WORKED EXAMPLE

The same five functions on four structures.

```
nums = [8, 3, 5, 3]
t = (8, 3, 5, 3)
s = {8, 3, 5}
d = {"math": 80, "eng": 70, "cs": 90}
print(len(nums), min(nums), max(nums), sum(nums), sorted(nums))
print(len(t), min(t), max(t), sum(t), sorted(t))
print(len(s), min(s), max(s), sum(s), sorted(s))
print(len(d), min(d), max(d), sum(d.values()), sorted(d))
```

OUTPUT

```
4 3 8 19 [3, 3, 5, 8]
4 3 8 19 [3, 3, 5, 8]
3 3 8 16 [3, 5, 8]
3 cs math 240 ['cs', 'eng', 'math']
```

On the dictionary, `min(d)` and `max(d)` compare **keys as strings**: "cs" comes first alphabetically, "math" last. `sum(d)` would try to add the keys "math" + "eng" + ... and fail. Use `sum(d.values())` — $80 + 70 + 90 = 240$. The set dropped the duplicate 3, so `len(s)` is 3 and `sum(s)` is 16.

`sorted()` versus `.sort()`

```
original = [8, 3, 5]
print("before sort:", original)
print("sorted():", sorted(original))
print("after sorted():", original)
original.sort()
print("after .sort():", original)
```

OUTPUT

```
before sort: [8, 3, 5]
sorted(): [3, 5, 8]
after sorted(): [8, 3, 5]
after .sort(): [3, 5, 8]
```

`.sort()` exists only on lists and rewrites the original. `sorted()` works on any iterable and leaves the original alone.

REMEMBER IT

LEN-MIN-MAX-SUM — count, smallest, largest, total. For a dictionary: `len` / `min` / `max` / `sorted` use **keys**; `sum` needs `.values()`.

COMMON MISTAKE

`sum()` needs numbers. `sum(["a", "b"])` raises `TypeError`. Empty structures: `len([])` is 0, but `min([])` and `max([])` raise `ValueError` because there is no smallest of nothing.

اردو میں سمجھیں

`len()` عناصر گنتا ہے، `min()` سب سے چھوٹا، `max()` سب سے بڑا، `sum()` اعداد کا مجموعہ، اور `sorted()` نئی ترتیب شدہ فہرست دیتا ہے بغیر اصل کو بدلے ہیں۔ ڈکشنری پر `min` اور `max` کلیدوں پر چلتے ہیں؛ قدروں کا مجموعہ `sum(d.values())` سے نکالیں۔ `.sort()` صرف فہرست کا میتھڈ ہے جو اصل فہرست بدل دیتا ہے۔

CHECK YOURSELF

1. For `s = {5, 1, 9, 3, 7}`, what are `len(s)`, `min(s)`, `max(s)`, `sum(s)`?
2. Does `sorted(s)` return a set or a list?
3. How do you total the values of `{"math": 80, "eng": 70, "cs": 90}`?

Answers: 1. 5, 1, 9, 25. 2. A list: `[1, 3, 5, 7, 9]`. 3. `sum(d.values())` → 240.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. For `s = {5, 1, 9, 3, 7}`, what are `len(s)`, `min(s)`, `max(s)`, `sum(s)`?

3 marks. Explain Common Built-in Functions (`min`, `max`, `len`, `sum`) with two clear points and one example.

5 marks. Write a 5-mark answer on Common Built-in Functions (`min`, `max`, `len`, `sum`): definition, two points, a labelled diagram or table, and one example.

Answers: 1. 5, 1, 9, 25. 3. Several built-in functions work across lists, tuples, sets and dictionaries.; You do not call them with a dot on the object (except when a type also has its own method, such as `list.sort()`). 5. Use the recipe in the blue box. Model opening: Several built-in functions work across lists, tuples, sets and dictionaries.

BATCH HOMEWORK

Write a 5-mark answer on **Common Built-in Functions (`min`, `max`, `len`, `sum`)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.1.6 Activity: Student Attendance System

ACADEMY SESSION

Session 6 of 14 · 45 minutes (second half) · paired with Common Built-in Functions (`min`, `max`, `len`, `sum`).

45–75 min — this topic. Board working for **Activity: Student Attendance System**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Teachers need a quick way to mark who is in class.

Error clinic: Only the exact string "yes" after `.lower()` counts as present.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Activity: Student Attendance System**. Write: Teachers need a quick way to mark who is in class.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Teachers need a quick way to mark who is in class. (2) This program stores names in a list, asks about each student, counts how many said yes, and prints a summary with `len()`. — + example.

5 marks: 3-mark structure + table: Student / Typed answer / After `.lower()` / `present_count` + the worked example from this topic.

LEARN IT

Teachers need a quick way to mark who is in class. This program stores names in a **list**, asks about each student, counts how many said yes, and prints a summary with `len()`.

Store names in a list → Ask present? for each → Count yes → Print totals

```
students = ["Ali", "Sara", "Ayesha"]
present_count = 0
print("--- Attendance System ---\n")
for student in students:
    status = input(f"Is {student} present? (yes/no): ").lower()
    if status == "yes":
        present_count += 1
print("\n--- Attendance Summary ---")
print("Total Students:", len(students))
print("Students Present:", present_count)
print("Students Absent:", len(students) - present_count)
```

WORKED EXAMPLE

Sample run. Ali yes, Sara no, Ayesha yes. `.lower()` means YES or Yes still counts as present.

OUTPUT

```
--- Attendance System ---

Is Ali present? (yes/no): yes
Is Sara present? (yes/no): no
Is Ayesha present? (yes/no): yes

--- Attendance Summary ---
Total Students: 3
Students Present: 2
Students Absent: 1
```

Student	Typed answer	After <code>.lower()</code>	<code>present_count</code>
Ali	yes	yes → add 1	1
Sara	no	not yes	1
Ayesha	yes	yes → add 1	2

Absent = `len(students) - present_count` = 3 - 2 = 1. The counter must start at 0 **before** the loop. If you put `present_count = 0` inside the loop, the count would reset for every student.

REMEMBER IT

Counter pattern: start at 0, loop, add 1 when a condition is true. You will reuse this in the word-frequency program (add 1 per word) and the grade tracker (add each mark).

COMMON MISTAKE

Only the exact string "yes" after `.lower()` counts as present. "y" or "present" is treated as absent. In a longer program you could also accept "y"; this activity keeps the rule simple.

اردو میں سمجھیں

حاضری کا پروگرام طلبہ کے نام ایک فہرست میں رکھتا ہے، ہر نام کے لیے پوچھتا ہے، اور yes پر شمار کار (Counter) ایک بڑھاتا ہے۔ کل طلبہ `len(students)` سے، غیر حاضر کل - حاضر سے نکلتے ہیں۔ شمار کار لوپ سے پہلے صفر ہونا چاہیے۔

CHECK YOURSELF

1. If all three students type `no`, what is printed for present and absent?
2. Why is `.lower()` used on the answer?

Answers: 1. Present 0, Absent 3. 2. So that YES, Yes and yes all match the string "yes".

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. If all three students type `no`, what is printed for present and absent?

3 marks. Explain Activity: Student Attendance System with two clear points and one example.

5 marks. Write a 5-mark answer on Activity: Student Attendance System: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Present 0, Absent 3. 3. Teachers need a quick way to mark who is in class.; This program stores names in a list, asks about each student, counts how many said yes, and prints a summary with `len()`. 5. Use the recipe in the blue box. Model opening: Teachers need a quick way to mark who is in class.

BATCH HOMEWORK

Write a 5-mark answer on **Activity: Student Attendance System** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.1.7 Activity: Word Frequency Counter

ACADEMY SESSION

Session 7 of 14 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Count how many times each word appears in a sentence.

Error clinic: This program is case-sensitive and space-based.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Activity: Word Frequency Counter**. Write: Count how many times each word appears in a sentence.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Count how many times each word appears in a sentence. (2) This is a classic use of a dictionary plus `.get()`: the word is the key, the count is the value. — + example.

5 marks: 3-mark structure + table: After seeing / word_freq + the worked example from this topic.

LEARN IT

Count how many times each word appears in a sentence. This is a classic use of a **dictionary** plus `.get()`: the word is the key, the count is the value.

```
sentence = "python is easy python is fun python is powerful"
words = sentence.split()
word_freq = {}
for word in words:
    word_freq[word] = word_freq.get(word, 0) + 1
print(f"Sentence: '{sentence}'\n")
print("Word Frequency Table:")
for word, count in word_freq.items():
    print(f"{word:<10} : {count}")
top_word = max(word_freq, key=word_freq.get)
print(f"\nMost Frequent: '{top_word}' ({word_freq[top_word]} times)")
```

WORKED EXAMPLE

Logic, step by step.

1. `sentence.split()` cuts on spaces and gives
['python', 'is', 'easy', 'python', 'is', 'fun', 'python', 'is', 'powerful'].
2. For a new word, `word_freq.get(word, 0)` is 0, then you store $0 + 1 = 1$.
3. For a word already in the dictionary, `.get(word, 0)` returns the current count, then you add 1.
4. `{word:<10}` pads the word to 10 characters so the colons line up.
5. `max(word_freq, key=word_freq.get)` picks the key whose value is largest. If two words share the top count, `max` returns the first of those keys in insertion order.

OUTPUT

Sentence: 'python is easy python is fun python is powerful'

Word Frequency Table:

```
python      : 3
is          : 3
easy        : 1
fun         : 1
powerful    : 1
```

Most Frequent: 'python' (3 times)

After seeing	word_freq
python	{'python': 1}
is	{'python': 1, 'is': 1}
easy	{'python': 1, 'is': 1, 'easy': 1}
python (again)	{'python': 2, 'is': 1, 'easy': 1}
... end of sentence	{'python': 3, 'is': 3, 'easy': 1, 'fun': 1, 'powerful': 1}

Here `python` and `is` both occur 3 times. `max` returns `'python'` because it appears first in the dictionary.

REMEMBER IT

The heart of every counter is one line: `d[item] = d.get(item, 0) + 1`. You can count letters, roll numbers or votes with the same pattern.

COMMON MISTAKE

This program is case-sensitive and space-based. "Python" and "python" would be two keys. Punctuation such as `easy.` would not match `easy`. For a class exercise, keep the sentence lowercase with spaces only, as here. If you wrote `word_freq[word] += 1` without `.get` on a new word, you would get `KeyError`.

اردو میں سمجھیں

جملے کو `.split()` سے الفاظ کی فہرست بناتے ہیں، پھر ہر لفظ ڈکشنری میں کلید ہوتا ہے اور اس کی گنتی قدر- نئے لفظ کے لیے `1 + get(word, 0)` سے گنتی 1 سے شروع ہوتی ہے۔ `max(... , key=word_freq.get)` سب سے زیادہ بار آنے والا لفظ دیتا ہے۔

CHECK YOURSELF

1. How many times does "is" occur in the sample sentence?
2. Why use `.get(word, 0)` instead of `word_freq[word]` on the right-hand side?

Answers: 1. Three times. 2. Because a brand-new word is not yet a key; `.get` returns 0 instead of raising `KeyError`.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. How many times does "is" occur in the sample sentence?

3 marks. Explain Activity: Word Frequency Counter with two clear points and one example.

5 marks. Write a 5-mark answer on Activity: Word Frequency Counter: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Three times 3. Count how many times each word appears in a sentence.; This is a classic use of a dictionary plus `.get()`: the word is the key, the count is the value. 5. Use the recipe in the blue box. Model opening: Count how many times each word appears in a sentence.

BATCH HOMEWORK

Write a 5-mark answer on **Activity: Word Frequency Counter** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.2 Functions in Python ★ Golden

ACADEMY SESSION

Session 8 of 14 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: When the same instructions are written again and again, that is duplicate code.

Error clinic: Defining is not calling.

Exam wording to train: Write the four benefits (reusability, modularity, readability, maintainability) as separate bullets — that is a standard short question.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Functions in Python**. Write: When the same instructions are written again and again, that is duplicate code.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Duplicate code makes a program longer, harder to read, and painful to update (you must fix every copy). (2) A function lets you write the instructions once and run them whenever you call the function's name. — + example.

5 marks: 3-mark structure + table: Benefit / Meaning + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

When the same instructions are written again and again, that is **duplicate code**. Duplicate code makes a program longer, harder to read, and painful to update (you must fix every copy). A **function** lets you write the instructions **once** and run them whenever you call the function's name.

Benefit	Meaning
Code reusability	Write once, use anywhere.
Modularity	Break a big problem into small named tasks.
Readability	Shorter, cleaner files with meaningful names.
Maintainability	Fix a bug in one place and every call is fixed.

```
def greet():  
    print("Hello, World!")  
  
greet()  
greet()
```

OUTPUT

```
Hello, World!  
Hello, World!
```

The body is written once. Two calls run it twice. To change the message you edit one line inside `greet`.

Key components of a function



- **Keyword** — Python uses `def` to start a definition.
- **Function name** — the identifier you call, e.g. `greet`.
- **Parameters** — input names inside the parentheses. When you call the function, the values you pass are called **arguments**.
- **Body** — the indented block that runs on each call.
- **Return statement** — sends a result back to the caller (3.2.2).

```
def add(a, b):  
    print(f"Adding {a} + {b}")  
    return a + b  
  
result = add(4, 6)  
print(result)
```

OUTPUT

```
Adding 4 + 6
10
```

Here `a` and `b` are parameters. `4` and `6` are arguments. `return a + b` sends 10 back, and that 10 is stored in `result`.

WORKED EXAMPLE

Without a function you would copy the print-and-add lines every time you needed a sum. With a function, a new sum is one call: `add(10, 20)`, `add(1.5, 2.5)`.

REMEMBER IT

DRY — Don't Repeat Yourself. If you are about to copy-paste a block, wrap it in `def`. Name functions with verbs: `greet`, `add`, `save_grades`.

COMMON MISTAKE

Defining is not calling. After `def greet():` nothing prints until you write `greet()`. Forgetting the parentheses — writing `greet` alone — does not run the body. The body must be indented; a line at column 0 is outside the function.

اردو میں سمجھیں

فونکشن (Function) ہدایات کا وہ بلاک ہے جو ایک بار لکھا جاتا ہے اور بار بار بلایا جا سکتا ہے۔ اس سے کوڈ مختصر، ماڈیولر اور آسان اصلاح والا بنتا ہے۔
تعریف `def` سے شروع ہوتی ہے، نام اور پیرامیٹرز قوسین میں ہوتے ہیں، جسم انڈینٹ ہوتا ہے، اور `return` نتیجہ واپس بھیج سکتا ہے۔ تعریف کرنے سے فونکشن چلتا نہیں جب تک آپ اسے کال نہ کریں۔

EXAM TIP

Write the four benefits (reusability, modularity, readability, maintainability) as separate bullets — that is a standard short question. For long questions, define a function, label `def`, name, parameters, body and `return`, then show one call. "What is duplicate code and how do functions solve it?" is also common.

CHECK YOURSELF

1. What keyword starts a function definition?
2. How many times does `Hello, World!` print in the `greet` program above, and why?

Answers: 1. `def`. 2. Twice, because `greet()` is called twice.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What keyword starts a function definition?

3 marks. Explain Functions in Python with two clear points and one example.

5 marks. Write the four benefits (reusability, modularity, readability, maintainability) as separate bullets — that is a standard short question. For long questions, define a function, label `def`, name, parameters, body and `return`, then show one call.

8 marks. Functions in Python: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. `def` 3. Duplicate code makes a program longer, harder to read, and painful to update (you must fix every copy).; A function lets you write the instructions once and run them whenever you call the function's name. 5. Use the recipe in the blue box. Model opening: When the same instructions are written again and again, that is duplicate code. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Functions in Python** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.2.1 Types of Functions (Built-in vs User-defined)

ACADEMY SESSION

Session 9 of 14 · 45 minutes (first half) · paired with Functions with Return Values.

10–45 min — this topic. Lock the definition and table for **Types of Functions (Built-in vs User-defined)**. Starter (0–10) is from last class. Second half is Functions with Return Values.

On the board: There are two main types of functions in Python.

Error clinic: Do not name your function list, print, sum or input.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Types of Functions (Built-in vs User-defined)**. Write: There are two main types of functions in Python.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) a) Built-in functions are already defined by Python. (2) Examples you have already used: len(), range(), sum(), print(), input(), min(), max(), sorted(), int(), float(), type(). — + example.

5 marks: 3-mark structure + table: Built-in / User-defined + the worked example from this topic.

LEARN IT

There are two main types of functions in Python.

a) Built-in functions are already defined by Python. You just call them. Examples you have already used: len(), range(), sum(), print(), input(), min(), max(), sorted(), int(), float(), type().

b) User-defined functions are functions **you** create with `def` for tasks that no built-in covers in one step — greeting a user, dividing with a zero check, writing a grade file.

	Built-in	User-defined
Who writes it?	The Python language	The programmer
How you start	Just call the name	First write <code>def name(...):</code>
Examples	<code>len("Ali")</code> → 3	<code>def add(a, b): return a + b</code>
Purpose	Everyday operations needed by everyone	Your program's specific jobs

WORKED EXAMPLE

Side by side. Counting letters is built-in. Combining a greeting with a name is user-defined.

```
print(len("Sindh"))

def greet_student(name):
    print("Hello, ", name)

greet_student("Hassan")
greet_student("Malika")
```

OUTPUT

```
5
Hello, Hassan
Hello, Malika
```

You did not write the code inside `len`. You did write the code inside `greet_student`, then reused it for two names.

REMEMBER IT

If Python already has it (`len`, `sum`, `max`), do not rewrite it. Write a user-defined function when you are packaging **your** steps.

COMMON MISTAKE

Do not name your function `list`, `print`, `sum` or `input`. You would hide the built-in name for the rest of that file. Choose names such as `print_bill` or `sum_marks`.

اردو میں سمجھیں

بلٹ ان فنکشن پائتھن میں پہلے سے موجود ہوتے ہیں، جیسے `len()` اور `print()`۔ یوزر ڈیفائنڈ فنکشن وہ ہیں جو پروگرامر `def` سے خود بناتا ہے تاکہ مخصوص کام بار بار کیا جا سکے۔ جو کام بلٹ ان پہلے کر دیتے ہیں انہیں دوبارہ نہ لکھیں۔

CHECK YOURSELF

1. Is `range()` built-in or user-defined?
2. Which keyword creates a user-defined function?

Answers: 1. Built-in. 2. `def`.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Is `range()` built-in or user-defined?

3 marks. Explain Types of Functions (Built-in vs User-defined) with two clear points and one example.

5 marks. Write a 5-mark answer on Types of Functions (Built-in vs User-defined): definition, two points, a labelled diagram or table, and one example.

Answers: 1. Built-in 3. a) Built-in functions are already defined by Python.; Examples you have already used: `len()`, `range()`, `sum()`, `print()`, `input()`, `min()`, `max()`, `sorted()`, `int()`, `float()`, `type()`. 5. Use the recipe in the blue box. Model opening: There are two main types of functions in Python.

BATCH HOMEWORK

Write a 5-mark answer on **Types of Functions (Built-in vs User-defined)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.2.2 Functions with Return Values

ACADEMY SESSION

Session 9 of 14 · 45 minutes (second half) · paired with Types of Functions (Built-in vs User-defined).

45–75 min — this topic. Board working for **Functions with Return Values**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: A function can either print a result (show it on the screen) or return a result (send it back to the caller).

Error clinic: Writing `print(a * b)` inside `multiply` and then `result = multiply(5, 3)` stores `None` in `result`, not 15.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Functions with Return Values**. Write: A function can either print a result (show it on the screen) or return a result (send it back to the caller).

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) A returned value can be stored in a variable, printed later, or used in a further calculation. (2) The call is replaced by the returned value, as if you had written that value in its place. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

A function can either **print** a result (show it on the screen) or **return** a result (send it back to the caller). A returned value can be stored in a variable, printed later, or used in a further calculation. The call is replaced by the returned value, as if you had written that value in its place.

```
def multiply(a, b):  
    return a * b  
  
result = multiply(5, 3)  
print("The answer is:", result)
```

OUTPUT

The answer is: 15

`multiply(5, 3)` evaluates to 15. That 15 is stored in `result`.

WORKED EXAMPLE

Print versus return. This is the difference examiners want.

```
def show_sum(a, b):  
    print(a + b)  
  
def give_sum(a, b):  
    return a + b  
  
x = show_sum(2, 3)  
print("stored from show_sum:", x)  
y = give_sum(2, 3)  
print("stored from give_sum:", y)  
print("double it:", y * 2)
```

OUTPUT

```
5  
stored from show_sum: None  
stored from give_sum: 5  
double it: 10
```

`show_sum` prints 5 inside the function, then returns `None` (the default when there is no `return`). You cannot double that answer later. `give_sum` hands 5 back, so `y * 2` is 10. Use `print` for messages; use `return` for results the rest of the program still needs.

REMEMBER IT

return = send back; print = show now. `return` also **exits** the function immediately. Lines after `return` in the same function do not run.

COMMON MISTAKE

Writing `print(a * b)` inside `multiply` and then `result = multiply(5, 3)` stores `None` in `result`, not 15. If you later write `result + 1` you get `TypeError`. Return the number; let the caller decide whether to print it.

اردو میں سمجھیں

`return` نتیجہ کال کرنے والے پروگرام کو واپس بھیجتا ہے تاکہ وہ متغیر میں محفوظ ہو سکے یا آگے حساب میں لگے۔ اگر `return` نہ ہو تو فنکشن `None` دیتا ہے۔ `print` صرف اسکرین پر دکھاتا ہے؛ اس سے حاصل شدہ قیمت دوبارہ استعمال نہیں ہوتی۔

CHECK YOURSELF

1. What is stored in `result` after `result = multiply(5, 3)` with `return a * b`?
2. What does a function return if it has no `return` statement?

Answers: 1. 15. 2. `None`.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is stored in `result` after `result = multiply(5, 3)` with `return a * b`?

3 marks. Explain Functions with Return Values with two clear points and one example.

5 marks. Write a 5-mark answer on Functions with Return Values: definition, two points, a labelled diagram or table, and one example.

Answers: 1. 15. 3. A returned value can be stored in a variable, printed later, or used in a further calculation.; The call is replaced by the returned value, as if you had written that value in its place. 5. Use the recipe in the blue box. Model opening: A function can either print a result (show it on the screen) or return a result (send it back to the caller).

BATCH HOMEWORK

Write a 5-mark answer on **Functions with Return Values** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.2.3 Activity: Arithmetic Calculator Using Functions

ACADEMY SESSION

Session 10 of 14 · 45 minutes (first half) · paired with Scope of Local and Global Variables.

10–45 min — this topic. Lock the definition and table for **Activity: Arithmetic Calculator Using Functions**. Starter (0–10) is from last class. Second half is Scope of Local and Global Variables.

On the board: Each arithmetic operation is a separate function.

Error clinic: `input()` returns a string.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Activity: Arithmetic Calculator Using Functions**. Write: Each arithmetic operation is a separate function.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) That is modularity: addition is one small task, division is another (with a guard against dividing by zero). (2) The main program only asks for two numbers and calls the functions. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Each arithmetic operation is a **separate function**. That is modularity: addition is one small task, division is another (with a guard against dividing by zero). The main program only asks for two numbers and calls the functions.

```
def add(a, b):
    return a + b

def subtract(a, b):
    return a - b

def multiply(a, b):
    return a * b

def divide(a, b):
    if b != 0:
        return a / b
    else:
        return "Cannot divide by zero"

num1 = float(input("Enter first number: "))
num2 = float(input("Enter second number: "))
print("Addition:", add(num1, num2))
print("Subtraction:", subtract(num1, num2))
print("Multiplication:", multiply(num1, num2))
print("Division:", divide(num1, num2))
```

WORKED EXAMPLE

Sample run with 12 and 4. `float` is used so decimals work; even whole numbers print with a decimal (12 becomes 12.0).

OUTPUT

```
Enter first number: 12
Enter second number: 4
Addition: 16.0
Subtraction: 8.0
Multiplication: 48.0
Division: 3.0
```

Check: $12 + 4 = 16$, $12 - 4 = 8$, $12 \times 4 = 48$, $12 \div 4 = 3$. In Python 3, `/` always produces a float, so 3.0 not 3.

Zero divisor:

```
def divide(a, b):
    if b != 0:
        return a / b
    else:
        return "Cannot divide by zero"

print(divide(10, 0))
print(divide(10, 2))
```

OUTPUT

```
Cannot divide by zero
5.0
```

Without the `if b != 0` test, `10 / 0` would raise `ZeroDivisionError` and stop the program.

REMEMBER IT

Four functions, four names: `add`, `subtract`, `multiply`, `divide`. The main program should look like a contents page — a sequence of calls — not a pile of formulae.

COMMON MISTAKE

`input()` returns a string. If you skip `float()` (or `int()`), `add` would concatenate: `"12" + "4"` is `"124"`. Convert first. Also, `divide` returns either a number or a string; do not later do arithmetic on the error message.

اردو میں سمجھیں

کیلکولیٹر میں ہر عمل الگ فنکشن ہے: جمع، تفریق، ضرب، تقسیم۔ یہ ماڈیولریٹی ہے۔ تقسیم سے پہلے صفر کی جانچ ضروری ہے ورنہ پروگرام رک جاتا ہے۔ `input()` سے ملنے والی تار کو `float()` سے عدد بنانا لازمی ہے ورنہ جمع جوڑنے کے بجائے الفاظ جوڑ دے گی۔

CHECK YOURSELF

1. What does `divide(10, 0)` return in this activity?
2. Why are the numbers converted with `float()`?

Answers: 1. The string "Cannot divide by zero". 2. Because `input()` returns text; `float()` turns it into a number so `+` `-` `*` `/` do arithmetic, including decimals.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does `divide(10, 0)` return in this activity?

3 marks. Explain Activity: Arithmetic Calculator Using Functions with two clear points and one example.

5 marks. Write a 5-mark answer on Activity: Arithmetic Calculator Using Functions: definition, two points, a labelled diagram or table, and one example.

Answers: 1. The string "Cannot divide by zero" 3. That is modularity: addition is one small task, division is another (with a guard against dividing by zero).; The main program only asks for two numbers and calls the functions. 5. Use the recipe in the blue box. Model opening: Each arithmetic operation is a separate function.

BATCH HOMEWORK

Write a 5-mark answer on **Activity: Arithmetic Calculator Using Functions** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.2.4 Scope of Local and Global Variables

ACADEMY SESSION

Session 10 of 14 · 45 minutes (second half) · paired with Activity: Arithmetic Calculator Using Functions.

45–75 min — this topic. Board working for **Scope of Local and Global Variables**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Scope is the region of a program where a variable can be seen and used.

Error clinic: If you only read `x` inside the function, Python uses the global.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Scope of Local and Global Variables**. Write: Scope is the region of a program where a variable can be seen and used.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Python has two scopes you must know for this chapter. (2) A local variable is created inside a function. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Scope is the region of a program where a variable can be seen and used. Python has two scopes you must know for this chapter.

i) Local scope. A **local variable** is created inside a function. It exists only while that function is running. The main program cannot read it.

ii) Global scope. A **global variable** is created outside all functions. Any function may **read** it, and the main program can use it too.

WORKED EXAMPLE

Local — the name is invisible outside.

```
def calc():
    secret = 50
    print(secret)

calc()
print(secret)
```

OUTPUT

```
50
Traceback (most recent call last):
  File "local_scope.py", line 5, in <module>
    print(secret)
NameError: name 'secret' is not defined
```

First the function prints 50. Then the main program tries `print(secret)` and fails: `secret` was born inside `calc` and died when `calc` finished.

Global — readable inside and outside.

```
x = 10

def show():
    print("Inside function:", x)

show()
print("Outside function:", x)
```

OUTPUT

```
Inside function: 10
Outside function: 10
```

Assignment inside a function creates a new local with the same name. It does not change the global:

```
x = 10

def show():
    x = 99
    print("Inside:", x)

show()
print("Outside:", x)
```

OUTPUT

```
Inside: 99
Outside: 10
```

Inside, `x = 99` is a local. After the call, the global is still 10.

REMEMBER IT

Local = inside the room; global = in the corridor. Everyone can see the corridor. Things left in a room are gone when you leave. Prefer locals. Too many globals make bugs hard to find because any function might be using them.

COMMON MISTAKE

If you only **read** `x` inside the function, Python uses the global. If you **assign** to `x` anywhere in that function, Python treats `x` as local for the whole function. Mixing the two without care causes `UnboundLocalError`. Keep function inputs as parameters and outputs as `return` values instead of editing globals.

اردو میں سمجھیں

دائرہ کار (Scope) بتاتا ہے کہ متغیر کہاں دکھائی دیتا ہے۔ لوکل متغیر فنکشن کے اندر بنتا ہے اور فنکشن ختم ہوتے ہی غائب ہو جاتا ہے؛ باہر سے پڑھنے پر `NameError` آتا ہے۔ گلوبل متغیر تمام فنکشنز سے باہر بنتا ہے اور اندر سے پڑھا جا سکتا ہے۔ فنکشن کے اندر اسی نام کو نئی قدر دینے سے نیا لوکل بنتا ہے، گلوبل نہیں بدلتا۔

CHECK YOURSELF

1. Where is a local variable defined?
2. In the last example, what does the main program print for `x` after `show()` ?

Answers: 1. Inside a function. 2. 10 (the global is unchanged).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Where is a local variable defined?

3 marks. Explain Scope of Local and Global Variables with two clear points and one example.

5 marks. Write a 5-mark answer on Scope of Local and Global Variables: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Inside a function 3. Python has two scopes you must know for this chapter.; A local variable is created inside a function. 5. Use the recipe in the blue box. Model opening: Scope is the region of a program where a variable can be seen and used.

BATCH HOMEWORK

Write a 5-mark answer on **Scope of Local and Global Variables** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.3 & 3.4 File Handling and Operations (Modes `r`, `w`, `a`) ★ Golden

ACADEMY SESSION

Session 11 of 14 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: File handling is a program's ability to create, read, write, update and delete files on disk.

Error clinic: Forgetting `.close()` can leave data in a memory buffer so the file on disk looks empty or incomplete — or the file can stay locked.

Exam wording to train: Define file handling, contrast RAM with disk, list modes `r` / `w` / `a` with one property each, and warn that `w` overwrites.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define & **3.4 File Handling and Operations (Modes r, w, a)**. Write: File handling is a program's ability to create, read, write, update and delete files on disk.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).


3 marks: definition + two points — (1) Variables live in RAM and vanish when the program ends. (2) Files live on a hard disk or SSD and stay there — they are persistent. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

File handling is a program's ability to create, read, write, update and delete files on disk. Variables live in **RAM** and vanish when the program ends. Files live on a **hard disk or SSD** and stay there — they are **persistent**.



Read copies data from disk into RAM. Write copies data from RAM onto disk.

Types of files

Type	What it stores	Examples
Text file	Human-readable characters. You can open it in a text editor.	.txt, .csv, .py
Binary file	Raw bytes, not meant to be read as text.	.jpg, .mp3, .dat

This chapter uses text files.

The `open()` function and modes

You must open a file before you use it: `open(filepath, mode)`.

Mode	Name	Description
'r'	Read	Open for reading. Fails if the file does not exist.
'w'	Write	Open for writing. Erases existing content. Creates the file if it is missing.
'a'	Append	Open for writing at the end . Keeps old content. Creates the file if it is missing.
'rb' / 'wb'	Binary	Read or write bytes (images, audio).

File object methods

Method	What it does
<code>.read()</code>	Whole file as one string.
<code>.readlines()</code>	All lines as a list of strings (each usually ends with <code>\n</code>).
<code>.write("text")</code>	Writes a string. You must add <code>\n</code> yourself for a new line.
<code>.close()</code>	Saves to disk, closes the file, frees RAM. Essential if you did not use <code>with</code> .

WORKED EXAMPLE

Create a file in write mode.

```
new_file = open('myfile.txt', 'w')
new_file.write("The quick brown fox jumps over the lazy dog!!!\n")
new_file.close()
print("File has been created successfully.")
```

OUTPUT

```
File has been created successfully.
```

If `myfile.txt` did not exist, `'w'` created it. The sentence is now on disk. `.close()` flushes the buffer so the bytes actually reach the disk.

Danger of `'w'`: opening an existing file in `'w'` deletes everything first.

```
f = open('myfile.txt', 'w')
f.write("FIRST\n")
f.close()
f = open('myfile.txt', 'w')
f.write("SECOND\n")
f.close()
with open('myfile.txt', 'r') as f:
    print(f.read(), end="")
```

OUTPUT

```
SECOND
```

`FIRST` is gone. To keep old lines and add a new one, use `'a'`:

```
f = open('notes.txt', 'w')
f.write("Line 1\n")
f.close()
f = open('notes.txt', 'a')
f.write("Line 2\n")
f.close()
with open('notes.txt', 'r') as f:
    print(f.read(), end="")
```

OUTPUT

```
Line 1
Line 2
```

REMEMBER IT

r = Read existing, w = Wipe then write, a = Add at end. Remember: `write` does not add a newline unless you type `\n`.

COMMON MISTAKE

Forgetting `.close()` can leave data in a memory buffer so the file on disk looks empty or incomplete — or the file can stay locked. Section 3.6 shows `with`, which closes for you even after an error. Never use `'w'` when you only meant to add a line; that is the most common way students wipe their own data.

اردو میں سمجھیں

فائل ہینڈلنگ سے ڈیٹا ڈسک پر مستقل (Persistent) رہتا ہے، برخلاف RAM کے متغیرات کے جو پروگرام بند ہوتے ہی مٹ جاتے ہیں۔ `open(path, mode)` سے فائل کھلتی ہے: `'r'` پڑھنے کے لیے (فائل ہونی چاہیے)، `'w'` لکھنے کے لیے (پراانا مواد مٹ جاتا ہے)، `'a'` آخر میں جوڑنے کے لیے۔ کام کے بعد `.close()` ضروری ہے اگر `with` استعمال نہ ہو۔

EXAM TIP

Define file handling, contrast RAM with disk, list modes `r / w / a` with one property each, and warn that `w` overwrites. Short programs that write one line and close the file are common. Mention `.read()`, `.readlines()`, `.write()` and `.close()` by name.

CHECK YOURSELF

1. Which mode overwrites an existing file?
2. Which mode fails if the file is missing?
3. Why must `.write` often include `\n`?

Answers: 1. `'w'` . 2. `'r'` . 3. Because `write()` does not start a new line by itself; without `\n` the next write continues on the same line.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which mode overwrites an existing file?

3 marks. Explain & 3.4 File Handling and Operations (Modes `r, w, a`) with two clear points and one example.

5 marks. Define file handling, contrast RAM with disk, list modes `r / w / a` with one property each, and warn that `w` overwrites. Short programs that write one line and close the file are common. Mention...

8 marks. & 3.4 File Handling and Operations (Modes `r, w, a`): 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. `'w'` 3. Variables live in RAM and vanish when the program ends.; Files live on a hard disk or SSD and stay there — they are persistent. 5. Use the recipe in the blue box. Model opening: File handling is a program's ability to create, read, write, update and delete files on disk. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on & 3.4 File Handling and Operations (Modes `r, w, a`) using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.6 The with Statement (Context Manager) ★ Golden

ACADEMY SESSION

Session 12 of 14 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: It is easy to forget `.close()`.

Error clinic: You cannot read from `f` after the `with` block — the file is already closed.

Exam wording to train: Define the `with` statement as a context manager that guarantees `close`.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **The with Statement (Context Manager)**. Write: It is easy to forget `.close()`.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) If the program crashes before `.close()` runs, the file may be incomplete or corrupted. (2) Python's `with` statement is a context manager: it opens the file, runs the indented block, and always closes the file when the block ends —... — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

It is easy to forget `.close()`. If the program crashes before `.close()` runs, the file may be incomplete or corrupted. Python's `with` statement is a **context manager**: it opens the file, runs the indented block, and **always closes** the file when the block ends — even if an error occurs inside.

with `open(...)` as `f` → use `f` → block ends → file closed automatically

```
with open('myfile.txt', 'w') as new_file:
    new_file.write("Context managers are safe!\n")
# no .close() here – with already closed the file
```

After the indented block, `new_file` is closed. You do not write `new_file.close()`.

3.7 Activity: reading file content

`.read()` pulls the whole file into RAM. For a huge file that can waste memory. The professional pattern is to **iterate line by line**.

```
with open('myfile.txt', 'w') as new_file:
    new_file.write("Context managers are safe!\n")

with open('myfile.txt', 'r') as read_file:
    for line in read_file:
        print(line, end="")
print("\n\nFile read successfully.")
```

OUTPUT

Context managers are safe!

File read successfully.

`end=""` stops `print` from adding a second newline: each line from the file already ends with `\n`.

WORKED EXAMPLE

Three ways to read the same small file.

```
with open('sample.txt', 'w') as f:
    f.write("Ali 80\nSara 90\nAyesha 75\n")

with open('sample.txt', 'r') as f:
    print("=== .read() ===")
    print(repr(f.read()))

with open('sample.txt', 'r') as f:
    print("=== .readlines() ===")
    print(f.readlines())

with open('sample.txt', 'r') as f:
    print("=== line by line ===")
    for line in f:
        print(line, end="")
```

OUTPUT

```
=== .read() ===
'Ali 80\nSara 90\nAyesha 75\n'
=== .readlines() ===
['Ali 80\n', 'Sara 90\n', 'Ayesha 75\n']
=== line by line ===
Ali 80
Sara 90
Ayesha 75
```

`repr` shows the hidden `\n` characters. `.readlines()` is handy when you need a list (the grade tracker uses this). Line-by-line looping is best for large files because only one line sits in memory at a time.

REMEMBER IT

with = "take, use, put back." Prefer `with open(...) as f:` in every new program. You still choose the mode: `'r'`, `'w'` or `'a'`.

COMMON MISTAKE

You cannot read from `f` after the `with` block — the file is already closed. Do all reading and writing inside the block. Also, `print(line)` without `end=""` looks double-spaced because both the line and `print` add a newline.

اردو میں سمجھیں

`with` بیان ایک کانٹیکسٹ مینیجر (Context Manager) ہے جو فائل کو بلاک کے اختتام پر خود بند کر دیتا ہے، چاہے اندر غلطی ہو جائے۔
بڑی فائلیں ایک ایک سطر کے لوپ سے پڑھنا بہتر ہے بجائے پورے مواد کو `.read()` سے میموری میں بھرنے کے۔
`print(line, end="")` دگنی خالی سطر روکتا ہے۔

EXAM TIP

Define the `with` statement as a context manager that guarantees `close`. Contrast it with manual `open / close`. Be ready to write a four-line program that writes with `with` and a four-line program that reads line by line. Mention memory: iterating is safer for large files than `.read()`.

CHECK YOURSELF

1. What does a context manager guarantee for a file?
2. Why pass `end=""` when printing each line from a file?

Answers: 1. That the file is closed when the `with` block ends, even if an error occurs. 2. Because each line already ends with `\n`; `print` would otherwise add another newline and the output would look double-spaced.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does a context manager guarantee for a file?

3 marks. Explain The `with` Statement (Context Manager) with two clear points and one example.

5 marks. Define the `with` statement as a context manager that guarantees `close`. Contrast it with manual `open/close`. Be ready to write a four-line program that writes with `with` and a four-line program that...

8 marks. The `with` Statement (Context Manager): 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. That the file is closed when the `with` block ends, even if an error occurs. 3. If the program crashes before `.close()` runs, the file may be incomplete or corrupted.; Python's `with` statement is a context manager: it opens the file, runs the indented block, and always closes the file when the block ends —... 5. Use the recipe in the blue box. Model opening: It is easy to forget `.close()`. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **The `with` Statement (Context Manager)** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.8 Errors and Exceptions (Try-Except)

ACADEMY SESSION

Session 13 of 14 · 45 minutes (first half) · paired with Mini File Handling Project: Grade Tracker.

10–45 min — this topic. Lock the definition and table for **Errors and Exceptions (Try-Except)**. Starter (0–10) is from last class. Second half is Mini File Handling Project: Grade Tracker.

On the board: An exception is an error raised while the program is running — for example opening a file that is not there.

Error clinic: Do not wrap your entire program in one silent `except`: that ignores every mistake.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Errors and Exceptions (Try-Except)**. Write: An exception is an error raised while the program is running — for example opening a file that is not there.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Without handling, Python prints a traceback and stops. (2) A try/except block catches the error and lets you show a clear message instead of crashing. — + example.

5 marks: 3-mark structure + table: Error type / Meaning + the worked example from this topic.

LEARN IT

An **exception** is an error raised while the program is running — for example opening a file that is not there. Without handling, Python prints a traceback and **stops**. A `try / except` block catches the error and lets you show a clear message instead of crashing.

Error type	Meaning
<code>FileNotFoundError</code>	The path does not exist.
<code>PermissionError</code>	The operating system will not let you read or write that file.
<code>IOError</code>	A general input/output problem (disk full, disk disconnected).

Put risky code in `try`. Put the recovery in `except ErrorType`. A final `except Exception as e` can catch anything else, using `e` as the error object.

```
try:
    with open('missing_data.txt', 'r') as f:
        content = f.read()
        print(content)
except FileNotFoundError:
    print("Error: The file does not exist. Please check the name.")
except Exception as e:
    print(f"An unexpected error occurred: {e}")
```

OUTPUT

```
Error: The file does not exist. Please check the name.
```

Without `try`, the same open raises:

OUTPUT

```
Traceback (most recent call last):
  File "missing.py", line 1, in <module>
    open('missing_data.txt', 'r')
FileNotFoundError: [Errno 2] No such file or directory: 'missing_data.txt'
```

WORKED EXAMPLE

When the file exists, the except blocks are skipped.

```
with open('ok.txt', 'w') as f:
    f.write("Present\n")

try:
    with open('ok.txt', 'r') as f:
        content = f.read()
        print(content, end="")
except FileNotFoundError:
    print("Error: The file does not exist. Please check the name.")
```

OUTPUT

```
Present
```

Professional software does not dump a red traceback on a user. If a file is missing or a disk fails, the user should see a calm sentence such as “Please check the file name” or “Please try again later.”

REMEMBER IT

try = attempt; except = backup plan. Catch the **specific** error first (`FileNotFoundError`), then a general `Exception` if you need it. Order matters: a bare `except Exception` first would swallow the specific error.

COMMON MISTAKE

Do not wrap your entire program in one silent `except:` that ignores every mistake. You would hide real bugs. Catch the errors you expect, and keep the message honest. `'w'` and `'a'` create a missing file, so they do not raise `FileNotFoundError`; `'r'` does.

اردو میں سمجھیں

ایکسپشن (`Exception`) چلتے پروگرام کی غلطی ہے، جیسے غیر موجود فائل کھولنا۔ `try` میں خطرناک کوڈ لکھیں اور `except FileNotFoundError` میں صاف پیغام دکھائیں تاکہ پروگرام کریش نہ ہو۔ پیشہ ورانہ سافٹ ویئر صارف کو سرخ ٹریس بیک کی بجائے سمجھ آنے والا جملہ دکھاتا ہے۔

CHECK YOURSELF

1. Which exception is raised when `open('missing_data.txt', 'r')` cannot find the file?
2. Does the sample program crash, or print a message, when the file is missing?

Answers: 1. `FileNotFoundError`. 2. It prints "Error: The file does not exist. Please check the name." and continues.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which exception is raised when `open('missing_data.txt', 'r')` cannot find the file?

3 marks. Explain Errors and Exceptions (Try-Except) with two clear points and one example.

5 marks. Write a 5-mark answer on Errors and Exceptions (Try-Except): definition, two points, a labelled diagram or table, and one example.

Answers: 1. `FileNotFoundError` 3. Without handling, Python prints a traceback and stops.; A try/except block catches the error and lets you show a clear message instead of crashing. 5. Use the recipe in the blue box. Model opening: An exception is an error raised while the program is running — for example opening a file that is not there.

BATCH HOMEWORK

Write a 5-mark answer on **Errors and Exceptions (Try-Except)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

3.9 Mini File Handling Project: Grade Tracker

ACADEMY SESSION

Session 13 of 14 · 45 minutes (second half) · paired with Errors and Exceptions (Try-Except).

45–75 min — this topic. Board working for **Mini File Handling Project: Grade Tracker**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: This project uses `'w'` to create a grades file, `'a'` to add a student later, and `'r'` to read every line and compute an average.

Error clinic: If a line has no colon, `split(":")` will not produce two parts and the unpacking name, `grade = ...`

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Mini File Handling Project: Grade Tracker**. Write: This project uses 'w' to create a grades file, 'a' to add a student later, and 'r' to read every line and compute an average.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) This project uses 'w' to create a grades file, 'a' to add a student later, and 'r' to read every line and compute an average. (2) It combines file handling, string methods and arithmetic. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

This project uses 'w' to create a grades file, 'a' to add a student later, and 'r' to read every line and compute an average. It combines file handling, string methods and arithmetic.

Write names and marks ('w') → Append a new student ('a') → Read lines ('r') → Split, total, average

```
with open("grades.txt", "w") as f:
    f.write("Alice: 88\n")
    f.write("Bob: 75\n")
    f.write("Carol: 92\n")
    print("Grades file created.")

with open("grades.txt", "a") as f:
    f.write("David: 81\n")
    print("New student appended.")

with open("grades.txt", "r") as f:
    lines = f.readlines()
    total = 0
    for line in lines:
        name, grade = line.strip().split(":")
        print(f"{name} scored {grade}")
        total += int(grade)
    average = total / len(lines)
    print(f"\nClass average: {average:.1f}")
```

WORKED EXAMPLE

What happens in memory and on disk.

1. 'w' creates grades.txt (or wipes an old one) with three lines.
2. 'a' adds David: 81\n at the end. Alice, Bob and Carol stay.
3. .readlines() returns
['Alice: 88\n', 'Bob: 75\n', 'Carol: 92\n', 'David: 81\n'].
4. .strip() removes the trailing \n. .split(":") turns "Alice: 88" into ["Alice", " 88"].
5. int(grade) accepts the extra space: int(" 88") is 88.
6. Total = 88 + 75 + 92 + 81 = 336. Average = 336 / 4 = 84.0. The format :.1f prints one decimal place.

OUTPUT

```
Grades file created.
New student appended.
Alice scored 88
Bob scored 75
Carol scored 92
David scored 81

Class average: 84.0
```

The extra space before each mark in the output comes from the space after the colon in the file ("Alice: 88"). int() ignores it. To tidy the printout you could use grade.strip() as well; the average would not change.

REMEMBER IT

Same file, three modes, three `with` blocks. Never open the same file in `'w'` when you only meant to add David — that would delete Alice, Bob and Carol.

COMMON MISTAKE

If a line has no colon, `split(":")` will not produce two parts and the unpacking `name, grade = ...` will raise `ValueError`. Keep the `Name: mark` format. An empty file would make `len(lines)` zero and then `total / 0` would fail — a real system should check that, just as `divide` checked for zero.

اردو میں سمجھیں

گریڈ ٹریکر پہلے `'w'` سے فائل بناتا ہے، پھر `'a'` سے نیا طالب علم جوڑتا ہے، پھر `'r'` سے تمام سطریں پڑھ کر اوسط نکالتا ہے۔ ہر سطر کو `strip` اور `split(":")` سے نام اور نمبر میں توڑا جاتا ہے۔ اوسط = کل نمبر ÷ طلبہ کی تعداد۔ `'w'` دوبارہ استعمال کرنے سے پرانے ریکارڈ مٹ جائیں گے۔

CHECK YOURSELF

1. What is the class average in the sample, and how is it calculated?
2. Why is David written with mode `"a"` rather than `"w"`?

Answers: 1. 84.0 because $(88+75+92+81)/4 = 336/4 = 84.0$. 2. Because `"a"` appends; `"w"` would erase the three existing students.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is the class average in the sample, and how is it calculated?

3 marks. Explain Mini File Handling Project: Grade Tracker with two clear points and one example.

5 marks. Write a 5-mark answer on Mini File Handling Project: Grade Tracker: definition, two points, a labelled diagram or table, and one example.

Answers: 1. 84.0 because $(88+75+92+81)/4 = 336/4 = 84.0$ 3. This project uses `'w'` to create a grades file, `'a'` to add a student later, and `'r'` to read every line and compute an average.; It combines file handling, string methods and arithmetic. 5. Use the recipe in the blue box. Model opening: This project uses `'w'` to create a grades file, `'a'` to add a student later, and `'r'` to read every line and compute an average.

BATCH HOMEWORK

Write a 5-mark answer on **Mini File Handling Project: Grade Tracker** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Career Opportunities

ACADEMY SESSION

Session 14 of 14 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The skills in this chapter — data structures, functions and files — are the same skills used in many jobs.

Error clinic: You do not need all four job titles for the exam.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Career Opportunities**. Write: The skills in this chapter — data structures, functions and files — are the same skills used in many jobs.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Data analyst — uses lists and dictionaries, then file handling, to process, visualise and interpret data for decisions. (2) Automation engineer — writes scripts that repeat file and testing tasks so humans do not have to. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

The skills in this chapter — data structures, functions and files — are the same skills used in many jobs.

- **Python / software developer** — builds applications, scripts and tools in Python, one of the most widely used languages in industry.
- **Data analyst** — uses lists and dictionaries, then file handling, to process, visualise and interpret data for decisions.
- **Automation engineer** — writes scripts that repeat file and testing tasks so humans do not have to.
- **Game developer** — uses functions, data structures and logic to build interactive games.

WORKED EXAMPLE

The word-frequency dictionary is a tiny version of what a data analyst does with a much larger file of customer comments. The grade tracker is a tiny version of a school information system. The attendance list is a tiny version of an HR register. Same structures, larger files.

REMEMBER IT

Four careers: **P-D-A-G** — Python developer, Data analyst, Automation engineer, Game developer.

COMMON MISTAKE

You do not need all four job titles for the exam. You do need one sentence each if the paper asks "List career opportunities related to this chapter."

اردو میں سمجھیں

اس باب کی مہارتیں پائتھن ڈویلپر، ڈیٹا اینالسٹ، آٹومیشن انجینئر اور گیم ڈویلپر کے کام میں روز استعمال ہوتی ہیں۔ فہرستیں، ڈکشنریز، فنکشنز اور فائلیں چھوٹے اسکول پروگراموں سے لے کر بڑے صنعتی نظام تک ایک جیسی بنیاد ہیں۔

CHECK YOURSELF

1. Which career uses lists, dictionaries and files to interpret business data?
2. Name two careers listed in this chapter.

Answers: 1. Data analyst. 2. Any two of: Python/software developer, data analyst, automation engineer, game developer.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which career uses lists, dictionaries and files to interpret business data?

3 marks. Explain Career Opportunities with two clear points and one example.

5 marks. Write a 5-mark answer on Career Opportunities: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Data analyst 3. Data analyst — uses lists and dictionaries, then file handling, to process, visualise and interpret data for decisions.; Automation engineer — writes scripts that repeat file and testing tasks so humans do not have to. 5. Use the recipe in the blue box. Model opening: The skills in this chapter — data structures, functions and files — are the same skills used in many jobs.

BATCH HOMEWORK

Write a 5-mark answer on **Career Opportunities** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Chapter 3 Review

Chapter summary

- Python programs rest on primitive types (`int` , `float` , `bool`) and abstract structures: lists, tuples, sets and dictionaries.
- A **list** is ordered and mutable, written with `[]` . Index from 0; `[-1]` is last. Slice stop is exclusive. Methods include `append` , `insert` , `remove` , `sort` , `reverse` , `clear` .
- A **tuple** is ordered and immutable, written with `()` . Item assignment raises `TypeError` . Only `count` and `index` exist as methods.
- A **set** is unordered and unique, written with `{}` . Use `|` & `-` & `^` for union, intersection, difference and symmetric difference. Prefer `discard` over `remove` .
- A **dictionary** maps unique keys to values. `d[key]` can raise `KeyError` ; `d.get(key, default)` is safe. Duplicate keys keep the last value.
- `min` , `max` , `len` , `sum` and `sorted` work across structures. On a dict, `min` / `max` / `sorted` use keys; total values with `sum(d.values())` . `sorted()` returns a new list; `.sort()` changes a list in place.
- Functions written with `def` give reusability, modularity, readability and maintainability. Built-in functions already exist; user-defined functions solve your tasks.
- `return` sends a value to the caller. Without `return` , the result is `None` . Local variables live inside a function; global variables live outside all functions.
- Files persist on disk. Modes: `r` read (must exist), `w` write (overwrites), `a` append. Methods: `read` , `readlines` , `write` , `close` .
- The `with` statement is a context manager that closes the file automatically. Loop line by line to read large files safely.
- `try / except FileNotFoundError` stops a missing file from crashing the program.
- The grade tracker writes with `w` , appends with `a` , reads with `r` , splits each `Name: mark` line, and computes the mean.

Key terms

Term	Meaning	اردو
Data structure	A way of organising values so a program can store and use them.	ڈیٹا سٹرکچر
Primitive type	A basic single value: <code>int</code> , <code>float</code> , <code>bool</code> .	بنیادی قسم
List	Ordered, mutable sequence written with <code>[]</code> .	فہرست
Index	The position of an item, starting at 0 (or -1 from the end).	انڈیکس
Slicing	Copying a portion of a sequence with <code>start:stop:step</code> .	سلائسنگ
Traversal	Visiting each element in turn, usually with a loop.	گشت / تراورسل
Mutable	Can be changed after creation.	قابل تبدیلی
Immutable	Cannot be changed after creation.	ناقابل تبدیلی
Tuple	Ordered, immutable sequence written with <code>()</code> .	ٹیپل
Set	Unordered collection of unique items written with <code>{}</code> .	سیٹ
Union	All unique items from two sets (<code> </code>).	اجتماع
Intersection	Items common to both sets (<code>&</code>).	اشتراک
Dictionary	Mutable map of unique keys to values.	ڈکشنری
Key	The unique lookup name in a dictionary.	کلید
Value	The data stored under a key.	قدر
Function	A named, reusable block of code.	فنکشن
Parameter	An input name in a function definition.	پیرامیٹر
Return value	The result sent back with <code>return</code> .	واپسی کی قدر
Local variable	A name that exists only inside a function.	مقامی متغیر
Global variable	A name defined outside all functions.	عالمی متغیر
File handling	Creating, reading, writing and closing disk files.	فائل ہینڈلنگ
File mode	How a file is opened: <code>r</code> , <code>w</code> , <code>a</code> (or binary).	فائل موڈ
Context manager	A <code>with</code> block that sets up a resource and cleans it up.	کانٹیکسٹ مینیجر
Exception	A runtime error object, such as <code>FileNotFoundError</code> .	ایکسپشن
try / except	A pair of blocks that attempt code and handle errors.	ٹرائی / ایکسپٹ

Practice: multiple choice

- Which structure is ordered and mutable?
 - List
 - Tuple
 - Set
 - Frozen set
- What does `nums[2:6]` return if `nums = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]`?
 - `[2, 3, 4, 5, 6]`
 - `[2, 3, 4, 5, 6, 7]`
 - `[2, 3, 4, 5]`
 - `[3, 4, 5, 6]`
- `t = (1, 2, 3)` then `t[0] = 99` raises
 - `KeyError`
 - `TypeError`
 - `ValueError`
 - `IndexError`
- A set is best described as
 - ordered with duplicates
 - indexed and mutable
 - key-value pairs
 - unordered with unique elements
- If `A = {1, 2, 3, 4}` and `B = {3, 4, 5, 6}`, then `A & B` is
 - `{3, 4}`
 - `{1, 2}`
 - `{1, 2, 3, 4, 5, 6}`
 - `{1, 2, 5, 6}`
- `{"a": 1, "a": 2, "a": 3}` prints
 - `{'a': 1}`
 - `{'a': 1, 'a': 2, 'a': 3}`
 - `{'a': 3}`
 - a `KeyError`
- The safe way to read a possibly missing dictionary key is
 - `d[key]`
 - `d.get(key)`
 - `d.keys(key)`
 - `d.index(key)`
- For `s = {5, 1, 9, 3, 7}`, `sum(s)` is
 - 5
 - 9
 - 7
 - 25
- Which statement is true?
 - `sorted(x)` returns a new list and leaves `x` unchanged
 - `sorted(x)` works only on lists
 - `.sort()` works on tuples
 - `.sort()` returns a new list
- A function is created with the keyword
 - `func`
 - `def`
 - `define`
 - `return`
- A function that has no `return` statement returns
 - 0
 - False
 - None
 - an empty string
- A variable defined inside a function is
 - local
 - global
 - persistent
 - public
- Opening a file with mode `'w'`
 - fails if the file already exists
 - adds new text at the end
 - is read-only
 - erases existing content (and creates the file if needed)
- The `with open(...) as f:` statement is used mainly because
 - it makes the file binary
 - it closes the file automatically
 - it is faster than lists
 - it prevents `KeyError`
- Reading a missing file in mode `'r'` without `try` raises
 - `TypeError`
 - `KeyError`
 - `FileNotFoundError`
 - `ValueError`

Practice: short questions

1. Define a data structure. Distinguish primitive from abstract data structures with one example of each.
2. What is negative indexing? Give the expression that returns the last item of a list named `fruits`.
3. State four differences between a list and a tuple.
4. Differentiate `.remove()` and `.discard()` on a set.
5. Why can a dictionary not have two identical keys? What happens if you write the same key twice?
6. Contrast `sorted()` with list `.sort()`.
7. List four benefits of using functions.
8. Define local scope and global scope.
9. Write the meaning of file modes `'r'`, `'w'` and `'a'`.
10. What is a context manager? Why is `with` safer than calling `.close()` yourself?

Practice: long / problem questions

1. Compare list, tuple, set and dictionary in a table (syntax, order, mutability, duplicates, how you access an item, one typical use). Then write two lines of Python that create one example of each holding the numbers 1, 2 and 2, and state what each structure actually stores.
2. Write a complete Python program that takes a sentence, counts the frequency of each word using a dictionary and `.get()`, prints a two-column table, and prints the most frequent word. Trace your program on `"python is easy python is fun python is powerful"`.
3. Write an arithmetic calculator with four user-defined functions `add`, `subtract`, `multiply` and `divide`. `divide` must not crash when the second number is 0. Explain how `return` is used and why `input` values are converted with `float`.
4. Explain file handling. Describe modes `r`, `w` and `a`, the `with` statement, and `try/except FileNotFoundError`. Include a short program that writes one line with `with` and another that reads a file that might be missing.
5. The grade tracker writes three students with `'w'`, appends David with `'a'`, then computes the class average. Write the full program, show the exact output for marks 88, 75, 92 and 81, and explain `strip`, `split(":")` and `average:.1f`.

Answer key

Multiple choice

1. a
2. c
3. b
4. d
5. a
6. c
7. b
8. d
9. a
10. b
11. c
12. a
13. d
14. b
15. c

Short questions — model answers

1. A data structure organises values in a program. Primitive types hold one value (e.g. `int 17`). Abstract structures hold collections and richer operations (e.g. a list of marks).
2. Negative indexing counts from the right. `fruits[-1]` is the last item. `fruits[-2]` is the second last.
3. List: `[]`, mutable, many methods, slightly slower, use when data will change. Tuple: `()`, immutable, only `count / index`, slightly faster, use for protected records. Both are ordered and allow duplicates and indexing.
4. Both delete an element. `remove` raises `KeyError` if the value is absent. `discard` does nothing in that case, so it is the safer choice.
5. Each key must identify one value (like one roll number per student). A repeated key does not crash; the last assigned value overwrites the earlier one, e.g. `{"a": 3}`.
6. `sorted(x)` is a built-in function for any iterable; it returns a new list and does not change `x`. `.sort()` is a list method that sorts in place and returns `None`.
7. Reusability (write once, call many times), modularity (small named tasks), readability (shorter files), maintainability (fix one definition).
8. Local: defined inside a function; invisible outside; gone when the function ends. Global: defined outside all functions; readable throughout the program.
9. `'r'` read, error if missing. `'w'` write, create if missing, erase old content. `'a'` append at the end, create if missing, keep old content.
10. A context manager sets up a resource and cleans it up. `with open(...)` as `f` closes the file when the block ends, even after an exception, so you cannot forget `.close()` and you are safer if the program crashes mid-write.

Long questions — model answers

1. Use the comparison table from 3.1.4 (brackets, ordered/mutable/duplicates/access/empty/use). Examples:

```
print([1, 2, 2])
print((1, 2, 2))
print({1, 2, 2})
print({"a": 1, "b": 2, "b": 2})
```

OUTPUT

```
[1, 2, 2]
(1, 2, 2)
{1, 2}
{'a': 1, 'b': 2}
```

The list and tuple keep both 2s and an order. The set drops the extra 2. The dictionary keeps unique keys; the second "b" overwrites the first.

2. Use the program in 3.1.7. Trace: nine tokens; `python` and `is` end at 3; others at 1. Output matches the worked example, including Most Frequent: 'python' (3 times) because `max` returns the first key among ties. Heart of the loop:
`word_freq[word] = word_freq.get(word, 0) + 1`.
3. Use the four functions from 3.2.3. `return` sends each result to `print` in the main program. `divide` returns the string "Cannot divide by zero" when `b == 0`. `float(input(...))` is required because `input` returns a string and `"12" + "4"` would concatenate. Sample 12 and 4: 16.0, 8.0, 48.0, 3.0.
4. File handling stores data on disk so it outlives the program. Modes: `r` read / must exist; `w` wipe-or-create; `a` add-or-create. `with` closes automatically. Try/except:

```
with open("note.txt", "w") as f:
    f.write("Saved\n")
try:
    with open("note.txt", "r") as f:
        print(f.read(), end="")
except FileNotFoundError:
    print("Error: The file does not exist. Please check the name.")
```

OUTPUT

```
Saved
```

If the name were wrong, the except message would print instead of a traceback.

5. Full program as in 3.9. Disk after append:

OUTPUT

```
Alice: 88
Bob: 75
Carol: 92
David: 81
```

Output of the program (exact):

OUTPUT

```
Grades file created.
New student appended.
Alice scored 88
Bob scored 75
Carol scored 92
David scored 81

Class average: 84.0
```

`strip` removes `\n`; `split(":")` separates name and mark; `int(grade)` allows the extra space; `{average:.1f}` prints one decimal. $336 \div 4 = 84.0$.

Self-assessment: I can...

- ☐ Choose list, tuple, set or dictionary for a given problem and justify the choice.
- ☐ Explain tuple immutability and the inner-list exception, and use `count / index`.
- ☐ Update a dictionary, access values with `.get()`, and loop with `.items()`.
- ☐ Write a user-defined function with parameters and a `return` value, and contrast it with a built-in.
- ☐ Open a text file in `r`, `w` or `a` using `with`, and read it line by line.
- ☐ Index, slice, traverse and update a list, including `[-1]` and the main methods.
- ☐ Build a set, drop duplicates, and compute union, intersection, difference and symmetric difference.
- ☐ Apply `min`, `max`, `len`, `sum` and `sorted` correctly, including on dictionaries.
- ☐ State whether a name is local or global and predict a `NameError`.
- ☐ Catch `FileNotFoundError` and complete the grade-tracker project with the correct average.

CHAPTER 4

Data and Analysis

This chapter shows you how to pull data from a SQLite database with Python, clean it in Pandas, draw the right chart, and summarise a dataset with mean, median, mode and standard deviation. These are the same steps a data analyst uses every day.

اس باب میں آپ سیکھیں گے کہ پائتھن سے ایس کیو لائٹ ڈیٹا بیس کیسے جوڑا جاتا ہے، پینڈاز میں ڈیٹا کیسے صاف ہوتا ہے، درست چارٹ کیسے بنتا ہے، اور اوسط، میڈین، موڈ اور معیاری انحراف سے خلاصہ کیسے نکلتا ہے۔

What you will learn

- Define data analysis and say why Python is used for it.
- Create a SQLite database, table, insert, select, commit and close.
- Create calculated columns and handle NaN with `isnull`, `fillna` and `dropna`.
- Choose and code bar, line, pie, histogram, scatter and box plots.
- Name the five parts of a Python database connection in order.
- Build a Pandas DataFrame from a dictionary, CSV or Excel file.
- Organise data in tables and frequency distributions.
- Compute mean, median, mode, range, variance, standard deviation, min and max by hand, and know that pandas `.std()` uses `n-1`.

ACADEMY CALENDAR

Academy calendar: 9 topics · 5 Golden · **9 classes of 90 minutes** + one 40-minute weekly test after this chapter.

Class	Topics	Kind	Board focus
Class 01	Concept of Data Analysis	Single · 90 min	Data analysis is examining, organising and interpreting data so you can extract useful...
Class 02	Data Sources and Database Connection	★ Golden · 90 min	Data sources are where information comes from: school records, websites, sensors,...
Class 03	Creating a SQLite Database in Python	Single · 90 min	SQLite is built into Python.
Class 04	Pandas and DataFrames	★ Golden · 90 min	Pandas is a third-party library for tables.
Class 05	Handling Missing Values (NaN)	★ Golden · 90 min	Missing cells are NaN ("Not a Number").
Class 06	Data Organization and Representation	Single · 90 min	Organised data is easier to read.
Class 07	Data Visualization and Types of Graphs	★ Golden · 90 min	Pick the graph that matches the question.
Class 08	Descriptive Statistics	★ Golden · 90 min	Descriptive statistics squeeze a long list into a few honest numbers.
Class 09	Career Opportunities	Single · 90 min	The skills in this chapter map onto real jobs: data analyst (Pandas, Excel), database...

Weekly test: 15 MCQ from this chapter + two 5-mark Golden questions. Mark to the recipes. Re-teach any Golden below 60% in the next starter.

گولڈن موضوع پوری کلاس لیتا ہے۔ ہفتہ وار ٹیسٹ کے بعد کمزور گولڈن دوبارہ پڑھائیں۔

4.1 Concept of Data Analysis

ACADEMY SESSION

Session 1 of 9 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Data analysis is examining, organising and interpreting data so you can extract useful information.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Concept of Data Analysis**. Write: Data analysis is examining, organising and interpreting data so you can extract useful information.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Schools study results, shops study sales, hospitals study patient records — all to make a decision, spot a trend or solve a problem. (2) Python is popular for this work because it is readable, talks to files and databases, does statistics, and draws graphs. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Data analysis is examining, organising and interpreting data so you can extract useful information. Schools study results, shops study sales, hospitals study patient records — all to make a decision, spot a trend or solve a problem.

Python is popular for this work because it is readable, talks to files and databases, does statistics, and draws graphs. Five lines of Pandas often replace an hour of spreadsheet clicking.

WORKED EXAMPLE

A Hyderabad college has 400 CS marks in a spreadsheet. Analysis answers: What is the average? How many failed? Is the second shift weaker than the first? The numbers are data; those answers are information.

اردو میں سمجھیں

ڈیٹا کا تجزیہ یعنی اعداد کو ترتیب دے کر ان سے فیصلے کے قابل معلومات نکالنا۔ پائٹھن اس لیے منتخب کیا جاتا ہے کہ وہ فائلیں، ڈیٹا بیس، حساب اور گراف سب سنبھال لیتا ہے۔

CHECK YOURSELF

1. Give one school use of data analysis.
2. Name two Python superpowers for analysis.

Answers: 1. Study results to improve teaching (or similar). 2. Any two: read CSV/Excel/databases, organise tables, statistics, charts.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Give one school use of data analysis.

3 marks. Explain Concept of Data Analysis with two clear points and one example.

5 marks. Write a 5-mark answer on Concept of Data Analysis: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Study results to improve teaching (or similar) 3. Schools study results, shops study sales, hospitals study patient records — all to make a decision, spot a trend or solve a problem.; Python is popular for this work because it is readable, talks to files and databases, does statistics,... 5. Use the recipe in the blue box. Model opening: Data analysis is examining, organising and interpreting data so you can extract useful information.

BATCH HOMEWORK

Write a 5-mark answer on **Concept of Data Analysis** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.1.1 – 4.1.2 Data Sources and Database Connection ★ Golden

ACADEMY SESSION

Session 2 of 9 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Data sources are where information comes from: school records, websites, sensors, databases.

Exam wording to train: Write the five names in order and one line each.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Data Sources and Database Connection**. Write: Data sources are where information comes from: school records, websites, sensors, databases.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Connectivity is the conversation between your Python program and that source so you can read and update data. (2) Five components of a database connection, in the order they actually work: — + example.

5 marks: 3-mark structure + table: # / Component / Role + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Data sources are where information comes from: school records, websites, sensors, databases.

Connectivity is the conversation between your Python program and that source so you can read and update data.

Five components of a database connection, in the order they actually work:

#	Component	Role
1	Database	Organised store (SQLite = one .db file; MySQL = a server for big apps)
2	Driver	Translator between Python and that DBMS (sqlite3 is built in)
3	Connection object	Opens, manages and closes the pipeline
4	Cursor object	Runs SQL and walks through result rows
5	SQL queries	CREATE, INSERT, SELECT, UPDATE, DELETE



EXAM TIP

Write the five names in order and one line each. A common trap is swapping cursor and connection: the connection is the pipe; the cursor is the messenger that travels through it.

اردو میں سمجھیں

خمسة اجزاء: ڈیٹا بیس، ڈرائیور، کنکشن، کرسر، ایس کیو ایل۔ کنکشن پائپ ہے، کرسر اس پائپ میں چل کر حکم چلاتا ہے۔

CHECK YOURSELF

1. Which object executes `SELECT *` ?

2. Is SQLite a driver, a database, or both?

Answers: 1. The cursor. 2. SQLite is the database; the `sqlite3` module is the driver.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which object executes `SELECT *`?

3 marks. Explain Data Sources and Database Connection with two clear points and one example.

5 marks. Write the five names in order and one line each. A common trap is swapping cursor and connection: the connection is the pipe; the cursor is the messenger that travels through it.

8 marks. Data Sources and Database Connection: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. The cursor 3. Connectivity is the conversation between your Python program and that source so you can read and update data.; Five components of a database connection, in the order they actually work: 5. Use the recipe in the blue box. Model opening: Data sources are where information comes from: school records, websites, sensors, databases. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Data Sources and Database Connection** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.2 Creating a SQLite Database in Python

ACADEMY SESSION

Session 3 of 9 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: SQLite is built into Python.

Error clinic: Forgetting `commit()` is the classic bug: the program prints nothing next time because the insert was never saved.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Creating a SQLite Database in Python**. Write: SQLite is built into Python.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The whole database is one .db file next to your script — no password, no port, no server. (2) Nine steps you must be able to write from memory: — + example.

5 marks: 3-mark structure + table: Step / Why it matters + the worked example from this topic.

LEARN IT

SQLite is built into Python. The whole database is one .db file next to your script — no password, no port, no server. Nine steps you must be able to write from memory:

```
import sqlite3
conn = sqlite3.connect("school.db") # 1-2 driver + connection
cur = conn.cursor() # 3 cursor
cur.execute("CREATE TABLE IF NOT EXISTS students (id INTEGER, name TEXT, marks INTEGER)")
cur.execute("INSERT INTO students VALUES (1, 'Ali', 85)")
conn.commit() # 6 SAVE or the row vanishes
cur.execute("SELECT * FROM students")
rows = cur.fetchall()
for r in rows:
    print(r)
conn.close() # 9 unlock the file
```

OUTPUT
(1, 'Ali', 85)

Step	Why it matters
connect	Creates the file if it does not exist
cursor	Vehicle that carries SQL
execute	Runs one SQL command
commit	Writes INSERT/UPDATE/DELETE to disk
fetchall	Brings SELECT results into a Python list of tuples
close	Frees memory and unlocks the file

COMMON MISTAKE

Forgetting `commit()` is the classic bug: the program prints nothing next time because the insert was never saved. Forgetting `close()` can lock `school.db` so the next run fails.

REMEMBER IT

Strings inside SQL use single quotes: `'Ali'`. Python strings around the SQL use double quotes (or a triple-quoted string).

اردو میں سمجھیں

EXECUTE, COMMIT, SELECT, FETCALL, کرس، کنکٹ، امپورٹ، ترتیب: ایک فائل ہے۔ پورا ڈیٹا بیس ایک فائل ہے۔ ساتھ آتی ہے، پورا ڈیٹا بیس ایک فائل ہے۔ ترتیب: امپورٹ، کنکٹ، کرس، EXECUTE, COMMIT, SELECT, FETCALL, ایس کیو لائٹ پائنتھن کے ساتھ آتی ہے، پورا ڈیٹا بیس ایک فائل ہے۔

CHECK YOURSELF

1. What does `*` mean in `SELECT *`?
2. Which call must follow `INSERT`?

Answers: 1. All columns. 2. `conn.commit()`.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does `*` mean in `SELECT *`?

3 marks. Explain Creating a SQLite Database in Python with two clear points and one example.

5 marks. Write a 5-mark answer on Creating a SQLite Database in Python: definition, two points, a labelled diagram or table, and one example.

Answers: 1. All columns 3. The whole database is one `.db` file next to your script — no password, no port, no server.; Nine steps you must be able to write from memory: 5. Use the recipe in the blue box. Model opening: SQLite is built into Python.

BATCH HOMEWORK

Write a 5-mark answer on **Creating a SQLite Database in Python** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.3 Pandas and DataFrames ★ Golden

ACADEMY SESSION

Session 4 of 9 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Pandas is a third-party library for tables.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Pandas and DataFrames**. Write: Pandas is a third-party library for tables.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Install once: pip install pandas in the terminal (not inside the .py file). (2) Convention: import pandas as pd. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Pandas is a third-party library for tables. Install once: `pip install pandas` in the terminal (not inside the .py file). Convention: `import pandas as pd`.

A **DataFrame** is a 2-D table of rows and columns, like Excel or an SQL table. You can filter, sort and calculate whole columns without writing a for loop.

```
import pandas as pd
data = {
    "Name": ["Ali", "Sara", "Ahmed"],
    "Math": [85, 90, 78],
    "Science": [80, 88, 70],
}
df = pd.DataFrame(data)
print(df)
```

OUTPUT

	Name	Math	Science
0	Ali	85	80
1	Sara	90	88
2	Ahmed	78	70

`read_csv('students.csv')` and `read_excel('students.xlsx', sheet_name='Sheet1')` load files. `df.head()` prints the first five rows — use it on large files so you do not flood the screen.

```
df["Total"] = df["Math"] + df["Science"]
df["Average"] = df["Total"] / 2
print(df)
```

OUTPUT

	Name	Math	Science	Total	Average
0	Ali	85	80	165	82.5
1	Sara	90	88	178	89.0
2	Ahmed	78	70	148	74.0

WORKED EXAMPLE

Check: Ali $85+80=165$, $165/2=82.5$. Sara $90+88=178$, 89.0 . Ahmed $78+70=148$, 74.0 .

اردو میں سمجھیں

پینڈا ڈیٹا فریم دیتا ہے۔ ڈکشنری، سی ایس وی یا ایکسل سے لوڈ کریں۔ نئے کالم بغیر لوپ کے پوری قطار پر حساب کر کے بنتے ہیں۔ `head()` صرف پہلی پانچ قطاریں دکھاتا ہے۔

CHECK YOURSELF

1. What is `pd`?
2. Why not `print(df)` on a million-row file?

Answers: 1. The usual alias for pandas. 2. It would print everything; use `df.head()`.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is `pd`?

3 marks. Explain Pandas and DataFrames with two clear points and one example.

5 marks. Write a 5-mark answer on Pandas and DataFrames: definition, two points, a labelled diagram or table, and one example.

8 marks. Pandas and DataFrames: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. The usual alias for pandas. 3. Install once: `pip install pandas` in the terminal (not inside the `.py` file).; Convention: `import pandas as pd`. 5. Use the recipe in the blue box. Model opening: Pandas is a third-party library for tables. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Pandas and DataFrames** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.3.3 Handling Missing Values (NaN) ★ Golden

ACADEMY SESSION

Session 5 of 9 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Missing cells are NaN ("Not a Number").

Error clinic: Filling a salary gap with the mean of a company that includes the CEO can hide poverty (the same outlier problem as the mean).

Exam wording to train: State: identify with isnull/sum, fill numeric gaps with the mean, fill categories with a label, or drop rows if filling would invent a lie.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Handling Missing Values (NaN)**. Write: Missing cells are NaN ("Not a Number").

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Statistics crash or lie if you ignore them. (2) Three tools: isnull() (True where empty), fillna(value) (replace), dropna() (delete the row). — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

8–10 marks: 5-mark structure + a complete truth table and a labelled gate / logic diagram + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Missing cells are **NaN** ("Not a Number"). Statistics crash or lie if you ignore them. Three tools: isnull() (True where empty), fillna(value) (replace), dropna() (delete the row).

```
import pandas as pd
df = pd.DataFrame({
    "Name": ["Ali", "Sara", "Ahmed", "Ayesha"],
    "Marks": [85.0, None, 78.0, 92.0],
    "Grade": ["A", "A", None, "A"],
})
print(df.isnull().sum())
```

OUTPUT

```
Name      0
Marks      1
Grade      1
dtype: int64
```

WORKED EXAMPLE

Replace Marks with the mean of the known marks, and Grade with a label. Known marks 85, 78, 92 → mean = $255/3 = 85.0$.

```
avg = df["Marks"].mean()          # 85.0
df["Marks"] = df["Marks"].fillna(avg)
df["Grade"] = df["Grade"].fillna("Not Assigned")
print(df)
```

OUTPUT

	Name	Marks	Grade
0	Ali	85.0	A
1	Sara	85.0	A
2	Ahmed	78.0	Not Assigned
3	Ayesha	92.0	A

`df = df.dropna()` would instead delete Sara's row and Ahmed's row (any row that still had a NaN).

EXAM TIP

State: identify with `isnull / sum`, fill numeric gaps with the mean, fill categories with a label, or drop rows if filling would invent a lie. Never analyse first and clean second.

COMMON MISTAKE

Filling a salary gap with the mean of a company that includes the CEO can hide poverty (the same outlier problem as the mean). Know why the value is missing before you fill.

اردو میں سمجھیں

خالی خانے NaN ہیں۔ `isnull` تلاش، `fillna` بھرنا (اکثر اوسط سے)، `dropna` قطار ہٹانا۔ پہلے صاف کرو، پھر تجزیہ۔

CHECK YOURSELF

1. What does `df.isnull().sum()` return?
2. Does `dropna()` delete a column or a row by default?

Answers: 1. Count of NaNs in each column. 2. Any **row** that contains at least one NaN.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does `df.isnull().sum()` return?

3 marks. Explain Handling Missing Values (NaN) with two clear points and one example.

5 marks. State: identify with `isnull/sum`, fill numeric gaps with the mean, fill categories with a label, or drop rows if filling would invent a lie. Never analyse first and clean second.

8 marks. Handling Missing Values (NaN): 5-mark answer plus a complete truth table and a labelled gate / logic diagram.

Answers: 1. Count of NaNs in each column 3. Statistics crash or lie if you ignore them.; Three tools: `isnull()` (True where empty), `fillna(value)` (replace), `dropna()` (delete the row). 5. Use the recipe in the blue box. Model opening: Missing cells are NaN ("Not a Number"). 8. Same 5-mark body + a complete truth table and a labelled gate / logic diagram + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Handling Missing Values (NaN)** using the recipe in this topic. Include a complete truth table and a labelled gate / logic diagram. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.4 Data Organization and Representation

ACADEMY SESSION

Session 6 of 9 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Organised data is easier to read.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Data Organization and Representation**. Write: Organised data is easier to read.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Frequency distribution — how many items fall in each range (bin). (2) Graph — a picture of a trend or comparison (next topics). — + example.

5 marks: 3-mark structure + table: Range of marks / Frequency (students) + the worked example from this topic.

LEARN IT

Organised data is easier to read. Three everyday forms:

- **Table** — exact values side by side (Ali 85 Math, 80 Science).
- **Frequency distribution** — how many items fall in each range (bin).
- **Graph** — a picture of a trend or comparison (next topics).

Range of marks	Frequency (students)
50–59	5
60–69	7
70–79	9
80–89	4
90–100	2

Most students scored 70–79. That pattern is hard to see in a raw list of 27 marks, and obvious in this table. Matplotlib (`import matplotlib.pyplot as plt`) turns tables into graphs: `import` → `figure` → `plot` → `labels` → `title` → `show()`.

اردو میں سمجھیں

ٹیبل درست عدد دکھاتی ہے، تعدد کی جدول بتاتی ہے کتنے طلبہ کس رینج میں ہیں، گراف رجحان دکھاتا ہے۔ میٹپلاٹ لب گراف بناتی ہے۔

CHECK YOURSELF

1. How many students scored 80 or above in the table?
2. Name the library that draws graphs in Python.

Answers: 1. $4 + 2 = 6$. 2. Matplotlib (pyplot).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. How many students scored 80 or above in the table?

3 marks. Explain Data Organization and Representation with two clear points and one example.

5 marks. Write a 5-mark answer on Data Organization and Representation: definition, two points, a labelled diagram or table, and one example.

Answers: 1. $4 + 2 = 6$ 3. Frequency distribution — how many items fall in each range (bin).; Graph — a picture of a trend or comparison (next topics). 5. Use the recipe in the blue box. Model opening: Organised data is easier to read.

BATCH HOMEWORK

Write a 5-mark answer on **Data Organization and Representation** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.5 Data Visualization and Types of Graphs ★ Golden

ACADEMY SESSION

Session 7 of 9 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Pick the graph that matches the question.

Exam wording to train: "Which graph and why?" is a 3-mark gift.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Data Visualization and Types of Graphs**. Write: Pick the graph that matches the question.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Pick the graph that matches the question. (2) Then label axes and give a title — an unlabelled chart scores zero in an exam. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a fully labelled diagram copied from the board + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Pick the graph that matches the question. Then label axes and give a title — an unlabelled chart scores zero in an exam.

Chart	Shows	Watch out
Bar / column	Compare discrete categories (subjects, departments)	Column = vertical; bar often = horizontal
Line	Change over time (temperature, visitors)	Needs an ordered x-axis (months, years)
Pie	Parts of one whole as percentages	Bad with many or almost-equal slices
Histogram	Distribution of one numeric variable in bins	Bars touch (continuous range), unlike a bar chart
Scatter	Relationship of two numeric variables	Each dot is one pair (x, y)
Box plot	Min, Q1, median, Q3, max, and outliers	Best tool for spotting extreme values

4.5.1 Bar / column

```
import matplotlib.pyplot as plt
subjects = ["English", "Math", "Science", "History"]
marks = [64, 82, 71, 49]
plt.bar(subjects, marks, color="skyblue", edgecolor="black")
plt.title("Marks vs Subjects")
plt.xlabel("Subjects")
plt.ylabel("Marks out of 100")
```

4.5.2 Line

```
months = ["Jan", "Feb", "Mar", "Apr", "May", "Jun"]
temps = [12, 15, 20, 25, 30, 35]
plt.plot(months, temps, marker="o")
plt.title("Average Monthly Temperature")
plt.grid(True)
```

4.5.3 Pie

```
subjects = ["Math", "Physics", "CS", "Biology"]
students = [25, 15, 30, 10] # total 80
plt.pie(students, labels=subjects, autopct="%1.1f%%", startangle=90)
```

Check: Math $25/80 = 31.25\% \rightarrow 31.2\%$. Physics 18.8% . CS 37.5% . Biology 12.5% .

4.5.4 Histogram

```
scores = [45, 50, 55, 60, 62, 65, 68, 70, 72, 75, 78, 80, 82, 85, 90, 95]
plt.hist(scores, bins=[40, 50, 60, 70, 80, 90, 100], edgecolor="black")
```




4.5.5 Scatter

```
plt.scatter([10, 20, 30, 40, 50, 60, 70, 80],
            [2, 4, 5, 4, 7, 8, 9, 12], color="green", alpha=0.7)
plt.title("Rainfall vs Crop Yield") # positive correlation
```

4.5.6 Box plot

```
plt.boxplot([[55, 60, 65, 70, 75, 80, 85],
            [40, 65, 70, 72, 75, 80, 95]],
            tick_labels=["Class A", "Class B"])
```

The box is the middle 50% (Q1 to Q3). The line inside is the median. Whiskers reach min and max (or a fence, with outliers drawn as dots). Class B is more spread out than Class A.



Column compares; line shows a trend; pie shows share; the box summarises spread around the median.

EXAM TIP

"Which graph and why?" is a 3-mark gift. Write the name, what it shows, and one reason the others are worse.

بار/کالم اقسام کا موازنہ، لائن وقت کا رجحان، پائی حصے، ہسٹوگرام مسلسل تقسیم (بار آپس میں لگے)، اسکیٹر دو متغیرات کا تعلق، باکس پلاٹ پانچ اعداد اور آؤٹ لائن۔

CHECK YOURSELF

1. Why do histogram bars touch?
2. Rainfall vs yield — which chart?

Answers: 1. The x-axis is a continuous numeric range, not separate categories. 2. Scatter (two numeric variables, looking for correlation).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Why do histogram bars touch?

3 marks. Explain Data Visualization and Types of Graphs with two clear points and one example.

5 marks. "Which graph and why?" is a 3-mark gift. Write the name, what it shows, and one reason the others are worse.

8 marks. Data Visualization and Types of Graphs: 5-mark answer plus a fully labelled diagram copied from the board.

Answers: 1. The x-axis is a continuous numeric range, not separate categories 3. Pick the graph that matches the question.; Then label axes and give a title — an unlabelled chart scores zero in an exam. 5. Use the recipe in the blue box. Model opening: Pick the graph that matches the question. 8. Same 5-mark body + a fully labelled diagram copied from the board + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Data Visualization and Types of Graphs** using the recipe in this topic. Include a fully labelled diagram copied from the board. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

4.6 Descriptive Statistics ★ Golden

ACADEMY SESSION

Session 8 of 9 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Descriptive statistics squeeze a long list into a few honest numbers.

Error clinic: Do not report variance as if it were in "marks".

Exam wording to train: Always state whether you used n or $n-1$.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Descriptive Statistics**. Write: Descriptive statistics squeeze a long list into a few honest numbers.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Central tendency asks “what is typical?”. (2) Spread asks “how mixed is the list?”. — + example.

5 marks: 3-mark structure + table: Measure / How / Use when + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Descriptive statistics squeeze a long list into a few honest numbers. **Central tendency** asks “what is typical?”. **Spread** asks “how mixed is the list?”.

4.6.1 Mean, median, mode

Measure	How	Use when
Mean	Sum ÷ n. Uses every value.	Values sit close together. Example: ordinary test scores.
Median	Middle after sorting. Odd n: centre. Even n: mean of the two centre values.	Outliers would wreck the mean (CEO salary).
Mode	Most frequent value. May be none, one, or several.	Most popular choice (shoe size).

WORKED EXAMPLE

Marks 70, 80, 90. Mean = $240/3 = 80$.

Odd list 35, 10, 15, 70, 95. Sort: 10, 15, 35, 70, 95. Median = **35**.

Bottles sold 20, 25, 20, 30, 20, 25, 20. Mode = **20** (appears four times).

Outlier trap: nine people earn 10, one earns 1000. Mean = $1090/10 = 109$ (looks rich). Median = 10 (tells the truth).

4.6.2 Spread: range, variance, standard deviation, min, max

- **Min / max** — smallest and largest. Marks 70, 80, 90, 60, 75 → min 60, max 90.
- **Range** = max – min. Sales 120, 150, 180 → range 60.
- **Population variance** $\sigma^2 = (\text{sum of squared deviations from the mean}) \div n$.
- **Sample variance** s^2 uses $\div (n-1)$. `pandas.Series.std()` uses the sample version.
- **Standard deviation** = $\sqrt{\text{variance}}$. Same units as the data (marks, not marks²). Low SD → tight, consistent. High SD → spread out, unpredictable.

WORKED EXAMPLE

Full working on 70, 80, 90. Mean $\mu = 80$. Deviations -10, 0, +10. Squares 100, 0, 100. Sum = 200.

Population variance $\sigma^2 = 200/3 = \mathbf{66.67}$ (2 d.p.). Population SD $\sigma = \sqrt{(200/3)} = \mathbf{8.16}$ (2 d.p.).

Sample variance $s^2 = 200/2 = \mathbf{100}$. Sample SD $s = 10$. That is what `pd.Series([70,80,90]).std()` returns.

EXAM TIP

Always state whether you used n or $n-1$. Show the sorted list for the median. For SD, show: mean $\rightarrow$ deviations $\rightarrow$ squares $\rightarrow$ divide $\rightarrow$ square root. A box plot pictures min, Q1, median, Q3, max of the same data.

COMMON MISTAKE

Do not report variance as if it were in "marks". Variance is marks^2 . Quote the standard deviation when you want a sentence in the original units.

اردو میں سمجھیں

اوسط سب کا مجموعہ تقسیم تعداد، میڈین ترتیب کے بعد بیچ، موڈ سب سے زیادہ بار آنے والا۔ رینج بڑا منفی چھوٹا۔ ویرینس اوسط سے فاصلوں کے مربع کی اوسط ہے، معیاری انحراف اس کا جذر ہے اور اصل اکائی میں ہوتا ہے۔ سینڈاز $\text{std}()$ (نمونے والا $n-1$) استعمال کرتا ہے۔

CHECK YOURSELF

1. Median of 4, 8, 6, 10, 2?
2. Range of 120, 150, 180?
3. Does pandas `.std()` divide by n or $n-1$?

Answers: 1. Sorted 2,4,6,8,10 $\rightarrow$ 6. 2. 60. 3. $n-1$ (sample).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Median of 4, 8, 6, 10, 2?

3 marks. Explain Descriptive Statistics with two clear points and one example.

5 marks. Always state whether you used n or $n-1$. Show the sorted list for the median. For SD, show: mean $\rightarrow$ deviations $\rightarrow$ squares $\rightarrow$ divide $\rightarrow$ square root. A box plot pictures min, Q1, median, Q3, max of the same...

8 marks. Descriptive Statistics: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. Sorted 2,4,6,8,10 $\rightarrow$ 6 3. Central tendency asks "what is typical?"; Spread asks "how mixed is the list?". 5. Use the recipe in the blue box. Model opening: Descriptive statistics squeeze a long list into a few honest numbers. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Descriptive Statistics** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Career Opportunities

ACADEMY SESSION

Session 9 of 9 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The skills in this chapter map onto real jobs: data analyst (Pandas, Excel), database administrator (SQLite/MySQL), data scientist (statistics + modelling), visualisation specialist (Matplotlib,...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Career Opportunities**. Write: The skills in this chapter map onto real jobs: data analyst (Pandas, Excel), database administrator (SQLite/MySQL), data scientist (statistics + modelling), visualisation specialist (Matplotlib,...

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The skills in this chapter map onto real jobs: data analyst (Pandas, Excel), database administrator (SQLite/MySQL), data scientist... (2) Second distinct point (not a repeat of the definition) — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

The skills in this chapter map onto real jobs: data analyst (Pandas, Excel), database administrator (SQLite/MySQL), data scientist (statistics + modelling), visualisation specialist (Matplotlib, Power BI), business-intelligence analyst (dashboards for managers), backend developer (the code that talks to the database).

اردو میں سمجھیں

یہ باب ڈیٹا اینالسٹ، ڈیٹا بیس ایڈمن، ڈیٹا سائنسدان، ویژولائزیشن اور بیک اینڈ ڈویلپر جیسے کیریئرز کی بنیاد ہے۔

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Define Career Opportunities.

3 marks. Explain Career Opportunities with two clear points and one example.

5 marks. Write a 5-mark answer on Career Opportunities: definition, two points, a labelled diagram or table, and one example.

Answers: 1. The skills in this chapter map onto real jobs: data analyst (Pandas, Excel), database administrator (SQLite/MySQL), data scientist (statistics + modelling), visualisation specialist (Matplotlib, Power BI),... 3. The skills in this chapter map onto real jobs: data analyst (Pandas, Excel), database administrator (SQLite/MySQL), data scientist... 5. Use the recipe in the blue box. Model opening: The skills in this chapter map onto real jobs: data analyst (Pandas, Excel), database administrator (SQLite/MySQL), data scientist (statistics + modelling),...

BATCH HOMEWORK

Write a 5-mark answer on **Career Opportunities** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Chapter 4 Review

Chapter summary

- Data analysis turns raw facts into decisions. Python reads files and databases, calculates and plots.
- Connection chain: database → driver → connection → cursor → SQL.
- SQLite: connect, cursor, execute, commit, fetchall, close. No commit means no save.
- A DataFrame is a 2-D table. Load with a dictionary, `read_csv` or `read_excel`. New columns are vectorised arithmetic.
- NaN: find (`isnull`), fill (`fillna` , often with the mean), or drop (`dropna`).
- Tables give exact values; frequency bins show how many in each range.
- Bar/column = categories; line = time; pie = parts of a whole; histogram = numeric distribution (touching bars); scatter = two variables; box = five-number summary + outliers.
- Mean uses every value and is sensitive to outliers; median is the middle; mode is the most common.
- Range = max–min. Variance = mean squared deviation ($\div n$ or $\div n-1$). SD = $\sqrt{\text{variance}}$. pandas `.std()` uses $n-1$.

Key terms

Term	Meaning	اردو
Data analysis	Examining data to extract useful information.	ڈیٹا کا تجزیہ
Connectivity	Link between a program and a data source.	رابطہ کاری
Driver	Translator between Python and a DBMS.	ڈرائیور
Connection	Open pipeline to the database.	کنکشن
Cursor	Object that executes SQL and fetches rows.	کرسر
SQLite	Built-in file-based database.	ایس کیو لائٹ
commit	Save INSERT/UPDATE/DELETE to disk.	کمیٹ / محفوظ کرنا
Pandas	Library for table-like data.	پینڈاز
DataFrame	2-D labelled table of rows and columns.	ڈیٹا فریم
NaN	Missing value ("Not a Number").	خالی / غیر موجود قدر
Frequency	How many items fall in a class/bin.	تعدد
Histogram	Distribution chart whose bars touch.	ہسٹوگرام
Scatter plot	Dots showing two numeric variables.	اسکیٹر پلاٹ
Box plot	Min, Q1, median, Q3, max (and outliers).	باکس پلاٹ
Mean	Arithmetic average.	اوسط
Median	Middle value of a sorted list.	میڈین / درمیانی قدر
Mode	Most frequent value.	موڈ / کثرت
Range	Max – min.	حد / رینج
Variance	Mean of squared deviations from the mean.	ویریانس / تغیر
Standard deviation	Square root of variance (original units).	معیاری انحراف
Outlier	An extreme unusual value.	آؤٹ لائر

Practice: multiple choice

1. The object that executes SQL is the:
 - a. driver
 - b. cursor
 - c. DataFrame
 - d. histogram
2. After INSERT you must:
 - a. close then commit
 - b. commit
 - c. drop the table
 - d. call head()
3. Pandas is installed with:
 - a. import pandas
 - b. pip install pandas
 - c. sqlite3.connect
 - d. plt.show()
4. `df.head()` shows:
 - a. the last 5 rows
 - b. the first 5 rows
 - c. only NaNs
 - d. the standard deviation
5. Missing Pandas values appear as:
 - a. NULL in every chart
 - b. NaN
 - c. 0 always
 - d. a pie slice
6. To delete every row that contains a gap:
 - a. fillna
 - b. dropna
 - c. fetchall
 - d. commit
7. A line graph is best for:
 - a. parts of a whole
 - b. a trend over months
 - c. two unrelated categories
 - d. a primary key
8. Histogram bars:
 - a. must have gaps
 - b. touch, because bins are a continuous range
 - c. always show time
 - d. replace the mean
9. Rainfall vs crop yield is a:
 - a. pie chart
 - b. scatter plot
 - c. primary key
 - d. mode
10. A box plot's inner line is the:
 - a. mean
 - b. mode
 - c. median
 - d. range
11. Mean of 70, 80, 90 is:
 - a. 70
 - b. 80
 - c. 90
 - d. 240
12. Median of 10, 15, 35, 70, 95 is:
 - a. 10
 - b. 35
 - c. 70
 - d. 45
13. Mode of 20, 25, 20, 30, 20, 25, 20 is:
 - a. 25
 - b. 30
 - c. 20
 - d. 7
14. Range of 120, 150, 180 is:
 - a. 30
 - b. 60
 - c. 150
 - d. 180
15. pandas `.std()` divides by:
 - a. n
 - b. n-1
 - c. 2n
 - d. zero

Practice: short questions

1. List the five components of a Python database connection in order.
2. Why is `conn.commit()` required after INSERT?
3. What is a DataFrame? How do you load a CSV into one?
4. Differentiate `fillna` and `dropna`.
5. When is a pie chart a poor choice?
6. Differentiate a bar chart and a histogram.
7. Why is the median better than the mean for company salaries?
8. Define range, min and max with the list 70, 80, 90, 60, 75.
9. Why do we take the square root of variance?
10. State two careers that use this chapter's skills.

Practice: long / problem questions

1. Write a complete Python program that creates `school.db`, a `students` table, inserts Ali 85 and Sara 90, commits, prints all rows, and closes. Number the five connection components beside the matching lines.
2. Starting from the dictionary of Ali/Sara/Ahmed marks, write Pandas code to build a DataFrame, add Total and Average columns, and print it. Show the exact output.
3. Given Marks [85, None, 78, 92] and Grade ["A","A", None, "A"], show `isnull().sum()`, then fill Marks with the mean and Grade with "Not Assigned". Compute the mean by hand.
4. For each goal pick a chart and justify in one sentence: (a) CS vs IT vs Eng enrolment, (b) website hits from Jan to Jun, (c) share of four clubs in one college, (d) distribution of 200 heights, (e) hours studied vs marks, (f) comparing spread of two classes.
5. For 4, 8, 6, 10, 2 compute mean, median, range, population variance and population SD. Show every step. Then say what pandas `.std()` would report instead.
6. Explain, with a numeric example, how an outlier distorts the mean but not the median. Link this to when you would draw a box plot.

Answer key

Multiple choice

1. b
2. b
3. b
4. b
5. b
6. b
7. b
8. b
9. b
10. c
11. b
12. b
13. c
14. b
15. b

Short questions — model answers

1. Database, driver, connection object, cursor object, SQL queries.
2. Without commit the insert stays in memory and disappears when the program ends, so the next run cannot see the row.
3. A 2-D table of labelled rows and columns. `df = pd.read_csv("file.csv")`.
4. `fillna(v)` replaces NaN with v (the row stays). `dropna()` deletes any row that still contains a NaN.
5. When there are many slices, or the values are almost equal, so the eye cannot compare them.
6. Bar: separate categories, gaps between bars. Histogram: one numeric variable grouped into bins; bars touch.
7. A huge CEO salary pulls the mean up; the median stays with the typical worker.
8. Min 60, max 90, range 30.
9. Variance is in squared units. The SD brings the spread back to the original units (marks, rupees, °C).
10. Any two: data analyst, DBA, data scientist, visualisation specialist, BI analyst, backend developer.

Long questions — model answers

1. Use the nine-step listing in 4.2 with two INSERTs. Label: sqlite3 = driver, connect = connection, cursor = cursor, execute strings = SQL, school.db = database.
2. Output is the three-row table with Total 165, 178, 148 and Average 82.5, 89.0, 74.0 (see the worked example).
3. isnull sum: Marks 1, Grade 1. Mean of 85, 78, 92 = $255/3 = 85.0$. After fill: Sara Marks 85.0, Ahmed Grade "Not Assigned".
4. (a) column/bar — compare categories. (b) line — time. (c) pie — parts of a whole. (d) histogram — numeric distribution. (e) scatter — two numeric variables. (f) box — spread and outliers.
5. Sorted 2,4,6,8,10. Sum 30, mean 6, median 6, range 8. Deviations -4,-2,0,2,4. Squares 16,4,0,4,16 sum 40. $\sigma^2 = 40/5 = 8$. $\sigma = \sqrt{8} = 2.828$ (3 d.p.). pandas `.std()` uses $40/4 = 10$, $\sqrt{10} \approx 3.162$.
6. Nine salaries of 10 and one of 1000: mean 109, median 10. Draw a box plot — the 1000 appears as an outlier dot above the whisker, so the distortion is visible.

Self-assessment: I can...

- | | |
|--|--|
| ☐ name the five connection components in order. | ☐ write SQLite connect / create / insert / commit / select / close. |
| ☐ build a DataFrame and add a calculated column. | ☐ find, fill and drop missing values. |
| ☐ choose bar, line, pie, histogram, scatter or box for a problem. | ☐ compute mean, median, mode, range, variance and SD by hand. |
| ☐ state that pandas std uses $n-1$. | |

CHAPTER 5

Application and Impacts of Computing

This chapter shows you how computers learn from data with machine learning, neural networks and deep learning, how to collaborate online without leaking secrets, how to protect data and stop cyber threats, and how to keep digital teamwork fair for every student in Sindh.

اس باب میں آپ سیکھیں گے کہ مشین لرننگ، نیورل نیٹ ورکس اور ڈیپ لرننگ کمپیوٹر کو ڈیٹا سے کیسے سکھاتے ہیں، آن لائن کام کو محفوظ کیسے رکھا جائے، ڈیٹا کی حفاظت اور سائبر خطرات کا مقابلہ کیسے کیا جائے، اور ڈیجیٹل تعاون کو سب کے لیے منصفانہ کیسے بنایا جائے۔

What you will learn

- Define **machine learning (ML)** and describe the three steps: data input, learning, prediction.
- Define **deep learning (DL)** and draw the relationship **AI $\supset$ ML $\supset$ DL**.
- List the six components of deep learning and give applications of NN and DL in daily life and in Pakistan.
- Protect data using encryption (including a Caesar cipher), strong passwords, the 3-2-1 backup rule and a firewall.
- Distinguish **equal access** from **equity** and describe the functions of equity in digital collaboration.
- Explain a **neural network (NN)** as a brain-inspired model with an input layer, hidden layers and an output layer.
- Name the eight components of a neural network and compute a neuron's output from given numbers.
- Explain **secure collaboration**: authentication, multi-factor authentication (MFA) and access control.
- Identify common threats (malware, phishing, DoS) and apply mitigation techniques.
- Name common collaboration tools and use them fairly and safely.

ACADEMY CALENDAR

Academy calendar: 17 topics · 5 Golden · **13 classes of 90 minutes** + one 40-minute weekly test after this chapter.

Class	Topics	Kind	Board focus
Class 01	Machine Learning, Neural Networks and Deep Learning + Machine Learning (ML)	Paired · 90 min	Machine learning (ML), neural networks (NN) and deep learning (DL) are important areas of...
Class 02	Neural Networks (NN)	★ Golden · 90 min	A neural network is a computer model that learns patterns from data.
Class 03	Deep Learning (DL)	Single · 90 min	Deep learning is a machine-learning method in which computers use multi-layer neural...
Class 04	Components of Neural Networks	★ Golden · 90 min	The components of a neural network can be understood through its layered architecture.
Class 05	Components of Deep Learning + Future of AI, NN and DL in Pakistan	Paired · 90 min	Deep learning relies on specific advanced components to achieve its high accuracy.
Class 06	Applications of Neural Networks and Deep Learning	Single · 90 min	Neural networks and deep learning are widely used in modern life.
Class 07	Secure Collaboration (Authentication, MFA, Access Control)	★ Golden · 90 min	Digital tools allow people to share files, attend online classes, edit documents and work...

Class	Topics	Kind	Board focus
Class 08	Data Protection (Encryption, Passwords, Backup, Firewall)	Single · 90 min	Data protection means keeping digital information safe from unauthorised access, misuse,...
Class 09	Common Security Threats (Malware, Phishing, DoS)	★ Golden · 90 min	A security threat is any action, event or weakness that can harm a computer system or its...
Class 10	Identifying Security Threats + Apply Mitigation Techniques	Paired · 90 min	Identifying security threats means noticing signs that data or systems may be at risk.
Class 11	Equity and Equal Access in Digital Collaboration	Single · 90 min	Collaboration tools are vital for online learning and teamwork.
Class 12	Functions of Equity and Equal Access	★ Golden · 90 min	Equity and equal access are not slogans.
Class 13	Collaboration Tools + Career Opportunities	Paired · 90 min	Digital collaboration tools are online platforms that support communication, file...

Weekly test: 15 MCQ from this chapter + two 5-mark Golden questions. Mark to the recipes. Re-teach any Golden below 60% in the next starter.

گولڈن موضوع پوری کلاس لیتا ہے۔ ہفتہ وار ٹیسٹ کے بعد کمزور گولڈن دوبارہ پڑھائیں۔

5.1 Machine Learning, Neural Networks and Deep Learning

ACADEMY SESSION

Session 1 of 13 · 45 minutes (first half) · paired with Machine Learning (ML).

10–45 min — this topic. Lock the definition and table for **Machine Learning, Neural Networks and Deep Learning**. Starter (0–10) is from last class. Second half is Machine Learning (ML).

On the board: Machine learning (ML), neural networks (NN) and deep learning (DL) are important areas of artificial intelligence (AI).

Error clinic: Mistake: “AI, ML and DL are three different, separate subjects.” Fix: They nest.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Machine Learning, Neural Networks and Deep Learning**. Write: Machine learning (ML), neural networks (NN) and deep learning (DL) are important areas of artificial intelligence (AI).

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Speech recognition (for example Siri, Alexa, or Urdu voice typing on a phone). (2) Photo search categorisation (typing “car” in a gallery and seeing car photos). — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

LEARN IT


Machine learning (ML), **neural networks (NN)** and **deep learning (DL)** are important areas of **artificial intelligence (AI)**. **AI** is the broad field in which computers perform tasks that normally need human thinking, such as recognising a face, understanding speech or making a decision.

These technologies help computers **learn from data** and make useful decisions **without being explicitly programmed for every single step**. You do not write a separate rule for every possible face or every Urdu accent. You show the computer many examples, and it finds the patterns itself.

They are used in many modern systems:

- **Face unlock** on smartphones.
- **Speech recognition** (for example Siri, Alexa, or Urdu voice typing on a phone).
- **Photo search** categorisation (typing “car” in a gallery and seeing car photos).
- **Medical diagnosis** from X-rays and scans.
- **Language translation** (English to Urdu or Sindhi).

Remember the nesting: **AI is the biggest set**. Inside AI sits **ML**. Inside ML sits **DL**. Every deep-learning system is a kind of machine learning, and every machine-learning system is a kind of AI — but not every AI system is deep learning.



The set relationship $AI \supset ML \supset DL$. Deep learning is a method of machine learning; machine learning is a part of artificial intelligence.

WORKED EXAMPLE

Worked example: place each system in the correct set. Sara in Karachi uses three features on her phone.

1. **A chess app that follows fixed if-then rules** written by a programmer (“if the queen is attacked, move it”). This is **AI** (the machine decides), but it is **not ML**, because it does not learn from data.
2. **A JazzCash fraud filter** that was trained on thousands of past transactions and then flags a new unusual payment. This is **ML** (and therefore also AI). If it uses only a simple model with few layers, it may **not** be DL.
3. **Face unlock** that studied millions of face images through many hidden layers. This is **DL** — and therefore also ML and AI.

Exam sentence you can write: *All DL is ML, all ML is AI, but not all AI is ML, and not all ML is DL.*

REMEMBER IT

Russian-doll memory trick. Picture three boxes. The outer box is **AI**. Inside it is a smaller box **ML**. Inside that is the smallest box **DL**. You cannot take DL out of ML, and you cannot take ML out of AI.

COMMON MISTAKE

Mistake: "AI, ML and DL are three different, separate subjects."

Fix: They nest. $DL \subset ML \subset AI$. A deep-learning face-unlock system is all three at once.

اردو میں سمجھیں

مصنوعی ذہانت (AI) سب سے بڑا میدان ہے۔ اس کے اندر مشین لرننگ (ML) ہے، اور مشین لرننگ کے اندر ڈیپ لرننگ (DL) ہے۔ یہ ٹیکنالوجیز کمپیوٹر کو ڈیٹا سے سکھاتی ہیں تاکہ ہر قدم الگ الگ پروگرام کیے بغیر فیصلے کیے جا سکیں، جیسے چہرے سے فون کھولنا یا آواز پہچاننا۔

CHECK YOURSELF

1. Which is the largest set: AI, ML or DL?
2. Is every neural-network face-unlock system an example of AI? Why?
3. Give one modern system from this section that uses these technologies.

Answers: 1. AI ($AI \supset ML \supset DL$). 2. Yes — DL is inside ML, and ML is inside AI. 3. Any of: face unlock, speech recognition, photo search, medical diagnosis, language translation.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which is the largest set: AI, ML or DL?

3 marks. Explain Machine Learning, Neural Networks and Deep Learning with two clear points and one example.

5 marks. Write a 5-mark answer on Machine Learning, Neural Networks and Deep Learning: definition, two points, a labelled diagram or table, and one example.

Answers: 1. AI ($AI \supset ML \supset DL$) 3. Speech recognition (for example Siri, Alexa, or Urdu voice typing on a phone).; Photo search categorisation (typing "car" in a gallery and seeing car photos). 5. Use the recipe in the blue box. Model opening: Machine learning (ML), neural networks (NN) and deep learning (DL) are important areas of artificial intelligence (AI).

BATCH HOMEWORK

Write a 5-mark answer on **Machine Learning, Neural Networks and Deep Learning** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.1.1 Machine Learning (ML)

ACADEMY SESSION

Session 1 of 13 · 45 minutes (second half) · paired with Machine Learning, Neural Networks and Deep Learning.

45–75 min — this topic. Board working for **Machine Learning (ML)**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: A machine learning model is the system that learns from data and gives an output.

Error clinic: Mistake: "The computer is intelligent on day one." Fix: An ML model is useful only after training on enough good data.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Machine Learning (ML)**. Write: A machine learning model is the system that learns from data and gives an output.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Think of it as the trained brain of a computer program. (2) In ordinary programming you write every rule yourself: if marks ≥ 40 then "Pass". — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

A **machine learning model** is the system that **learns from data and gives an output**. Think of it as the **trained brain** of a computer program.

In ordinary programming you write every rule yourself: *if marks ≥ 40 then "Pass"*. In machine learning you **do not list every rule**. You give the model many examples (data), it finds the patterns, and later it decides about new cases it has never seen.

How it works — three steps:

1. Data input → 2. Learning (find patterns) → 3. Prediction on new data

- 1. Data input.** The model is given massive amounts of data — for example thousands of past BISE marksheets, or millions of crop photos from Sindh fields.
- 2. Learning.** It studies the data and **learns patterns and rules automatically**. It might notice that students who scored low in Chapter 3 also failed the board exam, or that yellow spots on cotton leaves often mean a pest.
- 3. Prediction.** After training, it can make **accurate predictions or decisions** when given **new, unseen data** — a new student's record, or a new leaf photograph.

Note from the source: there are many types of machine-learning models. A **neural network** is one important type. **Deep learning** is a highly advanced method of machine learning.

WORKED EXAMPLE

Worked example: a wheat-yield model for a farm near Sukkur.

Step 1 — Data input. For 8 years the farm recorded: rainfall (mm), temperature, fertiliser bags used, and the actual yield (maunds per acre).

Step 2 — Learning. The model studies those rows. It finds, for example, that yield rises with fertiliser up to a point, and falls when temperature is very high in April.

Step 3 — Prediction. This year the farmer types in this season's rainfall and temperature. The model has never seen this exact year before, but it predicts "about 32 maunds per acre." The farmer plans storage and a buyer in advance.

Nobody wrote a giant list of "if rain = 120 and temp = 38 then yield = ...". The model learned the pattern from data.

REMEMBER IT

D-L-P. Machine learning is **D**ata in, **L**earn patterns, **P**redict. "Data Learns to Predict."

COMMON MISTAKE

Mistake: "The computer is intelligent on day one."

Fix: An ML model is useful only **after training** on enough good data. Garbage data → garbage predictions. Also, neural networks are *one* type of ML, not the only type; deep learning is a *method* that uses deep neural networks.

اردو میں سمجھیں

مشین لرننگ ماڈل وہ نظام ہے جو ڈیٹا سے سیکھ کر نتیجہ دیتا ہے — کمپیوٹر پروگرام کا تربیت یافتہ دماغ۔ پہلے بہت سا ڈیٹا دیا جاتا ہے، پھر ماڈل خود اصول اور پیٹرن سیکھتا ہے، اور تربیت کے بعد نئے ان دیکھے ڈیٹا پر پیش گوئی کرتا ہے۔ نیورل نیٹ ورک مشین لرننگ کی ایک اہم قسم ہے، اور ڈیپ لرننگ اس کا ایک اعلیٰ طریقہ ہے۔

CHECK YOURSELF

1. What are the three steps of how an ML model works?
2. What is a machine-learning model compared to in the source?
3. After training, what kind of data can the model handle?

Answers: 1. Data input, learning, prediction. 2. The trained brain of a computer program. 3. New, unseen data.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What are the three steps of how an ML model works?

3 marks. Explain Machine Learning (ML) with two clear points and one example.

5 marks. Write a 5-mark answer on Machine Learning (ML): definition, two points, a labelled diagram or table, and one example.

Answers: 1. Data input, learning, prediction. 3. Think of it as the trained brain of a computer program.; In ordinary programming you write every rule yourself: if marks ≥ 40 then "Pass". 5. Use the recipe in the blue box. Model opening: A machine learning model is the system that learns from data and gives an output.

BATCH HOMEWORK

Write a 5-mark answer on **Machine Learning (ML)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.1.2 Neural Networks (NN) ★ Golden

ACADEMY SESSION

Session 2 of 13 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A neural network is a computer model that learns patterns from data.

Error clinic: Mistake: "A neural network is an actual human brain inside the computer." Fix: It is only inspired by the brain.

Exam wording to train: Very common questions: "What is a neural network?" (2–3 marks), "Name its three layers and explain each with the face-unlock example" (5 marks), and "How is a..."

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Neural Networks (NN)**. Write: A neural network is a computer model that learns patterns from data.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Hidden layer(s) — the “thinking” in the middle. Nodes here combine the inputs and learn features (eye distance, nose shape, an edge in a... (2) Output layer — gives the final answer (unlock / keep locked; “this is a cat”; “pass / fail”). — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

8–10 marks: 5-mark structure + a labelled ER diagram (rectangle / oval / diamond) or the relational schema + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **neural network** is a computer model that **learns patterns from data**. It is **directly inspired by the human brain**, but it works as a **mathematical computer system** — not as living tissue.

Your brain has billions of nerve cells (**neurons**) that pass signals to each other. A neural network copies this idea with small processing units also called **neurons** or **nodes**. These nodes are **connected** and **pass information from one layer to another**, performing calculations at each step.

A typical neural network has three kinds of layer:

- **Input layer** — receives the raw data (pixels of a face, samples of a sound, marks of a student).
- **Hidden layer(s)** — the “thinking” in the middle. Nodes here combine the inputs and learn features (eye distance, nose shape, an edge in a photo).
- **Output layer** — gives the final answer (unlock / keep locked; “this is a cat”; “pass / fail”).

Input layer → Hidden layer(s) → Output layer

WORKED EXAMPLE

Practical example from the source: face unlock.

Step 1 — Input layer. You look at your phone. The camera captures your face as numbers (brightness of each pixel). Those numbers enter the input layer.

Step 2 — Hidden layers. The system studies face features such as **eye distance** and **nose shape**. Early hidden nodes may detect edges and shadows; later hidden nodes combine those into “this looks like Sara’s face.” It compares them with stored data from when you first set up the phone.

Step 3 — Output layer. If the features match, the phone **unlocks**. If they do not (your brother holds the phone), it stays locked.

The same three-layer story works for an NADRA-style biometric gate at a college: camera (input) → feature matching (hidden) → open the turnstile or not (output).

REMEMBER IT

I-H-O. Input receives, Hidden thinks, Output decides. “In Hidden Out.” A neural network is a **brain-inspired maths machine**, not a copy of a living brain.

COMMON MISTAKE

Mistake: “A neural network is an actual human brain inside the computer.”

Fix: It is only **inspired by** the brain. It is mathematics: numbers, multiplications and additions running on ordinary hardware.

نیورل نیٹ ورک ایک کمپیوٹر ماڈل ہے جو ڈیٹا سے پیٹرن سیکھتا ہے۔ یہ انسانی دماغ سے متاثر ہے مگر ایک ریاضیاتی نظام کے طور پر کام کرتا ہے۔ چھوٹی اکائیاں نیورون یا نوڈ کہلاتی ہیں، جو تھوں میں جڑی ہوتی ہیں: ان پٹ تھ ڈیٹا لیتی ہے، پوشیدہ تھ سوچتی ہے، اور آؤٹ پٹ تھ فیصلہ دیتی ہے — جیسے چہرے سے فون کھولنا۔

EXAM TIP

Very common questions: "What is a neural network?" (2–3 marks), "Name its three layers and explain each with the face-unlock example" (5 marks), and "How is a neural network related to the human brain?"

Full-mark recipe: (1) definition — computer model that learns patterns from data, inspired by the brain, mathematical; (2) neurons/nodes connected across layers; (3) Input / Hidden / Output, each in one sentence; (4) walk the camera → features (eye distance, nose shape) → unlock path. Draw the three boxes if the paper asks for a diagram.

CHECK YOURSELF

1. What are the small processing units of a neural network called?
2. In face unlock, which layer studies eye distance and nose shape?
3. Is a neural network a living brain? Explain in one sentence.

Answers: 1. Neurons or nodes. 2. Hidden layers. 3. No — it is inspired by the brain but works as a mathematical computer system.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What are the small processing units of a neural network called?

3 marks. Explain Neural Networks (NN) with two clear points and one example.

5 marks. Very common questions: "What is a neural network?" (2–3 marks), "Name its three layers and explain each with the face-unlock example" (5 marks), and "How is a neural network related to the human..."

8 marks. Neural Networks (NN): 5-mark answer plus a labelled ER diagram (rectangle / oval / diamond) or the relational schema.

Answers: 1. Neurons or nodes 3. Hidden layer(s) — the "thinking" in the middle. Nodes here combine the inputs and learn features (eye distance, nose shape, an edge in a...; Output layer — gives the final answer (unlock / keep locked; "this is a cat"; "pass / fail"). 5. Use the recipe in the blue box. Model opening: A neural network is a computer model that learns patterns from data. 8. Same 5-mark body + a labelled ER diagram (rectangle / oval / diamond) or the relational schema + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Neural Networks (NN)** using the recipe in this topic. Include a labelled ER diagram (rectangle / oval / diamond) or the relational schema. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.1.3 Deep Learning (DL)

ACADEMY SESSION

Session 3 of 13 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Deep learning is a machine-learning method in which computers use multi-layer neural networks to learn complex patterns from data.

Error clinic: Mistake: “Deep learning and neural networks are two names for the same thing.” Fix: A neural network is the model (layers + nodes + connections).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Deep Learning (DL)**. Write: Deep learning is a machine-learning method in which computers use multi-layer neural networks to learn complex patterns from data.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Early layers learn simple features — edges, shapes, colours. (2) Deeper layers combine those simple features to understand complex patterns — a whole face, or a specific car model (a Cultus versus a... — + example.

5 marks: 3-mark structure + table: Neural network (the model) / Deep learning (the method) + the worked example from this topic.

LEARN IT

Deep learning is a machine-learning method in which computers use **multi-layer neural networks** to learn **complex patterns** from data.

The word “**deep**” is used because data passes through **several hidden layers** before the system produces the final output. Each layer learns a **different level of detail**:

- **Early layers** learn simple features — edges, shapes, colours.
- **Deeper layers** combine those simple features to understand complex patterns — a whole face, or a specific car model (a Cultus versus a Corolla).

A network with only one or two hidden layers is a **shallow** neural network. Deep learning is always “deep”: it needs **huge amounts of data** and **processing power**.

Neural network vs deep learning

	Neural network (the model)	Deep learning (the method)
What it is	A system/model that has layers, nodes and connections to help it learn.	A specific method that trains neural networks containing many hidden layers .
Depth	Can be simple (shallow) with just one or two hidden layers.	Always “deep,” requiring huge amounts of data and processing power to learn complex patterns.
Role	The architecture (the “machine”).	The way we train a deep version of that machine.

WORKED EXAMPLE

Real-world example from the source: photo gallery search.

A modern gallery app on a smartphone uses deep learning to recognise faces, objects or places in thousands of photos.

Step 1. During training (done by the company, using millions of images) early layers learned edges and colours; deeper layers learned “wheel”, “petal”, “minaret”.

Step 2. The trained network has already scanned your phone's photos and tagged them.

Step 3. You type “car” or “flower” in the search bar. The app instantly shows related photos because its deep neural network has already learned visual patterns from millions of training images.

A student in Hyderabad can type “Ajrak” or “cricket” and jump to those pictures without scrolling for ten minutes.

REMEMBER IT

Deep = many hidden layers. Shallow NN: 1–2 hidden layers. Deep NN: many hidden layers, huge data, strong computers. Simple features first, complex meaning later.

COMMON MISTAKE

Mistake: “Deep learning and neural networks are two names for the same thing.”

Fix: A neural network is the **model** (layers + nodes + connections). Deep learning is the **method** of training networks that have **many** hidden layers. A small NN with one hidden layer is not deep learning.

اردو میں سمجھیں

ڈیپ لرننگ مشین لرننگ کا وہ طریقہ ہے جس میں کئی پوشیدہ تہوں والے نیورل نیٹ ورک استعمال ہوتے ہیں۔ “ڈیپ” اس لیے کہ ڈیٹا کئی تہوں سے گزر کر پیچیدہ پیٹرن سیکھتا ہے: پہلی تہیں کنارے اور رنگ سیکھتی ہیں، گہری تہیں پورا چہرہ یا گاڑی کی قسم پہچانتی ہیں۔ یہ طریقہ بہت سے ڈیٹا اور طاقتور کمپیوٹنگ کا طالب ہے۔

CHECK YOURSELF

1. Why is the method called “deep” learning?
2. What do early layers learn, and what do deeper layers learn?
3. Can a neural network with one hidden layer be called deep learning?

Answers: 1. Because data passes through several hidden layers. 2. Early: simple features (edges, shapes, colours). Deeper: complex patterns (a whole face, a car model). 3. No — that is a shallow network; DL always uses many hidden layers.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Why is the method called “deep” learning?

3 marks. Explain Deep Learning (DL) with two clear points and one example.

5 marks. Write a 5-mark answer on Deep Learning (DL): definition, two points, a labelled diagram or table, and one example.

Answers: 1. Because data passes through several hidden layers 3. Early layers learn simple features — edges, shapes, colours.; Deeper layers combine those simple features to understand complex patterns — a whole face, or a specific car model (a Cultus versus a... 5. Use the recipe in the blue box. Model opening: Deep learning is a machine-learning method in which computers use multi-layer neural networks to learn complex patterns from data.

BATCH HOMEWORK

Write a 5-mark answer on **Deep Learning (DL)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.1.4 Components of Neural Networks ★ Golden

ACADEMY SESSION

Session 4 of 13 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: The components of a neural network can be understood through its layered architecture.

Error clinic: Mistake: Forgetting to add the bias, or multiplying instead of adding after the products.

Exam wording to train: Golden questions: "List the components of a neural network" (often 8 names + one line each), "What are weights and bias?", and a numerical neuron: given x , w ,...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Components of Neural Networks**. Write: The components of a neural network can be understood through its layered architecture.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The components of a neural network can be understood through its layered architecture. (2) Data enters, gets processed, and exits, with mathematical adjustments happening inside. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a labelled network: input layer → hidden layer → output layer + a one-line conclusion. Method marks are awarded for working.

LEARN IT

The components of a neural network can be understood through its **layered architecture**. Data **enters**, gets **processed**, and **exits**, with mathematical adjustments happening inside.

#	Component	Description
1	Input layer	Receives the initial raw data (for example image pixels, sound waves, text).


#	Component	Description
2	Neurons / nodes	Small processing units that receive, calculate, and pass information forward.
3	Hidden layer(s)	The layers between input and output. They process the data and learn patterns from it.
4	Weights	Numbers that show the importance or strength of connections between neurons.
5	Bias	An extra constant value added to help the model adjust its result and improve accuracy.
6	Activation function	A mathematical gate that decides whether the information is important enough to move to the next layer.
7	Output layer	Gives the final computed result, decision or prediction (for example "This is a cat").
8	Loss function	Checks the error (how much the model's answer is wrong compared with reality) so the network can correct itself.

What happens inside one neuron


Each neuron does a short calculation:

1. Multiply each input x by its weight w .
2. Add those products together, then add the **bias** b . This total is the **weighted sum** s .
3. Pass s through an **activation function**. A simple exam-friendly gate is a **threshold (step) function**: if s is at least the threshold, the neuron **fires** (output = 1); otherwise output = 0.

In symbols: $s = (x_1 \times w_1) + (x_2 \times w_2) + \dots + b$, then $y = 1$ if $s \geq \text{threshold}$, else $y = 0$.



One neuron: inputs $\times$ weights are summed, bias is added, then an activation function decides the output y .



A small neural network: 3 input nodes, 4 hidden nodes, 2 output nodes. Each line is a weighted connection.

WORKED EXAMPLE

Worked example: neuron calculation with numbers. A college in Larkana uses a tiny network to guess whether a student is ready for a test. One hidden neuron receives two inputs:

Symbol	Meaning	Value
x1	Hours studied yesterday (scaled 0 to 1)	0.8
x2	Attendance this month (scaled 0 to 1)	0.5
w1	Weight of hours studied	0.4
w2	Weight of attendance	0.6
b	Bias	0.1
threshold	Activation gate	0.5

Step 1 — weighted products.

$$x1 \times w1 = 0.8 \times 0.4 = \mathbf{0.32}$$

$$x2 \times w2 = 0.5 \times 0.6 = \mathbf{0.30}$$

Step 2 — add bias to get the weighted sum s.

$$s = 0.32 + 0.30 + 0.1 = \mathbf{0.72}$$

Step 3 — activation (threshold 0.5). Is $0.72 \geq 0.5$? **Yes**, so the neuron fires: **y = 1** (ready for the test).

Step 4 — a second student with $x1 = 0.2$ (almost no study) and $x2 = 0.3$:

$$s = (0.2 \times 0.4) + (0.3 \times 0.6) + 0.1 = 0.08 + 0.18 + 0.1 = \mathbf{0.36}$$

0.36 is **less than** 0.5, so **y = 0** (not ready). The same neuron, different inputs, different decision.

You can check the first student in Python 3:

```
x1, x2 = 0.8, 0.5
w1, w2 = 0.4, 0.6
b = 0.1
s = x1 * w1 + x2 * w2 + b
y = 1 if s >= 0.5 else 0
print(round(s, 2))
print(y)
```

OUTPUT

```
0.72
1
```

Loss function, briefly. If the true answer for the first student was actually “not ready” (true $y = 0$) but the model said 1, the loss is high. Training then slightly changes weights and bias so the next guess is closer to reality.

REMEMBER IT

Weights = importance. Bias = extra nudge. Activation = yes/no gate. Loss = how wrong. A large weight means that input matters more. Bias shifts the sum up or down so the gate can open at the right place.

COMMON MISTAKE

Mistake: Forgetting to add the bias, or multiplying instead of adding after the products.

Fix: Always **multiply first** (each x by its w), **then add** the products, **then add b** , **then** apply the activation. Write the four lines in the exam as we did above.

اردو میں سمجھیں

نیورل نیٹ ورک کے اجزاء ہیں: ان پٹ تہ، نیورون، پوشیدہ تہ، وزن (Weights)، بائیس (Bias)، ایکٹیویشن فنکشن، آؤٹ پٹ تہ اور لاس فنکشن۔ ہر نیورون ان پٹ کو وزن سے ضرب دے کر جمع کرتا ہے، بائیس جوڑتا ہے، پھر ایک گیٹ فیصلہ کرتا ہے کہ سگنل آگے جائے یا نہیں۔ وزن تعلق کی طاقت بتاتا ہے؛ لاس فنکشن غلطی ناپتا ہے تاکہ ماڈل خود درست ہو سکے۔

EXAM TIP

Golden questions: "List the components of a neural network" (often 8 names + one line each), "What are weights and bias?", and a **numerical neuron**: given x , w , b and a threshold, find s and y .

Show every arithmetic step. Underline the final y . If asked for a diagram, draw Input $\rightarrow$ Hidden $\rightarrow$ Output with circles and connecting lines, and label weights on the lines. Mention the loss function as the component that measures error so the network can correct itself.

CHECK YOURSELF

1. What do weights show?
2. Using $x_1 = 1$, $x_2 = 0$, $w_1 = 0.5$, $w_2 = 0.5$, $b = 0$, threshold = 0.4, what is y ?
3. What does the loss function check?

Answers: 1. The importance or strength of connections between neurons. 2. $s = 1 \times 0.5 + 0 \times 0.5 + 0 = 0.5$; $0.5 \geq 0.4$ so $y = 1$. 3. The error — how much the model's answer is wrong compared with reality.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What do weights show?

3 marks. Explain Components of Neural Networks with two clear points and one example.

5 marks. Golden questions: "List the components of a neural network" (often 8 names + one line each), "What are weights and bias?", and a numerical neuron: given x , w , b and a threshold, find s and y . Show...

8 marks. Components of Neural Networks: 5-mark answer plus a labelled network: input layer $\rightarrow$ hidden layer $\rightarrow$ output layer.

Answers: 1. The importance or strength of connections between neurons 3. The components of a neural network can be understood through its layered architecture.; Data enters, gets processed, and exits, with mathematical adjustments happening inside. 5. Use the recipe in the blue box. Model opening: The components of a neural network can be understood through its layered architecture. 8. Same 5-mark body + a labelled network: input layer $\rightarrow$ hidden layer $\rightarrow$ output layer + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Components of Neural Networks** using the recipe in this topic. Include a labelled network: input layer → hidden layer → output layer. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.1.5 Components of Deep Learning

ACADEMY SESSION

Session 5 of 13 · 45 minutes (first half) · paired with Future of AI, NN and DL in Pakistan.

10–45 min — this topic. Lock the definition and table for **Components of Deep Learning**. Starter (0–10) is from last class. Second half is Future of AI, NN and DL in Pakistan.

On the board: Deep learning relies on specific advanced components to achieve its high accuracy.

Error clinic: Mistake: "Deep learning is just 'a neural network'." Fix: Name the six extras: huge data, many hidden layers, automatic features, a learning algorithm...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Components of Deep Learning**. Write: Deep learning relies on specific advanced components to achieve its high accuracy.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Deep learning relies on specific advanced components to achieve its high accuracy. (2) These components differentiate it from basic machine learning. — + example.

5 marks: 3-mark structure + table: # / Component / What it means + the worked example from this topic.

LEARN IT

Deep learning relies on specific advanced components to achieve its high accuracy. These components **differentiate it from basic machine learning**.

#	Component	What it means
1	Large input data	Deep learning is " data hungry ." It needs massive datasets (thousands or millions of records) for better learning and accuracy.
2	Many hidden layers	Uses dozens or hundreds of hidden layers to learn deeper, more intricate patterns.

#	Component	What it means
3	Automatic feature learning	Unlike older models where humans had to manually highlight important features, deep learning extracts important features by itself .
4	Learning algorithm	Math routines (like backpropagation) that help the system reduce mistakes and improve learning continuously.
5	High computing power	Processing millions of data points across deep layers needs specialised, strong hardware, such as GPUs (Graphics Processing Units).
6	Training process	The model is trained again and again in loops called epochs to gradually improve its final performance.

A **GPU** was originally made for video games' graphics, but it can do thousands of small multiplications in parallel — exactly what deep networks need. An **epoch** is one full pass through the training data. Ten epochs means the model has seen every training example ten times, adjusting weights a little each time.

Backpropagation means sending the error (from the loss function) **backwards** through the layers so each weight can be nudged in the direction that reduces the next error.

WORKED EXAMPLE

Worked example: cotton-leaf disease detector for a farm in Mirpurkhas. Match each DL component.

1. **Large input data.** Researchers collect 80,000 labelled photos: healthy leaves and leaves with whitefly damage.
2. **Many hidden layers.** The network has 20 hidden layers so it can go from "green edge" to "this exact pest pattern."
3. **Automatic feature learning.** No agronomist types in "look for yellow circles." The network finds the useful spots itself.
4. **Learning algorithm.** After a wrong guess ("healthy" when it was diseased), backpropagation lowers the weights that caused the mistake.
5. **High computing power.** Training runs on a GPU workstation at a university lab in Karachi; a school laptop would take weeks.
6. **Training process.** They train for 30 epochs. After epoch 1 accuracy is 62%; after epoch 30 it is 94% on photos it has not trained on.

REMEMBER IT

D-L-A-L-G-T. Data (lots), Layers (many), Automatic features, Learning algorithm, GPU power, Training epochs. "Deep Learners Always Love Good Training."

COMMON MISTAKE

Mistake: "Deep learning is just 'a neural network'."

Fix: Name the six extras: huge data, many hidden layers, automatic features, a learning algorithm (backpropagation), GPUs, and repeated epochs. A shallow NN with a small spreadsheet is ordinary ML, not DL.

ڈیپ لرننگ کو عام مشین لرننگ سے یہ چیزیں الگ کرتی ہیں: بہت بڑا ڈیٹا، بہت سی پوشیدہ تہیں، خود بخود خصوصیات نکالنا، سیکھنے کا الگورتھم جیسے بیک پروپیگیشن (Backpropagation)، طاقتور ہارڈویئر جیسا کہ جی پی یو (GPU)، اور بار بار تربیت جسے ایپوک (Epoch) کہتے ہیں۔

CHECK YOURSELF

1. Why is deep learning called "data hungry"?
2. What is an epoch?
3. Name the hardware often used for DL, and the learning algorithm named in the source.

Answers: 1. It needs massive datasets (thousands or millions of records) for accuracy. 2. One training loop — one full pass through the training data. 3. GPUs (Graphics Processing Units); backpropagation.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Why is deep learning called "data hungry"?

3 marks. Explain Components of Deep Learning with two clear points and one example.

5 marks. Write a 5-mark answer on Components of Deep Learning: definition, two points, a labelled diagram or table, and one example.

Answers: 1. It needs massive datasets (thousands or millions of records) for accuracy. 3. Deep learning relies on specific advanced components to achieve its high accuracy.; These components differentiate it from basic machine learning. 5. Use the recipe in the blue box. Model opening: Deep learning relies on specific advanced components to achieve its high accuracy.

BATCH HOMEWORK

Write a 5-mark answer on **Components of Deep Learning** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Future of AI, NN and DL in Pakistan

ACADEMY SESSION

Session 5 of 13 · 45 minutes (second half) · paired with Components of Deep Learning.

45–75 min — this topic. Board working for **Future of AI, NN and DL in Pakistan**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Machine learning, neural networks and deep learning will play a key role in Pakistan's future.

Error clinic: Mistake: Writing only "AI will make Pakistan modern" with no sector or example.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Future of AI, NN and DL in Pakistan**. Write: Machine learning, neural networks and deep learning will play a key role in Pakistan's future.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Machine learning, neural networks and deep learning will play a key role in Pakistan's future. (2) The National AI Policy 2025 highlights how artificial intelligence is now part of national planning, focusing on innovation,... — + example.

5 marks: 3-mark structure + table: Sector / Potential impact in Pakistan + the worked example from this topic.

LEARN IT

Machine learning, neural networks and deep learning will play a key role in Pakistan's future. The **National AI Policy 2025** highlights how artificial intelligence is now part of national planning, focusing on **innovation, skill-building, ethical use and digital growth**.

Sector	Potential impact in Pakistan
Education	Smart learning systems, online tutoring, automatic assessments, and finding where students need specific help.
Healthcare	Disease detection, medical image analysis, and managing hospital data. Crucial for rural areas lacking specialist doctors.
Agriculture	Monitoring crops, predicting weather, managing irrigation, and estimating yields — highly important for Pakistan's economy.
Business and banking	Fraud detection, customer support (chatbots), market forecasting, and intelligent risk analysis.
Local languages	Speech recognition, translation and text-to-speech tools for Urdu, Sindhi and other regional languages.

To benefit from this future, Pakistan needs skilled individuals. You should focus on **programming (such as Python), mathematics, data analysis, problem-solving** and the **ethical use of technology**.

WORKED EXAMPLE

Worked example: pick a sector and write a three-line "impact paragraph" for 5 marks.

Agriculture: A cotton grower in Sanghar photographs leaves on a cheap phone. A deep-learning model trained on Pakistani crop images flags whitefly early. The farmer sprays only the affected block, saves pesticide cost, and protects yield — which matters because agriculture is a large part of Pakistan's economy.

REMEMBER IT

Five sectors: E-H-A-B-L. Education, Healthcare, Agriculture, Business/banking, Local languages. Policy words: innovation, skills, ethics, digital growth.

COMMON MISTAKE

Mistake: Writing only "AI will make Pakistan modern" with no sector or example.

Fix: Name the National AI Policy 2025, pick two sectors from the table, and give a local example (rural hospital without a specialist; Urdu/Sindhi speech tools; bank fraud).

قومی اے آئی پالیسی 2025 کے مطابق مصنوعی ذہانت پاکستان کی منصوبہ بندی کا حصہ ہے: جدت، مہارت، اخلاقی استعمال اور ڈیجیٹل ترقی۔ تعلیم، صحت، زراعت، بینکنگ اور اردو و سندھی جیسی مقامی زبانوں میں اس کے اثرات ہوں گے۔ طلبہ کو پائتھن، ریاضی، ڈیٹا کا تجزیہ، مسئلہ حل کرنا اور ٹیکنالوجی کا اخلاقی استعمال سیکھنا چاہیے۔

CHECK YOURSELF

1. Name the national policy mentioned for AI in Pakistan.
2. Why is AI in healthcare especially important for rural areas?
3. List three skills students should learn to prepare for this future.

Answers: 1. National AI Policy 2025. 2. Those areas often lack specialist doctors; AI can help with disease detection and medical image analysis. 3. Any three of: programming (Python), mathematics, data analysis, problem-solving, ethical use of technology.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name the national policy mentioned for AI in Pakistan.

3 marks. Explain Future of AI, NN and DL in Pakistan with two clear points and one example.

5 marks. Write a 5-mark answer on Future of AI, NN and DL in Pakistan: definition, two points, a labelled diagram or table, and one example.

Answers: 1. National AI Policy 2025 3. Machine learning, neural networks and deep learning will play a key role in Pakistan's future.; The National AI Policy 2025 highlights how artificial intelligence is now part of national planning, focusing on innovation,... 5. Use the recipe in the blue box. Model opening: Machine learning, neural networks and deep learning will play a key role in Pakistan's future.

BATCH HOMEWORK

Write a 5-mark answer on **Future of AI, NN and DL in Pakistan** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.2 Applications of Neural Networks and Deep Learning

ACADEMY SESSION

Session 6 of 13 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Neural networks and deep learning are widely used in modern life.

Error clinic: Mistake: Mixing up speech recognition and NLP.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Applications of Neural Networks and Deep Learning**. Write: Neural networks and deep learning are widely used in modern life.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Neural networks and deep learning are widely used in modern life. (2) Many intelligent systems use them in the background to recognise information, make predictions and support users. — + example.

5 marks: 3-mark structure + table: # / Application / What it does / Example + the worked example from this topic.

LEARN IT

Neural networks and deep learning are widely used in modern life. Many intelligent systems use them in the background to **recognise information, make predictions and support users**.

#	Application	What it does	Example
1	Image recognition	Identifies objects, faces or patterns in images. Used in security cameras, photo search and biometric locks.	Unlocking a smartphone using face recognition; a camera at a Karachi plaza matching a face with a staff list.
2	Speech recognition	Converts spoken words into digital text or commands. Deep learning helps with accents, pronunciation and voice patterns.	A student speaks to Google Assistant or Alexa to set a morning alarm; Urdu voice search on a phone.
3	Natural Language Processing (NLP)	Helps computers understand, process and respond to human language grammatically and in context. Core of chatbots, translators and AI writers.	Using Google Translate to turn a difficult English paragraph into Urdu; a bank chatbot answering in Urdu.
4	Healthcare systems	Analyse complex medical images (X-rays, CT scans, MRIs) to detect diseases early and accurately.	A hospital system highlighting abnormal patterns in a lung X-ray that might indicate pneumonia or tumours — useful at a DHQ hospital that has few radiologists.

#	Application	What it does	Example
5	Recommendation systems	Analyse past behaviour and preferences to suggest content, products or services.	A student watches computer-science videos on YouTube; the platform recommends more programming tutorials.
6	Autonomous vehicles	Self-driving cars use neural networks to process real-time camera and radar data: roads, signals, pedestrians, obstacles.	A self-driving car detects a pedestrian crossing and automatically applies the brakes.
7	Fraud detection	Banks compare current activity with previous spending patterns to catch unusual transactions.	An HBL or Meezan app flags a sudden Rs 80,000 payment from a new city at 3 a.m.
8	Assistive technologies	AI supports people with disabilities.	Speech-to-text tools for users who have difficulty typing; screen readers that speak Urdu text aloud.

WORKED EXAMPLE

Worked example: match the app to the application name — a day in Ahmed's life in Hyderabad.

1. 7:00 am — phone unlocks by face. → **Image recognition**.
2. 7:05 am — "Ok Google, set alarm for Maghrib." → **Speech recognition**.
3. 8:00 am — Google Translate helps with an English article. → **NLP**.
4. 4:00 pm — YouTube suggests a Python tutorial after he watched Chapter 5 notes. → **Recommendation system**.
5. 9:00 pm — JazzCash texts "We blocked a payment that does not match your pattern." → **Fraud detection**.

REMEMBER IT

Eight applications: I-S-N-H-R-A-F-A. Image, Speech, NLP, Healthcare, Recommendations, Autonomous vehicles, Fraud, Assistive tech. "I See New Hospitals Recommend Autonomous Fraud-Assist."

COMMON MISTAKE

Mistake: Mixing up speech recognition and NLP.

Fix: Speech recognition turns **sound into text** (or a command). NLP understands the **meaning of language** (grammar, context, translation, chat replies). You can have NLP on typed text with no microphone at all.

اردو میں سمجھیں

نیورل نیٹ ورکس اور ڈیپ لرننگ کی مشہور ایپلی کیشنز یہ ہیں: تصویر کی پہچان، آواز کی پہچان، قدرتی زبان کی پروسیسنگ (NLP)، صحت کے نظام، تجویز کرنے والے نظام، خود چلنے والی گاڑیاں، فراڈ کی نشاندہی اور معاون ٹیکنالوجیز۔ روزمرہ میں چہرے سے فون کھولنا، یوٹیوب کی تجاویز اور بینک کا مشکوک لین دین پکڑنا سب اسی خاندان سے ہیں۔

CHECK YOURSELF

1. Which application converts spoken words into text or commands?
2. Give the source example of a recommendation system.
3. How do self-driving cars use neural networks?

Answers: 1. Speech recognition. 2. YouTube recommending more programming tutorials after a student watches computer-science videos. 3. They process real-time camera and radar data to understand roads, traffic signals, pedestrians and obstacles (for example braking for a pedestrian).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which application converts spoken words into text or commands?

3 marks. Explain Applications of Neural Networks and Deep Learning with two clear points and one example.

5 marks. Write a 5-mark answer on Applications of Neural Networks and Deep Learning: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Speech recognition 3. Neural networks and deep learning are widely used in modern life.; Many intelligent systems use them in the background to recognise information, make predictions and support users. 5. Use the recipe in the blue box. Model opening: Neural networks and deep learning are widely used in modern life.

BATCH HOMEWORK

Write a 5-mark answer on **Applications of Neural Networks and Deep Learning** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.3.1 Secure Collaboration (Authentication, MFA, Access Control)

★ Golden

ACADEMY SESSION

Session 7 of 13 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Digital tools allow people to share files, attend online classes, edit documents and work together from different locations.

Error clinic: Mistake: Treating authentication and access control as the same thing.

Exam wording to train: Typical items: "Define secure collaboration", "Differentiate authentication and access control", "What is MFA/2FA?", "Explain five elements of secure..."

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Secure Collaboration (Authentication, MFA, Access Control)**. Write: Digital tools allow people to share files, attend online classes, edit documents and work together from different locations.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Collaboration is useful only when data is protected and communication remains safe. (2) Secure collaboration means using digital tools to work together in a safe, controlled and responsible way. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

8–10 marks: 5-mark structure + named threat + one mitigation + a local example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Digital tools allow people to **share files, attend online classes, edit documents and work together from different locations**. Collaboration is useful only when **data is protected** and **communication remains safe**.

Secure collaboration means using digital tools to work together in a **safe, controlled and responsible** way. It depends on several key elements.

i) Authentication / identity verification

Authentication is **confirming the identity of a user before allowing access**. Common methods:

- **Username and password**
- **PIN** (a short number code)
- **OTP — One-Time Password**, a code that works only once, usually sent by SMS or an authenticator app
- **Biometrics** — fingerprint or face

Source example: a **banking app sending an OTP to your phone before login**.

Multi-factor authentication (MFA) and two-factor authentication (2FA)

A **factor** is a category of proof:

- **Something you know** — password or PIN.
- **Something you have** — your phone, an OTP, a bank SMS.
- **Something you are** — fingerprint, face (biometrics).

Multi-factor authentication (MFA) means the system asks for **two or more different factors** before it trusts you. **Two-factor authentication (2FA)** is the common case of MFA that uses **exactly two** factors — usually password + OTP.

If a thief in another city steals only your password, MFA still blocks them because they do not have your phone (or your fingerprint).

ii) Access control

Access control decides **what an authenticated user is allowed to do**: View, Edit, Comment, Download, Share.

Authentication answers **“Who are you?”** Access control answers **“What may you do?”**

Source example: a teacher shares a Google Doc with students as **"view only"**, but gives group leaders **"edit"** permissions.

iii) Accountability and tracking

User actions are linked to **verified accounts**. You can see who opened, edited, deleted or shared a file. Example: a school **LMS** (Learning Management System) tracks which teacher uploaded an assignment and which student submitted it.

iv) Data privacy

Data privacy means protecting personal and sensitive information and using it **only for the purpose it was collected**. It involves:

- **Protection** — keeping names, numbers, marks and passwords secure.
- **Controlled sharing** — sharing only with the right people.
- **Confidentiality** — data stays private during storage and transmission.
- **Compliance** — following legal and ethical rules for data handling.

v) Safe communication / transmission

Exchanging information through digital platforms **securely**, protecting messages from unauthorised interception or wiretapping. Example: a teacher shares class instructions through an **official, encrypted LMS** rather than an open public forum or an unknown WhatsApp broadcast.

WORKED EXAMPLE

Worked example: a Class XII Google Classroom in Sukkur.

Step 1 — Authentication. Each student signs in with a school email and password. The college turns on MFA: after the password, Google sends an OTP to the student's registered Jazz/Zong number.

Step 2 — Access control. All 40 students can **view** the assignment sheet. Only the four group leaders can **edit** the shared report. Nobody except the teacher can **delete** the class materials. A student who left the college is removed from the class (access revoked).

Step 3 — Accountability. Version history shows that Ali edited paragraph 2 at 8:14 pm and that Hina submitted the PDF at 9:02 pm.

Step 4 — Privacy and safe transmission. Marks stay inside Classroom; the teacher does not post CNIC numbers or phone numbers in a public Facebook group. Traffic to Google is encrypted, unlike an open public forum.

If Ali shares his password with a cousin, authentication is broken. If the teacher gives every student "edit" on the marksheet, access control is broken even though login still works.

REMEMBER IT

A-A-A-P-S. Authentication, Access control, Accountability, Privacy, Safe transmission. MFA = at least two different factor types (know / have / are). 2FA is MFA with two factors.

COMMON MISTAKE

Mistake: Treating authentication and access control as the same thing.

Fix: Login only proves identity. After login, access control still limits View / Edit / Comment / Download / Share. A student who is authenticated must not automatically get teacher rights.

محفوظ تعاون کا مطلب ہے ڈیجیٹل ٹولز سے محفوظ، کنٹرول شدہ اور ذمہ دارانہ انداز میں ساتھ کام کرنا۔ تصدیق (Authentication) یہ جانچتی ہے کہ صارف کون ہے؛ رسائی کنٹرول (Access Control) یہ طے کرتا ہے کہ وہ کیا کر سکتا ہے (صرف دیکھنا، ترمیم، تبصرہ)۔ کثیر عنصری تصدیق (MFA) دو یا زیادہ مختلف ثبوت مانگتی ہے، جیسے پاس ورڈ اور او ٹی پی (OTP)۔ حساب دہی، ڈیٹا پرائیویسی اور محفوظ ترسیل بھی ضروری ہیں۔

EXAM TIP

Typical items: "Define secure collaboration", "Differentiate authentication and access control", "What is MFA/2FA?", "Explain five elements of secure collaboration with examples."

Write the five headings (authentication, access control, accountability, privacy, safe transmission). For MFA, name the three factor types and say that 2FA is password + OTP in a banking app. Use the Google Doc "view only vs edit" example — examiners look for it.

CHECK YOURSELF

1. What question does authentication answer, and what question does access control answer?
2. Password + OTP is an example of which idea?
3. Give the source example of access control in a Google Doc.

Answers: 1. Authentication: who are you? Access control: what may you do? 2. Two-factor / multi-factor authentication (2FA/MFA). 3. Teacher shares the document as view-only with students but gives group leaders edit permission.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

- 1 mark.** What question does authentication answer, and what question does access control answer?
- 3 marks.** Explain Secure Collaboration (Authentication, MFA, Access Control) with two clear points and one example.
- 5 marks.** Typical items: "Define secure collaboration", "Differentiate authentication and access control", "What is MFA/2FA?", "Explain five elements of secure collaboration with examples." Write the five...
- 8 marks.** Secure Collaboration (Authentication, MFA, Access Control): 5-mark answer plus named threat + one mitigation + a local example.

Answers: 1. Authentication: who are you? Access control: what may you do? 3. Collaboration is useful only when data is protected and communication remains safe.; Secure collaboration means using digital tools to work together in a safe, controlled and responsible way. 5. Use the recipe in the blue box. Model opening: Digital tools allow people to share files, attend online classes, edit documents and work together from different locations. 8. Same 5-mark body + named threat + one mitigation + a local example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Secure Collaboration (Authentication, MFA, Access Control)** using the recipe in this topic. Include named threat + one mitigation + a local example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.3.2 Data Protection (Encryption, Passwords, Backup, Firewall)

ACADEMY SESSION

Session 8 of 13 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Data protection means keeping digital information safe from unauthorised access, misuse, loss, damage or accidental deletion.

Error clinic: Mistake 1: Shifting the wrong way, or forgetting wrap-around ($X, Y, Z + 3 \rightarrow A, B, C$).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Data Protection (Encryption, Passwords, Backup, Firewall)**. Write: Data protection means keeping digital information safe from unauthorised access, misuse, loss, damage or accidental deletion.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Data protection means keeping digital information safe from unauthorised access, misuse, loss, damage or accidental deletion. (2) Second distinct point (not a repeat of the definition) — + example.

5 marks: 3-mark structure + table: Plain / S / I / N / D / H + the worked example from this topic.

LEARN IT

Data protection means keeping digital information safe from **unauthorised access, misuse, loss, damage or accidental deletion**.

1. Data encryption

Encryption changes readable data (**plaintext**) into a coded form called **ciphertext**. Unauthorised users cannot understand ciphertext without the key.

- **Symmetric encryption** — the **same key** is used to encrypt and to decrypt.
- **Asymmetric encryption** — **two keys**: a **public key** to encrypt, a **private key** to decrypt.

A simple exam cipher is the **Caesar cipher** (a symmetric substitution cipher). You shift every letter a fixed number of places along the alphabet. Shift 3 is the classic key: $A \rightarrow D, B \rightarrow E, \dots, Z \rightarrow C$ (the alphabet wraps around).

2. Strong passwords

A strong password includes **uppercase, lowercase, numbers and symbols**. It resists **brute-force** guessing (trying every possible combination). Source example: `Zk@2026#Pass`.

Weak: `ahmed123`, `pakistan`, `sindh`, your date of birth. Never reuse the same password on the college LMS and on JazzCash.

3. Backup and recovery — the 3-2-1 rule

A **backup** is a copy of data in a safe location (cloud or external drive) so you can **restore** it after hardware damage, ransomware or accidental deletion.

The **3-2-1 backup rule** is a practical standard:

- **3** copies of the data (the original plus two backups).
- **2** different types of storage media (for example laptop disk + USB, or disk + cloud).
- **1** copy **off-site** (a different building or the cloud), so a fire or theft at home does not destroy every copy.

4. Firewall and antivirus software

A **firewall** is a security **barrier** that **monitors network traffic** and **blocks suspicious internet access**. Think of it as a checkpoint on the road between your device (or college lab) and the internet.

Antivirus software detects and removes harmful software (viruses, spyware and other malware) from the **local machine**.

Firewall $\approx$ guards the **door to the network**. Antivirus $\approx$ searches **inside the house** for intruders already present.

WORKED EXAMPLE

Worked example A — Caesar cipher, shift = 3. Encrypt the plaintext **SINDH**, then decrypt the result.

Write the alphabet and count three letters forward. Wrap after Z back to A.

Plain	S	I	N	D	H
+3	V	L	Q	G	K

Ciphertext = **VLQ GK**.

Decrypt: shift each letter **back** by 3: V $\rightarrow$ S, L $\rightarrow$ I, Q $\rightarrow$ N, G $\rightarrow$ D, K $\rightarrow$ H. You recover **SINDH**.

Spaces and punctuation are often left unchanged. The same key (3) is used both ways, so Caesar is **symmetric**.

Second check: **CAT** + 3 $\rightarrow$ C $\rightarrow$ F, A $\rightarrow$ D, T $\rightarrow$ W $\rightarrow$ **FDW**.

```
def caesar(text, shift):
    result = ""
    for ch in text:
        if ch.isalpha():
            base = ord("A") if ch.isupper() else ord("a")
            result += chr((ord(ch) - base + shift) % 26 + base)
        else:
            result += ch
    return result

print(caesar("SINDH", 3))
print(caesar("VLQ GK", -3))
print(caesar("CAT", 3))
```

OUTPUT
VLQ GK
SINDH
FDW

Worked example B — 3-2-1 for Fatima's Class XII project in Hyderabad.

1. **Copy 1 (original):** project folder on her laptop hard disk.
2. **Copy 2 (different media):** the same folder on a USB drive she keeps in her bag.
3. **Copy 3 (off-site):** uploaded to Google Drive (cloud servers are not in her house).

That is 3 copies, 2 media types (internal disk + USB, with cloud as the off-site copy), 1 off-site. When her brother deletes the laptop folder, she restores from USB or Drive.

Password check: Zk@2026#Pass has uppercase Z, lowercase letters, digits 2026, and symbols @ and #. fatima has none of those extras — reject it.

3 copies → 2 media types → 1 copy off-site

REMEMBER IT

Cipher = lock the message. Password = lock the door. 3-2-1 = spare keys in three places. Firewall = gate. Antivirus = indoor search. Caesar: shift letters; same key both ways (symmetric).

COMMON MISTAKE

Mistake 1: Shifting the wrong way, or forgetting wrap-around (X, Y, Z + 3 → A, B, C).

Mistake 2: Two copies on the same laptop (Documents and Desktop) and calling it 3-2-1. That is still one disk in one house.

Fix: Count letters on a written alphabet. For backups, different media and one copy that would survive a house fire.

اردو میں سمجھیں

ڈیٹا پروٹیکشن کا مطلب ہے معلومات کو غیر مجاز رسائی، غلط استعمال، نقصان یا حادثاتی حذف سے بچانا۔ انکرپشن پڑھے جانے والے متن کو سائفر ٹیکسٹ بنا دیتی ہے؛ سیزر سائفر میں ہر حرف کو مقررہ جگہوں سے آگے سرکایا جاتا ہے۔ مضبوط پاس ورڈ میں بڑے، چھوٹے حروف، عدد اور علامات ہوں۔ 1-2-3 بیک اپ: تین کاپیاں، دو قسم کے میڈیا، ایک کاپی باہر (آف سائٹ)۔ فائر وال نیٹ ورک ٹریفک روکتی ہے؛ اینٹی وائرس مقامی نقصان دہ سافٹ ویئر ہٹاتا ہے۔

CHECK YOURSELF

1. Encrypt PAK with a Caesar shift of 3.
2. What do the 3, the 2 and the 1 stand for in 3-2-1 backup?
3. In asymmetric encryption, which key encrypts and which key decrypts?

Answers: 1. SDN (P→S, A→D, K→N). 2. 3 copies, 2 different media, 1 off-site copy. 3. Public key encrypts; private key decrypts.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Encrypt PAK with a Caesar shift of 3.

3 marks. Explain Data Protection (Encryption, Passwords, Backup, Firewall) with two clear points and one example.

5 marks. Write a 5-mark answer on Data Protection (Encryption, Passwords, Backup, Firewall): definition, two points, a labelled diagram or table, and one example.

Answers: 1. SDN (P→S, A→D, K→N) 3. Data protection means keeping digital information safe from unauthorised access, misuse, loss, damage or accidental deletion. 5. Use the recipe in the blue box. Model opening: Data protection means keeping digital information safe from unauthorised access, misuse, loss, damage or accidental deletion.

BATCH HOMEWORK

Write a 5-mark answer on **Data Protection (Encryption, Passwords, Backup, Firewall)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.4.1 Common Security Threats (Malware, Phishing, DoS) ★ Golden

ACADEMY SESSION

Session 9 of 13 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A security threat is any action, event or weakness that can harm a computer system or its data.

Error clinic: Mistake: Calling every cyber problem a “virus”, or mixing phishing with malware.

Exam wording to train: Expect “Define a security threat”, “Explain malware / phishing / DoS with examples”, and “Differentiate data theft and identity theft.” List all six threats if...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Common Security Threats (Malware, Phishing, DoS)**. Write: A security threat is any action, event or weakness that can harm a computer system or its data.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Mitigation techniques are protective measures used to prevent threats or reduce their impact. (2) This section names the common threats; later sections show how to spot them and how to reduce the damage. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + named threat + one mitigation + a local example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **security threat** is any action, event or weakness that can **harm a computer system or its data**.

Mitigation techniques are protective measures used to prevent threats or reduce their impact. This section names the common threats; later sections show how to spot them and how to reduce the damage.

#	Threat	What it is	Example
1	Malware	Harmful software designed to damage a computer, steal data, or gain unauthorised access. Includes viruses , worms , spyware , ransomware and Trojans .	Installing cracked software that secretly corrupts files, or a “free game” USB that encrypts a college lab’s coursework (ransomware).

#	Threat	What it is	Example
2	Phishing	A social-engineering trick that deceives users into sharing personal information (passwords, bank details, OTPs) using fake emails or websites that look genuine.	An SMS that looks like JazzCash or HBL asking you to "verify" by typing your OTP on a fake page.
3	Unauthorised access	Entering a system, account or file without permission. Often caused by weak passwords, shared passwords, or leaving devices unlocked.	A classmate using an unlocked lab PC to open someone else's Google Classroom.
4	Data theft / identity theft	Data theft is stealing or copying data without permission. Identity theft is using another person's stolen details (name, CNIC, bank details) to pretend to be them online and commit fraud.	A leaked list of CNICs used to open a SIM or a wallet in someone else's name.
5	Denial of Service (DoS)	A website or system is flooded with thousands of fake requests, causing it to slow down or crash, so real users cannot access the service.	Hackers flooding an online exam portal so students cannot log in on BISE result day or during an e-test.
6	Human error	Mistakes by legitimate users: accidentally deleting files, sending confidential data to the wrong email, or falling for a simple scam.	A teacher emailing the whole marksheet to the wrong parent; a student forwarding an OTP "to help the bank."

Malware types in one line each: a **virus** attaches to files and spreads when you share them; a **worm** spreads by itself across a network; **spyware** secretly watches you; **ransomware** locks your files and demands money; a **Trojan** pretends to be useful software but hides harm.

Social engineering means tricking a **person**, not breaking a lock with maths. Phishing is the most common exam example.

Phishing

Fake bank email / SMS
steals password or OTP

DoS attack

Flood of fake requests
server overload / crash

Identity theft

Stolen CNIC / details
fraud in your name

Three high-yield threats: phishing (fake messages), DoS (server overload), identity theft (stolen CNIC or bank details).

WORKED EXAMPLE

Worked example: classify the incident.

1. Bilal downloads a “cracked” Photoshop. Next day his project files are unreadable and a note asks for Bitcoin. → **Malware** (ransomware), started by cracked software.
2. Ayesha gets an email “Your Meezan account will close in 2 hours. Click here and send OTP.” The link is meezn-pk.tk, not the real bank. → **Phishing**.
3. On e-test morning the college portal spins forever; the admin graph shows 200,000 requests from one pattern of fake traffic. → **DoS**.
4. Someone opens a JazzCash wallet using Ahmed’s CNIC copy from a leaked form. → **Identity theft** (after data theft).
5. The lab assistant emails the password list to the whole staff by choosing the wrong group. → **Human error**.

REMEMBER IT

Malware = bad program. Phishing = fake message. DoS = flood. Identity theft = stolen ‘you’. Human error = honest mistake. Cracked software and unknown USBs are the usual door for malware in Pakistani colleges.

COMMON MISTAKE

Mistake: Calling every cyber problem a “virus”, or mixing phishing with malware.

Fix: A virus is only one kind of malware. Phishing is a **trick against the user**; it may not install any file at all. DoS does not steal your password — it makes the service unusable for everyone.

اردو میں سمجھیں

سیکیورٹی خطرہ وہ عمل یا کمزوری ہے جو نظام یا ڈیٹا کو نقصان پہنچائے۔ میلویئر نقصان دہ سافٹ ویئر ہے (وائرس، ورم، سپائی ویئر، رینسم ویئر، ٹروجن)۔ فٹنگ جعلی ای میل یا ویب سائٹ سے پاس ورڈ اور او ٹی پی چھینتی ہے۔ ڈو ایس (DoS) جعلی درخواستوں کی بارش سے سائٹ کریش کر دیتا ہے۔ دیگر خطرات: غیر مجاز رسائی، ڈیٹا/شناخت کی چوری، اور انسانی غلطی۔

EXAM TIP

Expect “Define a security threat”, “Explain malware / phishing / DoS with examples”, and “Differentiate data theft and identity theft.” List all six threats if the question says “common security threats.” For DoS, write: flood of fake requests → slowdown or crash → real users blocked, and quote the online exam portal. For phishing, write social engineering + fake genuine-looking email/site + passwords/OTPs.

CHECK YOURSELF

1. Name five types of malware listed in the source.
2. What does a DoS attack do to a website?
3. How is identity theft different from data theft?

Answers: 1. Viruses, worms, spyware, ransomware, Trojans. 2. Floods it with thousands of fake requests so it slows down or crashes and real users cannot access it. 3. Data theft is stealing/copying data; identity theft is using stolen personal details (name, CNIC, bank) to pretend to be that person and commit fraud.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name five types of malware listed in the source.

3 marks. Explain Common Security Threats (Malware, Phishing, DoS) with two clear points and one example.

5 marks. Expect "Define a security threat", "Explain malware / phishing / DoS with examples", and "Differentiate data theft and identity theft." List all six threats if the question says "common security..."

8 marks. Common Security Threats (Malware, Phishing, DoS): 5-mark answer plus named threat + one mitigation + a local example.

Answers: 1. Viruses, worms, spyware, ransomware, Trojans 3. Mitigation techniques are protective measures used to prevent threats or reduce their impact.; This section names the common threats; later sections show how to spot them and how to reduce the damage. 5. Use the recipe in the blue box. Model opening: A security threat is any action, event or weakness that can harm a computer system or its data. 8. Same 5-mark body + named threat + one mitigation + a local example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Common Security Threats (Malware, Phishing, DoS)** using the recipe in this topic. Include named threat + one mitigation + a local example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.4.2 Identifying Security Threats

ACADEMY SESSION

Session 10 of 13 · 45 minutes (first half) · paired with Apply Mitigation Techniques.

10–45 min — this topic. Lock the definition and table for **Identifying Security Threats**. Starter (0–10) is from last class. Second half is Apply Mitigation Techniques.

On the board: Identifying security threats means noticing signs that data or systems may be at risk.

Error clinic: Mistake: Ignoring early signs ("the PC is just old") until the ransomware note appears.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Identifying Security Threats**. Write: Identifying security threats means noticing signs that data or systems may be at risk.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Identifying security threats means noticing signs that data or systems may be at risk. (2) Early identification helps you act before serious damage occurs. — + example.

5 marks: 3-mark structure + table: Sign / indicator / What it likely means + the worked example from this topic.

LEARN IT

Identifying security threats means **noticing signs** that data or systems may be at risk. Early identification helps you act before serious damage occurs.

Sign / indicator	What it likely means
Slow performance, missing files, or random pop-ups.	Malware or background unauthorised activity.
Failed login attempts or strange login locations.	Attempted unauthorised access .
Emails urging quick action, asking for an OTP, or containing bad grammar / strange links.	Classic phishing .
Unexpected deletion, copying or movement of records.	Data theft or insider misuse.
Sudden massive spike in server requests or a very slow website.	An ongoing DoS attack.

The first line of defence is also simple behaviour: avoid **unsafe downloads, cracked software, unverified websites and infected USB drives**.

WORKED EXAMPLE

Worked example: read the signs in a college computer lab in Khairpur.

1. Three PCs show pop-ups and Word files have vanished after students used a "game" USB. → Treat as **malware**. Disconnect from the network; run antivirus; stop USB use.
2. Google Classroom emails: "Your account will be deleted in 30 minutes. Confirm password here." Link spelling is go0gle. → **Phishing**. Do not click; report to the teacher.
3. The e-portal that was fine at 8:00 am is unreachable at 8:05; the technician sees a sudden spike in requests. → Suspect **DoS**.
4. Nadia's Gmail security page shows a login from another country at 4 a.m. → **Unauthorised access** attempt. Change password; turn on MFA.

REMEMBER IT

Slow/pop-ups → malware. Odd logins → unauthorised access. Urgent OTP email → phishing. Files moving → theft. Traffic spike → DoS.

COMMON MISTAKE

Mistake: Ignoring early signs ("the PC is just old") until the ransomware note appears.

Fix: One unusual login or one OTP email is enough to investigate. Early action is cheaper than recovery.

اردو میں سمجھیں

خطرے کی جلد پہچان نقصان سے پہلے اقدام ممکن بناتی ہے۔ سست روی، غائب فائلیں یا پاپ اپ میلویئر کی علامت ہیں؛ عجیب لاگ ان غیر مجاز رسائی کی؛ فوری او ٹی پی والی ای میل فشننگ کی؛ ریکارڈ کا اچانک منتقل ہونا ڈیٹا چوری کی؛ سرور پر درخواستوں کا دھماکہ ڈو ایس کی۔ کریک سافٹ ویئر، نامعلوم یو ایس بی اور غیر تصدیق شدہ ویب سائٹوں سے بچیں۔

CHECK YOURSELF

1. Random pop-ups and missing files most likely indicate what?
2. An email with bad grammar that demands your OTP is a sign of what?
3. Name four unsafe habits that invite these threats.

Answers: 1. Malware (or background unauthorised activity). 2. Phishing. 3. Unsafe downloads, cracked software, unverified websites, infected USB drives.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Random pop-ups and missing files most likely indicate what?

3 marks. Explain Identifying Security Threats with two clear points and one example.

5 marks. Write a 5-mark answer on Identifying Security Threats: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Malware (or background unauthorised activity) 3. Identifying security threats means noticing signs that data or systems may be at risk.; Early identification helps you act before serious damage occurs. 5. Use the recipe in the blue box. Model opening: Identifying security threats means noticing signs that data or systems may be at risk.

BATCH HOMEWORK

Write a 5-mark answer on **Identifying Security Threats** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.4.3 Apply Mitigation Techniques

ACADEMY SESSION

Session 10 of 13 · 45 minutes (second half) · paired with Identifying Security Threats.

45–75 min — this topic. Board working for **Apply Mitigation Techniques**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Mitigation techniques are actions taken to prevent security threats or reduce their harmful effects once identified.

Error clinic: Mistake: “If I installed antivirus I am 100% safe.” Fix: Antivirus does not stop you from typing an OTP into a fake page.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Apply Mitigation Techniques**. Write: Mitigation techniques are actions taken to prevent security threats or reduce their harmful effects once identified.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Mitigation techniques are actions taken to prevent security threats or reduce their harmful effects once identified. (2) Technology helps, but it cannot stop all threats if the user is careless. — + example.

5 marks: 3-mark structure + table: # / Technique / How it helps + the worked example from this topic.

LEARN IT

Mitigation techniques are actions taken to **prevent** security threats or **reduce their harmful effects** once identified. Technology helps, but it cannot stop all threats if the user is careless.

#	Technique	How it helps
1	Antivirus and firewalls	Antivirus scans and removes harmful software (for example from USB drives). A firewall monitors network traffic and blocks suspicious access from the internet.
2	Strong passwords and 2FA	Complex passwords slow brute-force guessing. 2FA adds an extra layer: an OTP on your phone as well as the password.
3	Data encryption	Converts data into unreadable code during transmission. Protects passwords and sensitive data if they are intercepted.
4	Regular backups	Copies on cloud or external drives allow quick recovery after a crash, human error or ransomware.
5	User awareness (the human factor)	Training users to avoid unknown links, suspicious attachments and password sharing. The human is often the weakest link — and the strongest defence when trained.

WORKED EXAMPLE

Worked example: match each threat to a mitigation — BISE e-test week at a college in Larkana.

Threat seen	Mitigation to apply
USB games in the lab, pop-ups starting.	Scan with antivirus ; block unknown USBs; enable the lab firewall .
Phishing SMS about “update your portal password.”	User awareness : do not click; verify on the official site typed by hand. Turn on 2FA .
Fear that intercepted Wi-Fi could show passwords.	Use sites with encryption (HTTPS / encrypted LMS); never send passwords in plain WhatsApp.
Ransomware risk to project files.	Regular 3-2-1 backups so files can be restored without paying.
Shared passwords on a sticky note on the monitor.	Strong unique passwords + 2FA; remove the note; awareness session.

REMEMBER IT

Five shields: A-F, P-2, E, B, U. Antivirus+Firewall, Passwords+2FA, Encryption, Backups, User awareness. Ransomware is why backups matter: if files are locked, a clean copy brings them back.

COMMON MISTAKE

Mistake: “If I installed antivirus I am 100% safe.”

Fix: Antivirus does not stop you from typing an OTP into a fake page. Mitigation is a **set** of techniques plus human caution.

تحفظ کی تدابیر خطرات کو روکتی یا ان کا نقصان کم کرتی ہیں: اینٹی وائرس اور فائر وال، مضبوط پاس ورڈ اور دو عنصری تصدیق (2FA)، انکریپشن، باقاعدہ بیک اپ، اور صارف کی آگاہی۔ ٹیکنالوجی تب ناکام ہو جاتی ہے جب صارف نامعلوم لنک کھولے یا پاس ورڈ بانٹے۔

CHECK YOURSELF

1. How does 2FA add a layer on top of a password?
2. Why do regular backups help after ransomware?
3. What three careless behaviours should awareness training stop?

Answers: 1. It also requires an OTP sent to your phone (a second factor). 2. You can restore a clean copy instead of losing the files (or paying). 3. Unknown links, suspicious attachments, and password sharing.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. How does 2FA add a layer on top of a password?

3 marks. Explain Apply Mitigation Techniques with two clear points and one example.

5 marks. Write a 5-mark answer on Apply Mitigation Techniques: definition, two points, a labelled diagram or table, and one example.

Answers: 1. It also requires an OTP sent to your phone (a second factor) 3. Mitigation techniques are actions taken to prevent security threats or reduce their harmful effects once identified.; Technology helps, but it cannot stop all threats if the user is careless. 5. Use the recipe in the blue box. Model opening: Mitigation techniques are actions taken to prevent security threats or reduce their harmful effects once identified.

BATCH HOMEWORK

Write a 5-mark answer on **Apply Mitigation Techniques** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.5 Equity and Equal Access in Digital Collaboration

ACADEMY SESSION

Session 11 of 13 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Collaboration tools are vital for online learning and teamwork.

Error clinic: Mistake: "We gave everyone the same login, so the class is fair." Fix: Same login is equal access only.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Equity and Equal Access in Digital Collaboration**. Write: Collaboration tools are vital for online learning and teamwork.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) To use these tools fairly, all users must participate without barriers. (2) You must understand the difference between equal access and equity. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Collaboration tools are vital for online learning and teamwork. To use these tools fairly, all users must participate **without barriers**. You must understand the difference between **equal access** and **equity**.

Equal access

Giving everyone the **exact same** opportunity, tools and resources.

Example: providing every student with the **same login ID** to access a Zoom class.

Equity

Giving **additional, specific support** to users who need it, so they can reach the **same outcome**.

Example: turning on live **subtitles/captions** in Zoom specifically for a student who has hearing difficulties.

Equal access is the same starting kit. Equity is extra help so a person who faces a barrier can still finish the race with everyone else. Fair collaboration needs **both**: the same Zoom link for all (equal access) **and** captions, recorded lectures or a low-data app where needed (equity).

WORKED EXAMPLE

Worked example: one class, two ideas. A teacher in Thatta starts online classes.

Equal access: every student receives the same Zoom ID and password. That is fair in the sense of "same tool," but a student with hearing loss still cannot follow the spoken lecture, and a student in a village with a weak 2G signal cannot join video.

Equity: the teacher turns on captions, posts a low-size audio recording, and accepts the assignment as a Google Doc in the browser (not only through a heavy app). Now those two students can reach the **same learning outcome**.

REMEMBER IT

Equal = same tools. Equity = extra support for the same outcome. Same shoes for all vs a ramp for the wheelchair user.

COMMON MISTAKE

Mistake: "We gave everyone the same login, so the class is fair."

Fix: Same login is equal access only. If some students still cannot hear, see, afford a smartphone, or get electricity, you still need equity.

اردو میں سمجھیں

مساوی رسائی (Equal Access) سب کو ایک جیسے اوزار دیتی ہے، جیسے ایک ہی زوم لاگ ان۔ انصاف (Equity) ضرورت مند کو اضافی مدد دیتی ہے تاکہ وہی نتیجہ نکل سکے، جیسے سماعت کی مشکل والے طالب علم کے لیے زندہ ذیلی عنوانات (Captions)۔ منصفانہ تعاون کے لیے دونوں چاہییں۔

CHECK YOURSELF

1. Define equal access in one sentence.
2. Define equity in one sentence.
3. Why are Zoom captions an example of equity, not merely equal access?

Answers: 1. Giving everyone the exact same opportunity, tools and resources. 2. Giving additional, specific support so users who need it can reach the same outcome. 3. Because they are extra support for a student with hearing difficulties, not the same identical tool given to all.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Define equal access in one sentence.

3 marks. Explain Equity and Equal Access in Digital Collaboration with two clear points and one example.

5 marks. Write a 5-mark answer on Equity and Equal Access in Digital Collaboration: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Giving everyone the exact same opportunity, tools and resources 3. To use these tools fairly, all users must participate without barriers.; You must understand the difference between equal access and equity. 5. Use the recipe in the blue box. Model opening: Collaboration tools are vital for online learning and teamwork.

BATCH HOMEWORK

Write a 5-mark answer on **Equity and Equal Access in Digital Collaboration** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.5.1 Functions of Equity and Equal Access ★ Golden

ACADEMY SESSION

Session 12 of 13 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Equity and equal access are not slogans.

Error clinic: Mistake: Describing only captions and stopping.

Exam wording to train: Golden question: “Explain the functions of equity and equal access in digital collaboration” (5–8 marks).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Functions of Equity and Equal Access**. Write: Equity and equal access are not slogans.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) They do work in a digital classroom. (2) The source lists four functions. — + example.

5 marks: 3-mark structure + table: Function / What it does / Pakistani example + the worked example from this topic.

8–10 marks: 5-mark structure + working code with correct indentation and a short trace of one example + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Equity and equal access are not slogans. They **do work** in a digital classroom. The source lists four functions.

Function	What it does	Pakistani example
1. Providing need-based support (equity)	Help tailored to individuals.	Audio descriptions for visually impaired students; a screen reader so a blind student in Karachi can hear a digital textbook.
2. Removing barriers	Help students in remote areas attend online classes.	Mobile-friendly, low-data apps so a student in Tharparkar or the katcha areas of Sindh can join without a fibre connection.
3. Enabling active participation	Students who miss live class can still take part.	Recorded lectures so load-shedding or an internet outage in Hyderabad does not make a student fall behind.
4. Supporting different learning needs	Offer more than one format.	Videos, text notes and audio of the same Chapter 5 topic so each student learns in the way that suits them best.

WORKED EXAMPLE

Worked example: design four functions for one class WhatsApp + Classroom group in Nawabshah.

1. **Need-based support:** Ali is visually impaired — share materials as selectable text (not only photos) so a screen reader can speak them; add a short audio description of each diagram.
2. **Remove barriers:** post a 5 MB audio summary instead of a 200 MB video for students on expensive mobile data.
3. **Active participation:** upload the Zoom recording within an hour; students whose lights went out at 7 pm watch it at 11 pm.
4. **Different learning needs:** the same lesson as (a) a 12-minute video, (b) a one-page PDF, (c) an Urdu audio note.

Discussion from the source: if a teacher **only** accepts assignments via an app that needs a **high-end smartphone**, is that equal access? **No**. It creates a **hardware barrier** for lower-income students. Web-based or light apps give better access.

REMEMBER IT

Four functions: Support, Remove, Participate, Formats. “Some Rural Pupils Fail” without them — Support (need-based), Remove barriers, Participate via recordings, Formats (video/text/audio).

COMMON MISTAKE

Mistake: Describing only captions and stopping.

Fix: Examiners want all four functions. Include remote-area low-data apps, recorded lectures for power cuts, and multiple formats — these are in the Sindh source on purpose.

انصاف اور مساوی رسائی کے چار کام ہیں: ضرورت کے مطابق مدد (جیسے نابینا طالب علم کے لیے آڈیو وضاحت)، رکاوٹیں ہٹانا (دور دراز علاقوں کے لیے کم ڈیٹا والی ایپس)، فعال شرکت ممکن بنانا (لوڈ شیڈنگ کے لیے ریکارڈ شدہ لیکچر)، اور مختلف اندازِ تعلیم کی حمایت (ویڈیو، متن، آڈیو)۔ مہنگے فون والی ایپ پر صرف اسی طرح اسائنمنٹ لینا مساوی رسائی نہیں۔

EXAM TIP

Golden question: "Explain the functions of equity and equal access in digital collaboration" (5–8 marks). Write the four headings in order, one example each, and add the hardware-barrier point (high-end app vs light/web app). Another favourite: "Differentiate equal access and equity with examples" — same login vs captions.

CHECK YOURSELF

1. List the four functions of equity and equal access.
2. How do recorded lectures enable active participation in Pakistan?
3. Why is a high-end-smartphone-only assignment unfair?

Answers: 1. Need-based support; removing barriers; enabling active participation; supporting different learning needs. 2. Students who face power or internet outages can watch later and not fall behind. 3. It creates a hardware barrier for lower-income students; web-based or light apps give better access.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. List the four functions of equity and equal access.

3 marks. Explain Functions of Equity and Equal Access with two clear points and one example.

5 marks. Golden question: "Explain the functions of equity and equal access in digital collaboration" (5–8 marks). Write the four headings in order, one example each, and add the hardware-barrier point...

8 marks. Functions of Equity and Equal Access: 5-mark answer plus working code with correct indentation and a short trace of one example.

Answers: 1. Need-based support; removing barriers; enabling active participation; supporting different learning needs. 3. They do work in a digital classroom.; The source lists four functions. 5. Use the recipe in the blue box. Model opening: Equity and equal access are not slogans. 8. Same 5-mark body + working code with correct indentation and a short trace of one example + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Functions of Equity and Equal Access** using the recipe in this topic. Include working code with correct indentation and a short trace of one example. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

5.5.2 Collaboration Tools

ACADEMY SESSION

Session 13 of 13 · 45 minutes (first half) · paired with Career Opportunities.

10–45 min — this topic. Lock the definition and table for **Collaboration Tools**. Starter (0–10) is from last class. Second half is Career Opportunities.

On the board: Digital collaboration tools are online platforms that support communication, file sharing, learning and teamwork across different locations.

Error clinic: Mistake: Running the whole course only on WhatsApp.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Collaboration Tools**. Write: Digital collaboration tools are online platforms that support communication, file sharing, learning and teamwork across different locations.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Digital collaboration tools are online platforms that support communication, file sharing, learning and teamwork across different locations. (2) Second distinct point (not a repeat of the definition) — + example.

5 marks: 3-mark structure + table: Tool / Primary function and educational use + the worked example from this topic.

LEARN IT

Digital collaboration tools are online platforms that support **communication, file sharing, learning and teamwork** across different locations.

Tool	Primary function and educational use
Google Docs	Write, edit, comment and share documents in real time. Excellent for group assignments.
Zoom	Online meetings, virtual classes, screen sharing and video-based communication.
Microsoft Teams	A unified workspace for online meetings, file sharing, class groups and structured teamwork.
Google Classroom / LMS	Learning Management Systems help teachers manage lectures, distribute assignments, conduct quizzes and grade student activities.
WhatsApp	Quick class announcements, urgent reminders and instant group communication. Must be used responsibly.
Email	Formal communication, official notices, submitting large attachments, and keeping a professional written record.

Responsibly on WhatsApp means: no leaking of classmates' marks or photos, no fake forwards, and no forcing a student who has no smartphone to miss official work that was never posted on the LMS.

WORKED EXAMPLE

Worked example: choose the right tool for each job in a Hyderabad college group project.

1. Write the report together after school, from different houses. → **Google Docs** (real-time edit and comments).
2. Sunday 7 pm teacher explanation with slides. → **Zoom** or **Teams** (video + screen share). Turn on captions (equity).
3. Collect homework, quiz and grades in one place. → **Google Classroom / LMS**.
4. "Tomorrow's test is postponed — tell everyone in the next ten minutes." → **WhatsApp** class group (then repeat on Classroom so nobody is left out).
5. Send the principal a formal complaint with a 8 MB scanned letter. → **Email** (written record + attachment).

REMEMBER IT

Docs = write together. Zoom/Teams = meet. Classroom = official class hub. WhatsApp = fast but informal. Email = formal record.

COMMON MISTAKE

Mistake: Running the whole course only on WhatsApp.

Fix: WhatsApp is for quick reminders. Assignments, marks and lectures belong on an LMS so there is access control, a record, and a path that does not depend on one person's phone.

اردو میں سمجھیں

ڈیجیٹل تعاون کے اوزار مختلف مقامات سے بات چیت، فائل شیئرنگ اور ٹیم ورک چلاتے ہیں: گوگل ڈاکس مشترکہ تحریر کے لیے، زوم اور مائیکروسافٹ ٹیمز میٹنگ کے لیے، گوگل کلاس روم یا ایل ایم ایس باقاعدہ پڑھائی کے لیے، واٹس ایپ فوری اطلاع کے لیے (ذمہ داری سے)، اور ای میل رسمی ریکارڈ کے لیے۔

CHECK YOURSELF

1. Which tool is excellent for real-time group writing?
2. What four jobs does an LMS / Google Classroom help a teacher do?
3. What is email especially good for?

Answers: 1. Google Docs. 2. Manage lectures, distribute assignments, conduct quizzes, grade activities. 3. Formal communication, official notices, large attachments, and a professional written record.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which tool is excellent for real-time group writing?

3 marks. Explain Collaboration Tools with two clear points and one example.

5 marks. Write a 5-mark answer on Collaboration Tools: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Google Docs 3. Digital collaboration tools are online platforms that support communication, file sharing, learning and teamwork across different locations. 5. Use the recipe in the blue box. Model opening: Digital collaboration tools are online platforms that support communication, file sharing, learning and teamwork across different locations.

BATCH HOMEWORK

Write a 5-mark answer on **Collaboration Tools** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Career Opportunities

ACADEMY SESSION

Session 13 of 13 · 45 minutes (second half) · paired with Collaboration Tools.

45–75 min — this topic. Board working for **Career Opportunities**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: This unit covers neural networks, deep learning, secure collaboration, data protection and digital equity.

Error clinic: Mistake: Confusing an ethical hacker with a criminal hacker.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Career Opportunities**. Write: This unit covers neural networks, deep learning, secure collaboration, data protection and digital equity.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) This unit covers neural networks, deep learning, secure collaboration, data protection and digital equity. (2) Mastery of these ideas opens high-demand careers in Artificial Intelligence and Cybersecurity — including in Pakistan's banks, software... — + example.

5 marks: 3-mark structure + table: Career / What the person does + the worked example from this topic.

LEARN IT

This unit covers neural networks, deep learning, secure collaboration, data protection and digital equity. Mastery of these ideas opens high-demand careers in **Artificial Intelligence** and **Cybersecurity** — including in Pakistan's banks, software houses, universities and public projects linked to the National AI Policy 2025.

Career	What the person does
Machine Learning Engineer	Builds and trains machine-learning and neural-network models used in face recognition, NLP and recommendation systems.
Cybersecurity Analyst	Monitors systems for threats such as malware and phishing, and applies mitigation (firewalls, 2FA) to protect organisational data.
AI Researcher	Studies and develops new techniques in artificial intelligence and deep learning, often in university labs or high-tech R&D centres.
Data Privacy Officer	Ensures the organisation's data handling complies with legal privacy principles, protecting sensitive user information and secure collaboration.
Ethical Hacker	Legally tests systems and networks for vulnerabilities (penetration testing) before malicious attackers can exploit them via DoS or malware.

WORKED EXAMPLE

Worked example: match the job.

1. "Train a model that tags Urdu news headlines." → **Machine Learning Engineer**.
2. "Watch the bank's logs for phishing domains and turn on 2FA." → **Cybersecurity Analyst**.
3. "With written permission, try to break the college portal before criminals do." → **Ethical Hacker**.

REMEMBER IT

AI careers lean on Python, maths and ethics. Cyber careers lean on threats, 2FA, firewalls and careful testing. Both need clear communication.

COMMON MISTAKE

Mistake: Confusing an ethical hacker with a criminal hacker.

Fix: An ethical hacker has **permission** and reports weaknesses so they can be fixed. Attacking without permission is a crime.

اس باب سے جڑے پیشے ہیں: مشین لرننگ انجینئر، سائبر سیکیورٹی اینالسٹ، اے آئی محقق، ڈیٹا پرائیویسی آفیسر اور اخلاقی ہیکر۔ اخلاقی ہیکر اجازت کے ساتھ کمزوریاں ڈھونڈتا ہے تاکہ مجرمانہ حملے سے پہلے انہیں ٹھیک کیا جا سکے۔

CHECK YOURSELF

1. Who legally tests a network for weaknesses before attackers do?
2. Which career focuses on compliance and protecting sensitive user information?

Answers: 1. Ethical hacker. 2. Data Privacy Officer.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Who legally tests a network for weaknesses before attackers do?

3 marks. Explain Career Opportunities with two clear points and one example.

5 marks. Write a 5-mark answer on Career Opportunities: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Ethical hacker 3. This unit covers neural networks, deep learning, secure collaboration, data protection and digital equity.; Mastery of these ideas opens high-demand careers in Artificial Intelligence and Cybersecurity — including in Pakistan's banks,... 5. Use the recipe in the blue box. Model opening: This unit covers neural networks, deep learning, secure collaboration, data protection and digital equity.

BATCH HOMEWORK

Write a 5-mark answer on **Career Opportunities** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Chapter 5 Review

Chapter summary

- **ML** is a model (a trained brain) that learns from data in three steps: input, learning, prediction on new unseen data — without a hand-written rule for every case.
- **AI** $\supset$ **ML** $\supset$ **DL**: deep learning sits inside machine learning, which sits inside artificial intelligence.
- A **neural network** is a brain-inspired mathematical model of connected neurons in an input layer, hidden layer(s) and output layer (face unlock: camera $\rightarrow$ features $\rightarrow$ unlock).
- **Deep learning** trains neural networks with many hidden layers; early layers learn simple features, deeper layers learn complex patterns. It needs huge data and computing power.
- NN components: input layer, neurons, hidden layers, weights, bias, activation function, output layer, loss function. A neuron computes $s = \sum(x \times w) + b$, then an activation gate.
- DL components: large data, many hidden layers, automatic feature learning, learning algorithm (backpropagation), GPUs, training epochs. Pakistan's National AI Policy 2025 covers education, health, agriculture, banking and local languages.
- Applications: image and speech recognition, NLP, healthcare imaging, recommendations, autonomous vehicles, fraud detection, assistive tech.
- **Secure collaboration**: authentication (who), MFA/2FA (two or more factors), access control (what you may do), accountability, privacy, safe transmission.
- **Data protection**: encryption (plaintext $\rightarrow$ ciphertext; symmetric vs asymmetric; Caesar shift), strong passwords, 3-2-1 backup, firewall and antivirus.
- Threats: malware, phishing, unauthorised access, data/identity theft, DoS, human error. Spot them by pop-ups, odd logins, urgent OTP emails, missing files, traffic spikes.
- Mitigation: antivirus + firewall, strong passwords + 2FA, encryption, regular backups, user awareness.
- **Equal access** = same tools for all; **equity** = extra support for the same outcome. Functions: need-based support, removing barriers, recorded participation, multiple formats. Tools: Docs, Zoom, Teams, Classroom/LMS, WhatsApp, email.

Key terms

Term	Meaning	اردو
Artificial intelligence (AI)	The broad field in which machines perform tasks that normally need human thinking.	مصنوعی ذہانت
Machine learning (ML)	A model that learns patterns from data and then predicts on new data.	مشین لرننگ
Neural network (NN)	A brain-inspired mathematical model of connected neurons in layers.	نیورل نیٹ ورک
Deep learning (DL)	An ML method that trains neural networks with many hidden layers.	ڈیپ لرننگ
Weight	A number showing the strength or importance of a connection between neurons.	وزن (وزنِ تعلق)
Bias	An extra constant added to a neuron's sum to improve accuracy.	بائیس
Activation function	A gate that decides whether a signal is important enough to pass on.	ایکٹیویشن فنکشن
Loss function	A measure of how wrong the model's answer is compared with reality.	لاس فنکشن
Epoch	One full training pass through the dataset.	ایپوک (تربیتی چکر)
GPU	Graphics Processing Unit — specialised hardware used to train deep networks.	جی پی یو
NLP	Natural Language Processing — computers understanding and producing human language.	قدرتی زبان کی پروسیسنگ
Authentication	Confirming a user's identity before access (password, PIN, OTP, biometrics).	تصدیقِ شناخت
MFA / 2FA	Multi-/two-factor authentication: two or more different proofs of identity.	کثیر / دو عنصری تصدیق
Access control	Rules for what an authenticated user may do (view, edit, share, ...).	رسائی پر قابو
Encryption	Turning plaintext into ciphertext so unauthorised people cannot read it.	رمز کاری (انکرپشن)
Caesar cipher	A symmetric cipher that shifts letters by a fixed number of places.	سیزر سائفر

Term	Meaning	اردو
3-2-1 backup	Three copies, two media types, one copy stored off-site.	3-2-1 بیک اپ
Firewall	A barrier that monitors network traffic and blocks suspicious access.	فائر وال
Malware	Harmful software such as viruses, worms, spyware, ransomware and Trojans.	میلویئر
Phishing	Fake messages or sites that trick people into giving passwords or OTPs.	فشنگ
Denial of Service (DoS)	Flooding a service with fake requests so real users cannot use it.	سروس سے انکار
Equal access	Giving everyone the same tools and opportunity.	مساوی رسائی
Equity	Giving extra, specific support so people facing barriers reach the same outcome.	انصاف (ایکویٹی)
LMS	Learning Management System — platform for lectures, assignments, quizzes and grades.	تعلیمی نظم کا نظام

Practice: multiple choice

1. A machine-learning model works in which order?
 - a. Prediction, then data input, then learning
 - b. Data input, learning, then prediction on new data
 - c. Only prediction, with no data
 - d. Writing a separate rule for every case
2. A neural network is best described as:
 - a. a living human brain placed in a computer
 - b. a backup disk
 - c. a brain-inspired mathematical model of connected neurons
 - d. a type of firewall
3. The word "deep" in deep learning refers to:
 - a. several hidden layers through which data passes
 - b. very loud speakers
 - c. using only one neuron
 - d. storing data underground
4. In the relationship $AI \supset ML \supset DL$, the innermost set is:
 - a. AI
 - b. ML
 - c. equal access
 - d. DL
5. Weights in a neural network show the:
 - a. colour of the screen
 - b. importance or strength of connections between neurons
 - c. size of the hard disk
 - d. student's roll number
6. For $x_1 = 1$, $x_2 = 0$, $w_1 = 0.5$, $w_2 = 0.5$, $b = 0$ and threshold 0.4, the neuron output y is:
 - a. 1
 - b. 0
 - c. 0.4
 - d. 2
7. Which of the following is a component of deep learning (not of a tiny shallow network)?
 - a. Exactly one hidden layer and ten rows of data
 - b. Manual listing of every feature by a human, always
 - c. Many hidden layers, huge datasets and GPUs
 - d. A Caesar cipher
8. Unlocking a phone by matching facial features is mainly an example of:
 - a. a DoS attack
 - b. 3-2-1 backup
 - c. equal access
 - d. image recognition
9. Authentication means:
 - a. choosing who may edit a file
 - b. confirming a user's identity before allowing access
 - c. shifting letters in a cipher
 - d. flooding a server with requests
10. Password plus an OTP sent to a phone is an example of:
 - a. MFA / 2FA
 - b. a worm
 - c. a shallow neural network
 - d. equity captions

11. With a Caesar cipher of shift 3, the plaintext CAT becomes:
 - a. DBU
 - b. CAW
 - c. FDW
 - d. ZXQ
12. The 3-2-1 backup rule requires:
 - a. three passwords only
 - b. one copy on the same laptop twice
 - c. no off-site copy
 - d. three copies, two media types, one copy off-site
13. Phishing is:
 - a. a social-engineering trick using fake emails or sites to steal passwords or OTPs
 - b. a type of GPU
 - c. an activation function
 - d. a collaboration tool like Zoom
14. A Denial of Service (DoS) attack:
 - a. always steals a CNIC
 - b. floods a system with fake requests so it slows or crashes
 - c. is the same as a strong password
 - d. is a hidden layer
15. Turning on live captions in Zoom for a student with hearing difficulties is an example of:
 - a. malware
 - b. a DoS attack
 - c. equal access only, with no extra support
 - d. equity

Practice: short questions

1. Define a machine-learning model and state the three steps of how it works.
2. What is a neural network? Name its three kinds of layer and link them to face unlock.
3. Differentiate a neural network (the model) from deep learning (the method).
4. State the relationship $AI \supset ML \supset DL$ in words.
5. List eight components of a neural network. What do weights and bias do?
6. Name six components of deep learning.
7. Differentiate authentication, MFA and access control with one example each.
8. Encrypt SINDH using a Caesar cipher with shift 3. State whether this cipher is symmetric or asymmetric.
9. Define malware, phishing and DoS. Give one Pakistani-style example of each.
10. Differentiate equal access and equity. List four functions of equity and equal access.

Practice: long / problem questions

1. Explain machine learning, neural networks and deep learning. Draw and label the set diagram $AI \supset ML \supset DL$. Include the face-unlock walk-through and the photo-gallery example.
2. A neuron has inputs $x_1 = 0.8$, $x_2 = 0.5$, weights $w_1 = 0.4$, $w_2 = 0.6$, bias $b = 0.1$ and threshold 0.5. (a) Compute the weighted sum s and the output y . (b) Repeat for $x_1 = 0.2$, $x_2 = 0.3$. (c) Name all eight NN components and sketch a 3-4-2 network. (d) List the six DL components and map them onto a cotton-leaf disease detector in Sindh.
3. Describe eight applications of neural networks and deep learning with examples. Then discuss the future of AI in Pakistan with reference to the National AI Policy 2025 and five sectors.
4. What is secure collaboration? Explain authentication, MFA/2FA, access control, accountability, data privacy and safe transmission, using a Google Classroom / banking-app scenario from Pakistan.
5. Define data protection. Explain encryption (symmetric vs asymmetric) with a full Caesar-cipher working of SINDH (shift 3). Describe strong passwords, the 3-2-1 backup rule, firewall and antivirus.
6. Define a security threat. Explain malware, phishing, unauthorised access, data/identity theft, DoS and human error. Give a table of identifying signs and a matching set of mitigation techniques. End with equity versus equal access and a fair choice of collaboration tools.

Answer key

Multiple choice

1. b
2. c
3. a
4. d
5. b
6. a
7. c
8. d
9. b
10. a
11. c
12. d
13. a
14. b
15. d

Short questions — model answers

1. An ML model is the system that learns from data and gives an output — the trained brain of a program. Steps: (1) data input — massive data is given; (2) learning — it studies data and finds patterns/rules automatically; (3) prediction — after training it decides on new, unseen data.
2. A neural network is a computer model that learns patterns from data; it is inspired by the human brain but works as a mathematical system of connected neurons/nodes. Input layer receives the camera image; hidden layers study features such as eye distance and nose shape; output layer unlocks the phone if they match stored data.
3. A neural network is the model: layers, nodes and connections; it can be shallow (one or two hidden layers). Deep learning is the method of training networks that have many hidden layers, needing huge data and processing power for complex patterns.
4. Artificial intelligence is the largest set; machine learning is a part of AI; deep learning is a part of ML. All DL is ML and all ML is AI, but not all AI is ML and not all ML is DL.
5. Input layer; neurons/nodes; hidden layer(s); weights; bias; activation function; output layer; loss function. Weights show connection strength/importance. Bias is an extra constant that helps adjust the result and improve accuracy.
6. Large input data; many hidden layers; automatic feature learning; learning algorithm (e.g. backpropagation); high computing power (GPUs); training process (epochs).
7. Authentication confirms identity before access (password, PIN, OTP, biometrics — e.g. bank OTP). MFA/2FA requires two or more factor types, typically password + OTP. Access control decides what that user may do (view/edit/comment/download/share — e.g. Google Doc view-only for the class, edit for group leaders).
8. $S \rightarrow V$, $I \rightarrow L$, $N \rightarrow Q$, $D \rightarrow G$, $H \rightarrow K$ so ciphertext VLQ GK. Caesar uses the same shift key to encrypt and decrypt, so it is symmetric.
9. Malware: harmful software (viruses, worms, spyware, ransomware, Trojans) — e.g. cracked software that corrupts files. Phishing: fake genuine-looking email/SMS/site stealing passwords or OTPs — e.g. fake JazzCash OTP page. DoS: flood of fake requests that slows or crashes a service — e.g. online exam portal students cannot enter.
10. Equal access: same tools/opportunity for everyone (same Zoom login). Equity: extra specific support so people with barriers reach the same outcome (captions for hearing difficulties). Functions: need-based support; removing barriers (low-data apps for remote areas); enabling participation (recorded lectures during load-shedding); supporting different learning needs (video, text, audio).

Long questions — model answers

1. **ML**: trained-brain model; data → learn patterns → predict on unseen data; used in face unlock, speech, photo search, diagnosis, translation. **NN**: brain-inspired maths model; neurons pass information through Input, Hidden, Output; face unlock: camera (input), eye distance/nose shape (hidden), unlock (output). **DL**: ML method with multi-layer NNs; “deep” = several hidden layers; early layers: edges/shapes/colours; deeper: whole face or car model; gallery search example. **Diagram**: three nested sets labelled AI, ML, DL with AI outermost. Sentence: $DL \subset ML \subset AI$.
2. **(a)** $s = 0.8 \times 0.4 + 0.5 \times 0.6 + 0.1 = 0.32 + 0.30 + 0.1 = 0.72$; $0.72 \geq 0.5$ so $y = 1$. **(b)** $s = 0.2 \times 0.4 + 0.3 \times 0.6 + 0.1 = 0.08 + 0.18 + 0.1 = 0.36$; $0.36 < 0.5$ so $y = 0$. **(c)** Eight components as in the table; sketch three input circles, four hidden, two output, labelled layers. **(d)** Huge labelled leaf photos; many hidden layers; features learned automatically; backpropagation; GPU training; many epochs until accuracy rises — cotton pest detector for a Sindh farm.
3. Cover all eight: image recognition (face lock, cameras); speech (assistant alarm, Urdu voice); NLP (Translate, chatbots); healthcare (X-ray/CT/MRI, pneumonia); recommendations (YouTube CS videos); autonomous vehicles (brake for pedestrian); fraud (unusual bank transaction); assistive (speech-to-text). Then Policy 2025: innovation, skills, ethics, digital growth. Sectors: education (tutoring, assessments); healthcare (rural diagnosis); agriculture (crops, irrigation, yield); business/banking (fraud, chatbots); local languages (Urdu, Sindhi). Students need Python, maths, data analysis, problem-solving, ethics.
4. Secure collaboration = working together with digital tools in a safe, controlled, responsible way. Authentication: prove identity (password/PIN/OTP/biometrics); bank OTP example. MFA: two or more of know/have/are; 2FA = password + phone OTP. Access control: view/edit/comment/download/share; teacher view-only vs group-leader edit. Accountability: LMS tracks who uploaded/submitted. Privacy: protect names, marks, passwords; share only with the right people; confidentiality; legal/ethical compliance. Safe transmission: encrypted official LMS, not an open public forum. Classroom scenario: school email + MFA, role permissions, version history, no CNICs on public WhatsApp.
5. Data protection = keeping digital information safe from unauthorised access, misuse, loss, damage or accidental deletion. Encryption: plaintext → ciphertext; symmetric = same key both ways; asymmetric = public encrypt, private decrypt. Caesar shift 3: SINDH → VLQKG; decrypt by -3; wrap-around at Z. Strong password: upper, lower, number, symbol (e.g. Zk@2026#Pass) against brute force. 3-2-1: three copies, two media, one off-site (laptop + USB + Google Drive). Firewall: barrier monitoring/blocking suspicious network traffic. Antivirus: detects/removes malware on the local machine.
6. A security threat is any action, event or weakness that can harm a system or its data. Malware (cracked software); phishing (fake bank mail); unauthorised access (unlocked PC, weak/shared passwords); data theft vs identity theft (stolen CNIC used for fraud); DoS (exam portal flood); human error (wrong email, deleting files, falling for a scam). Signs table: pop-ups/missing files → malware; odd logins → unauthorised access; urgent OTP/bad grammar → phishing; records moved → theft; traffic spike → DoS. Mitigation: antivirus+firewall; strong passwords+2FA; encryption in transit; regular backups; user awareness (no unknown links, attachments, or shared passwords). Equal access vs equity; do not require a high-end phone-only app. Tools: Docs, Zoom, Teams, Classroom/LMS, WhatsApp (responsible), email (formal record).

Self-assessment: I can...

- | | |
|--|--|
| ☐ define ML and explain data input → learning → prediction. | ☐ draw $AI \supset ML \supset DL$ and give a system that belongs in each layer. |
| ☐ describe a neural network and the face-unlock I-H-O path. | ☐ compute a neuron's weighted sum and threshold output from numbers. |
| ☐ list eight NN components and six DL components. | ☐ give eight applications of NN/DL and Pakistan's AI policy sectors. |
| ☐ explain authentication, MFA/2FA and access control with examples. | ☐ encrypt a short word with a Caesar cipher and apply the 3-2-1 backup rule. |
| ☐ identify malware, phishing and DoS from signs and name mitigations. | ☐ distinguish equal access from equity and state four functions of equity. |
| ☐ choose a fair collaboration tool (Docs, Zoom, Teams, LMS, WhatsApp, email). | |

CHAPTER 6

Entrepreneurship in the Digital Age

This chapter shows you how a real problem in your home, college or bazaar can become a business idea, and how you can test that idea cheaply with paper sketches, prototypes and a Minimum Viable Product (MVP) before you spend a lot of money. You will also learn how to choose your first users, the beachhead market, and how to collect feedback honestly and safely.

اس باب میں آپ سیکھیں گے کہ روزمرہ زندگی کے کسی حقیقی مسئلے کو کاروباری خیال میں کیسے بدلا جائے، اور پروٹوٹائپ (Prototype) اور ایم وی پی (MVP) کے ذریعے کم خرچ میں اس خیال کو کیسے آزمایا جائے۔

What you will learn

- Define **entrepreneur** and **entrepreneurship** and describe the habits of an entrepreneur.
- Turn an everyday problem into a business idea using the steps Observe, Ask Users, Select One Problem, Suggest Solution, Test Early.
- Draw and explain the prototype development cycle: Design, Build, Test, Iterate.
- Identify the **riskiest assumption** of a business idea and design a small test for it.
- Choose a focused **beachhead market** for a new idea.
- Explain how digital tools (WhatsApp, Google Forms, Facebook pages, simple websites) make it cheap and quick to start and test a business.
- Define a **prototype**, list its uses, and compare low-, mid- and high-fidelity prototypes.
- Define a **Minimum Viable Product (MVP)** and state at least five differences between a prototype and an MVP.
- Prepare an MVP plan using the MVP planning checklist, and test the MVP with number-based and comment-based feedback.
- Complete a small group project and use digital tools ethically, safely and fairly.

ACADEMY CALENDAR

Academy calendar: 18 topics · 5 Golden · **14 classes of 90 minutes** + one 40-minute weekly test after this chapter.

Class	Topics	Kind	Board focus
Class 01	Entrepreneur and Entrepreneurship	Single · 90 min	An entrepreneur is a person who identifies a problem, thinks of a solution, and tries to...
Class 02	Entrepreneurship in the Digital Age	★ Golden · 90 min	Entrepreneurship in the digital age means using digital tools to start, test, improve,...
Class 03	Local Examples of Digital Entrepreneurship (Table 6.1) + From Problem to Business Idea	Paired · 90 min	Digital entrepreneurship can begin from ordinary problems.
Class 04	Prototype	★ Golden · 90 min	A prototype is an early model of a product, service, website, or app.

Class	Topics	Kind	Board focus
Class 05	Types of Prototypes	Single · 90 min	Prototypes are commonly divided into three types according to their level of detail,...
Class 06	Prototype Development Cycle	★ Golden · 90 min	Prototype development is not a one-time activity.
Class 07	Class Activity: Create a Prototype	Single · 90 min	Business idea scenario.
Class 08	Minimum Viable Product (MVP)	★ Golden · 90 min	A Minimum Viable Product (MVP) is the simplest working version of a product.
Class 09	Difference between Prototype and MVP + Identifying the Riskiest Assumption	Paired · 90 min	Prototype and MVP are related, but not the same.
Class 10	Developing an MVP + Case Study: MVP for a Canteen Pre-Order System	Paired · 90 min	To develop an MVP, the team must select only the essential features.
Class 11	Testing an MVP	Single · 90 min	MVP testing means giving the basic working version to real users and studying their...
Class 12	Beachhead Market	★ Golden · 90 min	A beachhead market is a small and focused group of first users.
Class 13	Complete Student Project + Ethical and Safe Use of Digital Tools	Paired · 90 min	You will work in groups and complete one small entrepreneurship project.
Class 14	Career Opportunities	Single · 90 min	This unit covered entrepreneurship in the digital age, turning problems into business...

Weekly test: 15 MCQ from this chapter + two 5-mark Golden questions. Mark to the recipes. Re-teach any Golden below 60% in the next starter.

گولڈن موضوع پوری کلاس لیتا ہے۔ ہفتہ وار ٹیسٹ کے بعد کمزور گولڈن دوبارہ پڑھائیں۔

6.1 Entrepreneur and Entrepreneurship

ACADEMY SESSION

Session 1 of 14 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: An entrepreneur is a person who identifies a problem, thinks of a solution, and tries to change that solution into a product or service.

Error clinic: Mistake: "Only rich people with big offices can be entrepreneurs." Fix: The source clearly says many entrepreneurs begin with a small idea and limited...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Entrepreneur and Entrepreneurship**. Write: An entrepreneur is a person who identifies a problem, thinks of a solution, and tries to change that solution into a product or service.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) They take calculated risks. A calculated risk is a risk you take after thinking about what you could lose and how to keep that loss small.... (2) They improve their idea step by step. They do not expect the first attempt to be perfect. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

An **entrepreneur** is a person who **identifies a problem, thinks of a solution, and tries to change that solution into a product or service**.

An entrepreneur does not always begin with a large company or a big office. Many begin with a small idea, limited resources, and a strong wish to solve a problem. Think of a young person in Karachi who starts by delivering home-cooked lunch boxes to a few offices, or a student in Sukkur who repairs mobile phones for neighbours. They started small.

Entrepreneurs usually show three habits:

- **They observe people and listen to their needs.** They notice what annoys people again and again.
- **They take calculated risks.** A *calculated risk* is a risk you take after thinking about what you could lose and how to keep that loss small. It is not gambling.
- **They improve their idea step by step.** They do not expect the first attempt to be perfect.

What is entrepreneurship?

Entrepreneurship is the **process** of **planning, starting, testing, and improving** a business idea. It involves **creativity, problem-solving, teamwork, communication, and calculated risk**.

Notice the difference: the *entrepreneur* is the **person**; *entrepreneurship* is the **process** that person goes through.

REMEMBER IT

Simple meaning. An entrepreneur asks: "*What problem can I solve?*" Entrepreneurship is the process of testing and improving that solution until it becomes useful for people.

Remember the three-step journey:

1. Problem → 2. Solution → 3. Product

WORKED EXAMPLE

Worked example: spotting the three steps. Ayesha lives in Larkana. Her mother and other women in the street make beautiful hand-embroidered *rillis*, but they can only sell them to visitors.

Step 1, Problem: skilled women have products but very few buyers.

Step 2, Solution: show the rillis online so buyers from other cities can see them.

Step 3, Product/Service: a Facebook page with photos, prices and a "message to order" button.

Ayesha is the **entrepreneur**. Planning the page, posting photos, seeing which designs sell, and changing prices is **entrepreneurship**.

COMMON MISTAKE

Mistake: "Only rich people with big offices can be entrepreneurs."

Fix: The source clearly says many entrepreneurs begin with a small idea and limited resources. What matters is a real problem, a useful solution, and the willingness to improve it.

اردو میں سمجھیں

کاروباری شخص (Entrepreneur) وہ ہوتا ہے جو کسی مسئلے کو پہچانتا ہے، اس کا حل سوچتا ہے اور اس حل کو کسی پراڈکٹ یا سروس میں بدلنے کی کوشش کرتا ہے۔ کاروبار شروع کرنے، آزمائے اور بہتر بنانے کے پورے عمل کو انٹرپرائیورشپ (Entrepreneurship) کہتے ہیں۔ ایسا شخص لوگوں کی بات سنتا ہے، سوچ سمجھ کر خطرہ مول لیتا ہے اور اپنے خیال کو قدم بہ قدم بہتر بناتا ہے۔

CHECK YOURSELF

1. Is "entrepreneurship" a person or a process?
2. Name the three habits of an entrepreneur given in the source.
3. What is a calculated risk?

Answers: 1. A process (planning, starting, testing and improving a business idea). 2. Observing people and listening to their needs; taking calculated risks; improving the idea step by step. 3. A risk taken after thinking carefully about the possible loss and keeping that loss small.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Is "entrepreneurship" a person or a process?

3 marks. Explain Entrepreneur and Entrepreneurship with two clear points and one example.

5 marks. Write a 5-mark answer on Entrepreneur and Entrepreneurship: definition, two points, a labelled diagram or table, and one example.

Answers: 1. A process (planning, starting, testing and improving a business idea) 3. They take calculated risks. A calculated risk is a risk you take after thinking about what you could lose and how to keep that loss small....; They improve their idea step by step. They do not expect the first attempt to be perfect. 5. Use the recipe in the blue box. Model opening: An entrepreneur is a person who identifies a problem, thinks of a solution, and tries to change that solution into a product or service.

BATCH HOMEWORK

Write a 5-mark answer on **Entrepreneur and Entrepreneurship** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.2 Entrepreneurship in the Digital Age ★ Golden

ACADEMY SESSION

Session 2 of 14 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Entrepreneurship in the digital age means using digital tools to start, test, improve, and grow a business idea.

Error clinic: Mistake: "Digital entrepreneurship means building a mobile app." Fix: An app is only one option.

Exam wording to train: Common questions: "Define entrepreneurship in the digital age", "How have digital tools changed entrepreneurship?" and "Give examples of digital..."

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Entrepreneurship in the Digital Age**. Write: Entrepreneurship in the digital age means using digital tools to start, test, improve, and grow a business idea.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) These tools may include mobile phones, social media, websites, online forms, digital payments, maps, videos, and simple apps. (2) In Pakistan you already know many of them: WhatsApp, Facebook, Instagram, TikTok, YouTube, Google Forms, Google Maps, and digital payments... — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

8–10 marks: 5-mark structure + a one-page canvas: problem, user, riskiest assumption, test + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Entrepreneurship in the digital age means using **digital tools** to **start, test, improve, and grow** a business idea.

These tools may include **mobile phones, social media, websites, online forms, digital payments, maps, videos, and simple apps**. In Pakistan you already know many of them: WhatsApp, Facebook, Instagram, TikTok, YouTube, Google Forms, Google Maps, and digital payments such as JazzCash, Easypaisa or Raast.

The power of digital tools

A digital entrepreneur **does not always need to create a complex mobile app**. Sometimes a **WhatsApp group**, a **Google Form**, a **Facebook page**, or a **simple website** is enough to test an idea.

In the past

- Large investment needed.
- Offices and shops had to be rented first.
- Long planning before anyone saw the product.
- A failed idea meant a big loss.

Today (digital age)

- A small idea can be tested **quickly**.
- Free tools: WhatsApp, Google Forms, Facebook.
- Feedback arrives in hours or days.
- If users do not like the idea, the team can **change it before spending too much money**.

WORKED EXAMPLE

Real-world relevance (from the source).

Example 1: A student selling **handmade cards through Instagram**. She posts photos of her Eid cards, people message her, and she delivers. No website, no app.

Example 2: A shopkeeper creating a **WhatsApp catalogue for Ajrak**. WhatsApp Business lets him list each Ajrak with a photo and price. Customers in Hyderabad or Karachi browse and order through chat.

Both are digital entrepreneurship **without writing a single line of code**.

Walk-through: how the Ajrak seller tests a new design cheaply.

1. He photographs 3 new Ajrak designs and adds them to the catalogue (cost: almost zero).
2. He sends the catalogue link to his customer broadcast list.
3. After one week he counts the orders per design.
4. He prints more of the design that sold most and stops the one nobody ordered.

He learned what customers want **before** printing a large stock.

REMEMBER IT

Remember "S-T-I-G": digital tools help you **Start, Test, Improve and Grow**. Think: "Start The Idea Growing."

COMMON MISTAKE

Mistake: "Digital entrepreneurship means building a mobile app."

Fix: An app is only one option. A WhatsApp group, Google Form, Facebook page or simple website is often enough, and much cheaper, to test whether people want your idea.

اردو میں سمجھیں

ڈیجیٹل دور میں انٹرپرائیورسپ کا مطلب ہے موبائل فون، سوشل میڈیا، ویب سائٹ، آن لائن فارم اور ڈیجیٹل ادائیگی جیسے ٹولز کے ذریعے کاروبار شروع کرنا، آزمانا اور بڑھانا۔ ہر بار پیچیدہ ایپ بنانا ضروری نہیں؛ واٹس ایپ گروپ یا گوگل فارم بھی کافی ہو سکتا ہے۔ اگر لوگوں کو خیال پسند نہ آئے تو زیادہ پیسہ خرچ ہونے سے پہلے اسے بدلا جا سکتا ہے۔

EXAM TIP

Common questions: "Define entrepreneurship in the digital age", "How have digital tools changed entrepreneurship?" and "Give examples of digital entrepreneurship without coding." Write the definition (start, test, improve, grow using digital tools), list 4–5 tools, give the past-versus-today contrast (big investment versus quick, cheap testing), and quote the Instagram cards and the WhatsApp Ajrak catalogue examples.

CHECK YOURSELF

1. List four digital tools that the source mentions.
2. Why is it easier to change a business idea today than in the past?
3. Give one example of digital entrepreneurship that needs no coding.

Answers: 1. Any four of: mobile phones, social media, websites, online forms, digital payments, maps, videos, simple apps. 2. Because a small idea can be tested quickly and cheaply, so if users do not like it the team can change it before spending too much money. 3. Selling handmade cards through Instagram, or a WhatsApp catalogue for Ajrak.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. List four digital tools that the source mentions.

3 marks. Explain Entrepreneurship in the Digital Age with two clear points and one example.

5 marks. Common questions: "Define entrepreneurship in the digital age", "How have digital tools changed entrepreneurship?" and "Give examples of digital entrepreneurship without coding." Write the definition...

8 marks. Entrepreneurship in the Digital Age: 5-mark answer plus a one-page canvas: problem, user, riskiest assumption, test.

Answers: 1. Any four of: mobile phones, social media, websites, online forms, digital payments, maps, videos, simple apps. 3. These tools may include mobile phones, social media, websites, online forms, digital payments, maps, videos, and simple apps.; In Pakistan you already know many of them: WhatsApp, Facebook, Instagram, TikTok, YouTube, Google Forms, Google... 5. Use the recipe in the blue box. Model opening: Entrepreneurship in the digital age means using digital tools to start, test, improve, and grow a business idea. 8. Same 5-mark body + a one-page canvas: problem, user, riskiest assumption, test + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Entrepreneurship in the Digital Age** using the recipe in this topic. Include a one-page canvas: problem, user, riskiest assumption, test. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Local Examples of Digital Entrepreneurship (Table 6.1)

ACADEMY SESSION

Session 3 of 14 · 45 minutes (first half) · paired with From Problem to Business Idea.

10–45 min — this topic. Lock the definition and table for **Local Examples of Digital Entrepreneurship (Table 6.1)**. Starter (0–10) is from last class. Second half is From Problem to Business Idea.

On the board: Digital entrepreneurship can begin from ordinary problems.

Error clinic: Important: A digital business idea should not be selected only because it sounds modern.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Local Examples of Digital Entrepreneurship (Table 6.1)**. Write: Digital entrepreneurship can begin from ordinary problems.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Digital entrepreneurship can begin from ordinary problems. (2) The examples below are close to the context of Sindh and Pakistan, where many students, parents, and small service providers already use... — + example.

5 marks: 3-mark structure + table: Problem / Digital Idea / Possible First Users / Urdu Context + the worked example from this topic.

LEARN IT

Digital entrepreneurship can begin from **ordinary problems**. The examples below are close to the context of Sindh and Pakistan, where many students, parents, and small service providers already use mobile phones.

Problem	Digital Idea	Possible First Users	Urdu Context
Parents miss college notices.	WhatsApp notice and reminder service.	Parents of first-year students.	والدین تک کالج کے نوٹس پہنچانے کے لیے واٹس ایپ سروس۔
Small embroidery shop has few customers.	Simple catalogue with order form on Facebook or WhatsApp.	Customers in the same city.	کڑھائی کی دکان کے لیے واٹس ایپ کیٹلاگ۔
Students forget test dates.	Google Calendar guide or simple reminder app.	Grade XII students.	ٹیسٹ کی تاریخیں یاد دلانے والی ایپ یا کیلنڈر۔
Canteen has long queues during break.	Pre-order form for snacks.	Students and teachers.	کینٹین کے لیے پری آرڈر فارم۔

Read each row from left to right: a **problem** → a **simple digital idea** → a **small group of first users**. You will see these same examples again later in the chapter (the canteen pre-order system becomes a full case study).

WORKED EXAMPLE

Worked example: adding your own row. Follow the same pattern for a new local problem.

Problem	Digital Idea	Possible First Users
Students in a Mirpurkhas college lose water bottles, calculators and ID cards and never find them.	Lost-and-found Google Form plus a WhatsApp group where found items are posted with a photo.	Students of one college.

Check: Is it a **real** problem? Yes, it happens every week. Is the idea **simple**? Yes, a form and a group. Are the first users **reachable**? Yes, they are in the same college.

COMMON MISTAKE

Important: A digital business idea should **not** be selected only because it sounds modern. It should solve a **real problem for real users**. If the problem is weak, the business idea will also be weak.

For example, "an AI app that chooses your shirt colour" sounds modern, but if nobody actually struggles with that, nobody will use it.

REMEMBER IT

Think "Problem first, tool second." Start with the pain, not with the technology.

اردو میں سمجھیں

جدول 6.1 بتاتی ہے کہ ڈیجیٹل کاروبار عام مسائل سے شروع ہو سکتا ہے، جیسے والدین کا کالج نوٹس نہ دیکھ پانا، کڑھائی کی دکان پر کم گاہک، ٹیسٹ کی تاریخ بھول جانا یا کینٹین پر لمبی قطار۔ کوئی خیال صرف اس لیے نہ چنیں کہ وہ جدید لگتا ہے؛ اسے حقیقی لوگوں کا حقیقی مسئلہ حل کرنا چاہیے۔

CHECK YOURSELF

1. In Table 6.1, what digital idea is suggested for a small embroidery shop?
2. Who are the possible first users of the canteen pre-order form?
3. Why should an idea not be chosen only because it sounds modern?

Answers: 1. A simple catalogue with an order form on Facebook or WhatsApp. 2. Students and teachers. 3. Because it must solve a real problem for real users; a weak problem gives a weak business idea.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. In Table 6.1, what digital idea is suggested for a small embroidery shop?

3 marks. Explain Local Examples of Digital Entrepreneurship (Table 6.1) with two clear points and one example.

5 marks. Write a 5-mark answer on Local Examples of Digital Entrepreneurship (Table 6.1): definition, two points, a labelled diagram or table, and one example.

Answers: 1. A simple catalogue with an order form on Facebook or WhatsApp 3. Digital entrepreneurship can begin from ordinary problems.; The examples below are close to the context of Sindh and Pakistan, where many students, parents, and small service providers already use... 5. Use the recipe in the blue box. Model opening: Digital entrepreneurship can begin from ordinary problems.

BATCH HOMEWORK

Write a 5-mark answer on **Local Examples of Digital Entrepreneurship (Table 6.1)** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.3 From Problem to Business Idea

ACADEMY SESSION

Session 3 of 14 · 45 minutes (second half) · paired with Local Examples of Digital Entrepreneurship (Table 6.1).

45–75 min — this topic. Board working for **From Problem to Business Idea**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: A good business idea usually starts from observing daily life.

Error clinic: Mistake 1: Choosing a huge problem ("fix traffic in Karachi").

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **From Problem to Business Idea**. Write: A good business idea usually starts from observing daily life.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Who faces this problem? (2) How often does it happen? — + example.

5 marks: 3-mark structure + table: Step / What Students Do / Example + the worked example from this topic.

LEARN IT

A good business idea usually starts from **observing daily life**. Look around your home, college, market, village, or city and ask these simple questions:

1. **What problem do people face?**
2. **Who faces this problem?**
3. **How often does it happen?**
4. **What do people currently do to solve it?**
5. **Can technology help in a simple way?**

A short way to remember them: **What? Who? How often? Current fix? Tech help?**

WORKED EXAMPLE

Example scenario (from the source): study material before exams.

Students cannot find study material before exams. The quick answer is "students are careless", but that is not the real issue.

Apply the five questions:

1. **What problem?** Students cannot find notes before exams.
2. **Who?** Students of a class or college.
3. **How often?** Before every test and exam.
4. **Current fix?** Notes are shared in many places: WhatsApp, email, photocopies, and class groups. Students search all of them.
5. **Tech help?** Yes: a simple **subject-wise notes organizer** where all files are placed in one location (for example, one shared Google Drive folder per subject).

The real problem is **scattered notes**, and the idea solves exactly that.

Scope of the problem

Avoid choosing **very large problems** at the start, such as "improving the whole education system". A better problem is **smaller and clear**, such as helping Grade XII students track **practical file submission dates**. Smaller problems are **easier to test and improve**.

Table 6.2: From problem to idea

The journey from observing a problem to creating an idea follows a structured path.

Step	What Students Do	Example
Observe	Notice repeated problems around home, college, or market.	Students forget practical file dates.
Ask Users	Talk to people who face the problem.	Ask five classmates how they remember deadlines.
Select One Problem	Choose one clear problem only.	Practical file reminder.
Suggest Solution	Think of a simple digital or paper-based solution.	Reminder form or app screen.
Test Early	Show the idea to users before final development.	Ask classmates if they will use it.

After this, the idea moves along the full path that the rest of this chapter follows:



REMEMBER IT

Mnemonic for Table 6.2: "Only Ask Simple Solutions Today": Observe, Ask users, Select one problem, Suggest solution, Test early.

COMMON MISTAKE

Mistake 1: Choosing a huge problem ("fix traffic in Karachi"). **Fix:** Narrow it ("help students of one college know when their van will arrive").

Mistake 2: Skipping "Ask Users" and guessing what people need. **Fix:** Talk to at least five real people who face the problem.

اردو میں سمجھیں

اچھا کاروباری خیال روزمرہ زندگی کے مشاہدے سے شروع ہوتا ہے۔ پوچھیں: مسئلہ کیا ہے، کس کو ہے، کتنی بار ہوتا ہے، لوگ ابھی کیا کرتے ہیں، اور کیا ٹیکنالوجی آسان طریقے سے مدد کر سکتی ہے؟ شروع میں چھوٹا اور واضح مسئلہ چنیں، کیونکہ اسے آزمانا اور بہتر بنانا آسان ہوتا ہے۔

CHECK YOURSELF

1. Write the five steps of Table 6.2 in order.
2. Why is "improving the whole education system" a poor first problem?
3. In the study-material example, what is the real problem?

Answers: 1. Observe, Ask Users, Select One Problem, Suggest Solution, Test Early. 2. It is too large and unclear; small, clear problems are easier to test and improve. 3. Notes are scattered in many places (WhatsApp, email, photocopies, class groups), not that students are careless.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Write the five steps of Table 6.2 in order.

3 marks. Explain From Problem to Business Idea with two clear points and one example.

5 marks. Write a 5-mark answer on From Problem to Business Idea: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Observe, Ask Users, Select One Problem, Suggest Solution, Test Early 3. Who faces this problem?; How often does it happen? 5. Use the recipe in the blue box. Model opening: A good business idea usually starts from observing daily life.

BATCH HOMEWORK

Write a 5-mark answer on **From Problem to Business Idea** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.4 Prototype ★ Golden

ACADEMY SESSION

Session 4 of 14 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A prototype is an early model of a product, service, website, or app.

Error clinic: Mistake: Thinking a prototype must work or must look beautiful.

Exam wording to train: Expect "Define prototype and write its benefits" (3–5 marks).

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Prototype**. Write: A prototype is an early model of a product, service, website, or app.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) It shows how the idea may look or work. (2) It is NOT the final product. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a one-page canvas: problem, user, riskiest assumption, test + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **prototype** is an **early model** of a product, service, website, or app. It shows **how the idea may look or work**. It is **NOT the final product**. It is made to **test the idea and collect feedback**.

Think of the clay model an architect makes before building a house, or the sample *kameez* a tailor stitches before making 50 for a shop. The model lets people say "make this bigger" or "move that here" before real money is spent.

Why is a prototype useful?


A prototype helps students and entrepreneurs **explain their idea clearly**, because users can **see something** instead of only listening to words.

- **It makes the idea visible.**
- **It helps the team find mistakes early.** Users can point out if a button is hard to find, if a screen has too much text, or if a feature is missing.
- **It saves time and money** before final coding begins. Fixing a pencil sketch takes a minute; fixing finished code can take days.

What form can a prototype take?

A prototype may be a **paper sketch**, a **cardboard model**, a **clickable PowerPoint**, a **Canva design**, a **Figma wireframe**, a **simple website layout**, or a **sample service process chart**. A *wireframe* is a simple outline drawing of a screen that shows where things go (boxes, buttons, text) without colours or pictures.

For example, for a **canteen pre-order system**, students can just **draw the screens on paper**.



A paper prototype of a canteen pre-order system: three hand-drawn screens joined by arrows (select item → enter name → collect order).

WORKED EXAMPLE

Worked example: how a paper prototype finds a mistake early. Bilal's team in a Nawabshah college draws the three screens above on A4 paper.

1. They hand screen 1 to a classmate and say, "Order a samosa."
2. The classmate looks for a quantity box and cannot find one. She asks, "What if I want two?"
3. The team notes: **feature missing: quantity**.
4. They add a small "Qty: []" box with a pencil in 30 seconds.

If they had already coded an app, adding quantity would have meant changing the database, the screen and the order list. The prototype **saved time and money**.

REMEMBER IT

Prototype = "practice model". It is like a rough draft of an essay: you show it, get corrections, and rewrite it before the final copy.

COMMON MISTAKE

Mistake: Thinking a prototype must work or must look beautiful.

Fix: A prototype only has to make the idea **visible** so users can react. A pencil sketch is a valid prototype.

پروٹوٹائپ (Prototype) کسی پراڈکٹ، سروس، ویب سائٹ یا ایپ کا ابتدائی نمونہ ہوتا ہے جو دکھاتا ہے کہ خیال کیسا نظر آئے گا یا کیسے کام کرے گا۔ یہ حتمی پراڈکٹ نہیں ہوتا بلکہ خیال کو آزمانے اور رائے (Feedback) لینے کے لیے بنایا جاتا ہے۔ یہ کاغذ کا خاکہ، گتے کا ماڈل، پاورپوائنٹ یا فگما (Figma) ڈیزائن بھی ہو سکتا ہے، اور اس سے غلطیاں جلد پکڑی جاتی ہیں اور وقت اور پیسہ بچتا ہے۔

EXAM TIP

Expect "Define prototype and write its benefits" (3–5 marks). Write: (1) definition with the words *early model*, *not the final product*, *test the idea and collect feedback*; (2) three benefits: makes the idea visible, finds mistakes early, saves time and money; (3) forms it can take (paper sketch, cardboard model, clickable PowerPoint, Canva, Figma wireframe); (4) the canteen paper-screens example.

CHECK YOURSELF

1. Is a prototype the final product?
2. Name four forms a prototype can take.
3. Give two kinds of problems users can point out by looking at a prototype.

Answers: 1. No. It is an early model made to test the idea and collect feedback. 2. Any four: paper sketch, cardboard model, clickable PowerPoint, Canva design, Figma wireframe, simple website layout, sample service process chart. 3. Any two: a button is hard to find, a screen has too much text, a feature is missing.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Is a prototype the final product?

3 marks. Explain Prototype with two clear points and one example.

5 marks. Expect "Define prototype and write its benefits" (3–5 marks). Write: (1) definition with the words *early model*, *not the final product*, *test the idea and collect feedback*; (2) three benefits: makes...

8 marks. Prototype: 5-mark answer plus a one-page canvas: problem, user, riskiest assumption, test.

Answers: 1. No. It is an early model made to test the idea and collect feedback. 3. It shows how the idea may look or work.; It is NOT the final product. 5. Use the recipe in the blue box. Model opening: A prototype is an early model of a product, service, website, or app. 8. Same 5-mark body + a one-page canvas: problem, user, riskiest assumption, test + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Prototype** using the recipe in this topic. Include a one-page canvas: problem, user, riskiest assumption, test. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.5 Types of Prototypes

ACADEMY SESSION

Session 5 of 14 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Prototypes are commonly divided into three types according to their level of detail, called fidelity.

Error clinic: Mistake: Starting with a high-fidelity prototype or a full app because it "looks professional".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Types of Prototypes**. Write: Prototypes are commonly divided into three types according to their level of detail, called fidelity.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Fidelity means how close the prototype is to the final product. (2) Low fidelity = far from final; high fidelity = very close to final. — + example.

5 marks: 3-mark structure + table: Type / Meaning / Best Use / Example + the worked example from this topic.

LEARN IT

Prototypes are commonly divided into **three types** according to their level of detail, called **fidelity**.

Fidelity means how close the prototype is to the final product. Low fidelity = far from final; high fidelity = very close to final.

6.5.1 Low-Fidelity Prototype

A **quick and rough** model made at the **very beginning**. It is **drawn on paper**. It does **not focus on colours or fonts**. It shows the **main idea and flow** (which screen comes after which). It is **very suitable for students** because it is **cheap, fast, and easy to change**.

6.5.2 Mid-Fidelity Prototype

Clearer than a paper sketch. It is created in **PowerPoint, Canva, or Figma**. It shows screens and **navigation** in a more organised way, but **without final graphics**. It is useful to **test screen-to-screen navigation**, for example by linking slides so that clicking "Next" opens the next screen.

6.5.3 High-Fidelity Prototype

Looks **very close to the final product**. It includes **realistic colours, buttons, sample data, and working features**. It **takes more time** and should **only be created after the basic idea is tested**.

Comparison of prototype types

For most school and college projects, you should **begin with a low-fidelity prototype**. A common mistake is to start building a full app before knowing whether users need it. A rough prototype protects you from this mistake.

Table 6.3: Types of prototypes

Type	Meaning	Best Use	Example
Low-Fidelity	A quick and rough model of the idea.	Very early testing.	Hand-drawn app screens for homework reminder.
Mid-Fidelity	A clearer model that shows layout and flow.	Testing navigation.	Clickable screens in PowerPoint or Figma.
High-Fidelity	A detailed model close to the final product.	Testing realistic experience.	Working demo of a small order form website.

Low-Fi (Paper)



Mid-Fi (PowerPoint)



High-Fi (Figma/HTML)

Extra comparison to help you revise:

Feature	Low-Fidelity	Mid-Fidelity	High-Fidelity
Tool	Paper and pencil	PowerPoint, Canva, Figma	Figma (detailed), HTML
Colours and fonts	No	Not final	Realistic
Clickable?	No (you move papers by hand)	Yes, basic links	Yes, with working features
Cost and time	Lowest, fastest	Medium	Highest, slowest
Easy to change?	Very easy	Fairly easy	Harder
When	Very beginning	After the flow is agreed	Only after the basic idea is tested

WORKED EXAMPLE

Worked example: one idea, three fidelities. Idea: a Homework Reminder for a college in Jacobabad.

1. **Low-fi:** Sana draws three screens on paper in 15 minutes: "Today", "Add homework", "Reminder". Classmates point at the drawings to "use" them.
2. **Mid-fi:** After feedback, she makes three PowerPoint slides with grey boxes and links them with hyperlinks, so tapping "Add" opens the Add slide. Now she tests whether people can move between screens easily.
3. **High-fi:** Once users clearly want it, she builds a small HTML page with real colours, a working form and sample homework data.

Each step costs more, so she only moves up when the previous step proves the idea is worth it.

REMEMBER IT

Fidelity = "faithfulness" to the final product. Remember **Paper → PowerPoint → Polished** (low → mid → high).

COMMON MISTAKE

Mistake: Starting with a high-fidelity prototype or a full app because it "looks professional".

Fix: Begin with low fidelity. If users do not need the idea, you have lost only paper and an hour, not weeks of work.

اردو میں سمجھیں

فیدلیٹی (Fidelity) کا مطلب ہے کہ پروٹوٹائپ حتمی پراڈکٹ سے کتنا ملتا جلتا ہے۔ لو فیدلیٹی کاغذ پر بنایا گیا سستا اور جلدی بننے والا خاکہ ہے؛ مڈ فیدلیٹی پاورپوائنٹ، کینوا یا فگما میں بنتا ہے اور اسکرینوں کے درمیان آنا جانا (Navigation) دکھاتا ہے؛ ہائی فیدلیٹی بالکل اصل پراڈکٹ جیسا لگتا ہے اور اسے بنیادی خیال آزمانے کے بعد ہی بنانا چاہیے۔

CHECK YOURSELF

1. What does "fidelity" mean?
2. Which type of prototype is best for testing navigation?
3. Why should students begin with low fidelity?

Answers: 1. How close the prototype is to the final product. 2. Mid-fidelity (e.g. clickable screens in PowerPoint or Figma). 3. It is cheap, fast and easy to change, and it protects them from building a full app before knowing whether users need it.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What does "fidelity" mean?

3 marks. Explain Types of Prototypes with two clear points and one example.

5 marks. Write a 5-mark answer on Types of Prototypes: definition, two points, a labelled diagram or table, and one example.

Answers: 1. How close the prototype is to the final product 3. Fidelity means how close the prototype is to the final product.; Low fidelity = far from final; high fidelity = very close to final. 5. Use the recipe in the blue box. Model opening: Prototypes are commonly divided into three types according to their level of detail, called fidelity.

BATCH HOMEWORK

Write a 5-mark answer on **Types of Prototypes** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.6 Prototype Development Cycle ★ Golden

ACADEMY SESSION

Session 6 of 14 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Prototype development is not a one-time activity.

Error clinic: Mistake 1: Drawing the stages as a straight line that ends at "Iterate".

Exam wording to train: A favourite long question: "Explain the prototype development cycle with a diagram." Draw the four boxes in a circle with arrows, write one or two lines for...

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Prototype Development Cycle**. Write: Prototype development is not a one-time activity.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).


3 marks: definition + two points — (1) A prototype is created, tested, improved, and tested again. (2) This repeating process is called iteration. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a one-page canvas: problem, user, riskiest assumption, test + a one-line conclusion. Method marks are awarded for working.

LEARN IT

Prototype development is **not a one-time activity**. A prototype is **created, tested, improved, and tested again**. This repeating process is called **iteration**. The main stages are **Design, Build, Test, and Iterate**.



The prototype development cycle: Design → Build → Test → Iterate, then back to Design.

Stage	What happens
1. Design	Understand the problem and plan the solution. Decide what the prototype should show (e.g. screen flow, features).
2. Build	Create the first version (physical or digital). The aim is not beauty; the aim is to make the idea visible.
3. Test	Show the prototype to users. Observe what they understand and what they find difficult.
4. Iterate	Improve the prototype based on user feedback. Remove unnecessary parts and add missing features.

WORKED EXAMPLE

Worked example: two rounds of the cycle. A team in Thatta wants a WhatsApp catalogue for a local Ajrak shop.

Round 1

- **Design:** The problem is that customers do not know which designs and prices are available. Plan: one page per design with photo, price and an "Order" message.
- **Build:** They make a paper booklet with 6 hand-drawn "catalogue pages".
- **Test:** They show it to 5 customers. Three ask, "Is this single or double-sided Ajrak? What size?"
- **Iterate:** They add size and type to every page.

Round 2

- **Design:** Add the size and type fields, and a delivery note.
- **Build:** They make the catalogue in WhatsApp Business with real photos.
- **Test:** 5 new customers browse it. Now nobody asks about size; one says the delivery charge is unclear.
- **Iterate:** They add "Delivery in Thatta: Rs 100" to each item.

Each round produces a clearer version, because each change comes from real feedback.

REMEMBER IT

Mnemonic: "Do Big Things Iteratively" = Design, Build, Test, Iterate. And remember the arrow at the end goes **back to Design**: it is a **cycle**, not a line.

COMMON MISTAKE

Mistake 1: Drawing the stages as a straight line that ends at "Iterate". **Fix:** Always draw a loop with an arrow from Iterate back to Design.

Mistake 2: Making the Build stage beautiful. **Fix:** The source says "The aim is not beauty; the aim is to make the idea visible."

اردو میں سمجھیں

پروٹوٹائپ ایک ہی بار میں نہیں بنتا؛ اسے بنایا، آزمایا، بہتر کیا اور دوبارہ آزمایا جاتا ہے۔ اس بار بار دہرانے کے عمل کو **ٹریشن** (Iteration) کہتے ہیں۔ چار مراحل ہیں: ڈیزائن (مسئلہ سمجھ کر حل کی منصوبہ بندی)، بلڈ (پہلا نمونہ بنانا)، ٹیسٹ (صارفین کو دکھانا) اور **ٹریت** (رائے کی بنیاد پر بہتری)۔

EXAM TIP

A favourite long question: "Explain the prototype development cycle with a diagram." Draw the four boxes in a **circle** with arrows, write one or two lines for each stage using the source's words, define **iteration**, and finish with a short example (e.g. the ClassBuddy activity in 6.7). Marks are often lost for drawing a straight line instead of a cycle.

CHECK YOURSELF

1. What is iteration?
2. At which stage do you observe what users find difficult?
3. What is the aim of the Build stage?

Answers: 1. The repeating process of creating, testing, improving and testing a prototype again. 2. The Test stage. 3. To make the idea visible (not to make it beautiful).

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. What is iteration?

3 marks. Explain Prototype Development Cycle with two clear points and one example.

5 marks. A favourite long question: "Explain the prototype development cycle with a diagram." Draw the four boxes in a circle with arrows, write one or two lines for each stage using the source's words,...

8 marks. Prototype Development Cycle: 5-mark answer plus a one-page canvas: problem, user, riskiest assumption, test.

Answers: 1. The repeating process of creating, testing, improving and testing a prototype again. 3. A prototype is created, tested, improved, and tested again.; This repeating process is called iteration. 5. Use the recipe in the blue box. Model opening: Prototype development is not a one-time activity. 8. Same 5-mark body + a one-page canvas: problem, user, riskiest assumption, test + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Prototype Development Cycle** using the recipe in this topic. Include a one-page canvas: problem, user, riskiest assumption, test. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.7 Class Activity: Create a Prototype

ACADEMY SESSION

Session 7 of 14 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: Business idea scenario.

Error clinic: Mistake: Feeling that negative feedback means the prototype "failed", or changing the design for every single comment.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Class Activity: Create a Prototype**. Write: Business idea scenario.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) A group of students wants to design a simple "Homework Helper" or "ClassBuddy" reminder system. (2) The team will not immediately build a complete mobile app. — + example.

5 marks: 3-mark structure + table: Finding / Meaning / Design Decision + the worked example from this topic.

LEARN IT

Business idea scenario. Students often forget **homework deadlines, test dates, and required class items**. A group of students wants to design a simple "**Homework Helper**" or "**ClassBuddy**" reminder system.

The team will **not** immediately build a complete mobile app. They will first **understand the problem, draw a low-fidelity prototype, test it with classmates, and improve it**. This activity is the development cycle of 6.6 in action.

1. Understand → 2. Draw low-fi → 3. Test → 4. Analyse feedback → 5. Improve

Step 1: Understand the problem

The team **interviews ten students**. They find that **7 out of 10** students (that is 70%) forget at least one task in a week. Students want **reminders before leaving home**, and some prefer a **very simple design**.

Table 6.4: Understanding user needs

Finding	Meaning	Design Decision
7 out of 10 forget tasks.	The problem is common.	App should show a daily task list.
Reminders needed before leaving home.	Reminder time is important.	Add morning notification option.
Students want simple apps.	Design must be simple.	Use large buttons and clear labels.

Step 2: Draw a low-fidelity prototype

The team draws **three screens on paper**: (1) **Today's classes**, (2) **Add homework**, (3) **Show reminder**. **Arrows** show how a user moves from one screen to another.

Step 3: Test the prototype

The team gives the paper screens to **five classmates**. The **observer watches silently** to see if users can understand the design by themselves. Users are given one task: **"add one homework task"**.

Step 4: Analyse feedback

The team looks for **repeated problems** in the feedback to identify what actually needs fixing.

Table 6.5: Changing feedback into improvement

User Feedback	Problem Identified	Improvement
"I cannot quickly find Add Homework."	Button is not visible.	Make Add Homework button larger and centre it.
"I want reminders by subject."	Reminder is too general.	Add subject name and due date fields.
"I want to see all tasks for the week."	Only daily view is not enough.	Add a 'Weekly View' button.

Step 5: Improve the prototype

The team **redraws the home screen** with a **larger Add Homework button**, a **subject list**, and a **weekly view**. This second version is clearer because it is based on real user feedback.

A prototype has not failed when users give negative feedback; it only fails if the team ignores useful feedback.

WORKED EXAMPLE

Worked example: link the activity to the cycle.

Cycle stage	ClassBuddy activity step
Design	Step 1: interview 10 students, make design decisions (Table 6.4).
Build	Step 2: draw three paper screens with arrows.
Test	Step 3: five classmates try "add one homework task" while the observer watches silently.
Iterate	Steps 4 and 5: analyse feedback (Table 6.5) and redraw the home screen.

Why watch silently? If the observer explains ("tap here"), the team never learns that the button is hard to find. Silence shows the real difficulty.

REMEMBER IT

Feedback → Problem → Improvement. Every comment should be turned into a problem statement and then one clear change, exactly like the three columns of Table 6.5.

COMMON MISTAKE

Mistake: Feeling that negative feedback means the prototype "failed", or changing the design for every single comment.

Fix: Negative feedback is useful information. Look for **repeated** problems and fix those first. The prototype only fails if you ignore useful feedback.

اس سرگرمی میں طلبہ "کلاس بڈی" (ClassBuddy) نامی یاد دہانی نظام بناتے ہیں۔ پہلے دس طلبہ سے بات کر کے مسئلہ سمجھتے ہیں، پھر کاغذ پر تین اسکرینیں بناتے ہیں، پانچ ساتھیوں سے خاموشی سے آزمواتے ہیں، رائے کا تجزیہ کرتے ہیں اور ڈیزائن بہتر کرتے ہیں۔ منفی رائے سے پروٹوٹائپ ناکام نہیں ہوتا؛ ناکامی تب ہے جب مفید رائے کو نظرانداز کیا جائے۔

CHECK YOURSELF

1. In Step 1, how many students forgot at least one task in a week, and what percentage is that?
2. Name the three paper screens drawn in Step 2.
3. What improvement was made for the feedback "I want to see all tasks for the week"?

Answers: 1. 7 out of 10, which is 70%. 2. Today's classes, Add homework, Show reminder. 3. A 'Weekly View' button was added.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. In Step 1, how many students forgot at least one task in a week, and what percentage is that?

3 marks. Explain Class Activity: Create a Prototype with two clear points and one example.

5 marks. Write a 5-mark answer on Class Activity: Create a Prototype: definition, two points, a labelled diagram or table, and one example.

Answers: 1. 7 out of 10, which is 70% 3. A group of students wants to design a simple "Homework Helper" or "ClassBuddy" reminder system.; The team will not immediately build a complete mobile app. 5. Use the recipe in the blue box. Model opening: Business idea scenario.

BATCH HOMEWORK

Write a 5-mark answer on **Class Activity: Create a Prototype** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.8 Minimum Viable Product (MVP) ★ Golden

ACADEMY SESSION

Session 8 of 14 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A Minimum Viable Product (MVP) is the simplest working version of a product.

Error clinic: Mistake 1: Calling a paper sketch an MVP.

Exam wording to train: Typical questions: "What is an MVP?"

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Minimum Viable Product (MVP)**. Write: A Minimum Viable Product (MVP) is the simplest working version of a product.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Minimum: it has only the essential features. No extras. (2) Viable: it is usable enough to actually solve the main problem. ("Viable" means able to work successfully.) — + example.

5 marks: 3-mark structure + table: Complete canteen app (final product) / Canteen MVP + the worked example from this topic.

8–10 marks: 5-mark structure + a one-page canvas: problem, user, riskiest assumption, test + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **Minimum Viable Product (MVP)** is the **simplest working version** of a product. It includes **only the most important features** needed to **test the idea with real users**.

- **Minimum:** it has only the **essential** features. No extras.
- **Viable:** it is **usable enough** to actually solve the main problem. ("Viable" means able to work successfully.)

An MVP is **not the final product**. It is also **not only a drawing**. It is a **small working version** used to test whether users actually need the solution.

WORKED EXAMPLE

Example from the source: canteen app.

Complete canteen app (final product)	Canteen MVP
Login, online payment, delivery tracking, discount offers...	A simple Google Form where students select snacks before break.

Step-by-step: how to cut a big idea down to an MVP.

1. List all features you dream of: login, payment, delivery tracking, discounts.
2. Ask of each one: "Without this, can a student still pre-order a snack?"
3. Login? Not needed; the student can type name and class. Payment? Not needed; pay at the counter. Delivery tracking? Not needed; students collect. Discounts? Not needed.
4. What is left is the core: **choose snack + name + class**. A Google Form does this for free.

That form is **minimum** (no extras) and **viable** (students really can pre-order with it).

REMEMBER IT

Simple meaning. An MVP answers: "**Will people actually use this solution?**" It tests **real use and behaviour**, not only the visual design.

Analogy: before opening a full restaurant, a cook in Hyderabad sells biryani from home to office workers for two weeks. If people keep ordering, the idea is worth growing. That home kitchen is the MVP.

COMMON MISTAKE

Mistake 1: Calling a paper sketch an MVP. **Fix:** A sketch is a prototype. An MVP must **work** and be used by **real users**.

Mistake 2: Thinking MVP means a low-quality or broken product. **Fix:** It is small but **viable**; it must genuinely solve the main problem.

ایم وی پی (Minimum Viable Product) کسی پراڈکٹ کا سب سے سادہ مگر کام کرنے والا ورژن ہے جس میں صرف ضروری خصوصیات ہوتی ہیں۔ "منیمم" کا مطلب ہے صرف ضروری چیزیں، اور "وائیبل" کا مطلب ہے کہ وہ اصل مسئلہ حل کرنے کے قابل ہو۔ یہ حتمی پراڈکٹ نہیں بلکہ یہ جانچنے کا ذریعہ ہے کہ کیا لوگ واقعی اسے استعمال کریں گے، جیسے کینٹین کے لیے ایک سادہ گوگل فارم۔

EXAM TIP

Typical questions: "What is an MVP? Explain the words Minimum and Viable" and "Give an example of an MVP." Write the full form, the definition (simplest working version, only most important features, test with real users), explain both words, state that it is neither the final product nor only a drawing, and give the canteen Google Form example. Mention the key question: "Will people actually use this solution?"

CHECK YOURSELF

1. Write the full form of MVP.
2. What does "Viable" mean in MVP?
3. What question does an MVP answer?

Answers: 1. Minimum Viable Product. 2. Usable enough to actually solve the main problem. 3. "Will people actually use this solution?"

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Write the full form of MVP.

3 marks. Explain Minimum Viable Product (MVP) with two clear points and one example.

5 marks. Typical questions: "What is an MVP? Explain the words Minimum and Viable" and "Give an example of an MVP." Write the full form, the definition (simplest working version, only most important features,...

8 marks. Minimum Viable Product (MVP): 5-mark answer plus a one-page canvas: problem, user, riskiest assumption, test.

Answers: 1. Minimum Viable Product 3. Minimum: it has only the essential features. No extras.; Viable: it is usable enough to actually solve the main problem. ("Viable" means able to work successfully.) 5. Use the recipe in the blue box. Model opening: A Minimum Viable Product (MVP) is the simplest working version of a product.

8. Same 5-mark body + a one-page canvas: problem, user, riskiest assumption, test + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Minimum Viable Product (MVP)** using the recipe in this topic. Include a one-page canvas: problem, user, riskiest assumption, test. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.9 Difference between Prototype and MVP

ACADEMY SESSION

Session 9 of 14 · 45 minutes (first half) · paired with Identifying the Riskiest Assumption.

10–45 min — this topic. Lock the definition and table for **Difference between Prototype and MVP**. Starter (0–10) is from last class. Second half is Identifying the Riskiest Assumption.

On the board: Prototype and MVP are related, but not the same.

Error clinic: Mistake: Thinking "high-fidelity prototype" and "MVP" are the same because both look good.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Difference between Prototype and MVP**. Write: Prototype and MVP are related, but not the same.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) A prototype is mainly used to show and test the design of an idea. (2) An MVP is used to test real use and market demand. — + example.

5 marks: 3-mark structure + table: Point / Prototype / MVP + the worked example from this topic.

LEARN IT

Prototype and MVP are **related, but not the same**. A **prototype** is mainly used to **show and test the design** of an idea. An **MVP** is used to **test real use and market demand**. *Market demand* means whether enough people want the product and will use (or pay for) it.

Usually a prototype comes first and an MVP comes after it: Problem → Idea → Prototype → Feedback → MVP.

Table 6.6: Prototype and MVP comparison

Point	Prototype	MVP
Main purpose	To show how the idea may look or work.	To test whether users will actually use the solution.
Working status	May not work; can be a sketch or model.	Must work at least in a basic way.
Users	Small group gives feedback on design.	Early real users test the product in daily life.
Cost	Very low cost.	Low cost but may need some basic development.
Example	Paper screens for a canteen order system.	Google Form used for real canteen orders for three days.

REMEMBER IT

Key takeaway

Prototype = "Does it **look right** and make sense?"

MVP = "Will people **actually use it** and find value in it?"

Memory hook: **Prototype** → **P**icture of the idea; **MVP** → **M**arket test of the idea.

WORKED EXAMPLE

Worked example: classify each item. Decide whether each is a prototype or an MVP and give the reason.

1. Hand-drawn screens of a tuition-finder app shown to 6 friends. → **Prototype**: it does not work; it tests design.
2. A WhatsApp broadcast group that really sends van arrival times to parents of one route for a week. → **MVP**: it works and real users use it daily.
3. Clickable PowerPoint screens of a notes organizer. → **Prototype** (mid-fidelity): links work, but nobody uses it for real notes.
4. A shared Google Drive folder per subject that a class actually uses before the monthly test. → **MVP**: real use in daily life.

Rule used: **Does it work, and is it used by real users in real life?** If yes → MVP. If it only shows the design → prototype.

COMMON MISTAKE

Mistake: Thinking "high-fidelity prototype" and "MVP" are the same because both look good.

Fix: The difference is **purpose and real use**, not appearance. A beautiful Figma design that nobody uses for real orders is still a prototype; a plain Google Form taking real orders is an MVP.

اردو میں سمجھیں

پروٹوٹائپ اور ایم وی پی آپس میں جڑے ہیں مگر ایک جیسے نہیں۔ پروٹوٹائپ خیال کا ڈیزائن دکھاتا اور آزماتا ہے اور ضروری نہیں کہ کام کرے، جبکہ ایم وی پی کم از کم بنیادی طور پر کام کرتا ہے اور اصل صارفین روزمرہ زندگی میں اسے استعمال کرتے ہیں۔ پروٹوٹائپ پوچھتا ہے "کیا یہ ٹھیک لگتا ہے؟" اور ایم وی پی پوچھتا ہے "کیا لوگ واقعی اسے استعمال کریں گے؟"

CHECK YOURSELF

1. Which one must work at least in a basic way?
2. Give the source's example of a prototype and of an MVP for the canteen.
3. Which question does a prototype answer?

Answers: 1. The MVP. 2. Prototype: paper screens for a canteen order system. MVP: a Google Form used for real canteen orders for three days. 3. "Does it look right and make sense?"

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which one must work at least in a basic way?

3 marks. Explain Difference between Prototype and MVP with two clear points and one example.

5 marks. Write a 5-mark answer on Difference between Prototype and MVP: definition, two points, a labelled diagram or table, and one example.

Answers: 1. The MVP 3. A prototype is mainly used to show and test the design of an idea.; An MVP is used to test real use and market demand. 5. Use the recipe in the blue box. Model opening: Prototype and MVP are related, but not the same.

BATCH HOMEWORK

Write a 5-mark answer on **Difference between Prototype and MVP** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.10 Identifying the Riskiest Assumption

ACADEMY SESSION

Session 9 of 14 · 45 minutes (second half) · paired with Difference between Prototype and MVP.

45–75 min — this topic. Board working for **Identifying the Riskiest Assumption**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Every business idea is based on assumptions.

Error clinic: Mistake: Testing easy, safe assumptions (colours, names) first and leaving the dangerous one for later.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Identifying the Riskiest Assumption**. Write: Every business idea is based on assumptions.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) An assumption is something we believe to be true, but have not tested yet. (2) The riskiest assumption is the belief that can make the entire business fail if it turns out to be wrong. — + example.

5 marks: 3-mark structure + table: Business Idea / Possible Risky Assumption / How to Test It (MVP) + the worked example from this topic.

LEARN IT

Every business idea is based on **assumptions**. An **assumption** is something we **believe to be true, but have not tested yet**.

The **riskiest assumption** is the belief that can make the **entire business fail** if it turns out to be wrong.

Entrepreneurs should **identify and test the riskiest assumption early**, because it **saves time and money**. If it is wrong, you find out before building everything else.

Table 6.7: Testing risky assumptions

Business Idea	Possible Risky Assumption	How to Test It (MVP)
Online tuition finder	Students will pay for online tutoring.	Ask 20 students and offer a trial class to see if they sign up.
Canteen pre-order form	Students will order snacks before break.	Test a Google Form for one week in real time.
Ajrak online catalogue	Customers will place orders through WhatsApp.	Share catalogue with 30 customers and record actual orders.
College van update system	Parents and students will check van updates daily.	Create a trial WhatsApp broadcast group for one route.

Notice that every test measures **what people actually do** (sign up, order, check), not just what they say.

WORKED EXAMPLE

Worked example: finding the riskiest assumption. Idea: a home-tutor booking service for Grade IX–X students in Sukkur.

Step 1, list assumptions:

1. Parents want home tutors for their children.
2. Good tutors in Sukkur are willing to join.
3. Parents will **pay a booking fee** through our service instead of finding tutors through relatives.
4. Parents will like our logo.

Step 2, ask of each: "If this is wrong, does the whole business fail?" Logo (4): no, easily changed. Parents wanting tutors (1): very likely true; many already hire tutors. Tutors joining (2): important, but easy to check by phoning a few tutors. Paying a booking fee (3): if parents refuse to pay, the business earns nothing, so **this is the riskiest assumption**.

Step 3, design a small MVP test: post the offer in 3 parent WhatsApp groups for one week, offer a first booking at a small fee, and **count how many actually pay**.

REMEMBER IT

Ask: "What would kill this idea?" The answer is usually the riskiest assumption. Test it **first**, cheaply, with real behaviour.

COMMON MISTAKE

Mistake: Testing easy, safe assumptions (colours, names) first and leaving the dangerous one for later.

Fix: Test the assumption that could make the whole business fail first. Also, do not trust only "Yes, I would use it". Measure actual sign-ups or orders.

اردو میں سمجھیں

ہر کاروباری خیال کچھ مفروضوں (Assumptions) پر قائم ہوتا ہے، یعنی وہ باتیں جنہیں ہم سچ سمجھتے ہیں مگر ابھی آزمایا نہیں۔ سب سے خطرناک مفروضہ (Riskiest Assumption) وہ ہے جو غلط نکلے تو پورا کاروبار ناکام ہو جائے۔ اسے شروع میں ہی چھوٹے ایم وی پی سے آزمانا چاہیے تاکہ وقت اور پیسہ بچ سکے۔

CHECK YOURSELF

1. Define assumption.
2. What is the risky assumption for the Ajrak online catalogue, and how is it tested?
3. Why test the riskiest assumption early?

Answers: 1. Something we believe to be true but have not tested yet. 2. Customers will place orders through WhatsApp; share the catalogue with 30 customers and record actual orders. 3. Because if it is wrong the whole business fails, so testing it early saves time and money.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Define assumption.

3 marks. Explain Identifying the Riskiest Assumption with two clear points and one example.

5 marks. Write a 5-mark answer on Identifying the Riskiest Assumption: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Something we believe to be true but have not tested yet. 3. An assumption is something we believe to be true, but have not tested yet.; The riskiest assumption is the belief that can make the entire business fail if it turns out to be wrong. 5. Use the recipe in the blue box. Model opening: Every business idea is based on assumptions.

BATCH HOMEWORK

Write a 5-mark answer on **Identifying the Riskiest Assumption** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.11 Developing an MVP

ACADEMY SESSION

Session 10 of 14 · 45 minutes (first half) · paired with Case Study: MVP for a Canteen Pre-Order System.

10–45 min — this topic. Lock the definition and table for **Developing an MVP**. Starter (0–10) is from last class. Second half is Case Study: MVP for a Canteen Pre-Order System.

On the board: To develop an MVP, the team must select only the essential features.

Error clinic: Mistake: Writing a list of ten "main features".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Developing an MVP**. Write: To develop an MVP, the team must select only the essential features.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Extra features should be avoided at the beginning. (2) A common mistake is trying to build everything at once. — + example.

5 marks: 3-mark structure + table: MVP Element / Question to Ask / Example Answer + the worked example from this topic.

LEARN IT

To develop an MVP, the team must **select only the essential features**. Extra features should be avoided at the beginning. A common mistake is **trying to build everything at once**. This makes the product **difficult, costly, and slow**.

An **MVP plan** should clearly explain: the **problem, target users, main feature, basic design, estimated cost, marketing method, feedback method, and improvement plan**.

Table 6.8: MVP planning checklist

MVP Element	Question to Ask	Example Answer
Problem	What problem are we solving?	Students wait too long at canteen.
Target users	Who will use it first?	Grade XII students in one college.
Main feature	What is the ONE feature that solves it?	Pre-order snacks before break.
Basic design	What steps are needed?	Menu, name, class, order time.
Cost	What free/low-cost tools to use?	Google Form or printed slips.
Marketing	How will early users hear about it?	WhatsApp message to class group.
Feedback	How will users respond?	Short feedback form after 3 days.

The eighth element, the **improvement plan**, answers "What will we change after feedback?" (you will see it in the case study in 6.12).

WORKED EXAMPLE

Worked example: filling the checklist for a new idea. Idea: a college notice reminder for parents in Hyderabad (from Table 6.1).

MVP Element	Answer
Problem	Parents miss college notices (fee dates, PTMs, holidays).
Target users	Parents of first-year (Class XI) students of one college.
Main feature	Send each notice to parents' phones on the same day.
Basic design	Photo of notice + 2-line summary in Urdu and Sindhi + date.
Cost	Free: WhatsApp broadcast list from the college office phone.
Marketing	Students give a printed slip to parents with the number to save.
Feedback	After 2 weeks, a 3-question voice-note or phone survey of 20 parents.
Improvement plan	If parents say notices come too late, send a reminder 1 day before each date.

Notice: only **one** main feature, a **free** tool, and a clear way to collect feedback.

REMEMBER IT

Mnemonic for the 8 elements: "People Try My Bakery; Cheap Muffins Find Improvement": Problem, Target users, Main feature, Basic design, Cost, Marketing, Feedback, Improvement plan.

COMMON MISTAKE

Mistake: Writing a list of ten "main features".

Fix: The checklist asks for the **ONE** feature that solves the problem. Everything else waits until the MVP proves people want it.

اردو میں سمجھیں

ایم وی پی بناتے وقت صرف ضروری خصوصیات چنیں؛ سب کچھ ایک ساتھ بنانے سے کام مشکل، مہنگا اور سست ہو جاتا ہے۔ ایم وی پی منصوبے میں مسئلہ، پہلے صارفین، ایک بنیادی خصوصیت، سادہ ڈیزائن، کم خرچ ٹولز، تشہیر کا طریقہ، رائے لینے کا طریقہ اور بہتری کا منصوبہ واضح ہونا چاہیے۔

CHECK YOURSELF

1. Why is building everything at once a mistake?
2. List the eight elements of an MVP plan.
3. In Table 6.8, what is the marketing method?

Answers: 1. It makes the product difficult, costly and slow. 2. Problem, target users, main feature, basic design, estimated cost, marketing method, feedback method, improvement plan. 3. A WhatsApp message to the class group.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Why is building everything at once a mistake?

3 marks. Explain Developing an MVP with two clear points and one example.

5 marks. Write a 5-mark answer on Developing an MVP: definition, two points, a labelled diagram or table, and one example.

Answers: 1. It makes the product difficult, costly and slow 3. Extra features should be avoided at the beginning.; A common mistake is trying to build everything at once. 5. Use the recipe in the blue box. Model opening: To develop an MVP, the team must select only the essential features.

BATCH HOMEWORK

Write a 5-mark answer on **Developing an MVP** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.12 Case Study: MVP for a Canteen Pre-Order System

ACADEMY SESSION

Session 10 of 14 · 45 minutes (second half) · paired with Developing an MVP.

45–75 min — this topic. Board working for **Case Study: MVP for a Canteen Pre-Order System**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Problem: In a college, students wait in long lines at the canteen.

Error clinic: Mistake: Thinking only the students' opinion matters.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Case Study: MVP for a Canteen Pre-Order System**. Write: Problem: In a college, students wait in long lines at the canteen.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Sometimes snacks finish before students reach the counter. (2) A group wants to test a canteen pre-order idea. — + example.

5 marks: 3-mark structure + table: MVP Element / Decision + the worked example from this topic.

LEARN IT

Problem: In a college, students wait in long lines at the canteen. Sometimes snacks finish before students reach the counter. A group wants to test a canteen pre-order idea.

Goal: Their aim is **NOT** to create a complete app immediately. Their aim is to test **whether students will place orders before break** and **whether the canteen can manage these orders**.

The approach

1. The team creates a **paper prototype** showing three steps: **select item, enter name, collect order**.
2. **Feedback** from the prototype suggests the **menu should be short** and **payment should be at collection time**.
3. For the actual MVP, the team uses a **Google Form**. Students select **one of five items**.
4. The canteen prepares these pre-orders. This MVP is tested for **three days only** to learn quickly.




Table 6.9: MVP plan for canteen pre-order system

MVP Element	Decision
Features	Menu list, student name, class, item, and quantity.
Cost & Tools	Free Google Form or printed order slips.
Marketing	Class announcement and WhatsApp group message.
Testing period	Three days.
Feedback method	Ask students if they saved time and would use it again.
Improvement	Keep only 5 items; close orders 20 minutes before break.

Result: Students liked saving time, but **canteen staff found too many items difficult**. The team improved the MVP by **keeping only five items** and creating a **separate collection line**. This improvement is based on real feedback.

WORKED EXAMPLE

Worked example: trace the case study through the chapter's ideas.

Chapter idea	Where it appears in the case study
Real problem (6.3)	Long queues; snacks finish before students reach the counter.
Low-fidelity prototype (6.5)	Paper screens: select item, enter name, collect order.
Iteration (6.6)	Feedback led to a short menu and payment at collection.
MVP (6.8)	Google Form with one of five items, used for real orders.
Riskiest assumption (6.10)	Students will order before break, and the canteen can manage the orders.
Beachhead market (6.14)	One college canteen during break.

Why "close orders 20 minutes before break"? Staff need time to prepare. If orders arrive at the last minute, the pre-order line becomes as slow as the normal line, and the main benefit disappears.

REMEMBER IT

Remember the case study as **"5 items, 3 days, 20 minutes"**: five menu items, a three-day test, orders closing twenty minutes before break.

COMMON MISTAKE

Mistake: Thinking only the students' opinion matters.

Fix: The case study tested **two** things: whether students will order **and** whether the canteen can manage the orders. The staff's feedback (too many items) caused the key improvement.

اردو میں سمجھیں

ایک کالج میں طلبہ کینٹین کی لمبی قطاروں میں انتظار کرتے تھے۔ ٹیم نے فوراً ایپ بنانے کے بجائے پہلے کاغذی پروٹوٹائپ بنایا، پھر تین دن کے لیے گوگل فارم کو ایم وی پی کے طور پر آزمایا جس میں پانچ اشیاء تھیں۔ طلبہ کو وقت کی بچت پسند آئی مگر عملے کو زیادہ اشیاء مشکل لگیں، اس لیے صرف پانچ اشیاء رکھی گئیں، الگ قطار بنائی گئی اور بریک سے بیس منٹ پہلے آرڈر بند کیے گئے۔

CHECK YOURSELF

1. Which tool was used for the canteen MVP, and for how long was it tested?
2. What two things did the team want to test?
3. What two improvements were made after the result?

Answers: 1. A Google Form, tested for three days. 2. Whether students will place orders before break, and whether the canteen can manage these orders. 3. Keeping only five items and creating a separate collection line (orders also close 20 minutes before break).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which tool was used for the canteen MVP, and for how long was it tested?

3 marks. Explain Case Study: MVP for a Canteen Pre-Order System with two clear points and one example.

5 marks. Write a 5-mark answer on Case Study: MVP for a Canteen Pre-Order System: definition, two points, a labelled diagram or table, and one example.

Answers: 1. A Google Form, tested for three days 3. Sometimes snacks finish before students reach the counter.; A group wants to test a canteen pre-order idea. 5. Use the recipe in the blue box. Model opening: Problem: In a college, students wait in long lines at the canteen.

BATCH HOMEWORK

Write a 5-mark answer on **Case Study: MVP for a Canteen Pre-Order System** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.13 Testing an MVP

ACADEMY SESSION

Session 11 of 14 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: MVP testing means giving the basic working version to real users and studying their response.

Error clinic: Mistake: Launching the MVP first and deciding later what to measure.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Testing an MVP**. Write: MVP testing means giving the basic working version to real users and studying their response.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Comments (qualitative data) explain what users liked, disliked, or found confusing. (2) How many users will test it. — + example.

5 marks: 3-mark structure + table: Type of Feedback / Question / Example Result + the worked example from this topic.

LEARN IT

MVP testing means giving the basic working version to **real users** and **studying their response**. The team should collect **both numbers and comments**.

- **Numbers** (quantitative data) show how many users tried the MVP and how many may use it again.
- **Comments** (qualitative data) explain what users liked, disliked, or found confusing.

Testing should be **planned before the MVP is launched**. Decide:

1. **How many users** will test it.
2. **How long** the test will continue.
3. **What information** will be collected.

Table 6.10: Feedback during MVP testing

Type of Feedback	Question	Example Result
Number-based	How many users tried it?	40 students used the form.
Number-based	How many would use it again?	30 out of 40 said yes.
Comment-based	What was confusing?	Did not know order closing time.
Observation	Where did users face difficulty?	Forgot to enter class name.

Observation means the team watches users and notes difficulties themselves, even ones users do not mention.

WORKED EXAMPLE

Worked example: studying the results in Table 6.10.

1. **Repeat-use rate** = (users who would use it again ÷ users who tried it) × 100 = (30 ÷ 40) × 100 = **75%**.
2. **Did not want to use again** = 40 – 30 = **10 students** = (10 ÷ 40) × 100 = **25%**.
3. **Comment:** "Did not know order closing time" → **Fix:** write "Orders close 20 minutes before break" at the top of the form and in the WhatsApp message.
4. **Observation:** "Forgot to enter class name" → **Fix:** make the Class field **required** in the Google Form so it cannot be submitted empty.
5. **Decide what to fix first:** the closing-time problem stops people from ordering at all, so fix it first; the class-name problem only makes collection slower.

Three out of four users would come back, which is a promising sign; fixing the two problems could raise that number further.

REMEMBER IT

Data skill link. Feedback is useful only when it is studied: **Count** the responses → **Look** for repeated problems → **Decide** which improvement comes first. Remember "C-L-D: Count, Look, Decide."

COMMON MISTAKE

Mistake: Launching the MVP first and deciding later what to measure.

Fix: Plan the number of users, the test length and the questions **before** launch. Otherwise you may forget to record important data (for example, how many people opened the form but did not submit).

اردو میں سمجھیں

ایم وی پی کی جانچ کا مطلب ہے کہ بنیادی کام کرنے والا ورژن اصل صارفین کو دیا جائے اور ان کے ردعمل کا مطالعہ کیا جائے۔ اعداد بتاتے ہیں کتنے لوگوں نے استعمال کیا اور کتنے دوبارہ کریں گے، جبکہ تبصرے بتاتے ہیں کیا پسند آیا اور کیا الجھن تھی۔ جانچ کی منصوبہ بندی پہلے سے کریں، جوابات گنتیں، بار بار آنے والے مسائل تلاش کریں اور پہلے سب سے اہم بہتری کریں۔

CHECK YOURSELF

1. Name the three types of feedback in Table 6.10.
2. If 50 people tried an MVP and 35 would use it again, what is the repeat-use rate?
3. Name the three things to decide before launching an MVP test.

Answers: 1. Number-based, comment-based, observation. 2. $(35 \div 50) \times 100 = 70\%$. 3. How many users will test it, how long the test will continue, and what information will be collected.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name the three types of feedback in Table 6.10.

3 marks. Explain Testing an MVP with two clear points and one example.

5 marks. Write a 5-mark answer on Testing an MVP: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Number-based, comment-based, observation. 3. Comments (qualitative data) explain what users liked, disliked, or found confusing.; How many users will test it. 5. Use the recipe in the blue box. Model opening: MVP testing means giving the basic working version to real users and studying their response.

BATCH HOMEWORK

Write a 5-mark answer on **Testing an MVP** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.14 Beachhead Market ★ Golden

ACADEMY SESSION

Session 12 of 14 ★ Golden · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: A beachhead market is a small and focused group of first users.

Error clinic: Mistake: Thinking a bigger first market means more success ("everyone can use my app").

Exam wording to train: Asked as "Define beachhead market and give its characteristics" or "Suggest a beachhead market for ...".

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Beachhead Market**. Write: A beachhead market is a small and focused group of first users.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) These users have a clear need and are likely to try the product early. (2) Instead of trying to serve everyone, entrepreneurs first focus on one small group. — + example.

5 marks: 3-mark structure + labelled diagram + the worked example from this topic.

8–10 marks: 5-mark structure + a one-page canvas: problem, user, riskiest assumption, test + a one-line conclusion. Method marks are awarded for working.

LEARN IT

A **beachhead market** is a **small and focused group of first users**. These users have a **clear need** and are **likely to try the product early**.


Instead of trying to serve everyone, entrepreneurs **first focus on one small group**. This helps them **test the MVP properly and improve it before expanding**.

The word comes from the army: a *beachhead* is the small piece of beach soldiers capture first when they land; from there they move inland. In business, your beachhead is the first small group you "win".

Characteristics of a good beachhead market

- It should be **specific and narrowly defined**.
- It should be **reachable** by the startup team.
- The users should have a **strong, immediate need** for the solution.

For example, targeting "**all students in Pakistan**" is too broad for a new study app. "**Grade XII students preparing for board exams in one college**" is much more focused and easier to reach.



Start with the small inner circle (beachhead), learn and improve, then expand outward.

Table 6.11: Choosing a focused beachhead market

Business Idea	Weak First Market	Better Beachhead Market
Study app	All students in Pakistan.	Grade XII students preparing for exams in one college.
Canteen pre-order	All canteens in the city.	One college canteen during lunch break.
Ajrak catalogue	All online shoppers.	Existing customers of one local shop.
Van update system	All transport users.	Students and parents of ONE specific college van route.

Choosing a small first market **does not mean the idea will remain small forever**. After learning from this group, the idea can be improved and expanded, even globally.

WORKED EXAMPLE

Worked example: test a proposed beachhead against the three characteristics. Idea: an app that reminds farmers about irrigation water turns (*warabandi*).

Proposed market	Specific?	Reachable?	Strong, immediate need?	Verdict
All farmers in Sindh	No	No (millions of people, many districts)	Varies	Weak
Farmers on one watercourse near Badin whose sons/daughters study in the team's college	Yes	Yes (through classmates)	Yes (missing a turn damages crops)	Good beachhead

Expansion path: one watercourse → nearby watercourses → the whole district → other districts.

REMEMBER IT

Remember S-R-U: Specific, Reachable, Urgent need. If you cannot meet your first users within a week, your market is too big.

COMMON MISTAKE

Mistake: Thinking a bigger first market means more success ("everyone can use my app").

Fix: A broad market is hard to reach and hard to learn from. Win a small group first, learn, improve, then expand.

اردو میں سمجھیں

بیج ہیڈ مارکیٹ (Beachhead Market) پہلے صارفین کا ایک چھوٹا اور مخصوص گروہ ہے جسے حل کی واضح اور فوری ضرورت ہو اور جو پراڈکٹ جلد آزمانے پر تیار ہو۔ سب کو ایک ساتھ خدمت دینے کے بجائے پہلے ایک چھوٹے گروہ پر توجہ دیں، جیسے "پاکستان کے تمام طلبہ" کے بجائے "ایک کالج کے بارہویں جماعت کے طلبہ"۔ وہاں سے سیکھ کر خیال کو بعد میں پھیلایا جا سکتا ہے۔

EXAM TIP

Asked as "Define beachhead market and give its characteristics" or "Suggest a beachhead market for ...". Write the definition (small, focused group of first users with a clear need, likely to try early), the three characteristics (specific, reachable, strong immediate need), one weak-versus-better pair from Table 6.11, and the line that a small first market does not mean the idea stays small.

CHECK YOURSELF

1. Give the three characteristics of a good beachhead market.
2. What is the better beachhead market for the van update system?
3. Does choosing a small first market mean the business will stay small?

Answers: 1. Specific and narrowly defined; reachable by the team; users have a strong, immediate need. 2. Students and parents of ONE specific college van route. 3. No. After learning from the first group, the idea can be improved and expanded.

ACADEMY DRILL

Timed 20 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Give the three characteristics of a good beachhead market.

3 marks. Explain Beachhead Market with two clear points and one example.

5 marks. Asked as "Define beachhead market and give its characteristics" or "Suggest a beachhead market for ...". Write the definition (small, focused group of first users with a clear need, likely to try...

8 marks. Beachhead Market: 5-mark answer plus a one-page canvas: problem, user, riskiest assumption, test.

Answers: 1. Specific and narrowly defined; reachable by the team; users have a strong, immediate need 3. These users have a clear need and are likely to try the product early.; Instead of trying to serve everyone, entrepreneurs first focus on one small group. 5. Use the recipe in the blue box. Model opening: A beachhead market is a small and focused group of first users. 8. Same 5-mark body + a one-page canvas: problem, user, riskiest assumption, test + one-line conclusion.

BATCH HOMEWORK

Write an 8-mark answer on **Beachhead Market** using the recipe in this topic. Include a one-page canvas: problem, user, riskiest assumption, test. Then redraw the board work from memory on a fresh page — no notes.

How you will mark it tomorrow: Mark to the 8–10 mark recipe. Any answer with no working is half marks.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.15 Complete Student Project

ACADEMY SESSION

Session 13 of 14 · 45 minutes (first half) · paired with Ethical and Safe Use of Digital Tools.

10–45 min — this topic. Lock the definition and table for **Complete Student Project**. Starter (0–10) is from last class. Second half is Ethical and Safe Use of Digital Tools.

On the board: You will work in groups and complete one small entrepreneurship project.

Error clinic: Mistake: Writing an MVP plan that lists every feature of the dream app.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Complete Student Project**. Write: You will work in groups and complete one small entrepreneurship project.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) The project should be simple, local, and possible in the classroom. (2) The purpose is to practise the complete journey: problem → prototype → feedback → MVP plan → risky assumption → beachhead market. — + example.

5 marks: 3-mark structure + table: Item / Your group's answer + the worked example from this topic.

LEARN IT

You will work in **groups** and complete one small entrepreneurship project. The project should be **simple, local, and possible in the classroom**.

The purpose is to practise the **complete journey**: problem → prototype → feedback → MVP plan → risky assumption → beachhead market.

Suggested project ideas: homework and test reminder system, college notice organizer, canteen pre-order system, small shop WhatsApp catalogue, college van update system, lost and found item reporting system, study notes organizer.

Table 6.12: Student project sheet (template)

Item	Your group's answer
Problem statement	
Target users	
Business idea	
Low-fidelity prototype description	
Feedback from users	
Improvement made after feedback	
MVP plan	
Riskiest assumption	
How to test the riskiest assumption	
Beachhead market	
Marketing method for first users	

WORKED EXAMPLE

Worked example: a completed project sheet (Lost and Found system).

Item	Answer
Problem statement	Students of our college in Mirpurkhas lose items (bottles, calculators, ID cards) and rarely get them back because there is no central place to report them.
Target users	Students and staff of our college.
Business idea	A Lost and Found WhatsApp group plus a Google Form to report lost or found items.
Low-fidelity prototype	Two paper screens: "Report lost item" (item, colour, place, phone of class rep) and "Found items list" with sketches.
Feedback from users	6 of 8 testers asked for photos; 3 did not want their own phone number shown.
Improvement made	Added a photo upload; replaced personal numbers with "collect from the library desk".
MVP plan	Google Form + one WhatsApp group run by two volunteers; free; tested for two weeks.
Riskiest assumption	Students who find items will take the trouble to report them.
How to test it	Count how many "found" reports arrive in two weeks compared with "lost" reports.
Beachhead market	Grade XII students of our college.
Marketing method	Announcement in morning assembly, a poster at the library and a message in each class group.

Table 6.13: Rubric for project assessment

A **rubric** is a marking guide that describes what excellent, satisfactory and weak work looks like for each part of a project.

Criteria	Excellent	Satisfactory	Needs Improvement
Problem ID	Clear, local, and important.	Understandable but needs detail.	Vague or too broad.
Prototype	Shows clear flow and features.	Shows the basic idea.	Incomplete or unclear.
Feedback & Fixes	Collected properly; changes clearly based on feedback.	Collected but analysis is weak; some changes made.	No clear feedback collected; changes not explained.
MVP Plan	Essential features and clear testing plan.	Basic features but needs testing clarity.	Confused with the final product.

REMEMBER IT

Use the rubric **before** you submit: read your project sheet row by row and ask, "Is this Excellent yet?" For "Feedback & Fixes", always write **which** feedback caused **which** change.

COMMON MISTAKE

Mistake: Writing an MVP plan that lists every feature of the dream app. The rubric marks this as "Confused with the final product".

Fix: Keep the MVP to the essential feature(s) and add a clear testing plan (how many users, how long, what you will measure).

اردو میں سمجھیں

طلبہ گروپوں میں ایک چھوٹا، مقامی اور آسان منصوبہ مکمل کرتے ہیں جس میں مسئلے سے پروٹوٹائپ، رائے، ایم وی پی منصوبہ، سب سے خطرناک مفروضہ اور بیج بیڈ مارکیٹ تک پورا سفر شامل ہوتا ہے۔ منصوبے کو جانچنے کے لیے روبرک (Rubric) استعمال ہوتا ہے جو مسئلے کی پہچان، پروٹوٹائپ، رائے و بہتری اور ایم وی پی منصوبے کو بہترین، تسلی بخش یا بہتری کی ضرورت کے درجوں میں پرکھتا ہے۔

CHECK YOURSELF

1. Name four suggested project ideas.
2. What does "Excellent" look like for Problem ID in the rubric?
3. Which rubric level says "Confused with the final product"?

Answers: 1. Any four: homework and test reminder system, college notice organizer, canteen pre-order system, small shop WhatsApp catalogue, college van update system, lost and found reporting system, study notes organizer. 2. Clear, local, and important. 3. Needs Improvement (for the MVP Plan).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name four suggested project ideas.

3 marks. Explain Complete Student Project with two clear points and one example.

5 marks. Write a 5-mark answer on Complete Student Project: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Any four: homework and test reminder system, college notice organizer, canteen pre-order system, small shop WhatsApp catalogue, college van update system, lost and found reporting system, study notes organizer. 3. The project should be simple, local, and possible in the classroom.; The purpose is to practise the complete journey: problem → prototype → feedback → MVP plan → risky assumption → beachhead market. 5. Use the recipe in the blue box. Model opening: You will work in groups and complete one small entrepreneurship project.

BATCH HOMEWORK

Write a 5-mark answer on **Complete Student Project** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

6.16 Ethical and Safe Use of Digital Tools

ACADEMY SESSION

Session 13 of 14 · 45 minutes (second half) · paired with Complete Student Project.

45–75 min — this topic. Board working for **Ethical and Safe Use of Digital Tools**, then a short drill. 75–85 error clinic covers both topics in this class.

On the board: Digital entrepreneurship should be responsible.

Error clinic: Mistake: "More data is always better, so let's collect everything." Fix: Collect only what you need to answer your test questions.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Ethical and Safe Use of Digital Tools**. Write: Digital entrepreneurship should be responsible.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Truthfulness: report results honestly; do not make up numbers or hide bad feedback. (2) Fairness: treat all users equally. — + example.

5 marks: 3-mark structure + four-point explanation + the worked example from this topic.

LEARN IT

Digital entrepreneurship should be **responsible**. When collecting user feedback, you must respect:

- **Privacy:** people's personal information belongs to them.
- **Truthfulness:** report results honestly; do not make up numbers or hide bad feedback.
- **Fairness:** treat all users equally.

You should **not collect unnecessary personal information** or **share phone numbers or photos without permission**.

Equity point

A good digital solution should consider users who have **weak internet**, **limited devices**, or **language difficulty**. A design with **large buttons**, **simple Urdu/Sindhi instructions**, and **low data usage** helps ensure **equal access**. *Equity* means making sure everyone, including people with fewer resources, can use the solution.

WORKED EXAMPLE

Worked example: fix an unethical feedback form. A team's canteen feedback form asks:

1. Full name, father's name, CNIC/B-form number, home address. → **Problem:** unnecessary personal data. **Fix:** ask only class (or nothing personal at all).
2. "Upload your selfie." → **Problem:** photos are not needed and could be misused. **Fix:** remove.
3. The team plans to post all respondents' phone numbers in the class group. → **Problem:** sharing numbers without permission. **Fix:** never share; keep responses private to the team.
4. The form is in English only and has a 5 MB video at the top. → **Problem:** excludes users with language difficulty or weak internet. **Fix:** add Urdu/Sindhi instructions and remove the heavy video.

When presenting, the team reports "30 out of 40 would use it again" exactly, without rounding it up to "almost everyone". That is truthfulness.

REMEMBER IT

Ask yourself "P-T-F-E": Is it Private, Truthful, Fair, and Equal-access?

COMMON MISTAKE

Mistake: "More data is always better, so let's collect everything."

Fix: Collect only what you need to answer your test questions. Extra personal data creates risk for users and gives you no benefit.

اردو میں سمجھیں

ڈیجیٹل کاروبار ذمہ داری سے کرنا چاہیے۔ رائے جمع کرتے وقت لوگوں کی رازداری (Privacy)، سچائی اور انصاف کا خیال رکھیں؛ غیر ضروری ذاتی معلومات نہ لیں اور اجازت کے بغیر فون نمبر یا تصاویر شیئر نہ کریں۔ اچھا حل کمزور انٹرنیٹ، محدود موبائل اور زبان کی مشکل والے لوگوں کا بھی خیال رکھتا ہے، جیسے بڑے بٹن، آسان اردو یا سندھی ہدایات اور کم ڈیٹا کا استعمال۔

CHECK YOURSELF

1. Name the three values students must respect when collecting feedback.
2. Give two things students must not do with users' information.
3. List three design features that support equal access.

Answers: 1. Privacy, truthfulness, fairness. 2. Collect unnecessary personal information; share phone numbers or photos without permission. 3. Large buttons, simple Urdu/Sindhi instructions, low data usage.

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Name the three values students must respect when collecting feedback.

3 marks. Explain Ethical and Safe Use of Digital Tools with two clear points and one example.

5 marks. Write a 5-mark answer on Ethical and Safe Use of Digital Tools: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Privacy, truthfulness, fairness 3. Truthfulness: report results honestly; do not make up numbers or hide bad feedback.; Fairness: treat all users equally. 5. Use the recipe in the blue box. Model opening: Digital entrepreneurship should be responsible.

BATCH HOMEWORK

Write a 5-mark answer on **Ethical and Safe Use of Digital Tools** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Career Opportunities

ACADEMY SESSION

Session 14 of 14 · 90 minutes (full class).

Full 90-minute class: 0–10 starter · 10–35 concept lock · 35–55 board working · 55–75 academy drill · 75–85 error clinic · 85–90 homework out.

On the board: This unit covered entrepreneurship in the digital age, turning problems into business ideas, prototyping, building MVPs, and identifying beachhead markets.

Error clinic: Mistake: Thinking startup careers are only for programmers.

بورڈ پر تعریف، جدول اور خاکہ لکھیں؛ ڈرل کے بعد تین عام غلطیاں ایک خانے میں درست کریں۔

FULL-MARK ANSWER RECIPE

Train this wording every class: *Define. Explain. Example. Diagram. Working.*

1 mark: Define **Career Opportunities**. Write: This unit covered entrepreneurship in the digital age, turning problems into business ideas, prototyping, building MVPs, and identifying beachhead markets.

2 marks: definition + one local example (JazzCash, school portal, NADRA, load-shedding).

3 marks: definition + two points — (1) Mastery of these concepts opens the door to careers in startups and digital innovation. (2) Pakistan has many incubators (for example, National Incubation Centres, NICs, in major cities) that support young founders. — + example.

5 marks: 3-mark structure + table: Career / What the person does + the worked example from this topic.

LEARN IT

This unit covered entrepreneurship in the digital age, turning problems into business ideas, prototyping, building MVPs, and identifying beachhead markets. Mastery of these concepts opens the door to careers in **startups and digital innovation**. Pakistan has many incubators (for example, National Incubation Centres, NICs, in major cities) that support young founders.

Career	What the person does
Tech Entrepreneur / Startup Founder	Identifies a real-world problem and builds a digital product or service to solve it, guiding it from prototype through to MVP and market launch.
Product Manager	Guides a product's direction by identifying user needs, prioritising features, and testing ideas through prototypes and MVPs.
Business Analyst	Analyses business problems and processes to recommend digital solutions, often testing assumptions before full investment.
Innovation / Startup Consultant	Advises businesses or founders on validating ideas, building MVPs, and identifying beachhead markets.
Digital Marketing Specialist	Plans how a new product or MVP will reach its first (beachhead) market and grow its user base.
Venture / Incubator Analyst	Evaluates early-stage startup ideas and prototypes for potential investment or incubation support.

WORKED EXAMPLE

Worked example: match the task to the career.

1. "Decide whether the canteen app should add payments next or a weekly menu." → **Product Manager** (prioritising features).
2. "Run a WhatsApp and Instagram campaign to get the first 100 users in one college." → **Digital Marketing Specialist**.
3. "Review 20 student startup pitches and pick 5 for incubation." → **Venture / Incubator Analyst**.

REMEMBER IT

Every career in the table uses the same chapter skills: **understand users, test assumptions, start small**.

COMMON MISTAKE

Mistake: Thinking startup careers are only for programmers.

Fix: Product managers, analysts, consultants and marketers often write little or no code; they test ideas and understand users.

اردو میں سمجھیں

اس باب کی مہارتیں اسٹارٹ اپ اور ڈیجیٹل جدت کے شعبوں میں روزگار کے دروازے کھولتی ہیں، جیسے اسٹارٹ اپ بانی، پراڈکٹ مینیجر، بزنس اینالسٹ، اسٹارٹ اپ کنسلٹنٹ، ڈیجیٹل مارکیٹنگ ماہر اور انکیوبیٹر اینالسٹ۔ ان سب کاموں میں صارف کو سمجھنا، مفروضے آزمانا اور چھوٹے پیمانے سے شروع کرنا بنیادی ہے۔

CHECK YOURSELF

1. Which career plans how an MVP will reach its beachhead market?

2. What does a Business Analyst often do before full investment?

Answers: 1. Digital Marketing Specialist. 2. Tests assumptions (after analysing business problems and processes).

ACADEMY DRILL

Timed 10 minutes. Books closed. Mark at once with the answers in this box — this is class work, not homework.

1 mark. Which career plans how an MVP will reach its beachhead market?

3 marks. Explain Career Opportunities with two clear points and one example.

5 marks. Write a 5-mark answer on Career Opportunities: definition, two points, a labelled diagram or table, and one example.

Answers: 1. Digital Marketing Specialist 3. Mastery of these concepts opens the door to careers in startups and digital innovation.; Pakistan has many incubators (for example, National Incubation Centres, NICs, in major cities) that support young founders. 5. Use the recipe in the blue box. Model opening: This unit covered entrepreneurship in the digital age, turning problems into business ideas, prototyping, building MVPs, and identifying beachhead markets.

BATCH HOMEWORK

Write a 5-mark answer on **Career Opportunities** using Define · Explain · Example · Diagram. Learn the Check yourself questions so you can answer them in 60 seconds at the start of next class.

How you will mark it tomorrow: Collect next class. Stamp full / half / zero against the 5-mark recipe.

کل جمع کرائیں؛ بغیر ورکنگ کے جواب آدھے نمبر ہیں۔

Chapter 6 Review

Chapter summary

- **Entrepreneur:** a person who identifies a problem, thinks of a solution, and turns it into a product or service; observes people, takes calculated risks, improves step by step.
- **Entrepreneurship:** the process of planning, starting, testing and improving a business idea until it becomes useful (Problem → Solution → Product).
- **Digital age:** entrepreneurs use accessible digital tools (social media, forms, websites, WhatsApp, digital payments) to start and test ideas quickly with low investment; often no coding is needed.
- A digital idea must solve a **real problem for real users**, not just sound modern (Table 6.1 examples: notices, embroidery shop, test dates, canteen queues).
- **Business ideas** come from observing daily life and talking directly to users: Observe → Ask Users → Select One Problem → Suggest Solution → Test Early. Start with a small, clear problem.
- **Prototype:** an early model used to show and test the design of an idea; not the final product; makes the idea visible, finds mistakes early, saves time and money.
- **Fidelity** is how close a prototype is to the final product: Low (paper), Mid (PowerPoint/Canva/Figma, tests navigation), High (realistic, Figma/HTML, only after the idea is tested).
- **Development cycle:** Design → Build → Test → Iterate, repeated (iteration). Feedback is crucial; a prototype fails only if useful feedback is ignored.
- **MVP:** the simplest working version with only essential features (Minimum) that still solves the main problem (Viable); it tests real use and market demand.
- **Prototype vs MVP:** prototype asks "Does it look right?"; MVP asks "Will people actually use it?" A prototype may not work; an MVP must.
- **Riskiest assumption:** the untested belief that, if wrong, will make the business fail; test it early with real behaviour.
- **MVP plan:** problem, target users, ONE main feature, basic design, cost, marketing, feedback, improvement plan. Do not build everything at once.
- **Canteen case study:** paper prototype → Google Form MVP with 5 items for 3 days → staff found too many items hard → kept 5 items, separate line, orders close 20 minutes before break.
- **MVP testing:** plan users, duration and data in advance; collect numbers (40 tried, 30 would return = 75%) and comments/observations; count, look for repeated problems, fix the most important first.
- **Beachhead market:** a small, focused, reachable group of first users with a strong, immediate need; win it first, then expand.
- **Ethics and equity:** respect privacy, truthfulness and fairness; collect no unnecessary data; share nothing without permission; design for weak internet, limited devices and Urdu/Sindhi speakers.

Key terms

Term	Meaning	اردو
Entrepreneur	A person who identifies a problem, thinks of a solution, and turns it into a product or service.	کاروباری شخص
Entrepreneurship	The process of planning, starting, testing and improving a business idea.	کاروبار کاری
Calculated risk	A risk taken after carefully thinking about the possible loss and keeping it small.	سوچا سمجھا خطرہ
Digital entrepreneurship	Using digital tools to start, test, improve and grow a business idea.	ڈیجیٹل کاروبار کاری
Business idea	A proposed product or service that solves a real problem for real users.	کاروباری خیال
Target users	The people who will use the product first.	ہدف صارفین
Prototype	An early model of a product, service, website or app made to test the idea and collect feedback.	ابتدائی نمونہ
Fidelity	How close a prototype is to the final product.	اصل سے مطابقت کا درجہ
Low-fidelity prototype	A quick, rough paper model showing the main idea and flow.	کم تفصیل والا نمونہ
Mid-fidelity prototype	A clearer model in PowerPoint, Canva or Figma showing layout and navigation without final graphics.	درمیانی تفصیل والا نمونہ
High-fidelity prototype	A detailed model close to the final product with realistic colours, buttons, data and working features.	زیادہ تفصیل والا نمونہ
Wireframe	A simple outline drawing of a screen showing where items go, without colours or pictures.	اسکرین کا خاکہ
Navigation	How a user moves from one screen to another.	اسکرینوں کے درمیان آمد و رفت
Iteration	Repeating the cycle of creating, testing and improving.	بار بار دہرانا
Feedback	Users' responses and comments about a product or idea.	رائے
Minimum Viable Product (MVP)	The simplest working version of a product with only the essential features, used to test the idea with real users.	کم از کم قابل عمل پراڈکٹ

Term	Meaning	اردو
Viable	Usable enough to actually solve the main problem.	قابلِ عمل
Market demand	Whether enough people want and will use or pay for a product.	بازار کی طلب
Assumption	Something we believe to be true but have not tested yet.	مفروضہ
Riskiest assumption	The belief that would make the whole business fail if it turned out to be wrong.	سب سے خطرناک مفروضہ
MVP plan	A plan stating problem, target users, main feature, design, cost, marketing, feedback and improvement.	ایم وی پی کا منصوبہ
Number-based feedback	Feedback in counts, e.g. how many tried the MVP or would use it again.	عددی رائے
Comment-based feedback	Feedback in words explaining likes, dislikes or confusion.	تبصراتی رائے
Observation	Watching users to see where they face difficulty.	مشاہدہ
Beachhead market	A small, focused group of first users with a clear need who are likely to try the product early.	ابتدائی مخصوص مارکیٹ
Rubric	A marking guide describing levels of quality for each criterion.	جانچ کا معیار نامہ
Privacy	A person's right to control their personal information.	رازداری
Equity	Making sure people with fewer resources or language difficulty can also use a solution.	مساوی رسائی
Startup	A new, small business built around a new product or service idea.	نیا کاروبار

Practice: multiple choice

1. An entrepreneur is best described as a person who:
 - a. only invests money in big companies
 - b. identifies a problem and tries to turn a solution into a product or service
 - c. always works from a large office
 - d. only writes computer programs
2. In prototyping, "fidelity" means:
 - a. the cost of the prototype
 - b. the number of users
 - c. how close the prototype is to the final product
 - d. the speed of the internet
3. Which of these is a low-fidelity prototype?
 - a. Hand-drawn app screens on paper
 - b. A working demo website of an order form
 - c. Clickable screens in Figma
 - d. An app published on the Play Store
4. A mid-fidelity prototype is mainly useful for testing:
 - a. online payments
 - b. screen-to-screen navigation
 - c. market demand over three days
 - d. investor interest
5. The correct order of the prototype development cycle is:
 - a. Build, Design, Iterate, Test
 - b. Test, Build, Design, Iterate
 - c. Design, Test, Build, Iterate
 - d. Design, Build, Test, Iterate
6. Creating, testing, improving and testing a prototype again is called:
 - a. iteration
 - b. incubation
 - c. marketing
 - d. assumption
7. In MVP, the letter "V" stands for:
 - a. Visual
 - b. Valuable
 - c. Viable
 - d. Virtual
8. Which is the best MVP for a canteen pre-order idea?
 - a. A full app with login, payment, delivery tracking and discounts
 - b. A Google Form used for real orders for three days
 - c. Paper sketches shown to five friends
 - d. A colourful poster of the menu
9. A prototype mainly answers which question?
 - a. Does it look right and make sense?
 - b. Will people pay for it every month?
 - c. How big is the national market?
 - d. How much profit will we make?
10. The riskiest assumption is:
 - a. the cheapest feature to build
 - b. the colour scheme of the app
 - c. the name of the company
 - d. the belief that, if wrong, can make the whole business fail
11. Which is the best beachhead market for a new study app?
 - a. All students in Pakistan
 - b. All online shoppers
 - c. Grade XII students preparing for board exams in one college
 - d. All transport users
12. Which is NOT a characteristic of a good beachhead market?
 - a. Specific and narrowly defined
 - b. Reachable by the startup team
 - c. Users have a strong, immediate need
 - d. As large as possible from the first day
13. "30 out of 40 said they would use it again" is which type of feedback?
 - a. Number-based
 - b. Comment-based
 - c. Observation
 - d. Rubric-based
14. Which is an ethical practice when collecting user feedback?
 - a. Collect CNIC numbers of all users
 - b. Share users' phone numbers in the class group
 - c. Collect only necessary information and share nothing without permission
 - d. Change results so the idea looks better
15. To support users with weak internet and language difficulty, a design should use:
 - a. heavy videos on every screen
 - b. English-only instructions
 - c. features that need the latest phone
 - d. large buttons, simple Urdu/Sindhi instructions and low data usage

Practice: short questions

1. Define entrepreneur and entrepreneurship. How are they different?
2. What is meant by entrepreneurship in the digital age? Give two local examples that need no coding.
3. Write the five questions you should ask to find a problem in daily life.
4. Why should a student choose a small problem at the start? Give one example of a too-large and one of a suitable problem.
5. Define prototype and give three reasons why it is useful.
6. Differentiate between low-, mid- and high-fidelity prototypes, with one example of each.
7. Define MVP and explain the words "Minimum" and "Viable".
8. What is the riskiest assumption? Give the risky assumption and its test for the college van update system.
9. An MVP was tried by 40 students and 30 said they would use it again. Calculate the repeat-use rate and name two other kinds of feedback to collect.
10. State the three characteristics of a good beachhead market and give one weak and one better first market for an Ajrak catalogue.

Practice: long / problem questions

1. Explain the prototype development cycle with a labelled diagram. Use the ClassBuddy class activity to show what happens at each stage, and explain why negative feedback does not mean the prototype has failed.
2. Compare a prototype and an MVP under five headings (purpose, working status, users, cost, example). Use the canteen pre-order system as your example and state the key question each one answers.
3. **Plan an MVP for a college van update system** for a college in Hyderabad, where students and parents often do not know when the van will arrive. Fill in all eight elements of the MVP planning checklist, and also state the riskiest assumption, how to test it, and the beachhead market.
4. **Plan an MVP for a small Sindhi topi and Ajrak shop in Hala** that wants online customers. Describe a low-fidelity prototype, the MVP, its riskiest assumption and test, the beachhead market, the marketing method, and two ethical or equity points the shop must follow.
5. A team tested a Lost and Found MVP (Google Form + WhatsApp group) in a college of 60 Grade XII students for two weeks. 45 students tried it; 36 of them said they would use it again; 12 of the users said they did not know where to collect found items; the team observed that many reports had no photo. (a) Calculate the percentage of the class who tried it, the repeat-use rate among users, and the percentage of users confused about collection. (b) Classify each piece of feedback by type. (c) Decide which improvement to make first and justify it.

Answer key

Multiple choice

1. b
2. c
3. a
4. b
5. d
6. a
7. c
8. b
9. a
10. d
11. c
12. d
13. a
14. c
15. d

Short questions — model answers

1. An **entrepreneur** is a person who identifies a problem, thinks of a solution and tries to change that solution into a product or service. **Entrepreneurship** is the process of planning, starting, testing and improving a business idea, involving creativity, problem-solving, teamwork, communication and calculated risk. The entrepreneur is the person; entrepreneurship is the process.
2. It means using digital tools such as mobile phones, social media, websites, online forms, digital payments, maps, videos and simple apps to start, test, improve and grow a business idea. Examples: a student selling handmade cards through Instagram; a shopkeeper making a WhatsApp catalogue for Ajrak.
3. What problem do people face? Who faces this problem? How often does it happen? What do people currently do to solve it? Can technology help in a simple way?
4. Small, clear problems are easier to test and improve. Too large: "improving the whole education system". Suitable: "helping Grade XII students track practical file submission dates".
5. A prototype is an early model of a product, service, website or app that shows how the idea may look or work; it is not the final product and is made to test the idea and collect feedback. Useful because it makes the idea visible, helps find mistakes early (hard-to-find buttons, too much text, missing features), and saves time and money before final coding.
6. Low-fidelity: quick, rough paper model showing main idea and flow, e.g. hand-drawn homework-reminder screens. Mid-fidelity: clearer model in PowerPoint/Canva/Figma showing layout and navigation without final graphics, e.g. clickable PowerPoint screens. High-fidelity: detailed model close to the final product with realistic colours, buttons, sample data and working features, e.g. a working demo of a small order-form website.
7. An MVP (Minimum Viable Product) is the simplest working version of a product with only the most important features, used to test the idea with real users. Minimum: only the essential features, no extras. Viable: usable enough to actually solve the main problem.
8. It is the belief that can make the entire business fail if it turns out to be wrong. For the van update system: "Parents and students will check van updates daily." Test: create a trial WhatsApp broadcast group for one route.
9. Repeat-use rate = $(30 \div 40) \times 100 = 75\%$. Other feedback: comment-based (e.g. "What was confusing?") and observation (e.g. where users faced difficulty, such as forgetting to enter class name).
10. Specific and narrowly defined; reachable by the team; users have a strong, immediate need. Ajrak catalogue: weak = all online shoppers; better = existing customers of one local shop.

Long questions — model answers

1. **Prototype development cycle.** Draw four boxes in a loop: Design → Build → Test → Iterate → back to Design. Prototype development is not one-time; repeating the cycle is called iteration.
 - o **Design:** understand the problem and plan what the prototype shows. ClassBuddy: interview 10 students; 7 of 10 forget tasks, so show a daily task list; reminders are needed before leaving home, so add a morning notification; students want simplicity, so use large buttons and clear labels.
 - o **Build:** create the first version to make the idea visible (not beautiful). ClassBuddy: three paper screens (Today's classes, Add homework, Show reminder) joined by arrows.
 - o **Test:** show it to users and observe. ClassBuddy: five classmates try "add one homework task" while the observer watches silently.
 - o **Iterate:** improve from feedback. ClassBuddy: larger, centred Add Homework button; subject name and due date fields; a Weekly View button.

Negative feedback is information that shows what to fix; the prototype fails only if the team ignores useful feedback.

2. **Prototype vs MVP.** Purpose: prototype shows how the idea may look or work; MVP tests whether users will actually use it. Working status: prototype may not work (sketch or model); MVP must work at least in a basic way. Users: prototype, a small group giving design feedback; MVP, early real users in daily life. Cost: prototype very low; MVP low but may need basic development. Example: prototype = paper screens for a canteen order system; MVP = Google Form used for real canteen orders for three days. Key questions: prototype, "Does it look right and make sense?"; MVP, "Will people actually use it and find value in it?"

3. **MVP plan: college van update system (Hyderabad).**

- o Problem: students and parents do not know when the van will arrive, so students wait outside for a long time or miss the van.
- o Target users: students and parents on one van route.
- o Main feature: the driver or a route monitor sends a short "Van left / 5 minutes away" message.
- o Basic design: one WhatsApp broadcast message with route stop name, time and status; voice note option for parents who cannot read.
- o Cost: free, using a WhatsApp broadcast list on the monitor's phone.
- o Marketing: a message in the class WhatsApp group and a printed slip for parents with the number to save.
- o Feedback: after one week, a 3-question Google Form or phone call: Did you check the updates daily? Did you wait less? Would you continue?
- o Improvement plan: if messages arrive too late, send them earlier; if many parents do not read, switch to voice notes; then expand to a second route.
- o Riskiest assumption: parents and students will check van updates daily. Test: trial broadcast group for one route for one week, counting how many people read or reply to messages each day.
- o Beachhead market: students and parents of ONE specific college van route.

4. **MVP plan: topi and Ajrak shop in Hala.**

- o Low-fidelity prototype: paper catalogue pages, one per product, with a sketch, price, size/type and "Message to order"; shown to 5 customers to see if information is clear.
- o MVP: a WhatsApp Business catalogue with real photos and prices for 10–15 best-selling items; orders by chat; payment by cash on delivery or JazzCash/Easypaisa.
- o Riskiest assumption: customers will actually place orders through WhatsApp. Test: share the catalogue with 30 existing customers and record actual orders for two weeks.
- o Beachhead market: existing customers of this one shop (people who have bought before and whose numbers the shop already has with permission).
- o Marketing: broadcast message to existing customers, a QR code at the shop counter, posts in local Facebook groups.
- o Ethics: share no customer numbers or photos without permission; give truthful prices, sizes and photos. Equity: simple Urdu/Sindhi descriptions and compressed photos for low data use.
- o Improvement plan: drop designs nobody orders, add more of the popular ones, then expand to customers in Hyderabad and Karachi.

5. Lost and Found MVP analysis.

- o (a) Tried: $(45 \div 60) \times 100 = 75\%$ of the class. Repeat-use rate: $(36 \div 45) \times 100 = 80\%$. Confused about collection: $(12 \div 45) \times 100 = 26.7\%$ (about 27%).
- o (b) "45 tried" and "36 would use again": number-based. "Did not know where to collect": comment-based (12 users said it). "Many reports had no photo": observation.
- o (c) Fix the collection confusion first: it is a repeated problem (more than a quarter of users) and it stops the system's main purpose, which is returning items to owners. Add "Collect found items from the library desk" at the top of the form and pin it in the WhatsApp group. Next, make the photo field strongly encouraged (or required for found items), since photos help owners recognise items. Re-test for another week and compare the numbers.

Self-assessment: I can...

- | | |
|--|--|
| ☐ define entrepreneur and entrepreneurship and describe an entrepreneur's habits. | ☐ explain how digital tools let me start and test an idea cheaply, with local examples. |
| ☐ use the five questions and the steps of Table 6.2 to turn a problem into an idea. | ☐ define a prototype and list its benefits and possible forms. |
| ☐ compare low-, mid- and high-fidelity prototypes. | ☐ draw and explain the Design-Build-Test-Iterate cycle. |
| ☐ turn user feedback into problems and improvements, as in Table 6.5. | ☐ define an MVP and explain how it differs from a prototype. |
| ☐ identify the riskiest assumption of an idea and design a test for it. | ☐ fill in an MVP plan and analyse MVP test results with percentages. |
| ☐ choose a specific, reachable beachhead market. | ☐ collect feedback ethically and design for equal access. |

FINAL REVISION

One-page recaps and a mock paper

Use these pages in the last week before the exam. Read one recap aloud from memory, then sit the mock paper in 2 hours 30 minutes with no notes.

امتحان سے ایک ہفتہ پہلے خلاصے زبانی دہرائیں، پھر ماک پیپر بغیر نوٹس کے حل کریں۔

Chapter 1 recap — Human Computer Interaction

- HCI = study of how people and computers work together so systems are usable, useful and satisfying.
- Traditional interaction = keyboard, mouse, menus. Natural interaction = touch, voice, gesture, gaze.
- Components: user, computer, interaction (input + output + feedback) inside an environment.
- UI = how it looks and the controls. UX = how the whole experience feels. Wireframe → prototype (Figma) → test.
- Evaluate with usability tests, heuristic evaluation, A/B tests and automated checks. Golden: accessibility, HCI problems, UI vs UX, testing methods.

Chapter 2 recap — Algorithms and Data Structures

- Correctness: trace table (variable values after every step) or stepwise reasoning.
- Clarity: modularity (small named parts) and readability (names, comments, indentation).
- Efficiency: count steps, conditions, repetitions. Big O: $O(1)$ constant, $O(\log n)$ binary search, $O(n)$ linear, $O(n \log n)$ good sorts, $O(n^2)$ nested loops.
- Linear DS: array, linked list, stack (LIFO, push/pop), queue (FIFO, enqueue/dequeue). Non-linear: tree (one root, parent-child), graph (nodes + edges).
- Pick the structure from the problem: undo → stack; printer jobs → queue; hierarchy → tree; maps → graph; fast index → array.

Chapter 3 recap — Python Data Structures, Functions and Files

- list [] ordered, mutable. tuple () ordered, immutable. set {} unordered, unique. dict {k:v} key-value, mutable.
- Functions: def, parameters, return. Local vs global scope. Built-in vs user-defined.
- Files: "r" read, "w" overwrite, "a" append. Always prefer with open(...) as f so the file closes itself.
- Exceptions: try / except / else / finally. Catch specific errors (ValueError, FileNotFoundError).

Chapter 4 recap — Data and Analysis

- SQLite in Python: connect → cursor → execute → commit → close. Always commit writes.
- Pandas DataFrame = table. load CSV/Excel, isnull, dropna, fillna, sort, filter, groupby.
- Charts: bar (categories), line (trend over time), pie (parts of a whole, few slices), histogram (distribution), scatter (relationship of two variables), box (spread and outliers).
- Mean = average. Median = middle after sorting. Mode = most frequent. Range = max-min. Variance / std-dev measure spread. pandas .std() uses sample n-1.

Chapter 5 recap — AI, Security and Collaboration

- AI ⊃ Machine Learning ⊃ Deep Learning. A neuron: weighted sum + bias, then an activation function. Deep = many hidden layers.
- Secure collaboration: authentication (passwords, MFA), access control (who may do what).
- Protect data: encryption, strong passwords, 3-2-1 backup, firewall. Threats: malware, phishing, DoS/DDoS, social engineering.
- Equity: everyone can take part (devices, language, disability, bandwidth). Tools: shared docs, video, LMS, versioning.

Chapter 6 recap — Entrepreneurship in the Digital Age

- Entrepreneur = person who turns a problem into a venture, taking risk. Digital tools make testing cheap (WhatsApp, Forms, a Facebook page).
- Prototype = experimental model. Low / mid / high fidelity. Cycle: Design → Build → Test → Iterate.
- MVP = smallest product that tests the riskiest assumption with real users. Prototype ≠ MVP (MVP is used in the real market).
- Beachhead market = the first, narrow group you can win. Measure retention, not only sign-ups. Use data ethically.

ACADEMY SESSION

Academy exam week — 7 days × 90 minutes.

Days 1-6: one chapter recap as an error clinic. Starter test from that chapter's Golden topics. Two students write a 5-mark answer on the board using the recipe.

Day 7: sit the mock paper in 2 hours 30 minutes, academy hall conditions. No notes, no phones. Invigilate as the board will.

چھ دن خلاصے اور ایئر کلینک، ساتویں دن ماک پیپر بغیر نوٹس کے کرائیں۔

BATCH HOMEWORK

After the mock, students mark with the key in this book. Each student lists every Golden topic they missed. Those topics become the last two 90-minute revision classes.

Collect the list next class. Re-teach any Golden that more than a third of the batch missed.

FULL-MARK ANSWER RECIPE

Mark the mock to the same 1 / 3 / 5 / 8–10 recipes used all year. An answer with no working, no diagram, or no example cannot score full marks.

Mock paper — Computer Science XII

Time: 2 hours 30 minutes | Total: 75 marks | Answer all of A and B; attempt three from C.

Section A — Multiple choice (15 × 1 = 15)

1. HCI stands for:
 - a. Human Computer Interaction
 - b. High Code Interface
 - c. Hardware Control Input
 - d. Hybrid Computing Internet
2. A wireframe is:
 - a. the final coloured UI
 - b. a simple layout sketch of screens
 - c. a compiled program
 - d. an encryption key
3. Which is $O(\log n)$?
 - a. Linear search
 - b. Nested for-loops
 - c. Binary search
 - d. Reading one array cell
4. A stack is:
 - a. FIFO
 - b. LIFO
 - c. random access only
 - d. unordered unique items
5. Which Python type is immutable?
 - a. list
 - b. dict
 - c. set
 - d. tuple
6. The file mode that overwrites an existing file is:
 - a. r
 - b. a
 - c. w
 - d. x+
7. `with open("t.txt") as f` is useful because:
 - a. it encrypts the file
 - b. it closes the file automatically
 - c. it creates a DataFrame
 - d. it skips exceptions
8. After INSERT in sqlite3 you must:
 - a. rollback always
 - b. commit
 - c. drop the table
 - d. print the cursor
9. A pie chart is a poor choice when:
 - a. you have 3 parts of a total
 - b. you have 20 tiny slices
 - c. you show percentages of a whole
 - d. you label each slice
10. pandas `df['x'].std()` uses:
 - a. population n
 - b. sample n-1
 - c. median
 - d. mode
11. Deep Learning is a subset of:
 - a. only statistics
 - b. Machine Learning
 - c. only HCI
 - d. only networking
12. MFA means:
 - a. Many File Archives
 - b. Multi-Factor Authentication
 - c. Main Firewall Access
 - d. Minimum Function API
13. A Caesar cipher is a form of:
 - a. phishing
 - b. encryption
 - c. a firewall
 - d. a prototype
14. An MVP is:
 - a. the most polished version of a product
 - b. the smallest product that tests the riskiest assumption
 - c. a paper sketch only
 - d. a full company registration
15. A printer job list is best modelled as a:
 - a. stack
 - b. queue
 - c. binary tree
 - d. set

Section B — Short questions (10 × 3 = 30)

1. Differentiate UI and UX with one example.
2. What is a trace table? Why is it better than "it looks right"?
3. Draw a 3-node stack after push 10, push 20, pop. Label TOS.
4. Write one difference each: list vs tuple vs set vs dictionary.
5. Write a Python function `area(l, w)` that returns $l*w$, and a call that prints it.
6. Name the five steps of a database connection in Python.
7. When would you draw a scatter plot rather than a line graph?
8. Compute mean, median and range of 4, 8, 6, 10, 2.
9. List three signs of a phishing message.
10. Differentiate a prototype and an MVP.

Section C — Long questions (3 × 10 = 30). Attempt any three.

1. A college wants a new student-portal. Describe need analysis, a low-fidelity wireframe of the login + timetable screens, three accessibility principles you would apply, and one usability test you would run.
2. Trace this algorithm with a table for $n = 5$: $total=0$; for i in $1..n$: $total = total + i$; return $total$. State its Big O and rewrite it as a formula that is $O(1)$.
3. Write a Python program that reads a text file of lines "name,marks", stores results in a dictionary, and writes "name: grade" to an output file using `with`. Grade A if marks ≥ 80 else B. Include exception handling if the file is missing.
4. Using the dataset 12, 18, 12, 20, 15, compute mean, median, mode, range, population variance and population standard deviation, showing every step. Then state which chart you would use to show the distribution and why.
5. A Karachi canteen wants a pre-order app. Identify the problem, the riskiest assumption, an MVP, a beachhead market, two test metrics, and one ethical rule for student data.

Mock paper — answers

Section A

1. a
2. b
3. c
4. b
5. d
6. c
7. b
8. b
9. b
10. b
11. b
12. b
13. b
14. b
15. b

Section B

1. UI is the screens and controls (buttons, colours). UX is the whole journey (time to complete a task, frustration, trust). Example: a JazzCash send-money screen (UI) vs how safe and quick the payment felt (UX).
2. A trace table lists each variable after every instruction. It proves correctness on a chosen input; "it looks right" misses off-by-one and uninitialised variables.
3. After push 10, TOS=10. After push 20, TOS=20 (10 below). After pop, 20 removed, TOS=10.
4. list: ordered mutable. tuple: ordered immutable. set: unordered unique. dict: keyed pairs.
5. `def area(l, w): return l * w then print(area(3, 4))` → 12.
6. connect, cursor, execute, commit, close.
7. Scatter: two measured variables (height vs marks) with no single time axis. Line: one quantity changing over an ordered time or sequence.
8. Sorted: 2,4,6,8,10. Mean = $30/5 = 6$. Median = 6. Range = $10-2 = 8$.
9. Unknown sender, urgent threat ("account will close today"), a link that does not match the real bank, request for OTP/password, poor Urdu/English, unexpected attachment.
10. A prototype is a model used to learn (often internal). An MVP is a real, usable product with just enough features to test the riskiest assumption with actual customers.

Section C — outline

1. Need analysis: who (students, teachers), tasks (view timetable, submit leave), constraints (mobile, slow internet). Wireframe: simple boxes for logo, fields, button, a second screen with a 5-day table. Accessibility: large tap targets, colour not the only signal, Urdu/English labels, screen-reader names. Test: five students think-aloud while logging in; record errors and time.
2. $i=1$ total=1; $i=2$ total=3; $i=3$ total=6; $i=4$ total=10; $i=5$ total=15. Loop body runs n times → $O(n)$. Formula $n*(n+1)/2$ is $O(1)$.
3. try: with open(path) as f: for line in f: name, m = line.strip().split(","); d[name]=int(m) except FileNotFoundError: print("missing"). Then with open(out,"w") as g: write grades. Show one sample dictionary.
4. Sorted 12,12,15,18,20. Mean $77/5=15.4$. Median 15. Mode 12. Range 8. Population variance: deviations -3.4, -3.4, -0.4, 2.6, 4.6; squares 11.56, 11.56, 0.16, 6.76, 21.16; sum 51.2; $/5 = 10.24$. std = 3.2. Histogram to show distribution (or bar of frequencies).
5. Problem: long canteen queues between periods. Riskiest assumption: students will pre-order 10 minutes before break. MVP: WhatsApp number + Google Form, pickup tokens, no app. Beachhead: one shift of first-year students. Metrics: % of orders picked up, time-to-collect, repeat use. Ethical: do not publish phone numbers; delete form responses after the term.