

Lecture 04

Data and Analysis

Chapter lecture — 15 topics with explanations, worked examples, Urdu notes, practice questions and a full answer key.

BIEK Computer Science XI · Bilingual support: English + اردو

بی آئی ای کے کمپیوٹر سائنس — گیارہویں جماعت

15 book lectures in this pack

★ Golden topics, Urdu notes, review and answer key

XI

How to use this BIEK Computer Science lecture

Each PDF is a classroom lecture from the BIEK / Sindh Computer Science textbooks (New Sindh Curriculum, STBB Grade XI–XII). Read *Learn it*, study the SVG diagram, try the worked example on paper, then answer *Check yourself* before looking at the answers. **Extra board practice** (MCQs, short and long questions) is added after the book content — it is not in the textbook. Career-only extras that were not in the book lecture list have been removed. Math is rendered with MathJax. ★ Golden topics are high-yield in board exams. The green box repeats the idea in Urdu.

ہر لیکچر بی آئی ای کے / سندھ نصاب کی کتاب کے درس کے مطابق ہے۔ سبق پڑھیں، مثال حل کریں، پھر چیک یورسیلف کے سوالات کے جواب اپنے نوٹ بک میں لکھیں۔ کتاب کے بعد اضافی بورڈ پریکٹس ہے۔ ★ گولڈن ٹاپکس امتحان میں زیادہ پوچھے جاتے ہیں۔

Lectures in this pack

Chapter 4: Data and Analysis. Study one lecture at a time, then use the chapter review and answer key at the end of this PDF.

L01. 4.1.1 Data, Information and Database

L02. 4.1.2 Database Management System (DBMS)

L03. 4.2 Database Components (Tables, Records, Fields)

L04. 4.3.1 Keys and Integrity Constraints

L05. 4.3 Relational Database Management System (RDBMS)

L06. 4.4 Entity Relationship Model (ER-Model)

L07. 4.5 Referential Integrity (Cascade Update & Delete)

L08. 4.6 Relational Schema Development

L09. 4.7 Case Study — Library Management System

L10. 4.8 Different Database Objects (Tables, Forms, Queries, Reports)

L11. 4.9 Creation of Tables in Microsoft Access

L12. 4.10 Designing Forms for Data Manipulation

L13. 4.11 Creating Queries in MS Access

L14. 4.11.4 Data Summarization & Statistical Analysis

L15. 4.11.6 Data Visualization in MS Access (Charts)

Data and Analysis

This chapter teaches you how raw facts become organised information in a database, how tables are linked with keys, how to draw an ER diagram, and how to build tables, forms, queries and charts in Microsoft Access. Banks, NADRA, college libraries and fee offices all run on these ideas.

اس باب میں آپ سیکھیں گے کہ خام حقائق کو ڈیٹا بیس میں کیسے منظم کیا جاتا ہے، ٹیبلز کو کیسے سے کیسے جوڑا جاتا ہے، ای آر خاکہ کیسے بنتا ہے، اور مائیکروسافٹ ایکسیس میں ٹیبل، فارم، کوئری اور چارٹ کیسے بنائے جاتے ہیں۔

What you will learn

- Distinguish data, information and a database, and explain what a DBMS does.
- Choose candidate, primary, alternate and foreign keys and state integrity rules.
- Explain referential integrity, Cascade Update and Cascade Delete with before/after tables.
- Develop the college-library case study from requirements to the final ER schema.
- Create tables in Access (Datasheet and Design view) and pick data types.
- Identify tables, records and fields in a given example.
- Draw ER diagrams (entities, attributes, relationships) and give cardinality 1:1, 1:M, M:N.
- Write a relational schema and resolve an M:N relationship with a junction table.
- State the job of tables, forms, queries and reports.
- Build a form with the Form Wizard and a SELECT query with criteria, AND/OR, totals and charts.

4.1.1 Data, Information and Database

LEARN IT

Data are unprocessed facts, figures or observations. They can be **quantitative** (numbers: 80, 75, 90) or **qualitative** (descriptions: the colours of cars in a parking lot). Data on its own is not very useful — a list of marks does not yet tell you whether the class is strong.

When you organise, process and interpret data, it becomes **information**. Information has meaning and supports a decision. Example: "The class average is 80%, so we can move to the next chapter."

A **database** is an organised collection of **related** data, stored in a structured way so it can be accessed, managed and updated easily. Paper registers and loose files make searching painful; a database is built for search, update and sharing.



Aspect	Data	Information
Definition	Raw facts and figures	Processed, meaningful data
Example	85, 90, 75	Average marks = 83.3%
Usefulness	Little, on its own	Useful for decisions

WORKED EXAMPLE

Five CS XI marks: 80, 75, 90, 70, 85. Sum = 400. Average = $400 \div 5 = 80\%$. The numbers are data; "the class average is 80%" is information; a **Student** table holding every student's marks is a database.

REMEMBER IT

Exam line: *Data is raw; information is processed data used for decision-making. Always add one pair of examples.*

COMMON MISTAKE

Do not call a jumble of WhatsApp numbers a database. Related + structured + easy to update is what makes it a database.

اردو میں سمجھیں

ڈیٹا خام حقائق ہیں، معلومات وہی حقائق ہیں جب انہیں ترتیب دے کر معنی دے دیا جائے۔ ڈیٹا بیس متعلقہ ڈیٹا کا منظم ذخیرہ ہے جسے آسانی سے تلاش اور تبدیل کیا جا سکتا ہے۔

CHECK YOURSELF

1. Is "Nadia, Class 11, 72 marks" data or information?
2. Why is a stack of unmarked answer sheets not a database?

Answers: 1. Data (raw facts about one student). 2. It is not organised in a structured, searchable, updatable collection of related records.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Data is:

- a. Raw unprocessed facts
- b. Always information
- c. Always a graph
- d. A program

MCQ 2. Information is:

- a. Processed, meaningful data
- b. Noise only
- c. A cable
- d. A gate

MCQ 3. A database is:

- a. An organised collection of related data
- b. A single unsorted scrap
- c. A CPU fan
- d. A pie chart

MCQ 4. Marks 45, 67, 12 are:

- a. Data
- b. Information already
- c. A query
- d. A report

MCQ 5. "Ali failed" after processing marks is:

- a. Information
- b. Raw data only
- c. A primary key
- d. A form

MCQ 6. Storing related tables together is the job of a:

- a. Database
- b. Compiler
- c. Router
- d. K-map

Extra short questions

1. Differentiate data and information with a school example.
2. Define database.
3. Give two problems of storing data only in paper lists.
4. Is a phone contacts app a database?

Extra long question

1. A college keeps loose pages of marks. Argue, with definitions, why they should move to a database, and what information a principal could then get.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Data: 45, 67. Information: class average is 56 so we need extra classes.
2. Organised related data stored so it can be retrieved quickly.
3. Slow search, duplication, hard updates, errors.
4. Yes — organised related records (name, number).

Long

1. Define data/information/database. Benefits: search, consistency, reports (fail list, subject averages). One risk: need backup/access control.

4.1.2 Database Management System (DBMS)

LEARN IT

A **DBMS** is software that lets you create, manage and interact with databases. It sits between the user and the stored files. You never edit raw data files by hand — you talk to the DBMS (Access, MySQL, Oracle, SQLite) and it handles storage, security and consistency.

Advantages you must be able to list:

- **Less redundancy.** The department name is stored once, not in every student row.
- **Consistency.** Change a phone number once; every screen that uses it shows the new number.
- **Security.** Only authorised users see sensitive fields (an admin sees marks; office staff see names).
- **Integrity.** Rules stop duplicate roll numbers and empty primary keys.

WORKED EXAMPLE

In a paper register, Ali's address is written on the admission page, the fee page and the sports page. If he moves house, two of the three pages stay wrong. In a DBMS, `Address` lives in one **Student** table. Every form and report reads that single field.

اردو میں سمجھیں

ڈی بی ایم ایس وہ سافٹ ویئر ہے جو صارف اور ڈیٹا بیس کے درمیان پل کا کام کرتا ہے۔ اس سے تکرار کم ہوتی ہے، ڈیٹا ایک جیسا رہتا ہے، صرف مجاز افراد دیکھ سکتے ہیں، اور غلط اندراج رک جاتی ہے۔

CHECK YOURSELF

1. Name two DBMS programs.
2. Which advantage stops two students sharing the same roll number?

Answers: 1. MS Access, MySQL (Oracle, SQLite also). 2. Integrity (unique / primary-key constraint).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A DBMS is software that:

- a. Creates and manages databases
- b. Draws only pie charts
- c. Routes IP
- d. Sorts using bubble only

MCQ 2. Examples of DBMS:

- a. MS Access, MySQL, SQLite, Oracle
- b. Python only
- c. Figma only
- d. Chrome only

MCQ 3. DBMS handles:

- a. Storage, retrieval, security, multi-user access
- b. Only fonts
- c. Only OSI layer 1
- d. Only NAND

MCQ 4. Without a DBMS, programs would:

- a. Each invent their own file format
- b. Run faster always
- c. Need no keys
- d. Need no SQL

MCQ 5. Access is used in XI because:

- a. It is a GUI DBMS for tables/forms/queries/reports
- b. It is a programming language
- c. It is Agile
- d. It is analog

MCQ 6. SQLite in XII is a:

- a. Lightweight DBMS/library
- b. Chart
- c. Gate
- d. Sprint

Extra short questions

1. Define DBMS.
2. Four DBMS functions.
3. DBMS vs database.
4. Name two desktop and two server DBMS.

Extra long question

1. Compare managing 500 students in Excel vs a DBMS (Access). Use data integrity, search, multi-user and reports.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Database Management System: software to define, store, query, protect and share a database.
2. Create tables, insert/update/delete, query, enforce keys/security, backup.
3. Database is the data; DBMS is the software that manages it.
4. Desktop: Access, SQLite. Server: MySQL, Oracle, PostgreSQL.

Long

1. Excel: easy but duplicates, weak keys, clash when two people edit. DBMS: primary keys, queries, forms, reports, controlled access.

4.2 Database Components (Tables, Records, Fields)

LEARN IT

The basic structure is a **table** (also called a relation): rows and columns, like a spreadsheet, holding facts about one kind of thing (Students, Teachers, Books).

A **record** (row, tuple) is one complete instance — everything about Ali. A **field** (column, attribute) is one kind of fact — the whole `Name` column, or the whole `Grade` column.

Roll No	Name	Course	Grade
101	Ali	CS	A
102	Sara	IT	B+
103	Ahmed	CS	A

The row `101 | Ali | CS | A` is one **record**. The `Name` column is one **field**.

REMEMBER IT

Memory: **row = record = one person. column = field = one question on the admission form.**

COMMON MISTAKE

Do not mix two entities in one table (students and library books together). Each entity gets its own table; keys will link them later.

اردو میں سمجھیں

ٹیبل قطاروں اور کالموں میں ڈیٹا رکھتا ہے۔ ایک قطار ایک ریکارڈ (مثلاً علی کی پوری معلومات) ہے، ایک کالم ایک فیلڈ (مثلاً صرف نام) ہے۔

CHECK YOURSELF

1. How many records and how many fields are in the table above?
2. Is "CS" a record or a field value?

Answers: 1. 3 records, 4 fields. 2. A value stored in the Course field.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A table is:

- a. Rows and columns of one entity type
- b. A Python for-loop
- c. A cable
- d. A sprint

MCQ 2. A record is:

- a. One row
- b. One column
- c. The DBMS name
- d. A query

MCQ 3. A field/attribute is:

- a. One column
- b. The whole database
- c. A report
- d. A form

MCQ 4. A value in one cell is:

- a. A data item
- b. A relationship
- c. A schema
- d. A view

MCQ 5. Students table columns might be:

- a. id, name, class
- b. AND, OR, NOT
- c. HTTP, TCP
- d. Mean, π

MCQ 6. Many records share the same:

- a. Fields (structure)
- b. Primary key value
- c. OSI layer
- d. Random NAND

Extra short questions

1. Define table, record, field.
2. Give a 3-field student record example.
3. What is a data type of a field?
4. Why not put two entities in one messy table?

Extra long question

1. Design a Marks table: fields, types, one sample record, and which field will likely become the primary key.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Table: entity set. Record: one instance. Field: one property.

2. 101 | Ali | 85

3. The kind of value: Number, Text, Date, Yes/No.

4. Duplication and update anomalies — later ER/normalisation.

Long

1. roll (Number, PK), name (Text), subject (Text), marks (Number). Sample 12, Ali, CS, 85.
Justify uniqueness of roll or roll+subject.

4.3.1 Keys and Integrity Constraints ★ Golden

LEARN IT

A **key** is a field (or a set of fields) that uniquely identifies records and links tables. Integrity constraints are the rules that keep those keys honest.

Candidate key. Any field (or combination) that *could* uniquely identify a row. A table may have several. In an Employee table: EmpID, EmpLicense# and EmpPassport are all candidate keys.

Primary key (PK). The one candidate you actually choose. Rules: unique, never NULL, only one PK per table (it may be a **composite** of two columns). Example: EmpID.

Alternate key. The leftover candidate keys. After EmpID is chosen, EmpLicense# and EmpPassport become alternate keys — still unique, just not “the” identifier.

Foreign key (FK). A field in this table that refers to the PK of another table. It *may* contain duplicates (many employees in one department) and, in some designs, NULL.

WORKED EXAMPLE

Classroom analogy. Roll Number, B-Form number and phone number can all identify a student (candidate keys). The school picks Roll Number as the primary key. B-Form and phone become alternate keys. In a **Result** table, RollNo is a foreign key pointing back to Student.

Table	Field	Role
Student	RollNo	Primary key
Student	BFormNo	Alternate key
Result	RollNo	Foreign key → Student.RollNo
Result	ExamID + RollNo	Could be a composite primary key

EXAM TIP

Board questions: “Differentiate primary and foreign key” (table of 4 points) and “Why can a PK not be NULL?” Because a NULL would mean “this row has no identity”, so the DBMS could not tell rows apart.

COMMON MISTAKE

A phone number is a bad PK: people change numbers, two siblings may share one, and some students have none (NULL). Roll numbers are issued by the school and stay unique.

اردو میں سمجھیں

کینڈیڈیٹ کی وہ فیلڈ ہے جو ریکارڈ کی شناخت کر سکے۔ پرائمری کی منتخب شدہ شناخت ہے — منفرد اور خالی نہیں۔ جو بچ جائیں وہ آلٹرنیٹ کیز ہیں۔ فارن کی دوسرے ٹیبل کی پرائمری کی طرف اشارہ کرتی ہے اور ٹیبلز کو جوڑتی ہے۔

CHECK YOURSELF

1. Can a table have two primary keys?
2. Can a foreign key have duplicate values?

Answers: 1. No — only one PK (it may be composite). 2. Yes — many child rows may point to the same parent.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A primary key:

- a. Uniquely identifies each record
- b. May freely repeat
- c. Is always a name
- d. Is a chart

MCQ 2. A candidate key is:

- a. Any field set that could be the PK
- b. A foreign key
- c. A report
- d. A form

MCQ 3. An alternate key is:

- a. A candidate not chosen as PK
- b. A duplicate PK
- c. A null PK
- d. A pie

MCQ 4. A foreign key:

- a. Refers to a PK in another table
- b. Is always unique in its table
- c. Sorts the table
- d. Encrypts the DB

MCQ 5. NULL in a primary key is:

- a. Not allowed
- b. Required
- c. A default
- d. A relationship type

MCQ 6. Integrity constraints exist to:

- a. Stop invalid data
- b. Draw graphs
- c. Route packets
- d. Compile Python

Extra short questions

1. Define PK, FK, candidate, alternate.
2. Give a two-table example with an FK.
3. Entity integrity rule.
4. Why not use student name as PK?

Extra long question

1. For Members and Borrow in a library, choose keys and write two integrity rules. Show one invalid insert the DBMS should reject. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. PK: chosen unique identifier. Candidate: any unique identifier. Alternate: unused candidate. FK: copy of another table's PK.
2. Students(roll PK); Marks(roll FK, subject, score).
3. PK unique and not NULL.
4. Names duplicate and change.

Long

1. MemberID PK; Borrow(BorrowID PK, MemberID FK). Reject Borrow with unknown MemberID or NULL MemberID. Mention cascade later.

4.3 Relational Database Management System (RDBMS)

LEARN IT

An **RDBMS** stores data in several tables and uses primary and foreign keys to keep relationships. Banks, universities and NADRA use RDBMS software. Extra strengths on top of a plain DBMS:

- Reduces redundancy by splitting data into related tables.
- Supports many users at once, with permissions.
- Is queried with **SQL** (Structured Query Language) — a standard language of SELECT, INSERT, UPDATE, DELETE.

WORKED EXAMPLE

Instead of one giant spreadsheet of students-and-departments, an RDBMS has
Department(DeptID, DeptName) and Student(RollNo, Name, DeptID FK). CS is stored once.

SQL: SELECT Name FROM Student WHERE DeptID = 1;

اردو میں سمجھیں

آر ڈی بی ایم ایس کئی ٹیبلز میں ڈیٹا رکھتا ہے اور کیز سے ان کے تعلقات برقرار رکھتا ہے۔ ایس کیو ایل سے سوال پوچھے جاتے ہیں۔ اس سے تکرار کم اور کئی صارفین محفوظ طریقے سے کام کر سکتے ہیں۔

CHECK YOURSELF

1. What language do you use to query an RDBMS?
2. Why split Department out of the Student table?

Answers: 1. SQL. 2. To store the department name once (less redundancy) and update it in one place.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A DBMS is software that:

- a. Creates and manages databases
- b. Draws only pie charts
- c. Routes IP
- d. Sorts using bubble only

MCQ 2. Examples of DBMS:

- a. MS Access, MySQL, SQLite, Oracle
- b. Python only
- c. Figma only
- d. Chrome only

MCQ 3. DBMS handles:

- a. Storage, retrieval, security, multi-user access
- b. Only fonts
- c. Only OSI layer 1
- d. Only NAND

MCQ 4. Without a DBMS, programs would:

- a. Each invent their own file format
- b. Run faster always
- c. Need no keys
- d. Need no SQL

MCQ 5. Access is used in XI because:

- a. It is a GUI DBMS for tables/forms/queries/reports
- b. It is a programming language
- c. It is Agile
- d. It is analog

MCQ 6. SQLite in XII is a:

- a. Lightweight DBMS/library
- b. Chart
- c. Gate
- d. Sprint

Extra short questions

1. Define DBMS.
2. Four DBMS functions.
3. DBMS vs database.
4. Name two desktop and two server DBMS.

Extra long question

1. Compare managing 500 students in Excel vs a DBMS (Access). Use data integrity, search, multi-user and reports.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Database Management System: software to define, store, query, protect and share a database.
2. Create tables, insert/update/delete, query, enforce keys/security, backup.
3. Database is the data; DBMS is the software that manages it.
4. Desktop: Access, SQLite. Server: MySQL, Oracle, PostgreSQL.

Long


1. Excel: easy but duplicates, weak keys, clash when two people edit. DBMS: primary keys, queries, forms, reports, controlled access.

4.4 Entity Relationship Model (ER-Model) ★ Golden

LEARN IT

The **ER model** is the architect's blueprint: you draw what will be stored and how it connects *before* you create tables in Access. Three building blocks:

Component	Meaning	Symbol	Example
Entity	A real-world object we store data about	Rectangle	STUDENT, TEACHER, COURSE
Attribute	A property of an entity. PK is underlined	Oval	StudentID, Name, Class
Relationship	How two entities are connected	Diamond	Enrolls, Teaches, Has



Rectangle = entity, diamond = relationship, oval = attribute. Underline the primary-key attribute.

Cardinality (types of relationship)

Type	Meaning	Example
One-to-One (1:1)	One record $\leftrightarrow$ exactly one record. Rare; often for security.	One student has one ID card.
One-to-Many (1:M)	One record in A $\leftrightarrow$ many in B. The most common type.	One teacher teaches many students.
Many-to-Many (M:N)	Many in A $\leftrightarrow$ many in B.	Many students enrol in many classes.

COMMON MISTAKE

The M:N rule. A relational database cannot store M:N directly — it duplicates data. Break it into two 1:M relationships with a **junction table** (also called a bridge or associative table). Example: Enrollment(StudentID, ClassID, Date).

EXAM TIP

Always state cardinality on the diagram (1 and M at the ends of the line). For M:N, the long question is "how do you resolve it?" — draw the junction entity with two foreign keys.

اردو میں سمجھیں

ای آر ماڈل ڈیٹا بیس کا خاکہ ہے۔ مستطیل ہستی، بیضوی صفت، لوزی تعلق۔ تعلقات 1:1، M:1 یا M:N ہوتے ہیں۔ M:N کو دو M:1 میں توڑنے کے لیے جنکشن ٹیبل بنانا پڑتا ہے۔

CHECK YOURSELF

1. What symbol is used for a relationship?
2. A hospital: one patient, many appointments. Cardinality?

Answers: 1. Diamond. 2. 1:M (Patient 1 — has — M Appointment).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. An ER model is drawn:

- a. Before building tables
- b. After deleting the DB
- c. Only in Python
- d. Only in OSI

MCQ 2. An entity is:

- a. A real-world thing we store
- b. A Python keyword
- c. A cable
- d. A sprint

MCQ 3. A relationship 1:M means:

- a. One A, many B
- b. Many A, many B only
- c. One to one only
- d. No link

MCQ 4. M:N in an RDBMS needs:

- a. A bridge/associative table
- b. A pie chart
- c. A stack
- d. A NAND

MCQ 5. A diamond in ER often shows:

- a. A relationship
- b. An attribute oval only
- c. A PK square
- d. A report

MCQ 6. Cardinality is:

- a. 1:1, 1:M, M:N
- b. Big O
- c. TCP window
- d. Variance

Extra short questions

1. Define ER model.
2. Three relationship types with examples.
3. How do you convert 1:M to tables?
4. Why ER first?

Extra long question

1. Draw ER for Library: Member, Book, Borrow. Mark keys, cardinality, and how you resolve M:N. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Entity-Relationship: conceptual design of entities, attributes, relationships.

2. 1:1 person–NIC; 1:M mother–children / member–borrows; M:N students–courses.
3. PK of the 1 side copied as FK on the M side.
4. Cheaper to fix a diagram than a populated database.

Long

1. Member 1—M Borrow M—1 Book (Borrow as relationship-entity with date). If Book–Member M:N, Borrow is the bridge with composite/surrogate key.

4.5 Referential Integrity (Cascade Update & Delete) ★ Golden

LEARN IT

Referential integrity means every foreign-key value in a child table must match an existing primary-key value in the parent — or be NULL if the design allows it. It stops **orphan records**.

If Result.StudentID is a FK to Student.StudentID, you cannot type Result for student 999 if 999 is not in Student. You also cannot delete student 101 while results for 101 still exist — unless you first handle those child rows.

Parent — STUDENT

ID	Name
101	Ali
102	Sara

Child — RESULT

ID	Grade
101	A
999	F — rejected

Cascade operations

Cascade Update. Change the PK in the parent, and every matching FK in the child changes automatically. Ali's ID 101 → 201 updates Enrollments too. Nothing is left pointing at a vanished 101.

Cascade Delete. Delete the parent, and related child rows are deleted too. If Sara (102) leaves school, her Enrolment and Result rows disappear. That prevents "ghost" marks for a student who is gone.

WORKED EXAMPLE

Before Cascade Update

Student.ID	Enrol.StudentID
101	101

After changing 101 → 201 with Cascade Update ON

Student.ID	Enrol.StudentID
201	201

If Cascade Update were OFF, Access would refuse the change, or (in a sloppy file) leave Enrol stuck on 101 — an orphan.

COMMON MISTAKE

Cascade Delete is powerful and dangerous. Deleting one parent can wipe years of child history. In a real school, you more often **archive** a student (a Status field) than delete them.

EXAM TIP

Write: definition, why it matters (no orphans), then one numbered example of Cascade Update and one of Cascade Delete. Mention parent vs child.

اردو میں سمجھیں

ریفرنشل انٹیگریٹی کا مطلب ہے بچہ ٹیبل کی فارن کی ہمیشہ والدین کی موجود پرائمری کی طرف اشارہ کرے۔ کیسکیڈ اپ ڈیٹ والدین کی کی بدلنے پر بچوں کو خود بدل دیتی ہے؛ کیسکیڈ ڈیلیٹ والدین مٹانے پر متعلقہ بچے ریکارڈ بھی مٹا دیتی ہے۔

CHECK YOURSELF

1. What is an orphan record?
2. Cascade Delete: parent Teacher is removed. What happens to that teacher's Class rows?

Answers: 1. A child row whose FK value does not exist in the parent. 2. They are deleted automatically (if Cascade Delete is on).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Referential integrity means:

- a. Every FK matches an existing PK (or is NULL if allowed)
- b. Names are unique
- c. Files are encrypted
- d. Charts are labelled

MCQ 2. Cascade update:

- a. Changes child FKs when the parent PK changes
- b. Deletes the DBMS
- c. Sorts tables
- d. Draws ER

MCQ 3. Cascade delete:

- a. Deletes child rows when the parent is deleted
- b. Inserts a parent
- c. Creates a view
- d. Opens a form

MCQ 4. Inserting an FK that does not exist should:

- a. Be rejected
- b. Be auto-sorted
- c. Draw a pie
- d. Start Agile

MCQ 5. Orphan records are:

- a. Child rows whose parent is gone
- b. Primary keys
- c. Reports
- d. Queries

MCQ 6. Referential integrity is enforced by the:

- a. DBMS
- b. Monitor
- c. Mouse
- d. Compiler of Python only

Extra short questions

1. Define referential integrity.
2. What does cascade update solve?
3. When is cascade delete dangerous?
4. Give an invalid operation.

Extra long question

1. In Members–Borrow, specify restrict vs cascade for UPDATE and DELETE with a Sindh-college story. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. FK values must exist in the parent PK (unless NULL is allowed).
2. If roll number 12 becomes 112, all Marks.roll 12 become 112 automatically.
3. Deleting a member could wipe years of borrow history — sometimes restrict instead.
4. INSERT borrow for MemberID 999 when no such member.

Long

1. UPDATE MemberID: cascade so old cards still match. DELETE member who still has books: restrict (cannot delete). DELETE member with no books: allow. Show one rejected SQL/Access action.

4.6 Relational Schema Development

LEARN IT

A **relational schema** is the formal written design of the database: table names, fields, primary keys, foreign keys and how tables relate. You write it *before* clicking around in Access.

It defines (1) how data is split into tables, (2) which columns each table has, (3) which fields are PK/FK, (4) the relationships. Benefits: less redundancy, integrity planned in advance, easier to grow later.

WORKED EXAMPLE

Written schema for a tiny college:

```
Department (DeptID PK, DeptName)
Student     (RollNo PK, Name, Class, DeptID FK → Department)
Course      (CourseID PK, Title, Credit, DeptID FK → Department)
```

REMEMBER IT

Skipping the schema is like building a house without a drawing. You get messy, broken structures that are painful to repair.

اردو میں سمجھیں

ریلیشنل اسکیم ڈیٹا بیس کا لکھا ہوا نقشہ ہے: کون سے ٹیبل، کون سے فیلڈ، کون سی کیز، کون سے تعلقات۔ سافٹ ویئر کھولنے سے پہلے یہ بنانا چاہیے۔

CHECK YOURSELF

1. Name two things a schema must show.
2. Give one reason to write a schema before opening Access.

Answers: 1. Tables/fields and keys/relationships. 2. It reduces redundancy and mistakes (any valid benefit).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A relational schema is:

- a. The blueprint of tables, keys, types
- b. A running query result
- c. A pie chart
- d. A Python list

MCQ 2. Student(roll PK, name, class) is a:

- a. Schema notation
- b. Python call
- c. OSI frame
- d. MVP

MCQ 3. Schema is designed:

- a. Before stuffing thousands of rows
- b. After losing the backup
- c. Instead of ER
- d. By the compiler

MCQ 4. Data types in schema stop:

- a. Wrong values (text in marks)
- b. TCP errors
- c. NAND delay
- d. Figma overflow

MCQ 5. Foreign keys in schema implement:

- a. Relationships
- b. Sorts
- c. Charts
- d. Sprints

MCQ 6. Changing schema later is:

- a. Painful once data exists
- b. Free always
- c. Impossible in Access
- d. A gate

Extra short questions

1. Define relational schema.
2. Write schema for Book.
3. How does schema differ from ER?
4. Name two things schema documents besides columns.

Extra long question

1. Turn your library ER into a schema listing: three tables, keys, two constraints. Justify one data type.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Formal structure: relation names, attributes, types, keys.
2. Book(ISBN PK, title, author, copies: Number).
3. ER is conceptual diagram; schema is the relational implementation.
4. PKs, FKs, unique, not null, relationships.

Long

1. Member(MemberID PK, name Text, phone Text unique). Book(ISBN PK, title Text, copies Number). Borrow(BorrowID PK, MemberID FK, ISBN FK, date Date). Copies is Number because you count them.

4.7 Case Study — Library Management System

LEARN IT

A college library needs a database. Walk the seven steps examiners expect.

Step 1 — Requirements. A book has ID, title, author, publisher. A member (student/teacher) has ID, name, contact. A member can borrow many books; a book can be borrowed by different members over time. Record Issue Date and Return Date.

Step 2 — Entities. Book, Member. (Borrowing will need a third entity in step 6.)

Step 3 — Attributes. Book: BookID (PK), Title, Author, Publisher. Member: MemberID (PK), Name, ContactInfo.

Step 4 — Relationship. Member *borrow*s Book.

Step 5 — Cardinality. One member borrows many books over time; one book is borrowed by many members over time → **M:N**.

Step 6 — Resolve M:N. Add junction entity **BorrowRecord**: BorrowID (PK), MemberID (FK), BookID (FK), IssueDate, ReturnDate. Now Member 1—M BorrowRecord M—1 Book (two 1:M links).

Step 7 — Final schema.

```
Member      (MemberID PK, Name, ContactInfo)
Book        (BookID PK, Title, Author, Publisher)
BorrowRecord (BorrowID PK, MemberID FK, BookID FK, IssueDate, ReturnDate)
```



Final library ER: two 1:M relationships through the BorrowRecord junction table.

WORKED EXAMPLE

Sample rows after Sara borrows “Khushwant” on 5 Oct 2026:

BorrowID	MemberID	BookID	IssueDate	ReturnDate
5001	102	B-17	2026-10-05	

The same book can later be borrowed by Ali as BorrowID 5002 — no duplicated book title, no duplicated member address.

لائبریری میں ممبر اور کتاب کا تعلق بہت-سے-بہت-سے ہے، اس لیے بورو ریکارڈ نامی پل ٹیبل بناتے ہیں جس میں دونوں کی فارن کیز اور اجراء/واپسی کی تاریخ ہوتی ہے۔

CHECK YOURSELF

1. Why is BorrowRecord needed?
2. Where do IssueDate and ReturnDate belong, and why not on Book?

Answers: 1. To break M:N into two 1:M links. 2. On BorrowRecord — they belong to a *transaction*, not to the book itself (a book is issued many times).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The library case study starts from:

- a. Requirements
- b. Random tables
- c. Pie charts
- d. Sprints only

MCQ 2. Member to Borrow is typically:

- a. 1:M
- b. Always 1:1
- c. No relation
- d. M:1 the other way only if reversed

MCQ 3. Book to Borrow is typically:

- a. 1:M (one book title/copy can be borrowed many times)
- b. Always M:N without a bridge
- c. 1:1 mandatory
- d. A stack

MCQ 4. M:N Member–Book is resolved by:

- a. Borrow record table
- b. A pie
- c. A NAND
- d. OSI

MCQ 5. A good case-study answer shows:

- a. ER then schema then sample rows
- b. Only careers
- c. Only Python turtle
- d. Only Figma

MCQ 6. Fine calculation would be stored in:

- a. Borrow (or computed in a query)
- b. The OSI header
- c. A K-map
- d. A histogram bin

Extra short questions

1. List four requirements of a college library system.
2. Name the entities.
3. Why a Borrow entity?
4. One report the librarian wants.

Extra long question

1. Walk the seven case-study steps from the notes: requirements → entities → attributes → relationships → keys → resolve M:N → final ER. Draw the final diagram.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Register members; catalogue books; issue/return; calculate fines; search.
2. Member, Book, Borrow (and maybe Copy if multiple copies).
3. The issue event has its own date/fine — and it breaks M:N.
4. Overdue list: member, book, days late.

Long

1. Follow the textbook library walk-through. Final: Member 1–M Borrow M–1 Book. Keys labelled. One sentence on cascade.

4.8 Different Database Objects (Tables, Forms, Queries, Reports)

LEARN IT

Four objects you will meet in Access. Learn the one-line jobs cold:

Object	Job	You ...
Table	Stores the data (foundation; every other object depends on it)	keep the actual records here
Form	Friendly screen for enter / edit / view (text boxes, drop-downs)	type data in; fewer mistakes than a raw grid
Query	Ask a question: filter, sort, calculate	e.g. "students above 80%"
Report	Formatted output for printing or sharing	read only — never type into a report

REMEMBER IT

Store → Enter → Search → Print. Tables, Forms, Queries, Reports.

COMMON MISTAKE

A query does not copy the table into a second storage place. It is a saved question. Change the table, re-run the query, and the answer updates.

اردو میں سمجھیں

ٹیبل ڈیٹا رکھتی ہے، فارم سے اندراج ہوتا ہے، کوئری سوال پوچھ کر چھانتی ہے، رپورٹ چھپائی کے لیے سنواری ہوئی پیشکش ہے — اس میں ڈیٹا بھرا نہیں جاتا۔

CHECK YOURSELF

1. Which object would you use for a printed fee slip?
2. Which object actually holds the fee amount?

Answers: 1. Report. 2. Table.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. The four Access objects are:

- a. Tables, forms, queries, reports
- b. Lists, tuples, sets, dicts
- c. AND OR NOT XOR
- d. HTTP TCP IP ETH

MCQ 2. Tables store:

- a. The actual data
- b. Only print layout
- c. Only VBA
- d. Only charts

MCQ 3. Forms are for:

- a. Friendly data entry
- b. Physical cabling
- c. Big O proofs
- d. Sorting theories

MCQ 4. Queries:

- a. Ask questions / filter / calculate without changing stored rows (select)
- b. Always delete tables
- c. Draw OSI
- d. Compile C

MCQ 5. Reports are for:

- a. Printable summaries
- b. Capturing packets
- c. NAND grouping
- d. Figma prototypes

MCQ 6. You should enter daily data in a:

- a. Form (not raw datasheet if avoidable)
- b. Report
- c. Macro only
- d. Relationship window only

Extra short questions

1. Role of each object in one line.
2. Why not type into reports?
3. A select query does not:
4. Give one example object for a library.

Extra long question

1. Design the four objects for an attendance database. Say what each contains and how a teacher uses them in one period.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Table: store. Form: enter. Query: ask. Report: print/share.
2. Reports are output; they do not store new rows.
3. By itself permanently delete table data (unless you run a delete-query).
4. Query: books overdue; Report: overdue letters; Form: issue desk.

Long

1. Table Students+Attendance. Form mark present. Query absentees today. Report monthly letter. Flow: form → table → query → report.

4.9 Creation of Tables in Microsoft Access

LEARN IT

Plan first (4.9.1): purpose, field list, data type of each field, which field is the PK.

Datasheet View (4.9.2) — fast, spreadsheet-like, good for beginners, weak on rules.

1. Create tab → Table.
2. A blank grid appears.
3. Double-click Field1, Field2, ... to rename.
4. Type data; Access guesses the data type.

Limitation: you cannot easily say “Marks cannot exceed 100”. Professionals use Design View.

Design View (4.9.3) — full control before any data is typed.

1. Create tab → Table Design.
2. Type each Field Name (StudentID, Name, ...).
3. Pick the Data Type from the dropdown.
4. Right-click the unique field → Primary Key (key icon).
5. Save the table.

Data type	Use it for
Short Text	Names, addresses, phone numbers (you do not add phone numbers). Up to 255 characters.
Number	Values you calculate with: Age, Marks, Quantity.
Date/Time	Date of birth, admission date, appointment time.
Currency	Fees, salary.
AutoNumber	Access fills a unique sequential number — excellent PK.

COMMON MISTAKE

Phone numbers look numeric but are Short Text. Leading zeros (0333...) would vanish in a Number field, and you never sum two phone numbers.

اردو میں سمجھیں

پہلے ٹیبل کا منصوبہ بنائیں۔ ڈیٹا شیٹ ویو تیز لیکن کمزور ہے؛ ڈیزائن ویو میں فیلڈ، ڈیٹا ٹائپ اور پرائمری کی خود منتخب کرتے ہیں۔ فون نمبر شارٹ ٹیکسٹ رکھیں۔

CHECK YOURSELF

1. Best data type for StudentID if you want Access to generate it?
2. Best data type for FeeAmount?

Answers: 1. AutoNumber. 2. Currency.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Design View is best when you:

- a. Need full control of names, types, keys before data
- b. Want a random spreadsheet
- c. Draw Figma
- d. Ping a router

MCQ 2. Datasheet View is for:

- a. Typing rows after the structure exists
- b. Defining PK only
- c. Writing Python
- d. OSI captures

MCQ 3. A Number field should not store:

- a. Phone numbers that need leading zeros (use Text)
- b. Marks
- c. Counts
- d. IDs that are truly numeric

MCQ 4. Primary key is set in:

- a. Design View (key icon)
- b. A report footer
- c. A pie
- d. Agile sticky

MCQ 5. Yes/No fields store:

- a. Boolean-like presence
- b. Paragraphs
- c. Images only
- d. OSI layers

MCQ 6. Creating tables is step one because:

- a. Everything else hangs on the structure
- b. Reports can store data
- c. Queries invent columns from nothing always
- d. Forms replace keys

Extra short questions

1. Steps to create a table in Design View.
2. When Datasheet create is OK?
3. Why set field size/validation?
4. Name three data types you used in class.

Extra long question

1. Create (on paper) Design View for Students: four fields, PK, one validation rule, and say what error Access shows if the rule fails.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Create → Table Design; field name; data type; PK; save name.
2. Quick throwaway; still go back to Design to set PK/types.
3. Stop 999 marks out of 100; stop 40-character roll numbers.
4. Short Text, Number, Date/Time, Yes/No, Currency, AutoNumber.

Long

1. Roll AutoNumber/Number PK; Name Short Text required; Marks Number 0–100 validation; Passed Yes/No. Invalid marks: validation text "0 to 100".

4.10 Designing Forms for Data Manipulation

LEARN IT

A form is the screen people actually type into. It cuts errors and can show validation messages. Every form **must** have a data source — a table or a query. A form with no source has nowhere to save.

Form Wizard (the exam method):

1. Create tab → Form Wizard.
2. Select the table (e.g. Student).
3. Move fields with > (one) or >> (all).
4. Choose layout. **Columnar** = one record at a time, best for data entry.
5. Name it ("Student Registration") → Finish.

WORKED EXAMPLE

A Student Registration form shows Student ID (AutoNumber, locked), Full Name, Class, Department as labelled boxes, plus Save. The clerk never sees the raw datasheet and cannot accidentally overwrite the next row.

اردو میں سمجھیں

فارم اندراج کی سادہ اسکرین ہے۔ ہر فارم کسی ٹیبل یا کوئری سے جڑا ہوتا ہے۔ فارم وزرڈ سے ٹیبل چنائیں، فیلڈز منتخب کریں، کالم نما لے آؤٹ بہتر ہے، نام دے کر ختم کریں۔

CHECK YOURSELF

1. Can a form exist without a table or query?
2. Which layout is best for entering one student at a time?

Answers: 1. No — it needs a data source. 2. Columnar.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A form is:

- a. A screen for entering/editing records
- b. A printed summary only
- c. A TCP socket
- d. A sort

MCQ 2. Bound controls show:

- a. Fields from a table/query
- b. Random clipart only
- c. OSI headers
- d. NAND

MCQ 3. Validation on a form:

- a. Stops bad keystrokes before they hit the table
- b. Sorts binary search
- c. Encrypts OSI
- d. Draws histograms

MCQ 4. A combo box is for:

- a. Picking from a list (e.g. class names)
- b. Drawing ER
- c. Pinging
- d. Compiling

MCQ 5. Why forms vs datasheet?

- a. Fewer mistakes, one-record focus, hidden dangerous fields
- b. Forms store more rows than tables
- c. Datasheets cannot show data
- d. Forms replace primary keys

MCQ 6. Navigation buttons on a form:

- a. Move among records
- b. Create queries
- c. Set PK
- d. Start sprints

Extra short questions

1. Define form.
2. Two controls and their use.
3. How does a form enforce a rule visually?
4. Wizard vs Design View?

Extra long question

1. Design an Issue-Book form: record source, four controls, one validation, and how it prevents an orphan borrow.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Interface to enter, edit, view records, with validation.
2. Text box: name. Combo: class list. Button: save/new.
3. Required star, dropdown instead of free text, cannot tab off an empty PK.
4. Wizard fast; Design for layout and extra controls.

Long

1. Source Borrow+combo of MemberID and ISBN from parent tables (combo bound to FK). Date default today. Validation: due>issue. Combo prevents typing a non-existent member.

4.11 Creating Queries in MS Access ★ Golden

LEARN IT

A query retrieves, filters and analyses data **without changing the original tables**. A simple SELECT query:

1. Create tab → Query Design.
2. Show Table → add Student → Close.
3. Double-click the fields you want; they drop into the grid.
4. Red Run (!) button executes it.

Criteria restrict rows. Type a value in the Criteria row under a field.

Goal	Where to type	Example
Single criterion	Criteria row, one column	Department → "Computer Science"
AND (both must match)	Same Criteria row, two columns	Name "Ali" and Department "Computer Science"
OR (either may match)	Criteria row and the or: row	Department "IT" or "Computer Science"

Wildcards in Access: * = any characters, ? = one character. Like "A*" finds Ali, Ahmed, Ayesha.

WORKED EXAMPLE

Equivalent SQL (what Access writes behind the grid):

```
SELECT StudentName, Department
FROM Student
WHERE Department = "Computer Science";

SELECT StudentName, Department
FROM Student
WHERE StudentName = "Ali" AND Department = "Computer Science";

SELECT StudentName, Department
FROM Student
WHERE Department = "IT" OR Department = "Computer Science";
```

EXAM TIP

Remember: AND = same row in the grid; OR = different rows. Examiners draw a blank grid and ask you to fill Criteria and or:.

COMMON MISTAKE

Text criteria need quotes: "IT". Numbers do not: ≥ 80 . Mixing these is a common cause of empty results.

اردو میں سمجھیں

کوئری ٹیبل کو بدلے بغیر سوال پوچھتی ہے۔ ایک شرط Criteria قطار میں، AND ایک ہی قطار کی دو کالموں میں، OR الگ قطار (or): میں۔ وائلڈ کارڈ * کئی حروف، ؟ ایک حرف۔

CHECK YOURSELF

1. Criteria for marks at least 80?
2. You want CS or IT. Same row or two rows?

Answers: 1. ≥ 80 under Marks. 2. Two rows (OR).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A query is:

- a. A request to retrieve/filter/calculate data
- b. A printed letter
- c. A cable
- d. A gate

MCQ 2. Criteria in a query:

- a. Filter rows (e.g. Marks $\geq$ 40)
- b. Change field types
- c. Draw ER
- d. Set the OS

MCQ 3. A parameter query asks:

- a. The user for a value at run time
- b. The CPU voltage
- c. TCP window
- d. Figma frames

MCQ 4. Select queries by default:

- a. Do not delete stored rows
- b. Always wipe the table
- c. Always cascade
- d. Always print

MCQ 5. Sorting in a query:

- a. Orders the result (Asc/Desc)
- b. Changes PK
- c. Encrypts
- d. Creates a form

MCQ 6. This topic is ★ because board papers love:

- a. Writing criteria and showing results
- b. Cabling
- c. NAND only
- d. Sprints

Extra short questions

1. Define query.
2. Write criteria: CS students with marks < 40.
3. Difference between filter on a datasheet and a query.
4. What is a calculated field in a query?

Extra long question

1. Design a query: join Students and Marks, show Fail list (marks<40) sorted by name, with a calculated column 40-Marks as Needed. Write QBE grid/SQL-like criteria. ★ Golden.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. A saved question that selects, filters, sorts, calculates from tables.
2. Class = "CS" AND Marks < 40 (field names as in the table).
3. Query is reusable, can join tables, calculate, feed reports.
4. Total:[Math]+[Eng] — not stored, computed.

Long

1. Tables joined on roll. Fields Name, Subject, Marks, Needed: 40-[Marks]. Criteria Marks<40. Sort Name. Result sample two rows.

4.11.4 Data Summarization & Statistical Analysis

LEARN IT

Grouping combines rows that share a value (all CS students together) and then an **aggregate** calculates a number for the group. In Access click Totals (Σ) to reveal the Total row in the grid.

Function	What it calculates
COUNT()	How many records (students in IT)
SUM()	Total of a number field (fees collected)
AVG()	Mean
MAX() / MIN()	Highest / lowest in the group

WORKED EXAMPLE

Average marks per department: add Department and Marks; Totals Σ ; Department $\rightarrow$ Group By; Marks $\rightarrow$ Avg; Run.

Department	Avg of Marks
Computer Science	82.5
IT	76.0

Check: CS marks 80, 85 $\rightarrow$ average $(80+85)/2 = 82.5$. IT 70, 82 $\rightarrow 76.0$.

```
SELECT Department, AVG(Marks) AS AvgOfMarks
FROM Student
GROUP BY Department;
```

اردو میں سمجھیں

گروپ بائی ایک جیسے ریکارڈ جوڑتا ہے، پھر COUNT, SUM, AVG, MAX, MIN سے خلاصہ نکلتا ہے۔ ایکسیس میں Σ بٹن Total قطار کھولتا ہے۔

CHECK YOURSELF

1. Which Total setting goes under Department?
2. Which function counts how many books each member has borrowed?

Answers: 1. Group By. 2. COUNT (of BorrowID or BookID) grouped by MemberID.

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. Grouping in a query:

- a. Collapses rows that share a value (e.g. by class)
- b. Deletes the table
- c. Draws OSI
- d. Opens Figma

MCQ 2. Count(*) with group by class gives:

- a. How many students per class
- b. The PK
- c. A pie automatically
- d. A stack

MCQ 3. Avg(Marks) is:

- a. An aggregate
- b. A primary key
- c. A form control always
- d. A foreign key

MCQ 4. Sum is for:

- a. Totals (fees, marks)
- b. Sorting names alphabetically
- c. Encryption
- d. Routing

MCQ 5. Min/Max in a totals query:

- a. Smallest/largest in the group
- b. The table name
- c. The form wizard
- d. TCP ports

MCQ 6. You summarise when:

- a. n is large and you need a picture of each group
- b. You have one row
- c. You draw NAND
- d. You write sprints

Extra short questions

1. Name four aggregate functions.
2. What must you set in Access Totals query?
3. Example: average marks per subject.
4. Why not list 2000 rows to the principal?

Extra long question

1. From a Marks table, design two totals queries: (1) count of fails per class (2) average marks per subject. Show the Group By row.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Count, Sum, Avg, Min, Max.
2. Group By on the category; Count/Avg on the measure.
3. Group by Subject; Avg(Marks).
4. A 5-row summary is decidable; a dump is not.

Long




1. (1) Class Group By; Marks Count with criteria <40 or a Fail Yes/No Count. (2) Subject Group By; Marks Avg. Sample output.

4.11.6 Data Visualization in MS Access (Charts)

LEARN IT

Charts turn numbers into a picture so a pattern jumps out. Pick the chart that matches the question:

Chart	Shape	Best for
Bar (horizontal)	Bars sideways	Categories with long names (English, Mathematics, ...)
Column (vertical)	Bars standing	Side-by-side comparison (2024 / 2025 / 2026 admissions)
Pie	Slices of a circle	Parts of one whole (percent of CS vs IT vs Eng). Few slices.
Line	Dots joined	A trend over time (visitors per month)



Column = compare categories. Pie = share of a total. Line = change over time.

EXAM TIP

"Which chart?" — line for time, pie for composition, bar/column for comparing categories. Mention one reason.

اردو میں سمجھیں

بار لمبے ناموں والی اقسام، کالم سادہ موازنہ، پائی حصوں کا تناسب، لائن وقت کے ساتھ رجحان۔ چارٹ کوئری یا ٹیبل کے اعداد کو تصویر بناتا ہے۔

CHECK YOURSELF

1. Website visitors each month — which chart?
2. Share of boys vs girls in one class — which chart?

Answers: 1. Line. 2. Pie (two parts of a whole).

Extra board practice

These MCQs and questions are extra to the textbook. Close the notes, attempt them, then open the key.

MCQ 1. A column chart in Access is for:

- a. Comparing categories
- b. Parts of a whole only
- c. Time only
- d. OSI only

MCQ 2. A pie chart shows:

- a. Share of a total
- b. A trend of 60 months well
- c. Binary search
- d. Foreign keys

MCQ 3. A line chart shows:

- a. Change over time
- b. Unrelated categories best
- c. ER diamonds
- d. NAND

MCQ 4. Charts should be based on:

- a. A summarised query, not 10,000 raw rows if possible
- b. The relationship window
- c. Python turtle
- d. Figma

MCQ 5. Unlabelled axes in an exam chart score:

- a. Near zero
- b. Full marks
- c. Bonus NAND
- d. An extra sprint

MCQ 6. Choose the chart that matches the question, same rule as:

- a. Matplotlib in XII
- b. Bubble sort
- c. TCP handshake
- d. K-maps

Extra short questions

1. When pie vs column?
2. When line?
3. Why chart a totals query not the raw table?
4. Three labels every chart needs.

Extra long question

1. For library data pick a chart: (a) books per genre (b) issues per month (c) share of lost vs on-shelf vs borrowed. Justify and sketch.

Extra answer key

MCQs: 1. A 2. A 3. A 4. A 5. A 6. A

Short

1. Pie: composition of one whole (few slices). Column: compare separate categories.
2. Enrolment 2019–2026 — time.
3. The chart needs one number per category, not every student.
4. Title, axis titles / legend, units.

Long

1. (a) column (b) line (c) pie. Each sketch labelled. One sentence why the others are worse.

Data and Analysis

15 single-page lessons · 4 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- Data = raw facts; information = processed data used for decisions; a database stores related data in a structured, updatable way.
- A DBMS is the software layer that provides less redundancy, consistency, security and integrity.
- Table = rows (records) and columns (fields). One table, one entity.
- Candidate keys could identify a row; the primary key is the one you choose (unique, not NULL); leftover candidates are alternate keys; a foreign key points at another table's PK.
- An RDBMS keeps several related tables and is queried with SQL.
- ER symbols: rectangle entity, oval attribute, diamond relationship. Cardinality 1:1, 1:M, M:N. M:N needs a junction table.
- Referential integrity forbids orphan FKs. Cascade Update copies a changed PK into children; Cascade Delete removes children with the parent.
- Write a relational schema before building. Library case: Member and Book are M:N, resolved by BorrowRecord.
- Objects: tables store, forms enter, queries search, reports print.
- Access Design View sets field names, data types and the PK. Phone numbers are Short Text; money is Currency; auto IDs are AutoNumber.
- Forms need a table/query source; Wizard + columnar layout for data entry.
- Query criteria: one value; AND on the same row; OR on two rows. Totals Σ for Group By / Count / Sum / Avg / Max / Min.
- Bar/column compare categories, pie shows parts of a whole, line shows a trend over time.

Key terms

Term	Meaning	اردو
Data	Raw facts and figures.	ڈیٹا / خام حقائق
Information	Processed data that supports a decision.	معلومات
Database	Organised collection of related data.	ڈیٹا بیس
DBMS	Software that creates and manages databases.	ڈیٹا بیس مینجمنٹ سسٹم
Table	Rows and columns about one entity.	ٹیبل
Record	One row — one instance.	ریکارڈ
Field	One column — one attribute.	فیلڈ
Primary key	Chosen unique, non-empty identifier.	پرائمری کی

Foreign key	Field that refers to another table's PK.	فارن کی
Candidate key	Any field(s) that could be the PK.	کینڈیڈیٹ کی
Alternate key	A candidate not chosen as PK.	آلٹرنیٹ کی
RDBMS	DBMS that stores related tables linked by keys.	ریلیشنل ڈی بی ایم ایس

CHAPTER 4 EXAM · CLOSED BOOK

Data and Analysis

75 marks · 1 hour 15 minutes · no notes · no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 15 and the recap. **Section A** — all 15 MCQs (1 mark). **Section B** — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. 15 + 30 + 30 = 75. A 5-mark / 10-mark answer needs Define · Explain · Example · Diagram · Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

- Processed data used for a decision is called:
 - a field
 - information
 - a query
 - redundancy
- A complete row about one student is a:
 - field
 - report
 - record
 - schema
- A primary key cannot contain:
 - numbers
 - text
 - NULL
 - an AutoNumber
- EmpLicense# after EmpID is chosen as PK is an:
 - foreign key
 - alternate key
 - orphan
 - report

5. A foreign key:
 - a. must be unique in the child table
 - b. may contain duplicates
 - c. cannot exist in an RDBMS
 - d. is always AutoNumber
6. The ER symbol for a relationship is a:
 - a. rectangle
 - b. oval
 - c. diamond
 - d. circle
7. The most common cardinality is:
 - a. 1:1
 - b. 1:M
 - c. M:N stored as-is
 - d. 0:0
8. M:N is stored in an RDBMS by:
 - a. duplicating both tables
 - b. a junction table
 - c. deleting one entity
 - d. using a pie chart
9. A child row whose StudentID is not in Student is:
 - a. a candidate key
 - b. an orphan record
 - c. a form
 - d. a primary key
10. Changing parent ID 101 → 201 and seeing the child follow is:
 - a. Cascade Delete
 - b. Cascade Update
 - c. a SELECT query
 - d. a pie chart
11. Which Access object is for printing a report card?
 - a. Table
 - b. Form
 - c. Query
 - d. Report
12. Phone numbers should be stored as:
 - a. Number
 - b. Currency
 - c. Short Text
 - d. Date/Time
13. AND criteria go:
 - a. on two different rows of the grid
 - b. on the same Criteria row
 - c. in a report header
 - d. only in SQL Server
14. To average marks per department you set Department to:
 - a. Sum
 - b. Where
 - c. Group By
 - d. Expression
15. The best chart for admissions in 2024, 2025, 2026 is a:
 - a. pie chart
 - b. column chart
 - c. junction table
 - d. foreign key

Section B — Short questions (10 × 3 = 30)

1. Differentiate data and information with one example each.
2. List four advantages of a DBMS.
3. Define record and field with reference to a Student table.
4. Differentiate primary key and foreign key (four points).
5. Why can a relational database not store M:N directly?
6. What is referential integrity? Give one rejected-insert example.
7. Differentiate Cascade Update and Cascade Delete.
8. State the four Access objects and the job of each in one line.
9. Why are phone numbers Short Text, not Number?
10. How do you express OR in Query Design?

Section C — Long questions (attempt any 3 × 10 = 30)

1. Draw a complete ER diagram for Student–Course enrolment (M:N). Resolve it with a junction entity. Write the relational schema with keys marked.
2. A Result table uses StudentID as a foreign key. Explain referential integrity, then show before/after tables for (a) Cascade Update of ID 101 → 201 and (b) Cascade Delete of student 102.
3. Work through the library case study: requirements, entities, attributes, relationship, cardinality, junction table, final schema. Include two sample BorrowRecord rows.
4. Write step-by-step how to create a Student table in Access Design View (fields RollNo Number PK, Name Short Text, Marks Number, Fee Currency, AdmDate Date/Time) and then a columnar form with the Wizard.
5. Write the Query Design settings and the SQL to list CS students with Marks ≥ 80, sorted by Name. Then write a totals query that shows COUNT of students and AVG(Marks) for each Department.
6. A principal wants to see (i) fee collected per class, (ii) the share of each class in total enrolment, (iii) enrolment over five years. Which chart for each, and why?

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

- 4.1.1 Data, Information and Database.** Answers: 1. Data (raw facts about one student). 2. It is not organised in a structured, searchable, updatable collection of related records.
- 4.1.2 Database Management System (DBMS).** Answers: 1. MS Access, MySQL (Oracle, SQLite also). 2. Integrity (unique / primary-key constraint).
- 4.2 Database Components (Tables, Records, Fields).** Answers: 1. 3 records, 4 fields. 2. A value stored in the Course field.
- 4.3.1 Keys and Integrity Constraints.** Answers: 1. No — only one PK (it may be composite). 2. Yes — many child rows may point to the same parent.
- 4.3 Relational Database Management System (RDBMS).** Answers: 1. SQL. 2. To store the department name once (less redundancy) and update it in one place.
- 4.4 Entity Relationship Model (ER-Model).** Answers: 1. Diamond. 2. 1:M (Patient 1 — has — M Appointment).
- 4.5 Referential Integrity (Cascade Update & Delete).** Answers: 1. A child row whose FK value does not exist in the parent. 2. They are deleted automatically (if Cascade Delete is on).
- 4.6 Relational Schema Development.** Answers: 1. Tables/fields and keys/relationships. 2. It reduces redundancy and mistakes (any valid benefit).
- 4.7 Case Study — Library Management System.** Answers: 1. To break M:N into two 1:M links. 2. On BorrowRecord — they belong to a *transaction*, not to the book itself (a book is issued many times).
- 4.8 Different Database Objects (Tables, Forms, Queries, Reports).** Answers: 1. Report. 2. Table.
- 4.9 Creation of Tables in Microsoft Access.** Answers: 1. AutoNumber. 2. Currency.
- 4.10 Designing Forms for Data Manipulation.** Answers: 1. No — it needs a data source. 2. Columnar.
- 4.11 Creating Queries in MS Access.** Answers: 1. ≥ 80 under Marks. 2. Two rows (OR).
- 4.11.4 Data Summarization & Statistical Analysis.** Answers: 1. Group By. 2. COUNT (of BorrowID or BookID) grouped by MemberID.
- 4.11.6 Data Visualization in MS Access (Charts).** Answers: 1. Line. 2. Pie (two parts of a whole).

Answer key

Multiple choice

- | | | | | |
|------|------|------|-------|-------|
| 1. b | 4. b | 7. b | 10. b | 13. b |
| 2. c | 5. b | 8. b | 11. d | 14. c |
| 3. c | 6. c | 9. b | 12. c | 15. b |

Short questions — model answers

- Data = raw facts (80, 75, 90). Information = processed meaning ("average is 81.7%, the class is ready").
- Less redundancy, consistency, security (authorised access), integrity (valid, unique keys). (Sharing / backup also accepted.)

3. Record = one student's full row (101, Ali, CS, A). Field = one column such as Name.
4. PK uniquely identifies a row, cannot be NULL, one per table, lives in the parent. FK refers to a PK, may duplicate, may be NULL, lives in the child, creates the relationship.
5. It would duplicate attributes of both entities. Split into two 1:M links with a junction table that holds both FKs plus extra attributes (dates).
6. Every FK must match an existing parent PK. Inserting Result.StudentID = 999 is rejected if 999 is not in Student — that would have been an orphan.
7. Cascade Update copies a changed parent PK into child FKs. Cascade Delete removes child rows when the parent is deleted.
8. Table stores; form enters; query searches/filters; report prints.
9. They are identifiers, not quantities; leading zeros would vanish; you never add two numbers of a phone.
10. Put one value on the Criteria row and the other on the or: row of the same field (or of different fields if that is the question).

Long questions — model answers

1. Entities STUDENT and COURSE, relationship Enrolls (M:N). Junction ENROLLMENT(EnrollID PK, StudentID FK, CourseID FK, Date). Schema: Student(StudentID PK, Name, Class); Course(CourseID PK, Title); Enrollment as above. Diagram: 1 — M — M — 1 through the junction.
2. (a) Parent 101 Ali → 201 Ali; child Result rows that said 101 now say 201. (b) Delete parent 102 Sara; all Result and Enrolment rows with 102 disappear. Integrity definition: FK must match a live PK; this stops orphans and keeps reports true.
3. Follow steps 1–7 in the chapter. Sample: (5001, 102, B-17, 2026-10-05, NULL); (5002, 101, B-17, 2026-10-12, 2026-10-20) — same book, two members, no duplicated titles.
4. Create → Table Design; enter the five fields and types; right-click RollNo → Primary Key; Save as Student. Create → Form Wizard → Student → >> all fields → Columnar → name Student Registration → Finish.
5. Grid: Name, Department, Marks. Criteria under Department: "CS" (or "Computer Science"); Criteria under Marks: ≥ 80 (same row = AND); Sort under Name: Ascending. SQL: `SELECT Name, Department, Marks FROM Student WHERE Department="CS" AND Marks  $\geq$  80 ORDER BY Name`; Totals query: Department Group By, StudentID Count, Marks Avg.
6. (i) Column or bar — compare categories (classes). (ii) Pie — each class is a part of one whole enrolment. (iii) Line — a trend over years.

Self-assessment: I can...

- | | |
|---|---|
| ☐ explain data vs information vs database vs DBMS. | ☐ point at records and fields in a table. |
| ☐ choose PK / FK / candidate / alternate keys correctly. | ☐ draw ER symbols and label 1:1, 1:M, M:N. |

- ☐ resolve M:N with a junction table.
- ☐ write a relational schema including the library case study.
- ☐ create a table in Design View and pick data types.
- ☐ choose bar, column, pie or line for a given question.
- ☐ explain referential integrity and both cascade operations with examples.
- ☐ match tables, forms, queries and reports to a task.
- ☐ build a Wizard form and a criteria query (AND, OR, totals).