

Computer Science XII

Self-Taught / Coaching-Academy Bootcamp — one official book for students and teachers. Chapter-wise lecture notes at readable size. ★ Golden concepts sit inside each chapter, then that chapter's exam.

102 lecture notes · 32 Golden concepts · 68 academy classes · six papers + mock

Bilingual support: English + اردو

مشتکہ اسٹڈی گائیڈ — خود سیکھیں یا اکیڈمی بوٹ کیمپ، گولڈن اسی باب میں

01 Computer Systems (HCI)

02 Computational Thinking & Algorithms

03 Programming Fundamentals

04 Data and Analysis

05 Application and Impacts of Computing

06 Entrepreneurship in the Digital Age

XII

Imprint

Title	Computer Science XII — Self-Taught / Coaching-Academy Bootcamp (Combo Edition)
Audience	Students (self-taught) and teachers / academy coaches
Curriculum	New Sindh Curriculum 2025-27
Language	English with Urdu support
Structure	102 lecture notes · 32 Golden concepts · 68 academy classes · six chapter papers + mock
Study time	About 36 h 50 min self-taught, or the academy calendar (90-minute classes)
Format	A4 print / screen · MathJax SVG mathematics · inline SVG diagrams
Series	01 Computer Systems (HCI) · 02 Computational Thinking & Algorithms · 03 Programming Fundamentals · 04 Data and Analysis · 05 Application and Impacts of Computing · 06 Entrepreneurship in the Digital Age

What you hold

The published combo Study Guide for the grade. The same pages serve a student working alone and a coach running a bootcamp. ★ Golden concepts are taught first inside each chapter. Check yourself answers stay sealed after the chapter exam.

یہ جماعت کی آفیشل مشترکہ اسٹڈی گائیڈ ہے۔ طالب علم اور استاد ایک ہی صفحات استعمال کرتے ہیں۔

How to use this Study Guide

This is the official **Self-Taught / Coaching-Academy Bootcamp** combo for the whole grade. Students study alone. Teachers and academy coaches run the same pages as a bootcamp. ★ Golden concepts sit *inside* the chapter that teaches them. Each lesson starts on its own page and continues at the same type size. Blank pages are not used.

یہ طلبہ اور اساتذہ کی مشترکہ اسٹڈی گائیڈ ہے۔ خود سیکھیں یا اکیڈمی بوٹ کیمپ چلائیں۔ گولڈن تصورات اسی باب میں ہیں۔ خالی صفحے نہیں۔

Two tracks — one book

SELF-PACED

Track A — Self-taught student. Read Learn it slowly. Cover the worked example and redo it on paper. Write Check yourself in your notebook. Do not open the chapter key. Sit the 75-mark chapter exam closed-book, then mark.

ACADEMY SESSION

Track B — Coach / teacher. Academy: 90-minute batch (★ Golden = full class; other notes pair). School: 40-minute period (★ = one period). Use the Student · Coach strip on each lesson for board work and oral questions. Same exam, same sealed key.

Inside every chapter

1. **Chapter opener.** Outcomes, ★ Golden concepts of this chapter, then the dual-track card (self-taught hours + academy classes).
2. ★ **Golden lecture notes first.** High-yield ideas, full detail. Do these if time is short.
3. **The other lecture notes.** Remaining topics in syllabus order.
4. **Exam preparation.** Recap, then a 75-mark closed-book paper. The key is sealed for the student; the coach marks to the same scheme.

What the coloured boxes mean

LEARN IT

The main explanation. Read it slowly.

WORKED EXAMPLE

A solved example. Cover it and try first.

REMEMBER IT

A memory trick or analogy.

COMMON MISTAKE

A mistake students often make.

اردو میں سمجھیں

اسی موضوع کی اردو میں آسان وضاحت۔

EXAM TIP

How Golden topics are asked in board exams.

CHECK YOURSELF

Quick questions. Write answers in your notebook. The key follows the chapter exam.

STUDENT • COACH

Student minutes and coach session on the same strip.

GOLDEN TOPIC

★ **Golden** a high-yield concept taught first in that chapter.

How to sit a chapter exam

75 marks • 1 hour 15 minutes • no notes. Section A all 15 MCQ (1 mark). Section B all 10 short (3 marks). Section C any three long (10 marks); at least one must be ★ Golden. A 5-mark or 10-mark answer needs **Define • Explain • Example • Diagram • Working**.

Bootcamp planner

Self-taught: 102 notes · 32 ★ · about **36 h 50 min** plus the mock week. **Academy:** 68 classes of 90 minutes, then chapter papers. **School teacher:** ★ Golden = one 40-minute period; other notes = half to three-quarters of a period.

Ch	Title	Notes	★	Self-taught	Academy	Exam
Ch 1	Computer Systems (HCI)	16	5	5 h 50 min	11 × 90 min	75 marks · 1 h 15 min
Ch 2	Computational Thinking & Algorithms	24	6	8 h	15 × 90 min	75 marks · 1 h 15 min
Ch 3	Programming Fundamentals	18	6	6 h 30 min	12 × 90 min	75 marks · 1 h 15 min
Ch 4	Data and Analysis	9	5	4 h 5 min	7 × 90 min	75 marks · 1 h 15 min
Ch 5	Application and Impacts of Computing	17	5	6 h 5 min	11 × 90 min	75 marks · 1 h 15 min
Ch 6	Entrepreneurship in the Digital Age	18	5	6 h 20 min	12 × 90 min	75 marks · 1 h 15 min
Final	Recaps + mock paper	—	—	6 h	Exam week	75 marks · 2 h 30 min

ایک ٹریک رکھیں۔ طالب علم نوٹس اور امتحان؛ اکیڈمی 90 منٹ کلاس؛ استاد 40 منٹ پیراڈ۔

Contents

Chapter-wise lecture notes. ★ Golden concepts sit under the chapter that teaches them. Self-taught and academy tracks share these same pages.

Chapter 1: Computer Systems (HCI) — 16 lecture notes (5 ★)

★ Golden concepts

- ★ 1.2 Applications of HCI (Domains of Life)
- ★ 1.7 Human-Computer Interaction Problems
- ★ 1.11.2 Testing Methods (Usability, A/B, Automated)
- ★ 1.4 Importance of HCI
- ★ 1.9 User Interface Design (UI vs UX)

Lecture notes

- 1.1 Fundamentals of Human-Computer Interaction
- 1.3 Components of HCI
- Interface Types, Environment and Feedback
- 1.6 Need Analysis for Interface Design
- 1.9.3–1.9.5 Wireframing, Figma and Prototypes
- Career Opportunities in UI/UX
- 1.1.1 Traditional Interaction and 1.1.2 Natural Interaction
- Types of User Interaction
- 1.5 Accessibility Principles
- 1.8 Methods for Improving HCI
- 1.11 Test and Evaluate HCI (Evaluation Methods)

- Exam preparation — recap + 75-mark paper + key

Chapter 2: Computational Thinking & Algorithms — 24 lecture notes (6 ★)

★ Golden concepts

- ★ 2.1.1 Trace Tables
- ★ 2.3.1 Number of Steps (Big O Notation)
- ★ Linear Data Structures: Stack
- ★ 2.1.3 Comparing Trace Tables and Stepwise Reasoning
- ★ 2.5 Concept of Data Structure
- ★ Linear Data Structures: Queue

Lecture notes

- 2.1 Analyze algorithms for correctness
- 2.2 Evaluating the Clarity of an Algorithm
- 2.2.2 Readability
- 2.3.2 Number of Conditions
- 2.3.4 The Efficiency Evaluation Framework
- 2.5.1 Linear Data Structures: Array
- 2.5.2 Non-Linear Data Structures: Tree
- 2.5.3 Operations on Data Structures
- 2.7 Trace data retrieval in Array, List and Queue
- 2.1.2 Stepwise Reasoning
- 2.2.1 Modularity
- 2.3 Assess Algorithm Efficiency
- 2.3.3 Number of Repetitions
- 2.4 Refinements to improve clarity and efficiency
- Linear Data Structures: Linked List
- Non-Linear Data Structures: Graph
- 2.6 Identify data structures in problem scenarios
- Career Opportunities in Algorithms

- Exam preparation — recap + 75-mark paper + key

Chapter 3: Programming Fundamentals — 18 lecture notes (6 ★)

★ Golden concepts

- ★ 3.1.1 Lists (Ordered, Mutable, Methods)
- ★ 3.1.2 Tuples (Ordered, Immutable)
- ★ 3.1.4 Dictionaries (Key-Value Pairs)
- ★ 3.2 Functions in Python
- ★ 3.3 & 3.4 File Handling and Operations (Modes r, w, a)
- ★ 3.6 The with Statement (Context Manager)

Lecture notes

- 3.1 Data Structures in Python
- 3.1.3 Sets (Unordered, Unique, Math Operations)
- 3.1.5 Common Built-in Functions (min, max, len, sum)
- 3.1.6 Activity: Student Attendance System
- 3.1.7 Activity: Word Frequency Counter
- 3.2.1 Types of Functions (Built-in vs User-defined)
- 3.2.2 Functions with Return Values
- 3.2.3 Activity: Arithmetic Calculator Using Functions
- 3.2.4 Scope of Local and Global Variables
- 3.8 Errors and Exceptions (Try-Except)
- 3.9 Mini File Handling Project: Grade Tracker
- Career Opportunities

- Exam preparation — recap + 75-mark paper + key

Chapter 4: Data and Analysis — 9 lecture notes (5 ★)

★ Golden concepts

- ★ 4.1.1 – 4.1.2 Data Sources and Database Connection
- ★ 4.3 Pandas and DataFrames
- ★ 4.3.3 Handling Missing Values (NaN)
- ★ 4.5 Data Visualization and Types of Graphs
- ★ 4.6 Descriptive Statistics

Lecture notes

- 4.1 Concept of Data Analysis
- 4.2 Creating a SQLite Database in Python
- 4.4 Data Organization and Representation
- Career Opportunities

- Exam preparation — recap + 75-mark paper + key

Chapter 5: Application and Impacts of Computing — 17 lecture notes (5 ★)

★ Golden concepts

- ★ 5.1.2 Neural Networks (NN)
- ★ 5.1.4 Components of Neural Networks
- ★ 5.3.1 Secure Collaboration (Authentication, MFA, Access Control)
- ★ 5.4.1 Common Security Threats (Malware, Phishing, DoS)
- ★ 5.5.1 Functions of Equity and Equal Access

Lecture notes

- 5.1 Machine Learning, Neural Networks and Deep Learning
- 5.1.1 Machine Learning (ML)
- 5.1.3 Deep Learning (DL)
- 5.1.5 Components of Deep Learning
- Future of AI, NN and DL in Pakistan
- 5.2 Applications of Neural Networks and Deep Learning
- 5.3.2 Data Protection (Encryption, Passwords, Backup, Firewall)
- 5.4.2 Identifying Security Threats
- 5.4.3 Apply Mitigation Techniques
- 5.5 Equity and Equal Access in Digital Collaboration
- 5.5.2 Collaboration Tools
- Career Opportunities

- Exam preparation — recap + 75-mark paper + key

Chapter 6: Entrepreneurship in the Digital Age — 18 lecture notes (5 ★)

◦ ★ Golden concepts

- ★ 6.2 Entrepreneurship in the Digital Age
- ★ 6.4 Prototype
- ★ 6.6 Prototype Development Cycle
- ★ 6.8 Minimum Viable Product (MVP)
- ★ 6.14 Beachhead Market

◦ Lecture notes

- 6.1 Entrepreneur and Entrepreneurship
- 6.3 From Problem to Business Idea
- 6.7 Class Activity: Create a Prototype
- 6.10 Identifying the Riskiest Assumption
- 6.12 Case Study: MVP for a Canteen Pre-Order System
- 6.15 Complete Student Project
- Career Opportunities
- Local Examples of Digital Entrepreneurship (Table 6.1)
- 6.5 Types of Prototypes
- 6.9 Difference between Prototype and MVP
- 6.11 Developing an MVP
- 6.13 Testing an MVP
- 6.16 Ethical and Safe Use of Digital Tools

- Exam preparation — recap + 75-mark paper + key

Final revision: recaps and mock paper (75 marks, 2 h 30 min)

Colophon

Computer Systems (HCI)

This chapter teaches you Human-Computer Interaction (HCI): how people and computers talk to each other, how to design screens that are easy and fair to use, and how to test those designs before they go live. You will apply every idea to things you already use in Pakistan — a bank ATM, JazzCash, and a school portal.

اس باب میں آپ ہیومن کمپیوٹر انٹرایکشن (HCI) سیکھیں گے: انسان اور کمپیوٹر آپس میں کیسے بات کرتے ہیں، اسکرینیں کیسے آسان اور منصفانہ بنائی جاتی ہیں، اور انہیں عوام تک پہنچانے سے پہلے کیسے جانچا جاتا ہے۔

What you will learn

- Define HCI (also called CHI and MMI) and name the five sensory channels of interaction.
- Describe HCI applications in health care, banking, education, and networking.
- Explain environment and the two kinds of feedback.
- Carry out a need analysis before designing an interface.
- Differentiate UI from UX, and compare wireframes, Figma work and prototypes.
- Differentiate traditional interaction from natural interaction with local examples.
- Name the components of HCI and classify types of user interaction and interface.
- State why HCI is important and apply five accessibility principles.
- Identify common HCI problems and methods for improving HCI.
- Choose evaluation and testing methods (SUS, NPS, usability, A/B, automated audits).

GOLDEN CONCEPTS

★ **Golden concepts in this chapter.** These ideas are taught first as lecture notes. If time is short, lock these before the other notes, then sit the chapter exam.

- ★ **1.2 Applications of HCI (Domains of Life).** HCI is used to design and develop interactive systems such as desktop applications, websites and mobile apps.
- ★ **1.4 Importance of HCI.** HCI ensures that machines are approachable and usable, turning complex technology into everyday tools.
- ★ **1.7 Human-Computer Interaction Problems.** HCI problems are common difficulties that stop users from using technology smoothly.
- ★ **1.9 User Interface Design (UI vs UX).** UI design is the process of creating and organizing the visual elements of a software application so users can interact with it easily and efficiently.
- ★ **1.11.2 Testing Methods (Usability, A/B, Automated).** Testing involves observing how the system behaves under specific conditions.

اس باب کے گولڈن تصورات پہلے پڑھیں۔ باقی نوٹس بعد میں۔

STUDENT • COACH

Self-taught. 16 notes • 5 ★ first • about 5 h 50 min.
After the last note, sit the chapter exam (75 marks, 1 h 15 min).

Coach / teacher. 11 academy classes of 90 minutes (each ★ Golden is a full class; other notes pair). School:
★ = one 40-minute period.

ACADEMY CALENDAR**Chapter 1 academy calendar.**

Class	Topics	Kind
Class 01	Applications of HCI (Domains of Life)	★ 90 min
Class 02	Importance of HCI	★ 90 min
Class 03	Human-Computer Interaction Problems	★ 90 min
Class 04	User Interface Design (UI vs UX)	★ 90 min
Class 05	Testing Methods (Usability, A/B, Automated)	★ 90 min
Class 06	Fundamentals of Human-Computer Interaction + Traditional Interaction and 1.1.2 Natural Interaction	90 min
Class 07	Components of HCI + Types of User Interaction	90 min
Class 08	Interface Types, Environment and Feedback + Accessibility Principles	90 min
Class 09	Need Analysis for Interface Design + Methods for Improving HCI	90 min
Class 10	Wireframing, Figma and Prototypes + Test and Evaluate HCI (Evaluation Methods)	90 min
Class 11	Career Opportunities in UI/UX	90 min

1.2 Applications of HCI (Domains of Life) ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 01 of 11 · 90 min · full Golden class. Board: HCI is used to design and develop interactive systems such as desktop applications, websites and mobile apps..


Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

HCI is used to design and develop interactive systems such as **desktop applications, websites and mobile apps**. These are **human-centred solutions** built to meet user needs across many domains of life. A domain is an area of daily activity — health, money, school, talking to people.

When you design for a domain, you design for that domain's **users, tasks and risks**. A mistake on a games app is annoying. A mistake on a medical or banking screen can harm a person or lose money. That is why examiners treat this topic as golden.

Domain	Application examples	User benefit
Health care	Patient portals, telemedicine apps, assistive technologies	Improves access to medical services remotely
Banking	Mobile banking apps, secure ATM interfaces	Enables quick transactions and secure financial management
Education	E-learning platforms (LMS), online exam portals	Enhances teaching, learning and student engagement
Networking and communication	Social media, messaging apps (WhatsApp), Zoom	Connects people globally through collaboration tools



HCI sits at the centre of four everyday domains: healthcare, banking, education and networking.

WORKED EXAMPLE

Worked example: the same HCI idea in three Pakistani systems.

Step 1 — ATM (banking). You insert a card, the screen shows large buttons (Fast Cash, Balance, Other), you enter a PIN on the keypad, and you take cash. HCI benefit: a quick, secure transaction without a human teller.

Step 2 — JazzCash (banking + communication). You log in with a PIN or fingerprint, choose Send Money, type a number and amount, confirm, and see "Successful" with a JazzCash SMS. HCI benefit: money moves in seconds from a shop in Larkana to a student in Karachi.

Step 3 — School portal (education). A Grade XII student opens the college LMS, taps "Download date sheet", and submits a leave form. HCI benefit: learning and admin tasks happen without standing in a queue at the office.

Step 4 — Compare the user benefit. Banking HCI saves time and keeps money safe. Education HCI raises engagement. Health HCI (a Sehat/telemedicine app) brings a doctor to a village phone. Networking HCI (WhatsApp, Zoom) keeps a family in Dubai in touch with parents in Sukkur.

REMEMBER IT

Exam mnemonic H-BEN: Health, Banking, Education, Networking. For each, write: one application + one user benefit. That structure scores full marks on "applications of HCI".

COMMON MISTAKE

Mistake: Listing brand names only ("WhatsApp, JazzCash, Zoom") without saying the *domain* and the *user benefit*.

Fix: Always write three parts: domain → example → what the user gains. "Banking: JazzCash mobile app — enables quick, secure transfers."

اردو میں سمجھیں

ایچ سی آئی کی ایپلیکیشنز صحت، بینکنگ، تعلیم اور نیٹ ورکنگ کے شعبوں میں انسانی ضروریات پوری کرتی ہیں۔ صحت میں مریض پورٹل اور ٹیلی میڈیسن دور سے علاج دیتے ہیں، بینکنگ میں موبائل ایپ اور اے ٹی ایم تیز اور محفوظ لین دین دیتے ہیں، تعلیم میں ای لرننگ اور آن لائن امتحان مشغولیت بڑھاتے ہیں، اور وائس ایپ یا زوم لوگوں کو جوڑتے ہیں۔

EXAM TIP

Very common 5–8 mark question: "Explain applications of HCI in different domains of life with examples." Draw a four-row table (Health care, Banking, Education, Networking & communication). Each row: one or two application names + the user benefit from the source. Add a local line (ATM / JazzCash / school portal) to show you can apply the idea. Do not write a story about only one app.

CHECK YOURSELF

1. Name the four domains of HCI given in the source.
2. What user benefit does HCI bring in banking?
3. Give one education application and one networking application.

Write your answers in your notebook. The key follows this chapter's exam.

1.4 Importance of HCI ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 02 of 11 · 90 min · full Golden class. Board: HCI ensures that machines are approachable and usable, turning complex technology into everyday tools..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

HCI ensures that machines are approachable and usable, turning complex technology into everyday tools. **Good design** makes technology simple and enjoyable (touchscreens). **Poor design** causes confusion and risks (unclear buttons on medical devices).

This is why HCI is not optional decoration. A confusing JazzCash confirm button can send money to the wrong number. A confusing school-portal "Submit" can lock a student out of an online exam. Importance questions in the board exam expect the five implications below, each with a sentence of explanation.

Implication	Description
1. Enhance productivity	Well-designed interfaces help users work faster, make fewer mistakes, and achieve goals efficiently.
2. Promotes inclusivity	Accessibility features (screen readers, voice commands) empower marginalized groups and ensure equal use of technology for everyone.
3. Drives innovation	Emerging tech such as AR/VR, AI and IoT rely strictly on solid HCI principles for people to actually adopt and use them.
4. Economic impact	User-friendly products gain higher adoption rates, customer loyalty and market success, driving profits.
5. Ethical responsibility	Responsible design ensures technology respects user privacy, reduces bias and supports human well-being.

WORKED EXAMPLE

Worked example: good vs poor HCI, same task.

Task: send Rs 2,000 through JazzCash to a parent.

Good HCI: large "Send Money" button, amount shown in words and numbers, last 4 digits of the number repeated, fingerprint confirm, green "Successful" plus SMS. Result: fast, few mistakes, the user trusts the app (productivity + economic loyalty + ethics of clear consent).

Poor HCI: tiny grey buttons, no amount-in-words, no confirm screen, no tick. Result: wrong number, no idea if it worked, user deletes the app and goes back to a bank queue.

Medical contrast from the source: unclear buttons on a medical device are not just ugly — they are dangerous. That is why ethical responsibility sits in this table.

REMEMBER IT

P-I-I-E-E: Productivity, Inclusivity, Innovation, Economic impact, Ethics. Sentence: "Please Include Innovative, Ethical Earnings."

COMMON MISTAKE

Mistake: Writing only "HCI is important because it makes apps look nice."

Fix: Looks are a tiny part of UI. Importance answers must name productivity, inclusivity, innovation, money and ethics. Quote the medical-device warning if you have time.

اردو میں سمجھیں

اچھا ایچ سی آئی پیچیدہ ٹیکنالوجی کو روزمرہ کا آسان اوزار بناتا ہے؛ برا ڈیزائن الجھن اور خطرہ پیدا کرتا ہے، جیسے طبی آلے پر غیر واضح بٹن۔ پانچ مضمرات: پیداوری بڑھتی ہے، شمولیت آتی ہے، جدت اپنائی جاتی ہے، معیشت مضبوط ہوتی ہے، اور رازداری و انصاف کی اخلاقی ذمہ داری پوری ہوتی ہے۔

EXAM TIP

Typical wording: "Why is HCI important? Discuss its implications." (8 marks) Write a short opening (good design vs poor design) then five numbered points with one example each. Local examples that earn marks: ATM PIN privacy (ethics), screen reader on a school portal (inclusivity), JazzCash one-tap send (productivity), a bank's app beating a rival because it is easier (economic), AR classroom app that students actually use (innovation). Do not skip ethics — examiners look for privacy and well-being.

CHECK YOURSELF

1. Give one example of poor design mentioned in the source.
2. Which implication is about screen readers and equal use?
3. How does HCI create economic impact?

Write your answers in your notebook. The key follows this chapter's exam.

1.7 Human-Computer Interaction Problems ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 03 of 11 · 90 min · full Golden class. Board: HCI problems are common difficulties that stop users from using technology smoothly..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

HCI problems are common difficulties that stop users from using technology smoothly. They happen when systems fail to meet human needs or cognitive limits. **Cognitive limits** means the mind can only hold and process so much at once — if an app asks you to remember three SMS codes at the same time, it has gone past that limit.

Board answers score well when you name the problem, explain it in one line, and give a concrete example (the source examples are safe; a matching local example is even better).

Problem	Explanation and example
Interface complexity	Too many options or a confusing layout. Example: a shopping app with so many menus you cannot find the checkout button.
Poor feedback	The system does not show if an action worked or failed. Example: clicking Submit and the screen freezes with no confirmation.
Inconsistency	Different parts of the app look or act differently. Example: a magnifying-glass icon for Search on one page, a binocular icon on another.
Accessibility gaps	Design ignores people with disabilities. Example: a video tutorial platform without captions for deaf users.
Compatibility issues	Interface fails on different devices or browsers. Example: a website that works on a laptop but crashes on a mobile browser.
Contextual neglect	The system does not adjust to the user's situation. Example: a map app with no dark mode, blinding the driver at night.
High cognitive load	Users must memorize too much or follow overly complex steps. Example: a registration system forcing you to remember three different SMS codes at once.
Trust deficiency	The system feels unsafe or hides security cues. Example: an online store asking for credit cards but lacking an SSL/HTTPS lock icon.

WORKED EXAMPLE

Worked example: diagnose three local systems.

ATM: six tiny unmarked buttons beside the screen and no "Cash is coming" message → interface complexity + poor feedback. A user walks away while cash is still coming out.

JazzCash: "Send" is green on the home screen but orange on the confirm screen, and there is no padlock on the payment page → inconsistency + trust deficiency.

School portal: works in Chrome on a lab PC, blank on a student's Android browser; exam instructions are a caption-free video; login needs a portal password, an email OTP and an SMS OTP on the same screen → compatibility, accessibility gap, high cognitive load.

Once you can name the problem, Section 1.8 tells you how to fix it.

REMEMBER IT

Eight problems in two families: (1) Screen problems — complexity, inconsistency, accessibility, compatibility, context. (2) Mind-and-trust problems — poor feedback, cognitive load, trust. If the user is lost, look at the screen family. If the user is scared or exhausted, look at the mind family.

COMMON MISTAKE

Mistake: Writing "the app is bad" as an HCI problem, or mixing up cognitive load with compatibility.

Fix: Use the exact names from the table. Cognitive load is "too much to remember". Compatibility is "breaks on another device or browser".

اردو میں سمجھیں

ایچ سی آئی مسائل وہ رکاوٹیں ہیں جو سسٹم کو انسانی ضرورت یا ذہنی حد کے مطابق نہ ہونے پر پیدا ہوتی ہیں۔ آٹھ مسائل: انٹرفیس کی پیچیدگی، کمزور فیڈبیک، عدم مطابقت (ایک جیسا نہ ہونا)، رسائی کی کمی، آلہ/براؤزر سے ناسازگاری، سیاق کو نظرانداز کرنا، زیادہ ذہنی بوجھ، اور اعتماد کی کمی (جیسے HTTPS تالے کے بغیر کارڈ مانگنا)۔

EXAM TIP

Common 8-mark question: "Describe problems of HCI with examples." Aim for at least six of the eight, each in the pattern Name → one-line meaning → example. Memorise the source examples (checkout buried in menus, frozen Submit, binocular vs magnifying glass, no captions, laptop-only site, no dark mode, three SMS codes, missing HTTPS lock). Adding ATM / JazzCash / portal examples shows application and often gains the last marks.

CHECK YOURSELF

1. Which problem is a missing HTTPS lock on a payment page?
2. Why are three SMS codes at once an HCI problem?
3. A site works on a laptop but crashes on a phone. Name the problem.

Write your answers in your notebook. The key follows this chapter's exam.

1.9 User Interface Design (UI vs UX) ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 04 of 11 · 90 min · full Golden class. Board: UI design is the process of creating and organizing the visual elements of a software application so users can interact with it easily and efficiently..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

UI design is the process of creating and organizing the **visual elements** of a software application so users can interact with it easily and efficiently.

1.9.1 Components of a user interface

Component	Role
Buttons	Clickable elements that perform actions (Submit, Cancel).
Menus	Lists of options for navigating the system.
Icons	Small symbols representing tools or actions.
Text fields	Boxes where users type information (passwords, search).
Checkboxes / radio buttons	Selecting options in a form. Checkboxes allow several choices; radio buttons allow only one in a group.
Sliders	Adjusting values along a bar (volume, brightness).

1.9.2 User experience (UX)

UX is the overall experience a user has while interacting with a system — how smooth, comfortable and satisfying it feels.

UI is what you see; UX is how it feels.

WORKED EXAMPLE

Source example: food-delivery app. The UI is the nice pictures of burgers and the red buttons. The UX is that the app loads fast, tracking works, and the food arrives without the user getting frustrated.

Local walk-through: JazzCash.

- **UI:** green Send button, JazzCash logo, amount text field, fingerprint icon, menu of Bill / Load / Send.
- **UX:** login in two seconds, no crash in a weak-signal bazaar, money arrives, SMS comes, the user feels safe and finished — or, if it hangs with no tick, the UX is bad even if the buttons look pretty.

School portal: UI = logo, "Login" button, date-sheet menu icon. UX = a student finds the chemistry practical date in under a minute on a phone, without calling the clerk.

Pretty UI + slow, confusing flow = poor UX. Plain UI + fast, clear flow = good UX.

REMEMBER IT

Clothes vs day out. UI is the outfit (colours, buttons, icons). UX is the whole day (Did you arrive on time? Did you get wet? Were you stressed?). Examiners love the line: *UI is what you see; UX is how it feels.*

COMMON MISTAKE

Mistake: Writing "UI and UX are the same" or "UX is just colours".

Fix: UI = visual components (buttons, menus, icons, fields, checkboxes, sliders). UX = overall smoothness, comfort and satisfaction, including speed and whether the task succeeds.

اردو میں سمجھیں

یو آئی ڈیزائن بصری عناصر — بٹن، مینو، آئیکن، ٹیکسٹ فیلڈ، چیک باکس/ریڈیو، سلائیڈر — کو ترتیب دینا ہے۔ یو ایکس پورا تجربہ ہے: کتنا ہموار، آرام دہ اور اطمینان بخش لگا۔ یو آئی وہ ہے جو آپ دیکھتے ہیں؛ یو ایکس وہ ہے جو آپ محسوس کرتے ہیں۔ کھانے کی ڈیلیوری ایپ میں برگر کی خوبصورت تصویر یو آئی ہے، تیز لوڈنگ اور وقت پر کھانا یو ایکس ہے۔

EXAM TIP

Highest-yield short question in the chapter: "Differentiate between UI and UX with an example." Write: (1) the two definitions, (2) the sentence "UI is what you see; UX is how it feels", (3) the food-delivery example from the source, (4) optionally JazzCash or the school portal. For 5 marks also list four UI components. Do not spend the answer describing Figma — that is the next topic.

CHECK YOURSELF

1. List six UI components from the source.
2. In the food-delivery example, what is UX?
3. Complete: "UI is what you see; UX is ____."

Write your answers in your notebook. The key follows this chapter's exam.

1.11.2 Testing Methods (Usability, A/B, Automated) ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 05 of 11 · 90 min · full Golden class. Board: Testing involves observing how the system behaves under specific conditions..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Testing involves observing how the system behaves under specific conditions. Learn all seven methods. The three named in the heading — usability, A/B and automated — are the ones examiners ask most, but a complete answer also names the others.

1. **Usability testing:** observing real users while they perform realistic tasks, to measure efficiency and satisfaction. If the user gets stuck, designers know where to fix the UI.
2. **Task-based testing:** assigning a specific task (for example, "Find a product and add it to cart") and strictly measuring **completion time**, **success rate** and **number of errors**.
3. **Automated audits:** software bots scan websites to detect technical issues such as broken links, slow loading speeds or low colour contrast.
4. **A/B testing:** comparing two versions of an interface (A and B). Half the users see A, half see B. The one with more clicks or sign-ups wins.
5. **Compatibility testing:** verifying the system on different browsers (Chrome, Safari), devices (mobiles, tablets, PCs) and operating systems.
6. **Performance and load testing:** simulating high traffic (for example 10,000 users logging in at once) to see if speed drops or the server crashes.
7. **Keyboard and screen-reader walkthroughs:** navigating using *only* the keyboard (Tab/Enter) or assistive technologies, to check accessibility for users with disabilities.

Task-based

"Add to cart"
Time: 12 s
Success: Yes

A/B test

Version A | Version B
half / half users
more clicks wins

Automated audit

Bot scanning...
3 broken links
Low contrast

Three golden testing pictures: timed tasks, A versus B, and a bot that finds broken links and weak contrast.

WORKED EXAMPLE

Worked example: test JazzCash "Send Money" and a school portal with numbers.

Usability testing. Sit beside five students. Task: "Send Rs 100 to this test number." Do not help. Note where they pause. If three people look for Confirm at the bottom and it is at the top, that is your UI fix.

Task-based testing (numbers). Same task for 10 students.

- Success: 8 of 10 finish = success rate $(8 \div 10) \times 100 = 80\%$.
- Times: 12, 14, 11, 40, 13, 12, 15, 50, 14, 12 seconds. The two slow times (40, 50) are the students who got stuck — they also made errors.
- Errors: extra taps, wrong field. Count them. High errors + high time = poor HCI, even if most people eventually succeed.

A/B testing. Version A: green "Send" at the top. Version B: large orange "Send" under the amount. 200 users each. If B gets 140 completed payments and A gets 90, B wins. You keep B.

Automated audit. A bot reports 3 broken "Fee challan" links and low contrast on the portal's grey-on-grey marks table. Fix those before the board-exam rush.

Load testing. On result day, 10,000 students log in at 9:00 a.m. If the server crashes, performance testing failed — the UI never even appears.

Keyboard walkthrough. Unplug the mouse. Can a student Tab to "Download date sheet" and press Enter? If focus jumps randomly, accessibility testing failed.

REMEMBER IT

Task-based three numbers: Time, Success, Errors. **A/B:** two versions, split users, the higher clicks/sign-ups win. **Bot:** links, speed, contrast. **Load:** many users at once. **Keyboard:** Tab and Enter only.

COMMON MISTAKE

Mistake: Calling A/B testing "showing both designs to the same user and asking which is prettier".

Fix: Half the users see only A, half see only B. You measure behaviour (clicks, sign-ups), not a taste vote. Also: an automated audit does not replace watching real users — bots cannot see that a student is confused.

اردو میں سمجھیں

سات ٹیسٹنگ طریقے: یوزیبلٹی (حقیقی صارف کو کام کرتے دیکھنا)، ٹاسک بیسڈ (وقت، کامیابی، غلطیاں ناپنا)، خودکار آڈٹ (بوت ٹوٹے لنک، سست رفتار، کم کنٹراسٹ ڈھونڈنے)، اے/بی ٹیسٹ (آدھا صارف اے، آدھا بی؛ زیادہ کلک والا جیتے)، کمپیٹیبلٹی (براؤزر اور آلہ)، لوڈ ٹیسٹ (مثلاً دس ہزار لاگ ان)، اور صرف کی بورڈ یا اسکرین ریڈر سے چل کر رسائی کی جانچ۔

EXAM TIP

Golden 8-mark question: "Explain testing methods used in HCI." Write seven short paragraphs or a seven-row table. For full marks, define usability testing (observe real users on realistic tasks), give the three task-based measures, describe automated audits with the three bot findings (broken links, slow load, low contrast), explain A/B with the half-and-half rule, then add compatibility, load (10,000 users), and keyboard/screen-reader walkthroughs. If the paper asks only "usability, A/B and automated", go deep on those three and still mention the rest in one closing line.

CHECK YOURSELF

1. Name the three measurements in task-based testing.
2. In A/B testing, who sees version A?
3. Give two issues an automated audit can detect.

Write your answers in your notebook. The key follows this chapter's exam.

1.1 Fundamentals of Human-Computer Interaction

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 06 of 11 · 45 min · first half · with Traditional Interaction and 1.1.2 Natural Interaction. Board: Human-Computer Interaction (HCI) is the study and design of technology so that it serves people..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Human-Computer Interaction (HCI) is the study and design of technology so that it **serves people**. An HCI system is easy to use, efficient, and responsive to human needs. HCI is also known as **CHI** (Computer-Human Interface) or **MMI** (Man-Machine Interaction). The three names mean the same idea: the meeting point of a person and a machine.


HCI is not only "making a pretty screen". It asks: Can a student in Hyderabad find results on the school portal in 30 seconds? Can a grandmother send JazzCash without help? Can a person standing at an outdoor ATM in bright sunlight read the buttons?

Sensory channels of interaction

Humans and computers communicate through **sensory channels**. A sensory channel is a path that carries information to (or from) one of the human senses. Computers must send and receive signals on the same channels, or the conversation breaks.

Channel	How humans use it	How computers respond
Sight (بصارت)	Look at screens, graphics or videos.	Displays visuals on monitors and screens.
Touch (چھونا)	Tap, type or swipe.	Responds with clicks or vibrations (haptics).
Hearing (سننا)	Listen to sounds or voices.	Provides audio feedback via speakers.
Voice (آواز)	Speak commands (for example, "Alexa").	Processes speech and replies.
Spatial (مکانی)	Move in physical space.	Tracks position or body movement (for example, VR).

Haptics means physical feedback you can feel, such as a phone vibrating when a JazzCash payment succeeds. **Spatial** interaction means the system notices where your body is, as in a VR headset or a Kinect camera.



Five sensory channels meet at the human. HCI design must support the channels the user actually needs.

WORKED EXAMPLE

Worked example: map a JazzCash payment to channels. Sara in Sukkur sends Rs 500 to her brother.

1. **Sight:** she looks at the JazzCash home screen and the amount field.
2. **Touch:** she taps "Send Money" and types the mobile number.
3. **Voice (optional):** she could say "JazzCash, send five hundred rupees" if voice commands are on.
4. **Hearing + haptics:** a beep and a short vibration confirm "Payment successful".

If the app showed no tick, no sound and no vibration, Sara would not know whether the money left. That is an HCI failure, not a banking failure.

REMEMBER IT

Remember the three names: HCI = CHI = MMI. Think "Human meets Machine." Five channels: **S-T-H-V-S** — Sight, Touch, Hearing, Voice, Spatial. "See The Handy Voice in Space."

COMMON MISTAKE

Mistake: Writing "HCI is only about computer hardware" or mixing up Voice with Hearing.

Fix: HCI is about the *design of the conversation* between people and machines. Hearing is what you *listen to* (speakers). Voice is what you *speak* (microphone + speech software).

اردو میں سمجھیں

ہیومن کمپیوٹر انٹرایکشن (HCI) کا مطلب ہے ٹیکنالوجی کو اس طرح ڈیزائن کرنا کہ وہ انسانوں کے لیے فائدہ مند، آسان اور مؤثر ہو۔ اسے CHI یا MMI بھی کہتے ہیں۔ انسان اور کمپیوٹر پانچ حسی راستوں سے بات کرتے ہیں: بصارت، چھونا، سنا، آواز اور مکانی حرکت۔ ہیپٹکس (Haptics) وہ ارتعاش ہے جو آپ کو چھو کر محسوس ہوتا ہے۔

CHECK YOURSELF

1. Give two other names for HCI.
2. Which channel tracks body movement in VR?
3. Is a phone vibration sight, touch (haptics), or voice?

Write your answers in your notebook. The key follows this chapter's exam.

1.1.1 Traditional Interaction and 1.1.2 Natural Interaction

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 06 of 11 · 45 min · second half · with Fundamentals of Human-Computer Interaction. Board: 1.1.1 Traditional interaction is the basic way people use everyday devices..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

1.1.1 Traditional interaction is the basic way people use everyday devices. It relies on standard input and output: a mouse, a keyboard, a keypad, a monitor, speakers, or a simple touchscreen tap and swipe.

- **Computer:** moving a mouse and typing on a keyboard; output via monitor and speakers.
- **Smartphone (traditional use):** tapping and swiping on a touchscreen; output via screen lighting and vibrations.

1.1.2 Natural interaction is advanced, smart technology that lets people interact **without a mouse or keyboard**. It feels more human — you speak, move, or show your face, and the system understands.

- **Voice:** speaking commands into a device (for example, "Alexa, play a song").
- **Body and gesture:** facial recognition to unlock a phone, or playing VR games by waving hands.

Feature	Traditional	Natural
Main input	Mouse, keyboard, keypad, simple tap/swipe	Voice, face, hand/body gesture, movement
Feels like	Operating a machine	Talking or moving as you do with people
Examples	TV remote, ATM keypad, school-portal login typed on a PC	FaceID, Siri, Kinect games, "Hey Google"
Typical output	Screen, speakers, vibration	Spoken reply, unlock, tracking of the body in VR

WORKED EXAMPLE

Worked example: sort today's tools. List three traditional and three natural interfaces you might use in one day in Sindh.

Traditional: (1) HBL ATM keypad to withdraw cash. (2) College computer lab: mouse + keyboard to open the school portal. (3) Television remote at home.

Natural: (1) Unlocking a phone with FaceID. (2) Asking Google Assistant "Call Aslam". (3) A VR science demo in which you pick a molecule by waving your hand.

Notice: the *same smartphone* can be traditional (you type a PIN) or natural (the camera reads your face). The classification depends on **how you interact**, not on the brand of the device.

REMEMBER IT

Test sentence: If you must press keys or tap labelled buttons, it is traditional. If the machine understands speech, face or body movement, it is natural.

COMMON MISTAKE

Mistake: "Touchscreens are always natural interaction."

Fix: Ordinary tapping and swiping on a phone is still listed as traditional in this chapter. Natural interaction starts when the system understands voice, face, or full-body gesture without a mouse or keyboard.

اردو میں سمجھیں

روایتی تعامل (Traditional Interaction) میں ماؤس، کی بورڈ، کی پیڈ یا عام ٹیپ اور سوائپ استعمال ہوتے ہیں، جیسے اے ٹی ایم کی پیڈ۔ قدرتی تعامل (Natural Interaction) میں آواز، چہرہ یا جسم کی حرکت سے کام ہوتا ہے، جیسے فیس آئی ڈی (FaceID) یا "الیکسا، گانا چلاؤ"۔ درجہ بندی آلے کی نہیں، تعامل کے طریقے کی ہوتی ہے۔

CHECK YOURSELF

1. Is an ATM keypad traditional or natural?
2. Give one voice example of natural interaction from the source.
3. Why can one smartphone be both traditional and natural?

Write your answers in your notebook. The key follows this chapter's exam.

1.3 Components of HCI

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.


Coach / teacher. Class 07 of 11 · 45 min · first half · with Types of User Interaction. Board: HCI relies on several primary components that work together..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

HCI relies on several primary components that work together. If one component is weak, the whole interaction feels broken. The first four are the people, the machine, the conversation, and the job to be done.

	Component	Meaning
i	User (صارف)	Any individual or group that interacts with a computer system to achieve defined goals. Two categories: end users (people who directly operate the system, from beginners to experts) and stakeholders (people with an interest in the outcome, such as managers and clients).
ii	Computer system (کمپیوٹر سسٹم)	The platform where humans and computers communicate through input, output and feedback using an interface. It connects human actions with machine responses.
iii	User interaction (صارف کا تعامل)	The process through which a user communicates with a system by performing actions (clicking, tapping, typing, speaking). It transforms user intent into system responses.
iv	Task (کام)	The specific action users perform (for example, booking a ticket). It has three characteristics: task complexity (filling a form vs designing a 3D model), user knowledge (basic typing vs advanced programming), and time requirement (ATM withdrawal vs online passport application).



The user performs a task through interaction with a computer system. All four parts must fit together.

WORKED EXAMPLE

Worked example: label the four components of an HBL ATM withdrawal.

1. **User:** end user = the account holder standing at the machine; stakeholder = the bank that owns the ATM and must keep it safe and working.
2. **Computer system:** the ATM hardware plus the bank's software; it takes PIN input, shows a screen, and dispenses notes (output and feedback).
3. **User interaction:** insert card → type PIN → choose "Cash" → type amount → confirm. Intent ("I want Rs 5,000") becomes a machine response (cash + receipt).
4. **Task:** withdraw cash. Complexity: low (a few buttons). User knowledge: basic (PIN and amounts). Time: about one minute — much shorter than an online passport application.

REMEMBER IT

U-C-I-T: User, Computer system, Interaction, Task. "U Can Interact with Tasks." Then add three task questions: How hard? What skill? How long?

COMMON MISTAKE

Mistake: Calling the bank manager an "end user" of the ATM, or saying a task has only one property (difficulty).

Fix: The manager is usually a **stakeholder**. The person pressing the keys is the **end user**. A task always has complexity, knowledge and time — mention all three in long answers.

اردو میں سمجھیں

ایچ سی آئی کے چار بنیادی اجزاء ہیں: صارف (اینڈ یوزر جو خود سسٹم چلاتا ہے اور اسٹیک ہولڈر جس کا نتیجے میں مفاد ہے)، کمپیوٹر سسٹم (ان پٹ، آؤٹ پٹ اور فیڈبیک کا پلیٹ فارم)، صارف کا تعامل (کلک، ٹیپ، ٹائپ، بولنا) اور کام (ٹاسک) جس کی پیچیدگی، مطلوبہ مہارت اور وقت مختلف ہوتا ہے۔ اے ٹی ایم سے رقم نکالنا آسان اور مختصر کام ہے؛ پاسپورٹ کی آن لائن درخواست لمبا کام ہے۔

CHECK YOURSELF

1. What is the difference between an end user and a stakeholder?
2. Name the three characteristics of a task.
3. In a school portal, who is a stakeholder?

Write your answers in your notebook. The key follows this chapter's exam.

Types of User Interaction

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 07 of 11 · 45 min · second half · with Components of HCI. Board: User interaction can happen in many different ways depending on the technology used..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

User interaction can happen in many different ways depending on the technology used. Learn every type with one clean example — board questions often ask you to "list and explain" five or more.

Interaction type	Description	Examples
Direct manipulation	Handling digital objects on a screen exactly like physical objects.	Dragging files, zooming images with fingers
Command-based	Giving precise instructions through typed text commands.	MS-DOS, Linux terminal (<code>dir</code> , <code>cd ..</code>)
Menu-driven	Selecting from predefined lists or options instead of typing.	Clicking "Start Test" or "Download" on a portal
Form fill	Entering structured data into blank text fields.	Sign-up forms, ticket booking screens
Conversational	Communicating with systems using natural human language (text or voice).	Chatbots, ChatGPT, Google Assistant
Gesture-based	Using body or hand movements to control systems.	Swiping touchscreens, VR hand gestures
Voice interaction	Speaking commands directly to the system.	"Call Aslam" on a smartphone
Context-aware	Systems sense the environment and act automatically without a prompt.	Smart lighting turning on when you enter a room
Biometric	Using biological features for interaction and authentication.	Fingerprint unlock, FaceID
Haptic and tactile	Providing physical feedback to confirm actions.	Phone vibration when typing
Multimodal	Combining two or more interaction types together.	Voice + touch (speak a search, then tap)

WORKED EXAMPLE

Worked example: a full JazzCash "Send Money" session, labelled by type.

1. Open the app with a fingerprint → **biometric**.
2. Home screen shows Send Money, Bill Payment, Load → you tap Send Money → **menu-driven**.
3. Type the receiver's mobile number and the amount → **form fill**.
4. The keypad vibrates on each tap → **haptic**.
5. Optional: say "Send five hundred to Ali" then tap Confirm → **multimodal** (voice + touch).

Same idea on a **school portal**: menu-driven ("Date Sheet", "Fee Challan"), form fill (leave application), conversational (a chatbot "When is the chemistry practical?").

REMEMBER IT

Group them: hands on screen (direct, gesture, haptic) · words (command, conversational, voice) · lists and blanks (menu, form) · automatic/body (context-aware, biometric) · mix (multimodal).

COMMON MISTAKE

Mistake: Treating "voice interaction" and "conversational" as identical, or calling a dropdown menu "command-based".

Fix: Voice is spoken commands only. Conversational includes typed chat (ChatGPT) as well as voice. Command-based means you type precise codes such as `dir`, not clicking a menu.

اردو میں سمجھیں

تعامل کی اقسام میں براہ راست پیرا پھیری، کمانڈ، مینو، فارم، گفتگو (چیٹ بوٹ)، اشارہ، آواز، سیاق و سباق سے آگاہ نظام، بائیومیٹرک، بیپٹک اور ملٹی موڈل شامل ہیں۔ جاز کیش میں فنگر پرنٹ بائیومیٹرک ہے، "رقم بھیجیں" مینو ہے، نمبر لکھنا فارم ہے، اور آواز کے ساتھ ٹیپ ملٹی موڈل ہے۔

CHECK YOURSELF

1. Which type is a Linux `cd ..` command?
2. Smart lighting that turns on when you enter a room is which type?
3. Why is speaking a search and then tapping a result called multimodal?

Write your answers in your notebook. The key follows this chapter's exam.

Interface Types, Environment and Feedback

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 08 of 11 · 45 min · first half · with Accessibility Principles. Board: Components v–vii complete the HCI picture: the look of the controls, the place where you use them, and the signals that tell you "it worked" or "try again"..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Components v–vii complete the HCI picture: the look of the controls, the place where you use them, and the signals that tell you "it worked" or "try again".

v) User interface (UI)

The **user interface** is the medium through which humans interact with computer systems.

- **Graphical User Interface (GUI):** visual elements such as windows, icons and menus (Windows OS, Android).
- **Command-Line Interface (CLI):** text-based typing (MS-DOS, Linux terminal).
- **Touch interface:** tapping, swiping, pinching (smartphones, tablets).
- **Voice User Interface (VUI):** spoken commands (smart speakers).
- **Natural User Interface (NUI):** gestures, body movements or immersive environments (VR headsets, Microsoft Kinect).

vi) Environment

The **environment** is the real-world setting where a person uses a computer system. It is shaped by:

- **Physical conditions** — an ATM outdoors in sunlight, heat, noise, rain.
- **Social conditions** — a quiet classroom, a crowded bazaar, privacy at a PIN pad.
- **Technical hardware** — slow college Wi-Fi, a cracked phone screen, an old browser.

vii) Feedback

Feedback is the signal or response given to confirm or guide actions.

System feedback

Response from the computer: a "Loading..." bar, a "Message Sent!" tick, or an error sound.

User feedback

Input from the user to the system: tapping a "Submit" button, giving a 5-star rating.

WORKED EXAMPLE

Worked example: environment and feedback at a roadside ATM in Hyderabad.

Physical: noon sunlight washes out a dim screen — the GUI must use high contrast.

Social: people stand in a queue; the user needs a privacy shield around the PIN pad.

Technical: the printer may be out of paper, so on-screen "Take your cash" plus a beep still has to confirm the transaction.

System feedback: "Please wait", cash coming out, a printed or SMS receipt.

User feedback: the user presses Confirm, or later rates the bank's app 4 stars.

On a **school portal** during board-exam week, hundreds of students on weak Wi-Fi need a visible "Loading results..." bar. Silence after clicking "View marks" is poor system feedback.

REMEMBER IT

GUI vs CLI vs NUI: GUI = pictures you click. CLI = words you type. NUI = body you move. VUI = voice you speak. Touch = fingers on glass.

Feedback rule: **system talks back; user talks in.**

COMMON MISTAKE

Mistake: Mixing up system feedback with user feedback, or saying "environment" means only the software theme (dark mode).

Fix: A tick mark is system feedback. A 5-star rating is user feedback. Environment is the *real world* around the user — sun, noise, hardware — not the colour of the app (though a good UI will adapt to that world).

اردو میں سمجھیں

یوزر انٹرفیس وہ واسطہ ہے جس سے انسان سسٹم سے بات کرتا ہے: GUI تصاویر اور مینو، CLI لکھی کمانڈ، ٹچ، آواز (VUI) اور قدرتی اشارے (NUI)۔ ماحول وہ حقیقی جگہ ہے جہاں سسٹم استعمال ہوتا ہے — دھوپ میں اے ٹی ایم، خاموش کلاس روم، کمزور وائی فائی۔ سسٹم فیڈبیک مشین کا جواب ہے ("بھیج دیا گیا")؛ صارف کا فیڈبیک صارف کا ان پٹ ہے (سمٹ بٹن یا پانچ ستارے)۔

CHECK YOURSELF

1. Name five types of user interface given in the source.
2. Give one physical and one social example of environment.
3. Is a "Message Sent" tick system feedback or user feedback?

Write your answers in your notebook. The key follows this chapter's exam.

1.5 Accessibility Principles

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 08 of 11 · 45 min · second half · with Interface Types, Environment and Feedback. Board: Accessibility principles are HCI guidelines that ensure digital systems are usable by all individuals, including people with diverse physical, sensory and cognitive abilities..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Accessibility principles are HCI guidelines that ensure digital systems are usable by **all** individuals, including people with diverse physical, sensory and cognitive abilities. They remove barriers to create equal access.

Accessibility is not a "special extra". It is how you make sure a student with low vision, a shopkeeper who cannot use a mouse, or a colour-blind driver can still complete the task.

Principle	What it means	Example
1. High contrast (واضح رنگ)	Make text and pictures stand out clearly against the background.	Black text on a white background in a railway app, readable in bright sunlight.
2. Readable fonts (پڑھنے میں آسان تحریر)	Clear, simple fonts with proper size and spacing.	A school website using large Calibri so homework instructions are easy to read.
3. Colour-blind friendly design (رنگوں کی پہچان)	Do not depend <i>only</i> on colours; also use symbols or text labels.	A traffic app showing a red circle with a "STOP" label, not just a red colour.
4. Inclusive navigation (آسان نیویگیشن)	Give users different ways to move around a system.	A website that lets you use the Tab key to jump between buttons if you cannot use a mouse.
5. Multimodal detection (متعدد حسی ذرائع)	Present information in different formats (sight, sound, touch).	A video with text captions, or a phone vibrating to alert a user.

WORKED EXAMPLE

Worked example: audit a school portal against the five principles.

1. **Contrast:** are result PDFs pale grey on white? Fail — use dark text.
2. **Fonts:** is the fee-challan note in 9-point decorative script? Fail — large Calibri (or a similar simple font), as the source recommends.
3. **Colour:** is "fail" only a red row with no word "Fail"? Fail — add the word, for colour-blind students.
4. **Navigation:** can a student who cannot use a mouse reach "Download date sheet" with Tab + Enter? If not, fail.
5. **Multimodal:** does the principal's video assembly have captions, and does a fee-due alert vibrate as well as flash? If not, deaf or busy students miss it.

The same five checks apply to an outdoor ATM (sunlight contrast) and to JazzCash (large numerals, Urdu labels, vibration on success).

REMEMBER IT

C-F-C-N-M: Contrast, Fonts, Colour-blind, Navigation, Multimodal. "Can Friends Catch New Messages?"

COMMON MISTAKE

Mistake: "Accessibility is only for people with disabilities, so our class portal does not need it."

Fix: The source says usable by **all** individuals. High contrast also helps in sunlight; captions help in a noisy bus; large fonts help tired eyes during board exams.

اردو میں سمجھیں

رسائی پذیری (Accessibility) کے اصول یقینی بناتے ہیں کہ ہر انسان سسٹم استعمال کر سکے، بشمول مختلف جسمانی، حسی اور ذہنی صلاحیتوں والے افراد۔ پانچ اصول: اونچا تضاد (کنٹراسٹ)، پڑھنے میں آسان فونٹ، صرف رنگ پر انحصار نہ کرنا، کی بورڈ سمیت متبادل نیویگیشن، اور معلومات کو نظر، آواز اور لمس کئی شکلوں میں دینا۔

CHECK YOURSELF

1. Why is a red-only "STOP" sign a problem?
2. Which principle does the Tab key support?
3. Give the source's school-website font example.

Write your answers in your notebook. The key follows this chapter's exam.

1.6 Need Analysis for Interface Design

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 09 of 11 · 45 min · first half · with Methods for Improving HCI. Board: Need analysis is the process of identifying the gap between the existing situation and the desired outcome..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Need analysis is the process of identifying the gap between the **existing situation** and the **desired outcome**. In HCI it is done **before** designing a UI, so that you understand users' goals, tasks, abilities and expectations.

If you skip need analysis, you guess. Guessing is how a school portal ends up with 40 menus and no "Download date sheet" button on the home screen.

Steps in need analysis:

1. Identify the users → 2. Collect information → 3. Analyse needs → 4. Prioritise → 5. Develop solutions

1. **Identify the users:** who exactly will use the system? (elderly people, teenagers, ...)
2. **Information collection:** gather data using interviews, questionnaires or observations.
3. **Analyse user needs:** identify the core problems, goals and requirements.
4. **Prioritise needs:** decide which features are the most critical to build first.
5. **Develop solutions:** design a system that meets those verified needs.

WORKED EXAMPLE

Case study from the source: mobile banking app. Before building the app, the team interviews customers and discovers:

- Users want secure login via Fingerprint / FaceID.
- Elderly users need large buttons and simple navigation.
- Users want support for both English and local languages.

Result: the UI is designed around these proven needs, which makes success more likely.

Apply the five steps to a college portal in Sindh.

1. Users: Grade XI–XII students, parents, clerks, teachers. Not "everyone in Pakistan".
2. Collect: interview 20 students; questionnaire to parents; watch a queue at the office on fee day.
3. Analyse: students cannot find date sheets; parents cannot read English-only fee notices; clerks re-type the same form.
4. Prioritise: (1) date sheet on home screen, (2) Urdu/Sindhi fee notice, (3) online leave form. Fancy animations wait.
5. Solution: a simple portal with those three features, large buttons, bilingual labels.

REMEMBER IT

Need analysis = gap finding. Write: Existing = what hurts now. Desired = what "done" looks like. The UI must close that gap, not decorate it.

COMMON MISTAKE

Mistake: Starting in Figma on day one, then "asking users later".

Fix: Need analysis comes **before** UI design. Features you did not hear from users are guesses. Guessed features waste time and fail in exams when the question is "why do we analyse needs?"

اردو میں سمجھیں

نیڈ اینالیسس موجودہ صورتحال اور مطلوبہ نتیجے کے فرق کو یو آئی بنانے سے پہلے تلاش کرتا ہے۔ پانچ قدم: صارفین کی پہچان، انٹرویو یا مشاہدے سے معلومات، ضروریات کا تجزیہ، اہم خصوصیات کو ترجیح، پھر تصدیق شدہ ضرورتوں پر حل۔ موبائل بینکنگ کی مثال: فنگر پرنٹ لاگ ان، بڑے بٹن، اور انگریزی کے ساتھ مقامی زبان۔

CHECK YOURSELF

1. When in the design process is need analysis done?
2. List the five steps in order.
3. Name three needs found in the mobile-banking case study.

Write your answers in your notebook. The key follows this chapter's exam.

1.8 Methods for Improving HCI

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 09 of 11 · 45 min · second half · with Need Analysis for Interface Design. Board: Once you can name an HCI problem, you fix it with a matching method..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Once you can name an HCI problem, you fix it with a matching method. The source lists eight methods. Learn each with its tiny example — they pair almost one-to-one with Section 1.7.

- **Enhance usability:** simplify navigation (a clear "Buy Now" button).
- **Strengthen accessibility:** support disabilities (captions on videos).
- **Ensure consistency:** keep layouts uniform (the same "Save" button everywhere).
- **Provide clear feedback:** show action results ("Payment Successful" popup).
- **Improve adaptability:** responsive design (the website scales to mobile screens).
- **Apply user-centred design (UCD):** focus on real user goals and pilot-test.
- **Use multimodal interaction:** allow touch, voice or gesture inputs combined.
- **Continuous testing:** regularly update based on user feedback.

User-centred design (UCD) means the real user's goals drive every decision, and you trial (pilot-test) the design with those users instead of guessing in an office.

Responsive design means the layout rearranges itself for phone, tablet and PC, instead of staying a laptop-only page.

WORKED EXAMPLE

Worked example: match each JazzCash / portal problem to a fix.

Problem (1.7)	Method (1.8)
Cannot find "Send Money"	Enhance usability — one clear button
No captions on help video	Strengthen accessibility
Search icon changes from page to page	Ensure consistency
Submit freezes with no message	Clear feedback — "Payment Successful"
Portal crashes on mobile	Improve adaptability — responsive layout
Built features nobody asked for	UCD — interview, then pilot-test
Elderly user cannot type a long number	Multimodal — voice + touch
Complaints ignored after launch	Continuous testing and updates

REMEMBER IT

Think "problem → method" as a pair. Complexity ↔ usability. No captions ↔ accessibility. Different icons ↔ consistency. Freeze ↔ feedback. Phone crash ↔ adaptability. Guessing ↔ UCD. One input only ↔ multimodal. Launch and forget ↔ continuous testing.

COMMON MISTAKE

Mistake: Naming methods without saying *what they change* ("we will improve HCI" is not an answer).

Fix: Always attach the source example: "Provide clear feedback, for example a Payment Successful popup."

اردو میں سمجھیں

ایچ سی آئی بہتر بنانے کے طریقے: نیویگیشن آسان کرنا، رسائی بڑھانا (کیپشن)، ایک جیسا لے آؤٹ، واضح فیڈبیک ("ادائیگی کامیاب")، ریسپانسیو ڈیزائن، صارف مرکز ڈیزائن (UCD) اور پائلٹ ٹیسٹ، ملٹی موڈل ان پٹ، اور مسلسل جانچ۔ ہر مسئلے کا ایک جوڑی دار حل یاد رکھیں۔

CHECK YOURSELF

1. What does UCD stand for, and what extra step does it include?
2. Which method stops a website from failing on a phone?
3. Give the source's example of clear feedback.

Write your answers in your notebook. The key follows this chapter's exam.

1.9.3–1.9.5 Wireframing, Figma and Prototypes

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 10 of 11 · 45 min · first half · with Test and Evaluate HCI (Evaluation Methods). Board: 1.9.3 Wireframing is creating a basic visual outline or blueprint of a user interface before the final design..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

1.9.3 Wireframing is creating a basic visual outline or blueprint of a user interface **before** the final design. It plans the structure without focusing on colours or detailed graphics.


Low-fidelity wireframes (Lo-Fi)

A simple black-and-white sketch showing basic layout (boxes and lines). Used early to test and share ideas quickly. Focuses purely on structure and flow.

High-fidelity prototypes (Hi-Fi)

A detailed version that looks almost exactly like the final product. Includes real colours, fonts, images and interactive clickable buttons. Used for final user testing.

Lo-Fi sketch → Add details → Hi-Fi prototype



A school-portal login: Lo-Fi boxes and labels on the left; a coloured, realistic Hi-Fi prototype on the right.

1.10 What is Figma?

Figma is a popular, free, web-based tool used to design and collaborate on UI and prototypes. It works directly in a web browser — you do not have to install a heavy program on the college lab PCs.

Creating a low-fidelity design in Figma

1. **Sign up:** access the Figma workspace online.
2. **Create frames:** select the Frame tool (for example an iPhone-sized frame) to act as your screen canvas.
3. **Add shapes:** draw basic rectangles for buttons and circles for avatars.
4. **Add text:** use the text tool to label buttons (for example, "Sign Up").
5. **Duplicate and edit:** copy the frame to create the next screen (for example, the Home Screen).

1.9.5 Prototype design

A **prototype** is an early interactive model used to test design ideas **before writing actual code**. In Figma you use the Prototype tab to link screens together.

- Set a **Trigger** (for example, "On Tap").
- Set an **Action** (for example, "Navigate to Home Screen").

Real users can then click through the fake app to see if the navigation makes sense.

WORKED EXAMPLE

Worked example: JazzCash-style "Send Money" in Figma, without writing code.

1. Lo-Fi on paper or in Figma: three frames — Home (boxes: Send, Bills, Load), Amount (text field + Next), Success (tick + Done).
2. Show the sketch to two classmates. If they cannot find Send, move that box to the top. This is the point of Lo-Fi: cheap changes.
3. In Figma, add a phone frame, rectangles, and labels. Duplicate the frame for Home, Amount and Success.
4. Prototype tab: Trigger = On Tap of the Send rectangle; Action = Navigate to Amount. On Tap of Next → Success.
5. Hand the laptop to a student. If they tap Bills by mistake, the navigation is still wrong — fix it before any programmer writes Java or Kotlin.

REMEMBER IT

Lo-Fi = boxes. Hi-Fi = almost the real app. Prototype = clickable. Figma can hold all three stages. Trigger = what the user does. Action = where the fake app goes.

COMMON MISTAKE

Mistake: Colouring a Lo-Fi wireframe, or thinking a Figma prototype is the finished coded app.

Fix: Lo-Fi stays black-and-white on purpose so people discuss structure, not taste in colours. A prototype tests ideas before code; developers still have to build the real system afterwards.

وائر فریم یو آئی کا بنیادی خاکہ ہے، رنگوں سے پہلے۔ لو فائی سیاہ و سفید ڈیے ہیں؛ ہائی فائی تقریباً حتمی شکل ہے، رنگ، فونٹ اور کلک ہونے والے بٹن کے ساتھ۔ فگما (Figma) مفت ویب ٹول ہے: فریم بناؤ، شکل اور متن ڈالو، فریم کاپی کرو۔ پروٹوٹائپ کوڈ سے پہلے کا چلنے والا نمونہ ہے جس میں ٹرگر (On Tap) اور ایکشن (اگلی اسکرین) جوڑے جاتے ہیں۔

CHECK YOURSELF

1. What does a Lo-Fi wireframe deliberately leave out?
2. Where does Figma run?
3. In Figma prototyping, what is a trigger? Give the source example.

Write your answers in your notebook. The key follows this chapter's exam.

1.11 Test and Evaluate HCI (Evaluation Methods)

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 10 of 11 · 45 min · second half · with Wireframing, Figma and Prototypes. Board: Testing checks if the product works properly (finding bugs)..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Testing checks if the product works properly (finding bugs). **Evaluation** determines whether it meets users' needs (usability). Together they improve the product before release.

A school portal can be "bug-free" (testing passed) and still unusable if students cannot find the date sheet (evaluation failed). You need both.

1.11.1 Evaluation methods

Method	Description
SUS (System Usability Scale)	A standard 10-item questionnaire used to calculate a score for how usable a system is.
NPS (Net Promoter Score)	Asks users: "How likely are you to recommend this app to a friend?" Measures user loyalty.
Formative evaluation	Done during development to collect early feedback and improve the design continuously.
Summative evaluation	Done at the end of development to measure overall success against the original goals.
Expert reviews	Usability specialists review the app against established design standards (heuristics).

Heuristics are agreed rules of good design (for example "show system status", "be consistent"). An expert review checks the product against those rules without waiting for a huge user survey.

WORKED EXAMPLE

Worked example: when to use each method on a school portal.

1. Week 2 of building: show the Lo-Fi to five students, change the menu. That is **formative** evaluation.
2. A teacher who has studied HCI checks the screens against standard rules (Is feedback visible? Are labels consistent?). That is an **expert review**.
3. After the portal is "finished", 30 students fill the 10 SUS questions. A low score means it is still hard to use, even if there are no crashes.
4. Ask: "On a scale of 0–10, would you recommend this portal to a friend in another college?" That is **NPS** (loyalty).
5. Compare the finished portal with the original goals (date sheet in one tap, bilingual fee notice). That is **summative** evaluation.

REMEMBER IT

Formative = forming it (during). Summative = summing it up (end). SUS = 10 questions on usability. NPS = "Would you recommend it?" Expert = specialist vs heuristics.

COMMON MISTAKE

Mistake: Saying testing and evaluation are the same, or mixing formative with summative.

Fix: Testing = bugs. Evaluation = does it meet human needs. Formative is during; summative is at the end against original goals.

اردو میں سمجھیں

ٹیسٹنگ یہ دیکھتی ہے کہ پروڈکٹ ٹھیک چلتا ہے (بگز)؛ ایویلیوایشن یہ دیکھتی ہے کہ صارف کی ضرورت پوری ہوئی۔ SUS دس سوالوں والا استعمال کا اسکور ہے، NPS پوچھتا ہے کہ آپ یہ ایپ دوست کو کتنی تجویز کریں گے۔ فارمیٹو جانچ ترقی کے دوران ہوتی ہے، سمیٹو آخر میں اہداف کے خلاف۔ ماہر جائزہ ہیورسٹکس (Heuristics) پر ہوتا ہے۔

CHECK YOURSELF

1. What is the difference between testing and evaluation?
2. How many items are on the SUS questionnaire?
3. When is summative evaluation done?

Write your answers in your notebook. The key follows this chapter's exam.

Career Opportunities in UI/UX

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 11 of 11 · 90 min · single class. Board: The same HCI skills you practised on ATMs, JazzCash and school portals are real jobs..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

The same HCI skills you practised on ATMs, JazzCash and school portals are real jobs. Each role uses a different slice of this chapter.

Career	What the person does
UX designer	Researches user needs to ensure the app is intuitive and satisfying.
UI designer	Designs the visual layout (colours, typography, buttons) using tools such as Figma.
Interaction designer	Focuses on the flow between screens, animations and gestures.
Usability researcher	Runs SUS/NPS tests and A/B tests with real users to find flaws.
Accessibility specialist	Ensures products meet inclusive standards for people with disabilities.

WORKED EXAMPLE

Worked example: who does which JazzCash task?

- "Interview shopkeepers about sending money" → **UX designer**.
- "Pick the green, the typeface and the Send button in Figma" → **UI designer**.
- "On Tap Send, slide to Confirm, then Success" → **interaction designer**.
- "Run SUS and an A/B test of two Send buttons" → **usability researcher**.
- "Check contrast, captions and Tab order" → **accessibility specialist**.

REMEMBER IT

UI looks; UX asks; interaction connects screens; research measures; accessibility includes everyone.

COMMON MISTAKE

Mistake: "UI designer and UX designer are one job."

Fix: In small teams one person may wear both hats, but the source lists them separately: UX researches needs and satisfaction; UI draws the visual layout in tools like Figma.

اردو میں سمجھیں

اس باب سے ملازمتیں: یو ایکس ڈیزائنر صارف کی ضرورت تحقیق کرتا ہے، یو آئی ڈیزائنر فگما میں رنگ اور بٹن بناتا ہے، انٹریکشن ڈیزائنر اسکرینوں کا بہاؤ سنبھالتا ہے، یوزیبلٹی ریسرچر SUS، NPS اور اے/بی ٹیسٹ چلاتا ہے، اور ایکسیسیبلٹی ماہر سب کے لیے رسائی یقینی بناتا ہے۔

CHECK YOURSELF

1. Who runs SUS, NPS and A/B tests?
2. Which career uses Figma for colours, type and buttons?

Write your answers in your notebook. The key follows this chapter's exam.

Computer Systems (HCI)

16 single-page lessons · 5 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- **HCI** (also CHI, MMI) designs technology to be easy, efficient and responsive to people, using five sensory channels: sight, touch (haptics), hearing, voice and spatial.
- **Traditional interaction** uses mouse, keyboard, keypad or simple tap/swipe; **natural interaction** uses voice, face or body gesture without a mouse or keyboard.
- HCI applications cover **health care, banking, education, and networking/communication**, each with a clear user benefit (remote care, quick secure money, better learning, global connection).
- Four core components: **user** (end user vs stakeholder), **computer system**, **user interaction**, and **task** (complexity, knowledge, time).
- Interaction types include direct manipulation, command-based, menu-driven, form fill, conversational, gesture, voice, context-aware, biometric, haptic and multimodal.
- Interfaces: GUI, CLI, touch, VUI, NUI. **Environment** is physical, social and technical. **System feedback** is the machine's reply; **user feedback** is what the person sends in.
- HCI matters for productivity, inclusivity, innovation, economic impact and ethical responsibility. Poor design (unclear medical buttons) creates risk.
- Five accessibility principles: high contrast, readable fonts, colour-blind friendly labels, inclusive navigation, multimodal presentation.
- **Need analysis** finds the gap before UI design: identify users, collect data, analyse, prioritise, develop solutions (banking case: FaceID, large buttons, local language).
- Eight HCI problems: complexity, poor feedback, inconsistency, accessibility gaps, compatibility, contextual neglect, high cognitive load, trust deficiency.
- Improve HCI with usability, accessibility, consistency, clear feedback, adaptability (responsive design), UCD and pilot tests, multimodal input, and continuous testing.
- **UI** is the visual components (buttons, menus, icons, fields, checkboxes, sliders); **UX** is how the whole experience feels. UI is what you see; UX is how it feels.
- Lo-Fi wireframes plan structure; Hi-Fi prototypes look real; **Figma** is a free browser tool; prototypes use Trigger (On Tap) and Action (navigate) before code.
- Evaluation (SUS, NPS, formative, summative, expert/heuristic reviews) checks needs; testing (usability, task-based, automated, A/B, compatibility, load, keyboard/screen-reader) checks behaviour under conditions.

Key terms

Term	Meaning	اردو
HCI	Human-Computer Interaction; designing technology that is easy, efficient and responsive to people. Also called CHI or MMI.	انسان اور کمپیوٹر کا باہمی تعامل
Haptics	Physical feedback you can feel, such as a vibration.	لمسی / ارتعاشی جواب
Traditional interaction	Using standard input/output such as mouse, keyboard, keypad or simple tap and swipe.	روایتی تعامل
Natural interaction	Interacting without mouse or keyboard, using voice, face or body gesture.	قدرتی تعامل
End user	A person who directly operates the system.	حتمی صارف
Stakeholder	A person or group with an interest in the system's outcome (manager, client).	فریق مفاد
GUI	Graphical User Interface using windows, icons and menus.	تصویری صارف انٹرفیس
CLI	Command-Line Interface using typed text commands.	کمانڈ لائن انٹرفیس
NUI	Natural User Interface using gestures, body movement or immersive environments (VR, Kinect).	قدرتی صارف انٹرفیس
System feedback	The computer's response that confirms or guides an action.	نظام کا جواب
User feedback	Input the user sends to the system (Submit click, star rating).	صارف کی رائے / ان پٹ
Accessibility	Making digital systems usable by all, including people with diverse abilities.	رسائی پذیری

Computer Systems (HCI)

75 marks • 1 hour 15 minutes • no notes • no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 16 and the recap. **Section A** — all 15 MCQs (1 mark).

Section B — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define • Explain • Example • Diagram • Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. HCI is also known as:
 - a. CPU and ALU
 - b. CHI or MMI
 - c. HTTP or HTML
 - d. GUI only
2. Which sensory channel tracks body movement in VR?
 - a. Sight
 - b. Hearing
 - c. Spatial
 - d. Voice
3. Unlocking a phone with FaceID is an example of:
 - a. natural interaction
 - b. command-based interaction only
 - c. traditional interaction
 - d. CLI
4. Which domain of HCI includes patient portals and telemedicine?
 - a. Banking
 - b. Education
 - c. Networking
 - d. Health care
5. A bank manager who never uses the ATM but cares that it works is a:
 - a. stakeholder
 - b. end user
 - c. haptic device
 - d. wireframe
6. Typing `dir` in MS-DOS is:
 - a. menu-driven
 - b. command-based
 - c. context-aware
 - d. biometric
7. A "Message Sent!" tick mark is:
 - a. user feedback
 - b. a stakeholder
 - c. need analysis
 - d. system feedback
8. Unclear buttons on a medical device mainly show that poor HCI:
 - a. only affects game apps
 - b. is a colour preference
 - c. causes confusion and risk
 - d. improves load testing
9. Not depending only on colour, but adding a "STOP" label, is:
 - a. colour-blind friendly design
 - b. load testing
 - c. CLI design
 - d. A/B testing
10. Need analysis for a UI should be done:
 - a. after the product is sold
 - b. before designing the UI
 - c. only by programmers
 - d. instead of testing
11. An online store that asks for a credit card but shows no HTTPS lock has:
 - a. high contrast
 - b. natural interaction
 - c. summative evaluation
 - d. trust deficiency

L2. "UI is what you see; UX is how it feels" means:

- a. UI and UX are identical
- b. UX is only the logo colour
- c. UI is code and UX is hardware
- d. UI is visual elements; UX is the overall experience

L3. A Lo-Fi wireframe should focus on:

- a. final photographs and brand colours
- b. structure and flow using boxes and lines
- c. server load of 10,000 users
- d. writing the finished Python code

L4. The System Usability Scale (SUS) is:

- a. a 10-item questionnaire that scores usability
- b. a bot that finds broken links
- c. a type of ATM keypad
- d. a Figma trigger

L5. In A/B testing:

- a. every user sees both versions at once and votes for the prettier one
- b. only experts review heuristics
- c. half the users see A, half see B, and the version with more clicks or sign-ups wins
- d. the server is crashed on purpose

Section B — Short questions (10 × 3 = 30)

1. Define HCI. Give two other names for it and list the five sensory channels.
2. Differentiate traditional interaction from natural interaction with one example of each from daily Pakistani use.
3. State four domains of HCI. For each, give one application and one user benefit.
4. Name the four primary HCI components. Distinguish end user from stakeholder, and list the three characteristics of a task.
5. Define GUI, CLI, VUI and NUI, with one example of each.
6. Write five implications of the importance of HCI.
7. List the five accessibility principles with one example each.
8. What is need analysis? Write its five steps and three findings from the mobile-banking case study.
9. Differentiate UI from UX using the food-delivery example. Name six UI components.
10. What is A/B testing? How is it different from an automated audit?

Section C — Long questions (attempt any 3 × 10 = 30)

1. Explain the components of HCI (user, computer system, user interaction, task, interface types, environment, feedback). Illustrate every part with a labelled walk-through of a person withdrawing cash from an outdoor ATM in Hyderabad.
2. Describe eight HCI problems with examples. Then match each problem to a method of improving HCI. Use JazzCash or a school portal wherever it makes the example clearer.
3. "UI is what you see; UX is how it feels." Explain UI design, its six components, and UX. Then describe Lo-Fi wireframes, Hi-Fi prototypes, the steps of making a low-fidelity design in Figma, and how a Figma prototype uses a trigger and an action. Sketch a Lo-Fi school-portal login.
4. Differentiate testing from evaluation. Explain SUS, NPS, formative evaluation, summative evaluation and expert reviews. Then explain usability testing, task-based testing (including the three measurements), automated audits, A/B testing, compatibility testing, performance/load testing, and keyboard/screen-reader walkthroughs. Apply three of these methods to a college portal on result day.
5. A team is designing a JazzCash-style "Send Money" screen for elderly users in Sukkur who speak Sindhi, stand in bright sunlight, and have never used a CLI. Carry out a need analysis (five steps), list accessibility principles you will apply, choose interaction types, and say which evaluation and testing methods you will use before launch and why.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

1. **1.1 Fundamentals of Human-Computer Interaction.** Answers: 1. CHI (Computer-Human Interface) and MMI (Man-Machine Interaction). 2. Spatial. 3. Touch / haptics.
2. **1.1.1 Traditional Interaction and 1.1.2 Natural Interaction.** Answers: 1. Traditional. 2. "Alexa, play a song" (or any spoken command). 3. Because typing a PIN is traditional, while FaceID or a voice assistant on the same phone is natural — it depends on the method, not the device.
3. **1.2 Applications of HCI (Domains of Life).** Answers: 1. Health care, banking, education, networking and communication. 2. Quick transactions and secure financial management. 3. Education: LMS or online exam portal. Networking: social media, WhatsApp or Zoom.
4. **1.3 Components of HCI.** Answers: 1. End users directly operate the system; stakeholders have an interest in the outcome (managers, clients) but may not click the buttons. 2. Task complexity, user knowledge, time requirement. 3. The principal, IT admin or board office — they care about results even if students are the end users.
5. **Types of User Interaction.** Answers: 1. Command-based. 2. Context-aware. 3. Because it combines two or more types (voice + touch) in one task.
6. **Interface Types, Environment and Feedback.** Answers: 1. GUI, CLI, Touch, VUI, NUI. 2. Physical: ATM in sunlight. Social: a quiet classroom. 3. System feedback.
7. **1.4 Importance of HCI.** Answers: 1. Unclear buttons on medical devices. 2. Promotes inclusivity. 3. User-friendly products get higher adoption, loyalty and profits.
8. **1.5 Accessibility Principles.** Answers: 1. Colour-blind users may not see the meaning if there is no symbol or "STOP" text. 2. Inclusive navigation. 3. Large Calibri on a school website for homework instructions.
9. **1.6 Need Analysis for Interface Design.** Answers: 1. Before designing the UI. 2. Identify users; collect information; analyse needs; prioritise; develop solutions. 3. Fingerprint/FaceID login; large buttons and simple navigation for elderly users; English plus local languages.
10. **1.7 Human-Computer Interaction Problems.** Answers: 1. Trust deficiency. 2. High cognitive load — users must memorize too much. 3. Compatibility issues.
11. **1.8 Methods for Improving HCI.** Answers: 1. User-Centred Design; focus on real user goals and pilot-test. 2. Improve adaptability (responsive design). 3. A "Payment Successful" popup.
12. **1.9 User Interface Design (UI vs UX).** Answers: 1. Buttons, menus, icons, text fields, checkboxes/radio buttons, sliders. 2. The app loads fast, tracking works, food arrives without frustration. 3. how it feels.
13. **1.9.3–1.9.5 Wireframing, Figma and Prototypes.** Answers: 1. Colours and detailed graphics (it is structure only). 2. Directly in a web browser. 3. The user event that starts a move between screens, e.g. "On Tap".
14. **1.11 Test and Evaluate HCI (Evaluation Methods).** Answers: 1. Testing finds bugs / checks the product works; evaluation checks it meets users' needs (usability). 2. 10. 3. At the end of development, against the original goals.
15. **1.11.2 Testing Methods (Usability, A/B, Automated).** Answers: 1. Completion time, success rate, number of errors. 2. Half of the users (the other half see B). 3. Any two of: broken links, slow loading, low colour contrast.
16. **Career Opportunities in UI/UX.** Answers: 1. Usability researcher. 2. UI designer.

Answer key

Multiple choice

1. b
2. c
3. a
4. d
5. a
6. b
7. d
8. c
9. a
10. b
11. d
12. d
13. b
14. a
15. c

Short questions — model answers

1. HCI is the design of technology to serve people; systems that are easy to use, efficient and responsive. Also called CHI (Computer-Human Interface) and MMI (Man-Machine Interaction). Channels: sight, touch, hearing, voice, spatial.
2. Traditional uses standard I/O (mouse, keyboard, keypad, simple tap/swipe), e.g. an ATM keypad or typing on a school portal. Natural lets people interact without mouse or keyboard, using voice, face or gesture, e.g. FaceID or "Alexa, play a song".
3. Health care: patient portals / telemedicine — remote access to medical services. Banking: mobile banking and ATMs — quick, secure transactions. Education: LMS and exam portals — better teaching, learning and engagement. Networking: WhatsApp, Zoom, social media — global connection and collaboration.
4. User, computer system, user interaction, task. End users directly operate the system; stakeholders (managers, clients) have an interest in the outcome. Task characteristics: complexity, user knowledge, time requirement.
5. GUI: windows, icons, menus (Windows, Android). CLI: typed commands (MS-DOS, Linux). VUI: spoken commands (smart speakers). NUI: gestures, body, immersive VR/Kinect.
6. Enhance productivity; promote inclusivity; drive innovation (AR/VR, AI, IoT need solid HCI); economic impact (adoption, loyalty, profit); ethical responsibility (privacy, less bias, well-being).
7. High contrast (black text on white in a railway app); readable fonts (large Calibri on a school site); colour-blind friendly (STOP label, not colour alone); inclusive navigation (Tab key); multimodal detection (captions or vibration).
8. Need analysis finds the gap between the existing situation and the desired outcome, before UI design. Steps: identify users; collect information (interviews, questionnaires, observation); analyse needs; prioritise; develop solutions. Banking case: Fingerprint/FaceID login; large buttons and simple navigation for elderly users; English and local languages.
9. UI is the visual elements so people can interact easily; UX is the overall smoothness, comfort and satisfaction. Food app: UI = burger pictures and red buttons; UX = fast load, working tracking, food arrives without frustration. Components: buttons, menus, icons, text fields, checkboxes/radio buttons, sliders.
10. A/B testing shows version A to half the users and version B to the other half; the version with more clicks or sign-ups wins. An automated audit uses bots to scan for technical issues such as broken links, slow loading or low contrast; it does not split users between two designs.

Long questions — model answers

- 1. Components through an outdoor ATM.** User: end user = account holder; stakeholder = bank. Computer system: ATM hardware and bank software linking PIN input to cash output. Interaction: insert card, type PIN, choose Cash, confirm — intent becomes a response. Task: withdraw cash; low complexity, basic knowledge, about one minute (contrast with a long passport application). Interface: GUI on screen + keypad (traditional); possibly fingerprint (biometric). Environment: physical sunlight so contrast must be high; social queue so a privacy shield is needed; technical printer or network may fail. System feedback: "Please wait", cash, receipt/SMS. User feedback: pressing Confirm. If any part is weak (glare, no "cash coming" message), HCI fails even if the bank account is correct.
- 2. Problems and methods.** Interface complexity (buried checkout / hidden Send Money) → enhance usability (clear Buy Now / Send). Poor feedback (frozen Submit) → Payment Successful popup. Inconsistency (magnifying glass vs binoculars, or Send changing colour) → same Save/Send control everywhere. Accessibility gaps (no captions) → strengthen accessibility. Compatibility (laptop-only portal) → responsive/adaptability. Contextual neglect (map with no night mode; ATM unreadable in sun) → design for environment. High cognitive load (three SMS codes) → simplify steps. Trust deficiency (no HTTPS lock on JazzCash-style payment) → show security cues. Also apply UCD with a pilot test, multimodal input (voice + touch for elderly users), and continuous testing after launch.
- 3. UI, UX, wireframe, Figma, prototype.** UI design organises visual elements. Six components: buttons (Submit/Cancel), menus, icons, text fields, checkboxes/radio, sliders. UX = overall experience; UI is what you see, UX is how it feels; food-delivery pictures vs fast delivery. Lo-Fi: black-and-white boxes for structure; Hi-Fi: real colour, type, images, clickable controls for final tests. Figma: sign up in the browser; Frame tool for a phone canvas; rectangles and circles; text labels such as Sign Up; duplicate frames for the next screen. Prototype: before code, Prototype tab, Trigger = On Tap, Action = Navigate to Home. Sketch: header "LOGO / Portal", dashed Username and Password boxes, a LOGIN rectangle, "Forgot password?" — the Lo-Fi login in this chapter.
- 4. Test vs evaluate, then methods.** Testing finds bugs / whether it works; evaluation checks whether it meets user needs. SUS: 10-item usability score. NPS: "recommend to a friend?" (loyalty). Formative: during development. Summative: at the end vs original goals. Expert reviews: specialists vs heuristics. Usability testing: watch real users on realistic tasks. Task-based: time, success rate, errors (e.g. Add to cart in 12 s, success yes). Automated audit: bots find broken links, slow load, low contrast. A/B: half/half, more clicks win. Compatibility: Chrome/Safari, phone/tablet/PC, OS. Load: 10,000 logins at once. Keyboard/screen-reader: Tab/Enter and assistive tech. Result-day portal: load-test the 9:00 a.m. rush; usability-test "find chemistry marks"; automated audit for broken result links and grey-on-grey contrast; optional A/B of two home-screen layouts.
- 5. Send Money for elderly users in Sukkur.** Need analysis: (1) users = elderly Sindhi speakers, not teenagers; (2) collect: interviews and watch them at a JazzCash shop agent; (3) analyse: fear of wrong number, cannot read small English, glare on the phone; (4) prioritise: huge Sindhi "رقم بھیجیں", amount in words, confirm screen, high contrast; (5) solution: that UI, not a CLI. Accessibility: high contrast for sunlight, large simple fonts, not colour-only status, Tab/large targets, vibration + spoken confirm (multimodal). Interaction: menu-driven + form fill + biometric + haptic; optional voice. Evaluate formatively on paper then in Figma; expert review against heuristics; SUS and NPS before launch. Test: usability and task-based ("send Rs 100") measuring time/success/errors; A/B two button sizes; compatibility on cheap Androids; keyboard if a kiosk is used; do not skip a confirm screen — trust and feedback are the main risks.

Self-assessment: I can...

- ☐ define HCI, CHI and MMI and name the five sensory channels.
- ☐ describe HCI in health, banking, education and networking.
- ☐ name the types of user interaction and give an example of each.
- ☐ apply the five accessibility principles and carry out a need analysis.
- ☐ differentiate UI from UX and list six UI components.
- ☐ choose evaluation methods (SUS, NPS, formative, summative, expert).
- ☐ tell traditional interaction from natural interaction with local examples.
- ☐ label user, computer system, interaction, task, UI type, environment and feedback on an ATM, JazzCash or portal.
- ☐ explain why HCI is important using the five implications.
- ☐ name eight HCI problems and the methods that fix them.
- ☐ compare Lo-Fi, Hi-Fi, Figma steps and prototype triggers/actions.
- ☐ explain usability, task-based, automated, A/B, compatibility, load and keyboard tests.

Computational Thinking & Algorithms

Class XI taught you how to write algorithms. This chapter teaches you how to **judge** them: is the algorithm correct, clear and efficient? You will then learn the main **data structures** — array, linked list, stack, queue, tree and graph — so you can store data the smart way and trace how it is retrieved.

گیارہویں جماعت میں آپ نے الگورتھم لکھنا سیکھا۔ اس باب میں آپ سیکھیں گے کہ الگورتھم درست، واضح اور تیز ہے یا نہیں، اور ایرے، لنکڈ لسٹ، سٹیک، کیو، ٹری اور گراف جیسے ڈیٹا سٹرکچرز میں ڈیٹا کیسے رکھا اور نکالا جاتا ہے۔

What you will learn

- Define **correctness** and prove it with a complete **trace table**.
- Evaluate **clarity** using modularity (SRP, coupling, abstraction) and readability (names, flow, consistency).
- Explain how the number of **conditions** and **repetitions** changes efficiency, and apply the three-question efficiency framework.
- Define a **data structure** and classify it as linear or non-linear.
- Draw a tree and a graph, and name the five operations on data structures.
- Apply **stepwise reasoning** and compare it with a trace table on at least four points.
- Define **efficiency** in time and space, and state Big O for $O(1)$, $O(\log n)$, $O(n)$, $O(n \log n)$ and $O(n^2)$ with examples.
- Refine an algorithm for clearer names, modules, comments and fewer wasted steps.
- Draw and trace an array, linked list, stack (PUSH/POP) and queue (ENQUEUE/DEQUEUE).
- Choose a data structure for a real scenario and trace retrieval in an array, a linked list and a queue.

GOLDEN CONCEPTS

★ **Golden concepts in this chapter.** These ideas are taught first as lecture notes. If time is short, lock these before the other notes, then sit the chapter exam.

- ★ **2.1.1 Trace Tables.** A trace table is a technique used to monitor how the values of variables change during the execution of an algorithm.
- ★ **2.1.3 Comparing Trace Tables and Stepwise Reasoning.** Both methods verify correctness, but they fit different situations depending on the complexity and length of the algorithm.
- ★ **2.3.1 Number of Steps (Big O Notation).** When we discuss efficiency we ask how performance changes as the input size n increases.
- ★ **2.5 Concept of Data Structure.** A data structure is a systematic way of organising, storing and managing data so that an algorithm can access, modify and process it efficiently.
- ★ **Linear Data Structures: Stack.** A stack is a linear data structure that works on the LIFO principle: Last-In, First-Out.
- ★ **Linear Data Structures: Queue.** A queue organises data on the FIFO principle: First-In, First-Out.

اس باب کے گولڈن تصورات پہلے پڑھیں۔ باقی نوٹس بعد میں۔

STUDENT · COACH

Self-taught. 24 notes · 6 ★ first · about 8 h.
After the last note, sit the chapter exam (75 marks, 1 h 15 min).

Coach / teacher. 15 academy classes of 90 minutes (each ★ Golden is a full class; other notes pair). School: ★ = one 40-minute period.

ACADEMY CALENDAR**Chapter 2 academy calendar.**

Class	Topics	Kind
Class 01	Trace Tables	★ 90 min
Class 02	Comparing Trace Tables and Stepwise Reasoning	★ 90 min
Class 03	Number of Steps (Big O Notation)	★ 90 min
Class 04	Concept of Data Structure	★ 90 min
Class 05	Linear Data Structures: Stack	★ 90 min
Class 06	Linear Data Structures: Queue	★ 90 min
Class 07	Analyze algorithms for correctness + Stepwise Reasoning	90 min
Class 08	Evaluating the Clarity of an Algorithm + Modularity	90 min
Class 09	Readability + Assess Algorithm Efficiency	90 min
Class 10	Number of Conditions + Number of Repetitions	90 min
Class 11	The Efficiency Evaluation Framework + Refinements to improve clarity and efficiency	90 min
Class 12	Linear Data Structures: Array + Linear Data Structures: Linked List	90 min
Class 13	Non-Linear Data Structures: Tree + Non-Linear Data Structures: Graph	90 min
Class 14	Operations on Data Structures + Identify data structures in problem scenarios	90 min
Class 15	Trace data retrieval in Array, List and Queue + Career Opportunities in Algorithms	90 min

2.1.1 Trace Tables ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 01 of 15 · 90 min · full Golden class. Board: A trace table is a technique used to monitor how the values of variables change during the execution of an algorithm..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **trace table** is a technique used to monitor how the values of variables change during the execution of an algorithm. It is a **paper execution** of the code — a manual walkthrough, also called a **dry run**. You act as the computer and fill in one row after another.

Purpose of trace tables

- **Dry running:** execute the algorithm line by line by hand.
- **Debugging:** find logical errors where the algorithm runs but the output is wrong.
- **Validation:** check that the algorithm does what it is intended to do.

Components of a trace table

- **Line / step number** — which line is being executed.
- **Variables** — one column for every variable.
- **Input / output** — user inputs and printed results.
- **Condition check** — True/False for IF, WHILE, FOR, and similar tests.

WORKED EXAMPLE

Worked example: soldiers who meet the height rule. To qualify for training, a soldier's height must be between **1.57 and 1.91 metres, inclusive**.

Inputs: all soldiers' heights. Output: the count of eligible soldiers.

Step 1: Start

Step 2: SET Total = 0

Step 3: Set AllHeights = [1.91, 2.01, 1.87, 1.57, 1.48]

Step 4: FOR EACH height FROM AllHeights DO

Step 5: IF height $\geq$ 1.57 AND height $\leq$ 1.91 THEN

Step 6: SET Total = Total + 1

Step 7: END IF

Step 8: END FOR EACH

Step 9: Print Total

Step 10: End

Inclusive means the two boundary values **count**: 1.57 and 1.91 are eligible.

Step	Total	Height	AllHeights (input)	Height between 1.57 and 1.91?	Output
2	0				
3	0		1.91, 2.01, 1.87, 1.57, 1.48		
4	0	1.91			
5	0	1.91		True	
6	1	1.91			
4	1	2.01			
5	1	2.01		False (skip Step 6)	
4	1	1.87			
5	1	1.87		True	
6	2	1.87			
4	2	1.57			
5	2	1.57		True (boundary)	
6	3	1.57			
4	3	1.48			
5	3	1.48		False (skip Step 6)	
9	3				3

Eligible: 1.91, 1.87, 1.57. Not eligible: 2.01 (above 1.91) and 1.48 (below 1.57). Printed Total = **3**.

```
AllHeights = [1.91, 2.01, 1.87, 1.57, 1.48]
Total = 0
for height in AllHeights:
    if height  $\geq$  1.57 and height  $\leq$  1.91:
        Total = Total + 1
print(Total)
```

OUTPUT
3

REMEMBER IT

How to fill a trace table without getting lost. Write a new row every time a variable **changes** or a condition is **tested**. Copy unchanged values into the new row so you never guess. Circle the final output.

Mnemonic: **V-I-C-O** — **V**ariables, **I**nterface, **C**ondition, **O**utput. If a column is missing, the table is incomplete.

COMMON MISTAKE

Mistake 1: treating 1.57 or 1.91 as out of range. The words “inclusive” and the operators $\geq$ and $\leq$ mean the boundaries **are allowed**.

Mistake 2: updating Total on a False condition. If the IF is False, skip the SET line and leave Total unchanged.

Mistake 3: writing only the last Total. Examiners award marks for the **changing values in the table**, not only for the printed 3.

اردو میں سمجھیں

ٹریس ٹیبل الگورتھم کا کاغذی اجرا (Dry Run) ہے۔ ہر قطار میں لکیر نمبر، متغیرات کی نئی قیمتیں، ان پٹ/آؤٹ پٹ اور شرط کا نتیجہ (True/False) لکھا جاتا ہے۔ فوجیوں کی مثال میں قد 1.57 سے 1.91 میٹر تک ہونا چاہیے، حدود سمیت؛ پانچ قدوں میں سے تین اہل ہیں اس لیے آؤٹ پٹ 3 ہے۔

EXAM TIP

Very common long question: “Dry-run the given algorithm using a trace table and state the output.” Draw columns for **every** variable plus a condition column. Show the loop once per item. Boundary values ($\geq$, $\leq$, empty list) are favourite traps. Short questions ask: purpose of a trace table (dry run / debug / validate) and its components (line, variables, I/O, condition).

CHECK YOURSELF

1. List the four usual columns / components of a trace table.
2. In the soldier example, why is height 1.57 counted but 1.48 not counted?
3. What is printed, and how many times is Step 6 executed?

Write your answers in your notebook. The key follows this chapter's exam.

2.1.3 Comparing Trace Tables and Stepwise Reasoning

★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 02 of 15 · 90 min · full Golden class. Board: Both methods verify correctness, but they fit different situations depending on the complexity and length of the algorithm..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Both methods verify correctness, but they fit different situations depending on the **complexity and length** of the algorithm.

Feature	Trace table	Stepwise reasoning
Best for	Small algorithm blocks, complex loops, and beginners learning to track variables.	Large systems, architectural logic, and abstract mathematical proofs.
Effort required	High. Very tedious and impractical if a loop runs 1,000 times.	Moderate. Needs strong logical deduction and abstract thinking.
Primary goal	Catching syntax misinterpretations or specific arithmetic errors line by line.	Catching conceptual or structural flaws in the overall design.
Level	Micro-level (line by line). Checks exact values.	Macro-level (logic blocks). Checks overall state.

Trace table

Micro-level
Line by line
Exact values

Stepwise reasoning

Macro-level
Logic blocks
Overall state

Trace tables zoom in on values; stepwise reasoning zooms out on design.

WORKED EXAMPLE

Worked example: which method would you pick?

1. **A 12-line loop that adds five heights.** Use a **trace table**. The loop is short, you are a beginner, and you need the exact Total.
2. **A billing system with 40 functions.** Use **stepwise reasoning**. You cannot fill 10,000 rows. You check each module's start state, end state and edge cases.
3. **A loop from $i = 1$ to 1,000 that should produce $\text{Sum} = 500500$.** Do **not** write 1,000 rows. Argue: "Sum starts at 0; each i is added once; final $\text{Sum} = n(n+1)/2 = 1000 \times 1001/2 = 500500$." That is stepwise reasoning. Then dry-run a tiny N (say 5) with a trace table if you want extra confidence.

REMEMBER IT

Micro vs macro. Trace table = microscope (every cell). Stepwise reasoning = map (whole city). Beginners start with the microscope; designers need the map.

COMMON MISTAKE

Mistake: saying one method is "better" in every question.

Fix: they have different jobs. For a short dry-run in the exam, draw the table. For "explain why the algorithm is correct for any N ", write stepwise reasoning.

اردو میں سمجھیں

ٹریس ٹیبل خرد بینی (Micro) سطح پر کام کرتا ہے: ہر لائن اور ہر قیمت۔ مرحلہ وار استدلال بڑی (Macro) سطح پر ڈیزائن اور حالت چیک کرتا ہے۔ چھوٹے لوپ اور مبتدیوں کے لیے ٹیبل بہتر ہے؛ ہزار بار چلنے والے لوپ یا بڑے سسٹم کے لیے استدلال بہتر ہے۔

EXAM TIP

Differentiate questions are almost guaranteed: "Compare a trace table with stepwise reasoning." Write a **four-row table** (best for, effort, primary goal, micro/macro). Add one sentence of advice: table for small loops and exact values; reasoning for large systems and proofs. Do not write "trace table is always better".

CHECK YOURSELF

1. Which method is micro-level and checks exact values?
2. Why is a trace table a poor choice if a loop runs 1,000 times?
3. Which method is better for catching a structural flaw in a large design?

Write your answers in your notebook. The key follows this chapter's exam.

2.3.1 Number of Steps (Big O Notation) ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 03 of 15 · 90 min · full Golden class. Board: When we discuss efficiency we ask how performance changes as the input size n increases..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

When we discuss efficiency we ask how performance changes as the **input size n** increases.

Big O notation is a mathematical method used to describe how the running time (or memory) **grows** as n grows. We ignore small constants and keep the most important term: if an algorithm does $3n + 5$ steps we write $O(n)$.

In computer science, **log n** almost always means log base 2 (how many times you can halve n until you reach 1).

Five common classes

Class	Name	What happens when n grows	Typical example	Grade
$O(1)$	Constant	Time stays the same for 10 items or 10 million.	Access <code>arr[0]</code> (or any known index).	Excellent
$O(\log n)$	Logarithmic	Time grows very slowly; the problem is halved each step.	Binary search on a sorted list.	Great
$O(n)$	Linear	If n doubles, time roughly doubles.	Linear search of an unsorted list.	Fair / Good
$O(n \log n)$	Linearithmic	A little worse than linear; much better than n^2 . Common in good sorting.	Merge Sort (split in half, then merge).	Good
$O(n^2)$	Quadratic	Time grows with the square of n . Nested loops. Painful for large n .	Bubble Sort; compare every item with every other item.	Poor


The source stresses $O(1)$, $O(\log n)$, $O(n)$ and $O(n^2)$. $O(n \log n)$ is the class of efficient general-purpose sorts, so you should recognise it when a question says “better than Bubble Sort but more than linear”.

Growth table (log is $\log_2$)

Each cell is the approximate number of operations for that n . Read down a column to see how fast that class explodes.

n	$O(1)$	$O(\log n)$	$O(n)$	$O(n \log n)$	$O(n^2)$
2	1	1	2	2	4
4	1	2	4	8	16
8	1	3	8	24	64
16	1	4	16	64	256
32	1	5	32	160	1,024
1,024	1	10	1,024	10,240	1,048,576
1,000,000	1	~20	1,000,000	~20,000,000	1,000,000,000,000

From $n = 8$ to $n = 1,000,000$, $O(1)$ does not move, $O(\log n)$ only goes from 3 to about 20, $O(n)$ becomes a million, and $O(n^2)$ becomes a million million — which is why nested loops “fail for large datasets”.



Same $n = 16$. Quadratic work is already four times $n \log n$ and sixteen times linear.

Worked example A — $O(1)$: first element of an array. Whether the array holds 10 or 10 million values, `arr[0]` is one jump to a known address. `arr = [23, 76, 12, 90, 34, 68]` `print(arr[0])` 23
 Worked example B — $O(n)$: linear search. Each extra item adds one extra check. `def linear_search(items, key): for i, value in enumerate(items): if value == key: return i return -1`
`print(linear_search([10, 50, 20, 70, 90, 30], 20))` print(`linear_search([10, 50, 20, 70, 90, 30], 99)`) 2 -1
 Worked example C — $O(\log n)$: binary search on a sorted list. Each step throws away half of the remaining items. For 8 sorted numbers the worst case is about 4 comparisons ($\text{floor}(\log_2 8) + 1$). `def binary_search(arr, key): low = 0 high = len(arr) - 1 steps = 0 while low <= high: mid =`

`(low + high) // 2 steps = steps + 1 if arr[mid] == key: return mid, steps if arr[mid] < key: low = mid + 1 else: high = mid - 1`
`return -1, steps` `data = [3, 8, 12, 17, 23, 31, 40, 52]` `print(binary_search(data, 40))` print(`binary_search(data, 3)`) (6, 3) (0, 3)
 Key 40 is found at index 6 after 3 comparisons. Key 3 is found at index 0 after 3 comparisons. Never more than a handful of steps, even if the list later grows to a million (about 20 steps).
 Worked example D — $O(n \log n)$: Merge Sort idea. To sort 8 items, Merge Sort makes $\log_2 8 = 3$ split-levels, and each level walks all 8 items once, so work $\approx 8 \times 3 = 24$, which matches the growth table. Bubble Sort on 8 items is on the order of $8^2 = 64$ comparisons. That gap becomes enormous at $n = 1,000,000$.
 Worked example E — $O(n^2)$: nested loops. `n = 4 count = 0 for i in range(n): for j in range(n): count = count + 1 print(count)` 16 Inner body runs $n \times n = 16$ times. That is the pattern of Bubble Sort and of “compare every item with every other item”.

REMEMBER IT

Order from fastest to slowest (for large n): $O(1) \rightarrow O(\log n) \rightarrow O(n) \rightarrow O(n \log n) \rightarrow O(n^2)$

Mnemonic: **"Constant Logs Never Need Squares"** — Constant, Logarithmic, N, N-log-N, Squares.

COMMON MISTAKE

Mistake 1: writing $O(n)$ for binary search because "there is a loop". The loop runs about $\log n$ times, not n times.

Mistake 2: writing $O(2n)$ or $O(n+5)$. Big O drops constants: both are $O(n)$.

Mistake 3: using binary search on an **unsorted** list. Binary search is $O(\log n)$ only on sorted data.

اردو میں سمجھیں

بگ او (Big O) بتاتا ہے کہ ان پٹ n بڑھنے پر وقت یا میموری کیسے بڑھتی ہے۔ $O(1)$ مستقل (ایرے کا $arr[0]$ ، $O(\log n)$ ہر قدم پر آدھا (بائنری سرچ)، $O(n)$ لکیری (لینیئر سرچ)، $O(n \log n)$ اچھے سارٹ جیسے مرچ سارٹ، اور $O(n^2)$ مربع (بیل سارٹ، اندرونی لوپ)۔ n پر $O(n^2)$ ناقابل استعمال ہو جاتا ہے۔

EXAM TIP

Memorise the five rows of the class table (name, growth, one example, grade). Typical MCQ: "Accessing $arr[0]$ is ...?" $\rightarrow O(1)$. "Binary search is ...?" $\rightarrow O(\log n)$. "Nested loops / Bubble Sort ...?" $\rightarrow O(n^2)$. Long questions ask you to fill or interpret a growth table, or to say what happens if n becomes 10 times larger (linear $\rightarrow 10\times$ time; quadratic $\rightarrow 100\times$ time). Always mention that $\log n$ is "halving" and n^2 is "nested loops".

CHECK YOURSELF

1. Give one example each of $O(1)$, $O(\log n)$, $O(n)$ and $O(n^2)$.
2. From the growth table, how many operations does $O(n^2)$ need when $n = 32$?
3. Why is Merge Sort described as $O(n \log n)$?

Write your answers in your notebook. The key follows this chapter's exam.

2.5 Concept of Data Structure ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 04 of 15 · 90 min · full Golden class. Board: A data structure is a systematic way of organising, storing and managing data so that an algorithm can access, modify and process it efficiently..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT


A **data structure** is a systematic way of **organising, storing and managing** data so that an algorithm can access, modify and process it efficiently.

Real-life analogy. Books on a shelf are arranged in a set order, so you can find a title quickly. Files in folders are grouped on purpose. Data structures do the same job inside computer memory.

1. Linear data structures

Elements stand in a strict sequence, one after another. Each element (except the first and last) has exactly **one predecessor** and **one successor**.


Examples: Array, Linked List, Stack, Queue.



2. Non-linear data structures

Elements are connected in a hierarchy or a network. One element can connect to **several** others at the same time.

Examples: Tree, Graph.



Linear: a line of neighbours. Non-linear: a node with more than one connection.

WORKED EXAMPLE

Worked example: classify each everyday picture.

1. Students standing in a single assembly line → **linear** (each has one in front and one behind).
2. A family tree of grandparents, parents and children → **non-linear** (one parent, several children).
3. Roads linking Karachi, Hyderabad, Sukkur and Larkana in many ways → **non-linear** (a network).

REMEMBER IT

Ask: "Does each item have at most one next item?" Yes → linear. "Can one item link to many, or can links form a net?" → non-linear.

COMMON MISTAKE

Mistake: calling a tree "linear" because you can walk it from top to bottom.

Fix: walking is traversal. The **shape** is hierarchical: one parent, many children. That is non-linear.

اردو میں سمجھیں

ڈیٹا سٹرکچر ڈیٹا کو منظم طریقے سے رکھنے کا نظام ہے تاکہ الگورتھم اسے جلدی استعمال کر سکے۔ لکیری ڈھانچوں میں عناصر قطار میں ہوتے ہیں (ایرے، لنکڈ لسٹ، سٹیک، کیو)۔ غیر لکیری میں ایک عنصر کئی سے جڑ سکتا ہے (ٹری، گراف)۔ الماری کی کتابیں اور فولڈرز کی مثال یاد رکھیں۔

EXAM TIP

Define data structure in full (organise, store, manage; efficient access and processing). Then split linear vs non-linear with the "one predecessor and one successor" test, and list the four linear and two non-linear examples. The shelf / folder analogy earns a mark. MCQs: "Which is non-linear?" → Tree or Graph.

CHECK YOURSELF

1. Define data structure.
2. Name four linear and two non-linear examples.
3. What is true of each middle element in a linear structure?

Write your answers in your notebook. The key follows this chapter's exam.

Linear Data Structures: Stack ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 05 of 15 · 90 min · full Golden class. Board: A stack is a linear data structure that works on the LIFO principle: Last-In, First-Out..


Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **stack** is a linear data structure that works on the **LIFO** principle: **Last-In, First-Out**. The last element added is the first one removed. You cannot pull an item from the bottom or the middle.

- **PUSH** — add an item to the **top**.
- **POP** — remove the item from the **top**.

A **TOP** pointer always names the current top item. **Real-life example:** Undo in a text editor. Every action is piled on the stack; Undo POPs the most recent action first.



PUSH Data1, Data2, Data3 — first POP is Data3

Three PUSH operations. The TOP is Data 3, so the first POP returns Data 3.

WORKED EXAMPLE

Worked example: PUSH / POP trace. Start with an empty stack. Then PUSH Data1, PUSH Data2, PUSH Data3, POP, POP.

Step	Operation	Stack (bottom → top)	TOP	Popped value
0	(empty)	[]	none	
1	PUSH Data1	[Data1]	Data1	
2	PUSH Data2	[Data1, Data2]	Data2	
3	PUSH Data3	[Data1, Data2, Data3]	Data3	
4	POP	[Data1, Data2]	Data2	Data3
5	POP	[Data1]	Data1	Data2

```
stack = []
stack.append("Data1")
stack.append("Data2")
stack.append("Data3")
print("after 3 PUSHes:", stack)
print("POP:", stack.pop())
print("POP:", stack.pop())
print("left:", stack)
```

OUTPUT

```
after 3 PUSHes: ['Data1', 'Data2', 'Data3']
POP: Data3
POP: Data2
left: ['Data1']
```

Python's `list.append` is PUSH and `list.pop()` (no index) is POP from the top.

REMEMBER IT

LIFO = Last In First Out = "last plate washed is first plate used" on a canteen pile. Undo, Redo, Back button and function calls are all stacks.

COMMON MISTAKE

Mistake: POPing from the bottom, or mixing LIFO with FIFO.

Fix: stack = plates (top only). Queue = ticket line (front leaves, rear joins). If the first POP is Data1, you drew a queue, not a stack.

سٹیک LIFO پر چلتا ہے: جو سب سے بعد میں آیا وہ سب سے پہلے نکلے گا۔ اوپر رکھنا PUSH، اوپر سے ہٹانا POP، اور TOP پوائنٹر موجودہ سب سے اوپر عنصر بتاتا ہے۔ انڈو (Undo) کی مثال: ہر عمل ڈھیر پر پڑتا ہے، انڈو سب سے تازہ عمل ہٹاتا ہے۔

EXAM TIP

Define stack + LIFO, define PUSH and POP, mention TOP, give the Undo example, and draw the vertical boxes with TOP labelled. Trace questions: "Show the stack after PUSH A, PUSH B, POP, PUSH C." Work left to right; the first POP must be B. Never remove from the middle.

CHECK YOURSELF

1. Expand LIFO.
2. After PUSH Data1, Data2, Data3, what does the first POP return?
3. Why is Undo modelled as a stack?

Write your answers in your notebook. The key follows this chapter's exam.

Linear Data Structures: Queue ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 06 of 15 · 90 min · full Golden class. Board: A queue organises data on the FIFO principle: First-In, First-Out..


Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **queue** organises data on the **FIFO** principle: **First-In, First-Out**. Whoever arrives first is served first. Order truly matters.

- **ENQUEUE** — add an element at the **Rear** (back).
- **DEQUEUE** — remove an element from the **Front**.

Real-life example: several documents sent to a printer. The printer prints the first document received, then the next.



Next ENQUEUE joins after 90. Next DEQUEUE removes 55.

Three jobs waiting. New jobs join at the rear; service always takes the front.

WORKED EXAMPLE

Worked example: ENQUEUE / DEQUEUE trace. Start empty. ENQUEUE 55, 76, 90, then ENQUEUE D, then DEQUEUE.

Step	Operation	Queue (Front → Rear)	Front	Rear	Removed
0	(empty)	[]	—	—	
1	ENQUEUE 55	[55]	55	55	
2	ENQUEUE 76	[55, 76]	55	76	
3	ENQUEUE 90	[55, 76, 90]	55	90	
4	ENQUEUE D	[55, 76, 90, D]	55	D	
5	DEQUEUE	[76, 90, D]	76	D	55

```
from collections import deque
q = deque()
q.append(55)
q.append(76)
q.append(90)
q.append("D")
print("after ENQUEUE D:", list(q))
print("DEQUEUE:", q.popleft())
print("left:", list(q))
```

OUTPUT

```
after ENQUEUE D: [55, 76, 90, 'D']
DEQUEUE: 55
left: [76, 90, 'D']
```

`append` is ENQUEUE at the rear; `popleft` is DEQUEUE from the front. The first DEQUEUE is 55 (the oldest), never D.

REMEMBER IT

FIFO = First In First Out = a canteen line. Front = the person being served. Rear = the person who just joined.

COMMON MISTAKE

Mistake: DEQUEUEing from the rear, or ENQUEUEing at the front.

Fix: new items only at Rear; removal only at Front. If your first removal is D, you treated the queue as a stack.

کیو FIFO پر چلتی ہے: جو پہلے آیا وہ پہلے نکلے۔ پیچھے (Rear) شامل کرنا ENQUEUE، آگے (Front) سے ہٹانا DEQUEUE ہے۔ پرنٹر کی قطار: جو فائل پہلے بھیجی گئی وہ پہلے چھپے گی۔ پہلی DEQUEUE ہمیشہ سب سے پرانا عنصر نکالتی ہے۔

EXAM TIP

Define queue + FIFO, define ENQUEUE (rear) and DEQUEUE (front), give the printer example, draw the labelled Front/Rear diagram, and trace a short sequence. Examiners mix stack and queue on the same paper: if they say "first come, first served" write Queue; if they say "Undo" write Stack.

CHECK YOURSELF

1. Expand FIFO. Where is an item added, and where is it removed?
2. After ENQUEUE 55, 76, 90, what does DEQUEUE return?
3. Why is a printer a queue, not a stack?

Write your answers in your notebook. The key follows this chapter's exam.

2.1 Analyze algorithms for correctness

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 07 of 15 · 45 min · first half · with Stepwise Reasoning. Board: An algorithm is correct if its output matches the expected results for a given input..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

An algorithm is **correct** if its **output matches the expected results** for a given input. Analysing correctness means showing that the algorithm produces the intended output for **all valid inputs**, not just one lucky example.

Two methods are used in this course:

Trace tables → paper execution, line by line → Stepwise reasoning → logic blocks, overall state

You already met the idea of a dry run in Class XI. Here you learn to do it formally, and to choose the method that fits the size of the algorithm.

WORKED EXAMPLE

Worked example: what “correct” means. An algorithm is supposed to count how many of the heights 1.91, 2.01, 1.87, 1.57, 1.48 lie between 1.57 m and 1.91 m inclusive.

Expected output: **3** (1.91, 1.87 and 1.57 qualify; 2.01 is too tall; 1.48 is too short).

If a program prints 4, it **runs** but it is **not correct**. Correctness is about the right answer, not about “no crash”.

REMEMBER IT

Remember: **runs ≠ correct**. A logical error still produces output — just the wrong output. That is why we analyse correctness on paper before we trust the code.

COMMON MISTAKE

Mistake: testing only one “normal” input and calling the algorithm correct.

Fix: also try edge cases (empty list, $N = 0$, the exact boundary values 1.57 and 1.91). The definition says **all valid inputs**.

اردو میں سمجھیں

الگورتھم تب درست (Correct) سمجھا جاتا ہے جب دیے گئے ان پٹ پر اس کا آؤٹ پٹ وہی ہو جو ہونا چاہیے۔ صرف چل جانا کافی نہیں؛ منطقی غلطی سے غلط جواب بھی نکل سکتا ہے۔ درستگی جانچنے کے دو طریقے ہیں: ٹریس ٹیبل (Trace Table) اور مرحلہ وار استدلال (Stepwise Reasoning)۔

CHECK YOURSELF

1. When is an algorithm considered correct?
2. Name the two methods used to analyse correctness in this chapter.
3. Why is “the program ran without an error” not enough?

Write your answers in your notebook. The key follows this chapter’s exam.

2.1.2 Stepwise Reasoning

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 07 of 15 · 45 min · second half · with Analyze algorithms for correctness. Board: Stepwise reasoning (also called logic verification) breaks an algorithm into logical sections and checks the state of the algorithm at each stage..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Stepwise reasoning (also called **logic verification**) breaks an algorithm into logical sections and checks the **state** of the algorithm at each stage. A **state** is a snapshot of what is true about the variables at that moment (for example, "Sum currently holds the total of the numbers seen so far").

You do **not** fill a row for every line. You think through the logic:

1. Analyse each step of the algorithm.
2. Check: does it **start in a valid state**?
3. Does it **handle all possible cases**?
4. Are the **conditions correct**?
5. If the loop is correct at the **start** of an iteration, does it remain correct at the **end**?

WORKED EXAMPLE

Worked example: sum of the numbers from 1 to N.

Step 1: Start
Step 2: Input N
Step 3: SET Sum = 0
Step 4: For i = 1 to N
Step 5: Sum = Sum + i
Step 6: END For
Step 7: Print Sum
Step 8: End

Stepwise reasoning breakdown

Check	What you verify
Initial state	Sum = 0 before the loop. Valid: nothing has been added yet.
Loop boundary	The loop runs exactly from i = 1 to i = N. No missing number, no extra number.
Iteration	Each i is added once: after k iterations, Sum = 1+2+...+k.
Final state	When the loop ends, Sum holds 1+2+...+N, which is the required total.
Edge case N = 0	The loop body never runs, Sum stays 0. Correct (the sum of no numbers is 0).
Check case N = 5	Sum becomes 15, which matches $5 \times 6 / 2 = 15$.

```
N = 5
Sum = 0
for i in range(1, N + 1):
    Sum = Sum + i
print(Sum)
```

OUTPUT
15

```
N = 0
Sum = 0
for i in range(1, N + 1):
    Sum = Sum + i
print(Sum)
```

OUTPUT
0

REMEMBER IT

Think of stepwise reasoning as a **teacher checking a proof**, not as a cashier counting coins one by one. You ask "is this block always true?" instead of "what is Sum when $i = 17$?"

COMMON MISTAKE

Mistake: rewriting the whole trace table and calling it stepwise reasoning.

Fix: write short comments about **state** (start, loop, finish, edges). If you listed every i from 1 to 1000, you used the wrong method.

اردو میں سمجھیں

مرحلہ وار استدلال میں الگورتھم کو منطقی حصوں میں توڑ کر ہر مرحلے پر اس کی حالت (State) دیکھی جاتی ہے: کیا شروع درست ہے، کیا تمام صورتیں سنبھلی ہیں، کیا شرط صحیح ہے، اور کیا لوپ کے ہر چکر کے بعد بھی نتیجہ درست رہتا ہے۔ ایک سے N تک جمع کی مثال میں Sum شروع میں 0 ہے، لوپ 1 سے N تک چلتا ہے، اور $N=0$ پر جواب 0 ہی رہتا ہے۔

CHECK YOURSELF

1. What other name is given to stepwise reasoning?
2. For the sum algorithm, why is $\text{Sum} = 0$ a valid start?
3. What happens when $N = 0$, and is that correct?

Write your answers in your notebook. The key follows this chapter's exam.

2.2 Evaluating the Clarity of an Algorithm

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 08 of 15 · 45 min · first half · with Modularity. Board: Clarity means an algorithm is easy to read, understand and modify..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Clarity means an algorithm is easy to **read, understand and modify**. In many cases, evaluating clarity is even more important than making the algorithm slightly faster. A clear algorithm is easier to **maintain, debug and extend** over time.

The two key aspects of clarity are:

Clarity → Modularity (parts) → Readability (text and flow)

WORKED EXAMPLE

Worked example: speed versus clarity. Algorithm A finds the class average in 8 confusing lines with variables a , b , c . Algorithm B uses two named functions and takes the same number of additions. Both are $O(n)$. Algorithm B is the better school solution because the next person (or you, in three months) can change it without breaking it.

REMEMBER IT

Ask two questions: **“Can I split this into parts?”** (modularity) and **“Can another student read it aloud and understand it?”** (readability).

COMMON MISTAKE

Mistake: treating a clever one-line trick as “better” than a clear five-line solution.

Fix: the source says clarity is often more important than speed. Board answers should praise meaningful names and modules, not compacted code.

اردو میں سمجھیں

وضاحت (Clarity) کا مطلب ہے الگورتھم پڑھنا، سمجھنا اور بدلنا آسان ہو۔ بہت سی صورتوں میں وضاحت رفتار سے بھی اہم ہے۔ اس کے دو حصے ہیں: ماڈیولریتی (Modularity) یعنی کام کو حصوں میں بانٹنا، اور پڑھائی پن (Readability) یعنی متن اور بہاؤ صاف ہونا۔

CHECK YOURSELF

1. What does clarity mean?
2. Name the two key aspects of clarity.
3. Why can clarity matter more than a small speed gain?

Write your answers in your notebook. The key follows this chapter's exam.

2.2.1 Modularity

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 08 of 15 · 45 min · second half · with Evaluating the Clarity of an Algorithm. Board: Modularity means breaking an algorithm into smaller, independent parts such as functions, classes or modules..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Modularity means breaking an algorithm into smaller, independent parts such as **functions, classes or modules**. This makes the algorithm more organised and easier to work with.

How to evaluate modularity

1. **Single Responsibility Principle (SRP).** Each module should focus on **one** specific task. If a function calculates a sum, prints a report and saves a file, it violates SRP.
2. **Coupling.** Modules should be reusable in different contexts. Good modularity means **loose coupling**: a change in one part does not smash the others. Tight coupling is when two functions share so many hidden details that you cannot reuse one without the other.
3. **Abstraction.** A well-designed algorithm hides complex implementation details. You can call a sorting function without knowing whether it uses Bubble Sort or Selection Sort inside.

WORKED EXAMPLE

Worked example: average of an array.

Poor modularity (monoblock)

All logic sits in one block, so you cannot reuse the sum.

Step 1: Start
Step 2: Set A = [1, 2, 3, 4, 5]
Step 3: Set n = 5
Step 4: Set total = 0
Step 5: Set avg = 0
Step 6: For I = 1 to n
Step 7: total = total + A[I]
Step 8: End For
Step 9: avg = total / n
Step 10: Print avg
Step 11: End

Good modularity (functions)

Two clear functions: CalculateSum() and FindAverage().

Step 1: Start
Step 2: Set A = [1, 2, 3, 4, 5]
Step 3: Set n = 5
Step 4: Print FindAverage(A, n)
Step 5: End

```
Function FindAverage(A, n)
    Sum = CalculateSum(A, n)
    Avg = Sum / n
    Return Avg
End Function
```

```
Function CalculateSum(A, n)
    Set Total = 0
    For I = 1 to n
        Total = Total + A[I]
    End For
    Return Total
End Function
```

SRP check: CalculateSum only adds; FindAverage only divides. Loose coupling: you can reuse CalculateSum to find a total without computing an average. Abstraction: the main algorithm just calls FindAverage and does not see the loop.

The source pseudocode numbers array positions from 1. Python numbers them from 0, so the loop is for i in range(n).

```
def calculate_sum(A, n):
    total = 0
    for i in range(n):
        total = total + A[i]
    return total

def find_average(A, n):
    return calculate_sum(A, n) / n

A = [1, 2, 3, 4, 5]
n = 5
print(find_average(A, n))
```

OUTPUT

3.0

REMEMBER IT

SRP in one line: **one function, one job**. If you cannot name the function with a short verb-phrase (`CalculateSum` , `FindAverage`), it is doing too much.

COMMON MISTAKE

Mistake: copying the 1-based loop `for I = 1 to n: total = total + A[I]` into Python. Then `A[1]` skips the first item and `A[5]` crashes.

Fix: in Python use `for i in range(n)` so the indices are 0, 1, 2, 3, 4.

اردو میں سمجھیں

ماڈیولریٹی کا مطلب الگورتھم کو آزاد حصوں (فنکشن، کلاس، ماڈیول) میں توڑنا ہے۔ جانچ کے تین اصول: واحد ذمہ داری (SRP) یعنی ایک فنکشن ایک کام؛ ڈھیلی جڑت (Loose Coupling) تاکہ ایک حصہ بدلنے سے دوسرے نہ ٹوٹیں؛ اور تجرید (Abstraction) یعنی اندرونی تفصیل چھپا کر صرف کام منگوانا، جیسے سورٹ فنکشن بلائے بغیر یہ جانے کہ ہیل ہے یا سلیکشن۔

CHECK YOURSELF

1. What does SRP say each module should do?
2. In the good average algorithm, which function hides the loop?
3. Why is the monoblock harder to reuse?

Write your answers in your notebook. The key follows this chapter's exam.

2.2.2 Readability

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 09 of 15 · 45 min · first half · with Assess Algorithm Efficiency. Board: Readability is how easily another person can understand the purpose and logic of an algorithm without running it..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Readability is how easily another person can understand the purpose and logic of an algorithm **without running it**. It is about how clear the text and the flow are.

How to evaluate readability

1. **Naming conventions** — consistent rules for names. Good names make an algorithm easier to search and understand.
Bad: $v = d / t$
Good: `velocity = distance / time`
2. **Self-documentation** — the algorithm explains itself, so you need fewer comments.
Meaningful names and clean formatting make the purpose obvious.
3. **Control-flow simplicity** — keep the logic straightforward. Avoid deep nesting (IF inside IF inside IF), limit extra conditions, and keep each function on one task.
4. **Consistency** — one style throughout: indentation, spacing, and casing (`camelCase` or `snake_case`). Then the logic stands out instead of the mess.

Names → Self-doc → Simple flow → Consistent

WORKED EXAMPLE

Worked example: the same formula, two styles.

```
# Hard to read
d = 100
t = 4
s = 20
v = d / t
if v > s:
    if t > 0:
        print(v)
```

OUTPUT
25.0

```
# Readable
distance = 100
time = 4
velocity = distance / time
speed_limit = 20
if time > 0 and velocity > speed_limit:
    print(velocity)
```

OUTPUT
25.0

The second version uses names, avoids an IF nested inside an IF, and keeps one consistent snake_case style. You can understand it without running it. Both print 25.0, but only the second is clear.

REMEMBER IT

Remember readability as **N-S-S-C**: **N**ames, **S**elf-documentation, **S**imple flow, **C**onsistency.

COMMON MISTAKE

Mistake: dumping a comment on every line (`total = total + 1 # add one to total`).

Fix: if the name already says it, skip the comment. Comments should explain **why**, not repeat **what**.

اردو میں سمجھیں

پڑھائی پن یہ ہے کہ دوسرا شخص الگورتھم چلائے بغیر اس کا مقصد سمجھ لے۔ اچھے نام (`velocity = distance / time`)، خود بیان (کم تبصرے)، سادہ کنٹرول فلو (گہری IF کے بغیر) اور ایک جیسا انداز (`casing` اور `indentation`) اسے آسان بناتے ہیں۔

CHECK YOURSELF

1. Rewrite `v = d / t` with readable names.
2. What is deep nesting, and why is it a readability problem?
3. Name two style habits that support consistency.

Write your answers in your notebook. The key follows this chapter's exam.

2.3 Assess Algorithm Efficiency

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 09 of 15 · 45 min · second half · with Readability. Board: Algorithm efficiency is measured in terms of time and space — how fast it runs and how much memory it uses..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Algorithm efficiency is measured in terms of **time** and **space** — how fast it runs and how much memory it uses.

The key considerations for assessing efficiency are:

1. **Number of steps** (described with **Big O notation**).
2. **Number of conditions** (IF decisions).
3. **Number of repetitions** (loops).

Time (speed) + Space (memory) → Efficiency

WORKED EXAMPLE

Worked example: two ways to find a name in 1,000,000 sorted records.

Linear search checks about 1,000,000 names in the worst case (time grows with n). Binary search checks about 20 names (it halves the list each time). Both can be correct and clear. They are not equally efficient.

REMEMBER IT

Efficiency is always “as the input grows”. An algorithm that feels instant on 10 items can freeze on 10 million items if it is $O(n^2)$.

COMMON MISTAKE

Mistake: judging efficiency by how short the code looks.

Fix: a five-line nested loop can do n^2 work. Count steps, conditions and repetitions — not lines of text.

اردو میں سمجھیں

کارکردگی (Efficiency) وقت (رفتار) اور جگہ (میموری) سے ناپی جاتی ہے۔ تین چیزیں دیکھی جاتی ہیں: قدموں کی تعداد (بگ او)، شرطوں کی تعداد، اور دہرائی (لوپ) کی تعداد۔ چھوٹے ان پٹ پر تیز لگنے والا الگورتھم بڑے ان پٹ پر سست پڑ سکتا ہے۔

CHECK YOURSELF

1. Efficiency is measured in terms of which two resources?
2. List the three key considerations named in the source.

Write your answers in your notebook. The key follows this chapter's exam.

2.3.2 Number of Conditions

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 10 of 15 · 45 min · first half · with Number of Repetitions. Board: Conditions (IF statements) are decision points..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Conditions (IF statements) are decision points. Every condition forces the CPU to evaluate True or False, so excessive branching reduces performance.

- **Computational cost.** Each IF is extra work, even if the rest of the algorithm is simple.
- **Nested conditions.** IF inside IF often means a brute-force approach. It hurts both readability and speed.
- **Short-circuiting** (the optimisation goal). Stop evaluating as soon as the result is known. In a logical AND, if the first part is False the second part is skipped. In a logical OR, if the first part is True the second part is skipped.

WORKED EXAMPLE

Worked example: cheap test first. You only divide if the denominator is not zero. Place the cheap, safe test on the left so Python never evaluates the dangerous part.

```
x = 0
y = 10
if x != 0 and (y / x) > 2:
    print("ratio is large")
else:
    print("skipped safely")
```

OUTPUT

skipped safely

$x \neq 0$ is False, so AND short-circuits and y / x is never attempted. If you wrote the division first, the program would crash. Same idea in the soldier algorithm: a False height test skips Step 6.

REMEMBER IT

Put the **cheapest / most likely False** test first in an AND, and the **most likely True** test first in an OR. That is short-circuiting used on purpose.

COMMON MISTAKE

Mistake: writing a chain of nested IFs when one compound condition would do (as in the velocity example in 2.2.2).

Fix: flatten with AND/OR, and rely on short-circuiting instead of extra layers.

اردو میں سمجھیں

IF پروسیسر سے True/False پوچھتی ہے اس لیے زیادہ شاخیں کارکردگی گھٹاتی ہیں۔ اندرونی IF اکثر brute-force ہوتی ہے۔ شارٹ سرکٹ (Short-circuit) کا مطلب ہے جیسے ہی جواب معلوم ہو جانچ روک دی جائے، مثلاً AND میں پہلی شرط False ہو تو دوسری نہ چلے۔

CHECK YOURSELF

1. Why do extra IF statements reduce performance?
2. What does nested IF often indicate?
3. In $x \neq 0$ and $(y / x) > 2$ with $x = 0$, why is there no division-by-zero?

Write your answers in your notebook. The key follows this chapter's exam.

2.3.3 Number of Repetitions

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 10 of 15 · 45 min · second half · with Number of Conditions. Board: Repetitions (loops) are the most significant factor in algorithm efficiency..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Repetitions (loops) are the most significant factor in algorithm efficiency. The **structure of the loop** decides how time grows with n .

Type of repetition	Conceptual impact	Efficiency grade
Linear loop	Processes each element exactly once. Time grows in proportion to size.	Good — $O(n)$
Logarithmic repetition	Reduces the problem size by half each iteration (binary search). Huge time savings.	Excellent — $O(\log n)$
Nested loops	For each element, process all other elements. Operations explode.	Poor — $O(n^2)$

WORKED EXAMPLE

Worked example: count the inner-body runs.

```
n = 5
linear = 0
for i in range(n):
    linear = linear + 1

nested = 0
for i in range(n):
    for j in range(n):
        nested = nested + 1

print(linear, nested)
```

OUTPUT

5 25

One loop: 5. Nested loops: $25 = 5^2$. For $n = 1,000$ that would be 1,000 versus 1,000,000.

REMEMBER IT

Find the **deepest loop**. One loop $\approx O(n)$. Loop inside a loop $\approx O(n^2)$. A loop that halves $n \approx O(\log n)$.

COMMON MISTAKE

Mistake: counting the word `for` and ignoring how the index moves.

Fix: a loop `while n > 1: n = n // 2` is logarithmic, even though it is still "a loop".

اردو میں سمجھیں

دہرائی (لوپ) کارکردگی کا سب سے بڑا عامل ہے۔ ایک بار ہر عنصر پر چلنے والا لوپ $O(n)$ (اچھا)، ہر بار مسئلہ آدھا کرنے والا $O(\log n)$ (بہترین)، اور اندرونی لوپ $O(n^2)$ (خراب) ہے۔ اندرونی جسم کے چلنے کی گنتی سے یہ فرق صاف نظر آتا ہے۔

CHECK YOURSELF

1. What grade does the source give nested loops?
2. Why is binary search's loop logarithmic rather than linear?
3. If $n = 5$, how many times does a fully nested n -by- n pair of loops run?

Write your answers in your notebook. The key follows this chapter's exam.

2.3.4 The Efficiency Evaluation Framework

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 11 of 15 · 45 min · first half · with Refinements to improve clarity and efficiency. Board: To evaluate an algorithm at a conceptual level, ask three questions: Does it scale?.

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

To evaluate an algorithm at a conceptual level, ask three questions:

1. **Does it scale?** If n grows 10 times, does time jump 10 times (linear) or 100 times (quadratic)? Quadratic scaling fails for large datasets.
2. **What is the bottleneck?** Focus on the most time-consuming section (usually the deepest loop) and try to improve that part.
3. **Is the cost worth it?** A theoretically faster $O(\log n)$ algorithm can be too complex to code and maintain. For a list of just 50 items, a simple $O(n)$ linear search is practically better because it is simple.

Does it scale?



Where is the bottleneck?



Is the extra complexity worth it?

WORKED EXAMPLE

Worked example: 50 names versus 1 million names.

Situation	Scale	Bottleneck	Worth the cost?	Choice
50 unsorted class names	Tiny n	A single linear scan	Binary search needs a sort first, which is extra work and extra code	Linear search $O(n)$
1,000,000 sorted account numbers, searched all day	$n \times 10$ compared with 100,000 is already huge; quadratic would be impossible	The search loop	Yes — binary search is standard and well understood	Binary search $O(\log n)$

REMEMBER IT

Framework mnemonic: **S-B-W** — **S**cale, **B**ottleneck, **W**orth it.

COMMON MISTAKE

Mistake: always choosing the theoretically fastest Big O.

Fix: question 3 exists for a reason. For $n = 50$, simple $O(n)$ beats a fragile $O(\log n)$ implementation.

اردو میں سمجھیں

کارکردگی کے تین سوال: کیا الگورتھم n پر چل سکتا ہے (Scale)؟ سب سے سست جگہ کون سی ہے (Bottleneck، عموماً گہرا لوپ)؟ کیا تیز تر طریقے کی پیچیدگی اس چھوٹے فائدے کے لائق ہے؟ پچاس ناموں کے لیے سادہ $O(n)$ تلاش عملی طور پر بہتر ہو سکتی ہے۔

CHECK YOURSELF

1. If n grows $10\times$, how much slower is a quadratic algorithm?
2. Where do you usually look for the bottleneck?
3. Why might linear search beat binary search for 50 items?

Write your answers in your notebook. The key follows this chapter's exam.

2.4 Refinements to improve clarity and efficiency

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 11 of 15 · 45 min · second half · with The Efficiency Evaluation Framework. Board: Improving an algorithm means reviewing it step by step: simplifying logic, removing redundant work, and picking smart data structures..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Improving an algorithm means reviewing it step by step: simplifying logic, removing redundant work, and picking smart data structures. A clear algorithm is easier to follow; an efficient one wastes fewer steps.

2.4.1 Refinements for clarity

1. **Use meaningful names.** Replace vague variables with descriptive ones. Bad: $a = b / c$.
Good: `average = totalSum / totalItems`.
2. **Break into modules.** Divide a massive block into functions, for example separating `CalculateSum()` from the printing logic.
3. **Improve structure and indentation.** Packed loops and IF statements confuse the reader. Spacing reduces mental effort.
4. **Add comments.** Keep them short. Explain **why** something is done, not just what is happening, especially for tricky logic.

2.4.2 Refinements for efficiency

1. **Reduce unnecessary steps.** In Bubble Sort, after the first pass the largest value has settled at the end. Ignore that sorted tail on the next pass by shrinking the inner loop, and you save comparisons.
2. **Use better algorithms.** Searching 1 million **sorted** records with Binary Search instead of Linear Search changes the time from seconds to milliseconds.
3. **Avoid re-computing values** (memoization / caching). If a value never changes, compute it once outside the loop, store it, and reuse it.
4. **Use appropriate data structures.** Direct access → array. Hierarchical data → tree. Do not force one structure everywhere.

WORKED EXAMPLE

Worked example 1 — shrinking Bubble Sort's inner loop ($n = 5$). A naive inner loop always runs $n-1 = 4$ times, for 4 passes: 16 comparisons. The refined inner loop runs 4, then 3, then 2, then 1: 10 comparisons.

```
n = 5
naive = 0
for i in range(n - 1):
    for j in range(n - 1):
        naive = naive + 1

refined = 0
for i in range(n - 1):
    for j in range(n - 1 - i):
        refined = refined + 1

print(naive, refined)
```

OUTPUT
16 10

Worked example 2 — do not re-compute a constant inside the loop.

```
A = 3
B = 4
N = 5

# BAD: C is recalculated every time
for i in range(1, N + 1):
    C = A + B
    print(C * i)
```

OUTPUT
7
14
21
28
35

```
A = 3
B = 4
N = 5
# GOOD: compute C once
C = A + B
for i in range(1, N + 1):
    print(C * i)
```

OUTPUT
7
14
21
28
35

Same output, fewer additions. That is caching: compute once, reuse N times.

REMEMBER IT

Clarity: **N-M-I-C** (Names, Modules, Indentation, Comments). Efficiency: **S-A-C-D** (Shrink steps, Algorithm choice, Cache, Data structure).

COMMON MISTAKE

Mistake: "optimising" by renaming variables and thinking that is an efficiency refinement.

Fix: meaningful names improve **clarity**. Efficiency refinements change the **amount of work** (fewer loop iterations, a better algorithm, no re-compute, a better structure).

اردو میں سمجھیں

وضاحت بہتر کرنے کے لیے معنی خیز نام، ماڈیول، درست indentation اور مختصر تبصرے استعمال کریں۔ کارکردگی کے لیے فضول قدم ہٹائیں (بل سارٹ میں ترتیب شدہ دم نظر انداز کریں)، بہتر الگورتھم چنیں (لینیئر کی جگہ بائنری سرچ)، لوپ کے اندر وہی حساب بار بار نہ کریں (Caching/Memoization)، اور مناسب ڈیٹا سٹرکچر رکھیں۔

CHECK YOURSELF

1. Rewrite $a = b / c$ with meaningful names for an average.
2. After Bubble Sort's first pass, what should the next pass ignore?
3. In the A+B example, where should $c = A + B$ be written?

Write your answers in your notebook. The key follows this chapter's exam.

2.5.1 Linear Data Structures: Array

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 12 of 15 · 45 min · first half · with Linear Data Structures: Linked List. Board: An array holds a collection of similar items (the same data type) placed next to each other in contiguous memory (one continuous block)..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

An **array** holds a collection of **similar items** (the same data type) placed next to each other in **contiguous memory** (one continuous block).

Each item has a position number called an **index**, usually starting from **0**. Because the address of any cell can be calculated from the index, you can jump straight to it. That is **direct access** (also called random access), and it is $O(1)$.

Array name: A

23	76	12	90	34	68
0	1	2	3	4	5

$A[3] = 90$ (index starts at 0)

Six integers in contiguous cells. Direct access: $A[3]$ jumps to 90 without walking 23, 76 and 12.

WORKED EXAMPLE

Worked example: read by index.

```
A = [23, 76, 12, 90, 34, 68]
print(A[3])
print(A[0])
```

OUTPUT

```
90
23
```

REMEMBER IT

Index 0 is the first shelf on the row. The third item that humans call "number 4" is index 3.
Formula in your head: **position from the left, minus one.**

COMMON MISTAKE

Limitation. Arrays are fast to read by index but **inflexible** to grow in the middle. Inserting a new value between 12 and 90 means shifting 90, 34 and 68 one cell to the right. That shift is $O(n)$, so arrays are a poor fit when you insert and delete in the middle all the time.

اردو میں سمجھیں

ایرے ایک جیسے عناصر کو میموری کے لگاتار بلاک میں رکھتا ہے۔ ہر عنصر کا انڈیکس (عموماً 0 سے) ہوتا ہے جس سے براہ راست رسائی $O(1)$ میں مل جاتی ہے، جیسے $A[3] = 90$ ۔ درمیان میں نیا عنصر ڈالنے کے لیے دائیں طرف شفٹ کرنا پڑتا ہے جو سست ہے۔

CHECK YOURSELF

1. What does "contiguous memory" mean?
2. In the diagram, what is $A[2]$?
3. Why is inserting in the middle of an array inefficient?

Write your answers in your notebook. The key follows this chapter's exam.

Linear Data Structures: Linked List

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 12 of 15 · 45 min · second half · with Linear Data Structures: Array. Board: A linked list stores data as a chain..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT


A **linked list** stores data as a chain. Unlike an array, the items are **not** one continuous block. Each separate piece is a **node** sitting somewhere in memory.

Each node has two parts:

1. the actual **data**;
2. a **link** (pointer) holding the memory address of the **next** node.

The first node is pointed to by **HEAD**. The last node's link is **NULL** (nowhere). To find an item you start at HEAD and follow links one by one — **sequential access**, $O(n)$.

Real-life example: browser history. Clicking Back follows the pointer to the previous page-node.



Follow HEAD → 23 → 76 → 12 → 90 → NULL

Four nodes. The last link is NULL, which ends the chain.

WORKED EXAMPLE

Worked example: walk from HEAD to print every data field.

```
nodes = [23, 76, 12, 90]
for data in nodes:
    print(data, end=" → ")
print("NULL")
```

OUTPUT

23 → 76 → 12 → 90 → NULL

There is no `nodes[2]` jump in a real linked list. The loop above models following each link once. Inserting a new node between 76 and 12 only means changing two pointers — you do not shift the rest of a big block, which is why lists beat arrays for frequent insert/delete.

REMEMBER IT

Array = row of lockers with numbers on the doors. Linked list = treasure hunt: each clue (link) tells you where the next box is.

COMMON MISTAKE

Mistake: writing `list[3]` and calling it linked-list access.

Fix: a true linked list has no index. Python's `list` type is an array-like structure. In this chapter, "linked list" means HEAD-and-pointers.

اردو میں سمجھیں

لنکڈ لسٹ زنجیر کی طرح نوڈز پر مشتمل ہے جو میموری میں بکھرے ہو سکتے ہیں۔ ہر نوڈ میں ڈیٹا اور اگلے نوڈ کا پتہ (Link) ہوتا ہے۔ پہلا نوڈ HEAD سے ملتا ہے، آخری کا لنک NULL ہوتا ہے۔ براؤزر کا Back بٹن پچھلے نوڈ کے پوائنٹر پر چلتا ہے۔ رسائی ترتیب وار ہے، انڈیکس سے چھلانگ نہیں۔

CHECK YOURSELF

1. Name the two parts of a node.
2. What does the last node's link store?
3. Why is browser history a fair analogy?

Write your answers in your notebook. The key follows this chapter's exam.

2.5.2 Non-Linear Data Structures: Tree

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 13 of 15 · 45 min · first half · with Non-Linear Data Structures: Graph. Board: A tree organises data in a hierarchy..


Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **tree** organises data in a **hierarchy**. Everything branches out from a single starting point called the **root**.

It creates a strict **one-to-many (parent-child)** relationship. That is an excellent way to show how roles flow in an organisation.

Real-life examples: a family tree (grandparents → parents → children) and folders inside folders on a drive.



College tree: one root (Principal), then parent-child branches. No child has two parents in this model.

WORKED EXAMPLE

Worked example: name the relationships.

- Root: Principal.
- Children of the root: Administrative Head, Academic Dean.
- Children of Academic Dean: HOD Math, HOD CS.
- HOD CS has one parent (Academic Dean), not two — that is the tree rule. If HOD CS also reported sideways to Accounts as an equal link, the picture would become a **graph**.

REMEMBER IT

Tree = family / folders / organogram. One root. Branches down. Parent-child, not a web of equals.

COMMON MISTAKE

Mistake: drawing a tree with two roots, or with an arrow going back up to the Principal from HOD CS (a cycle).

Fix: one root, links only parent → child, no loops. Cycles belong to graphs.

اردو میں سمجھیں

ٹری ڈیٹا کو درجہ بندی (Hierarchy) میں رکھتی ہے جو ایک جڑ (Root) سے پھوٹتی ہے۔ تعلق والدین-بچہ (ایک سے کئی) ہوتا ہے، جیسے پرنسپل → ڈین → ایچ او ڈی، خاندانی شجرہ، یا فولڈر کے اندر فولڈر۔ دو جڑیں یا چکر ٹری کو گراف بنا دیتے ہیں۔

CHECK YOURSELF

1. What is the starting node of a tree called?
2. What kind of relationship does a tree model?
3. Give two real-life tree examples from the source.

Write your answers in your notebook. The key follows this chapter's exam.

Non-Linear Data Structures: Graph

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 13 of 15 · 45 min · second half · with Non-Linear Data Structures: Tree. Board: A graph organises data when things connect in a flexible, complex way..


Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **graph** organises data when things connect in a flexible, complex way. Unlike a tree, there is **no strict hierarchy**: any node can connect to any other node.

- **Nodes (vertices)** — the items (cities, people).
- **Edges** — the connections (roads, friendships).

Examples: Facebook friends; GPS mapping (the fastest route between two cities).



Four vertices A, B, C, D. Edges can form a cycle (A–B–D–C–A). A tree cannot do that.

WORKED EXAMPLE

Worked example: Karachi – Hyderabad – Sukkur – Larkana. Cities are vertices. Roads are edges. You can travel Karachi → Hyderabad → Sukkur or Karachi → Larkana → Sukkur. There is no single “root city”. That is a graph, and GPS uses it to pick a fast route.

REMEMBER IT

Tree $\subset$ Graph in shape-talk: a tree is a special graph with one root and no cycles. If you need cycles or many-to-many links, say **graph**.

COMMON MISTAKE

Mistake: using a tree for GPS because "Hyderabad comes under Sindh".

Fix: administration can be a tree; **roads** are a graph because you can loop and take alternative paths.

اردو میں سمجھیں

گراف لچکدار روابط کے لیے ہے: کوئی سخت درجہ بندی نہیں، کوئی بھی نوڈ کسی سے جڑ سکتا ہے۔ نوڈز (Vertices) چیزیں ہیں، کنارے (Edges) تعلق۔ فیس بک دوست اور GPS نقشہ کلاسیکی مثالیں ہیں۔ چکر (Cycle) اور کئی راستے گراف کو ٹری سے الگ کرتے ہیں۔

CHECK YOURSELF

1. What are the two parts of a graph?
2. Give two source examples of graphs.
3. State one difference between a tree and a graph.

Write your answers in your notebook. The key follows this chapter's exam.

2.5.3 Operations on Data Structures

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 14 of 15 · 45 min · first half · with Identify data structures in problem scenarios. Board: Whatever the shape, you keep meeting the same five operations:.

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Whatever the shape, you keep meeting the same five operations:

Operation	Meaning	Quick picture
Insertion	Adding a new item into the structure.	PUSH on a stack; ENQUEUE on a queue; putting 40 into an array.
Deletion	Removing an item that is no longer needed.	POP; DEQUEUE; deleting a node from a list.
Traversal	Going through each item one by one.	Walking HEAD → ... → NULL; visiting every tree node.
Searching	Finding a specific item.	Linear search in an array; following links until 87 is found.
Sorting	Arranging items in a proper order (ascending or descending).	Bubble Sort on an array of marks.

WORKED EXAMPLE

Worked example: name the operation.

1. "Print every song from the start of the playlist." → **Traversal**.
2. "Add a print job at the rear." → **Insertion** (ENQUEUE).
3. "Undo the last typing action." → **Deletion** (POP).
4. "Is roll number 87 in the list?" → **Searching**.
5. "Arrange heights from shortest to tallest." → **Sorting**.

REMEMBER IT

Memorise **I-D-T-S-S**: Insert, Delete, Traverse, Search, Sort.

COMMON MISTAKE

Mistake: calling a PUSH "sorting" because the stack looks tidy.

Fix: PUSH is insertion. Sorting means putting values in ascending or descending order.

اردو میں سمجھیں

ہر ڈیٹا سٹرکچر پر پانچ عمل ہوتے ہیں: داخل کرنا (Insertion)، حذف کرنا (Deletion)، ایک ایک کر کے گزرنا (Traversal)، تلاش (Searching) اور ترتیب (Sorting، صعودی یا نزولی)۔

CHECK YOURSELF

1. List the five operations.
2. Which operation is ENQUEUE?
3. Traversal vs searching — one difference?

Write your answers in your notebook. The key follows this chapter's exam.

2.6 Identify data structures in problem scenarios

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 14 of 15 · 45 min · second half · with Operations on Data Structures. Board: To pick a structure, first see how the data is organised..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

To pick a structure, first see how the data is organised. If each item has a clear “before and after”, it is **linear**. If it branches or connects to many items, it is **non-linear**.

2.6.1 Linear scenarios

1. **Storing student grades for a class → Array.** You usually know how many students there are, and all grades are the same type. Indices give rapid lookup.
2. **Music playlist / browser history → Linked list.** Every song knows what comes next. When one finishes, follow the pointer. Frequent insert/delete is cheap.
3. **Undo or Redo → Stack (LIFO).** Each typing or formatting action is PUSHed. Undo POPs the most recent action.
4. **Printer task scheduling → Queue (FIFO).** Documents print in the exact order they were received. First-come, first-served.

2.6.2 Non-linear scenarios

1. **Organisational chart of a college → Tree.** Principal is the root, then deans, then HODs, then teachers. Clear parent-child links.
2. **GPS navigation and maps → Graph.** Cities are nodes, roads are edges. No strict top-down hierarchy. Several routes can reach the same destination.

If the data...	Then it is...	Recommended structure
Follows “next” or “previous” logic	Linear	Array, Linked list
Follows “parent” and “child” logic	Non-linear	Tree
Follows “first-come, first-served” logic	Linear	Queue
Follows “connections / relationships” logic	Non-linear	Graph
Needs to be accessed in the reverse order of entry	Linear	Stack

WORKED EXAMPLE

Worked example: match five school problems.

Scenario	Structure	Why (one line)
Store 40 practical marks you already counted	Array	Fixed size, same type, need A[i] lookup.
A playlist where the teacher inserts a nasheed between two songs	Linked list	Insert by moving two pointers, no big shift.
Ctrl+Z after formatting a heading	Stack	Last action must come off first.
Students lining up for the photocopier	Queue	First in line is served first.
Friend links in a class WhatsApp "everyone knows everyone"	Graph	Any student can connect to any other.

REMEMBER IT

Decision order: reverse-of-entry? → stack. First-come? → queue. Parent-child? → tree. Many-to-many routes? → graph. Known list with indexes? → array. Lots of insert/delete in a sequence? → linked list.

COMMON MISTAKE

Mistake: choosing an array for Undo because "actions are stored in a list".

Fix: the **access rule** matters more than "it is a list". Undo is reverse order of entry → stack.

اردو میں سمجھیں

اگر ہر عنصر کا واضح اگلا/پچھلا ہے تو ڈھانچہ لکیری ہے؛ اگر شاخیں یا کئی روابط ہیں تو غیر لکیری۔ نمبر: ایرے؛ پلے لسٹ/ہسٹری: لنکڈ لسٹ؛ انڈو: سٹیک؛ پرنٹر: کیو؛ کالج کا چارٹ: ٹری؛ GPS: گراف۔ فیصلے کی جدول یاد کر لیں۔

CHECK YOURSELF

1. Which structure stores a class's grades, and why?
2. Printer jobs: stack or queue? Why?
3. "Needs reverse order of entry" maps to which structure?

Write your answers in your notebook. The key follows this chapter's exam.

2.7 Trace data retrieval in Array, List and Queue

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 15 of 15 · 45 min · first half · with Career Opportunities in Algorithms. Board: Tracing data retrieval means following the step-by-step path of how an algorithm finds or accesses data..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Tracing data retrieval means following the step-by-step path of how an algorithm finds or accesses data. Array, linked list and queue are all linear, but the **effort** to find an item is very different because of how they are organised inside.

2.7.1 Retrieval in an array

Every element has a fixed index from 0 to $n-1$ pointing at a spot in memory. If the algorithm already knows the index, it does not search: it **jumps** (direct access, $O(1)$).

Array = [10, 50, 20, 70, 90, 30]. Direct access: Array[2] = 20.

Loop iteration	Index	Array access	Value
1	0	Array[0]	10
2	1	Array[1]	50
3	2	Array[2]	20

```
Array = [10, 50, 20, 70, 90, 30]
print("Direct Array[2] =", Array[2])
for i in range(3):
    print(i + 1, i, f"Array[{i}]", Array[i])
```

OUTPUT

```
Direct Array[2] = 20
1 0 Array[0] 10
2 1 Array[1] 50
3 2 Array[2] 20
```

2.7.2 Retrieval in a linked list

Linked lists have **no index**. The only way is to start at HEAD and follow links one node at a time (sequential access, $O(n)$).

List: [12] → [98] → [23] → [87] → [56] → NULL. Search key: 87.

Step	Node data	Compare with 87	Action
1	12	12 != 87	Move next
2	98	98 != 87	Move next
3	23	23 != 87	Move next
4	87	87 == 87	FOUND — output True

```
nodes = [12, 98, 23, 87, 56]
key = 87
found = False
for i, value in enumerate(nodes, start=1):
    print(f"Step {i}: Check Node {i} ({value}).")
    if value == key:
        found = True
        print("FOUND! Output: True")
        break
    print("Not equal. Move Next.")
print("Result:", found)
```

OUTPUT

```
Step 1: Check Node 1 (12).
Not equal. Move Next.
Step 2: Check Node 2 (98).
Not equal. Move Next.
Step 3: Check Node 3 (23).
Not equal. Move Next.
Step 4: Check Node 4 (87).
FOUND! Output: True
Result: True
```

Key 87 sits at the fourth node, so you paid four checks. An array that already knew index 3 would have paid one jump.

2.7.3 Retrieval in a queue

A queue is FIFO. You **cannot** retrieve from the middle or the rear. The oldest item at the Front is always DEQUEUEED first.



You cannot pull B until A has left.

Queue A, B, C. ENQUEUE D joins the rear. DEQUEUE must remove A, not C or B.

```
from collections import deque
q = deque(["A", "B", "C"])
q.append("D")
print("after ENQUEUE D:", list(q))
print("DEQUEUE:", q.popleft())
print("now:", list(q))
```

OUTPUT

```
after ENQUEUE D: ['A', 'B', 'C', 'D']
DEQUEUE: A
now: ['B', 'C', 'D']
```

WORKED EXAMPLE

Worked example: three retrievals compared for "get 20 / get 87 / get A".

Structure	Target	Path	Can you jump?
Array [10, 50, 20, ...]	20 at index 2	Array[2] in one step, or scan 10, 50, 20	Yes, if the index is known
Linked list 12→98→23→87→...	87	Must visit 12, 98, 23, then 87	No
Queue A-B-C	A (the only legal retrieval)	DEQUEUE Front	No — never the middle

REMEMBER IT

Array jumps, list walks, queue waits. If the exam asks "why is array retrieval different?", write **direct access by index** versus **sequential links** versus **Front only**.

COMMON MISTAKE

Mistake: DEQUEUEing C because "C is the interesting letter", or reading linked-list node 4 as `list[3]` without walking.

Fix: show every hop in the table. Marks are for the path, not only for FOUND.

اردو میں سمجھیں

ایرے میں اگر انڈیکس معلوم ہو تو سیدھی چھلانگ لگتی ہے، جیسے `Array[2] = 20`۔ لنکڈ لسٹ میں HEAD سے ایک ایک نوڈ دیکھنا پڑتا ہے؛ 87 چوتھے نوڈ پر ملا۔ کیوں کہ صرف Front نکلتا ہے، درمیان سے نہیں؛ A, B, C میں DEQUEUE ہمیشہ A ہے۔

CHECK YOURSELF

1. What is `Array[2]` in [10, 50, 20, 70, 90, 30]?
2. How many nodes are checked before 87 is found in 12→98→23→87→56?
3. In queue A, B, C, can you retrieve B without removing A?

Write your answers in your notebook. The key follows this chapter's exam.

Career Opportunities in Algorithms

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 15 of 15 · 45 min · second half · with Trace data retrieval in Array, List and Queue. Board: The skills in this chapter — proving correctness, writing clear modules, judging Big O, and choosing data structures — are the daily tools of several computing careers..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

The skills in this chapter — proving correctness, writing clear modules, judging Big O, and choosing data structures — are the daily tools of several computing careers.

Career	What the person does
Software Engineer	Builds and maintains software that relies on data structures and efficient algorithms to solve logic problems.
Backend Developer	Builds server-side logic where choosing the right structure (array, queue) directly affects web performance.
Algorithm Engineer	Specialises in optimising algorithms for search engines, finance or logistics.
Systems Analyst	Evaluates and improves the efficiency and clarity of existing computer systems in an organisation.
Competitive Programmer	Solves complex algorithmic problems under time limits, a common path into top tech roles.

WORKED EXAMPLE

Worked example: match the task.

1. "Replace an $O(n^2)$ report with an $O(n \log n)$ sort so the payroll finishes overnight." → **Algorithm Engineer** (or a performance-minded Software Engineer).
2. "Put incoming HTTP requests into a FIFO buffer so the first visitor is served first." → **Backend Developer** (queue).
3. "Read a college's old fee software, find the nested-IF bottleneck, and recommend modules." → **Systems Analyst**.

REMEMBER IT

Every career in the table uses the same three tests you learned: **correct, clear, efficient** — plus the right data structure.

COMMON MISTAKE

Mistake: thinking only “Algorithm Engineer” needs Big O.

Fix: a backend developer who puts a nested loop on every page request will take a site down. Efficiency is a shared skill.

اردو میں سمجھیں

اس باب کی مہارتیں سافٹ ویئر انجینئر، بیک اینڈ ڈیولپر، الگورتھم انجینئر، سسٹمز اینالسٹ اور کمپیٹیٹو پروگرامر کے کام میں روز استعمال ہوتی ہیں: درست منطق، صاف ماڈیول، بگ او اور درست ڈیٹا سٹرکچر۔

CHECK YOURSELF

1. Which career specialises in search-engine or logistics algorithms?
2. Why does a backend developer care about queues and arrays?

Write your answers in your notebook. The key follows this chapter's exam.

Computational Thinking & Algorithms

24 single-page lessons · 6 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- **Correctness:** output matches expected results for valid inputs. Test with a trace table (manual dry run) or stepwise reasoning (logic verification).
- A **trace table** is micro-level: line, variables, I/O, conditions. Best for small loops. The soldier heights [1.91, 2.01, 1.87, 1.57, 1.48] print Total = 3.
- **Stepwise reasoning** is macro-level: valid start, all cases, correct conditions, loop stays correct. Sum 1..N starts at 0; N = 0 stays 0; N = 5 becomes 15.
- **Clarity** (read, understand, modify) often beats a tiny speed gain. It has two parts: modularity and readability.
- **Modularity:** SRP (one job), loose coupling, abstraction (call Sort without knowing Bubble vs Selection). Split CalculateSum and FindAverage.
- **Readability:** names (`velocity = distance / time`), self-documentation, simple flow, consistent style.
- **Efficiency** = time + space. Drivers: number of steps (Big O), conditions, repetitions.
- **Big O:** $O(1)$ constant (arr[0]), $O(\log n)$ binary search, $O(n)$ linear search, $O(n \log n)$ Merge Sort, $O(n^2)$ nested loops / Bubble Sort. Quadratic fails as n grows.
- **Framework:** Does it scale? What is the bottleneck (deepest loop)? Is the extra complexity worth it? For n = 50, simple $O(n)$ can beat fragile $O(\log n)$.
- **Refinements:** meaningful names, modules, indentation, why-comments; shrink Bubble Sort's inner loop; better algorithms; cache constants; pick the right structure.
- **Data structure:** systematic organising of data. Linear (one after another): array, linked list, stack, queue. Non-linear: tree, graph.
- **Array:** contiguous, index from 0, direct access $O(1)$, shifting on mid-insert. **Linked list:** nodes of data+link, HEAD to NULL, sequential access.
- **Stack LIFO:** PUSH/POP at TOP (Undo). **Queue FIFO:** ENQUEUE rear, DEQUEUE front (printer).
- **Tree:** one root, parent-child (college chart). **Graph:** vertices + edges, no strict hierarchy (GPS, friends).
- Five operations: insert, delete, traverse, search, sort. Choose by next/previous, parent/child, FIFO, relationships, or reverse-of-entry.
- **Retrieval:** array can jump to an index; a list walks from HEAD; a queue only removes the Front.

Key terms

Term	Meaning	اردو
Correctness	The algorithm's output matches the expected results for valid inputs.	درستگی
Trace table	A paper dry-run table of steps, variables, I/O and conditions.	ٹریس ٹیبل
Dry run	Executing an algorithm by hand, line by line.	دستی اجرا
Stepwise reasoning	Checking each logic block's state; also called logic verification.	مرحلہ وار استدلال
Clarity	How easy an algorithm is to read, understand and modify.	وضاحت
Modularity	Breaking work into independent functions, classes or modules.	ماڈیولریتی
Single Responsibility Principle	Each module should do one specific task.	واحد ذمہ داری کا اصول
Coupling	How tightly modules depend on each other; loose coupling is the goal.	ماڈیولز کی جڑت
Abstraction	Hiding implementation details so a caller need not know the inner method.	تجرید
Readability	How easily another person understands the logic without running it.	پڑھائی پن
Efficiency	How well an algorithm uses time (speed) and space (memory).	کارکردگی
Big O notation	A description of how running time or memory grows as n grows.	بگ او نوٹیشن

Computational Thinking & Algorithms

75 marks • 1 hour 15 minutes • no notes • no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 24 and the recap. **Section A** — all 15 MCQs (1 mark).

Section B — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define • Explain • Example • Diagram • Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. An algorithm is correct when:
 - a. it compiles with no syntax error
 - b. its output matches the expected results for the given input
 - c. it uses Big O notation
 - d. it has no comments
2. A trace table is best described as:
 - a. a paper execution that tracks variables line by line
 - b. a diagram of a tree
 - c. a type of graph edge
 - d. an $O(n^2)$ nested loop
3. Stepwise reasoning mainly checks:
 - a. printer ink levels
 - b. the colour of variable names
 - c. only the last printed line
 - d. the overall state of logic blocks
4. Which method is impractical if a loop runs 1,000 times?
 - a. Abstraction
 - b. A full trace table
 - c. Stepwise reasoning
 - d. Using a function
5. The Single Responsibility Principle says each module should:
 - a. focus on one specific task
 - b. print and save and calculate everything
 - c. avoid meaningful names
 - d. use nested IF only
6. Which assignment is more readable?
 - a. `v = d / t`
 - b. `x1 = a2 / b2`
 - c. `velocity = distance / time`
 - d. `a = b / c`
7. Accessing `arr[0]` is:
 - a. $O(n^2)$
 - b. $O(n \log n)$
 - c. $O(n)$
 - d. $O(1)$
8. Binary search on a sorted list is:
 - a. $O(\log n)$
 - b. $O(n^2)$
 - c. $O(1)$ always for any n
 - d. $O(n)$ because a loop exists
9. Bubble Sort and nested "compare every pair" loops are:
 - a. $O(1)$
 - b. $O(\log n)$
 - c. $O(n)$
 - d. $O(n^2)$
10. If n grows 10 times, a quadratic algorithm's time grows about:
 - a. 2 times
 - b. 10 times
 - c. 100 times
 - d. log 10 times

- L1. LIFO is the rule of a:
- a. queue
 - b. graph of cities
 - c. tree root only
 - d. stack
- L2. ENQUEUE adds an item at the:
- a. Front of a queue
 - b. TOP of a stack only
 - c. Rear of a queue
 - d. root of a tree
- L3. A college organogram with a Principal at the top is modelled as a:
- a. tree
 - b. queue
 - c. stack
 - d. contiguous array of roads
- L4. GPS maps (cities and roads, many possible routes) need a:
- a. stack of undo actions
 - b. graph
 - c. strict one-parent tree only
 - d. single array index
- L5. To retrieve 87 from HEAD→12→98→23→87→56 you must:
- a. jump with Array[87]
 - b. DEQUEUE the rear
 - c. follow four nodes from HEAD until 87 matches
 - d. POP from the bottom of a stack

Section B — Short questions (10 × 3 = 30)

1. Define correctness of an algorithm. Name the two analysis methods used in this chapter.
2. List the components of a trace table. Why is a dry run useful for debugging?
3. Give four differences between a trace table and stepwise reasoning.
4. What is modularity? Explain SRP, coupling and abstraction in one sentence each.
5. State four ways to evaluate readability, with one example of a bad name and a good name.
6. Define Big O notation. Give one example each of $O(1)$, $O(\log n)$, $O(n)$, $O(n \log n)$ and $O(n^2)$.
7. Write the three questions of the efficiency evaluation framework and answer them for searching 50 unsorted names.
8. List four refinements for clarity and four for efficiency.
9. Define data structure. Distinguish linear from non-linear with examples.
10. Define stack and queue. Include LIFO/FIFO, PUSH/POP, ENQUEUE/DEQUEUE, and one real-life example of each.

Section C — Long questions (attempt any $3 \times 10 = 30$)

1. The soldier-eligibility algorithm uses AllHeights = [1.91, 2.01, 1.87, 1.57, 1.48] and counts heights from 1.57 to 1.91 inclusive. (a) Draw a complete trace table. (b) State the printed Total. (c) Explain in stepwise-reasoning style why the boundaries 1.57 and 1.91 are counted. (d) Write equivalent Python and its output.
2. Copy the monoblock average algorithm for A = [1, 2, 3, 4, 5] and rewrite it with CalculateSum and FindAverage. (a) Show that SRP, loose coupling and abstraction are improved. (b) Dry-run both versions to the same average. (c) Give two readability improvements you would still make to the functions.
3. Using the growth table idea, (a) fill n = 8 and n = 32 for $O(1)$, $O(\log_2 n)$, $O(n)$, $O(n \log_2 n)$ and $O(n^2)$. (b) Explain what happens if n becomes 10 times larger for $O(n)$ and for $O(n^2)$. (c) A library has 1,000,000 sorted IDs. Choose linear or binary search using the Scale / Bottleneck / Worth-it framework. (d) Show a 4-by-4 nested loop counts 16 operations in Python.
4. Draw a labelled stack and a labelled queue. Then trace: (a) PUSH Data1, PUSH Data2, PUSH Data3, POP, POP. (b) ENQUEUE 55, 76, 90, D then DEQUEUE. Include Python that matches both traces. (c) Why is Undo a stack and a printer a queue?
5. A college needs structures for: (i) 200 integer marks, (ii) a playlist with frequent insertions, (iii) Undo in the fee-office editor, (iv) photocopier jobs, (v) the Principal–Dean–HOD chart, (vi) roads between Sindh cities. Identify each structure using the decision guide, draw the tree and the graph, and then trace retrieval of 20 from Array = [10, 50, 20, 70, 90, 30] and of 87 from the linked list 12→98→23→87→56→NULL.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

1. **2.1 Analyze algorithms for correctness.** Answers: 1. When its output matches the expected results for a given input (and does so for all valid inputs). 2. Trace tables and stepwise reasoning. 3. Because a logical error can still produce output — the wrong output.
2. **2.1.1 Trace Tables.** Answers: 1. Line/step number, variables, input/output, condition check. 2. 1.57 is the lower boundary (inclusive, so True); 1.48 is below 1.57 (False). 3. 3 is printed; Step 6 runs three times (for 1.91, 1.87 and 1.57).
3. **2.1.2 Stepwise Reasoning.** Answers: 1. Logic verification. 2. Because no numbers have been added yet, so the running total should be zero. 3. The loop does not run and Sum remains 0, which is the correct sum of no numbers.
4. **2.1.3 Comparing Trace Tables and Stepwise Reasoning.** Answers: 1. Trace table. 2. It is very tedious and impractical (too many rows). 3. Stepwise reasoning (macro-level, conceptual / structural flaws).
5. **2.2 Evaluating the Clarity of an Algorithm.** Answers: 1. The algorithm is easy to read, understand and modify. 2. Modularity and readability. 3. Because a clear algorithm is easier to maintain, debug and extend over time.
6. **2.2.1 Modularity.** Answers: 1. One specific task. 2. CalculateSum (FindAverage only divides; the main program only prints). 3. All logic is in one block, so you cannot call "just the sum" from another algorithm.
7. **2.2.2 Readability.** Answers: 1. velocity = distance / time. 2. IF inside IF inside IF (or similar); it makes the flow hard to follow. 3. Any two of: consistent indentation, spacing, and casing (camelCase or snake_case).
8. **2.3 Assess Algorithm Efficiency.** Answers: 1. Time (speed) and space (memory). 2. Number of steps (Big O), number of conditions, number of repetitions.
9. **2.3.1 Number of Steps (Big O Notation).** Answers: 1. $O(1)$ arr[0]; $O(\log n)$ binary search; $O(n)$ linear search; $O(n^2)$ Bubble Sort / nested loops. 2. 1,024. 3. It makes about $\log n$ split-levels and does about n work on each level, so $n \times \log n$.
10. **2.3.2 Number of Conditions.** Answers: 1. Each condition must be evaluated True/False by the CPU. 2. A brute-force approach (and it reduces readability and speed). 3. AND short-circuits: the first part is False, so the division is never evaluated.
11. **2.3.3 Number of Repetitions.** Answers: 1. Poor — $O(n^2)$. 2. Each iteration halves the remaining problem, so the number of iterations is about $\log n$. 3. 25.
12. **2.3.4 The Efficiency Evaluation Framework.** Answers: 1. About 100× slower (10^2). 2. The most time-consuming section, usually the deepest loop. 3. Binary search is more complex to code and maintain, and for $n = 50$ the simplicity of $O(n)$ is practically better.
13. **2.4 Refinements to improve clarity and efficiency.** Answers: 1. average = totalSum / totalItems. 2. The already-sorted largest value at the end (shrink the inner loop). 3. Once, outside the loop, then reuse C inside.
14. **2.5 Concept of Data Structure.** Answers: 1. A systematic way of organising, storing and managing data for efficient access, modification and processing. 2. Linear: array, linked list, stack, queue. Non-linear: tree, graph. 3. It has exactly one predecessor and one successor.
15. **2.5.1 Linear Data Structures: Array.** Answers: 1. The items sit in one continuous block, next to each other. 2. 12. 3. Later elements must all be shifted right to make room.
16. **Linear Data Structures: Linked List.** Answers: 1. Data, and a link/pointer to the next node. 2. NULL (no next node). 3. Back follows the pointer to the previous page-node instead of jumping by index.
17. **Linear Data Structures: Stack.** Answers: 1. Last-In, First-Out. 2. Data3. 3. Each action is PUSHed; Undo POPs the most recent action first.
18. **Linear Data Structures: Queue.** Answers: 1. First-In, First-Out; added at Rear, removed from Front. 2. 55. 3. Documents must print in the order they arrived (first received, first printed), not last-received first.
19. **2.5.2 Non-Linear Data Structures: Tree.** Answers: 1. The root. 2. One-to-many parent-child. 3. A family tree, and folders inside folders (or a college organogram).
20. **Non-Linear Data Structures: Graph.** Answers: 1. Nodes/vertices and edges. 2. Social networks (Facebook friends) and GPS mapping. 3. A tree has a hierarchy and one root; a graph has no strict hierarchy and any node may connect to any other (cycles allowed).
21. **2.5.3 Operations on Data Structures.** Answers: 1. Insertion, deletion, traversal, searching, sorting. 2. Insertion (at the rear of a queue). 3. Traversal visits every item; searching stops when the target is found (or the structure ends).
22. **2.6 Identify data structures in problem scenarios.** Answers: 1. Array — known size, same type, fast index lookup. 2. Queue, because first-come, first-served. 3. Stack.
23. **2.7 Trace data retrieval in Array, List and Queue.** Answers: 1. 20. 2. Four (12, 98, 23, 87). 3. No — a queue only DEQUEUEs the Front, so A must leave first.
24. **Career Opportunities in Algorithms.** Answers: 1. Algorithm Engineer. 2. The choice of structure (array, queue) directly affects web performance.

Answer key

Multiple choice

1. b
2. a
3. d
4. b
5. a
6. c
7. d
8. a
9. d
10. c
11. d
12. c
13. a
14. b
15. c

Short questions — model answers

1. An algorithm is correct if its output matches the expected results for a given input (and does so for all valid inputs). The two methods are trace tables and stepwise reasoning (logic verification).
2. Components: line/step number, a column per variable, input/output, and a condition-check column. A dry run acts as the computer, so you see logical errors where the program runs but the values go wrong, and you can validate that the intention is met.
3. Trace table: small blocks/complex loops/beginners; high effort (bad for 1,000 iterations); catches arithmetic/line mistakes; micro-level exact values. Stepwise reasoning: large systems and proofs; moderate effort; catches conceptual/structural flaws; macro-level overall state.
4. Modularity is breaking an algorithm into smaller independent parts (functions, classes, modules). SRP: each module does one task. Coupling: modules should be loosely coupled so a change in one does not break others. Abstraction: hide inner details (call Sort without knowing Bubble vs Selection).
5. Naming conventions, self-documentation, simple control flow, consistency of indentation/spacing/casing. Bad: `v = d / t`. Good: `velocity = distance / time`.
6. Big O describes how time or memory grows as n grows. $O(1)$: `arr[0]`; $O(\log n)$: binary search; $O(n)$: linear search; $O(n \log n)$: Merge Sort; $O(n^2)$: Bubble Sort / nested loops.
7. Does it scale? $n = 50$ is tiny, even $O(n)$ is fine. Bottleneck? A single scan of 50 names. Worth it? Binary search needs sorted data and more complex code, so linear search is practically better.
8. Clarity: meaningful names; modules; structure/indentation; short why-comments. Efficiency: reduce extra steps (shrink Bubble Sort's inner loop); better algorithms (binary vs linear on sorted millions); avoid re-computing (cache $C = A+B$ outside the loop); appropriate data structures (array for direct access, tree for hierarchy).
9. A data structure is a systematic way of organising, storing and managing data for efficient access, modification and processing. Linear: sequence with one predecessor and one successor (array, linked list, stack, queue). Non-linear: hierarchical or network links (tree, graph).
10. Stack: LIFO; PUSH adds at TOP; POP removes from TOP; example Undo. Queue: FIFO; ENQUEUE adds at Rear; DEQUEUE removes from Front; example printer jobs.

Long questions — model answers

1. (a) Columns: Step, Total, Height, AllHeights, condition, output. Step 2 sets Total = 0. Step 3 stores the five heights. Then five loop cycles:

- 1.91 → True → Total 1
- 2.01 → False → Total stays 1
- 1.87 → True → Total 2
- 1.57 → True (boundary) → Total 3
- 1.48 → False → Total stays 3

(b) Printed Total = **3**.

(c) The condition is height ≥ 1.57 AND height ≤ 1.91 , so the closed interval includes both ends. 1.57 and 1.91 satisfy the inequalities; 2.01 and 1.48 do not. Initial Total = 0 is valid; each True branch adds one; False skips the add; after five items Total is the count of eligible soldiers.

(d) Python:

```
AllHeights = [1.91, 2.01, 1.87, 1.57, 1.48]
Total = 0
for height in AllHeights:
    if height ≥ 1.57 and height ≤ 1.91:
        Total = Total + 1
print(Total)
```

OUTPUT
3

2. (a) Monoblock: one sequence does the loop, the division and the print, so you cannot reuse the sum. Modular version: CalculateSum only adds; FindAverage only divides; main only prints. SRP holds. CalculateSum can be called from another program (loose coupling). Main does not see the loop (abstraction).

(b) Both compute total = 15 and avg = $15/5 = 3.0$.

```
def calculate_sum(A, n):
    total = 0
    for i in range(n):
        total = total + A[i]
    return total

def find_average(A, n):
    return calculate_sum(A, n) / n

print(find_average([1, 2, 3, 4, 5], 5))
```

OUTPUT
3.0

(c) Keep snake_case names; avoid 1-based I in Python; a one-line comment on why you divide by n (empty-list guard could be added later) is enough — do not comment every addition.

3. (a) Growth ($\log_2$):

n	$O(1)$	$O(\log n)$	$O(n)$	$O(n \log n)$	$O(n^2)$
8	1	3	8	24	64
32	1	5	32	160	1,024

(b) $O(n)$: $10\times$ input $\rightarrow$ about $10\times$ time. $O(n^2)$: $10\times$ input $\rightarrow$ about $100\times$ time, which fails for large sets.

(c) Scale: a million IDs; linear worst case is a million checks, binary about 20. Bottleneck: the search. Worth it: the IDs are already sorted and binary search is standard, so choose **binary search** $O(\log n)$.

(d)

```
n = 4
count = 0
for i in range(n):
    for j in range(n):
        count = count + 1
print(count)
```

OUTPUT
16

4. Draw the vertical stack with TOP on Data3 after three PUSHes, and the horizontal queue with FRONT on 55 and REAR on 90 (then D).

(a) Stack: [] $\rightarrow$ [Data1] $\rightarrow$ [Data1, Data2] $\rightarrow$ [Data1, Data2, Data3] $\rightarrow$ POP Data3 $\rightarrow$ POP Data2 $\rightarrow$ [Data1].

```
stack = []
stack.append("Data1")
stack.append("Data2")
stack.append("Data3")
print(stack.pop())
print(stack.pop())
print(stack)
```

OUTPUT
Data3
Data2
['Data1']

(b) Queue: [55] $\rightarrow$ [55, 76] $\rightarrow$ [55, 76, 90] $\rightarrow$ [55, 76, 90, D] $\rightarrow$ DEQUEUE 55 $\rightarrow$ [76, 90, D].

```
from collections import deque
q = deque()
q.append(55)
q.append(76)
q.append(90)
q.append("D")
print(q.popleft())
print(list(q))
```

OUTPUT
55
[76, 90, 'D']

(c) Undo must cancel the most recent action (LIFO $\rightarrow$ stack). A printer must respect arrival order (FIFO $\rightarrow$ queue).

5. (i) Array — known count, same type, index lookup. (ii) Linked list — next-pointer, cheap insert. (iii) Stack — reverse order of entry. (iv) Queue — first-come, first-served. (v) Tree — parent-child from the Principal root (Administrative Head / Academic Dean, then Accounts, HR, HOD Math, HOD CS). (vi) Graph — cities as vertices, roads as edges, alternative routes.

Array retrieval: `Array[2] = 20` in one direct access (or after visiting 10 then 50 then 20 if you scan).

List retrieval: Step1 12 $\neq$ 87, Step2 98 $\neq$ 87, Step3 23 $\neq$ 87, Step4 87 = 87 FOUND True.

Self-assessment: I can...

- | | |
|---|---|
| ☐ prove correctness with a full trace table, including boundary values. | ☐ write stepwise reasoning (start, loop, finish, edges) and compare it with a trace table. |
| ☐ judge modularity (SRP, coupling, abstraction) and readability (N-S-S-C). | ☐ state $O(1)$, $O(\log n)$, $O(n)$, $O(n \log n)$ and $O(n^2)$ with examples and a growth table. |
| ☐ apply the Scale / Bottleneck / Worth-it framework, including the $n = 50$ warning. | ☐ refine an algorithm for names, modules, fewer loop steps and cached values. |
| ☐ define a data structure and classify linear vs non-linear. | ☐ draw and trace an array, linked list, stack (PUSH/POP) and queue (ENQUEUE/DEQUEUE). |
| ☐ draw a tree and a graph and pick a structure from a scenario using the decision guide. | ☐ trace retrieval: array jump, list walk from HEAD, queue Front only. |

Programming Fundamentals

This chapter teaches you how Python stores collections of data, how you write reusable functions, and how you save information in files so it is still there after the program ends. You will build small programs — attendance, a word counter, a calculator, and a grade tracker — that you can type and run yourself.

اس باب میں آپ سیکھیں گے کہ پائتھن (Python) ڈیٹا کو فہرست، ٹیپل، سیٹ اور ڈکشنری میں کیسے رکھتا ہے، فنکشن کیسے لکھے جاتے ہیں، اور فائلوں میں ڈیٹا کیسے محفوظ کیا جاتا ہے تاکہ پروگرام بند ہونے کے بعد بھی وہ موجود رہے۔

What you will learn

- Distinguish primitive types from abstract data structures (list, tuple, set, dictionary).
- Use tuples as ordered, immutable collections, including indexing and the two tuple methods.
- Store and retrieve key–value data with dictionaries, including safe access with `.get()`.
- Write user-defined functions with parameters and `return` values, and contrast them with built-in functions.
- Open text files in modes `r`, `w` and `a`, and close them safely with `with`.
- Create, index, slice, traverse and update lists using the main list methods.
- Build sets of unique items and compute union, intersection, difference and symmetric difference.
- Apply `min()`, `max()`, `len()`, `sum()` and `sorted()` across data structures.
- Explain local and global variable scope with short programs.
- Catch file errors with `try / except` and complete a grade-tracker file project.

GOLDEN CONCEPTS

★ **Golden concepts in this chapter.** These ideas are taught first as lecture notes. If time is short, lock these before the other notes, then sit the chapter exam.

- ★ **3.1.1 Lists (Ordered, Mutable, Methods).** A list is Python's most versatile built-in data structure.
- ★ **3.1.2 Tuples (Ordered, Immutable).** A tuple is an ordered collection that is immutable — once created, you cannot add, remove or replace items.
- ★ **3.1.4 Dictionaries (Key-Value Pairs).** A dictionary stores data as key–value pairs.
- ★ **3.2 Functions in Python.** When the same instructions are written again and again, that is duplicate code.
- ★ **3.3 & 3.4 File Handling and Operations (Modes `r`, `w`, `a`).** File handling is a program's ability to create, read, write, update and delete files on disk.
- ★ **3.6 The with Statement (Context Manager).** It is easy to forget `.close()`.

اس باب کے گولڈن تصورات پہلے پڑھیں۔ باقی نوٹس بعد میں۔

STUDENT · COACH

Self-taught. 18 notes · 6 ★ first · about 6 h 30 min. After the last note, sit the chapter exam (75 marks, 1 h 15 min).

Coach / teacher. 12 academy classes of 90 minutes (each ★ Golden is a full class; other notes pair). School: ★ = one 40-minute period.

ACADEMY CALENDAR

Chapter 3 academy calendar.

Class	Topics	Kind
Class 01	Lists (Ordered, Mutable, Methods)	★ 90 min
Class 02	Tuples (Ordered, Immutable)	★ 90 min
Class 03	Dictionaries (Key-Value Pairs)	★ 90 min
Class 04	Functions in Python	★ 90 min
Class 05	& 3.4 File Handling and Operations (Modes r, w, a)	★ 90 min
Class 06	The with Statement (Context Manager)	★ 90 min
Class 07	Data Structures in Python + Sets (Unordered, Unique, Math Operations)	90 min
Class 08	Common Built-in Functions (min, max, len, sum) + Activity: Student Attendance System	90 min
Class 09	Activity: Word Frequency Counter + Types of Functions (Built-in vs User-defined)	90 min
Class 10	Functions with Return Values + Activity: Arithmetic Calculator Using Functions	90 min
Class 11	Scope of Local and Global Variables + Errors and Exceptions (Try-Except)	90 min
Class 12	Mini File Handling Project: Grade Tracker + Career Opportunities	90 min

3.1.1 Lists (Ordered, Mutable, Methods) ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 01 of 12 · 90 min · full Golden class. Board: A list is Python's most versatile built-in data structure..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **list** is Python's most versatile built-in data structure. It stores an **ordered** collection of items in a single variable. Lists are **mutable** (you can change them after you create them) and they are written with **square brackets** `[]`.

Why use a list? One variable can hold thousands of values. You can mix types if you need to. You can add, remove and sort items as the program runs.


```
numbers = [10, 2, 15, 14, 3, 33]      # list of integers
names = ["Hassan", "Qasim", "Malika"] # list of strings
mixed = [1, "Python", 3.14, True]    # mixed data types
print(numbers)
print(names)
print(mixed)
```

OUTPUT

```
[10, 2, 15, 14, 3, 33]
['Hassan', 'Qasim', 'Malika']
[1, 'Python', 3.14, True]
```

List indexing (positive and negative)

Each item sits in a numbered slot called an **index**. Numbering starts at **0** from the left. Python also supports **negative indexing** from the right: **-1** is the last item, **-2** is the second last, and so on.



Positive indices count left to right from 0. Negative indices count right to left from -1.

```
fruits = ["apple", "mango", "banana", "grape", "kiwi"]
print(fruits[0])    # first item
print(fruits[4])    # last item (when you know the length)
print(fruits[-1])   # last item (works even if the list grows)
print(fruits[-5])   # first item, counted from the right
```

OUTPUT

```
apple
kiwi
kiwi
apple
```

REMEMBER IT

Always remember `[-1]`. If a list has 10,000 items and you do not want to compute `len(list) - 1`, write `list[-1]`. It grabs the last item in one step.

Slicing a list

Slicing copies a portion of a list into a **new** list. The original is not changed.

Syntax: `list[start:stop:step]`

- `start` — first index to include (default 0).
- `stop` — first index to **exclude**. The slice goes up to, but does **not** include, this index.
- `step` — jump size (default 1). A step of `-1` walks backwards.

```
nums = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
print(nums[2:6])
print(nums[:4])
print(nums[6:])
print(nums[::2])
print(nums[::-1])
```

OUTPUT

```
[2, 3, 4, 5]
[0, 1, 2, 3]
[6, 7, 8, 9]
[0, 2, 4, 6, 8]
[9, 8, 7, 6, 5, 4, 3, 2, 1, 0]
```

Trace of `nums[2:6]`: start at index 2 (value 2), take 3, 4, 5, and stop **before** index 6. Result `[2, 3, 4, 5]`. `nums[::-1]` is the standard way to reverse a list without changing the original (it returns a new reversed list).

Traversal

Traversal means visiting each element, one by one, in order. Use a `for` loop (the usual Python style) or a `while` loop with an index.

```
numsList = [10, 20, 30]
for num in numsList:
    print(num)
```

OUTPUT

```
10
20
30
```

```
numsList = [10, 20, 30]
index = 0
while index < len(numsList):
    print(numsList[index])
    index += 1
```

OUTPUT

```
10
20
30
```

The `for` loop gives you each value directly. The `while` loop needs a counter, a test `index < len(numsList)`, and `index += 1` so the loop ends.

Built-in list methods

Because a list is mutable, Python gives you methods that change it in place. `len()` is listed with them in many notes, but it is a **built-in function**: you write `len(fruits)`, not `fruits.len()`.

Operation	What it does
<code>len(list)</code>	Returns the number of items.
<code>.append(value)</code>	Adds an item at the end .
<code>.insert(index, value)</code>	Inserts an item at a chosen position (later items shift right).
<code>.remove(value)</code>	Removes the first matching value. Raises <code>ValueError</code> if it is missing.
<code>.clear()</code>	Removes every item. The list becomes <code>[]</code> .
<code>.count(value)</code>	How many times a value appears.
<code>.index(value)</code>	Index of the first occurrence.
<code>.sort()</code>	Sorts the list in place, ascending. Use <code>reverse=True</code> for descending.
<code>.reverse()</code>	Reverses the list in place (does not sort).

Worked example: methods change the same list step by step. `fruits = ['apple', 'banana', 'apple']`
`print(fruits)` `fruits.append('grape')` `print(fruits)` `fruits.remove('apple')` `print(fruits)` `fruits.sort()`
`print(fruits)` `['apple', 'banana', 'apple']` `['apple', 'banana', 'apple', 'grape']` `['banana', 'apple', 'grape']` `['apple', 'banana', 'grape']` After this line `List in memory` create `['apple', 'banana', 'apple']`
`.append('grape')` `['apple', 'banana', 'apple', 'grape']` `.remove('apple')` `['banana', 'apple', 'grape']` — only the first apple goes `.sort()` `['apple', 'banana', 'grape']` More methods on numbers: `nums = [10, 20, 30]` `print(len(nums))` `nums.insert(1, 15)` `print(nums)` `print(nums.count(20))`
`print(nums.index(30))` `nums.reverse()` `print(nums)` `nums.clear()` `print(nums)` 3 `[10, 15, 20, 30]` 1 3 `[30, 20, 15, 10]` `[]` `insert(1, 15)` places 15 at index 1, so 20 and 30 shift right. After that, 30 sits at index 3. `reverse()` flips the current order; it does not sort. `clear()` leaves an empty list `[]`, not the

value None. You can also replace an item by index, because lists are mutable: `numbers = [10, 2, 15]` `numbers[0] = 99` `print(numbers)` `[99, 2, 15]`

Advantages of lists

- **Mutable** — add, remove or replace items as the program runs.
- **Organised** — thousands of values live in one variable instead of `n1`, `n2`, `n3`...
- **Flexible** — integers, strings, booleans and even other lists can sit in the same list.

Activity: searching an element in a list

This program combines a list, user input, a `for` loop, an `if` test and a **flag** (a Boolean that remembers whether the search succeeded).

```
numbers = [5, 10, 15, 20, 25]
search = int(input("Enter number to search: "))
found = False
for num in numbers:
    if num == search:
        found = True
        break
if found:
    print("Number found in the list.")
else:
    print("Number NOT found in the list.")
```

Execution 1 — the user types 15, which is at index 2. The loop sets `found = True` and `break` stops the scan at once.

OUTPUT

```
Enter number to search: 15
Number found in the list.
```

Execution 2 — the user types 99. The loop finishes without a match, so the flag stays `False`.

OUTPUT

```
Enter number to search: 99
Number NOT found in the list.
```

Why `break`? If the value is found at index 1 in a list of 10,000 items, there is no need to check the remaining 9,998. `break` makes linear search cheaper as soon as it succeeds.

REMEMBER IT

LIST — Lots of items, Indexed from 0, Square brackets, Tweakable (mutable). Slice memory trick: "start is in, stop is out."

COMMON MISTAKE

Mistake 1: `.remove('apple')` deletes every apple. **Fix:** it deletes only the first match. Call it again if you need the next one, or use a loop.

Mistake 2: `.sort()` and `sorted()` are the same. **Fix:** `.sort()` is a list method that changes the original and returns `None`. `sorted()` is a function that works on many structures and returns a **new** list (see 3.1.5).

Mistake 3: `fruits[5]` on a five-item list. Valid positive indices are 0 to 4. Use `[-1]` for the last item.

اردو میں سمجھیں

فہرست (List) مربع بریکٹ `[]` میں لکھی جاتی ہے، ترتیب برقرار رکھتی ہے اور تبدیل کی جا سکتی ہے (Mutable). انڈیکس صفر سے شروع ہوتا ہے، اور `[-1]` آخری عنصر دیتا ہے۔ `.append()` آخر میں جوڑتا ہے، `.remove()` پہلی مشابہ قیمت ہٹاتا ہے، اور `.sort()` اصل فہرست کو ترتیب دیتا ہے۔ تلاش کرتے وقت `break` مل جانے کے بعد لوپ روک دیتا ہے۔

EXAM TIP

Lists appear every year: "What is a list?", "List four methods with one line each", "Differentiate list and tuple", "Write a program to search an element", "Predict the output of a slice." Write: ordered, mutable, `[]`, index from 0, `[-1]` for last. For a slice, always say the stop index is excluded. For `.remove()`, say "first occurrence only." Keep a short program ready that uses `append`, `remove` and `sort` with the printed list after each line.

CHECK YOURSELF

1. What does `nums[2:6]` return if `nums = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]`?
2. After `fruits = ['apple', 'banana', 'apple']` then `fruits.remove('apple')`, what is `fruits`?
3. Why does the search program use `break`?

Write your answers in your notebook. The key follows this chapter's exam.

3.1.2 Tuples (Ordered, Immutable) ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 02 of 12 · 90 min · full Golden class. Board: A tuple is an ordered collection that is immutable — once created, you cannot add, remove or replace items..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **tuple** is an ordered collection that is **immutable** — once created, you cannot add, remove or replace items. Think of it as a **read-only list**. Tuples use **parentheses** `()`. Like lists, they allow duplicates, mixed types, and indexing from 0 (including negative indices).

List []

Can add / remove / replace

Tuple ()

LOCKED — read-only

A list is an open box you can refill. A tuple is a sealed box you may only look into.

```
t = (10, 20, 30, 40, 50)
print(t[0])
print(t[-1])
print(t[1:4])
print(t[::-1])
```

OUTPUT

```
10
50
(20, 30, 40)
(50, 40, 30, 20, 10)
```

Slicing a tuple returns a **new tuple**, not a list. Negative indexing and `[::-1]` work exactly as they do for lists.

Immutability

You cannot assign to an index of a tuple. Python raises `TypeError`.

```
t = (1, 2, 3)
t[0] = 99
```

OUTPUT

```
Traceback (most recent call last):
  File "tuple.py", line 2, in <module>
    t[0] = 99
TypeError: 'tuple' object does not support item assignment
```

Exception: if a tuple contains a **mutable object** (a list inside the tuple), that inner object's contents can still change. The tuple still holds the same two list objects; you changed a list, not the tuple's structure.

```
t = ([1, 2], [3, 4])
t[0].append(99)
print(t)
```

OUTPUT

```
([1, 2, 99], [3, 4])
```

`t[0] = [9, 9]` would still be illegal, because that would replace the tuple's first item.
`t[0].append(99)` is legal because it mutates the list that already lives at index 0.

Traversal and methods

Traverse a tuple with `for`, just as you do a list. You are only reading, which is the usual reason to choose a tuple.

```
student = ("Ali", 20, "Computer Science")
for item in student:
    print(item)
```

OUTPUT

```
Ali
20
Computer Science
```

Because a tuple cannot grow or shrink, it has only **two** methods:

Method	Meaning
<code>.count(value)</code>	How many times the value appears.
<code>.index(value)</code>	Index of the first occurrence.

```
t = (10, 20, 10, 30, 10)
print(t.count(10))
print(t.index(20))
```


OUTPUT

```
3
1
```

Advantages of tuples

- **Protection** — coordinates, identity-card numbers or settings cannot be changed by accident.
- **Speed** — a fixed-size tuple is processed slightly faster than a list.
- **Hashable keys** — a tuple of immutables can be used as a dictionary key; a list cannot. (You will use dictionaries in 3.1.4.)

WORKED EXAMPLE

When to choose a tuple. A student's roll number, name and class form a record that should not be edited in place:

```
record = ("XII-CS-07", "Ayesha", "Computer Science")
print(record[0])
print(len(record))
```

OUTPUT

```
XII-CS-07
3
```

If later you need to change the class, you build a **new** tuple. You do not assign to `record[2]`.

REMEMBER IT

Tuple = locked lunchbox. You can see what is inside; you cannot swap the sandwich.

Memory: "Tuple is Tight (immutable), written with round brackets that look like a hug holding the data still."

COMMON MISTAKE

One-item trap: `(5)` is just the integer 5 with extra parentheses. A one-item tuple needs a trailing comma: `(5,)`.

```
t1 = (5)
t2 = (5,)
print(type(t1), t1)
print(type(t2), t2)
```

OUTPUT

```
<class 'int'> 5
<class 'tuple'> (5,)
```

An empty tuple is `()`.

ٹیپل (Tuple) گول بریکٹ () میں لکھا جاتا ہے، ترتیب رکھتا ہے مگر تبدیل نہیں ہو سکتا (Immutable)۔ انڈیکس اور سلائس فہرست جیسی ہیں، لیکن `t[0] = 99` سے `TypeError` آتا ہے۔ صرف دو میتھڈز ہیں: `count()` اور `index()`۔ حساس ڈیٹا کے لیے ٹیپل محفوظ ہے۔ اگر ٹیپل کے اندر فہرست ہو تو اس فہرست کے اندر کی اشیاء بدل سکتی ہیں۔

EXAM TIP

Expect "Differentiate list and tuple" (at least four points: brackets, mutability, methods, speed/protection), "Why use a tuple?", and "What happens if you write `t[0] = 1`?" Quote the `TypeError` wording. Mention the inner-list exception if the question is a 6-mark "explain with example." A one-item tuple `(5,)` is a favourite trick question.

CHECK YOURSELF

1. Name the two tuple methods.
2. What error does `t[0] = 99` raise for a tuple?
3. After `t = ([1, 2], [3, 4]); t[0].append(99)`, what is `t`?

Write your answers in your notebook. The key follows this chapter's exam.

3.1.4 Dictionaries (Key-Value Pairs) ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 03 of 12 · 90 min · full Golden class. Board: A dictionary stores data as key-value pairs..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **dictionary** stores data as **key-value pairs**. It works like a real dictionary: you look up a word (the **key**) to find its meaning (the **value**). Write a dictionary with curly braces, and put a **colon** between each key and value.

- **Ordered** (Python 3.7+): insertion order is kept.
- **Mutable**: you can add, change and delete pairs.
- **Keys are unique**: if you repeat a key, the last value silently overwrites the earlier one. Values may repeat.



You never search a dictionary by position. You search by key.

A school analogue: a **roll number** (key) can point to only one student (value). If you assign that roll number to someone else, the old link is gone.

Adding, changing and deleting

```

d = {"name": "Alice", "age": 30}
print(d)
d["age"] = 31
print(d)
d["city"] = "NYC"
print(d)
del d["city"]
print(d)
  
```

OUTPUT

```
{'name': 'Alice', 'age': 30}
{'name': 'Alice', 'age': 31}
{'name': 'Alice', 'age': 31, 'city': 'NYC'}
{'name': 'Alice', 'age': 31}
```

Assigning to an existing key updates the value. Assigning to a new key adds a pair. `del d["city"]` removes that pair.

The duplicate-keys rule. Python does not crash. The last assignment wins.

```
d = {"a": 1, "a": 2, "a": 3}
print(d)
```

OUTPUT

```
{'a': 3}
```

Accessing values safely

1. Direct brackets (risky)

`dict[key]` works if the key exists. If it is missing, the program crashes with `KeyError`.

2. `.get()` (safe)

`dict.get(key)` returns `None` if the key is missing. You may pass a default:

```
dict.get(key, 0).
```

```
person = {"name": "Alice", "age": 30}
print(person["name"])
print(person.get("salary"))
print(person.get("salary", 0))
print("name" in person)
print("salary" in person)
```

OUTPUT

```
Alice
None
0
True
False
```

The operator `in` tests **keys**, not values. `"Alice" in person` would be `False`.

```
person = {"name": "Alice", "age": 30}
print(person["salary"])
```

OUTPUT

```
Traceback (most recent call last):
  File "keyerror.py", line 2, in <module>
    print(person["salary"])
KeyError: 'salary'
```

Dictionary views and traversal

Three view methods return live objects. If the dictionary changes, the view reflects the change immediately.

Method	Returns
<code>.keys()</code>	All keys.
<code>.values()</code>	All values.
<code>.items()</code>	Key–value pairs as tuples.

```
d = {"a": 1}
keys = d.keys()
print(keys)
d["b"] = 2
print(keys)
```

OUTPUT

```
dict_keys(['a'])
dict_keys(['a', 'b'])
```

The variable `keys` was not rebuilt. The view updated itself.

```
inventory = {"apple": 50, "banana": 30, "cherry": 20}
print(list(inventory.keys()))
print(list(inventory.values()))
print(list(inventory.items()))
for key in inventory:
    print(key)
for val in inventory.values():
    print(val)
for key, val in inventory.items():
    print(f"{key} costs {val}")
```

OUTPUT

```
['apple', 'banana', 'cherry']
[50, 30, 20]
[('apple', 50), ('banana', 30), ('cherry', 20)]
apple
banana
cherry
50
30
20
apple costs 50
banana costs 30
cherry costs 20
```

A plain `for key in inventory` loops over keys (the default). `.items()` is the most useful form because you get both sides at once.

Comparison: list, tuple, set, dictionary

Feature	List	Tuple	Set	Dictionary
Written with	[]	()	{ }	{key: value}
Ordered	Yes	Yes	No	Yes (Python 3.7+)
Mutable	Yes	No	Yes (items must be immutable)	Yes
Duplicates	Allowed	Allowed	Removed	Duplicate keys not allowed (last value wins)
Access by	Index 0, 1, 2...	Index 0, 1, 2...	No index	Key
Empty value	[]	()	set()	{}
Typical use	Changing sequences	Fixed records	Unique items, set maths	Look-up tables

WORKED EXAMPLE

Same data, four structures. Three subject marks:

- List `[80, 70, 90]` — easy to append a fourth test.
- Tuple `(80, 70, 90)` — a frozen result slip.
- Set `{80, 70, 90}` — unique scores only; two papers of 80 would become one 80.
- Dictionary `{"math": 80, "eng": 70, "cs": 90}` — you ask "What is CS?" and get 90 without remembering an index.

REMEMBER IT

Keys are unique, like roll numbers. Values are the student records and may repeat (two students can both score 80). Memory: "**get** is gentle, brackets can **break**."

COMMON MISTAKE

Older notes (and the chapter summary in some slides) still call dictionaries "unordered." From Python 3.7 onwards insertion order is preserved, so you may write "ordered since 3.7." Keys must be immutable: a list cannot be a key; a tuple of numbers can. Do not write `{}` when you want an empty set.

ڈکشنری (Dictionary) کلید اور قدر (Key-Value) کے جوڑوں میں ڈیٹا رکھتی ہے۔ کلید منفرد ہوتی ہے؛ دہرائی ہوئی کلید پر آخری قدر رہ جاتی ہے۔ `d[key]` غیر موجود کلید پر `KeyError` دیتا ہے، جبکہ `d.get(key, default)` محفوظ ہے۔ `.values()`، `keys()` اور `items()` سے گھما جا سکتا ہے۔ فہرست انڈیکس سے، ڈکشنری کلید سے پہچانی جاتی ہے۔

EXAM TIP

High-yield: definition of a dictionary, difference between `d[key]` and `d.get(key)`, "what if a key is repeated?", traversal with `.items()`, and a full comparison table of the four structures. Memorise the comparison table in this section — it is a complete 8-mark answer if you add one example row. Always mention that `in` checks keys.

CHECK YOURSELF

1. What does `{"a": 1, "a": 2, "a": 3}` print?
2. What does `person.get("salary", 0)` return if `salary` is missing?
3. Which structure has no index and no duplicate items?

Write your answers in your notebook. The key follows this chapter's exam.

3.2 Functions in Python ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 04 of 12 · 90 min · full Golden class. Board: When the same instructions are written again and again, that is duplicate code..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

When the same instructions are written again and again, that is **duplicate code**. Duplicate code makes a program longer, harder to read, and painful to update (you must fix every copy). A **function** lets you write the instructions **once** and run them whenever you call the function's name.

Benefit	Meaning
Code reusability	Write once, use anywhere.
Modularity	Break a big problem into small named tasks.
Readability	Shorter, cleaner files with meaningful names.
Maintainability	Fix a bug in one place and every call is fixed.

```
def greet():
    print("Hello, World!")

greet()
greet()
```

OUTPUT

```
Hello, World!
Hello, World!
```

The body is written once. Two calls run it twice. To change the message you edit one line inside `greet`.

Key components of a function

def → name → parameters → indented body → return (optional)

- **Keyword** — Python uses `def` to start a definition.
- **Function name** — the identifier you call, e.g. `greet`.
- **Parameters** — input names inside the parentheses. When you call the function, the values you pass are called **arguments**.
- **Body** — the indented block that runs on each call.
- **Return statement** — sends a result back to the caller (3.2.2).

```
def add(a, b):
    print(f"Adding {a} + {b}")
    return a + b

result = add(4, 6)
print(result)
```

OUTPUT
Adding 4 + 6
10

Here `a` and `b` are parameters. `4` and `6` are arguments. `return a + b` sends 10 back, and that 10 is stored in `result`.

WORKED EXAMPLE

Without a function you would copy the print-and-add lines every time you needed a sum. With a function, a new sum is one call: `add(10, 20)`, `add(1.5, 2.5)`.

REMEMBER IT

DRY — Don't Repeat Yourself. If you are about to copy-paste a block, wrap it in `def`. Name functions with verbs: `greet`, `add`, `save_grades`.

COMMON MISTAKE

Defining is not calling. After `def greet():` nothing prints until you write `greet()`. Forgetting the parentheses — writing `greet` alone — does not run the body. The body must be indented; a line at column 0 is outside the function.

اردو میں سمجھیں

فونکشن (Function) ہدایات کا وہ بلاک ہے جو ایک بار لکھا جاتا ہے اور بار بار بلایا جا سکتا ہے۔ اس سے کوڈ مختصر، ماڈیولر اور آسان اصلاح والا بنتا ہے۔ تعریف `def` سے شروع ہوتی ہے، نام اور پیرامیٹرز قوسین میں ہوتے ہیں، جسم انڈینٹ ہوتا ہے، اور `return` نتیجہ واپس بھیج سکتا ہے۔ تعریف کرنے سے فونکشن چلتا نہیں جب تک آپ اسے کال نہ کریں۔

EXAM TIP

Write the four benefits (reusability, modularity, readability, maintainability) as separate bullets — that is a standard short question. For long questions, define a function, label `def`, name, parameters, body and `return`, then show one call. "What is duplicate code and how do functions solve it?" is also common.

CHECK YOURSELF

1. What keyword starts a function definition?
2. How many times does `Hello, World!` print in the `greet` program above, and why?

Write your answers in your notebook. The key follows this chapter's exam.

3.3 & 3.4 File Handling and Operations (Modes r, w, a) ★ Golden

STUDENT · COACH


Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 05 of 12 · 90 min · full Golden class. Board: File handling is a program's ability to create, read, write, update and delete files on disk..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

File handling is a program's ability to create, read, write, update and delete files on disk. Variables live in **RAM** and vanish when the program ends. Files live on a **hard disk or SSD** and stay there — they are **persistent**.



Read copies data from disk into RAM. Write copies data from RAM onto disk.

Types of files

Type	What it stores	Examples
Text file	Human-readable characters. You can open it in a text editor.	.txt, .csv, .py
Binary file	Raw bytes, not meant to be read as text.	.jpg, .mp3, .dat

This chapter uses text files.

The `open()` function and modes

You must open a file before you use it: `open(filepath, mode)`.

Mode	Name	Description
'r'	Read	Open for reading. Fails if the file does not exist.
'w'	Write	Open for writing. Erases existing content. Creates the file if it is missing.
'a'	Append	Open for writing at the end . Keeps old content. Creates the file if it is missing.
'rb' / 'wb'	Binary	Read or write bytes (images, audio).

File object methods

Method	What it does
<code>.read()</code>	Whole file as one string.
<code>.readlines()</code>	All lines as a list of strings (each usually ends with <code>\n</code>).
<code>.write("text")</code>	Writes a string. You must add <code>\n</code> yourself for a new line.
<code>.close()</code>	Saves to disk, closes the file, frees RAM. Essential if you did not use <code>with</code> .

WORKED EXAMPLE

Create a file in write mode.

```
new_file = open('myfile.txt', 'w')
new_file.write("The quick brown fox jumps over the lazy dog!!!\n")
new_file.close()
print("File has been created successfully.")
```

OUTPUT

```
File has been created successfully.
```

If `myfile.txt` did not exist, `'w'` created it. The sentence is now on disk. `.close()` flushes the buffer so the bytes actually reach the disk.

Danger of `'w'`: opening an existing file in `'w'` deletes everything first.

```
f = open('myfile.txt', 'w')
f.write("FIRST\n")
f.close()
f = open('myfile.txt', 'w')
f.write("SECOND\n")
f.close()
with open('myfile.txt', 'r') as f:
    print(f.read(), end="")
```

OUTPUT

```
SECOND
```

`FIRST` is gone. To keep old lines and add a new one, use `'a'`:

```
f = open('notes.txt', 'w')
f.write("Line 1\n")
f.close()
f = open('notes.txt', 'a')
f.write("Line 2\n")
f.close()
with open('notes.txt', 'r') as f:
    print(f.read(), end="")
```

OUTPUT

```
Line 1
Line 2
```

REMEMBER IT

r = Read existing, w = Wipe then write, a = Add at end. Remember: `write` does not add a newline unless you type `\n`.

COMMON MISTAKE

Forgetting `.close()` can leave data in a memory buffer so the file on disk looks empty or incomplete — or the file can stay locked. Section 3.6 shows `with`, which closes for you even after an error. Never use `'w'` when you only meant to add a line; that is the most common way students wipe their own data.

اردو میں سمجھیں

فائل ہینڈلنگ سے ڈیٹا ڈسک پر مستقل (Persistent) رہتا ہے، برخلاف RAM کے متغیرات کے جو پروگرام بند ہوتے ہی مٹ جاتے ہیں۔ `open(path, mode)` سے فائل کھلتی ہے: `'r'` پڑھنے کے لیے (فائل ہونی چاہیے)، `'w'` لکھنے کے لیے (پرانا مواد مٹ جاتا ہے)، `'a'` آخر میں جوڑنے کے لیے۔ کام کے بعد `.close()` ضروری ہے اگر `with` استعمال نہ ہو۔

EXAM TIP

Define file handling, contrast RAM with disk, list modes `r` / `w` / `a` with one property each, and warn that `w` overwrites. Short programs that write one line and close the file are common. Mention `.read()`, `.readlines()`, `.write()` and `.close()` by name.

CHECK YOURSELF

1. Which mode overwrites an existing file?
2. Which mode fails if the file is missing?
3. Why must `.write` often include `\n`?

Write your answers in your notebook. The key follows this chapter's exam.

3.6 The with Statement (Context Manager) ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 06 of 12 · 90 min · full Golden class. Board: It is easy to forget `.close()`.

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

It is easy to forget `.close()`. If the program crashes before `.close()` runs, the file may be incomplete or corrupted. Python's `with` statement is a **context manager**: it opens the file, runs the indented block, and **always closes** the file when the block ends — even if an error occurs inside.

with open(...) as f → use f → block ends → file closed automatically

```
with open('myfile.txt', 'w') as new_file:
    new_file.write("Context managers are safe!\n")
# no .close() here – with already closed the file
```

After the indented block, `new_file` is closed. You do not write `new_file.close()`.

3.7 Activity: reading file content

`.read()` pulls the whole file into RAM. For a huge file that can waste memory. The professional pattern is to **iterate line by line**.

```
with open('myfile.txt', 'w') as new_file:
    new_file.write("Context managers are safe!\n")

with open('myfile.txt', 'r') as read_file:
    for line in read_file:
        print(line, end="")
print("\n\nFile read successfully.")
```

OUTPUT

Context managers are safe!

File read successfully.

`end=""` stops `print` from adding a second newline: each line from the file already ends with `\n`.

WORKED EXAMPLE

Three ways to read the same small file.

```
with open('sample.txt', 'w') as f:
    f.write("Ali 80\nSara 90\nAyesha 75\n")

with open('sample.txt', 'r') as f:
    print("≡ .read() ≡")
    print(repr(f.read()))

with open('sample.txt', 'r') as f:
    print("≡ .readlines() ≡")
    print(f.readlines())

with open('sample.txt', 'r') as f:
    print("≡ line by line ≡")
    for line in f:
        print(line, end="")
```

OUTPUT

```
≡ .read() ≡
'Ali 80\nSara 90\nAyesha 75\n'
≡ .readlines() ≡
['Ali 80\n', 'Sara 90\n', 'Ayesha 75\n']
≡ line by line ≡
Ali 80
Sara 90
Ayesha 75
```

`repr` shows the hidden `\n` characters. `.readlines()` is handy when you need a list (the grade tracker uses this). Line-by-line looping is best for large files because only one line sits in memory at a time.

REMEMBER IT

with = “take, use, put back.” Prefer `with open(...) as f:` in every new program. You still choose the mode: `'r'`, `'w'` or `'a'`.

COMMON MISTAKE

You cannot read from `f` after the `with` block — the file is already closed. Do all reading and writing inside the block. Also, `print(line)` without `end=""` looks double-spaced because both the line and `print` add a newline.

with بیان ایک کانٹیکسٹ مینیجر (Context Manager) ہے جو فائل کو بلاک کے اختتام پر خود بند کر دیتا ہے، چاہے اندر غلطی ہو جائے۔ بڑی فائلیں ایک ایک سطر کے لوپ سے پڑھنا بہتر ہے بجائے پورے مواد کو `read()` سے میموری میں بھرنے کے۔ `print(line, end="")` دگنی خالی سطر روکتا ہے۔

EXAM TIP

Define the `with` statement as a context manager that guarantees close. Contrast it with manual `open / close`. Be ready to write a four-line program that writes with `with` and a four-line program that reads line by line. Mention memory: iterating is safer for large files than `.read()`.

CHECK YOURSELF

1. What does a context manager guarantee for a file?
2. Why pass `end=""` when printing each line from a file?

Write your answers in your notebook. The key follows this chapter's exam.

3.1 Data Structures in Python

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 07 of 12 · 45 min · first half · with Sets (Unordered, Unique, Math Operations). Board: A data structure is a way of organising values in a program so you can store them, find them and change them..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **data structure** is a way of organising values in a program so you can store them, find them and change them. Every useful program is built on data structures. Python gives you two layers:

- **Primitive data structures** — the basic types that hold **one** value. Examples: integers (`int`), floating-point numbers (`float`), and booleans (`bool`).
- **Abstract data structures** — higher-level containers built from primitive types so you can hold **many** values and run richer operations. Examples: **lists, tuples, sets, dictionaries**.

Python has these four abstract structures built in. You do not install anything extra. That is why collecting marks, names or settings is simpler in Python than in many other languages.

Category	Description	Examples
Primitive	Basic types that represent a single value.	<code>int</code> , <code>float</code> , <code>bool</code>
Abstract	Higher-level structures for collections and complex operations.	Lists, tuples, sets, dictionaries

WORKED EXAMPLE

One value versus a collection. A student's age is one integer. That student's three test marks need a list.

```
age = 17
height = 5.8
passed = True
marks = [80, 75, 90]
print(type(age))
print(type(height))
print(type(passed))
print(type(marks))
```

OUTPUT

```
<class 'int'>
<class 'float'>
<class 'bool'>
<class 'list'>
```

`type()` tells you which structure a value has. `age` is a primitive integer. `marks` is an abstract list that holds three integers together.

REMEMBER IT

Primitive = one piece. Abstract = a box of pieces. Think of a single rupee coin (primitive) versus a wallet that can hold many coins (list, tuple, set or dictionary).

COMMON MISTAKE

Do not call a list a “variable type” and stop there. A list is a **structure**: it has an order, methods, and rules. The four abstract structures look similar at first (they all hold several values) but they follow different rules. Learn those rules one by one in 3.1.1–3.1.4.

اردو میں سمجھیں

ڈیٹا سٹرکچر (Data Structure) پروگرام میں ڈیٹا کو ترتیب دینے کا طریقہ ہے۔ پرائمیٹو اقسام جیسے عدد (int) صرف ایک قیمت رکھتی ہیں، جبکہ فہرست، ٹیپل، سیٹ اور ڈکشنری کئی قیمتیں ایک ساتھ سنبھالتی ہیں۔ پائٹھن میں یہ چاروں سٹرکچرز پہلے سے موجود ہیں، اس لیے ڈیٹا جمع کرنا دوسری زبانوں کے مقابلے میں آسان ہے۔

CHECK YOURSELF

1. Name two primitive types and two abstract data structures in Python.
2. Why is a list called an abstract data structure rather than a primitive type?

Write your answers in your notebook. The key follows this chapter's exam.

3.1.3 Sets (Unordered, Unique, Math Operations)

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 07 of 12 · 45 min · second half · with Data Structures in Python. Board: A set stores an unordered, unindexed collection of unique elements..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **set** stores an **unordered, unindexed** collection of **unique** elements. It is inspired by mathematical sets. You write a set with **curly braces** `{}`. Duplicates are removed as soon as the set is created. Because there is no index, `myset[0]` is illegal.

The set itself is **mutable** (you can add and remove items). Each item inside must be **immutable** (numbers, strings, tuples of immutables — not lists).

```
nums = {1, 4, 3, 3, 2, 2}
print(nums)
```

OUTPUT

```
{1, 2, 3, 4}
```

The two 3s and two 2s collapse to one each. Do not depend on the printed order: a set is unordered. CPython often prints small integers in a tidy way, but that is not a language promise.

Adding and removing

Method	Description
<code>.add(value)</code>	Adds one element.
<code>.update(values)</code>	Adds many elements from a list, tuple or set.
<code>.remove(value)</code>	Removes the value. Raises <code>KeyError</code> if it is missing.
<code>.discard(value)</code>	Removes the value. Does not crash if it is missing.
<code>.clear()</code>	Removes every element. Result is <code>set()</code> .

```
s = {1, 2, 3}
s.add(4)
print(s)
s.update([5, 6])
print(s)
s.discard(99)
print(s)
s.remove(1)
print(s)
s.clear()
print(s)
```

OUTPUT

```
{1, 2, 3, 4}
{1, 2, 3, 4, 5, 6}
{1, 2, 3, 4, 5, 6}
{2, 3, 4, 5, 6}
set()
```

`discard(99)` quietly does nothing. After `clear()` Python prints `set()`, not `{}`, because `{}` already means an empty **dictionary**.

Compare with `.remove(99)` on a set that does not contain 99:

```
s = {1, 2, 3}
s.remove(99)
```


OUTPUT

```
Traceback (most recent call last):
  File "set_remove.py", line 2, in <module>
    s.remove(99)
  KeyError: 99
```

Prefer `.discard()` when the item might not be there, so a missing value does not crash the program.

Mathematical operations

Sets are built for union, intersection, difference and symmetric difference.



Overlap {3, 4} is the intersection. Left-only {1, 2} is $A - B$. Right-only {5, 6} is $B - A$.

Operation	Meaning	Syntax	Result for A, B above
Union	All unique items from both	<code>A B</code> or <code>A.union(B)</code>	<code>{1, 2, 3, 4, 5, 6}</code>
Intersection	Items in both	<code>A & B</code> or <code>A.intersection(B)</code>	<code>{3, 4}</code>
Difference	In A, not in B	<code>A - B</code> or <code>A.difference(B)</code>	<code>{1, 2}</code>
Symmetric difference	In either, but not both	<code>A ^ B</code> or <code>A.symmetric_difference(B)</code>	<code>{1, 2, 5, 6}</code>

```
A = {1, 2, 3, 4}
B = {3, 4, 5, 6}
print(A | B)
print(A & B)
print(A - B)
print(A ^ B)
```

OUTPUT

```
{1, 2, 3, 4, 5, 6}
{3, 4}
{1, 2}
{1, 2, 5, 6}
```

`B - A` would be `{5, 6}` — difference is not symmetric. Symmetric difference `A ^ B` is `(A - B) | (B - A)`.

Set traversal

There is no index, so you loop with `for`. Print order is not guaranteed. Use `sorted()` when you need a stable alphabetical or numerical order (it returns a list).

```
colors = {"red", "green", "blue"}
for color in sorted(colors):
    print(color)
```

OUTPUT

```
blue
green
red
```

WORKED EXAMPLE

Deduplication. A teacher types roll numbers and some are repeated. A set keeps each roll once:

```
rolls = [12, 5, 12, 8, 5, 19]
unique = set(rolls)
print(unique)
print(sorted(unique))
```

OUTPUT

```
{8, 19, 12, 5}
[5, 8, 12, 19]
```

`set(rolls)` drops duplicates. `sorted(unique)` gives a list in numeric order for a register.

REMEMBER IT

SET = Same-item Eaten Twice-never. Empty set is `set()`, never `{}`. Safe delete = `discard`; angry delete = `remove`.

COMMON MISTAKE

`myset[0]` raises `TypeError` because sets are unindexed. Convert with `list(myset)` only if you accept that the order is arbitrary. Do not put a list inside a set — lists are mutable, so they cannot be set elements.

اردو میں سمجھیں

سیٹ (Set) منفرد عناصر کا بغیر ترتیب اور بغیر انڈیکس مجموعہ ہے، جو `{}` میں لکھا جاتا ہے۔ دہرائی ہوئی قیمتیں خود بخود ختم ہو جاتی ہیں۔ `add()` اور `update()` عناصر جوڑتے ہیں، `discard()` محفوظ طریقے سے ہٹاتا ہے جبکہ `remove()` غیر موجود عنصر پر `KeyError` دیتا ہے۔ اجتماع (Union) `|`، اشتراک (Intersection) `&`، فرق - اور متوازی فرق `^` ریاضی کی کارروائیاں ہیں۔

CHECK YOURSELF

1. What is printed by `print({1, 4, 3, 3, 2, 2})` ?
2. Why prefer `.discard()` over `.remove()` ?
3. If $A = \{1, 2, 3, 4\}$ and $B = \{3, 4, 5, 6\}$, what is $A \wedge B$?

Write your answers in your notebook. The key follows this chapter's exam.

3.1.5 Common Built-in Functions (min, max, len, sum)

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 08 of 12 · 45 min · first half · with Activity: Student Attendance System. Board: Several built-in functions work across lists, tuples, sets and dictionaries..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Several built-in functions work across lists, tuples, sets and dictionaries. You do not call them with a dot on the object (except when a type also has its own method, such as `list.sort()`).

Function	Purpose	Works on
<code>min()</code>	Smallest element (numeric or alphabetical)	List, tuple, set, dictionary keys
<code>max()</code>	Largest element	List, tuple, set, dictionary keys
<code>len()</code>	Number of elements (for a dict: number of keys)	List, tuple, set, dictionary
<code>sum()</code>	Adds numeric elements	List, tuple, set, dictionary values via <code>sum(d.values())</code>
<code>sorted()</code>	Returns a new sorted list ; original unchanged	List, tuple, set, dictionary keys

```
s = {5, 1, 9, 3, 7}
print(len(s))
print(min(s))
print(max(s))
print(sum(s))
print(sorted(s))
```

OUTPUT

```
5
1
9
25
[1, 3, 5, 7, 9]
```

`5 + 1 + 9 + 3 + 7 = 25`. `sorted(s)` always returns a **list**, even when the input is a set.

WORKED EXAMPLE

The same five functions on four structures.

```
nums = [8, 3, 5, 3]
t = (8, 3, 5, 3)
s = {8, 3, 5}
d = {"math": 80, "eng": 70, "cs": 90}
print(len(nums), min(nums), max(nums), sum(nums), sorted(nums))
print(len(t), min(t), max(t), sum(t), sorted(t))
print(len(s), min(s), max(s), sum(s), sorted(s))
print(len(d), min(d), max(d), sum(d.values()), sorted(d))
```

OUTPUT

```
4 3 8 19 [3, 3, 5, 8]
4 3 8 19 [3, 3, 5, 8]
3 3 8 16 [3, 5, 8]
3 cs math 240 ['cs', 'eng', 'math']
```

On the dictionary, `min(d)` and `max(d)` compare **keys as strings**: "cs" comes first alphabetically, "math" last. `sum(d)` would try to add the keys "math" + "eng" + ... and fail. Use `sum(d.values())` — $80 + 70 + 90 = 240$. The set dropped the duplicate 3, so `len(s)` is 3 and `sum(s)` is 16.

sorted() versus .sort()

```
original = [8, 3, 5]
print("before sort:", original)
print("sorted():", sorted(original))
print("after sorted():", original)
original.sort()
print("after .sort():", original)
```

OUTPUT

```
before sort: [8, 3, 5]
sorted(): [3, 5, 8]
after sorted(): [8, 3, 5]
after .sort(): [3, 5, 8]
```

`.sort()` exists only on lists and rewrites the original. `sorted()` works on any iterable and leaves the original alone.

REMEMBER IT

LEN-MIN-MAX-SUM — count, smallest, largest, total. For a dictionary: `len` / `min` / `max` / `sorted` use **keys**; `sum` needs `.values()`.

COMMON MISTAKE

`sum()` needs numbers. `sum(["a", "b"])` raises `TypeError`. Empty structures: `len([])` is 0, but `min([])` and `max([])` raise `ValueError` because there is no smallest of nothing.

اردو میں سمجھیں

`len()` عناصر گنتا ہے، `min()` سب سے چھوٹا، `max()` سب سے بڑا، `sum()` اعداد کا مجموعہ، اور `sorted()` نئی ترتیب شدہ فہرست دیتا ہے بغیر اصل کو بدلے ہیں۔ ڈکشنری پر `min` اور `max` کلیدوں پر چلتے ہیں؛ قدروں کا مجموعہ `sum(d.values())` سے نکالیں۔ `sort()` صرف فہرست کا میتھڈ ہے جو اصل فہرست بدل دیتا ہے۔

CHECK YOURSELF

1. For `s = {5, 1, 9, 3, 7}`, what are `len(s)`, `min(s)`, `max(s)`, `sum(s)`?
2. Does `sorted(s)` return a set or a list?
3. How do you total the values of `{"math": 80, "eng": 70, "cs": 90}`?

Write your answers in your notebook. The key follows this chapter's exam.

3.1.6 Activity: Student Attendance System

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 08 of 12 · 45 min · second half · with Common Built-in Functions (min, max, len, sum).
Board: Teachers need a quick way to mark who is in class..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Teachers need a quick way to mark who is in class. This program stores names in a **list**, asks about each student, counts how many said yes, and prints a summary with `len()`.

Store names in a list → Ask present? for each → Count yes → Print totals

```
students = ["Ali", "Sara", "Ayesha"]
present_count = 0
print("--- Attendance System ---\n")
for student in students:
    status = input(f"Is {student} present? (yes/no): ").lower()
    if status == "yes":
        present_count += 1
print("\n--- Attendance Summary ---")
print("Total Students:", len(students))
print("Students Present:", present_count)
print("Students Absent:", len(students) - present_count)
```

WORKED EXAMPLE

Sample run. Ali yes, Sara no, Ayesha yes. `.lower()` means YES or Yes still counts as present.

OUTPUT

```
--- Attendance System ---

Is Ali present? (yes/no): yes
Is Sara present? (yes/no): no
Is Ayesha present? (yes/no): yes

--- Attendance Summary ---
Total Students: 3
Students Present: 2
Students Absent: 1
```

Student	Typed answer	After lower()	present_count
Ali	yes	yes → add 1	1
Sara	no	not yes	1
Ayesha	yes	yes → add 1	2

Absent = `len(students) - present_count` = 3 - 2 = 1. The counter must start at 0 **before** the loop. If you put `present_count = 0` inside the loop, the count would reset for every student.

REMEMBER IT

Counter pattern: start at 0, loop, add 1 when a condition is true. You will reuse this in the word-frequency program (add 1 per word) and the grade tracker (add each mark).

COMMON MISTAKE

Only the exact string "yes" after `.lower()` counts as present. "y" or "present" is treated as absent. In a longer program you could also accept "y" ; this activity keeps the rule simple.

اردو میں سمجھیں

حاضری کا پروگرام طلبہ کے نام ایک فہرست میں رکھتا ہے، ہر نام کے لیے پوچھتا ہے، اور yes پر شمار کار (Counter) ایک بڑھاتا ہے۔ کل طلبہ `len(students)` سے، غیر حاضر کل - حاضر سے نکلتے ہیں۔ شمار کار لوپ سے پہلے صفر ہونا چاہیے۔

CHECK YOURSELF

1. If all three students type no , what is printed for present and absent?
2. Why is `.lower()` used on the answer?

Write your answers in your notebook. The key follows this chapter's exam.

3.1.7 Activity: Word Frequency Counter

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 09 of 12 · 45 min · first half · with Types of Functions (Built-in vs User-defined). Board: Count how many times each word appears in a sentence..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Count how many times each word appears in a sentence. This is a classic use of a **dictionary** plus `.get()` : the word is the key, the count is the value.

```
sentence = "python is easy python is fun python is powerful"
words = sentence.split()
word_freq = {}
for word in words:
    word_freq[word] = word_freq.get(word, 0) + 1
print(f"Sentence: '{sentence}'\n")
print("Word Frequency Table:")
for word, count in word_freq.items():
    print(f"{word:<10} : {count}")
top_word = max(word_freq, key=word_freq.get)
print(f"\nMost Frequent: '{top_word}' ({word_freq[top_word]} times)")
```

WORKED EXAMPLE

Logic, step by step.

1. `sentence.split()` cuts on spaces and gives
`['python', 'is', 'easy', 'python', 'is', 'fun', 'python', 'is', 'powerful']`.
2. For a new word, `word_freq.get(word, 0)` is 0, then you store $0 + 1 = 1$.
3. For a word already in the dictionary, `.get(word, 0)` returns the current count, then you add 1.
4. `{word:<10}` pads the word to 10 characters so the colons line up.
5. `max(word_freq, key=word_freq.get)` picks the key whose value is largest. If two words share the top count, `max` returns the first of those keys in insertion order.

OUTPUT

Sentence: 'python is easy python is fun python is powerful'

Word Frequency Table:

```
python      : 3
is          : 3
easy        : 1
fun         : 1
powerful    : 1
```

Most Frequent: 'python' (3 times)

After seeing	<code>word_freq</code>
python	<code>{'python': 1}</code>
is	<code>{'python': 1, 'is': 1}</code>
easy	<code>{'python': 1, 'is': 1, 'easy': 1}</code>
python (again)	<code>{'python': 2, 'is': 1, 'easy': 1}</code>
... end of sentence	<code>{'python': 3, 'is': 3, 'easy': 1, 'fun': 1, 'powerful': 1}</code>

Here `python` and `is` both occur 3 times. `max` returns `'python'` because it appears first in the dictionary.

REMEMBER IT

The heart of every counter is one line: `d[item] = d.get(item, 0) + 1`. You can count letters, roll numbers or votes with the same pattern.

COMMON MISTAKE

This program is case-sensitive and space-based. "Python" and "python" would be two keys. Punctuation such as `easy.` would not match `easy`. For a class exercise, keep the sentence lowercase with spaces only, as here. If you wrote `word_freq[word] += 1` without `.get` on a new word, you would get `KeyError`.

اردو میں سمجھیں

جملے کو `.split()` سے الفاظ کی فہرست بناتے ہیں، پھر ہر لفظ ڈکشنری میں کلید ہوتا ہے اور اس کی گنتی قدر۔ نئے لفظ کے لیے `get(word, 0) + 1` سے گنتی 1 سے شروع ہوتی ہے۔ `max(..., key=word_freq.get)` سب سے زیادہ بار آنے والا لفظ دیتا ہے۔

CHECK YOURSELF

1. How many times does "is" occur in the sample sentence?
2. Why use `.get(word, 0)` instead of `word_freq[word]` on the right-hand side?

Write your answers in your notebook. The key follows this chapter's exam.

3.2.1 Types of Functions (Built-in vs User-defined)

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 09 of 12 · 45 min · second half · with Activity: Word Frequency Counter. Board: There are two main types of functions in Python..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

There are two main types of functions in Python.

a) Built-in functions are already defined by Python. You just call them. Examples you have already used: `len()`, `range()`, `sum()`, `print()`, `input()`, `min()`, `max()`, `sorted()`, `int()`, `float()`, `type()`.

b) User-defined functions are functions **you** create with `def` for tasks that no built-in covers in one step — greeting a user, dividing with a zero check, writing a grade file.

	Built-in	User-defined
Who writes it?	The Python language	The programmer
How you start	Just call the name	First write <code>def name(...):</code>
Examples	<code>len("Ali") → 3</code>	<code>def add(a, b): return a + b</code>
Purpose	Everyday operations needed by everyone	Your program's specific jobs

WORKED EXAMPLE

Side by side. Counting letters is built-in. Combining a greeting with a name is user-defined.

```
print(len("Sindh"))

def greet_student(name):
    print("Hello,", name)

greet_student("Hassan")
greet_student("Malika")
```

OUTPUT

```
5
Hello, Hassan
Hello, Malika
```

You did not write the code inside `len`. You did write the code inside `greet_student`, then reused it for two names.

REMEMBER IT

If Python already has it (`len` , `sum` , `max`), do not rewrite it. Write a user-defined function when you are packaging **your** steps.

COMMON MISTAKE

Do not name your function `list` , `print` , `sum` or `input` . You would hide the built-in name for the rest of that file. Choose names such as `print_bill` or `sum_marks` .

اردو میں سمجھیں

بلٹ ان فنکشن پائتھن میں پہلے سے موجود ہوتے ہیں، جیسے `len()` اور `print()`۔ یوزر ڈیفائنڈ فنکشن وہ ہیں جو پروگرامر `def` سے خود بناتا ہے تاکہ مخصوص کام بار بار کیا جا سکے۔ جو کام بلٹ ان پہلے کر دیتے ہیں انہیں دوبارہ نہ لکھیں۔

CHECK YOURSELF

1. Is `range()` built-in or user-defined?
2. Which keyword creates a user-defined function?

Write your answers in your notebook. The key follows this chapter's exam.

3.2.2 Functions with Return Values

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 10 of 12 · 45 min · first half · with Activity: Arithmetic Calculator Using Functions. Board: A function can either print a result (show it on the screen) or return a result (send it back to the caller)..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A function can either **print** a result (show it on the screen) or **return** a result (send it back to the caller). A returned value can be stored in a variable, printed later, or used in a further calculation. The call is replaced by the returned value, as if you had written that value in its place.

```
def multiply(a, b):
    return a * b

result = multiply(5, 3)
print("The answer is:", result)
```

OUTPUT

The answer is: 15

`multiply(5, 3)` evaluates to 15. That 15 is stored in `result`.

WORKED EXAMPLE

Print versus return. This is the difference examiners want.

```
def show_sum(a, b):
    print(a + b)

def give_sum(a, b):
    return a + b

x = show_sum(2, 3)
print("stored from show_sum:", x)
y = give_sum(2, 3)
print("stored from give_sum:", y)
print("double it:", y * 2)
```

OUTPUT

```
5
stored from show_sum: None
stored from give_sum: 5
double it: 10
```

`show_sum` prints 5 inside the function, then returns `None` (the default when there is no `return`). You cannot double that answer later. `give_sum` hands 5 back, so `y * 2` is 10. Use `print` for messages; use `return` for results the rest of the program still needs.

REMEMBER IT

return = send back; print = show now. `return` also **exits** the function immediately. Lines after `return` in the same function do not run.

COMMON MISTAKE

Writing `print(a * b)` inside `multiply` and then `result = multiply(5, 3)` stores `None` in `result`, not 15. If you later write `result + 1` you get `TypeError`. Return the number; let the caller decide whether to print it.

اردو میں سمجھیں

`return` نتیجہ کال کرنے والے پروگرام کو واپس بھیجتا ہے تاکہ وہ متغیر میں محفوظ ہو سکے یا آگے حساب میں لگے۔ اگر `return` نہ ہو تو فنکشن `None` دیتا ہے۔ `print` صرف اسکرین پر دکھاتا ہے؛ اس سے حاصل شدہ قیمت دوبارہ استعمال نہیں ہوتی۔

CHECK YOURSELF

1. What is stored in `result` after `result = multiply(5, 3)` with `return a * b`?
2. What does a function return if it has no `return` statement?

Write your answers in your notebook. The key follows this chapter's exam.

3.2.3 Activity: Arithmetic Calculator Using Functions

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 10 of 12 · 45 min · second half · with Functions with Return Values. Board: Each arithmetic operation is a separate function..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Each arithmetic operation is a **separate function**. That is modularity: addition is one small task, division is another (with a guard against dividing by zero). The main program only asks for two numbers and calls the functions.

```
def add(a, b):
    return a + b

def subtract(a, b):
    return a - b

def multiply(a, b):
    return a * b

def divide(a, b):
    if b != 0:
        return a / b
    else:
        return "Cannot divide by zero"

num1 = float(input("Enter first number: "))
num2 = float(input("Enter second number: "))
print("Addition:", add(num1, num2))
print("Subtraction:", subtract(num1, num2))
print("Multiplication:", multiply(num1, num2))
print("Division:", divide(num1, num2))
```

WORKED EXAMPLE

Sample run with 12 and 4. `float` is used so decimals work; even whole numbers print with a decimal (12 becomes 12.0).

OUTPUT

```
Enter first number: 12
Enter second number: 4
Addition: 16.0
Subtraction: 8.0
Multiplication: 48.0
Division: 3.0
```

Check: $12 + 4 = 16$, $12 - 4 = 8$, $12 \times 4 = 48$, $12 \div 4 = 3$. In Python 3, `/` always produces a float, so 3.0 not 3.

Zero divisor:

```
def divide(a, b):
    if b != 0:
        return a / b
    else:
        return "Cannot divide by zero"

print(divide(10, 0))
print(divide(10, 2))
```

OUTPUT

```
Cannot divide by zero
5.0
```

Without the `if b != 0` test, `10 / 0` would raise `ZeroDivisionError` and stop the program.

REMEMBER IT

Four functions, four names: `add`, `subtract`, `multiply`, `divide`. The main program should look like a contents page — a sequence of calls — not a pile of formulae.

COMMON MISTAKE

`input()` returns a string. If you skip `float()` (or `int()`), `add` would concatenate: `"12" + "4"` is `"124"`. Convert first. Also, `divide` returns either a number or a string; do not later do arithmetic on the error message.

اردو میں سمجھیں

کیلکولیٹر میں ہر عمل الگ فنکشن ہے: جمع، تفریق، ضرب، تقسیم۔ یہ ماڈیولریٹی ہے۔ تقسیم سے پہلے صفر کی جانچ ضروری ہے ورنہ پروگرام رک جاتا ہے۔ `input()` سے ملنے والی تار کو `float()` سے عدد بنانا لازمی ہے ورنہ جمع جوڑنے کے بجائے الفاظ جوڑ دے گی۔

CHECK YOURSELF

1. What does `divide(10, 0)` return in this activity?
2. Why are the numbers converted with `float()`?

Write your answers in your notebook. The key follows this chapter's exam.

3.2.4 Scope of Local and Global Variables

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 11 of 12 · 45 min · first half · with Errors and Exceptions (Try-Except). Board: Scope is the region of a program where a variable can be seen and used..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Scope is the region of a program where a variable can be seen and used. Python has two scopes you must know for this chapter.

i) Local scope. A **local variable** is created inside a function. It exists only while that function is running. The main program cannot read it.

ii) Global scope. A **global variable** is created outside all functions. Any function may **read** it, and the main program can use it too.

WORKED EXAMPLE

Local — the name is invisible outside.

```
def calc():
    secret = 50
    print(secret)

calc()
print(secret)
```

OUTPUT

```
50
Traceback (most recent call last):
  File "local_scope.py", line 5, in <module>
    print(secret)
NameError: name 'secret' is not defined
```

First the function prints 50. Then the main program tries `print(secret)` and fails: `secret` was born inside `calc` and died when `calc` finished.

Global — readable inside and outside.

```
x = 10

def show():
    print("Inside function:", x)

show()
print("Outside function:", x)
```

OUTPUT

```
Inside function: 10
Outside function: 10
```

Assignment inside a function creates a new local with the same name. It does not change the global:

```
x = 10

def show():
    x = 99
    print("Inside:", x)

show()
print("Outside:", x)
```

OUTPUT

```
Inside: 99
Outside: 10
```

Inside, `x = 99` is a local. After the call, the global is still 10.

REMEMBER IT

Local = inside the room; global = in the corridor. Everyone can see the corridor. Things left in a room are gone when you leave. Prefer locals. Too many globals make bugs hard to find because any function might be using them.

COMMON MISTAKE

If you only **read** `x` inside the function, Python uses the global. If you **assign** to `x` anywhere in that function, Python treats `x` as local for the whole function. Mixing the two without care causes `UnboundLocalError`. Keep function inputs as parameters and outputs as `return` values instead of editing globals.

اردو میں سمجھیں

دائرہ کار (Scope) بتاتا ہے کہ متغیر کہاں دکھائی دیتا ہے۔ لوکل متغیر فنکشن کے اندر بنتا ہے اور فنکشن ختم ہوتے ہی غائب ہو جاتا ہے؛ باہر سے پڑھنے پر `NameError` آتا ہے۔ گلوبل متغیر تمام فنکشنز سے باہر بنتا ہے اور اندر سے پڑھا جا سکتا ہے۔ فنکشن کے اندر اسی نام کو نئی قدر دینے سے نیا لوکل بنتا ہے، گلوبل نہیں بدلتا۔

CHECK YOURSELF

1. Where is a local variable defined?
2. In the last example, what does the main program print for `x` after `show()` ?

Write your answers in your notebook. The key follows this chapter's exam.

3.8 Errors and Exceptions (Try-Except)

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 11 of 12 · 45 min · second half · with Scope of Local and Global Variables. Board: An exception is an error raised while the program is running — for example opening a file that is not there..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

An **exception** is an error raised while the program is running — for example opening a file that is not there. Without handling, Python prints a traceback and **stops**. A `try / except` block catches the error and lets you show a clear message instead of crashing.

Error type	Meaning
<code>FileNotFoundError</code>	The path does not exist.
<code>PermissionError</code>	The operating system will not let you read or write that file.
<code>IOError</code>	A general input/output problem (disk full, disk disconnected).

Put risky code in `try`. Put the recovery in `except ErrorType`. A final `except Exception as e` can catch anything else, using `e` as the error object.

```
try:
    with open('missing_data.txt', 'r') as f:
        content = f.read()
        print(content)
except FileNotFoundError:
    print("Error: The file does not exist. Please check the name.")
except Exception as e:
    print(f"An unexpected error occurred: {e}")
```

OUTPUT

Error: The file does not exist. Please check the name.

Without `try`, the same open raises:

OUTPUT

```
Traceback (most recent call last):
  File "missing.py", line 1, in <module>
    open('missing_data.txt', 'r')
FileNotFoundError: [Errno 2] No such file or directory: 'missing_data.txt'
```

WORKED EXAMPLE

When the file exists, the except blocks are skipped.

```
with open('ok.txt', 'w') as f:
    f.write("Present\n")

try:
    with open('ok.txt', 'r') as f:
        content = f.read()
        print(content, end="")
except FileNotFoundError:
    print("Error: The file does not exist. Please check the name.")
```

OUTPUT

Present

Professional software does not dump a red traceback on a user. If a file is missing or a disk fails, the user should see a calm sentence such as "Please check the file name" or "Please try again later."

REMEMBER IT

try = attempt; except = backup plan. Catch the **specific** error first (`FileNotFoundError`), then a general `Exception` if you need it. Order matters: a bare `except Exception` first would swallow the specific error.

COMMON MISTAKE

Do not wrap your entire program in one silent `except:` that ignores every mistake. You would hide real bugs. Catch the errors you expect, and keep the message honest. `'w'` and `'a'` create a missing file, so they do not raise `FileNotFoundError`; `'r'` does.

اردو میں سمجھیں

ایکسپشن (Exception) چلتے پروگرام کی غلطی ہے، جیسے غیر موجود فائل کھولنا۔ `try` میں خطرناک کوڈ لکھیں اور `except` میں صاف پیغام دکھائیں تاکہ پروگرام کریش نہ ہو۔ پیشہ ورانہ سافٹ ویئر صارف کو سرخ ٹریس بیک کی بجائے سمجھ آنے والا جملہ دکھاتا ہے۔

CHECK YOURSELF

1. Which exception is raised when `open('missing_data.txt', 'r')` cannot find the file?
2. Does the sample program crash, or print a message, when the file is missing?

Write your answers in your notebook. The key follows this chapter's exam.

3.9 Mini File Handling Project: Grade Tracker

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 12 of 12 · 45 min · first half · with Career Opportunities. Board: This project uses 'w' to create a grades file, 'a' to add a student later, and 'r' to read every line and compute an average..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

This project uses 'w' to create a grades file, 'a' to add a student later, and 'r' to read every line and compute an average. It combines file handling, string methods and arithmetic.

Write names and marks ('w') → Append a new student ('a') → Read lines ('r') → Split, total, average

```
with open("grades.txt", "w") as f:
    f.write("Alice: 88\n")
    f.write("Bob: 75\n")
    f.write("Carol: 92\n")
print("Grades file created.")

with open("grades.txt", "a") as f:
    f.write("David: 81\n")
print("New student appended.")

with open("grades.txt", "r") as f:
    lines = f.readlines()
    total = 0
    for line in lines:
        name, grade = line.strip().split(":")
        print(f"{name} scored {grade}")
        total += int(grade)
    average = total / len(lines)
    print(f"\nClass average: {average:.1f}")
```

WORKED EXAMPLE

What happens in memory and on disk.

1. 'w' creates grades.txt (or wipes an old one) with three lines.
2. 'a' adds David: 81\n at the end. Alice, Bob and Carol stay.
3. .readlines() returns
['Alice: 88\n', 'Bob: 75\n', 'Carol: 92\n', 'David: 81\n'].
4. .strip() removes the trailing \n. .split(":") turns "Alice: 88" into ["Alice", " 88"].
5. int(grade) accepts the extra space: int(" 88") is 88.
6. Total = 88 + 75 + 92 + 81 = 336. Average = 336 / 4 = 84.0. The format :.1f prints one decimal place.

OUTPUT

```
Grades file created.
New student appended.
Alice scored 88
Bob scored 75
Carol scored 92
David scored 81

Class average: 84.0
```

The extra space before each mark in the output comes from the space after the colon in the file ("Alice: 88"). int() ignores it. To tidy the printout you could use grade.strip() as well; the average would not change.

REMEMBER IT

Same file, three modes, three with blocks. Never open the same file in 'w' when you only meant to add David — that would delete Alice, Bob and Carol.

COMMON MISTAKE

If a line has no colon, split(":") will not produce two parts and the unpacking name, grade = ... will raise ValueError. Keep the Name: mark format. An empty file would make len(lines) zero and then total / 0 would fail — a real system should check that, just as divide checked for zero.

اردو میں سمجھیں

گریڈ ٹریکر پہلے 'w' سے فائل بناتا ہے، پھر 'a' سے نیا طالب علم جوڑتا ہے، پھر 'r' سے تمام سطریں پڑھ کر اوسط نکالتا ہے۔ ہر سطر کو strip اور split(":") سے نام اور نمبر میں توڑا جاتا ہے۔ اوسط = کل نمبر ÷ طلبہ کی تعداد۔ 'w' دوبارہ استعمال کرنے سے پرانے ریکارڈ مٹ جائیں گے۔

CHECK YOURSELF

1. What is the class average in the sample, and how is it calculated?
2. Why is David written with mode "a" rather than "w" ?

Write your answers in your notebook. The key follows this chapter's exam.

Career Opportunities

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 12 of 12 · 45 min · second half · with Mini File Handling Project: Grade Tracker. Board: The skills in this chapter — data structures, functions and files — are the same skills used in many jobs..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

The skills in this chapter — data structures, functions and files — are the same skills used in many jobs.

- **Python / software developer** — builds applications, scripts and tools in Python, one of the most widely used languages in industry.
- **Data analyst** — uses lists and dictionaries, then file handling, to process, visualise and interpret data for decisions.
- **Automation engineer** — writes scripts that repeat file and testing tasks so humans do not have to.
- **Game developer** — uses functions, data structures and logic to build interactive games.

WORKED EXAMPLE

The word-frequency dictionary is a tiny version of what a data analyst does with a much larger file of customer comments. The grade tracker is a tiny version of a school information system. The attendance list is a tiny version of an HR register. Same structures, larger files.

REMEMBER IT

Four careers: **P-D-A-G** — Python developer, Data analyst, Automation engineer, Game developer.

COMMON MISTAKE

You do not need all four job titles for the exam. You do need one sentence each if the paper asks “List career opportunities related to this chapter.”

اردو میں سمجھیں

اس باب کی مہارتیں پائتھن ڈویلپر، ڈیٹا اینالسٹ، آٹومیشن انجینئر اور گیم ڈویلپر کے کام میں روز استعمال ہوتی ہیں۔ فہرستیں، ڈکشنریز، فنکشنز اور فائلیں چھوٹے اسکول پروگراموں سے لے کر بڑے صنعتی نظام تک ایک جیسی بنیاد ہیں۔

CHECK YOURSELF

1. Which career uses lists, dictionaries and files to interpret business data?
2. Name two careers listed in this chapter.

Write your answers in your notebook. The key follows this chapter's exam.

Programming Fundamentals

18 single-page lessons · 6 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- Python programs rest on primitive types (`int`, `float`, `bool`) and abstract structures: lists, tuples, sets and dictionaries.
- A **list** is ordered and mutable, written with `[]`. Index from 0; `[-1]` is last. Slice stop is exclusive. Methods include `append`, `insert`, `remove`, `sort`, `reverse`, `clear`.
- A **tuple** is ordered and immutable, written with `()`. Item assignment raises `TypeError`. Only `count` and `index` exist as methods.
- A **set** is unordered and unique, written with `{}`. Use `|` & `-` & `^` for union, intersection, difference and symmetric difference. Prefer `discard` over `remove`.
- A **dictionary** maps unique keys to values. `d[key]` can raise `KeyError`; `d.get(key, default)` is safe. Duplicate keys keep the last value.
- `min`, `max`, `len`, `sum` and `sorted` work across structures. On a dict, `min/max/sorted` use keys; total values with `sum(d.values())`. `sorted()` returns a new list; `.sort()` changes a list in place.
- Functions written with `def` give reusability, modularity, readability and maintainability. Built-in functions already exist; user-defined functions solve your tasks.
- `return` sends a value to the caller. Without `return`, the result is `None`. Local variables live inside a function; global variables live outside all functions.
- Files persist on disk. Modes: `r` read (must exist), `w` write (overwrites), `a` append. Methods: `read`, `readlines`, `write`, `close`.
- The `with` statement is a context manager that closes the file automatically. Loop line by line to read large files safely.
- `try/except FileNotFoundError` stops a missing file from crashing the program.
- The grade tracker writes with `w`, appends with `a`, reads with `r`, splits each `Name: mark` line, and computes the mean.

Key terms

Term	Meaning	اردو
Data structure	A way of organising values so a program can store and use them.	ڈیٹا سٹرکچر
Primitive type	A basic single value: <code>int</code> , <code>float</code> , <code>bool</code> .	بنیادی قسم
List	Ordered, mutable sequence written with <code>[]</code> .	فہرست
Index	The position of an item, starting at 0 (or -1 from the end).	انڈیکس
Slicing	Copying a portion of a sequence with <code>start:stop:step</code> .	سلائسنگ
Traversal	Visiting each element in turn, usually with a loop.	گشت / تراورسل
Mutable	Can be changed after creation.	قابل تبدیلی
Immutable	Cannot be changed after creation.	ناقابل تبدیلی
Tuple	Ordered, immutable sequence written with <code>()</code> .	ٹیپل
Set	Unordered collection of unique items written with <code>{}</code> .	سیٹ
Union	All unique items from two sets (<code> </code>).	اجتماع
Intersection	Items common to both sets (<code>&</code>).	اشتراک

Programming Fundamentals

75 marks • 1 hour 15 minutes • no notes • no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 18 and the recap. **Section A** — all 15 MCQs (1 mark).

Section B — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define • Explain • Example • Diagram • Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

- Which structure is ordered and mutable?
 - List
 - Tuple
 - Set
 - Frozen set
- What does `nums[2:6]` return if `nums = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]`?
 - `[2, 3, 4, 5, 6]`
 - `[2, 3, 4, 5, 6, 7]`
 - `[2, 3, 4, 5]`
 - `[3, 4, 5, 6]`
- `t = (1, 2, 3)` then `t[0] = 99` raises
 - `KeyError`
 - `TypeError`
 - `ValueError`
 - `IndexError`
- A set is best described as
 - ordered with duplicates
 - indexed and mutable
 - key–value pairs
 - unordered with unique elements
- If `A = {1, 2, 3, 4}` and `B = {3, 4, 5, 6}`, then `A & B` is
 - `{3, 4}`
 - `{1, 2}`
 - `{1, 2, 3, 4, 5, 6}`
 - `{1, 2, 5, 6}`
- `{"a": 1, "a": 2, "a": 3}` prints
 - `{'a': 1}`
 - `{'a': 1, 'a': 2, 'a': 3}`
 - `{'a': 3}`
 - a `KeyError`
- The safe way to read a possibly missing dictionary key is
 - `d[key]`
 - `d.get(key)`
 - `d.keys(key)`
 - `d.index(key)`
- For `s = {5, 1, 9, 3, 7}`, `sum(s)` is
 - 5
 - 9
 - 7
 - 25
- Which statement is true?
 - `sorted(x)` returns a new list and leaves `x` unchanged
 - `sorted(x)` works only on lists
 - `.sort()` works on tuples
 - `.sort()` returns a new list
- A function is created with the keyword
 - `func`
 - `def`
 - `define`
 - `return`

- L1. A function that has no `return` statement returns
- a. `0`
 - b. `False`
 - c. `None`
 - d. an empty string
- L2. A variable defined inside a function is
- a. local
 - b. global
 - c. persistent
 - d. public
- L3. Opening a file with mode `'w'`
- a. fails if the file already exists
 - b. adds new text at the end
 - c. is read-only
 - d. erases existing content (and creates the file if needed)
- L4. The `with open(...) as f:` statement is used mainly because
- a. it makes the file binary
 - b. it closes the file automatically
 - c. it is faster than lists
 - d. it prevents `KeyError`
- L5. Reading a missing file in mode `'r'` without `try` raises
- a. `TypeError`
 - b. `KeyError`
 - c. `FileNotFoundError`
 - d. `ValueError`

Section B — Short questions (10 × 3 = 30)

1. Define a data structure. Distinguish primitive from abstract data structures with one example of each.
2. What is negative indexing? Give the expression that returns the last item of a list named `fruits`.
3. State four differences between a list and a tuple.
4. Differentiate `.remove()` and `.discard()` on a set.
5. Why can a dictionary not have two identical keys? What happens if you write the same key twice?
6. Contrast `sorted()` with list `.sort()`.
7. List four benefits of using functions.
8. Define local scope and global scope.
9. Write the meaning of file modes `'r'`, `'w'` and `'a'`.
10. What is a context manager? Why is `with` safer than calling `.close()` yourself?

Section C — Long questions (attempt any 3 × 10 = 30)

1. Compare list, tuple, set and dictionary in a table (syntax, order, mutability, duplicates, how you access an item, one typical use). Then write two lines of Python that create one example of each holding the numbers 1, 2 and 2, and state what each structure actually stores.
2. Write a complete Python program that takes a sentence, counts the frequency of each word using a dictionary and `.get()`, prints a two-column table, and prints the most frequent word. Trace your program on `"python is easy python is fun python is powerful"`.
3. Write an arithmetic calculator with four user-defined functions `add`, `subtract`, `multiply` and `divide`. `divide` must not crash when the second number is 0. Explain how `return` is used and why `input` values are converted with `float`.
4. Explain file handling. Describe modes `r`, `w` and `a`, the `with` statement, and `try/except FileNotFoundError`. Include a short program that writes one line with `with` and another that reads a file that might be missing.
5. The grade tracker writes three students with `'w'`, appends David with `'a'`, then computes the class average. Write the full program, show the exact output for marks 88, 75, 92 and 81, and explain `strip`, `split(":")` and `average:.1f`.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

- 3.1 Data Structures in Python.** Answers: 1. Primitive: any two of int, float, bool. Abstract: any two of list, tuple, set, dictionary. 2. Because it is a higher-level container built from primitive values, holding many items and supporting operations such as append and slice.
- 3.1.1 Lists (Ordered, Mutable, Methods).** Answers: 1. [2, 3, 4, 5]. 2. ['banana', 'apple'] (only the first apple is removed). 3. To stop scanning once the value is found, so the rest of a long list is not checked.
- 3.1.2 Tuples (Ordered, Immutable).** Answers: 1. count and index. 2. TypeError: 'tuple' object does not support item assignment. 3. ([1, 2, 99], [3, 4]).
- 3.1.3 Sets (Unordered, Unique, Math Operations).** Answers: 1. {1, 2, 3, 4} (duplicates removed; order may vary). 2. discard does not raise KeyError if the value is missing. 3. {1, 2, 5, 6}.
- 3.1.4 Dictionaries (Key-Value Pairs).** Answers: 1. {'a': 3}. 2. 0. 3. A set.
- 3.1.5 Common Built-in Functions (min, max, len, sum).** Answers: 1. 5, 1, 9, 25. 2. A list: [1, 3, 5, 7, 9]. 3. sum(d.values()) → 240.
- 3.1.6 Activity: Student Attendance System.** Answers: 1. Present 0, Absent 3. 2. So that YES, Yes and yes all match the string "yes".
- 3.1.7 Activity: Word Frequency Counter.** Answers: 1. Three times. 2. Because a brand-new word is not yet a key; .get returns 0 instead of raising KeyError.
- 3.2 Functions in Python.** Answers: 1. def. 2. Twice, because greet() is called twice.
- 3.2.1 Types of Functions (Built-in vs User-defined).** Answers: 1. Built-in. 2. def.
- 3.2.2 Functions with Return Values.** Answers: 1. 15. 2. None.
- 3.2.3 Activity: Arithmetic Calculator Using Functions.** Answers: 1. The string "Cannot divide by zero". 2. Because input() returns text; float() turns it into a number so + - * / do arithmetic, including decimals.
- 3.2.4 Scope of Local and Global Variables.** Answers: 1. Inside a function. 2. 10 (the global is unchanged).
- 3.3 & 3.4 File Handling and Operations (Modes r, w, a).** Answers: 1. 'w'. 2. 'r'. 3. Because write() does not start a new line by itself; without \n the next write continues on the same line.
- 3.6 The with Statement (Context Manager).** Answers: 1. That the file is closed when the with block ends, even if an error occurs. 2. Because each line already ends with \n; print would otherwise add another newline and the output would look double-spaced.
- 3.8 Errors and Exceptions (Try-Except).** Answers: 1. FileNotFoundError. 2. It prints "Error: The file does not exist. Please check the name." and continues.
- 3.9 Mini File Handling Project: Grade Tracker.** Answers: 1. 84.0 because (88+75+92+81)/4 = 336/4 = 84.0. 2. Because "a" appends; "w" would erase the three existing students.
- Career Opportunities.** Answers: 1. Data analyst. 2. Any two of: Python/software developer, data analyst, automation engineer, game developer.

Answer key

Multiple choice

1. a
2. c
3. b
4. d
5. a
6. c
7. b
8. d
9. a
10. b
11. c
12. a
13. d
14. b
15. c

Short questions — model answers

1. A data structure organises values in a program. Primitive types hold one value (e.g. `int 17`). Abstract structures hold collections and richer operations (e.g. a list of marks).
2. Negative indexing counts from the right. `fruits[-1]` is the last item. `fruits[-2]` is the second last.
3. List: `[]`, mutable, many methods, slightly slower, use when data will change. Tuple: `()`, immutable, only `count / index`, slightly faster, use for protected records. Both are ordered and allow duplicates and indexing.
4. Both delete an element. `remove` raises `KeyError` if the value is absent. `discard` does nothing in that case, so it is the safer choice.
5. Each key must identify one value (like one roll number per student). A repeated key does not crash; the last assigned value overwrites the earlier one, e.g. `{"a": 3}`.
6. `sorted(x)` is a built-in function for any iterable; it returns a new list and does not change `x`. `.sort()` is a list method that sorts in place and returns `None`.
7. Reusability (write once, call many times), modularity (small named tasks), readability (shorter files), maintainability (fix one definition).
8. Local: defined inside a function; invisible outside; gone when the function ends. Global: defined outside all functions; readable throughout the program.
9. `'r'` read, error if missing. `'w'` write, create if missing, erase old content. `'a'` append at the end, create if missing, keep old content.
10. A context manager sets up a resource and cleans it up. `with open(...) as f` closes the file when the block ends, even after an exception, so you cannot forget `.close()` and you are safer if the program crashes mid-write.

Long questions — model answers

1. Use the comparison table from 3.1.4 (brackets, ordered/mutable/duplicates/access/empty/use). Examples:

```
print([1, 2, 2])
print((1, 2, 2))
print({1, 2, 2})
print({"a": 1, "b": 2, "b": 2})
```

OUTPUT

```
[1, 2, 2]
(1, 2, 2)
{1, 2}
{'a': 1, 'b': 2}
```

The list and tuple keep both 2s and an order. The set drops the extra 2. The dictionary keeps unique keys; the second "b" overwrites the first.

2. Use the program in 3.1.7. Trace: nine tokens; `python` and `is` end at 3; others at 1. Output matches the worked example, including Most Frequent: 'python' (3 times) because `max` returns the first key among ties. Heart of the loop: `word_freq[word] = word_freq.get(word, 0) + 1`.
3. Use the four functions from 3.2.3. `return` sends each result to `print` in the main program. `divide` returns the string "Cannot divide by zero" when `b == 0`. `float(input(...))` is required because `input` returns a string and `"12" + "4"` would concatenate. Sample 12 and 4: 16.0, 8.0, 48.0, 3.0.
4. File handling stores data on disk so it outlives the program. Modes: `r` read / must exist; `w` wipe-or-create; `a` add-or-create. `with` closes automatically. Try/except:

```
with open("note.txt", "w") as f:
    f.write("Saved\n")
try:
    with open("note.txt", "r") as f:
        print(f.read(), end="")
except FileNotFoundError:
    print("Error: The file does not exist. Please check the name.")
```

OUTPUT

```
Saved
```

If the name were wrong, the except message would print instead of a traceback.

5. Full program as in 3.9. Disk after append:

OUTPUT

```
Alice: 88
Bob: 75
Carol: 92
David: 81
```

Output of the program (exact):

OUTPUT

```
Grades file created.
New student appended.
Alice scored 88
Bob scored 75
Carol scored 92
David scored 81

Class average: 84.0
```

`strip` removes `\n`; `split(":")` separates name and mark; `int(grade)` allows the extra space; `{average:.1f}` prints one decimal. $336 \div 4 = 84.0$.

Self-assessment: I can...

- ☐ Choose list, tuple, set or dictionary for a given problem and justify the choice.
- ☐ Explain tuple immutability and the inner-list exception, and use `count / index`.
- ☐ Update a dictionary, access values with `.get()`, and loop with `.items()`.
- ☐ Write a user-defined function with parameters and a `return` value, and contrast it with a built-in.
- ☐ Open a text file in `r`, `w` or `a` using `with`, and read it line by line.
- ☐ Index, slice, traverse and update a list, including `[-1]` and the main methods.
- ☐ Build a set, drop duplicates, and compute union, intersection, difference and symmetric difference.
- ☐ Apply `min`, `max`, `len`, `sum` and `sorted` correctly, including on dictionaries.
- ☐ State whether a name is local or global and predict a `NameError`.
- ☐ Catch `FileNotFoundError` and complete the grade-tracker project with the correct average.

CHAPTER 4

Data and Analysis

This chapter shows you how to pull data from a SQLite database with Python, clean it in Pandas, draw the right chart, and summarise a dataset with mean, median, mode and standard deviation. These are the same steps a data analyst uses every day.

اس باب میں آپ سیکھیں گے کہ پائتھن سے ایس کیو لائٹ ڈیٹا بیس کیسے جوڑا جاتا ہے، پینڈاز میں ڈیٹا کیسے صاف ہوتا ہے، درست چارٹ کیسے بنتا ہے، اور اوسط، میڈین، موڈ اور معیاری انحراف سے خلاصہ کیسے نکلتا ہے۔

What you will learn

- Define data analysis and say why Python is used for it.
- Create a SQLite database, table, insert, select, commit and close.
- Create calculated columns and handle NaN with isnull, fillna and dropna.
- Choose and code bar, line, pie, histogram, scatter and box plots.
- Name the five parts of a Python database connection in order.
- Build a Pandas DataFrame from a dictionary, CSV or Excel file.
- Organise data in tables and frequency distributions.
- Compute mean, median, mode, range, variance, standard deviation, min and max by hand, and know that pandas `.std()` uses $n-1$.

GOLDEN CONCEPTS

★ **Golden concepts in this chapter.** These ideas are taught first as lecture notes. If time is short, lock these before the other notes, then sit the chapter exam.

- ★ **4.1.1 – 4.1.2 Data Sources and Database Connection.** Data sources are where information comes from: school records, websites, sensors, databases.
- ★ **4.3 Pandas and DataFrames.** Pandas is a third-party library for tables.
- ★ **4.3.3 Handling Missing Values (NaN).** Missing cells are NaN ("Not a Number").
- ★ **4.5 Data Visualization and Types of Graphs.** Pick the graph that matches the question.
- ★ **4.6 Descriptive Statistics.** Descriptive statistics squeeze a long list into a few honest numbers.

اس باب کے گولڈن تصورات پہلے پڑھیں۔ باقی نوٹس بعد میں۔

STUDENT · COACH

Self-taught. 9 notes · 5 ★ first · about 4 h 5 min. After the last note, sit the chapter exam (75 marks, 1 h 15 min).

Coach / teacher. 7 academy classes of 90 minutes (each ★ Golden is a full class; other notes pair). School: ★ = one 40-minute period.

ACADEMY CALENDAR**Chapter 4 academy calendar.**

Class	Topics	Kind
Class 01	Data Sources and Database Connection	★ 90 min
Class 02	Pandas and DataFrames	★ 90 min
Class 03	Handling Missing Values (NaN)	★ 90 min
Class 04	Data Visualization and Types of Graphs	★ 90 min
Class 05	Descriptive Statistics	★ 90 min
Class 06	Concept of Data Analysis + Creating a SQLite Database in Python	90 min
Class 07	Data Organization and Representation + Career Opportunities	90 min

4.1.1 – 4.1.2 Data Sources and Database Connection

★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 01 of 07 · 90 min · full Golden class. Board: Data sources are where information comes from: school records, websites, sensors, databases..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Data sources are where information comes from: school records, websites, sensors, databases. **Connectivity** is the conversation between your Python program and that source so you can read and update data.

Five components of a database connection, in the order they actually work:

#	Component	Role
1	Database	Organised store (SQLite = one .db file; MySQL = a server for big apps)
2	Driver	Translator between Python and that DBMS (sqlite3 is built in)
3	Connection object	Opens, manages and closes the pipeline
4	Cursor object	Runs SQL and walks through result rows
5	SQL queries	CREATE, INSERT, SELECT, UPDATE, DELETE

Python → Driver → Connection → Cursor → SQL → Database

EXAM TIP

Write the five names in order and one line each. A common trap is swapping cursor and connection: the connection is the pipe; the cursor is the messenger that travels through it.

اردو میں سمجھیں

خمسہ اجزاء: ڈیٹا بیس، ڈرائیور، کنکشن، کرسر، ایس کیو ایل۔ کنکشن پائپ ہے، کرسر اس پائپ میں چل کر حکم چلاتا ہے۔

CHECK YOURSELF

1. Which object executes `SELECT *` ?
2. Is SQLite a driver, a database, or both?

Write your answers in your notebook. The key follows this chapter's exam.

4.3 Pandas and DataFrames ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 02 of 07 · 90 min · full Golden class. Board: Pandas is a third-party library for tables..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Pandas is a third-party library for tables. Install once: `pip install pandas` in the terminal (not inside the `.py` file). Convention: `import pandas as pd`.

A **DataFrame** is a 2-D table of rows and columns, like Excel or an SQL table. You can filter, sort and calculate whole columns without writing a `for` loop.

```
import pandas as pd
data = {
    "Name": ["Ali", "Sara", "Ahmed"],
    "Math": [85, 90, 78],
    "Science": [80, 88, 70],
}
df = pd.DataFrame(data)
print(df)
```

OUTPUT

	Name	Math	Science
0	Ali	85	80
1	Sara	90	88
2	Ahmed	78	70

`read_csv('students.csv')` and `read_excel('students.xlsx', sheet_name='Sheet1')` load files. `df.head()` prints the first five rows — use it on large files so you do not flood the screen.

```
df["Total"] = df["Math"] + df["Science"]
df["Average"] = df["Total"] / 2
print(df)
```

OUTPUT

	Name	Math	Science	Total	Average
0	Ali	85	80	165	82.5
1	Sara	90	88	178	89.0
2	Ahmed	78	70	148	74.0

WORKED EXAMPLE

Check: Ali $85+80=165$, $165/2=82.5$. Sara $90+88=178$, 89.0 . Ahmed $78+70=148$, 74.0 .

اردو میں سمجھیں

پینڈا ڈیٹا فریم دیتا ہے۔ ڈکشنری، سی ایس وی یا ایکسل سے لوڈ کریں۔ نئے کالم بغیر لوپ کے پوری قطار پر حساب کر کے بنتے ہیں۔ `head()` صرف پہلی پانچ قطاریں دکھاتا ہے۔

CHECK YOURSELF

1. What is `pd`?
2. Why not `print(df)` on a million-row file?

Write your answers in your notebook. The key follows this chapter's exam.

4.3.3 Handling Missing Values (NaN) ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 03 of 07 · 90 min · full Golden class. Board: Missing cells are NaN ("Not a Number")..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Missing cells are **NaN** ("Not a Number"). Statistics crash or lie if you ignore them. Three tools: `isnull()` (True where empty), `fillna(value)` (replace), `dropna()` (delete the row).

```
import pandas as pd
df = pd.DataFrame({
    "Name": ["Ali", "Sara", "Ahmed", "Ayesha"],
    "Marks": [85.0, None, 78.0, 92.0],
    "Grade": ["A", "A", None, "A"],
})
print(df.isnull().sum())
```

OUTPUT

```
Name      0
Marks      1
Grade      1
dtype: int64
```

WORKED EXAMPLE

Replace Marks with the mean of the known marks, and Grade with a label. Known marks 85, 78, 92
 $\rightarrow \text{mean} = 255/3 = \mathbf{85.0}$.

```
avg = df["Marks"].mean()          # 85.0
df["Marks"] = df["Marks"].fillna(avg)
df["Grade"] = df["Grade"].fillna("Not Assigned")
print(df)
```

OUTPUT

	Name	Marks	Grade
0	Ali	85.0	A
1	Sara	85.0	A
2	Ahmed	78.0	Not Assigned
3	Ayesha	92.0	A

`df = df.dropna()` would instead delete Sara's row and Ahmed's row (any row that still had a NaN).

EXAM TIP

State: identify with `isnull / sum`, fill numeric gaps with the mean, fill categories with a label, or drop rows if filling would invent a lie. Never analyse first and clean second.

COMMON MISTAKE

Filling a salary gap with the mean of a company that includes the CEO can hide poverty (the same outlier problem as the mean). Know *why* the value is missing before you fill.

اردو میں سمجھیں

خالی خانے NaN ہیں۔ `isnull` تلاش، `fillna` بھرنا (اکثر اوسط سے)، `dropna` قطار ہٹانا۔ پہلے صاف کرو، پھر تجزیہ۔

CHECK YOURSELF

1. What does `df.isnull().sum()` return?
2. Does `dropna()` delete a column or a row by default?

Write your answers in your notebook. The key follows this chapter's exam.

4.5 Data Visualization and Types of Graphs ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 04 of 07 · 90 min · full Golden class. Board: Pick the graph that matches the question..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Pick the graph that matches the question. Then label axes and give a title — an unlabelled chart scores zero in an exam.

Chart	Shows	Watch out
Bar / column	Compare discrete categories (subjects, departments)	Column = vertical; bar often = horizontal
Line	Change over time (temperature, visitors)	Needs an ordered x-axis (months, years)
Pie	Parts of one whole as percentages	Bad with many or almost-equal slices
Histogram	Distribution of one numeric variable in bins	Bars touch (continuous range), unlike a bar chart
Scatter	Relationship of two numeric variables	Each dot is one pair (x, y)
Box plot	Min, Q1, median, Q3, max, and outliers	Best tool for spotting extreme values

4.5.1 Bar / column

```
import matplotlib.pyplot as plt
subjects = ["English", "Math", "Science", "History"]
marks = [64, 82, 71, 49]
plt.bar(subjects, marks, color="skyblue", edgecolor="black")
plt.title("Marks vs Subjects")
plt.xlabel("Subjects")
plt.ylabel("Marks out of 100")
```

4.5.2 Line

```
months = ["Jan", "Feb", "Mar", "Apr", "May", "Jun"]
temps = [12, 15, 20, 25, 30, 35]
plt.plot(months, temps, marker="o")
plt.title("Average Monthly Temperature")
plt.grid(True)
```

4.5.3 Pie

```
subjects = ["Math", "Physics", "CS", "Biology"]
students = [25, 15, 30, 10] # total 80
plt.pie(students, labels=subjects, autopct="%1.1f%%", startangle=90)
```

Check: Math $25/80 = 31.25\% \rightarrow 31.2\%$. Physics 18.8% . CS 37.5% . Biology 12.5% .

4.5.4 Histogram

```
scores = [45, 50, 55, 60, 62, 65, 68, 70, 72, 75, 78, 80, 82, 85, 90, 95]
plt.hist(scores, bins=[40, 50, 60, 70, 80, 90, 100], edgecolor="black")
```

4.5.5 Scatter

```
plt.scatter([10, 20, 30, 40, 50, 60, 70, 80],
            [2, 4, 5, 4, 7, 8, 9, 12], color="green", alpha=0.7)
plt.title("Rainfall vs Crop Yield") # positive correlation
```

4.5.6 Box plot

```
plt.boxplot([[55, 60, 65, 70, 75, 80, 85],
            [40, 65, 70, 72, 75, 80, 95]],
            tick_labels=["Class A", "Class B"])
```

The box is the middle 50% (Q1 to Q3). The line inside is the median. Whiskers reach min and max (or a fence, with outliers drawn as dots). Class B is more spread out than Class A.



Column compares; line shows a trend; pie shows share; the box summarises spread around the median.

EXAM TIP

"Which graph and why?" is a 3-mark gift. Write the name, what it shows, and one reason the others are worse.

اردو میں سمجھیں

بار/کالم اقسام کا موازنہ، لائن وقت کا رجحان، پائی حصے، ہسٹوگرام مسلسل تقسیم (بار آپس میں لگے)، اسکیٹر دو متغیرات کا تعلق، باکس پلاٹ پانچ اعداد اور آؤٹ لائنر۔

CHECK YOURSELF

1. Why do histogram bars touch?
2. Rainfall vs yield — which chart?

Write your answers in your notebook. The key follows this chapter's exam.

4.6 Descriptive Statistics ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 05 of 07 · 90 min · full Golden class. Board: Descriptive statistics squeeze a long list into a few honest numbers..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Descriptive statistics squeeze a long list into a few honest numbers. **Central tendency** asks "what is typical?". **Spread** asks "how mixed is the list?".

4.6.1 Mean, median, mode

Measure	How	Use when
Mean	Sum ÷ n. Uses every value.	Values sit close together. Example: ordinary test scores.
Median	Middle after sorting. Odd n: centre. Even n: mean of the two centre values.	Outliers would wreck the mean (CEO salary).
Mode	Most frequent value. May be none, one, or several.	Most popular choice (shoe size).

WORKED EXAMPLE

Marks 70, 80, 90. Mean = $240/3 = 80$.

Odd list 35, 10, 15, 70, 95. Sort: 10, 15, 35, 70, 95. Median = **35**.

Bottles sold 20, 25, 20, 30, 20, 25, 20. Mode = **20** (appears four times).

Outlier trap: nine people earn 10, one earns 1000. Mean = $1090/10 = 109$ (looks rich). Median = 10 (tells the truth).

4.6.2 Spread: range, variance, standard deviation, min, max

- **Min / max** — smallest and largest. Marks 70, 80, 90, 60, 75 → min 60, max 90.
- **Range** = max – min. Sales 120, 150, 180 → range 60.
- **Population variance** $\sigma^2 = \frac{1}{n} \sum (x_i - \mu)^2$.
- **Sample variance** s^2 uses $\div (n - 1)$. `pandas.Series.std()` uses the sample version.
- **Standard deviation** $\sigma = \sqrt{\sigma^2}$. Same units as the data (marks, not marks²). Low SD → tight, consistent. High SD → spread out, unpredictable.

$$\sigma^2 = \frac{1}{n} \sum_{i=1}^n (x_i - \mu)^2, \quad \sigma = \sqrt{\sigma^2}, \quad s^2 = \frac{1}{n-1} \sum_{i=1}^n (x_i - \bar{x})^2$$

WORKED EXAMPLE

Full working on 70, 80, 90. Mean $\mu = 80$. Deviations -10, 0, +10. Squares 100, 0, 100. Sum = 200.

Population variance $\sigma^2 = 200/3 = \mathbf{66.67}$ (2 d.p.). Population SD $\sigma = \sqrt{200/3} = \mathbf{8.16}$ (2 d.p.).

Sample variance $s^2 = 200/2 = \mathbf{100}$. Sample SD $s = 10$. That is what `pd.Series([70,80,90]).std()` returns.

EXAM TIP

Always state whether you used n or $n-1$. Show the sorted list for the median. For SD, show: mean → deviations → squares → divide → square root. A box plot pictures min, Q1, median, Q3, max of the same data.

COMMON MISTAKE

Do not report variance as if it were in “marks”. Variance is marks². Quote the standard deviation when you want a sentence in the original units.

اردو میں سمجھیں

اوسط سب کا مجموعہ تقسیم تعداد، میڈین ترتیب کے بعد بیچ، موڈ سب سے زیادہ بار آنے والا۔ رینج بڑا منفی چھوٹا۔ ویرینس اوسط سے فاصلوں کے مربع کی اوسط ہے، معیاری انحراف اس کا جذر ہے اور اصل اکائی میں ہوتا ہے۔ پینڈاز `std()` نمونے والا $(n-1)$ استعمال کرتا ہے۔

CHECK YOURSELF

1. Median of 4, 8, 6, 10, 2?
2. Range of 120, 150, 180?
3. Does `pandas .std()` divide by n or $n-1$?

Write your answers in your notebook. The key follows this chapter's exam.

4.1 Concept of Data Analysis

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 06 of 07 · 45 min · first half · with Creating a SQLite Database in Python. Board: Data analysis is examining, organising and interpreting data so you can extract useful information..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Data analysis is examining, organising and interpreting data so you can extract useful information. Schools study results, shops study sales, hospitals study patient records — all to make a decision, spot a trend or solve a problem.

Python is popular for this work because it is readable, talks to files and databases, does statistics, and draws graphs. Five lines of Pandas often replace an hour of spreadsheet clicking.

WORKED EXAMPLE

A Hyderabad college has 400 CS marks in a spreadsheet. Analysis answers: What is the average? How many failed? Is the second shift weaker than the first? The numbers are data; those answers are information.

اردو میں سمجھیں

ڈیٹا کا تجزیہ یعنی اعداد کو ترتیب دے کر ان سے فیصلے کے قابل معلومات نکالنا۔ پائٹھن اس لیے منتخب کیا جاتا ہے کہ وہ فائلیں، ڈیٹا بیس، حساب اور گراف سب سنبھال لیتا ہے۔

CHECK YOURSELF

1. Give one school use of data analysis.
2. Name two Python superpowers for analysis.

Write your answers in your notebook. The key follows this chapter's exam.

4.2 Creating a SQLite Database in Python

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 06 of 07 · 45 min · second half · with Concept of Data Analysis. Board: SQLite is built into Python..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

SQLite is built into Python. The whole database is one `.db` file next to your script — no password, no port, no server. Nine steps you must be able to write from memory:

```
import sqlite3
conn = sqlite3.connect("school.db")    # 1-2  driver + connection
cur = conn.cursor()                   # 3    cursor
cur.execute("CREATE TABLE IF NOT EXISTS students (id INTEGER, name TEXT, marks
INTEGER)")
cur.execute("INSERT INTO students VALUES (1, 'Ali', 85)")
conn.commit()                         # 6    SAVE or the row vanishes
cur.execute("SELECT * FROM students")
rows = cur.fetchall()
for r in rows:
    print(r)
conn.close()                          # 9    unlock the file
```

OUTPUT

```
(1, 'Ali', 85)
```

Step	Why it matters
<code>connect</code>	Creates the file if it does not exist
<code>cursor</code>	Vehicle that carries SQL
<code>execute</code>	Runs one SQL command
<code>commit</code>	Writes INSERT/UPDATE/DELETE to disk
<code>fetchall</code>	Brings SELECT results into a Python list of tuples
<code>close</code>	Frees memory and unlocks the file

COMMON MISTAKE

Forgetting `commit()` is the classic bug: the program prints nothing next time because the insert was never saved. Forgetting `close()` can lock `school.db` so the next run fails.

REMEMBER IT

Strings inside SQL use single quotes: `'Ali'`. Python strings around the SQL use double quotes (or a triple-quoted string).

اردو میں سمجھیں

ایس کیو لائٹ پائنتھن کے ساتھ آتی ہے، پورا ڈیٹا بیس ایک فائل ہے۔ ترتیب: امپورٹ، کنکٹ، کرسر، EXECUTE، COMMIT, SELECT, FETCHALL, CLOSE نہ ہو تو اندراج ضائع ہو جاتا ہے۔

CHECK YOURSELF

1. What does `*` mean in `SELECT *`?
2. Which call must follow `INSERT`?

Write your answers in your notebook. The key follows this chapter's exam.

4.4 Data Organization and Representation

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 07 of 07 · 45 min · first half · with Career Opportunities. Board: Organised data is easier to read..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Organised data is easier to read. Three everyday forms:

- **Table** — exact values side by side (Ali 85 Math, 80 Science).
- **Frequency distribution** — how many items fall in each range (bin).
- **Graph** — a picture of a trend or comparison (next topics).

Range of marks	Frequency (students)
50–59	5
60–69	7
70–79	9
80–89	4
90–100	2

Most students scored 70–79. That pattern is hard to see in a raw list of 27 marks, and obvious in this table. Matplotlib (`import matplotlib.pyplot as plt`) turns tables into graphs: `import` → `figure` → `plot` → `labels` → `title` → `show()`.

اردو میں سمجھیں

ٹیبل درست عدد دکھاتی ہے، تعدد کی جدول بتاتی ہے کتنے طلبہ کس رینج میں ہیں، گراف رجحان دکھاتا ہے۔ میٹپلاٹ لب گراف بناتی ہے۔

CHECK YOURSELF

1. How many students scored 80 or above in the table?
2. Name the library that draws graphs in Python.

Write your answers in your notebook. The key follows this chapter's exam.

Career Opportunities

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 07 of 07 · 45 min · second half · with Data Organization and Representation. Board: The skills in this chapter map onto real jobs: data analyst (Pandas, Excel), database administrator (SQLite/MySQL), data scientist (statistics + modelling), visualisation specialist (Matplotlib, Power BI), business-intelligence analyst (dashboards for managers), backend developer (the code that talks to the database)..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

The skills in this chapter map onto real jobs: data analyst (Pandas, Excel), database administrator (SQLite/MySQL), data scientist (statistics + modelling), visualisation specialist (Matplotlib, Power BI), business-intelligence analyst (dashboards for managers), backend developer (the code that talks to the database).

اردو میں سمجھیں

یہ باب ڈیٹا اینالسٹ، ڈیٹا بیس ایڈمن، ڈیٹا سائنسدان، ویژولائزیشن اور بیک اینڈ ڈویلپر جیسے کیریئرز کی بنیاد ہے۔

Data and Analysis

9 single-page lessons · 5 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- Data analysis turns raw facts into decisions. Python reads files and databases, calculates and plots.
- Connection chain: database → driver → connection → cursor → SQL.
- SQLite: connect, cursor, execute, commit, fetchall, close. No commit means no save.
- A DataFrame is a 2-D table. Load with a dictionary, `read_csv` or `read_excel`. New columns are vectorised arithmetic.
- NaN: find (`isnull`), fill (`fillna` , often with the mean), or drop (`dropna`).
- Tables give exact values; frequency bins show how many in each range.
- Bar/column = categories; line = time; pie = parts of a whole; histogram = numeric distribution (touching bars); scatter = two variables; box = five-number summary + outliers.
- Mean uses every value and is sensitive to outliers; median is the middle; mode is the most common.
- Range = max–min. Variance = mean squared deviation ($\div n$ or $\div n-1$). SD = $\sqrt{\text{variance}}$. pandas `.std()` uses $n-1$.

Key terms

Term	Meaning	اردو
Data analysis	Examining data to extract useful information.	ڈیٹا کا تجزیہ
Connectivity	Link between a program and a data source.	رابطہ کاری
Driver	Translator between Python and a DBMS.	ڈرائیور
Connection	Open pipeline to the database.	کنکشن
Cursor	Object that executes SQL and fetches rows.	کرسر
SQLite	Built-in file-based database.	ایس کیو لائٹ
commit	Save INSERT/UPDATE/DELETE to disk.	کمیت / محفوظ کرنا
Pandas	Library for table-like data.	پینڈا
DataFrame	2-D labelled table of rows and columns.	ڈیٹا فریم
NaN	Missing value ("Not a Number").	خالی / غیر موجود قدر
Frequency	How many items fall in a class/bin.	تعدد
Histogram	Distribution chart whose bars touch.	ہسٹوگرام

Data and Analysis

75 marks · 1 hour 15 minutes · no notes · no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 09 and the recap. **Section A** — all 15 MCQs (1 mark).

Section B — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define · Explain · Example · Diagram · Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. The object that executes SQL is the:
 - a. driver
 - b. cursor
 - c. DataFrame
 - d. histogram
2. After INSERT you must:
 - a. close then commit
 - b. commit
 - c. drop the table
 - d. call head()
3. Pandas is installed with:
 - a. import pandas
 - b. pip install pandas
 - c. sqlite3.connect
 - d. plt.show()
4. `df.head()` shows:
 - a. the last 5 rows
 - b. the first 5 rows
 - c. only NaNs
 - d. the standard deviation
5. Missing Pandas values appear as:
 - a. NULL in every chart
 - b. NaN
 - c. 0 always
 - d. a pie slice
6. To delete every row that contains a gap:
 - a. fillna
 - b. dropna
 - c. fetchall
 - d. commit
7. A line graph is best for:
 - a. parts of a whole
 - b. a trend over months
 - c. two unrelated categories
 - d. a primary key
8. Histogram bars:
 - a. must have gaps
 - b. touch, because bins are a continuous range
 - c. always show time
 - d. replace the mean
9. Rainfall vs crop yield is a:
 - a. pie chart
 - b. scatter plot
 - c. primary key
 - d. mode
10. A box plot's inner line is the:
 - a. mean
 - b. mode
 - c. median
 - d. range
11. Mean of 70, 80, 90 is:
 - a. 70
 - b. 80
 - c. 90
 - d. 240
12. Median of 10, 15, 35, 70, 95 is:
 - a. 10
 - b. 35
 - c. 70
 - d. 45
13. Mode of 20, 25, 20, 30, 20, 25, 20 is:
 - a. 25
 - b. 30
 - c. 20
 - d. 7
14. Range of 120, 150, 180 is:
 - a. 30
 - b. 60
 - c. 150
 - d. 180
15. pandas `.std()` divides by:
 - a. n
 - b. n-1
 - c. 2n
 - d. zero

Section B — Short questions (10 × 3 = 30)

1. List the five components of a Python database connection in order.
2. Why is `conn.commit()` required after INSERT?
3. What is a DataFrame? How do you load a CSV into one?
4. Differentiate `fillna` and `dropna`.
5. When is a pie chart a poor choice?
6. Differentiate a bar chart and a histogram.
7. Why is the median better than the mean for company salaries?
8. Define range, min and max with the list 70, 80, 90, 60, 75.
9. Why do we take the square root of variance?
10. State two careers that use this chapter's skills.

Section C — Long questions (attempt any 3 × 10 = 30)

1. Write a complete Python program that creates `school.db`, a `students` table, inserts Ali 85 and Sara 90, commits, prints all rows, and closes. Number the five connection components beside the matching lines.
2. Starting from the dictionary of Ali/Sara/Ahmed marks, write Pandas code to build a DataFrame, add Total and Average columns, and print it. Show the exact output.
3. Given Marks [85, None, 78, 92] and Grade ["A", "A", None, "A"], show `isnull().sum()`, then fill Marks with the mean and Grade with "Not Assigned". Compute the mean by hand.
4. For each goal pick a chart and justify in one sentence: (a) CS vs IT vs Eng enrolment, (b) website hits from Jan to Jun, (c) share of four clubs in one college, (d) distribution of 200 heights, (e) hours studied vs marks, (f) comparing spread of two classes.
5. For 4, 8, 6, 10, 2 compute mean, median, range, population variance and population SD. Show every step. Then say what pandas `.std()` would report instead.
6. Explain, with a numeric example, how an outlier distorts the mean but not the median. Link this to when you would draw a box plot.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

- 4.1 Concept of Data Analysis.** Answers: 1. Study results to improve teaching (or similar). 2. Any two: read CSV/Excel/databases, organise tables, statistics, charts.
- 4.1.1 – 4.1.2 Data Sources and Database Connection.** Answers: 1. The cursor. 2. SQLite is the database; the `sqlite3` module is the driver.
- 4.2 Creating a SQLite Database in Python.** Answers: 1. All columns. 2. `conn.commit()`.
- 4.3 Pandas and DataFrames.** Answers: 1. The usual alias for pandas. 2. It would print everything; use `df.head()`.
- 4.3.3 Handling Missing Values (NaN).** Answers: 1. Count of NaNs in each column. 2. Any **row** that contains at least one NaN.
- 4.4 Data Organization and Representation.** Answers: 1. $4 + 2 = 6$. 2. Matplotlib (pyplot).
- 4.5 Data Visualization and Types of Graphs.** Answers: 1. The x-axis is a continuous numeric range, not separate categories. 2. Scatter (two numeric variables, looking for correlation).
- 4.6 Descriptive Statistics.** Answers: 1. Sorted 2,4,6,8,10 $\rightarrow$ 6. 2. 60. 3. $n-1$ (sample).

Answer key

Multiple choice

1. b
2. b
3. b
4. b
5. b
6. b
7. b
8. b
9. b
10. c
11. b
12. b
13. c
14. b
15. b

Short questions — model answers

1. Database, driver, connection object, cursor object, SQL queries.
2. Without commit the insert stays in memory and disappears when the program ends, so the next run cannot see the row.
3. A 2-D table of labelled rows and columns. `df = pd.read_csv("file.csv")`.
4. `fillna(v)` replaces NaN with v (the row stays). `dropna()` deletes any row that still contains a NaN.
5. When there are many slices, or the values are almost equal, so the eye cannot compare them.
6. Bar: separate categories, gaps between bars. Histogram: one numeric variable grouped into bins; bars touch.
7. A huge CEO salary pulls the mean up; the median stays with the typical worker.
8. Min 60, max 90, range 30.
9. Variance is in squared units. The SD brings the spread back to the original units (marks, rupees, °C).
10. Any two: data analyst, DBA, data scientist, visualisation specialist, BI analyst, backend developer.

Long questions — model answers

1. Use the nine-step listing in 4.2 with two INSERTs. Label: `sqlite3` = driver, `connect` = connection, `cursor` = cursor, `execute strings` = SQL, `school.db` = database.
2. Output is the three-row table with Total 165, 178, 148 and Average 82.5, 89.0, 74.0 (see the worked example).
3. `isnull sum`: Marks 1, Grade 1. Mean of 85, 78, 92 = $255/3 = 85.0$. After fill: Sara Marks 85.0, Ahmed Grade "Not Assigned".
4. (a) column/bar — compare categories. (b) line — time. (c) pie — parts of a whole. (d) histogram — numeric distribution. (e) scatter — two numeric variables. (f) box — spread and outliers.
5. Sorted 2,4,6,8,10. Sum 30, mean 6, median 6, range 8. Deviations -4,-2,0,2,4. Squares 16,4,0,4,16 sum 40. $\sigma^2 = 40/5 = 8$. $\sigma = \sqrt{8} = 2.828$ (3 d.p.). pandas `.std()` uses $40/4 = 10$, $\sqrt{10} \approx 3.162$.
6. Nine salaries of 10 and one of 1000: mean 109, median 10. Draw a box plot — the 1000 appears as an outlier dot above the whisker, so the distortion is visible.

Self-assessment: I can...

- | | |
|--|--|
| ☐ name the five connection components in order. | ☐ write SQLite connect / create / insert / commit / select / close. |
| ☐ build a DataFrame and add a calculated column. | ☐ find, fill and drop missing values. |
| ☐ choose bar, line, pie, histogram, scatter or box for a problem. | ☐ compute mean, median, mode, range, variance and SD by hand. |
| ☐ state that pandas std uses $n-1$. | |

Application and Impacts of Computing

This chapter shows you how computers learn from data with machine learning, neural networks and deep learning, how to collaborate online without leaking secrets, how to protect data and stop cyber threats, and how to keep digital teamwork fair for every student in Sindh.

اس باب میں آپ سیکھیں گے کہ مشین لرننگ، نیورل نیٹ ورکس اور ڈیپ لرننگ کمپیوٹر کو ڈیٹا سے کیسے سکھاتے ہیں، آن لائن کام کو محفوظ کیسے رکھا جائے، ڈیٹا کی حفاظت اور سائبر خطرات کا مقابلہ کیسے کیا جائے، اور ڈیجیٹل تعاون کو سب کے لیے منصفانہ کیسے بنایا جائے۔

What you will learn

- Define **machine learning (ML)** and describe the three steps: data input, learning, prediction.
- Define **deep learning (DL)** and draw the relationship **AI $\supset$ ML $\supset$ DL**.
- List the six components of deep learning and give applications of NN and DL in daily life and in Pakistan.
- Protect data using encryption (including a Caesar cipher), strong passwords, the 3-2-1 backup rule and a firewall.
- Distinguish **equal access** from **equity** and describe the functions of equity in digital collaboration.
- Explain a **neural network (NN)** as a brain-inspired model with an input layer, hidden layers and an output layer.
- Name the eight components of a neural network and compute a neuron's output from given numbers.
- Explain **secure collaboration**: authentication, multi-factor authentication (MFA) and access control.
- Identify common threats (malware, phishing, DoS) and apply mitigation techniques.
- Name common collaboration tools and use them fairly and safely.

GOLDEN CONCEPTS

★ **Golden concepts in this chapter.** These ideas are taught first as lecture notes. If time is short, lock these before the other notes, then sit the chapter exam.

- ★ **5.1.2 Neural Networks (NN).** A neural network is a computer model that learns patterns from data.
- ★ **5.1.4 Components of Neural Networks.** The components of a neural network can be understood through its layered architecture.
- ★ **5.3.1 Secure Collaboration (Authentication, MFA, Access Control).** Digital tools allow people to share files, attend online classes, edit documents and work together from different locations.
- ★ **5.4.1 Common Security Threats (Malware, Phishing, DoS).** A security threat is any action, event or weakness that can harm a computer system or its data.
- ★ **5.5.1 Functions of Equity and Equal Access.** Equity and equal access are not slogans.

اس باب کے گولڈن تصورات پہلے پڑھیں۔ باقی نوٹس بعد میں۔

STUDENT · COACH

Self-taught. 17 notes · 5 ★ first · about 6 h 5 min. After the last note, sit the chapter exam (75 marks, 1 h 15 min).

Coach / teacher. 11 academy classes of 90 minutes (each ★ Golden is a full class; other notes pair). School: ★ = one 40-minute period.

ACADEMY CALENDAR**Chapter 5 academy calendar.**

Class	Topics	Kind
Class 01	Neural Networks (NN)	★ 90 min
Class 02	Components of Neural Networks	★ 90 min
Class 03	Secure Collaboration (Authentication, MFA, Access Control)	★ 90 min
Class 04	Common Security Threats (Malware, Phishing, DoS)	★ 90 min
Class 05	Functions of Equity and Equal Access	★ 90 min
Class 06	Machine Learning, Neural Networks and Deep Learning + Machine Learning (ML)	90 min
Class 07	Deep Learning (DL) + Components of Deep Learning	90 min
Class 08	Future of AI, NN and DL in Pakistan + Applications of Neural Networks and Deep Learning	90 min
Class 09	Data Protection (Encryption, Passwords, Backup, Firewall) + Identifying Security Threats	90 min
Class 10	Apply Mitigation Techniques + Equity and Equal Access in Digital Collaboration	90 min
Class 11	Collaboration Tools + Career Opportunities	90 min

5.1.2 Neural Networks (NN) ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 01 of 11 · 90 min · full Golden class. Board: A neural network is a computer model that learns patterns from data..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **neural network** is a computer model that **learns patterns from data**. It is **directly inspired by the human brain**, but it works as a **mathematical computer system** — not as living tissue.

Your brain has billions of nerve cells (**neurons**) that pass signals to each other. A neural network copies this idea with small processing units also called **neurons** or **nodes**. These nodes are **connected** and **pass information from one layer to another**, performing calculations at each step.

A typical neural network has three kinds of layer:

- **Input layer** — receives the raw data (pixels of a face, samples of a sound, marks of a student).
- **Hidden layer(s)** — the “thinking” in the middle. Nodes here combine the inputs and learn features (eye distance, nose shape, an edge in a photo).
- **Output layer** — gives the final answer (unlock / keep locked; “this is a cat”; “pass / fail”).

Input layer → Hidden layer(s) → Output layer

WORKED EXAMPLE

Practical example from the source: face unlock.

Step 1 — Input layer. You look at your phone. The camera captures your face as numbers (brightness of each pixel). Those numbers enter the input layer.

Step 2 — Hidden layers. The system studies face features such as **eye distance** and **nose shape**. Early hidden nodes may detect edges and shadows; later hidden nodes combine those into “this looks like Sara’s face.” It compares them with stored data from when you first set up the phone.

Step 3 — Output layer. If the features match, the phone **unlocks**. If they do not (your brother holds the phone), it stays locked.

The same three-layer story works for an NADRA-style biometric gate at a college: camera (input) → feature matching (hidden) → open the turnstile or not (output).

REMEMBER IT

I-H-O. Input receives, Hidden thinks, Output decides. "In Hidden Out." A neural network is a **brain-inspired maths machine**, not a copy of a living brain.

COMMON MISTAKE

Mistake: "A neural network is an actual human brain inside the computer."

Fix: It is only **inspired by** the brain. It is mathematics: numbers, multiplications and additions running on ordinary hardware.

اردو میں سمجھیں

نیورل نیٹ ورک ایک کمپیوٹر ماڈل ہے جو ڈیٹا سے پیٹرن سیکھتا ہے۔ یہ انسانی دماغ سے متاثر ہے مگر ایک ریاضیاتی نظام کے طور پر کام کرتا ہے۔ چھوٹی اکائیاں نیورون یا نوڈ کہلاتی ہیں، جو تہوں میں جڑی ہوتی ہیں: ان پٹ تہ ڈیٹا لیتی ہے، پوشیدہ تہ سوچتی ہے، اور آؤٹ پٹ تہ فیصلہ دیتی ہے — جیسے چہرے سے فون کھولنا۔

EXAM TIP

Very common questions: "What is a neural network?" (2–3 marks), "Name its three layers and explain each with the face-unlock example" (5 marks), and "How is a neural network related to the human brain?"

Full-mark recipe: (1) definition — computer model that learns patterns from data, inspired by the brain, mathematical; (2) neurons/nodes connected across layers; (3) Input / Hidden / Output, each in one sentence; (4) walk the camera → features (eye distance, nose shape) → unlock path. Draw the three boxes if the paper asks for a diagram.

CHECK YOURSELF

1. What are the small processing units of a neural network called?
2. In face unlock, which layer studies eye distance and nose shape?
3. Is a neural network a living brain? Explain in one sentence.

Write your answers in your notebook. The key follows this chapter's exam.

5.1.4 Components of Neural Networks ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 02 of 11 · 90 min · full Golden class.
Board: The components of a neural network can be understood through its layered architecture..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

The components of a neural network can be understood through its **layered architecture**. Data **enters**, gets **processed**, and **exits**, with mathematical adjustments happening inside.


#	Component	Description
1	Input layer	Receives the initial raw data (for example image pixels, sound waves, text).
2	Neurons / nodes	Small processing units that receive, calculate, and pass information forward.
3	Hidden layer(s)	The layers between input and output. They process the data and learn patterns from it.
4	Weights	Numbers that show the importance or strength of connections between neurons.
5	Bias	An extra constant value added to help the model adjust its result and improve accuracy.
6	Activation function	A mathematical gate that decides whether the information is important enough to move to the next layer.
7	Output layer	Gives the final computed result, decision or prediction (for example "This is a cat").
8	Loss function	Checks the error (how much the model's answer is wrong compared with reality) so the network can correct itself.

What happens inside one neuron


Each neuron does a short calculation:

1. Multiply each input x by its weight w .
2. Add those products together, then add the **bias** b . This total is the **weighted sum** s .
3. Pass s through an **activation function**. A simple exam-friendly gate is a **threshold (step) function**: if s is at least the threshold, the neuron **fires** (output = 1); otherwise output = 0.

In symbols: $s = (x_1 \times w_1) + (x_2 \times w_2) + \dots + b$, then $y = 1$ if $s \geq \text{threshold}$, else $y = 0$.



One neuron: inputs $\times$ weights are summed, bias is added, then an activation function decides the output y .



A small neural network: 3 input nodes, 4 hidden nodes, 2 output nodes. Each line is a weighted connection.

WORKED EXAMPLE

Worked example: neuron calculation with numbers. A college in Larkana uses a tiny network to guess whether a student is ready for a test. One hidden neuron receives two inputs:

Symbol	Meaning	Value
x1	Hours studied yesterday (scaled 0 to 1)	0.8
x2	Attendance this month (scaled 0 to 1)	0.5
w1	Weight of hours studied	0.4
w2	Weight of attendance	0.6
b	Bias	0.1
threshold	Activation gate	0.5

Step 1 — weighted products.

$$x1 \times w1 = 0.8 \times 0.4 = \mathbf{0.32}$$

$$x2 \times w2 = 0.5 \times 0.6 = \mathbf{0.30}$$

Step 2 — add bias to get the weighted sum s.

$$s = 0.32 + 0.30 + 0.1 = \mathbf{0.72}$$

Step 3 — activation (threshold 0.5). Is $0.72 \geq 0.5$? **Yes**, so the neuron fires: **y = 1** (ready for the test).

Step 4 — a second student with $x1 = 0.2$ (almost no study) and $x2 = 0.3$:

$$s = (0.2 \times 0.4) + (0.3 \times 0.6) + 0.1 = 0.08 + 0.18 + 0.1 = \mathbf{0.36}$$

0.36 is **less than** 0.5, so **y = 0** (not ready). The same neuron, different inputs, different decision.

You can check the first student in Python 3:

```
x1, x2 = 0.8, 0.5
w1, w2 = 0.4, 0.6
b = 0.1
s = x1 * w1 + x2 * w2 + b
y = 1 if s >= 0.5 else 0
print(round(s, 2))
print(y)
```

OUTPUT

```
0.72
1
```

Loss function, briefly. If the true answer for the first student was actually “not ready” (true $y = 0$) but the model said 1, the loss is high. Training then slightly changes weights and bias so the next guess is closer to reality.

REMEMBER IT

Weights = importance. Bias = extra nudge. Activation = yes/no gate. Loss = how wrong. A large weight means that input matters more. Bias shifts the sum up or down so the gate can open at the right place.

COMMON MISTAKE

Mistake: Forgetting to add the bias, or multiplying instead of adding after the products.

Fix: Always **multiply first** (each x by its w), **then add** the products, **then add b** , **then** apply the activation. Write the four lines in the exam as we did above.

اردو میں سمجھیں

نیورل نیٹ ورک کے اجزاء ہیں: ان پٹ تہ، نیورون، پوشیدہ تہ، وزن (Weights)، بائیس (Bias)، ایکٹیویشن فنکشن، آؤٹ پٹ تہ اور لاس فنکشن۔ ہر نیورون ان پٹ کو وزن سے ضرب دے کر جمع کرتا ہے، بائیس جوڑتا ہے، پھر ایک گیٹ فیصلہ کرتا ہے کہ سگنل آگے جائے یا نہیں۔ وزن تعلق کی طاقت بتاتا ہے؛ لاس فنکشن غلطی ناپتا ہے تاکہ ماڈل خود درست ہو سکے۔

EXAM TIP

Golden questions: "List the components of a neural network" (often 8 names + one line each), "What are weights and bias?", and a **numerical neuron**: given x , w , b and a threshold, find s and y .

Show every arithmetic step. Underline the final y . If asked for a diagram, draw Input $\rightarrow$ Hidden $\rightarrow$ Output with circles and connecting lines, and label weights on the lines. Mention the loss function as the component that measures error so the network can correct itself.

CHECK YOURSELF

1. What do weights show?
2. Using $x_1 = 1$, $x_2 = 0$, $w_1 = 0.5$, $w_2 = 0.5$, $b = 0$, threshold = 0.4, what is y ?
3. What does the loss function check?

Write your answers in your notebook. The key follows this chapter's exam.

5.3.1 Secure Collaboration (Authentication, MFA, Access Control) ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 03 of 11 · 90 min · full Golden class. Board: Digital tools allow people to share files, attend online classes, edit documents and work together from different locations..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Digital tools allow people to **share files, attend online classes, edit documents and work together from different locations**. Collaboration is useful only when **data is protected** and **communication remains safe**.

Secure collaboration means using digital tools to work together in a **safe, controlled and responsible** way. It depends on several key elements.

i) Authentication / identity verification

Authentication is **confirming the identity of a user before allowing access**. Common methods:

- **Username and password**
- **PIN** (a short number code)
- **OTP — One-Time Password**, a code that works only once, usually sent by SMS or an authenticator app
- **Biometrics** — fingerprint or face

Source example: a **banking app sending an OTP to your phone before login**.

Multi-factor authentication (MFA) and two-factor authentication (2FA)

A **factor** is a category of proof:

- **Something you know** — password or PIN.
- **Something you have** — your phone, an OTP, a bank SMS.
- **Something you are** — fingerprint, face (biometrics).

Multi-factor authentication (MFA) means the system asks for **two or more different factors** before it trusts you. **Two-factor authentication (2FA)** is the common case of MFA that uses **exactly two** factors — usually password + OTP.

If a thief in another city steals only your password, MFA still blocks them because they do not have your phone (or your fingerprint).

ii) Access control

Access control decides **what an authenticated user is allowed to do**: View, Edit, Comment, Download, Share.

Authentication answers **"Who are you?"** Access control answers **"What may you do?"**

Source example: a teacher shares a Google Doc with students as **"view only"**, but gives group leaders **"edit"** permissions.

iii) Accountability and tracking

User actions are linked to **verified accounts**. You can see who opened, edited, deleted or shared a file.

Example: a school **LMS** (Learning Management System) tracks which teacher uploaded an assignment and which student submitted it.

iv) Data privacy

Data privacy means protecting personal and sensitive information and using it **only for the purpose it was collected**. It involves:

- **Protection** — keeping names, numbers, marks and passwords secure.
- **Controlled sharing** — sharing only with the right people.
- **Confidentiality** — data stays private during storage and transmission.
- **Compliance** — following legal and ethical rules for data handling.

v) Safe communication / transmission

Exchanging information through digital platforms **securely**, protecting messages from unauthorised interception or wiretapping. Example: a teacher shares class instructions through an **official, encrypted LMS** rather than an open public forum or an unknown WhatsApp broadcast.

WORKED EXAMPLE

Worked example: a Class XII Google Classroom in Sukkur.

Step 1 — Authentication. Each student signs in with a school email and password. The college turns on MFA: after the password, Google sends an OTP to the student's registered Jazz/Zong number.

Step 2 — Access control. All 40 students can **view** the assignment sheet. Only the four group leaders can **edit** the shared report. Nobody except the teacher can **delete** the class materials. A student who left the college is removed from the class (access revoked).

Step 3 — Accountability. Version history shows that Ali edited paragraph 2 at 8:14 pm and that Hina submitted the PDF at 9:02 pm.

Step 4 — Privacy and safe transmission. Marks stay inside Classroom; the teacher does not post CNIC numbers or phone numbers in a public Facebook group. Traffic to Google is encrypted, unlike an open public forum.

If Ali shares his password with a cousin, authentication is broken. If the teacher gives every student "edit" on the marksheet, access control is broken even though login still works.

REMEMBER IT

A-A-A-P-S. Authentication, Access control, Accountability, Privacy, Safe transmission. MFA = at least two different factor types (know / have / are). 2FA is MFA with two factors.

COMMON MISTAKE

Mistake: Treating authentication and access control as the same thing.

Fix: Login only proves identity. After login, access control still limits View / Edit / Comment / Download / Share. A student who is authenticated must not automatically get teacher rights.

اردو میں سمجھیں

محفوظ تعاون کا مطلب ہے ڈیجیٹل ٹولز سے محفوظ، کنٹرول شدہ اور ذمہ دارانہ انداز میں ساتھ کام کرنا۔ تصدیق (Authentication) یہ جانچتی ہے کہ صارف کون ہے، رسائی کنٹرول (Access Control) یہ طے کرتا ہے کہ وہ کیا کر سکتا ہے (صرف دیکھنا، ترمیم، تبصرہ)۔ کثیر عنصری تصدیق (MFA) دو یا زیادہ مختلف ثبوت مانگتی ہے، جیسے پاس ورڈ اور او ٹی پی (OTP)۔ حساب دہی، ڈیٹا پرائیویسی اور محفوظ ترسیل بھی ضروری ہیں۔

EXAM TIP

Typical items: "Define secure collaboration", "Differentiate authentication and access control", "What is MFA/2FA?", "Explain five elements of secure collaboration with examples."

Write the five headings (authentication, access control, accountability, privacy, safe transmission). For MFA, name the three factor types and say that 2FA is password + OTP in a banking app. Use the Google Doc "view only vs edit" example — examiners look for it.

CHECK YOURSELF

1. What question does authentication answer, and what question does access control answer?
2. Password + OTP is an example of which idea?
3. Give the source example of access control in a Google Doc.

Write your answers in your notebook. The key follows this chapter's exam.

5.4.1 Common Security Threats (Malware, Phishing, DoS)

★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 04 of 11 · 90 min · full Golden class. Board: A security threat is any action, event or weakness that can harm a computer system or its data..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **security threat** is any action, event or weakness that can **harm a computer system or its data**. **Mitigation techniques** are protective measures used to prevent threats or reduce their impact. This section names the common threats; later sections show how to spot them and how to reduce the damage.

#	Threat	What it is	Example
1	Malware	Harmful software designed to damage a computer, steal data, or gain unauthorised access. Includes viruses, worms, spyware, ransomware and Trojans .	Installing cracked software that secretly corrupts files, or a "free game" USB that encrypts a college lab's coursework (ransomware).
2	Phishing	A social-engineering trick that deceives users into sharing personal information (passwords, bank details, OTPs) using fake emails or websites that look genuine.	An SMS that looks like JazzCash or HBL asking you to "verify" by typing your OTP on a fake page.
3	Unauthorised access	Entering a system, account or file without permission. Often caused by weak passwords, shared passwords, or leaving devices unlocked.	A classmate using an unlocked lab PC to open someone else's Google Classroom.
4	Data theft / identity theft	Data theft is stealing or copying data without permission. Identity theft is using another person's stolen details (name, CNIC, bank details) to pretend to be them online and commit fraud.	A leaked list of CNICs used to open a SIM or a wallet in someone else's name.
5	Denial of Service (DoS)	A website or system is flooded with thousands of fake requests, causing it to slow down or crash, so real users cannot access the service.	Hackers flooding an online exam portal so students cannot log in on BISE result day or during an e-test.
6	Human error	Mistakes by legitimate users: accidentally deleting files, sending confidential data to the wrong email, or falling for a simple scam.	A teacher emailing the whole marksheet to the wrong parent; a student forwarding an OTP "to help the bank."

Malware types in one line each: a **virus** attaches to files and spreads when you share them; a **worm** spreads by itself across a network; **spyware** secretly watches you; **ransomware** locks your files and demands money; a **Trojan** pretends to be useful software but hides harm.

Social engineering means tricking a **person**, not breaking a lock with maths. Phishing is the most common exam example.

Phishing Fake bank email / SMS steals password or OTP	DoS attack Flood of fake requests server overload / crash	Identity theft Stolen CNIC / details fraud in your name
--	--	--

Three high-yield threats: phishing (fake messages), DoS (server overload), identity theft (stolen CNIC or bank details).

WORKED EXAMPLE

Worked example: classify the incident.

1. Bilal downloads a "cracked" Photoshop. Next day his project files are unreadable and a note asks for Bitcoin. → **Malware** (ransomware), started by cracked software.
2. Ayesha gets an email "Your Meezan account will close in 2 hours. Click here and send OTP." The link is meezn-pk.tk, not the real bank. → **Phishing**.
3. On e-test morning the college portal spins forever; the admin graph shows 200,000 requests from one pattern of fake traffic. → **DoS**.
4. Someone opens a JazzCash wallet using Ahmed's CNIC copy from a leaked form. → **Identity theft** (after data theft).
5. The lab assistant emails the password list to the whole staff by choosing the wrong group. → **Human error**.

REMEMBER IT

Malware = bad program. Phishing = fake message. DoS = flood. Identity theft = stolen 'you'. Human error = honest mistake. Cracked software and unknown USBs are the usual door for malware in Pakistani colleges.

COMMON MISTAKE

Mistake: Calling every cyber problem a "virus", or mixing phishing with malware.

Fix: A virus is only one kind of malware. Phishing is a **trick against the user**; it may not install any file at all. DoS does not steal your password — it makes the service unusable for everyone.

سیکیورٹی خطرہ وہ عمل یا کمزوری ہے جو نظام یا ڈیٹا کو نقصان پہنچاے۔ میلویئر نقصان دہ سافٹ ویئر ہے (وائرس، ورم، سپائی ویئر، رینسم ویئر، ٹروجن)۔ فشننگ جعلی ای میل یا ویب سائٹ سے پاس ورڈ اور او ٹی پی چھینتی ہے۔ ڈو ایس (DoS) جعلی درخواستوں کی بارش سے سائٹ کریش کر دیتا ہے۔ دیگر خطرات: غیر مجاز رسائی، ڈیٹا/شناخت کی چوری، اور انسانی غلطی۔

EXAM TIP

Expect "Define a security threat", "Explain malware / phishing / DoS with examples", and "Differentiate data theft and identity theft." List all six threats if the question says "common security threats." For DoS, write: flood of fake requests → slowdown or crash → real users blocked, and quote the online exam portal. For phishing, write social engineering + fake genuine-looking email/site + passwords/OTPs.

CHECK YOURSELF

1. Name five types of malware listed in the source.
2. What does a DoS attack do to a website?
3. How is identity theft different from data theft?

Write your answers in your notebook. The key follows this chapter's exam.

5.5.1 Functions of Equity and Equal Access ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 05 of 11 · 90 min · full Golden class. Board: Equity and equal access are not slogans..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Equity and equal access are not slogans. They **do work** in a digital classroom. The source lists four functions.

Function	What it does	Pakistani example
1. Providing need-based support (equity)	Help tailored to individuals.	Audio descriptions for visually impaired students; a screen reader so a blind student in Karachi can hear a digital textbook.
2. Removing barriers	Help students in remote areas attend online classes.	Mobile-friendly, low-data apps so a student in Tharparkar or the katcha areas of Sindh can join without a fibre connection.
3. Enabling active participation	Students who miss live class can still take part.	Recorded lectures so load-shedding or an internet outage in Hyderabad does not make a student fall behind.
4. Supporting different learning needs	Offer more than one format.	Videos, text notes and audio of the same Chapter 5 topic so each student learns in the way that suits them best.

WORKED EXAMPLE

Worked example: design four functions for one class WhatsApp + Classroom group in Nawabshah.

- Need-based support:** Ali is visually impaired — share materials as selectable text (not only photos) so a screen reader can speak them; add a short audio description of each diagram.
- Remove barriers:** post a 5 MB audio summary instead of a 200 MB video for students on expensive mobile data.
- Active participation:** upload the Zoom recording within an hour; students whose lights went out at 7 pm watch it at 11 pm.
- Different learning needs:** the same lesson as (a) a 12-minute video, (b) a one-page PDF, (c) an Urdu audio note.

Discussion from the source: if a teacher **only** accepts assignments via an app that needs a **high-end smartphone**, is that equal access? **No**. It creates a **hardware barrier** for lower-income students. Web-based or light apps give better access.

REMEMBER IT

Four functions: Support, Remove, Participate, Formats. “Some Rural Pupils Fail” without them — Support (need-based), Remove barriers, Participate via recordings, Formats (video/text/audio).

COMMON MISTAKE

Mistake: Describing only captions and stopping.

Fix: Examiners want all four functions. Include remote-area low-data apps, recorded lectures for power cuts, and multiple formats — these are in the Sindh source on purpose.

اردو میں سمجھیں

انصاف اور مساوی رسائی کے چار کام ہیں: ضرورت کے مطابق مدد (جیسے نابینا طالب علم کے لیے آڈیو وضاحت)، ریکارڈ (دور دراز علاقوں کے لیے کم ڈیٹا والی ایپس)، فعال شرکت ممکن بنانا (لوڈ شیڈنگ کے لیے ریکارڈ شدہ لیکچر)، اور مختلف اندازِ تعلیم کی حمایت (ویڈیو، متن، آڈیو)۔ مہنگے فون والی ایپ پر صرف اسی طرح اسائنمنٹ لینا مساوی رسائی نہیں۔

EXAM TIP

Golden question: “Explain the functions of equity and equal access in digital collaboration” (5–8 marks). Write the four headings in order, one example each, and add the hardware-barrier point (high-end app vs light/web app). Another favourite: “Differentiate equal access and equity with examples” — same login vs captions.

CHECK YOURSELF

1. List the four functions of equity and equal access.
2. How do recorded lectures enable active participation in Pakistan?
3. Why is a high-end-smartphone-only assignment unfair?

Write your answers in your notebook. The key follows this chapter's exam.

5.1 Machine Learning, Neural Networks and Deep Learning

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 06 of 11 · 45 min · first half · with Machine Learning (ML). Board: Machine learning (ML), neural networks (NN) and deep learning (DL) are important areas of artificial intelligence (AI)..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT


Machine learning (ML), neural networks (NN) and deep learning (DL) are important areas of **artificial intelligence (AI)**. **AI** is the broad field in which computers perform tasks that normally need human thinking, such as recognising a face, understanding speech or making a decision.

These technologies help computers **learn from data** and make useful decisions **without being explicitly programmed for every single step**. You do not write a separate rule for every possible face or every Urdu accent. You show the computer many examples, and it finds the patterns itself.

They are used in many modern systems:

- **Face unlock** on smartphones.
- **Speech recognition** (for example Siri, Alexa, or Urdu voice typing on a phone).
- **Photo search** categorisation (typing "car" in a gallery and seeing car photos).
- **Medical diagnosis** from X-rays and scans.
- **Language translation** (English to Urdu or Sindhi).

Remember the nesting: **AI is the biggest set**. Inside AI sits **ML**. Inside ML sits **DL**. Every deep-learning system is a kind of machine learning, and every machine-learning system is a kind of AI — but not every AI system is deep learning.



The set relationship $AI \supset ML \supset DL$. Deep learning is a method of machine learning; machine learning is a part of artificial intelligence.

WORKED EXAMPLE

Worked example: place each system in the correct set. Sara in Karachi uses three features on her phone.

1. **A chess app that follows fixed if-then rules** written by a programmer ("if the queen is attacked, move it"). This is **AI** (the machine decides), but it is **not ML**, because it does not learn from data.
2. **A JazzCash fraud filter** that was trained on thousands of past transactions and then flags a new unusual payment. This is **ML** (and therefore also AI). If it uses only a simple model with few layers, it may **not** be DL.
3. **Face unlock** that studied millions of face images through many hidden layers. This is **DL** — and therefore also ML and AI.

Exam sentence you can write: *All DL is ML, all ML is AI, but not all AI is ML, and not all ML is DL.*

REMEMBER IT

Russian-doll memory trick. Picture three boxes. The outer box is **AI**. Inside it is a smaller box **ML**. Inside that is the smallest box **DL**. You cannot take DL out of ML, and you cannot take ML out of AI.

COMMON MISTAKE

Mistake: "AI, ML and DL are three different, separate subjects."

Fix: They nest. $DL \subset ML \subset AI$. A deep-learning face-unlock system is all three at once.

اردو میں سمجھیں

مصنوعی ذہانت (AI) سب سے بڑا میدان ہے۔ اس کے اندر مشین لرننگ (ML) ہے، اور مشین لرننگ کے اندر ڈیپ لرننگ (DL) ہے۔ یہ ٹیکنالوجیز کمپیوٹر کو ڈیٹا سے سکھاتی ہیں تاکہ ہر قدم الگ الگ پروگرام کیے بغیر فیصلے کیے جا سکیں، جیسے چہرے سے فون کھولنا یا آواز پہچاننا۔

CHECK YOURSELF

1. Which is the largest set: AI, ML or DL?
2. Is every neural-network face-unlock system an example of AI? Why?
3. Give one modern system from this section that uses these technologies.

Write your answers in your notebook. The key follows this chapter's exam.

5.1.1 Machine Learning (ML)

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 06 of 11 · 45 min · second half · with Machine Learning, Neural Networks and Deep Learning. Board: A machine learning model is the system that learns from data and gives an output..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **machine learning model** is the system that **learns from data and gives an output**. Think of it as the **trained brain** of a computer program.

In ordinary programming you write every rule yourself: *if marks ≥ 40 then "Pass"*. In machine learning you **do not list every rule**. You give the model many examples (data), it finds the patterns, and later it decides about new cases it has never seen.

How it works — three steps:

1. Data input → 2. Learning (find patterns) → 3. Prediction on new data

1. **Data input.** The model is given massive amounts of data — for example thousands of past BISE marksheets, or millions of crop photos from Sindh fields.
2. **Learning.** It studies the data and **learns patterns and rules automatically**. It might notice that students who scored low in Chapter 3 also failed the board exam, or that yellow spots on cotton leaves often mean a pest.
3. **Prediction.** After training, it can make **accurate predictions or decisions** when given **new, unseen data** — a new student's record, or a new leaf photograph.

Note from the source: there are many types of machine-learning models. A **neural network** is one important type. **Deep learning** is a highly advanced method of machine learning.

WORKED EXAMPLE

Worked example: a wheat-yield model for a farm near Sukkur.

Step 1 — Data input. For 8 years the farm recorded: rainfall (mm), temperature, fertiliser bags used, and the actual yield (maunds per acre).

Step 2 — Learning. The model studies those rows. It finds, for example, that yield rises with fertiliser up to a point, and falls when temperature is very high in April.

Step 3 — Prediction. This year the farmer types in this season's rainfall and temperature. The model has never seen this exact year before, but it predicts "about 32 maunds per acre." The farmer plans storage and a buyer in advance.

Nobody wrote a giant list of "if rain = 120 and temp = 38 then yield = ...". The model learned the pattern from data.

REMEMBER IT

D-L-P. Machine learning is **Data in, Learn patterns, Predict.** "Data Learns to Predict."

COMMON MISTAKE

Mistake: "The computer is intelligent on day one."

Fix: An ML model is useful only **after training** on enough good data. Garbage data → garbage predictions. Also, neural networks are *one* type of ML, not the only type; deep learning is a *method* that uses deep neural networks.

اردو میں سمجھیں

مشین لرننگ ماڈل وہ نظام ہے جو ڈیٹا سے سیکھ کر نتیجہ دیتا ہے — کمپیوٹر پروگرام کا تربیت یافتہ دماغ۔ پہلے بہت سا ڈیٹا دیا جاتا ہے، پھر ماڈل خود اصول اور پیٹرن سیکھتا ہے، اور تربیت کے بعد نئے ان دیکھے ڈیٹا پر پیش گوئی کرتا ہے۔ نیورل نیٹ ورک مشین لرننگ کی ایک اہم قسم ہے، اور ڈیپ لرننگ اس کا ایک اعلیٰ طریقہ ہے۔

CHECK YOURSELF

1. What are the three steps of how an ML model works?
2. What is a machine-learning model compared to in the source?
3. After training, what kind of data can the model handle?

Write your answers in your notebook. The key follows this chapter's exam.

5.1.3 Deep Learning (DL)

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 07 of 11 · 45 min · first half · with Components of Deep Learning. Board: Deep learning is a machine-learning method in which computers use multi-layer neural networks to learn complex patterns from data..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Deep learning is a machine-learning method in which computers use **multi-layer neural networks** to learn **complex patterns** from data.

The word **“deep”** is used because data passes through **several hidden layers** before the system produces the final output. Each layer learns a **different level of detail**:

- **Early layers** learn simple features — edges, shapes, colours.
- **Deeper layers** combine those simple features to understand complex patterns — a whole face, or a specific car model (a Cultus versus a Corolla).

A network with only one or two hidden layers is a **shallow** neural network. Deep learning is always “deep”: it needs **huge amounts of data** and **processing power**.

Neural network vs deep learning

	Neural network (the model)	Deep learning (the method)
What it is	A system/model that has layers, nodes and connections to help it learn.	A specific method that trains neural networks containing many hidden layers .
Depth	Can be simple (shallow) with just one or two hidden layers.	Always “deep,” requiring huge amounts of data and processing power to learn complex patterns.
Role	The architecture (the “machine”).	The way we train a deep version of that machine.

WORKED EXAMPLE

Real-world example from the source: photo gallery search.

A modern gallery app on a smartphone uses deep learning to recognise faces, objects or places in thousands of photos.

Step 1. During training (done by the company, using millions of images) early layers learned edges and colours; deeper layers learned "wheel", "petal", "minaret".

Step 2. The trained network has already scanned your phone's photos and tagged them.

Step 3. You type "car" or "flower" in the search bar. The app instantly shows related photos because its deep neural network has already learned visual patterns from millions of training images.

A student in Hyderabad can type "Ajrak" or "cricket" and jump to those pictures without scrolling for ten minutes.

REMEMBER IT

Deep = many hidden layers. Shallow NN: 1–2 hidden layers. Deep NN: many hidden layers, huge data, strong computers. Simple features first, complex meaning later.

COMMON MISTAKE

Mistake: "Deep learning and neural networks are two names for the same thing."

Fix: A neural network is the **model** (layers + nodes + connections). Deep learning is the **method** of training networks that have **many** hidden layers. A small NN with one hidden layer is not deep learning.

اردو میں سمجھیں

ڈیپ لرننگ مشین لرننگ کا وہ طریقہ ہے جس میں کئی پوشیدہ تہوں والے نیورل نیٹ ورک استعمال ہوتے ہیں۔ "ڈیپ" اس لیے کہ ڈیٹا کئی تہوں سے گزر کر پیچیدہ پیٹرن سیکھتا ہے: پہلی تہیں کنارے اور رنگ سیکھتی ہیں، گہری تہیں پورا چہرہ یا گاڑی کی قسم پہچانتی ہیں۔ یہ طریقہ بہت سے ڈیٹا اور طاقتور کمپیوٹنگ کا طالب ہے۔

CHECK YOURSELF

1. Why is the method called "deep" learning?
2. What do early layers learn, and what do deeper layers learn?
3. Can a neural network with one hidden layer be called deep learning?

Write your answers in your notebook. The key follows this chapter's exam.

5.1.5 Components of Deep Learning

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 07 of 11 · 45 min · second half · with Deep Learning (DL). Board: Deep learning relies on specific advanced components to achieve its high accuracy..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Deep learning relies on specific advanced components to achieve its high accuracy. These components **differentiate it from basic machine learning**.

#	Component	What it means
1	Large input data	Deep learning is “ data hungry .” It needs massive datasets (thousands or millions of records) for better learning and accuracy.
2	Many hidden layers	Uses dozens or hundreds of hidden layers to learn deeper, more intricate patterns.
3	Automatic feature learning	Unlike older models where humans had to manually highlight important features, deep learning extracts important features by itself .
4	Learning algorithm	Math routines (like backpropagation) that help the system reduce mistakes and improve learning continuously.
5	High computing power	Processing millions of data points across deep layers needs specialised, strong hardware, such as GPUs (Graphics Processing Units).
6	Training process	The model is trained again and again in loops called epochs to gradually improve its final performance.

A **GPU** was originally made for video games’ graphics, but it can do thousands of small multiplications in parallel — exactly what deep networks need. An **epoch** is one full pass through the training data. Ten epochs means the model has seen every training example ten times, adjusting weights a little each time.

Backpropagation means sending the error (from the loss function) **backwards** through the layers so each weight can be nudged in the direction that reduces the next error.

WORKED EXAMPLE

Worked example: cotton-leaf disease detector for a farm in Mirpurkhas. Match each DL component.

1. **Large input data.** Researchers collect 80,000 labelled photos: healthy leaves and leaves with whitefly damage.
2. **Many hidden layers.** The network has 20 hidden layers so it can go from "green edge" to "this exact pest pattern."
3. **Automatic feature learning.** No agronomist types in "look for yellow circles." The network finds the useful spots itself.
4. **Learning algorithm.** After a wrong guess ("healthy" when it was diseased), backpropagation lowers the weights that caused the mistake.
5. **High computing power.** Training runs on a GPU workstation at a university lab in Karachi; a school laptop would take weeks.
6. **Training process.** They train for 30 epochs. After epoch 1 accuracy is 62%; after epoch 30 it is 94% on photos it has not trained on.

REMEMBER IT

D-L-A-L-G-T. Data (lots), Layers (many), Automatic features, Learning algorithm, GPU power, Training epochs. "Deep Learners Always Love Good Training."

COMMON MISTAKE

Mistake: "Deep learning is just 'a neural network'."

Fix: Name the six extras: huge data, many hidden layers, automatic features, a learning algorithm (backpropagation), GPUs, and repeated epochs. A shallow NN with a small spreadsheet is ordinary ML, not DL.

اردو میں سمجھیں

ڈیپ لرننگ کو عام مشین لرننگ سے یہ چیزیں الگ کرتی ہیں: بہت بڑا ڈیٹا، بہت سی پوشیدہ تہیں، خود بخود خصوصیات نکالنا، سیکھنے کا الگورتھم جیسے بیک پروپیگیشن (Backpropagation)، طاقتور ہارڈویئر جیسا کہ جی پی یو (GPU)، اور بار بار تربیت جسے ایپوک (Epoch) کہتے ہیں۔

CHECK YOURSELF

1. Why is deep learning called "data hungry"?
2. What is an epoch?
3. Name the hardware often used for DL, and the learning algorithm named in the source.

Write your answers in your notebook. The key follows this chapter's exam.

Future of AI, NN and DL in Pakistan

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 08 of 11 · 45 min · first half · with Applications of Neural Networks and Deep Learning. Board: Machine learning, neural networks and deep learning will play a key role in Pakistan's future..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Machine learning, neural networks and deep learning will play a key role in Pakistan's future. The **National AI Policy 2025** highlights how artificial intelligence is now part of national planning, focusing on **innovation, skill-building, ethical use and digital growth**.

Sector	Potential impact in Pakistan
Education	Smart learning systems, online tutoring, automatic assessments, and finding where students need specific help.
Healthcare	Disease detection, medical image analysis, and managing hospital data. Crucial for rural areas lacking specialist doctors.
Agriculture	Monitoring crops, predicting weather, managing irrigation, and estimating yields — highly important for Pakistan's economy.
Business and banking	Fraud detection, customer support (chatbots), market forecasting, and intelligent risk analysis.
Local languages	Speech recognition, translation and text-to-speech tools for Urdu, Sindhi and other regional languages.

To benefit from this future, Pakistan needs skilled individuals. You should focus on **programming (such as Python), mathematics, data analysis, problem-solving** and the **ethical use of technology**.

WORKED EXAMPLE

Worked example: pick a sector and write a three-line “impact paragraph” for 5 marks.

Agriculture: A cotton grower in Sanghar photographs leaves on a cheap phone. A deep-learning model trained on Pakistani crop images flags whitefly early. The farmer sprays only the affected block, saves pesticide cost, and protects yield — which matters because agriculture is a large part of Pakistan’s economy.

REMEMBER IT

Five sectors: E-H-A-B-L. Education, Healthcare, Agriculture, Business/banking, Local languages. Policy words: innovation, skills, ethics, digital growth.

COMMON MISTAKE

Mistake: Writing only “AI will make Pakistan modern” with no sector or example.

Fix: Name the National AI Policy 2025, pick two sectors from the table, and give a local example (rural hospital without a specialist; Urdu/Sindhi speech tools; bank fraud).

اردو میں سمجھیں

قومی اے آئی پالیسی 2025 کے مطابق مصنوعی ذہانت پاکستان کی منصوبہ بندی کا حصہ ہے: جدت، مہارت، اخلاقی استعمال اور ڈیجیٹل ترقی۔ تعلیم، صحت، زراعت، بینکنگ اور اردو و سندھی جیسی مقامی زبانوں میں اس کے اثرات ہوں گے۔ طلبہ کو پائتھن، ریاضی، ڈیٹا کا تجزیہ، مسئلہ حل کرنا اور ٹیکنالوجی کا اخلاقی استعمال سیکھنا چاہیے۔

CHECK YOURSELF

1. Name the national policy mentioned for AI in Pakistan.
2. Why is AI in healthcare especially important for rural areas?
3. List three skills students should learn to prepare for this future.

Write your answers in your notebook. The key follows this chapter’s exam.

5.2 Applications of Neural Networks and Deep Learning

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 08 of 11 · 45 min · second half · with Future of AI, NN and DL in Pakistan. Board: Neural networks and deep learning are widely used in modern life..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Neural networks and deep learning are widely used in modern life. Many intelligent systems use them in the background to **recognise information, make predictions and support users.**

#	Application	What it does	Example
1	Image recognition	Identifies objects, faces or patterns in images. Used in security cameras, photo search and biometric locks.	Unlocking a smartphone using face recognition; a camera at a Karachi plaza matching a face with a staff list.
2	Speech recognition	Converts spoken words into digital text or commands. Deep learning helps with accents, pronunciation and voice patterns.	A student speaks to Google Assistant or Alexa to set a morning alarm; Urdu voice search on a phone.
3	Natural Language Processing (NLP)	Helps computers understand, process and respond to human language grammatically and in context. Core of chatbots, translators and AI writers.	Using Google Translate to turn a difficult English paragraph into Urdu; a bank chatbot answering in Urdu.
4	Healthcare systems	Analyse complex medical images (X-rays, CT scans, MRIs) to detect diseases early and accurately.	A hospital system highlighting abnormal patterns in a lung X-ray that might indicate pneumonia or tumours — useful at a DHQ hospital that has few radiologists.
5	Recommendation systems	Analyse past behaviour and preferences to suggest content, products or services.	A student watches computer-science videos on YouTube; the platform recommends more programming tutorials.
6	Autonomous vehicles	Self-driving cars use neural networks to process real-time camera and radar data: roads, signals, pedestrians, obstacles.	A self-driving car detects a pedestrian crossing and automatically applies the brakes.
7	Fraud detection	Banks compare current activity with previous spending patterns to catch unusual transactions.	An HBL or Meezan app flags a sudden Rs 80,000 payment from a new city at 3 a.m.
8	Assistive technologies	AI supports people with disabilities.	Speech-to-text tools for users who have difficulty typing; screen readers that speak Urdu text aloud.

WORKED EXAMPLE

Worked example: match the app to the application name — a day in Ahmed's life in Hyderabad.

1. 7:00 am — phone unlocks by face. → **Image recognition.**
2. 7:05 am — "Ok Google, set alarm for Maghrib." → **Speech recognition.**
3. 8:00 am — Google Translate helps with an English article. → **NLP.**
4. 4:00 pm — YouTube suggests a Python tutorial after he watched Chapter 5 notes. → **Recommendation system.**
5. 9:00 pm — JazzCash texts "We blocked a payment that does not match your pattern." → **Fraud detection.**

REMEMBER IT

Eight applications: I-S-N-H-R-A-F-A. Image, Speech, NLP, Healthcare, Recommendations, Autonomous vehicles, Fraud, Assistive tech. "I See New Hospitals Recommend Autonomous Fraud-Assist."

COMMON MISTAKE

Mistake: Mixing up speech recognition and NLP.

Fix: Speech recognition turns **sound into text** (or a command). NLP understands the **meaning of language** (grammar, context, translation, chat replies). You can have NLP on typed text with no microphone at all.

اردو میں سمجھیں

نیورل نیٹ ورکس اور ڈیپ لرننگ کی مشہور ایپلی کیشنز یہ ہیں: تصویر کی پہچان، آواز کی پہچان، قدرتی زبان کی پروسیسنگ (NLP)، صحت کے نظام، تجویز کرنے والے نظام، خود چلنے والی گاڑیاں، فراڈ کی نشاندہی اور معاون ٹیکنالوجیز۔ روزمرہ میں چہرے سے فون کھولنا، یوٹیوب کی تجاویز اور بینک کا مشکوک لین دین پکڑنا سب اسی خاندان سے ہیں۔

CHECK YOURSELF

1. Which application converts spoken words into text or commands?
2. Give the source example of a recommendation system.
3. How do self-driving cars use neural networks?

Write your answers in your notebook. The key follows this chapter's exam.

5.3.2 Data Protection (Encryption, Passwords, Backup, Firewall)

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 09 of 11 · 45 min · first half · with Identifying Security Threats. Board: Data protection means keeping digital information safe from unauthorised access, misuse, loss, damage or accidental deletion..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Data protection means keeping digital information safe from **unauthorised access, misuse, loss, damage or accidental deletion**.

1. Data encryption

Encryption changes readable data (**plaintext**) into a coded form called **ciphertext**. Unauthorised users cannot understand ciphertext without the key.

- **Symmetric encryption** — the **same key** is used to encrypt and to decrypt.
- **Asymmetric encryption** — **two keys**: a **public key** to encrypt, a **private key** to decrypt.

A simple exam cipher is the **Caesar cipher** (a symmetric substitution cipher). You shift every letter a fixed number of places along the alphabet. Shift 3 is the classic key: A → D, B → E, ..., Z → C (the alphabet wraps around).

2. Strong passwords

A strong password includes **uppercase, lowercase, numbers and symbols**. It resists **brute-force** guessing (trying every possible combination). Source example: Zk@2026#Pass .

Weak: ahmed123 , pakistan , sindh , your date of birth. Never reuse the same password on the college LMS and on JazzCash.

3. Backup and recovery — the 3-2-1 rule

A **backup** is a copy of data in a safe location (cloud or external drive) so you can **restore** it after hardware damage, ransomware or accidental deletion.

The **3-2-1 backup rule** is a practical standard:

- **3** copies of the data (the original plus two backups).
- **2** different types of storage media (for example laptop disk + USB, or disk + cloud).
- **1** copy **off-site** (a different building or the cloud), so a fire or theft at home does not destroy every copy.

4. Firewall and antivirus software

A **firewall** is a security **barrier** that **monitors network traffic** and **blocks suspicious internet access**. Think of it as a checkpoint on the road between your device (or college lab) and the internet.

Antivirus software detects and removes harmful software (viruses, spyware and other malware) from the **local machine**.

Firewall ≈ guards the **door to the network**. Antivirus ≈ searches **inside the house** for intruders already present.

WORKED EXAMPLE

Worked example A — Caesar cipher, shift = 3. Encrypt the plaintext **SINDH**, then decrypt the result.

Write the alphabet and count three letters forward. Wrap after Z back to A.

Plain	S	I	N	D	H
+3	V	L	Q	G	K

Ciphertext = **VLQ GK**.

Decrypt: shift each letter **back** by 3: V → S, L → I, Q → N, G → D, K → H. You recover **SINDH**.

Spaces and punctuation are often left unchanged. The same key (3) is used both ways, so Caesar is **symmetric**.

Second check: **CAT** + 3 → C→F, A→D, T→W → **FDW**.

```
def caesar(text, shift):
    result = ""
    for ch in text:
        if ch.isalpha():
            base = ord("A") if ch.isupper() else ord("a")
            result += chr((ord(ch) - base + shift) % 26 + base)
        else:
            result += ch
    return result

print(caesar("SINDH", 3))
print(caesar("VLQ GK", -3))
print(caesar("CAT", 3))
```

OUTPUT
VLQ GK
SINDH
FDW

Worked example B — 3-2-1 for Fatima's Class XII project in Hyderabad.

1. **Copy 1 (original):** project folder on her laptop hard disk.
2. **Copy 2 (different media):** the same folder on a USB drive she keeps in her bag.
3. **Copy 3 (off-site):** uploaded to Google Drive (cloud servers are not in her house).

That is 3 copies, 2 media types (internal disk + USB, with cloud as the off-site copy), 1 off-site. When her brother deletes the laptop folder, she restores from USB or Drive.

Password check: Zk@2026#Pass has uppercase Z, lowercase letters, digits 2026, and symbols @ and #. fatima has none of those extras — reject it.

3 copies



2 media types



1 copy off-site

REMEMBER IT

Cipher = lock the message. Password = lock the door. 3-2-1 = spare keys in three places.

Firewall = gate. Antivirus = indoor search. Caesar: shift letters; same key both ways (symmetric).

COMMON MISTAKE

Mistake 1: Shifting the wrong way, or forgetting wrap-around (X, Y, Z + 3 → A, B, C).

Mistake 2: Two copies on the same laptop (Documents and Desktop) and calling it 3-2-1. That is still one disk in one house.

Fix: Count letters on a written alphabet. For backups, different media and one copy that would survive a house fire.

اردو میں سمجھیں

ڈیٹا پروٹیکشن کا مطلب ہے معلومات کو غیر مجاز رسائی، غلط استعمال، نقصان یا حادثاتی حذف سے بچانا۔ انکرپشن پڑھے جانے والے متن کو سائفر ٹیکسٹ بنا دیتی ہے؛ سیزر سائفر میں ہر حرف کو مقررہ جگہوں سے آگے سرکایا جاتا ہے۔ مضبوط پاس ورڈ میں بڑے، چھوٹے حروف، عدد اور علامات ہوں۔ 3-2-1 بیک اپ: تین کاپیاں، دو قسم کے میڈیا، ایک کاپی باہر (آف سائٹ)۔ فائر وال نیٹ ورک ٹریفک روکتی ہے؛ اینٹی وائرس مقامی نقصان دہ سافٹ ویئر ہٹاتا ہے۔

CHECK YOURSELF

1. Encrypt PAK with a Caesar shift of 3.
2. What do the 3, the 2 and the 1 stand for in 3-2-1 backup?
3. In asymmetric encryption, which key encrypts and which key decrypts?

Write your answers in your notebook. The key follows this chapter's exam.

5.4.2 Identifying Security Threats

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 09 of 11 · 45 min · second half · with Data Protection (Encryption, Passwords, Backup, Firewall). Board: Identifying security threats means noticing signs that data or systems may be at risk..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Identifying security threats means **noticing signs** that data or systems may be at risk. Early identification helps you act before serious damage occurs.

Sign / indicator	What it likely means
Slow performance, missing files, or random pop-ups.	Malware or background unauthorised activity.
Failed login attempts or strange login locations.	Attempted unauthorised access .
Emails urging quick action, asking for an OTP, or containing bad grammar / strange links.	Classic phishing .
Unexpected deletion, copying or movement of records.	Data theft or insider misuse.
Sudden massive spike in server requests or a very slow website.	An ongoing DoS attack.

The first line of defence is also simple behaviour: avoid **unsafe downloads, cracked software, unverified websites and infected USB drives**.

WORKED EXAMPLE

Worked example: read the signs in a college computer lab in Khairpur.

1. Three PCs show pop-ups and Word files have vanished after students used a "game" USB. → Treat as **malware**. Disconnect from the network; run antivirus; stop USB use.
2. Google Classroom emails: "Your account will be deleted in 30 minutes. Confirm password here." Link spelling is go0gle. → **Phishing**. Do not click; report to the teacher.
3. The e-portal that was fine at 8:00 am is unreachable at 8:05; the technician sees a sudden spike in requests. → Suspect **DoS**.
4. Nadia's Gmail security page shows a login from another country at 4 a.m. → **Unauthorised access** attempt. Change password; turn on MFA.

REMEMBER IT

Slow/pop-ups → malware. Odd logins → unauthorised access. Urgent OTP email → phishing. Files moving → theft. Traffic spike → DoS.

COMMON MISTAKE

Mistake: Ignoring early signs ("the PC is just old") until the ransomware note appears.

Fix: One unusual login or one OTP email is enough to investigate. Early action is cheaper than recovery.

اردو میں سمجھیں

خطرے کی جلد پہچان نقصان سے پہلے اقدام ممکن بناتی ہے۔ سست روی، غائب فائلیں یا پاپ اپ میلویئر کی علامت ہیں؛ عجیب لاگ ان غیر مجاز رسائی کی؛ فوری او ٹی پی والی ای میل فشنگ کی؛ ریکارڈ کا اچانک منتقل ہونا ڈیٹا چوری کی؛ سرور پر درخواستوں کا دھماکہ ڈو ایس کی۔ کریک سافٹ ویئر، نامعلوم یو ایس بی اور غیر تصدیق شدہ ویب سائٹوں سے بچیں۔

CHECK YOURSELF

1. Random pop-ups and missing files most likely indicate what?
2. An email with bad grammar that demands your OTP is a sign of what?
3. Name four unsafe habits that invite these threats.

Write your answers in your notebook. The key follows this chapter's exam.

5.4.3 Apply Mitigation Techniques

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 10 of 11 · 45 min · first half · with Equity and Equal Access in Digital Collaboration. Board: Mitigation techniques are actions taken to prevent security threats or reduce their harmful effects once identified..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Mitigation techniques are actions taken to **prevent** security threats or **reduce their harmful effects** once identified. Technology helps, but it cannot stop all threats if the user is careless.

#	Technique	How it helps
1	Antivirus and firewalls	Antivirus scans and removes harmful software (for example from USB drives). A firewall monitors network traffic and blocks suspicious access from the internet.
2	Strong passwords and 2FA	Complex passwords slow brute-force guessing. 2FA adds an extra layer: an OTP on your phone as well as the password.
3	Data encryption	Converts data into unreadable code during transmission. Protects passwords and sensitive data if they are intercepted.
4	Regular backups	Copies on cloud or external drives allow quick recovery after a crash, human error or ransomware.
5	User awareness (the human factor)	Training users to avoid unknown links, suspicious attachments and password sharing. The human is often the weakest link — and the strongest defence when trained.

WORKED EXAMPLE

Worked example: match each threat to a mitigation — BISE e-test week at a college in Larkana.

Threat seen	Mitigation to apply
USB games in the lab, pop-ups starting.	Scan with antivirus ; block unknown USBs; enable the lab firewall .
Phishing SMS about "update your portal password."	User awareness : do not click; verify on the official site typed by hand. Turn on 2FA .
Fear that intercepted Wi-Fi could show passwords.	Use sites with encryption (HTTPS / encrypted LMS); never send passwords in plain WhatsApp.
Ransomware risk to project files.	Regular 3-2-1 backups so files can be restored without paying.
Shared passwords on a sticky note on the monitor.	Strong unique passwords + 2FA; remove the note; awareness session.

REMEMBER IT

Five shields: A-F, P-2, E, B, U. Antivirus+Firewall, Passwords+2FA, Encryption, Backups, User awareness. Ransomware is why backups matter: if files are locked, a clean copy brings them back.

COMMON MISTAKE

Mistake: "If I installed antivirus I am 100% safe."

Fix: Antivirus does not stop you from typing an OTP into a fake page. Mitigation is a **set** of techniques plus human caution.

اردو میں سمجھیں

تحفظ کی تدابیر خطرات کو روکتی یا ان کا نقصان کم کرتی ہیں: اینٹی وائرس اور فائر وال، مضبوط پاس ورڈ اور دو عنصری تصدیق (2FA)، انکریپشن، باقاعدہ بیک اپ، اور صارف کی آگاہی۔ ٹیکنالوجی تب ناکام ہو جاتی ہے جب صارف نامعلوم لنک کھولے یا پاس ورڈ بانٹے۔

CHECK YOURSELF

1. How does 2FA add a layer on top of a password?
2. Why do regular backups help after ransomware?
3. What three careless behaviours should awareness training stop?

Write your answers in your notebook. The key follows this chapter's exam.

5.5 Equity and Equal Access in Digital Collaboration

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 10 of 11 · 45 min · second half · with Apply Mitigation Techniques. Board: Collaboration tools are vital for online learning and teamwork..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Collaboration tools are vital for online learning and teamwork. To use these tools fairly, all users must participate **without barriers**. You must understand the difference between **equal access** and **equity**.

Equal access

Giving everyone the **exact same** opportunity, tools and resources.

Example: providing every student with the **same login ID** to access a Zoom class.

Equity

Giving **additional, specific support** to users who need it, so they can reach the **same outcome**.

Example: turning on live **subtitles/captions** in Zoom specifically for a student who has hearing difficulties.

Equal access is the same starting kit. Equity is extra help so a person who faces a barrier can still finish the race with everyone else. Fair collaboration needs **both**: the same Zoom link for all (equal access) **and** captions, recorded lectures or a low-data app where needed (equity).

WORKED EXAMPLE

Worked example: one class, two ideas. A teacher in Thatta starts online classes.

Equal access: every student receives the same Zoom ID and password. That is fair in the sense of "same tool," but a student with hearing loss still cannot follow the spoken lecture, and a student in a village with a weak 2G signal cannot join video.

Equity: the teacher turns on captions, posts a low-size audio recording, and accepts the assignment as a Google Doc in the browser (not only through a heavy app). Now those two students can reach the **same learning outcome**.

REMEMBER IT

Equal = same tools. Equity = extra support for the same outcome. Same shoes for all vs a ramp for the wheelchair user.

COMMON MISTAKE

Mistake: "We gave everyone the same login, so the class is fair."

Fix: Same login is equal access only. If some students still cannot hear, see, afford a smartphone, or get electricity, you still need equity.

اردو میں سمجھیں

مساوی رسائی (Equal Access) سب کو ایک جیسے اوزار دیتی ہے، جیسے ایک ہی زوم لاگ ان۔ انصاف (Equity) ضرورت مند کو اضافی مدد دیتی ہے تاکہ وہی نتیجہ نکل سکے، جیسے سماعت کی مشکل والے طالب علم کے لیے زندہ ذیلی عنوانات (Captions)۔ منصفانہ تعاون کے لیے دونوں چاہییں۔

CHECK YOURSELF

1. Define equal access in one sentence.
2. Define equity in one sentence.
3. Why are Zoom captions an example of equity, not merely equal access?

Write your answers in your notebook. The key follows this chapter's exam.

5.5.2 Collaboration Tools

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 11 of 11 · 45 min · first half · with Career Opportunities. Board: Digital collaboration tools are online platforms that support communication, file sharing, learning and teamwork across different locations..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Digital collaboration tools are online platforms that support **communication, file sharing, learning and teamwork** across different locations.

Tool	Primary function and educational use
Google Docs	Write, edit, comment and share documents in real time. Excellent for group assignments.
Zoom	Online meetings, virtual classes, screen sharing and video-based communication.
Microsoft Teams	A unified workspace for online meetings, file sharing, class groups and structured teamwork.
Google Classroom / LMS	Learning Management Systems help teachers manage lectures, distribute assignments, conduct quizzes and grade student activities.
WhatsApp	Quick class announcements, urgent reminders and instant group communication. Must be used responsibly.
Email	Formal communication, official notices, submitting large attachments, and keeping a professional written record.

Responsibly on WhatsApp means: no leaking of classmates' marks or photos, no fake forwards, and no forcing a student who has no smartphone to miss official work that was never posted on the LMS.

WORKED EXAMPLE

Worked example: choose the right tool for each job in a Hyderabad college group project.

1. Write the report together after school, from different houses. → **Google Docs** (real-time edit and comments).
2. Sunday 7 pm teacher explanation with slides. → **Zoom** or **Teams** (video + screen share). Turn on captions (equity).
3. Collect homework, quiz and grades in one place. → **Google Classroom / LMS**.
4. "Tomorrow's test is postponed — tell everyone in the next ten minutes." → **WhatsApp** class group (then repeat on Classroom so nobody is left out).
5. Send the principal a formal complaint with a 8 MB scanned letter. → **Email** (written record + attachment).

REMEMBER IT

Docs = write together. Zoom/Teams = meet. Classroom = official class hub. WhatsApp = fast but informal. Email = formal record.

COMMON MISTAKE

Mistake: Running the whole course only on WhatsApp.

Fix: WhatsApp is for quick reminders. Assignments, marks and lectures belong on an LMS so there is access control, a record, and a path that does not depend on one person's phone.

اردو میں سمجھیں

ڈیجیٹل تعاون کے اوزار مختلف مقامات سے بات چیت، فائل شیئرنگ اور ٹیم ورک چلاتے ہیں: گوگل ڈاکس مشترکہ تحریر کے لیے، زوم اور مائیکروسافٹ ٹیمز میٹنگ کے لیے، گوگل کلاس روم یا ایل ایم ایس باقاعدہ پڑھائی کے لیے، واٹس ایپ فوری اطلاع کے لیے (ذمہ داری سے)، اور ای میل رسمی ریکارڈ کے لیے۔

CHECK YOURSELF

1. Which tool is excellent for real-time group writing?
2. What four jobs does an LMS / Google Classroom help a teacher do?
3. What is email especially good for?

Write your answers in your notebook. The key follows this chapter's exam.

Career Opportunities

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 11 of 11 · 45 min · second half · with Collaboration Tools. Board: This unit covers neural networks, deep learning, secure collaboration, data protection and digital equity..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

This unit covers neural networks, deep learning, secure collaboration, data protection and digital equity. Mastery of these ideas opens high-demand careers in **Artificial Intelligence** and **Cybersecurity** — including in Pakistan's banks, software houses, universities and public projects linked to the National AI Policy 2025.

Career	What the person does
Machine Learning Engineer	Builds and trains machine-learning and neural-network models used in face recognition, NLP and recommendation systems.
Cybersecurity Analyst	Monitors systems for threats such as malware and phishing, and applies mitigation (firewalls, 2FA) to protect organisational data.
AI Researcher	Studies and develops new techniques in artificial intelligence and deep learning, often in university labs or high-tech R&D centres.
Data Privacy Officer	Ensures the organisation's data handling complies with legal privacy principles, protecting sensitive user information and secure collaboration.
Ethical Hacker	Legally tests systems and networks for vulnerabilities (penetration testing) before malicious attackers can exploit them via DoS or malware.

WORKED EXAMPLE

Worked example: match the job.

1. "Train a model that tags Urdu news headlines." → **Machine Learning Engineer.**
2. "Watch the bank's logs for phishing domains and turn on 2FA." → **Cybersecurity Analyst.**
3. "With written permission, try to break the college portal before criminals do." → **Ethical Hacker.**

REMEMBER IT

AI careers lean on Python, maths and ethics. Cyber careers lean on threats, 2FA, firewalls and careful testing. Both need clear communication.

COMMON MISTAKE

Mistake: Confusing an ethical hacker with a criminal hacker.

Fix: An ethical hacker has **permission** and reports weaknesses so they can be fixed. Attacking without permission is a crime.

اردو میں سمجھیں

اس باب سے جڑے پیشے ہیں: مشین لرننگ انجینئر، سائبر سیکیورٹی اینالسٹ، اے آئی محقق، ڈیٹا پرائیویسی آفیسر اور اخلاقی ہیکر۔ اخلاقی ہیکر اجازت کے ساتھ کمزوریاں ڈھونڈتا ہے تاکہ مجرمانہ حملے سے پہلے انہیں ٹھیک کیا جا سکے۔

CHECK YOURSELF

1. Who legally tests a network for weaknesses before attackers do?
2. Which career focuses on compliance and protecting sensitive user information?

Write your answers in your notebook. The key follows this chapter's exam.

Application and Impacts of Computing

17 single-page lessons · 5 Golden · read, close, say aloud, then sit the exam

Chapter in one look

- **ML** is a model (a trained brain) that learns from data in three steps: input, learning, prediction on new unseen data — without a hand-written rule for every case.
- **AI** $\supset$ **ML** $\supset$ **DL**: deep learning sits inside machine learning, which sits inside artificial intelligence.
- A **neural network** is a brain-inspired mathematical model of connected neurons in an input layer, hidden layer(s) and output layer (face unlock: camera $\rightarrow$ features $\rightarrow$ unlock).
- **Deep learning** trains neural networks with many hidden layers; early layers learn simple features, deeper layers learn complex patterns. It needs huge data and computing power.
- NN components: input layer, neurons, hidden layers, weights, bias, activation function, output layer, loss function. A neuron computes $s = \sum(x \times w) + b$, then an activation gate.
- DL components: large data, many hidden layers, automatic feature learning, learning algorithm (backpropagation), GPUs, training epochs. Pakistan's National AI Policy 2025 covers education, health, agriculture, banking and local languages.
- Applications: image and speech recognition, NLP, healthcare imaging, recommendations, autonomous vehicles, fraud detection, assistive tech.
- **Secure collaboration**: authentication (who), MFA/2FA (two or more factors), access control (what you may do), accountability, privacy, safe transmission.
- **Data protection**: encryption (plaintext $\rightarrow$ ciphertext; symmetric vs asymmetric; Caesar shift), strong passwords, 3-2-1 backup, firewall and antivirus.
- Threats: malware, phishing, unauthorised access, data/identity theft, DoS, human error. Spot them by pop-ups, odd logins, urgent OTP emails, missing files, traffic spikes.
- Mitigation: antivirus + firewall, strong passwords + 2FA, encryption, regular backups, user awareness.
- **Equal access** = same tools for all; **equity** = extra support for the same outcome. Functions: need-based support, removing barriers, recorded participation, multiple formats. Tools: Docs, Zoom, Teams, Classroom/LMS, WhatsApp, email.

Key terms

Term	Meaning	اردو
Artificial intelligence (AI)	The broad field in which machines perform tasks that normally need human thinking.	مصنوعی ذہانت
Machine learning (ML)	A model that learns patterns from data and then predicts on new data.	مشین لرننگ
Neural network (NN)	A brain-inspired mathematical model of connected neurons in layers.	نیورل نیٹ ورک
Deep learning (DL)	An ML method that trains neural networks with many hidden layers.	ڈیپ لرننگ
Weight	A number showing the strength or importance of a connection between neurons.	وزن (وزن تعلق)
Bias	An extra constant added to a neuron's sum to improve accuracy.	بائیس
Activation function	A gate that decides whether a signal is important enough to pass on.	ایکٹیویشن فنکشن
Loss function	A measure of how wrong the model's answer is compared with reality.	لاس فنکشن
Epoch	One full training pass through the dataset.	ایپوک (تربیتی چکر)
GPU	Graphics Processing Unit — specialised hardware used to train deep networks.	جی پی یو
NLP	Natural Language Processing — computers understanding and producing human language.	قدرتی زبان کی پروسیسنگ
Authentication	Confirming a user's identity before access (password, PIN, OTP, biometrics).	تصدیق شناخت

Application and Impacts of Computing

75 marks • 1 hour 15 minutes • no notes • no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 17 and the recap. **Section A** — all 15 MCQs (1 mark).

Section B — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define • Explain • Example • Diagram • Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. A machine-learning model works in which order?
 - a. Prediction, then data input, then learning
 - b. Data input, learning, then prediction on new data
 - c. Only prediction, with no data
 - d. Writing a separate rule for every case
2. A neural network is best described as:
 - a. a living human brain placed in a computer
 - b. a backup disk
 - c. a brain-inspired mathematical model of connected neurons
 - d. a type of firewall
3. The word “deep” in deep learning refers to:
 - a. several hidden layers through which data passes
 - b. very loud speakers
 - c. using only one neuron
 - d. storing data underground
4. In the relationship $AI \supset ML \supset DL$, the innermost set is:
 - a. AI
 - b. ML
 - c. equal access
 - d. DL
5. Weights in a neural network show the:
 - a. colour of the screen
 - b. importance or strength of connections between neurons
 - c. size of the hard disk
 - d. student’s roll number
6. For $x_1 = 1$, $x_2 = 0$, $w_1 = 0.5$, $w_2 = 0.5$, $b = 0$ and threshold 0.4, the neuron output y is:
 - a. 1
 - b. 0
 - c. 0.4
 - d. 2
7. Which of the following is a component of deep learning (not of a tiny shallow network)?
 - a. Exactly one hidden layer and ten rows of data
 - b. Manual listing of every feature by a human, always
 - c. Many hidden layers, huge datasets and GPUs
 - d. A Caesar cipher
8. Unlocking a phone by matching facial features is mainly an example of:
 - a. a DoS attack
 - b. 3-2-1 backup
 - c. equal access
 - d. image recognition
9. Authentication means:
 - a. choosing who may edit a file
 - b. confirming a user’s identity before allowing access
 - c. shifting letters in a cipher
 - d. flooding a server with requests

L0. Password plus an OTP sent to a phone is an example of:

- a. MFA / 2FA
- b. a worm
- c. a shallow neural network
- d. equity captions

L1. With a Caesar cipher of shift 3, the plaintext CAT becomes:

- a. DBU
- b. CAW
- c. FDW
- d. ZXQ

L2. The 3-2-1 backup rule requires:

- a. three passwords only
- b. one copy on the same laptop twice
- c. no off-site copy
- d. three copies, two media types, one copy off-site

L3. Phishing is:

- a. a social-engineering trick using fake emails or sites to steal passwords or OTPs
- b. a type of GPU
- c. an activation function
- d. a collaboration tool like Zoom

L4. A Denial of Service (DoS) attack:

- a. always steals a CNIC
- b. floods a system with fake requests so it slows or crashes
- c. is the same as a strong password
- d. is a hidden layer

L5. Turning on live captions in Zoom for a student with hearing difficulties is an example of:

- a. malware
- b. a DoS attack
- c. equal access only, with no extra support
- d. equity

Section B — Short questions (10 × 3 = 30)

1. Define a machine-learning model and state the three steps of how it works.
2. What is a neural network? Name its three kinds of layer and link them to face unlock.
3. Differentiate a neural network (the model) from deep learning (the method).
4. State the relationship $AI \supset ML \supset DL$ in words.
5. List eight components of a neural network. What do weights and bias do?
6. Name six components of deep learning.
7. Differentiate authentication, MFA and access control with one example each.
8. Encrypt SINDH using a Caesar cipher with shift 3. State whether this cipher is symmetric or asymmetric.
9. Define malware, phishing and DoS. Give one Pakistani-style example of each.
- L0. Differentiate equal access and equity. List four functions of equity and equal access.

Section C — Long questions (attempt any 3 × 10 = 30)

1. Explain machine learning, neural networks and deep learning. Draw and label the set diagram $AI \supset ML \supset DL$. Include the face-unlock walk-through and the photo-gallery example.
2. A neuron has inputs $x_1 = 0.8$, $x_2 = 0.5$, weights $w_1 = 0.4$, $w_2 = 0.6$, bias $b = 0.1$ and threshold 0.5. (a) Compute the weighted sum s and the output y . (b) Repeat for $x_1 = 0.2$, $x_2 = 0.3$. (c) Name all eight NN components and sketch a 3–4–2 network. (d) List the six DL components and map them onto a cotton-leaf disease detector in Sindh.
3. Describe eight applications of neural networks and deep learning with examples. Then discuss the future of AI in Pakistan with reference to the National AI Policy 2025 and five sectors.
4. What is secure collaboration? Explain authentication, MFA/2FA, access control, accountability, data privacy and safe transmission, using a Google Classroom / banking-app scenario from Pakistan.
5. Define data protection. Explain encryption (symmetric vs asymmetric) with a full Caesar-cipher working of SINDH (shift 3). Describe strong passwords, the 3-2-1 backup rule, firewall and antivirus.
6. Define a security threat. Explain malware, phishing, unauthorised access, data/identity theft, DoS and human error. Give a table of identifying signs and a matching set of mitigation techniques. End with equity versus equal access and a fair choice of collaboration tools.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

1. **5.1 Machine Learning, Neural Networks and Deep Learning.** Answers: 1. AI ($AI \supset ML \supset DL$). 2. Yes — DL is inside ML, and ML is inside AI. 3. Any of: face unlock, speech recognition, photo search, medical diagnosis, language translation.
2. **5.1.1 Machine Learning (ML).** Answers: 1. Data input, learning, prediction. 2. The trained brain of a computer program. 3. New, unseen data.
3. **5.1.2 Neural Networks (NN).** Answers: 1. Neurons or nodes. 2. Hidden layers. 3. No — it is inspired by the brain but works as a mathematical computer system.
4. **5.1.3 Deep Learning (DL).** Answers: 1. Because data passes through several hidden layers. 2. Early: simple features (edges, shapes, colours). Deeper: complex patterns (a whole face, a car model). 3. No — that is a shallow network; DL always uses many hidden layers.
5. **5.1.4 Components of Neural Networks.** Answers: 1. The importance or strength of connections between neurons. 2. $s = 1 \times 0.5 + 0 \times 0.5 + 0 = 0.5$; $0.5 \geq 0.4$ so $y = 1$. 3. The error — how much the model's answer is wrong compared with reality.
6. **5.1.5 Components of Deep Learning.** Answers: 1. It needs massive datasets (thousands or millions of records) for accuracy. 2. One training loop — one full pass through the training data. 3. GPUs (Graphics Processing Units); backpropagation.
7. **Future of AI, NN and DL in Pakistan.** Answers: 1. National AI Policy 2025. 2. Those areas often lack specialist doctors; AI can help with disease detection and medical image analysis. 3. Any three of: programming (Python), mathematics, data analysis, problem-solving, ethical use of technology.
8. **5.2 Applications of Neural Networks and Deep Learning.** Answers: 1. Speech recognition. 2. YouTube recommending more programming tutorials after a student watches computer-science videos. 3. They process real-time camera and radar data to understand roads, traffic signals, pedestrians and obstacles (for example braking for a pedestrian).
9. **5.3.1 Secure Collaboration (Authentication, MFA, Access Control).** Answers: 1. Authentication: who are you? Access control: what may you do? 2. Two-factor / multi-factor authentication (2FA/MFA). 3. Teacher shares the document as view-only with students but gives group leaders edit permission.
10. **5.3.2 Data Protection (Encryption, Passwords, Backup, Firewall).** Answers: 1. SDN ($P \rightarrow S, A \rightarrow D, K \rightarrow N$). 2. 3 copies, 2 different media, 1 off-site copy. 3. Public key encrypts; private key decrypts.
11. **5.4.1 Common Security Threats (Malware, Phishing, DoS).** Answers: 1. Viruses, worms, spyware, ransomware, Trojans. 2. Floods it with thousands of fake requests so it slows down or crashes and real users cannot access it. 3. Data theft is stealing/copying data; identity theft is using stolen personal details (name, CNIC, bank) to pretend to be that person and commit fraud.
12. **5.4.2 Identifying Security Threats.** Answers: 1. Malware (or background unauthorised activity). 2. Phishing. 3. Unsafe downloads, cracked software, unverified websites, infected USB drives.
13. **5.4.3 Apply Mitigation Techniques.** Answers: 1. It also requires an OTP sent to your phone (a second factor). 2. You can restore a clean copy instead of losing the files (or paying). 3. Unknown links, suspicious attachments, and password sharing.
14. **5.5 Equity and Equal Access in Digital Collaboration.** Answers: 1. Giving everyone the exact same opportunity, tools and resources. 2. Giving additional, specific support so users who need it can reach the same outcome. 3. Because they are extra support for a student with hearing difficulties, not the same identical tool given to all.
15. **5.5.1 Functions of Equity and Equal Access.** Answers: 1. Need-based support; removing barriers; enabling active participation; supporting different learning needs. 2. Students who face power or internet outages can watch later and not fall behind. 3. It creates a hardware barrier for lower-income students; web-based or light apps give better access.
16. **5.5.2 Collaboration Tools.** Answers: 1. Google Docs. 2. Manage lectures, distribute assignments, conduct quizzes, grade activities. 3. Formal communication, official notices, large attachments, and a professional written record.
17. **Career Opportunities.** Answers: 1. Ethical hacker. 2. Data Privacy Officer.

Answer key

Multiple choice

1. b
2. c
3. a
4. d
5. b
6. a
7. c
8. d
9. b
10. a
11. c
12. d
13. a
14. b
15. d

Short questions — model answers

1. An ML model is the system that learns from data and gives an output — the trained brain of a program. Steps: (1) data input — massive data is given; (2) learning — it studies data and finds patterns/rules automatically; (3) prediction — after training it decides on new, unseen data.
2. A neural network is a computer model that learns patterns from data; it is inspired by the human brain but works as a mathematical system of connected neurons/nodes. Input layer receives the camera image; hidden layers study features such as eye distance and nose shape; output layer unlocks the phone if they match stored data.
3. A neural network is the model: layers, nodes and connections; it can be shallow (one or two hidden layers). Deep learning is the method of training networks that have many hidden layers, needing huge data and processing power for complex patterns.
4. Artificial intelligence is the largest set; machine learning is a part of AI; deep learning is a part of ML. All DL is ML and all ML is AI, but not all AI is ML and not all ML is DL.
5. Input layer; neurons/nodes; hidden layer(s); weights; bias; activation function; output layer; loss function. Weights show connection strength/importance. Bias is an extra constant that helps adjust the result and improve accuracy.
6. Large input data; many hidden layers; automatic feature learning; learning algorithm (e.g. backpropagation); high computing power (GPUs); training process (epochs).
7. Authentication confirms identity before access (password, PIN, OTP, biometrics — e.g. bank OTP). MFA/2FA requires two or more factor types, typically password + OTP. Access control decides what that user may do (view/edit/comment/download/share — e.g. Google Doc view-only for the class, edit for group leaders).
8. $S \rightarrow V$, $I \rightarrow L$, $N \rightarrow Q$, $D \rightarrow G$, $H \rightarrow K$ so ciphertext VLQGK. Caesar uses the same shift key to encrypt and decrypt, so it is symmetric.
9. Malware: harmful software (viruses, worms, spyware, ransomware, Trojans) — e.g. cracked software that corrupts files. Phishing: fake genuine-looking email/SMS/site stealing passwords or OTPs — e.g. fake JazzCash OTP page. DoS: flood of fake requests that slows or crashes a service — e.g. online exam portal students cannot enter.
10. Equal access: same tools/opportunity for everyone (same Zoom login). Equity: extra specific support so people with barriers reach the same outcome (captions for hearing difficulties). Functions: need-based support; removing barriers (low-data apps for remote areas); enabling participation (recorded lectures during load-shedding); supporting different learning needs (video, text, audio).

Long questions — model answers

1. **ML**: trained-brain model; data → learn patterns → predict on unseen data; used in face unlock, speech, photo search, diagnosis, translation. **NN**: brain-inspired maths model; neurons pass information through Input, Hidden, Output; face unlock: camera (input), eye distance/nose shape (hidden), unlock (output). **DL**: ML method with multi-layer NNs; “deep” = several hidden layers; early layers: edges/shapes/colours; deeper: whole face or car model; gallery search example. **Diagram**: three nested sets labelled AI, ML, DL with AI outermost. Sentence: $DL \subset ML \subset AI$.
2. **(a)** $s = 0.8 \times 0.4 + 0.5 \times 0.6 + 0.1 = 0.32 + 0.30 + 0.1 = 0.72$; $0.72 \geq 0.5$ so $y = 1$. **(b)** $s = 0.2 \times 0.4 + 0.3 \times 0.6 + 0.1 = 0.08 + 0.18 + 0.1 = 0.36$; $0.36 < 0.5$ so $y = 0$. **(c)** Eight components as in the table; sketch three input circles, four hidden, two output, labelled layers. **(d)** Huge labelled leaf photos; many hidden layers; features learned automatically; backpropagation; GPU training; many epochs until accuracy rises — cotton pest detector for a Sindh farm.
3. Cover all eight: image recognition (face lock, cameras); speech (assistant alarm, Urdu voice); NLP (Translate, chatbots); healthcare (X-ray/CT/MRI, pneumonia); recommendations (YouTube CS videos); autonomous vehicles (brake for pedestrian); fraud (unusual bank transaction); assistive (speech-to-text). Then Policy 2025: innovation, skills, ethics, digital growth. Sectors: education (tutoring, assessments); healthcare (rural diagnosis); agriculture (crops, irrigation, yield); business/banking (fraud, chatbots); local languages (Urdu, Sindhi). Students need Python, maths, data analysis, problem-solving, ethics.
4. Secure collaboration = working together with digital tools in a safe, controlled, responsible way. Authentication: prove identity (password/PIN/OTP/biometrics); bank OTP example. MFA: two or more of know/have/are; 2FA = password + phone OTP. Access control: view/edit/comment/download/share; teacher view-only vs group-leader edit. Accountability: LMS tracks who uploaded/submitted. Privacy: protect names, marks, passwords; share only with the right people; confidentiality; legal/ethical compliance. Safe transmission: encrypted official LMS, not an open public forum. Classroom scenario: school email + MFA, role permissions, version history, no CNICs on public WhatsApp.
5. Data protection = keeping digital information safe from unauthorised access, misuse, loss, damage or accidental deletion. Encryption: plaintext → ciphertext; symmetric = same key both ways; asymmetric = public encrypt, private decrypt. Caesar shift 3: SINDH → VLQ GK; decrypt by -3 ; wrap-around at Z. Strong password: upper, lower, number, symbol (e.g. Zk@2026#Pass) against brute force. 3-2-1: three copies, two media, one off-site (laptop + USB + Google Drive). Firewall: barrier monitoring/blocking suspicious network traffic. Antivirus: detects/removes malware on the local machine.
6. A security threat is any action, event or weakness that can harm a system or its data. Malware (cracked software); phishing (fake bank mail); unauthorised access (unlocked PC, weak/shared passwords); data theft vs identity theft (stolen CNIC used for fraud); DoS (exam portal flood); human error (wrong email, deleting files, falling for a scam). Signs table: pop-ups/missing files → malware; odd logins → unauthorised access; urgent OTP/bad grammar → phishing; records moved → theft; traffic spike → DoS. Mitigation: antivirus+firewall; strong passwords+2FA; encryption in transit; regular backups; user awareness (no unknown links, attachments, or shared passwords). Equal access vs equity; do not require a high-end phone-only app. Tools: Docs, Zoom, Teams, Classroom/LMS, WhatsApp (responsible), email (formal record).

Self-assessment: I can...

- ☐ define ML and explain data input → learning → prediction.
- ☐ describe a neural network and the face-unlock I-H-O path.
- ☐ list eight NN components and six DL components.
- ☐ explain authentication, MFA/2FA and access control with examples.
- ☐ identify malware, phishing and DoS from signs and name mitigations.
- ☐ choose a fair collaboration tool (Docs, Zoom, Teams, LMS, WhatsApp, email).
- ☐ draw AI $\supset$ ML $\supset$ DL and give a system that belongs in each layer.
- ☐ compute a neuron's weighted sum and threshold output from numbers.
- ☐ give eight applications of NN/DL and Pakistan's AI policy sectors.
- ☐ encrypt a short word with a Caesar cipher and apply the 3-2-1 backup rule.
- ☐ distinguish equal access from equity and state four functions of equity.

Entrepreneurship in the Digital Age

This chapter shows you how a real problem in your home, college or bazaar can become a business idea, and how you can test that idea cheaply with paper sketches, prototypes and a Minimum Viable Product (MVP) before you spend a lot of money. You will also learn how to choose your first users, the beachhead market, and how to collect feedback honestly and safely.

اس باب میں آپ سیکھیں گے کہ روزمرہ زندگی کے کسی حقیقی مسئلے کو کاروباری خیال میں کیسے بدلا جائے، اور پروٹوٹائپ (Prototype) اور ایم وی پی (MVP) کے ذریعے کم خرچ میں اس خیال کو کیسے آزمایا جائے۔

What you will learn

- Define **entrepreneur** and **entrepreneurship** and describe the habits of an entrepreneur.
- Turn an everyday problem into a business idea using the steps Observe, Ask Users, Select One Problem, Suggest Solution, Test Early.
- Draw and explain the prototype development cycle: Design, Build, Test, Iterate.
- Identify the **riskiest assumption** of a business idea and design a small test for it.
- Choose a focused **beachhead market** for a new idea.
- Explain how digital tools (WhatsApp, Google Forms, Facebook pages, simple websites) make it cheap and quick to start and test a business.
- Define a **prototype**, list its uses, and compare low-, mid- and high-fidelity prototypes.
- Define a **Minimum Viable Product (MVP)** and state at least five differences between a prototype and an MVP.
- Prepare an MVP plan using the MVP planning checklist, and test the MVP with number-based and comment-based feedback.
- Complete a small group project and use digital tools ethically, safely and fairly.

GOLDEN CONCEPTS

★ **Golden concepts in this chapter.** These ideas are taught first as lecture notes. If time is short, lock these before the other notes, then sit the chapter exam.

- ★ **6.2 Entrepreneurship in the Digital Age.** Entrepreneurship in the digital age means using digital tools to start, test, improve, and grow a business idea.
- ★ **6.4 Prototype.** A prototype is an early model of a product, service, website, or app.
- ★ **6.6 Prototype Development Cycle.** Prototype development is not a one-time activity.
- ★ **6.8 Minimum Viable Product (MVP).** A Minimum Viable Product (MVP) is the simplest working version of a product.
- ★ **6.14 Beachhead Market.** A beachhead market is a small and focused group of first users.

اس باب کے گولڈن تصورات پہلے پڑھیں۔ باقی نوٹس بعد میں۔

STUDENT · COACH

Self-taught. 18 notes · 5 ★ first · about 6 h 20 min. After the last note, sit the chapter exam (75 marks, 1 h 15 min).

Coach / teacher. 12 academy classes of 90 minutes (each ★ Golden is a full class; other notes pair). School: ★ = one 40-minute period.

ACADEMY CALENDAR

Chapter 6 academy calendar.

Class	Topics	Kind
Class 01	Entrepreneurship in the Digital Age	★ 90 min
Class 02	Prototype	★ 90 min
Class 03	Prototype Development Cycle	★ 90 min
Class 04	Minimum Viable Product (MVP)	★ 90 min
Class 05	Beachhead Market	★ 90 min
Class 06	Entrepreneur and Entrepreneurship + Local Examples of Digital Entrepreneurship (Table 6.1)	90 min
Class 07	From Problem to Business Idea + Types of Prototypes	90 min
Class 08	Class Activity: Create a Prototype + Difference between Prototype and MVP	90 min
Class 09	Identifying the Riskiest Assumption + Developing an MVP	90 min
Class 10	Case Study: MVP for a Canteen Pre-Order System + Testing an MVP	90 min
Class 11	Complete Student Project + Ethical and Safe Use of Digital Tools	90 min
Class 12	Career Opportunities	90 min

6.2 Entrepreneurship in the Digital Age ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 01 of 12 · 90 min · full Golden class. Board: Entrepreneurship in the digital age means using digital tools to start, test, improve, and grow a business idea..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Entrepreneurship in the digital age means using **digital tools** to **start, test, improve, and grow** a business idea.

These tools may include **mobile phones, social media, websites, online forms, digital payments, maps, videos, and simple apps**. In Pakistan you already know many of them: WhatsApp, Facebook, Instagram, TikTok, YouTube, Google Forms, Google Maps, and digital payments such as JazzCash, Easypaisa or Raast.

The power of digital tools

A digital entrepreneur **does not always need to create a complex mobile app**. Sometimes a **WhatsApp group**, a **Google Form**, a **Facebook page**, or a **simple website** is enough to test an idea.

In the past

- Large investment needed.
- Offices and shops had to be rented first.
- Long planning before anyone saw the product.
- A failed idea meant a big loss.

Today (digital age)

- A small idea can be tested **quickly**.
- Free tools: WhatsApp, Google Forms, Facebook.
- Feedback arrives in hours or days.
- If users do not like the idea, the team can **change it before spending too much money**.

WORKED EXAMPLE

Real-world relevance (from the source).

Example 1: A student selling **handmade cards through Instagram**. She posts photos of her Eid cards, people message her, and she delivers. No website, no app.

Example 2: A shopkeeper creating a **WhatsApp catalogue for Ajrak**. WhatsApp Business lets him list each Ajrak with a photo and price. Customers in Hyderabad or Karachi browse and order through chat.

Both are digital entrepreneurship **without writing a single line of code**.

Walk-through: how the Ajrak seller tests a new design cheaply.

1. He photographs 3 new Ajrak designs and adds them to the catalogue (cost: almost zero).
2. He sends the catalogue link to his customer broadcast list.
3. After one week he counts the orders per design.
4. He prints more of the design that sold most and stops the one nobody ordered.

He learned what customers want **before** printing a large stock.

REMEMBER IT

Remember "S-T-I-G": digital tools help you **Start, Test, Improve and Grow**. Think: "Start The Idea Growing."

COMMON MISTAKE

Mistake: "Digital entrepreneurship means building a mobile app."

Fix: An app is only one option. A WhatsApp group, Google Form, Facebook page or simple website is often enough, and much cheaper, to test whether people want your idea.

اردو میں سمجھیں

ڈیجیٹل دور میں انٹرپرائیورسپ کا مطلب ہے موبائل فون، سوشل میڈیا، ویب سائٹ، آن لائن فارم اور ڈیجیٹل ادائیگی جیسے ٹولز کے ذریعے کاروبار شروع کرنا، آزمانا اور بڑھانا۔ ہر بار پیچیدہ ایپ بنانا ضروری نہیں؛ واٹس ایپ گروپ یا گوگل فارم بھی کافی ہو سکتا ہے۔ اگر لوگوں کو خیال پسند نہ آئے تو زیادہ پیسہ خرچ ہونے سے پہلے اسے بدلا جا سکتا ہے۔

EXAM TIP

Common questions: "Define entrepreneurship in the digital age", "How have digital tools changed entrepreneurship?" and "Give examples of digital entrepreneurship without coding." Write the definition (start, test, improve, grow using digital tools), list 4–5 tools, give the past-versus-today contrast (big investment versus quick, cheap testing), and quote the Instagram cards and the WhatsApp Ajrak catalogue examples.

CHECK YOURSELF

1. List four digital tools that the source mentions.
2. Why is it easier to change a business idea today than in the past?
3. Give one example of digital entrepreneurship that needs no coding.

Write your answers in your notebook. The key follows this chapter's exam.

6.4 Prototype ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 02 of 12 · 90 min · full Golden class. Board: A prototype is an early model of a product, service, website, or app..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **prototype** is an **early model** of a product, service, website, or app. It shows **how the idea may look or work**. It is **NOT the final product**. It is made to **test the idea and collect feedback**.

Think of the clay model an architect makes before building a house, or the sample *kameez* a tailor stitches before making 50 for a shop. The model lets people say "make this bigger" or "move that here" before real money is spent.

Why is a prototype useful?


A prototype helps students and entrepreneurs **explain their idea clearly**, because users can **see something** instead of only listening to words.

- **It makes the idea visible.**
- **It helps the team find mistakes early.** Users can point out if a button is hard to find, if a screen has too much text, or if a feature is missing.
- **It saves time and money** before final coding begins. Fixing a pencil sketch takes a minute; fixing finished code can take days.

What form can a prototype take?

A prototype may be a **paper sketch**, a **cardboard model**, a **clickable PowerPoint**, a **Canva design**, a **Figma wireframe**, a **simple website layout**, or a **sample service process chart**. A *wireframe* is a simple outline drawing of a screen that shows where things go (boxes, buttons, text) without colours or pictures.

For example, for a **canteen pre-order system**, students can just **draw the screens on paper**.



A paper prototype of a canteen pre-order system: three hand-drawn screens joined by arrows (select item → enter name → collect order).

WORKED EXAMPLE

Worked example: how a paper prototype finds a mistake early. Bilal's team in a Nawabshah college draws the three screens above on A4 paper.

1. They hand screen 1 to a classmate and say, "Order a samosa."
2. The classmate looks for a quantity box and cannot find one. She asks, "What if I want two?"
3. The team notes: **feature missing: quantity**.
4. They add a small "Qty: []" box with a pencil in 30 seconds.

If they had already coded an app, adding quantity would have meant changing the database, the screen and the order list. The prototype **saved time and money**.

REMEMBER IT

Prototype = "practice model". It is like a rough draft of an essay: you show it, get corrections, and rewrite it before the final copy.

COMMON MISTAKE

Mistake: Thinking a prototype must work or must look beautiful.

Fix: A prototype only has to make the idea **visible** so users can react. A pencil sketch is a valid prototype.

اردو میں سمجھیں

پروٹوٹائپ (Prototype) کسی پراڈکٹ، سروس، ویب سائٹ یا ایپ کا ابتدائی نمونہ ہوتا ہے جو دکھاتا ہے کہ خیال کیسا نظر آئے گا یا کیسے کام کرے گا۔ یہ حتمی پراڈکٹ نہیں ہوتا بلکہ خیال کو آزمانے اور رائے (Feedback) لینے کے لیے بنایا جاتا ہے۔ یہ کاغذ کا خاکہ، گتے کا ماڈل، پاورپوائنٹ یا فگما (Figma) ڈیزائن بھی ہو سکتا ہے، اور اس سے غلطیاں جلد پکڑی جاتی ہیں اور وقت اور پیسہ بچتا ہے۔

EXAM TIP

Expect "Define prototype and write its benefits" (3–5 marks). Write: (1) definition with the words *early model*, *not the final product*, *test the idea and collect feedback*; (2) three benefits: makes the idea visible, finds mistakes early, saves time and money; (3) forms it can take (paper sketch, cardboard model, clickable PowerPoint, Canva, Figma wireframe); (4) the canteen paper-screens example.

CHECK YOURSELF

1. Is a prototype the final product?
2. Name four forms a prototype can take.
3. Give two kinds of problems users can point out by looking at a prototype.

Write your answers in your notebook. The key follows this chapter's exam.

6.6 Prototype Development Cycle ★ Golden

STUDENT · COACH


Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 03 of 12 · 90 min · full Golden class. Board: Prototype development is not a one-time activity..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Prototype development is **not a one-time activity**. A prototype is **created, tested, improved, and tested again**. This repeating process is called **iteration**. The main stages are **Design, Build, Test, and Iterate**.



The prototype development cycle: Design → Build → Test → Iterate, then back to Design.

Stage	What happens
1. Design	Understand the problem and plan the solution. Decide what the prototype should show (e.g. screen flow, features).
2. Build	Create the first version (physical or digital). The aim is not beauty; the aim is to make the idea visible.
3. Test	Show the prototype to users. Observe what they understand and what they find difficult.
4. Iterate	Improve the prototype based on user feedback. Remove unnecessary parts and add missing features.

WORKED EXAMPLE

Worked example: two rounds of the cycle. A team in Thatta wants a WhatsApp catalogue for a local Ajrak shop.

Round 1

- **Design:** The problem is that customers do not know which designs and prices are available. Plan: one page per design with photo, price and an "Order" message.
- **Build:** They make a paper booklet with 6 hand-drawn "catalogue pages".
- **Test:** They show it to 5 customers. Three ask, "Is this single or double-sided Ajrak? What size?"
- **Iterate:** They add size and type to every page.

Round 2

- **Design:** Add the size and type fields, and a delivery note.
- **Build:** They make the catalogue in WhatsApp Business with real photos.
- **Test:** 5 new customers browse it. Now nobody asks about size; one says the delivery charge is unclear.
- **Iterate:** They add "Delivery in Thatta: Rs 100" to each item.

Each round produces a clearer version, because each change comes from real feedback.

REMEMBER IT

Mnemonic: "Do Big Things Iteratively" = Design, Build, Test, Iterate. And remember the arrow at the end goes **back to Design**: it is a **cycle**, not a line.

COMMON MISTAKE

Mistake 1: Drawing the stages as a straight line that ends at "Iterate". **Fix:** Always draw a loop with an arrow from Iterate back to Design.

Mistake 2: Making the Build stage beautiful. **Fix:** The source says "The aim is not beauty; the aim is to make the idea visible."

اردو میں سمجھیں

پروٹوٹائپ ایک ہی بار میں نہیں بنتا؛ اسے بنایا، آزمایا، بہتر کیا اور دوبارہ آزمایا جاتا ہے۔ اس بار بار دہرانے کے عمل کو **ایٹریشن** (Iteration) کہتے ہیں۔ چار مراحل ہیں: ڈیزائن (مسئلہ سمجھ کر حل کی منصوبہ بندی)، **بلڈ** (پہلا نمونہ بنانا)، ٹیسٹ (صارفین کو دکھانا) اور **ایٹریشن** (رائے کی بنیاد پر بہتری)۔

EXAM TIP

A favourite long question: "Explain the prototype development cycle with a diagram." Draw the four boxes in a **circle** with arrows, write one or two lines for each stage using the source's words, define **iteration**, and finish with a short example (e.g. the ClassBuddy activity in 6.7). Marks are often lost for drawing a straight line instead of a cycle.

CHECK YOURSELF

1. What is iteration?
2. At which stage do you observe what users find difficult?
3. What is the aim of the Build stage?

Write your answers in your notebook. The key follows this chapter's exam.

6.8 Minimum Viable Product (MVP) ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 04 of 12 · 90 min · full Golden class. Board: A Minimum Viable Product (MVP) is the simplest working version of a product..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **Minimum Viable Product (MVP)** is the **simplest working version** of a product. It includes **only the most important features** needed to **test the idea with real users**.

- **Minimum:** it has only the **essential** features. No extras.
- **Viable:** it is **usable enough** to actually solve the main problem. ("Viable" means able to work successfully.)

An MVP is **not the final product**. It is also **not only a drawing**. It is a **small working version** used to test whether users actually need the solution.

WORKED EXAMPLE

Example from the source: canteen app.

Complete canteen app (final product)	Canteen MVP
Login, online payment, delivery tracking, discount offers...	A simple Google Form where students select snacks before break.

Step-by-step: how to cut a big idea down to an MVP.

1. List all features you dream of: login, payment, delivery tracking, discounts.
2. Ask of each one: "Without this, can a student still pre-order a snack?"
3. Login? Not needed; the student can type name and class. Payment? Not needed; pay at the counter. Delivery tracking? Not needed; students collect. Discounts? Not needed.
4. What is left is the core: **choose snack + name + class**. A Google Form does this for free. That form is **minimum** (no extras) and **viable** (students really can pre-order with it).

REMEMBER IT

Simple meaning. An MVP answers: "**Will people actually use this solution?**" It tests **real use and behaviour**, not only the visual design.

Analogy: before opening a full restaurant, a cook in Hyderabad sells biryani from home to office workers for two weeks. If people keep ordering, the idea is worth growing. That home kitchen is the MVP.

COMMON MISTAKE

Mistake 1: Calling a paper sketch an MVP. **Fix:** A sketch is a prototype. An MVP must **work** and be used by **real users**.

Mistake 2: Thinking MVP means a low-quality or broken product. **Fix:** It is small but **viable**; it must genuinely solve the main problem.

اردو میں سمجھیں

ایم وی پی (Minimum Viable Product) کسی پراڈکٹ کا سب سے سادہ مگر کام کرنے والا ورژن ہے جس میں صرف ضروری خصوصیات ہوتی ہیں۔ "منیمم" کا مطلب ہے صرف ضروری چیزیں، اور "وائیل" کا مطلب ہے کہ وہ اصل مسئلہ حل کرنے کے قابل ہو۔ یہ حتمی پراڈکٹ نہیں بلکہ یہ جانچنے کا ذریعہ ہے کہ کیا لوگ واقعی اسے استعمال کریں گے، جیسے کینٹین کے لیے ایک سادہ گوگل فارم۔

EXAM TIP

Typical questions: "What is an MVP? Explain the words Minimum and Viable" and "Give an example of an MVP." Write the full form, the definition (simplest working version, only most important features, test with real users), explain both words, state that it is neither the final product nor only a drawing, and give the canteen Google Form example. Mention the key question: "Will people actually use this solution?"

CHECK YOURSELF

1. Write the full form of MVP.
2. What does "Viable" mean in MVP?
3. What question does an MVP answer?

Write your answers in your notebook. The key follows this chapter's exam.

6.14 Beachhead Market ★ Golden

STUDENT · COACH

Self-taught. 25 minutes ★. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 05 of 12 · 90 min · full Golden class. Board: A beachhead market is a small and focused group of first users..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A **beachhead market** is a **small and focused group of first users**. These users have a **clear need** and are **likely to try the product early**.


Instead of trying to serve everyone, entrepreneurs **first focus on one small group**. This helps them **test the MVP properly and improve it before expanding**.

The word comes from the army: a *beachhead* is the small piece of beach soldiers capture first when they land; from there they move inland. In business, your beachhead is the first small group you "win".

Characteristics of a good beachhead market

- It should be **specific and narrowly defined**.
- It should be **reachable** by the startup team.
- The users should have a **strong, immediate need** for the solution.

For example, targeting "**all students in Pakistan**" is too broad for a new study app. "**Grade XII students preparing for board exams in one college**" is much more focused and easier to reach.



Start with the small inner circle (beachhead), learn and improve, then expand outward.

Table 6.11: Choosing a focused beachhead market

Business Idea	Weak First Market	Better Beachhead Market
Study app	All students in Pakistan.	Grade XII students preparing for exams in one college.
Canteen pre-order	All canteens in the city.	One college canteen during lunch break.
Ajrak catalogue	All online shoppers.	Existing customers of one local shop.
Van update system	All transport users.	Students and parents of ONE specific college van route.

Choosing a small first market **does not mean the idea will remain small forever**. After learning from this group, the idea can be improved and expanded, even globally.

WORKED EXAMPLE

Worked example: test a proposed beachhead against the three characteristics. Idea: an app that reminds farmers about irrigation water turns (*warabandi*).

Proposed market	Specific?	Reachable?	Strong, immediate need?	Verdict
All farmers in Sindh	No	No (millions of people, many districts)	Varies	Weak
Farmers on one watercourse near Badin whose sons/daughters study in the team's college	Yes	Yes (through classmates)	Yes (missing a turn damages crops)	Good beachhead

Expansion path: one watercourse → nearby watercourses → the whole district → other districts.

REMEMBER IT

Remember S-R-U: Specific, Reachable, Urgent need. If you cannot meet your first users within a week, your market is too big.

COMMON MISTAKE

Mistake: Thinking a bigger first market means more success ("everyone can use my app").

Fix: A broad market is hard to reach and hard to learn from. Win a small group first, learn, improve, then expand.

بیج ہیڈ مارکیٹ (Beachhead Market) پہلے صارفین کا ایک چھوٹا اور مخصوص گروہ ہے جسے حل کی واضح اور فوری ضرورت ہو اور جو پراڈکٹ جلد آزمانے پر تیار ہو۔ سب کو ایک ساتھ خدمت دینے کے بجائے پہلے ایک چھوٹے گروہ پر توجہ دیں، جیسے "پاکستان کے تمام طلبہ" کے بجائے "ایک کالج کے بارہویں جماعت کے طلبہ"۔ وہاں سے سیکھ کر خیال کو بعد میں پھیلا دیا جا سکتا ہے۔

EXAM TIP

Asked as "Define beachhead market and give its characteristics" or "Suggest a beachhead market for ...". Write the definition (small, focused group of first users with a clear need, likely to try early), the three characteristics (specific, reachable, strong immediate need), one weak-versus-better pair from Table 6.11, and the line that a small first market does not mean the idea stays small.

CHECK YOURSELF

1. Give the three characteristics of a good beachhead market.
2. What is the better beachhead market for the van update system?
3. Does choosing a small first market mean the business will stay small?

Write your answers in your notebook. The key follows this chapter's exam.

6.1 Entrepreneur and Entrepreneurship

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 06 of 12 · 45 min · first half · with Local Examples of Digital Entrepreneurship (Table 6.1). Board: An entrepreneur is a person who identifies a problem, thinks of a solution, and tries to change that solution into a product or service..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

An **entrepreneur** is a person who **identifies a problem, thinks of a solution, and tries to change that solution into a product or service.**

An entrepreneur does not always begin with a large company or a big office. Many begin with a small idea, limited resources, and a strong wish to solve a problem. Think of a young person in Karachi who starts by delivering home-cooked lunch boxes to a few offices, or a student in Sukkur who repairs mobile phones for neighbours. They started small.

Entrepreneurs usually show three habits:

- **They observe people and listen to their needs.** They notice what annoys people again and again.
- **They take calculated risks.** A *calculated risk* is a risk you take after thinking about what you could lose and how to keep that loss small. It is not gambling.
- **They improve their idea step by step.** They do not expect the first attempt to be perfect.

What is entrepreneurship?

Entrepreneurship is the **process** of **planning, starting, testing, and improving** a business idea. It involves **creativity, problem-solving, teamwork, communication, and calculated risk.**

Notice the difference: the *entrepreneur* is the **person**; *entrepreneurship* is the **process** that person goes through.

REMEMBER IT

Simple meaning. An entrepreneur asks: "*What problem can I solve?*" Entrepreneurship is the process of testing and improving that solution until it becomes useful for people.

Remember the three-step journey:

1. Problem → 2. Solution → 3. Product

WORKED EXAMPLE

Worked example: spotting the three steps. Ayesha lives in Larkana. Her mother and other women in the street make beautiful hand-embroidered *rillis*, but they can only sell them to visitors.

Step 1, Problem: skilled women have products but very few buyers.

Step 2, Solution: show the rillis online so buyers from other cities can see them.

Step 3, Product/Service: a Facebook page with photos, prices and a "message to order" button.

Ayesha is the **entrepreneur**. Planning the page, posting photos, seeing which designs sell, and changing prices is **entrepreneurship**.

COMMON MISTAKE

Mistake: "Only rich people with big offices can be entrepreneurs."

Fix: The source clearly says many entrepreneurs begin with a small idea and limited resources. What matters is a real problem, a useful solution, and the willingness to improve it.

اردو میں سمجھیں

کاروباری شخص (Entrepreneur) وہ ہوتا ہے جو کسی مسئلے کو پہچانتا ہے، اس کا حل سوچتا ہے اور اس حل کو کسی پراڈکٹ یا سروس میں بدلنے کی کوشش کرتا ہے۔ کاروبار شروع کرنے، آزمانے اور بہتر بنانے کے پورے عمل کو انٹرپرائیورشپ (Entrepreneurship) کہتے ہیں۔ ایسا شخص لوگوں کی بات سنتا ہے، سوچ سمجھ کر خطرہ مول لیتا ہے اور اپنے خیال کو قدم بہ قدم بہتر بناتا ہے۔

CHECK YOURSELF

1. Is "entrepreneurship" a person or a process?
2. Name the three habits of an entrepreneur given in the source.
3. What is a calculated risk?

Write your answers in your notebook. The key follows this chapter's exam.

Local Examples of Digital Entrepreneurship (Table 6.1)

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 06 of 12 · 45 min · second half · with Entrepreneur and Entrepreneurship. Board: Digital entrepreneurship can begin from ordinary problems..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Digital entrepreneurship can begin from **ordinary problems**. The examples below are close to the context of Sindh and Pakistan, where many students, parents, and small service providers already use mobile phones.

Problem	Digital Idea	Possible First Users	Urdu Context
Parents miss college notices.	WhatsApp notice and reminder service.	Parents of first-year students.	والدین تک کالج کے نوٹس پہنچانے کے لیے واٹس ایپ سروس۔
Small embroidery shop has few customers.	Simple catalogue with order form on Facebook or WhatsApp.	Customers in the same city.	کڑھائی کی دکان کے لیے واٹس ایپ کیٹلاگ۔
Students forget test dates.	Google Calendar guide or simple reminder app.	Grade XII students.	ٹیسٹ کی تاریخیں یاد دلانے والی ایپ یا کیلنڈر۔
Canteen has long queues during break.	Pre-order form for snacks.	Students and teachers.	کینٹین کے لیے پری آرڈر فارم۔

Read each row from left to right: a **problem** → a **simple digital idea** → a **small group of first users**. You will see these same examples again later in the chapter (the canteen pre-order system becomes a full case study).

WORKED EXAMPLE

Worked example: adding your own row. Follow the same pattern for a new local problem.

Problem	Digital Idea	Possible First Users
Students in a Mirpurkhas college lose water bottles, calculators and ID cards and never find them.	Lost-and-found Google Form plus a WhatsApp group where found items are posted with a photo.	Students of one college.

Check: Is it a **real** problem? Yes, it happens every week. Is the idea **simple**? Yes, a form and a group. Are the first users **reachable**? Yes, they are in the same college.

COMMON MISTAKE

Important: A digital business idea should **not** be selected only because it sounds modern. It should solve a **real problem for real users**. If the problem is weak, the business idea will also be weak.

For example, "an AI app that chooses your shirt colour" sounds modern, but if nobody actually struggles with that, nobody will use it.

REMEMBER IT

Think "Problem first, tool second." Start with the pain, not with the technology.

اردو میں سمجھیں

جدول 6.1 بتاتی ہے کہ ڈیجیٹل کاروبار عام مسائل سے شروع ہو سکتا ہے، جیسے والدین کا کالج نوٹس نہ دیکھ پانا، کڑھائی کی دکان پر کم گاہک، ٹیسٹ کی تاریخ بھول جانا یا کینٹین پر لمبی قطار۔ کوئی خیال صرف اس لیے نہ چنیں کہ وہ جدید لگتا ہے؛ اسے حقیقی لوگوں کا حقیقی مسئلہ حل کرنا چاہیے۔

CHECK YOURSELF

1. In Table 6.1, what digital idea is suggested for a small embroidery shop?
2. Who are the possible first users of the canteen pre-order form?
3. Why should an idea not be chosen only because it sounds modern?

Write your answers in your notebook. The key follows this chapter's exam.

6.3 From Problem to Business Idea

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 07 of 12 · 45 min · first half · with Types of Prototypes. Board: A good business idea usually starts from observing daily life..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

A good business idea usually starts from **observing daily life**. Look around your home, college, market, village, or city and ask these simple questions:

1. **What problem do people face?**
2. **Who faces this problem?**
3. **How often does it happen?**
4. **What do people currently do to solve it?**
5. **Can technology help in a simple way?**

A short way to remember them: **What? Who? How often? Current fix? Tech help?**

WORKED EXAMPLE

Example scenario (from the source): study material before exams.

Students cannot find study material before exams. The quick answer is "students are careless", but that is not the real issue.

Apply the five questions:

1. **What problem?** Students cannot find notes before exams.
2. **Who?** Students of a class or college.
3. **How often?** Before every test and exam.
4. **Current fix?** Notes are shared in many places: WhatsApp, email, photocopies, and class groups. Students search all of them.
5. **Tech help?** Yes: a simple **subject-wise notes organizer** where all files are placed in one location (for example, one shared Google Drive folder per subject).

The real problem is **scattered notes**, and the idea solves exactly that.

Scope of the problem

Avoid choosing **very large problems** at the start, such as "improving the whole education system". A better problem is **smaller and clear**, such as helping Grade XII students track **practical file submission dates**. Smaller problems are **easier to test and improve**.

Table 6.2: From problem to idea

The journey from observing a problem to creating an idea follows a structured path.

Step	What Students Do	Example
Observe	Notice repeated problems around home, college, or market.	Students forget practical file dates.
Ask Users	Talk to people who face the problem.	Ask five classmates how they remember deadlines.
Select One Problem	Choose one clear problem only.	Practical file reminder.
Suggest Solution	Think of a simple digital or paper-based solution.	Reminder form or app screen.
Test Early	Show the idea to users before final development.	Ask classmates if they will use it.

After this, the idea moves along the full path that the rest of this chapter follows:



REMEMBER IT

Mnemonic for Table 6.2: "Only Ask Simple Solutions Today": Observe, Ask users, Select one problem, Suggest solution, Test early.

COMMON MISTAKE

Mistake 1: Choosing a huge problem ("fix traffic in Karachi"). **Fix:** Narrow it ("help students of one college know when their van will arrive").

Mistake 2: Skipping "Ask Users" and guessing what people need. **Fix:** Talk to at least five real people who face the problem.

اردو میں سمجھیں

اچھا کاروباری خیال روزمرہ زندگی کے مشاہدے سے شروع ہوتا ہے۔ پوچھیں: مسئلہ کیا ہے، کس کو ہے، کتنی بار ہوتا ہے، لوگ ابھی کیا کرتے ہیں، اور کیا ٹیکنالوجی آسان طریقے سے مدد کر سکتی ہے؟ شروع میں چھوٹا اور واضح مسئلہ چنیں، کیونکہ اسے آزمانا اور بہتر بنانا آسان ہوتا ہے۔

CHECK YOURSELF

1. Write the five steps of Table 6.2 in order.
2. Why is "improving the whole education system" a poor first problem?
3. In the study-material example, what is the real problem?

Write your answers in your notebook. The key follows this chapter's exam.

6.5 Types of Prototypes

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 07 of 12 · 45 min · second half · with From Problem to Business Idea. Board: Prototypes are commonly divided into three types according to their level of detail, called fidelity..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Prototypes are commonly divided into **three types** according to their level of detail, called **fidelity**. **Fidelity means how close the prototype is to the final product.** Low fidelity = far from final; high fidelity = very close to final.

6.5.1 Low-Fidelity Prototype

A **quick and rough** model made at the **very beginning**. It is **drawn on paper**. It does **not focus on colours or fonts**. It shows the **main idea and flow** (which screen comes after which). It is **very suitable for students** because it is **cheap, fast, and easy to change**.

6.5.2 Mid-Fidelity Prototype

Clearer than a paper sketch. It is created in **PowerPoint, Canva, or Figma**. It shows screens and **navigation** in a more organised way, but **without final graphics**. It is useful to **test screen-to-screen navigation**, for example by linking slides so that clicking "Next" opens the next screen.

6.5.3 High-Fidelity Prototype


Looks **very close to the final product**. It includes **realistic colours, buttons, sample data, and working features**. It **takes more time** and should **only be created after the basic idea is tested**.

Comparison of prototype types

For most school and college projects, you should **begin with a low-fidelity prototype**. A common mistake is to start building a full app before knowing whether users need it. A rough prototype protects you from this mistake.

Table 6.3: Types of prototypes

Type	Meaning	Best Use	Example
Low-Fidelity	A quick and rough model of the idea.	Very early testing.	Hand-drawn app screens for homework reminder.
Mid-Fidelity	A clearer model that shows layout and flow.	Testing navigation.	Clickable screens in PowerPoint or Figma.
High-Fidelity	A detailed model close to the final product.	Testing realistic experience.	Working demo of a small order form website.



Extra comparison to help you revise:

Feature	Low-Fidelity	Mid-Fidelity	High-Fidelity
Tool	Paper and pencil	PowerPoint, Canva, Figma	Figma (detailed), HTML
Colours and fonts	No	Not final	Realistic
Clickable?	No (you move papers by hand)	Yes, basic links	Yes, with working features
Cost and time	Lowest, fastest	Medium	Highest, slowest
Easy to change?	Very easy	Fairly easy	Harder
When	Very beginning	After the flow is agreed	Only after the basic idea is tested

WORKED EXAMPLE

Worked example: one idea, three fidelities. Idea: a Homework Reminder for a college in Jacobabad.

- Low-fi:** Sana draws three screens on paper in 15 minutes: "Today", "Add homework", "Reminder". Classmates point at the drawings to "use" them.
- Mid-fi:** After feedback, she makes three PowerPoint slides with grey boxes and links them with hyperlinks, so tapping "Add" opens the Add slide. Now she tests whether people can move between screens easily.
- High-fi:** Once users clearly want it, she builds a small HTML page with real colours, a working form and sample homework data.

Each step costs more, so she only moves up when the previous step proves the idea is worth it.

REMEMBER IT

Fidelity = "faithfulness" to the final product. Remember **Paper → PowerPoint → Polished** (low → mid → high).

COMMON MISTAKE

Mistake: Starting with a high-fidelity prototype or a full app because it "looks professional".

Fix: Begin with low fidelity. If users do not need the idea, you have lost only paper and an hour, not weeks of work.

اردو میں سمجھیں

فِڈیلیٹی (Fidelity) کا مطلب ہے کہ پروٹوٹائپ حتمی پراڈکٹ سے کتنا ملتا جلتا ہے۔ لو فِڈیلیٹی کاغذ پر بنایا گیا سستا اور جلدی بننے والا خاکہ ہے؛ مڈ فِڈیلیٹی پاورپوائنٹ، کینوا یا فگما میں بنتا ہے اور اسکرینوں کے درمیان آنا جانا (Navigation) دکھاتا ہے؛ ہائی فِڈیلیٹی بالکل اصل پراڈکٹ جیسا لگتا ہے اور اسے بنیادی خیال آزمانے کے بعد ہی بنانا چاہیے۔

CHECK YOURSELF

1. What does "fidelity" mean?
2. Which type of prototype is best for testing navigation?
3. Why should students begin with low fidelity?

Write your answers in your notebook. The key follows this chapter's exam.

6.7 Class Activity: Create a Prototype

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 08 of 12 · 45 min · first half · with Difference between Prototype and MVP. Board: Business idea scenario..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Business idea scenario. Students often forget **homework deadlines, test dates, and required class items**. A group of students wants to design a simple "**Homework Helper**" or "**ClassBuddy**" reminder system.

The team will **not** immediately build a complete mobile app. They will first **understand the problem, draw a low-fidelity prototype, test it with classmates, and improve it**. This activity is the development cycle of 6.6 in action.

1. Understand → 2. Draw low-fi → 3. Test → 4. Analyse feedback → 5. Improve

Step 1: Understand the problem

The team **interviews ten students**. They find that **7 out of 10** students (that is 70%) forget at least one task in a week. Students want **reminders before leaving home**, and some prefer a **very simple design**.

Table 6.4: Understanding user needs

Finding	Meaning	Design Decision
7 out of 10 forget tasks.	The problem is common.	App should show a daily task list.
Reminders needed before leaving home.	Reminder time is important.	Add morning notification option.
Students want simple apps.	Design must be simple.	Use large buttons and clear labels.

Step 2: Draw a low-fidelity prototype

The team draws **three screens on paper**: (1) **Today's classes**, (2) **Add homework**, (3) **Show reminder**. **Arrows** show how a user moves from one screen to another.

Step 3: Test the prototype

The team gives the paper screens to **five classmates**. The **observer watches silently** to see if users can understand the design by themselves. Users are given one task: **"add one homework task"**.

Step 4: Analyse feedback

The team looks for **repeated problems** in the feedback to identify what actually needs fixing.

Table 6.5: Changing feedback into improvement

User Feedback	Problem Identified	Improvement
"I cannot quickly find Add Homework."	Button is not visible.	Make Add Homework button larger and centre it.
"I want reminders by subject."	Reminder is too general.	Add subject name and due date fields.
"I want to see all tasks for the week."	Only daily view is not enough.	Add a 'Weekly View' button.

Step 5: Improve the prototype

The team **redraws the home screen** with a **larger Add Homework button**, a **subject list**, and a **weekly view**. This second version is clearer because it is based on real user feedback.

A prototype has not failed when users give negative feedback; it only fails if the team ignores useful feedback.

WORKED EXAMPLE

Worked example: link the activity to the cycle.

Cycle stage	ClassBuddy activity step
Design	Step 1: interview 10 students, make design decisions (Table 6.4).
Build	Step 2: draw three paper screens with arrows.
Test	Step 3: five classmates try "add one homework task" while the observer watches silently.
Iterate	Steps 4 and 5: analyse feedback (Table 6.5) and redraw the home screen.

Why watch silently? If the observer explains ("tap here"), the team never learns that the button is hard to find. Silence shows the real difficulty.

REMEMBER IT

Feedback → Problem → Improvement. Every comment should be turned into a problem statement and then one clear change, exactly like the three columns of Table 6.5.

COMMON MISTAKE

Mistake: Feeling that negative feedback means the prototype "failed", or changing the design for every single comment.

Fix: Negative feedback is useful information. Look for **repeated** problems and fix those first. The prototype only fails if you ignore useful feedback.

اردو میں سمجھیں

اس سرگرمی میں طلبہ "کلاس بڈی" (ClassBuddy) نامی یاد دہانی نظام بناتے ہیں۔ پہلے دس طلبہ سے بات کر کے مسئلہ سمجھتے ہیں، پھر کاغذ پر تین اسکرینیں بناتے ہیں، پانچ ساتھیوں سے خاموشی سے آزمواتے ہیں، رائے کا تجزیہ کرتے ہیں اور ڈیزائن بہتر کرتے ہیں۔ منفی رائے سے پروٹوٹائپ ناکام نہیں ہوتا؛ ناکامی تب ہے جب مفید رائے کو نظر انداز کیا جائے۔

CHECK YOURSELF

1. In Step 1, how many students forgot at least one task in a week, and what percentage is that?
2. Name the three paper screens drawn in Step 2.
3. What improvement was made for the feedback "I want to see all tasks for the week"?

Write your answers in your notebook. The key follows this chapter's exam.

6.9 Difference between Prototype and MVP

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 08 of 12 · 45 min · second half · with Class Activity: Create a Prototype. Board: Prototype and MVP are related, but not the same..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Prototype and MVP are **related, but not the same**. A **prototype** is mainly used to **show and test the design** of an idea. An **MVP** is used to **test real use and market demand**. *Market demand* means whether enough people want the product and will use (or pay for) it.

Usually a prototype comes first and an MVP comes after it: Problem → Idea → Prototype → Feedback → MVP.

Table 6.6: Prototype and MVP comparison

Point	Prototype	MVP
Main purpose	To show how the idea may look or work.	To test whether users will actually use the solution.
Working status	May not work; can be a sketch or model.	Must work at least in a basic way.
Users	Small group gives feedback on design.	Early real users test the product in daily life.
Cost	Very low cost.	Low cost but may need some basic development.
Example	Paper screens for a canteen order system.	Google Form used for real canteen orders for three days.

REMEMBER IT

Key takeaway

Prototype = "Does it **look right** and make sense?"

MVP = "Will people **actually use it** and find value in it?"

Memory hook: **Prototype** → **P**icture of the idea; **MVP** → **M**arket test of the idea.

WORKED EXAMPLE

Worked example: classify each item. Decide whether each is a prototype or an MVP and give the reason.

1. Hand-drawn screens of a tuition-finder app shown to 6 friends. → **Prototype**: it does not work; it tests design.
2. A WhatsApp broadcast group that really sends van arrival times to parents of one route for a week. → **MVP**: it works and real users use it daily.
3. Clickable PowerPoint screens of a notes organizer. → **Prototype** (mid-fidelity): links work, but nobody uses it for real notes.
4. A shared Google Drive folder per subject that a class actually uses before the monthly test. → **MVP**: real use in daily life.

Rule used: **Does it work, and is it used by real users in real life?** If yes → MVP. If it only shows the design → prototype.

COMMON MISTAKE

Mistake: Thinking "high-fidelity prototype" and "MVP" are the same because both look good.

Fix: The difference is **purpose and real use**, not appearance. A beautiful Figma design that nobody uses for real orders is still a prototype; a plain Google Form taking real orders is an MVP.

اردو میں سمجھیں

پروٹوٹائپ اور ایم وی پی آپس میں جڑے ہیں مگر ایک جیسے نہیں۔ پروٹوٹائپ خیال کا ڈیزائن دکھاتا اور آزماتا ہے اور ضروری نہیں کہ کام کرے، جبکہ ایم وی پی کم از کم بنیادی طور پر کام کرتا ہے اور اصل صارفین روزمرہ زندگی میں اسے استعمال کرتے ہیں۔ پروٹوٹائپ پوچھتا ہے "کیا یہ ٹھیک لگتا ہے؟" اور ایم وی پی پوچھتا ہے "کیا لوگ واقعی اسے استعمال کریں گے؟"

CHECK YOURSELF

1. Which one must work at least in a basic way?
2. Give the source's example of a prototype and of an MVP for the canteen.
3. Which question does a prototype answer?

Write your answers in your notebook. The key follows this chapter's exam.

6.10 Identifying the Riskiest Assumption

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 09 of 12 · 45 min · first half · with Developing an MVP. Board: Every business idea is based on assumptions..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Every business idea is based on **assumptions**. An **assumption** is something we **believe to be true, but have not tested yet**.

The **riskiest assumption** is the belief that can make the **entire business fail** if it turns out to be wrong.

Entrepreneurs should **identify and test the riskiest assumption early**, because it **saves time and money**. If it is wrong, you find out before building everything else.

Table 6.7: Testing risky assumptions

Business Idea	Possible Risky Assumption	How to Test It (MVP)
Online tuition finder	Students will pay for online tutoring.	Ask 20 students and offer a trial class to see if they sign up.
Canteen pre-order form	Students will order snacks before break.	Test a Google Form for one week in real time.
Ajrak online catalogue	Customers will place orders through WhatsApp.	Share catalogue with 30 customers and record actual orders.
College van update system	Parents and students will check van updates daily.	Create a trial WhatsApp broadcast group for one route.

Notice that every test measures **what people actually do** (sign up, order, check), not just what they say.

WORKED EXAMPLE

Worked example: finding the riskiest assumption. Idea: a home-tutor booking service for Grade IX–X students in Sukkur.

Step 1, list assumptions:

1. Parents want home tutors for their children.
2. Good tutors in Sukkur are willing to join.
3. Parents will **pay a booking fee** through our service instead of finding tutors through relatives.
4. Parents will like our logo.

Step 2, ask of each: "If this is wrong, does the whole business fail?" Logo (4): no, easily changed. Parents wanting tutors (1): very likely true; many already hire tutors. Tutors joining (2): important, but easy to check by phoning a few tutors. Paying a booking fee (3): if parents refuse to pay, the business earns nothing, so **this is the riskiest assumption**.

Step 3, design a small MVP test: post the offer in 3 parent WhatsApp groups for one week, offer a first booking at a small fee, and **count how many actually pay**.

REMEMBER IT

Ask: "What would kill this idea?" The answer is usually the riskiest assumption. Test it **first**, cheaply, with real behaviour.

COMMON MISTAKE

Mistake: Testing easy, safe assumptions (colours, names) first and leaving the dangerous one for later.

Fix: Test the assumption that could make the whole business fail first. Also, do not trust only "Yes, I would use it". Measure actual sign-ups or orders.

اردو میں سمجھیں

ہر کاروباری خیال کچھ مفروضوں (Assumptions) پر قائم ہوتا ہے، یعنی وہ باتیں جنہیں ہم سچ سمجھتے ہیں مگر ابھی آزمایا نہیں۔ سب سے خطرناک مفروضہ (Riskiest Assumption) وہ ہے جو غلط نکلے تو پورا کاروبار ناکام ہو جائے۔ اسے شروع میں ہی چھوٹے ایم وی پی سے آزمانا چاہیے تاکہ وقت اور پیسہ بچ سکے۔

CHECK YOURSELF

1. Define assumption.
2. What is the risky assumption for the Ajrak online catalogue, and how is it tested?
3. Why test the riskiest assumption early?

Write your answers in your notebook. The key follows this chapter's exam.

6.11 Developing an MVP

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 09 of 12 · 45 min · second half · with Identifying the Riskiest Assumption. Board: To develop an MVP, the team must select only the essential features..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

To develop an MVP, the team must **select only the essential features**. Extra features should be avoided at the beginning. A common mistake is **trying to build everything at once**. This makes the product **difficult, costly, and slow**.

An **MVP plan** should clearly explain: the **problem, target users, main feature, basic design, estimated cost, marketing method, feedback method, and improvement plan**.

Table 6.8: MVP planning checklist

MVP Element	Question to Ask	Example Answer
Problem	What problem are we solving?	Students wait too long at canteen.
Target users	Who will use it first?	Grade XII students in one college.
Main feature	What is the ONE feature that solves it?	Pre-order snacks before break.
Basic design	What steps are needed?	Menu, name, class, order time.
Cost	What free/low-cost tools to use?	Google Form or printed slips.
Marketing	How will early users hear about it?	WhatsApp message to class group.
Feedback	How will users respond?	Short feedback form after 3 days.

The eighth element, the **improvement plan**, answers "What will we change after feedback?" (you will see it in the case study in 6.12).

WORKED EXAMPLE

Worked example: filling the checklist for a new idea. Idea: a college notice reminder for parents in Hyderabad (from Table 6.1).

MVP Element	Answer
Problem	Parents miss college notices (fee dates, PTMs, holidays).
Target users	Parents of first-year (Class XI) students of one college.
Main feature	Send each notice to parents' phones on the same day.
Basic design	Photo of notice + 2-line summary in Urdu and Sindhi + date.
Cost	Free: WhatsApp broadcast list from the college office phone.
Marketing	Students give a printed slip to parents with the number to save.
Feedback	After 2 weeks, a 3-question voice-note or phone survey of 20 parents.
Improvement plan	If parents say notices come too late, send a reminder 1 day before each date.

Notice: only **one** main feature, a **free** tool, and a clear way to collect feedback.

REMEMBER IT

Mnemonic for the 8 elements: "People Try My Bakery; Cheap Muffins Find Improvement": Problem, Target users, Main feature, Basic design, Cost, Marketing, Feedback, Improvement plan.

COMMON MISTAKE

Mistake: Writing a list of ten "main features".

Fix: The checklist asks for the **ONE** feature that solves the problem. Everything else waits until the MVP proves people want it.

اردو میں سمجھیں

ایم وی پی بنانے وقت صرف ضروری خصوصیات چنیں؛ سب کچھ ایک ساتھ بنانے سے کام مشکل، مہنگا اور سست ہو جاتا ہے۔ ایم وی پی منصوبے میں مسئلہ، پہلے صارفین، ایک بنیادی خصوصیت، سادہ ڈیزائن، کم خرچ ٹولز، تشہیر کا طریقہ، رائے لینے کا طریقہ اور بہتری کا منصوبہ واضح ہونا چاہیے۔

CHECK YOURSELF

1. Why is building everything at once a mistake?
2. List the eight elements of an MVP plan.
3. In Table 6.8, what is the marketing method?

Write your answers in your notebook. The key follows this chapter's exam.

6.12 Case Study: MVP for a Canteen Pre-Order System

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 10 of 12 · 45 min · first half · with Testing an MVP. Board: Problem: In a college, students wait in long lines at the canteen..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Problem: In a college, students wait in long lines at the canteen. Sometimes snacks finish before students reach the counter. A group wants to test a canteen pre-order idea.

Goal: Their aim is **NOT** to create a complete app immediately. Their aim is to test **whether students will place orders before break** and **whether the canteen can manage these orders**.

The approach

1. The team creates a **paper prototype** showing three steps: **select item, enter name, collect order**.
2. **Feedback** from the prototype suggests the **menu should be short** and **payment should be at collection time**.
3. For the actual MVP, the team uses a **Google Form**. Students select **one of five items**.
4. The canteen prepares these pre-orders. This MVP is tested for **three days only** to learn quickly.

Paper prototype → Feedback: short menu, pay at collection → Google Form MVP → 3-day test →

Improve

Table 6.9: MVP plan for canteen pre-order system

MVP Element	Decision
Features	Menu list, student name, class, item, and quantity.
Cost & Tools	Free Google Form or printed order slips.
Marketing	Class announcement and WhatsApp group message.
Testing period	Three days.
Feedback method	Ask students if they saved time and would use it again.
Improvement	Keep only 5 items; close orders 20 minutes before break.

Result: Students liked saving time, but **canteen staff found too many items difficult**. The team improved the MVP by **keeping only five items** and creating a **separate collection line**. This improvement is based on real feedback.

WORKED EXAMPLE

Worked example: trace the case study through the chapter's ideas.

Chapter idea	Where it appears in the case study
Real problem (6.3)	Long queues; snacks finish before students reach the counter.
Low-fidelity prototype (6.5)	Paper screens: select item, enter name, collect order.
Iteration (6.6)	Feedback led to a short menu and payment at collection.
MVP (6.8)	Google Form with one of five items, used for real orders.
Riskiest assumption (6.10)	Students will order before break, and the canteen can manage the orders.
Beachhead market (6.14)	One college canteen during break.

Why "close orders 20 minutes before break"? Staff need time to prepare. If orders arrive at the last minute, the pre-order line becomes as slow as the normal line, and the main benefit disappears.

REMEMBER IT

Remember the case study as **"5 items, 3 days, 20 minutes"**: five menu items, a three-day test, orders closing twenty minutes before break.

COMMON MISTAKE

Mistake: Thinking only the students' opinion matters.

Fix: The case study tested **two** things: whether students will order **and** whether the canteen can manage the orders. The staff's feedback (too many items) caused the key improvement.

اردو میں سمجھیں

ایک کالج میں طلبہ کینٹین کی لمبی قطاروں میں انتظار کرتے تھے۔ ٹیم نے فوراً ایپ بنانے کے بجائے پہلے کاغذی پروٹوٹائپ بنایا، پھر تین دن کے لیے گوگل فارم کو ایم وی پی کے طور پر آزمایا جس میں پانچ اشیاء تھیں۔ طلبہ کو وقت کی بچت پسند آئی مگر عملے کو زیادہ اشیاء مشکل لگیں، اس لیے صرف پانچ اشیاء رکھی گئیں، الگ قطار بنائی گئی اور بریک سے بیس منٹ پہلے آرڈر بند کیے گئے۔

CHECK YOURSELF

1. Which tool was used for the canteen MVP, and for how long was it tested?
2. What two things did the team want to test?
3. What two improvements were made after the result?

Write your answers in your notebook. The key follows this chapter's exam.

6.13 Testing an MVP

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 10 of 12 · 45 min · second half · with Case Study: MVP for a Canteen Pre-Order System. Board: MVP testing means giving the basic working version to real users and studying their response..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

MVP testing means giving the basic working version to **real users** and **studying their response**. The team should collect **both numbers and comments**.

- **Numbers** (quantitative data) show how many users tried the MVP and how many may use it again.
- **Comments** (qualitative data) explain what users liked, disliked, or found confusing.

Testing should be **planned before the MVP is launched**. Decide:

1. **How many users** will test it.
2. **How long** the test will continue.
3. **What information** will be collected.

Table 6.10: Feedback during MVP testing

Type of Feedback	Question	Example Result
Number-based	How many users tried it?	40 students used the form.
Number-based	How many would use it again?	30 out of 40 said yes.
Comment-based	What was confusing?	Did not know order closing time.
Observation	Where did users face difficulty?	Forgot to enter class name.

Observation means the team watches users and notes difficulties themselves, even ones users do not mention.

WORKED EXAMPLE

Worked example: studying the results in Table 6.10.

1. **Repeat-use rate** = (users who would use it again ÷ users who tried it) × 100 = (30 ÷ 40) × 100 = **75%**.
2. **Did not want to use again** = 40 – 30 = **10 students** = (10 ÷ 40) × 100 = **25%**.
3. **Comment:** "Did not know order closing time" → **Fix:** write "Orders close 20 minutes before break" at the top of the form and in the WhatsApp message.
4. **Observation:** "Forgot to enter class name" → **Fix:** make the Class field **required** in the Google Form so it cannot be submitted empty.
5. **Decide what to fix first:** the closing-time problem stops people from ordering at all, so fix it first; the class-name problem only makes collection slower.

Three out of four users would come back, which is a promising sign; fixing the two problems could raise that number further.

REMEMBER IT

Data skill link. Feedback is useful only when it is studied: **Count** the responses → **Look** for repeated problems → **Decide** which improvement comes first. Remember "**C-L-D**: Count, Look, Decide."

COMMON MISTAKE

Mistake: Launching the MVP first and deciding later what to measure.

Fix: Plan the number of users, the test length and the questions **before** launch. Otherwise you may forget to record important data (for example, how many people opened the form but did not submit).

اردو میں سمجھیں

ایم وی پی کی جانچ کا مطلب ہے کہ بنیادی کام کرنے والا ورژن اصل صارفین کو دیا جائے اور ان کے ردعمل کا مطالعہ کیا جائے۔ اعداد بتاتے ہیں کتنے لوگوں نے استعمال کیا اور کتنے دوبارہ کریں گے، جبکہ تبصرے بتاتے ہیں کیا پسند آیا اور کیا الجھن تھی۔ جانچ کی منصوبہ بندی پہلے سے کریں، جوابات گنیں، بار بار آنے والے مسائل تلاش کریں اور پہلے سب سے اہم بہتری کریں۔

CHECK YOURSELF

1. Name the three types of feedback in Table 6.10.
2. If 50 people tried an MVP and 35 would use it again, what is the repeat-use rate?
3. Name the three things to decide before launching an MVP test.

Write your answers in your notebook. The key follows this chapter's exam.

6.15 Complete Student Project

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 11 of 12 · 45 min · first half · with Ethical and Safe Use of Digital Tools. Board: You will work in groups and complete one small entrepreneurship project..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

You will work in **groups** and complete one small entrepreneurship project. The project should be **simple, local, and possible in the classroom**.

The purpose is to practise the **complete journey**: problem → prototype → feedback → MVP plan → risky assumption → beachhead market.

Suggested project ideas: homework and test reminder system, college notice organizer, canteen pre-order system, small shop WhatsApp catalogue, college van update system, lost and found item reporting system, study notes organizer.

Table 6.12: Student project sheet (template)

Item	Your group's answer
Problem statement	
Target users	
Business idea	
Low-fidelity prototype description	
Feedback from users	
Improvement made after feedback	
MVP plan	
Riskiest assumption	
How to test the riskiest assumption	
Beachhead market	
Marketing method for first users	

WORKED EXAMPLE

Worked example: a completed project sheet (Lost and Found system).

Item	Answer
Problem statement	Students of our college in Mirpurkhas lose items (bottles, calculators, ID cards) and rarely get them back because there is no central place to report them.
Target users	Students and staff of our college.
Business idea	A Lost and Found WhatsApp group plus a Google Form to report lost or found items.
Low-fidelity prototype	Two paper screens: "Report lost item" (item, colour, place, phone of class rep) and "Found items list" with sketches.
Feedback from users	6 of 8 testers asked for photos; 3 did not want their own phone number shown.
Improvement made	Added a photo upload; replaced personal numbers with "collect from the library desk".
MVP plan	Google Form + one WhatsApp group run by two volunteers; free; tested for two weeks.
Riskiest assumption	Students who find items will take the trouble to report them.
How to test it	Count how many "found" reports arrive in two weeks compared with "lost" reports.
Beachhead market	Grade XII students of our college.
Marketing method	Announcement in morning assembly, a poster at the library and a message in each class group.

Table 6.13: Rubric for project assessment

A **rubric** is a marking guide that describes what excellent, satisfactory and weak work looks like for each part of a project.

Criteria	Excellent	Satisfactory	Needs Improvement
Problem ID	Clear, local, and important.	Understandable but needs detail.	Vague or too broad.
Prototype	Shows clear flow and features.	Shows the basic idea.	Incomplete or unclear.
Feedback & Fixes	Collected properly; changes clearly based on feedback.	Collected but analysis is weak; some changes made.	No clear feedback collected; changes not explained.
MVP Plan	Essential features and clear testing plan.	Basic features but needs testing clarity.	Confused with the final product.

REMEMBER IT

Use the rubric **before** you submit: read your project sheet row by row and ask, "Is this Excellent yet?" For "Feedback & Fixes", always write **which** feedback caused **which** change.

COMMON MISTAKE

Mistake: Writing an MVP plan that lists every feature of the dream app. The rubric marks this as "Confused with the final product".

Fix: Keep the MVP to the essential feature(s) and add a clear testing plan (how many users, how long, what you will measure).

اردو میں سمجھیں

طلبہ گروپوں میں ایک چھوٹا، مقامی اور آسان منصوبہ مکمل کرتے ہیں جس میں مسئلے سے پروٹوٹائپ، رائے، ایم وی پی منصوبہ، سب سے خطرناک مفروضہ اور بیچ بیڈ مارکیٹ تک پورا سفر شامل ہوتا ہے۔ منصوبے کو جانچنے کے لیے روبرک (Rubric) استعمال ہوتا ہے جو مسئلے کی پہچان، پروٹوٹائپ، رائے و بہتری اور ایم وی پی منصوبے کو بہترین، تسلی بخش یا بہتری کی ضرورت کے درجوں میں پرکھتا ہے۔

CHECK YOURSELF

1. Name four suggested project ideas.
2. What does "Excellent" look like for Problem ID in the rubric?
3. Which rubric level says "Confused with the final product"?

Write your answers in your notebook. The key follows this chapter's exam.

6.16 Ethical and Safe Use of Digital Tools

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 11 of 12 · 45 min · second half · with Complete Student Project. Board: Digital entrepreneurship should be responsible..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

Digital entrepreneurship should be **responsible**. When collecting user feedback, you must respect:

- **Privacy:** people's personal information belongs to them.
- **Truthfulness:** report results honestly; do not make up numbers or hide bad feedback.
- **Fairness:** treat all users equally.

You should **not collect unnecessary personal information** or **share phone numbers or photos without permission**.

Equity point

A good digital solution should consider users who have **weak internet, limited devices, or language difficulty**. A design with **large buttons, simple Urdu/Sindhi instructions, and low data usage** helps ensure **equal access**. *Equity* means making sure everyone, including people with fewer resources, can use the solution.

WORKED EXAMPLE

Worked example: fix an unethical feedback form. A team's canteen feedback form asks:

1. Full name, father's name, CNIC/B-form number, home address. → **Problem:** unnecessary personal data. **Fix:** ask only class (or nothing personal at all).
2. "Upload your selfie." → **Problem:** photos are not needed and could be misused. **Fix:** remove.
3. The team plans to post all respondents' phone numbers in the class group. → **Problem:** sharing numbers without permission. **Fix:** never share; keep responses private to the team.
4. The form is in English only and has a 5 MB video at the top. → **Problem:** excludes users with language difficulty or weak internet. **Fix:** add Urdu/Sindhi instructions and remove the heavy video.

When presenting, the team reports "30 out of 40 would use it again" exactly, without rounding it up to "almost everyone". That is truthfulness.

REMEMBER IT

Ask yourself "P-T-F-E": Is it **P**rivate, **T**ruthful, **F**air, and **E**qual-access?

COMMON MISTAKE

Mistake: "More data is always better, so let's collect everything."

Fix: Collect only what you need to answer your test questions. Extra personal data creates risk for users and gives you no benefit.

اردو میں سمجھیں

ڈیجیٹل کاروبار ذمہ داری سے کرنا چاہیے۔ رائے جمع کرتے وقت لوگوں کی رازداری (Privacy)، سچائی اور انصاف کا خیال رکھیں؛ غیر ضروری ذاتی معلومات نہ لیں اور اجازت کے بغیر فون نمبر یا تصاویر شیئر نہ کریں۔ اچھا حل کمزور انٹرنیٹ، محدود موبائل اور زبان کی مشکل والے لوگوں کا بھی خیال رکھتا ہے، جیسے بڑے بٹن، آسان اردو یا سندھی ہدایات اور کم ڈیٹا کا استعمال۔

CHECK YOURSELF

1. Name the three values students must respect when collecting feedback.
2. Give two things students must not do with users' information.
3. List three design features that support equal access.

Write your answers in your notebook. The key follows this chapter's exam.

Career Opportunities

STUDENT · COACH

Self-taught. 15 minutes. Read Learn it. Cover the example and redo it. Write Check yourself in your notebook. Do not open the chapter key.

Coach / teacher. Class 12 of 12 · 90 min · single class. Board: This unit covered entrepreneurship in the digital age, turning problems into business ideas, prototyping, building MVPs, and identifying beachhead markets..

Full-mark recipe. Define · Explain · Example · Diagram · Working.

LEARN IT

This unit covered entrepreneurship in the digital age, turning problems into business ideas, prototyping, building MVPs, and identifying beachhead markets. Mastery of these concepts opens the door to careers in **startups and digital innovation**. Pakistan has many incubators (for example, National Incubation Centres, NICs, in major cities) that support young founders.

Career	What the person does
Tech Entrepreneur / Startup Founder	Identifies a real-world problem and builds a digital product or service to solve it, guiding it from prototype through to MVP and market launch.
Product Manager	Guides a product's direction by identifying user needs, prioritising features, and testing ideas through prototypes and MVPs.
Business Analyst	Analyses business problems and processes to recommend digital solutions, often testing assumptions before full investment.
Innovation / Startup Consultant	Advises businesses or founders on validating ideas, building MVPs, and identifying beachhead markets.
Digital Marketing Specialist	Plans how a new product or MVP will reach its first (beachhead) market and grow its user base.
Venture / Incubator Analyst	Evaluates early-stage startup ideas and prototypes for potential investment or incubation support.

WORKED EXAMPLE

Worked example: match the task to the career.

1. "Decide whether the canteen app should add payments next or a weekly menu." → **Product Manager** (prioritising features).
2. "Run a WhatsApp and Instagram campaign to get the first 100 users in one college." → **Digital Marketing Specialist**.
3. "Review 20 student startup pitches and pick 5 for incubation." → **Venture / Incubator Analyst**.

REMEMBER IT

Every career in the table uses the same chapter skills: **understand users, test assumptions, start small**.

COMMON MISTAKE

Mistake: Thinking startup careers are only for programmers.

Fix: Product managers, analysts, consultants and marketers often write little or no code; they test ideas and understand users.

اردو میں سمجھیں

اس باب کی مہارتیں اسٹارٹ اپ اور ڈیجیٹل جدت کے شعبوں میں روزگار کے دروازے کھولتی ہیں، جیسے اسٹارٹ اپ بانی، پراڈکٹ مینیجر، بزنس اینالسٹ، اسٹارٹ اپ کنسلٹنٹ، ڈیجیٹل مارکیٹنگ ماہر اور انکیوبیٹر اینالسٹ۔ ان سب کاموں میں صارف کو سمجھنا، مفروضے آزمانا اور چھوٹے پیمانے سے شروع کرنا بنیادی ہے۔

CHECK YOURSELF

1. Which career plans how an MVP will reach its beachhead market?
2. What does a Business Analyst often do before full investment?

Write your answers in your notebook. The key follows this chapter's exam.

Entrepreneurship in the Digital Age

18 single-page lessons • 5 Golden • read, close, say aloud, then sit the exam

Chapter in one look

- **Entrepreneur:** a person who identifies a problem, thinks of a solution, and turns it into a product or service; observes people, takes calculated risks, improves step by step.
- **Entrepreneurship:** the process of planning, starting, testing and improving a business idea until it becomes useful (Problem → Solution → Product).
- **Digital age:** entrepreneurs use accessible digital tools (social media, forms, websites, WhatsApp, digital payments) to start and test ideas quickly with low investment; often no coding is needed.
- A digital idea must solve a **real problem for real users**, not just sound modern (Table 6.1 examples: notices, embroidery shop, test dates, canteen queues).
- **Business ideas** come from observing daily life and talking directly to users: Observe → Ask Users → Select One Problem → Suggest Solution → Test Early. Start with a small, clear problem.
- **Prototype:** an early model used to show and test the design of an idea; not the final product; makes the idea visible, finds mistakes early, saves time and money.
- **Fidelity** is how close a prototype is to the final product: Low (paper), Mid (PowerPoint/Canva/Figma, tests navigation), High (realistic, Figma/HTML, only after the idea is tested).
- **Development cycle:** Design → Build → Test → Iterate, repeated (iteration). Feedback is crucial; a prototype fails only if useful feedback is ignored.
- **MVP:** the simplest working version with only essential features (Minimum) that still solves the main problem (Viable); it tests real use and market demand.
- **Prototype vs MVP:** prototype asks "Does it look right?"; MVP asks "Will people actually use it?" A prototype may not work; an MVP must.
- **Riskiest assumption:** the untested belief that, if wrong, will make the business fail; test it early with real behaviour.
- **MVP plan:** problem, target users, ONE main feature, basic design, cost, marketing, feedback, improvement plan. Do not build everything at once.
- **Canteen case study:** paper prototype → Google Form MVP with 5 items for 3 days → staff found too many items hard → kept 5 items, separate line, orders close 20 minutes before break.
- **MVP testing:** plan users, duration and data in advance; collect numbers (40 tried, 30 would return = 75%) and comments/observations; count, look for repeated problems, fix the most important first.
- **Beachhead market:** a small, focused, reachable group of first users with a strong, immediate need; win it first, then expand.
- **Ethics and equity:** respect privacy, truthfulness and fairness; collect no unnecessary data; share nothing without permission; design for weak internet, limited devices and Urdu/Sindhi speakers.

Key terms

Term	Meaning	اردو
Entrepreneur	A person who identifies a problem, thinks of a solution, and turns it into a product or service.	کاروباری شخص
Entrepreneurship	The process of planning, starting, testing and improving a business idea.	کاروبار کاری
Calculated risk	A risk taken after carefully thinking about the possible loss and keeping it small.	سوچا سمجھا خطرہ
Digital entrepreneurship	Using digital tools to start, test, improve and grow a business idea.	ڈیجیٹل کاروبار کاری
Business idea	A proposed product or service that solves a real problem for real users.	کاروباری خیال
Target users	The people who will use the product first.	بدف صارفین
Prototype	An early model of a product, service, website or app made to test the idea and collect feedback.	ابتدائی نمونہ
Fidelity	How close a prototype is to the final product.	اصل سے مطابقت کا درجہ
Low-fidelity prototype	A quick, rough paper model showing the main idea and flow.	کم تفصیل والا نمونہ
Mid-fidelity prototype	A clearer model in PowerPoint, Canva or Figma showing layout and navigation without final graphics.	درمیانی تفصیل والا نمونہ
High-fidelity prototype	A detailed model close to the final product with realistic colours, buttons, data and working features.	زیادہ تفصیل والا نمونہ
Wireframe	A simple outline drawing of a screen showing where items go, without colours or pictures.	اسکرین کا خاکہ

Entrepreneurship in the Digital Age

75 marks • 1 hour 15 minutes • no notes • no phones

CHAPTER EXAM RULES

Instructions. Sit this exam after Lesson 18 and the recap. **Section A** — all 15 MCQs (1 mark).

Section B — all 10 short questions (3 marks). **Section C** — attempt any **three** long questions (10 marks). At least one Section C answer must be a ★ Golden topic. Write in your notebook. Do not open the key until time is up.

Marks. $15 + 30 + 30 = 75$. A 5-mark / 10-mark answer needs Define • Explain • Example • Diagram • Working.

سبق اور خلاصے کے بعد یہ امتحان بغیر نوٹس کے حل کریں۔ وقت پورا ہونے پر کلید کھولیں۔

Section A — Multiple choice (15 × 1 = 15)

1. An entrepreneur is best described as a person who:
 - a. only invests money in big companies
 - b. identifies a problem and tries to turn a solution into a product or service
 - c. always works from a large office
 - d. only writes computer programs
2. In prototyping, "fidelity" means:
 - a. the cost of the prototype
 - b. the number of users
 - c. how close the prototype is to the final product
 - d. the speed of the internet
3. Which of these is a low-fidelity prototype?
 - a. Hand-drawn app screens on paper
 - b. A working demo website of an order form
 - c. Clickable screens in Figma
 - d. An app published on the Play Store
4. A mid-fidelity prototype is mainly useful for testing:
 - a. online payments
 - b. screen-to-screen navigation
 - c. market demand over three days
 - d. investor interest
5. The correct order of the prototype development cycle is:
 - a. Build, Design, Iterate, Test
 - b. Test, Build, Design, Iterate
 - c. Design, Test, Build, Iterate
 - d. Design, Build, Test, Iterate
6. Creating, testing, improving and testing a prototype again is called:
 - a. iteration
 - b. incubation
 - c. marketing
 - d. assumption
7. In MVP, the letter "V" stands for:
 - a. Visual
 - b. Valuable
 - c. Viable
 - d. Virtual
8. Which is the best MVP for a canteen pre-order idea?
 - a. A full app with login, payment, delivery tracking and discounts
 - b. A Google Form used for real orders for three days
 - c. Paper sketches shown to five friends
 - d. A colourful poster of the menu
9. A prototype mainly answers which question?
 - a. Does it look right and make sense?
 - b. Will people pay for it every month?
 - c. How big is the national market?
 - d. How much profit will we make?
10. The riskiest assumption is:
 - a. the cheapest feature to build
 - b. the colour scheme of the app
 - c. the name of the company
 - d. the belief that, if wrong, can make the whole business fail

- L1. Which is the best beachhead market for a new study app?
- a. All students in Pakistan
 - b. All online shoppers
 - c. Grade XII students preparing for board exams in one college
 - d. All transport users
- L2. Which is NOT a characteristic of a good beachhead market?
- a. Specific and narrowly defined
 - b. Reachable by the startup team
 - c. Users have a strong, immediate need
 - d. As large as possible from the first day
- L3. "30 out of 40 said they would use it again" is which type of feedback?
- a. Number-based
 - b. Comment-based
 - c. Observation
 - d. Rubric-based
- L4. Which is an ethical practice when collecting user feedback?
- a. Collect CNIC numbers of all users
 - b. Share users' phone numbers in the class group
 - c. Collect only necessary information and share nothing without permission
 - d. Change results so the idea looks better
- L5. To support users with weak internet and language difficulty, a design should use:
- a. heavy videos on every screen
 - b. English-only instructions
 - c. features that need the latest phone
 - d. large buttons, simple Urdu/Sindhi instructions and low data usage

Section B — Short questions (10 × 3 = 30)

1. Define entrepreneur and entrepreneurship. How are they different?
2. What is meant by entrepreneurship in the digital age? Give two local examples that need no coding.
3. Write the five questions you should ask to find a problem in daily life.
4. Why should a student choose a small problem at the start? Give one example of a too-large and one of a suitable problem.
5. Define prototype and give three reasons why it is useful.
6. Differentiate between low-, mid- and high-fidelity prototypes, with one example of each.
7. Define MVP and explain the words "Minimum" and "Viable".
8. What is the riskiest assumption? Give the risky assumption and its test for the college van update system.
9. An MVP was tried by 40 students and 30 said they would use it again. Calculate the repeat-use rate and name two other kinds of feedback to collect.
10. State the three characteristics of a good beachhead market and give one weak and one better first market for an Ajrak catalogue.

Section C — Long questions (attempt any 3 × 10 = 30)

1. Explain the prototype development cycle with a labelled diagram. Use the ClassBuddy class activity to show what happens at each stage, and explain why negative feedback does not mean the prototype has failed.
2. Compare a prototype and an MVP under five headings (purpose, working status, users, cost, example). Use the canteen pre-order system as your example and state the key question each one answers.
3. **Plan an MVP for a college van update system** for a college in Hyderabad, where students and parents often do not know when the van will arrive. Fill in all eight elements of the MVP planning checklist, and also state the riskiest assumption, how to test it, and the beachhead market.
4. **Plan an MVP for a small Sindhi topi and Ajrak shop in Hala** that wants online customers. Describe a low-fidelity prototype, the MVP, its riskiest assumption and test, the beachhead market, the marketing method, and two ethical or equity points the shop must follow.
5. A team tested a Lost and Found MVP (Google Form + WhatsApp group) in a college of 60 Grade XII students for two weeks. 45 students tried it; 36 of them said they would use it again; 12 of the users said they did not know where to collect found items; the team observed that many reports had no photo. (a) Calculate the percentage of the class who tried it, the repeat-use rate among users, and the percentage of users confused about collection. (b) Classify each piece of feedback by type. (c) Decide which improvement to make first and justify it.

Answer key. Finish the Chapter Exam first, then mark. Do not peek while the clock is running.

پہلے امتحان مکمل کریں، پھر اس کلید سے نمبر لگائیں۔

Check yourself — answers

1. **6.1 Entrepreneur and Entrepreneurship.** Answers: 1. A process (planning, starting, testing and improving a business idea). 2. Observing people and listening to their needs; taking calculated risks; improving the idea step by step. 3. A risk taken after thinking carefully about the possible loss and keeping that loss small.
2. **6.2 Entrepreneurship in the Digital Age.** Answers: 1. Any four of: mobile phones, social media, websites, online forms, digital payments, maps, videos, simple apps. 2. Because a small idea can be tested quickly and cheaply, so if users do not like it the team can change it before spending too much money. 3. Selling handmade cards through Instagram, or a WhatsApp catalogue for Ajrak.
3. **Local Examples of Digital Entrepreneurship (Table 6.1).** Answers: 1. A simple catalogue with an order form on Facebook or WhatsApp. 2. Students and teachers. 3. Because it must solve a real problem for real users; a weak problem gives a weak business idea.
4. **6.3 From Problem to Business Idea.** Answers: 1. Observe, Ask Users, Select One Problem, Suggest Solution, Test Early. 2. It is too large and unclear; small, clear problems are easier to test and improve. 3. Notes are scattered in many places (WhatsApp, email, photocopies, class groups), not that students are careless.
5. **6.4 Prototype.** Answers: 1. No. It is an early model made to test the idea and collect feedback. 2. Any four: paper sketch, cardboard model, clickable PowerPoint, Canva design, Figma wireframe, simple website layout, sample service process chart. 3. Any two: a button is hard to find, a screen has too much text, a feature is missing.
6. **6.5 Types of Prototypes.** Answers: 1. How close the prototype is to the final product. 2. Mid-fidelity (e.g. clickable screens in PowerPoint or Figma). 3. It is cheap, fast and easy to change, and it protects them from building a full app before knowing whether users need it.
7. **6.6 Prototype Development Cycle.** Answers: 1. The repeating process of creating, testing, improving and testing a prototype again. 2. The Test stage. 3. To make the idea visible (not to make it beautiful).
8. **6.7 Class Activity: Create a Prototype.** Answers: 1. 7 out of 10, which is 70%. 2. Today's classes, Add homework, Show reminder. 3. A 'Weekly View' button was added.
9. **6.8 Minimum Viable Product (MVP).** Answers: 1. Minimum Viable Product. 2. Usable enough to actually solve the main problem. 3. "Will people actually use this solution?"
10. **6.9 Difference between Prototype and MVP.** Answers: 1. The MVP. 2. Prototype: paper screens for a canteen order system. MVP: a Google Form used for real canteen orders for three days. 3. "Does it look right and make sense?"
11. **6.10 Identifying the Riskiest Assumption.** Answers: 1. Something we believe to be true but have not tested yet. 2. Customers will place orders through WhatsApp; share the catalogue with 30 customers and record actual orders. 3. Because if it is wrong the whole business fails, so testing it early saves time and money.
12. **6.11 Developing an MVP.** Answers: 1. It makes the product difficult, costly and slow. 2. Problem, target users, main feature, basic design, estimated cost, marketing method, feedback method, improvement plan. 3. A WhatsApp message to the class group.
13. **6.12 Case Study: MVP for a Canteen Pre-Order System.** Answers: 1. A Google Form, tested for three days. 2. Whether students will place orders before break, and whether the canteen can manage these orders. 3. Keeping only five items and creating a separate collection line (orders also close 20 minutes before break).
14. **6.13 Testing an MVP.** Answers: 1. Number-based, comment-based, observation. 2. $(35 \div 50) \times 100 = 70\%$. 3. How many users will test it, how long the test will continue, and what information will be collected.
15. **6.14 Beachhead Market.** Answers: 1. Specific and narrowly defined; reachable by the team; users have a strong, immediate need. 2. Students and parents of ONE specific college van route. 3. No. After learning from the first group, the idea can be improved and expanded.
16. **6.15 Complete Student Project.** Answers: 1. Any four: homework and test reminder system, college notice organizer, canteen pre-order system, small shop WhatsApp catalogue, college van update system, lost and found reporting system, study notes organizer. 2. Clear, local, and important. 3. Needs Improvement (for the MVP Plan).
17. **6.16 Ethical and Safe Use of Digital Tools.** Answers: 1. Privacy, truthfulness, fairness. 2. Collect unnecessary personal information; share phone numbers or photos without permission. 3. Large buttons, simple Urdu/Sindhi instructions, low data usage.
18. **Career Opportunities.** Answers: 1. Digital Marketing Specialist. 2. Tests assumptions (after analysing business problems and processes).

Answer key

Multiple choice

1. b
2. c
3. a
4. b
5. d
6. a
7. c
8. b
9. a
10. d
11. c
12. d
13. a
14. c
15. d

Short questions — model answers

1. An **entrepreneur** is a person who identifies a problem, thinks of a solution and tries to change that solution into a product or service. **Entrepreneurship** is the process of planning, starting, testing and improving a business idea, involving creativity, problem-solving, teamwork, communication and calculated risk. The entrepreneur is the person; entrepreneurship is the process.
2. It means using digital tools such as mobile phones, social media, websites, online forms, digital payments, maps, videos and simple apps to start, test, improve and grow a business idea. Examples: a student selling handmade cards through Instagram; a shopkeeper making a WhatsApp catalogue for Ajrak.
3. What problem do people face? Who faces this problem? How often does it happen? What do people currently do to solve it? Can technology help in a simple way?
4. Small, clear problems are easier to test and improve. Too large: "improving the whole education system". Suitable: "helping Grade XII students track practical file submission dates".
5. A prototype is an early model of a product, service, website or app that shows how the idea may look or work; it is not the final product and is made to test the idea and collect feedback. Useful because it makes the idea visible, helps find mistakes early (hard-to-find buttons, too much text, missing features), and saves time and money before final coding.
6. Low-fidelity: quick, rough paper model showing main idea and flow, e.g. hand-drawn homework-reminder screens. Mid-fidelity: clearer model in PowerPoint/Canva/Figma showing layout and navigation without final graphics, e.g. clickable PowerPoint screens. High-fidelity: detailed model close to the final product with realistic colours, buttons, sample data and working features, e.g. a working demo of a small order-form website.
7. An MVP (Minimum Viable Product) is the simplest working version of a product with only the most important features, used to test the idea with real users. Minimum: only the essential features, no extras. Viable: usable enough to actually solve the main problem.
8. It is the belief that can make the entire business fail if it turns out to be wrong. For the van update system: "Parents and students will check van updates daily." Test: create a trial WhatsApp broadcast group for one route.
9. Repeat-use rate = $(30 \div 40) \times 100 = 75\%$. Other feedback: comment-based (e.g. "What was confusing?") and observation (e.g. where users faced difficulty, such as forgetting to enter class name).
10. Specific and narrowly defined; reachable by the team; users have a strong, immediate need. Ajrak catalogue: weak = all online shoppers; better = existing customers of one local shop.

Long questions — model answers

1. **Prototype development cycle.** Draw four boxes in a loop: Design → Build → Test → Iterate → back to Design. Prototype development is not one-time; repeating the cycle is called iteration.
 - **Design:** understand the problem and plan what the prototype shows. ClassBuddy: interview 10 students; 7 of 10 forget tasks, so show a daily task list; reminders are needed before leaving home, so add a morning notification; students want simplicity, so use large buttons and clear labels.
 - **Build:** create the first version to make the idea visible (not beautiful). ClassBuddy: three paper screens (Today's classes, Add homework, Show reminder) joined by arrows.
 - **Test:** show it to users and observe. ClassBuddy: five classmates try "add one homework task" while the observer watches silently.
 - **Iterate:** improve from feedback. ClassBuddy: larger, centred Add Homework button; subject name and due date fields; a Weekly View button.

Negative feedback is information that shows what to fix; the prototype fails only if the team ignores useful feedback.

2. **Prototype vs MVP.** Purpose: prototype shows how the idea may look or work; MVP tests whether users will actually use it. Working status: prototype may not work (sketch or model); MVP must work at least in a basic way. Users: prototype, a small group giving design feedback; MVP, early real users in daily life. Cost: prototype very low; MVP low but may need basic development. Example: prototype = paper screens for a canteen order system; MVP = Google Form used for real canteen orders for three days. Key questions: prototype, "Does it look right and make sense?"; MVP, "Will people actually use it and find value in it?"

3. **MVP plan: college van update system (Hyderabad).**

- Problem: students and parents do not know when the van will arrive, so students wait outside for a long time or miss the van.
- Target users: students and parents on one van route.
- Main feature: the driver or a route monitor sends a short "Van left / 5 minutes away" message.
- Basic design: one WhatsApp broadcast message with route stop name, time and status; voice note option for parents who cannot read.
- Cost: free, using a WhatsApp broadcast list on the monitor's phone.
- Marketing: a message in the class WhatsApp group and a printed slip for parents with the number to save.
- Feedback: after one week, a 3-question Google Form or phone call: Did you check the updates daily? Did you wait less? Would you continue?
- Improvement plan: if messages arrive too late, send them earlier; if many parents do not read, switch to voice notes; then expand to a second route.
- Riskiest assumption: parents and students will check van updates daily. Test: trial broadcast group for one route for one week, counting how many people read or reply to messages each day.
- Beachhead market: students and parents of ONE specific college van route.

4. MVP plan: topi and Ajrak shop in Hala.

- Low-fidelity prototype: paper catalogue pages, one per product, with a sketch, price, size/type and "Message to order"; shown to 5 customers to see if information is clear.
- MVP: a WhatsApp Business catalogue with real photos and prices for 10–15 best-selling items; orders by chat; payment by cash on delivery or JazzCash/Easypaisa.
- Riskiest assumption: customers will actually place orders through WhatsApp. Test: share the catalogue with 30 existing customers and record actual orders for two weeks.
- Beachhead market: existing customers of this one shop (people who have bought before and whose numbers the shop already has with permission).
- Marketing: broadcast message to existing customers, a QR code at the shop counter, posts in local Facebook groups.
- Ethics: share no customer numbers or photos without permission; give truthful prices, sizes and photos. Equity: simple Urdu/Sindhi descriptions and compressed photos for low data use.
- Improvement plan: drop designs nobody orders, add more of the popular ones, then expand to customers in Hyderabad and Karachi.

5. Lost and Found MVP analysis.

- (a) Tried: $(45 \div 60) \times 100 = 75\%$ of the class. Repeat-use rate: $(36 \div 45) \times 100 = 80\%$. Confused about collection: $(12 \div 45) \times 100 = 26.7\%$ (about 27%).
- (b) "45 tried" and "36 would use again": number-based. "Did not know where to collect": comment-based (12 users said it). "Many reports had no photo": observation.
- (c) Fix the collection confusion first: it is a repeated problem (more than a quarter of users) and it stops the system's main purpose, which is returning items to owners. Add "Collect found items from the library desk" at the top of the form and pin it in the WhatsApp group. Next, make the photo field strongly encouraged (or required for found items), since photos help owners recognise items. Re-test for another week and compare the numbers.

Self-assessment: I can...

- | | |
|--|--|
| ☐ define entrepreneur and entrepreneurship and describe an entrepreneur's habits. | ☐ explain how digital tools let me start and test an idea cheaply, with local examples. |
| ☐ use the five questions and the steps of Table 6.2 to turn a problem into an idea. | ☐ define a prototype and list its benefits and possible forms. |
| ☐ compare low-, mid- and high-fidelity prototypes. | ☐ draw and explain the Design–Build–Test–Iterate cycle. |
| ☐ turn user feedback into problems and improvements, as in Table 6.5. | ☐ define an MVP and explain how it differs from a prototype. |
| ☐ identify the riskiest assumption of an idea and design a test for it. | ☐ fill in an MVP plan and analyse MVP test results with percentages. |
| ☐ choose a specific, reachable beachhead market. | ☐ collect feedback ethically and design for equal access. |

FINAL REVISION

One-page recaps and a mock paper

Use these pages in the last week before the exam. Read one recap aloud from memory, then sit the mock paper in 2 hours 30 minutes with no notes.

امتحان سے ایک ہفتہ پہلے خلاصے زبانی دہرائیں، پھر ماک پیپر بغیر نوٹس کے حل کریں۔

Chapter 1 recap — Human Computer Interaction

- HCI = study of how people and computers work together so systems are usable, useful and satisfying.
- Traditional interaction = keyboard, mouse, menus. Natural interaction = touch, voice, gesture, gaze.
- Components: user, computer, interaction (input + output + feedback) inside an environment.
- UI = how it looks and the controls. UX = how the whole experience feels. Wireframe → prototype (Figma) → test.
- Evaluate with usability tests, heuristic evaluation, A/B tests and automated checks. Golden: accessibility, HCI problems, UI vs UX, testing methods.

Chapter 2 recap — Algorithms and Data Structures

- Correctness: trace table (variable values after every step) or stepwise reasoning.
- Clarity: modularity (small named parts) and readability (names, comments, indentation).
- Efficiency: count steps, conditions, repetitions. Big O: $O(1)$ constant, $O(\log n)$ binary search, $O(n)$ linear, $O(n \log n)$ good sorts, $O(n^2)$ nested loops.
- Linear DS: array, linked list, stack (LIFO, push/pop), queue (FIFO, enqueue/dequeue). Non-linear: tree (one root, parent-child), graph (nodes + edges).
- Pick the structure from the problem: undo → stack; printer jobs → queue; hierarchy → tree; maps → graph; fast index → array.

Chapter 3 recap — Python Data Structures, Functions and Files

- list [] ordered, mutable. tuple () ordered, immutable. set {} unordered, unique. dict {k:v} key-value, mutable.
- Functions: def, parameters, return. Local vs global scope. Built-in vs user-defined.
- Files: "r" read, "w" overwrite, "a" append. Always prefer with open(...) as f so the file closes itself.
- Exceptions: try / except / else / finally. Catch specific errors (ValueError, FileNotFoundError).

Chapter 4 recap — Data and Analysis

- SQLite in Python: connect → cursor → execute → commit → close. Always commit writes.
- Pandas DataFrame = table. load CSV/Excel, `isnull`, `dropna`, `fillna`, sort, filter, groupby.
- Charts: bar (categories), line (trend over time), pie (parts of a whole, few slices), histogram (distribution), scatter (relationship of two variables), box (spread and outliers).
- Mean = average. Median = middle after sorting. Mode = most frequent. Range = max–min. Variance / std-dev measure spread. pandas `.std()` uses sample $n-1$.

Chapter 5 recap — AI, Security and Collaboration

- AI ⊃ Machine Learning ⊃ Deep Learning. A neuron: weighted sum + bias, then an activation function. Deep = many hidden layers.
- Secure collaboration: authentication (passwords, MFA), access control (who may do what).
- Protect data: encryption, strong passwords, 3-2-1 backup, firewall. Threats: malware, phishing, DoS/DDoS, social engineering.
- Equity: everyone can take part (devices, language, disability, bandwidth). Tools: shared docs, video, LMS, versioning.

Chapter 6 recap — Entrepreneurship in the Digital Age

- Entrepreneur = person who turns a problem into a venture, taking risk. Digital tools make testing cheap (WhatsApp, Forms, a Facebook page).
- Prototype = experimental model. Low / mid / high fidelity. Cycle: Design → Build → Test → Iterate.
- MVP = smallest product that tests the riskiest assumption with real users. Prototype ≠ MVP (MVP is used in the real market).
- Beachhead market = the first, narrow group you can win. Measure retention, not only sign-ups. Use data ethically.

STUDENT · COACH

Self-taught. Read each recap aloud, close the book, say it again. Then sit the mock in 2 hours 30 minutes with no notes. Mark with the key. Repair only the Golden notes you missed.

Coach / teacher. Exam week: six 90-minute recap clinics, then the mock under hall conditions. Re-teach any Golden that more than a third of the batch missed.

FINAL MOCK · CLOSED BOOK

Mock paper

75 marks · 2 hours 30 minutes · no notes

Mock paper — Computer Science XII

Time: 2 hours 30 minutes | Total: 75 marks | Answer all of A and B; attempt three from C.

Section A — Multiple choice (15 × 1 = 15)

1. HCI stands for:
 - a. Human Computer Interaction
 - b. High Code Interface
 - c. Hardware Control Input
 - d. Hybrid Computing Internet
2. A wireframe is:
 - a. the final coloured UI
 - b. a simple layout sketch of screens
 - c. a compiled program
 - d. an encryption key
3. Which is $O(\log n)$?
 - a. Linear search
 - b. Nested for-loops
 - c. Binary search
 - d. Reading one array cell
4. A stack is:
 - a. FIFO
 - b. LIFO
 - c. random access only
 - d. unordered unique items
5. Which Python type is immutable?
 - a. list
 - b. dict
 - c. set
 - d. tuple
6. The file mode that overwrites an existing file is:
 - a. r
 - b. a
 - c. w
 - d. x+
7. `with open("t.txt") as f` is useful because:
 - a. it encrypts the file
 - b. it closes the file automatically
 - c. it creates a DataFrame
 - d. it skips exceptions
8. After INSERT in sqlite3 you must:
 - a. rollback always
 - b. commit
 - c. drop the table
 - d. print the cursor
9. A pie chart is a poor choice when:
 - a. you have 3 parts of a total
 - b. you have 20 tiny slices
 - c. you show percentages of a whole
 - d. you label each slice
10. pandas `df['x'].std()` uses:
 - a. population n
 - b. sample n-1
 - c. median
 - d. mode
11. Deep Learning is a subset of:
 - a. only statistics
 - b. Machine Learning
 - c. only HCI
 - d. only networking

L2. MFA means:

- a. Many File Archives
- b. Multi-Factor Authentication
- c. Main Firewall Access
- d. Minimum Function API

L3. A Caesar cipher is a form of:

- a. phishing
- b. encryption
- c. a firewall
- d. a prototype

L4. An MVP is:

- a. the most polished version of a product
- b. the smallest product that tests the riskiest assumption
- c. a paper sketch only
- d. a full company registration

L5. A printer job list is best modelled as a:

- a. stack
- b. queue
- c. binary tree
- d. set

Section B — Short questions (10 × 3 = 30)

1. Differentiate UI and UX with one example.
2. What is a trace table? Why is it better than "it looks right"?
3. Draw a 3-node stack after push 10, push 20, pop. Label TOS.
4. Write one difference each: list vs tuple vs set vs dictionary.
5. Write a Python function `area(l, w)` that returns $l \times w$, and a call that prints it.
6. Name the five steps of a database connection in Python.
7. When would you draw a scatter plot rather than a line graph?
8. Compute mean, median and range of 4, 8, 6, 10, 2.
9. List three signs of a phishing message.
10. Differentiate a prototype and an MVP.

Section C — Long questions (3 × 10 = 30). Attempt any three.

1. A college wants a new student-portal. Describe need analysis, a low-fidelity wireframe of the login + timetable screens, three accessibility principles you would apply, and one usability test you would run.
2. Trace this algorithm with a table for $n = 5$: $\text{total} = 0$; for i in $1..n$: $\text{total} = \text{total} + i$; return total. State its Big O and rewrite it as a formula that is $O(1)$.
3. Write a Python program that reads a text file of lines "name,marks", stores results in a dictionary, and writes "name: grade" to an output file using `with`. Grade A if marks ≥ 80 else B. Include exception handling if the file is missing.
4. Using the dataset 12, 18, 12, 20, 15, compute mean, median, mode, range, population variance and population standard deviation, showing every step. Then state which chart you would use to show the distribution and why.
5. A Karachi canteen wants a pre-order app. Identify the problem, the riskiest assumption, an MVP, a beachhead market, two test metrics, and one ethical rule for student data.

Mock paper — answers

Section A

1. a
2. b
3. c
4. b
5. d
6. c
7. b
8. b
9. b
10. b
11. b
12. b
13. b
14. b
15. b

Section B

1. UI is the screens and controls (buttons, colours). UX is the whole journey (time to complete a task, frustration, trust). Example: a JazzCash send-money screen (UI) vs how safe and quick the payment felt (UX).
2. A trace table lists each variable after every instruction. It proves correctness on a chosen input; "it looks right" misses off-by-one and uninitialised variables.
3. After push 10, TOS=10. After push 20, TOS=20 (10 below). After pop, 20 removed, TOS=10.
4. list: ordered mutable. tuple: ordered immutable. set: unordered unique. dict: keyed pairs.
5. `def area(l, w): return l * w` then `print(area(3, 4))` → 12.
6. connect, cursor, execute, commit, close.
7. Scatter: two measured variables (height vs marks) with no single time axis. Line: one quantity changing over an ordered time or sequence.
8. Sorted: 2,4,6,8,10. Mean = $30/5 = 6$. Median = 6. Range = $10-2 = 8$.
9. Unknown sender, urgent threat ("account will close today"), a link that does not match the real bank, request for OTP/password, poor Urdu/English, unexpected attachment.
10. A prototype is a model used to learn (often internal). An MVP is a real, usable product with just enough features to test the riskiest assumption with actual customers.

Section C — outline

1. Need analysis: who (students, teachers), tasks (view timetable, submit leave), constraints (mobile, slow internet). Wireframe: simple boxes for logo, fields, button, a second screen with a 5-day table. Accessibility: large tap targets, colour not the only signal, Urdu/English labels, screen-reader names. Test: five students think-aloud while logging in; record errors and time.
2. $i=1$ total=1; $i=2$ total=3; $i=3$ total=6; $i=4$ total=10; $i=5$ total=15. Loop body runs n times $\rightarrow O(n)$. Formula $n*(n+1)/2$ is $O(1)$.
3. try: with open(path) as f: for line in f: name, m = line.strip().split(","); d[name]=int(m) except FileNotFoundError: print("missing"). Then with open(out,"w") as g: write grades. Show one sample dictionary.
4. Sorted 12,12,15,18,20. Mean $77/5=15.4$. Median 15. Mode 12. Range 8. Population variance: deviations $-3.4, -3.4, -0.4, 2.6, 4.6$; squares 11.56,11.56,0.16,6.76,21.16; sum 51.2; $/5 = 10.24$. std = 3.2. Histogram to show distribution (or bar of frequencies).
5. Problem: long canteen queues between periods. Riskiest assumption: students will pre-order 10 minutes before break. MVP: WhatsApp number + Google Form, pickup tokens, no app. Beachhead: one shift of first-year students. Metrics: % of orders picked up, time-to-collect, repeat use. Ethical: do not publish phone numbers; delete form responses after the term.

Colophon

This **Self-Taught / Coaching-Academy Bootcamp (Combo Edition)** of Computer Science XII is the official Study Guide for students and teachers. It keeps chapter-wise lecture notes at readable type, embeds ★ Golden concepts inside each chapter, prints a Student · Coach strip on every lesson, and seals the key after the 75-mark chapter exam.

102 lecture notes · 32 Golden concepts · 68 academy classes · New Sindh Curriculum 2025-27 · English + اردو · A4.

یہ طلبہ اور اساتذہ کی آفیشل مشترکہ اسٹڈی گائیڈ ہے۔