

Point

x: double, y: double

- Point() - Point(double x, double y)

- Point(Point obj) - add()

- subtract() - distance()

- magnitude() - setX() - setY()

- getX() - getY()

- toString() - objCount()

- display()

Line

- Point p1 - Point p2

- objCount: int

- Line() - Line(Point p1, Point p2)

- Line(Line obj) - get P1()

- get P2() - slope()

- length() - midpoint()

- pointSlope()

- intersection(Line l)

- objCount()

- toString()

- display()

I why point class
I why vector class

Date: _____

Triangle	Complex Number
• Point p1 • Point p2	double real
• Point p3 • objCount: int	double imaginary
Triangle() - Triangle(Point)	ComplexNumber()
• Triangle(Point p1, Point p2, Point p3)	ComplexNumber(double real, double imaginary)
- getP1() • getP2() • getP3()	
- setP1() - setP2() - setP3()	ComplexNumber(ComplexNumber obj)
- sideA() - sideB()	getReal() - getImaginary()
- sideC() - isEquilateral()	- setReal() - setImaginary()
- isIsosceles() - objCount()	- add() - subtract()
- toString()	- magnitude()
- Display()	- toString()
	- display()

Rational Number
• numerator: int, denominator: int
• objCount: int
- RationalNumber()
- RationalNumber(int numerator, int denominator)
- RationalNumber(RationalNumber obj)
- setDenominator() - setNumerator()
- getDenominator() - getNumerator()
- add() - subtract()
- multiply() - divide()
• toDecimal() - objCount()
• toString() display()