


NOTES


1. ALL DIMENSIONS ARE IN mm. UNLESS OTHERWISE NOTED.
2. PRIOR TO INSTALLATION, EXACT LOCATION AND DIMENSIONS SHOULD BE CHECKED AND ADJUSTED BY FIELD.
3. THE CLEARANCE(GAP) SHALL BE KEEP AS SHOWN ON THIS DRAWING
4. PROVIDE FILLET WELD W/100% STRENGTH.
5. ALL PLATES AND STRUCTURAL SHAPES SHALL BE ASTM A-36 OR EQUIV. UNLESS OTHERWISE NOTED.
6. FOR GENERAL SUPPORT INFORMATION, SEE LINE-000-GA-4-0305, SPECIFICATION FOR PIPING HANGING AND SUPPORT.
7. FOR FILLET WELD, THE THROAT THICKNESS SHOULD BE MIN. 6mm

REFERENCE

NO	DWG NO	DESCRIPTION



HEIN
GLOBAL UTAMA




PT. KOKOH SEMESTA
ENGINEERING-MANUFACTURING-CONSTRUCTION

101-SS-03
PIPE SPECIAL SUPPORT FOR
101 AREA

101-SS-03	STD SS-101	N7009	PIPE SPECIAL SUPPORT FOR 101 AREA															1	28.25	0.64
101-SS-03	STD SS-101	N7009	PIPE SPECIAL SUPPORT FOR 101 AREA																	
101-SS-03	STD SS-101A-1	N7009	PIPE SPECIAL SUPPORT FOR 101 AREA	H BEAM	CS					100	x	100	x	6	x	8	x	50	L	2
101-SS-03	STD SS-101B-1	N7009	PIPE SPECIAL SUPPORT FOR 101 AREA	PIPE	A106-B					6.02	x	114.3	"		SCH	STD	x	917	L	1
101-SS-03	STD SS-101C-1	N7009	PIPE SPECIAL SUPPORT FOR 101 AREA	PLATE	CS					13	x	340					x	340	L	1

101-SS-03
PIPE SPECIAL SUPPORT FOR 101 AREA



UNIT NO
-

PROJ. NO
-

SCALE
NTS

SHEET
1

KS-HEIN-N7009

REV
00