4-24 Personal Research


Presenter: Yu-Chun Hung

Advisor: Peng-Sheng Cheng

Summary

- Focus on object detection part
 - Only yolov2-tiny can run.
 - The post process part is excruciate to write
- We should make the sample higher on image classification (currently 10 sample)

How to get result from tiny yolo v2?



How to get result from tiny yolo v2?

- 1. output tensor is (1, 125, 13, 13), input image is (1, 3, 416, 416)
- 2. output (13, 13) -> 32*32 pixel grid, we have 13*13
- 3. output 125 -> (x, y, w, h, confidence on grid) + (20 classification possibility) * (5 anchors)
- 4. Use NMS to remove overlap detection.
- 5. mAP benchmark on object detection

Currently we are on step 3, the yolo experiment is still running.

Mistake in yolov2-tiny

- v7 opset in onnx/models does not work, use v8 instead
- Do not normalize pixel value (0, 255) -> (0, 1)
- Don't use ChatGPT, use the existing solution on github instead.
- Use ONNX runtime to verify your model and postprocess is working or not first.

Image classification: MobileNet accuracy




Image classification: Resnet18 accuracy




Image classification: MobileNet Average MAE




Image classification: Resnet18 Average MAE




Image classification:

- Current Sample is 10, we should make it higher,
- Posit 8 all failed, Posit(16, 1) seems the best configuration of all.

Future work

- Finish tinyyolov2 benchmark
- Writing master thesis.