

# CS/ENGRD 2110

## SPRING 2017

Lecture 6: Consequence of type, casting; function equals  
<http://courses.cs.cornell.edu/cs2110>

# Announcements


2

- A3 will available on Piazza tomorrow. Refer often to the Piazza FAQ Note for A3
- Please read the assignment A1 FAQ Notes on the Piazza before asking a question. It might already be answered.

## Assignment A3: Doubly linked Lists

3

Idea: maintain a list (2, 5, 7) like this:





This is a singly linked list

To save space we write names like a6 instead of N@35abcd00



## How to insert a node at the beginning

4



## How to remove successor of a node in the middle

5



# Assignment A3: Use an **inner** class

6

```
public class C {  
    private int x;  
  
    public void m(int y) { ... ob= new Cin(...);  ob.b= 5;  }  
  
    private class Cin {  
        private int b;  
  
        public void mm() { ... x= b; ...  }  
    }  
}
```

In addition: methods of C can reference private components of Cin

Inside-out rule: Objects of Cin can reference components of the object of C in which they live.

# Assignment A3: Generics

7

```
public class LinkedList {  
    void add(Object elem) {...}  
    Object get(int index) {...}  
}
```

Values of linked list are  
probably of class Object

```
public class LinkedList<E> {  
    void add(E elem) {...}  
    E get(int index) {...}  
}
```

You can specify what  
type of values

```
ns = new LinkedList<Integer>();  
ns.add("Hello"); // error  
ns.add(5);  
String s = ns.get(0); // error  
int n = ns.get(0);
```

```
ss = new LinkedList<String>();  
ss.add("Hello");  
ss.add(5); // error  
String s = ss.get(0);  
int n = ss.get(0); // error
```

# Overview ref in text and JavaSummary.pptx

8

- Quick look at arrays **slide 50-55**
- Casting among classes **C.33-C.36 (not good)** **slide 34-41**
- Consequences of the class type **slide 34-41**
- Operator **instanceof** **slide 40**
- Function **equals** **slide 37-41**

**Homework.** Learn about while/ for loops in Java. Look in text.

**while** ( <bool expr> ) { ... } // syntax

**for** (int k= 0; k < 200; k= k+1) { ... } // example



# Classes we work with today




class hierarchy:

9

Work with a class **Animal** and subclasses like **Cat** and **Dog**

Put components common to animals in **Animal**

**Object** partition is there but not shown



# Animal[] v = new Animal[3];

10

declaration of  
array v

Create array  
of 3 elements

Assign value of  
new-exp to v

v ~~null~~ a6

Assign and refer to elements as usual:

v[0] = new Animal(...);

...

a = v[0].getAge();

	a6	
		Animal[]
0	null	
1	null	
2	null	

Sometimes use horizontal  
picture of an array:

	0	1	2
v	null	null	null

# Which function is called?

11

Which function is called by  
**v[0].toString()** ?

Remember, partition Object  
contains **toString()**

	0	1	2
v	a0	null	a1

Bottom-up or  
overriding rule  
says function  
toString in Cat  
partition

a0	
age 5	Animal
isOlder(Animal)	
toString() toNoise() getWeight()	
Cat	

a1	
age 6	Animal
isOlder(Animal)	
getString() toNoise()	
Dog	

# Consequences of a class type

12


`Animal[] v;`

declaration of `v`. Also means that each variable `v[k]` is of type `Animal`

The type of `v` is `Animal[]`

The type of each `v[k]` is `Animal`

The type is part of the syntax/grammar of the language. Known at compile time.




As we see on next slide, the type of a class variable like `v[k]` determines what methods can be called

## From an Animal variable, can use only methods available in class Animal


13

`a.getWeight()` is obviously illegal.  
The class won't compile.



When checking legality of a call like  
`a.getWeight(...)`

since the type of `a` is `Animal`, function `getWeight` must be declared in `Animal` or one of its superclasses.



## From an Animal variable, can use only methods available in class Animal


14

Suppose `a0` contains an object of a subclass Cat of Animal. By the rule below, `a.getWeight(...)` is still illegal. Remember, the test for legality is done at compile time, not while the program is running. ...

When checking legality of a call like `a.getWeight(...)`

since the type of `a` is Animal, function `getWeight` must be declared in Animal or one of its superclasses.

a a0 Animal



## From an Animal variable, can use only methods available in class Animal


15

The same object a0, from the viewpoint of a Cat variable and an Animal variable

c a0  
Cat


a a0  
Animal

c.getWeight() is legal



a.getWeight() is illegal

because  
getWeight  
is not  
available  
in class  
Animal




## Rule for determining legality of method call

16

c a0  
C

Rule: **c.m(...)** is legal and the program will compile  
ONLY if method **m** is declared in **C** or one of its  
superclasses

m(...) must be  
declared in one  
of these classes





# Another example


17

Type of v[0]: Animal

Should this call be allowed?  
Should program compile?

**v[0].getWeight()**

**v[k].getWeight()**



# View of object based on the type


18

Each element  $v[k]$  is of type **Animal**.

From  $v[k]$ , see only what is in partition **Animal** and partitions above it.

`getWeight()` not in class **Animal** or **Object**. Calls are illegal, program does not compile:

$v[0].getWeight()$   $v[k].getWeight()$



# Casting objects


19

You know about casts like

**(int)** (5.0 / 7.5)

**(double)** 6

**double** d= 5;    // automatic cast





Discuss casts up/down class hierarchy.

**Animal** h= **new** Cat("N", 5);

**Cat** c= (Cat) h;

A class cast doesn't change the object. It just changes the perspective —how it is viewed!



# Explicit casts: unary prefix operators

20

**Rule:** an object can be cast to the name of any partition that occurs within it — and to nothing else.

**a0** can be cast to **Object**, **Animal**, **Cat**.

An attempt to cast it to anything else causes an exception

(Cat) c

(Object) c

(Animal) (Animal) (Cat) (Object) c

These casts don't take any time. The object does not change. It's a change of perception

a0	
equals() ...	Object
age 5	Animal
isOlder(Animal)	
	Cat
getNoise() toString() getWeight()	

c a0  
Cat

# Implicit upward cast




21

```
public class Animal {  
    /** = "this Animal is older than h" */  
    public boolean isOlder(Animal h) {  
        return age > h.age;  
    }  
}
```

Call **c.isOlder(d)**

Variable h is created. **a1** is cast up to class **Animal** and stored in **h**

Upward casts done  
automatically when needed




# Example

22

```
public class Animal {  
    /** = "this is older than h" */  
    public boolean isOlder(Animal h) {  
        return age > h.age;  
    }  
}
```

Type of **h** is **Animal**. Syntactic property.

Determines at compile-time what components can be used: those available in **Animal**



If a method call is legal, the overriding rule determines which implementation is called

h 


a1
----

  
Animal

# Components used from h

23

```
public class Animal {  
    /** = "this is older than h" */  
    public boolean isOlder(Animal h) {  
        return age > h.age;  
    }  
}
```



`h.toString()` OK —it's in class `Object` partition  
`h.isOlder(...)` OK —it's in `Animal` partition  
`h.getWeight()` **ILLEGAL** —not in `Animal` partition or `Object` partition


By overriding rule, calls `toString()` in `Dog` partition

h `a1`  
Animal

# Explicit downward cast

24

```
public class Cat extends Animal {  
    private float weight;  
    /** return true iff ob is a Cat and its  
     * fields have same values as this */  
    public boolean equals(Object ob) {  
        ?  
        // { h is a Cat }  
        if ( ! super.equals(ob) ) return false;  
        Cat c= (Cat) ob ; // downward cast  
        return weight == c.getWeight();  
    }  
}
```



h a0  
Animal

(Dog) ob leads to runtime error.

Don't try to cast an object to something that it is not!



# Operator instanceof, explicit down cast

25

```
public class Cat extends Animal {  
    private float weight;  
    /** return true iff ob is a Cat and its  
     * fields have same values as this */  
    public boolean equals(Object ob) {  
        if ( ! (ob instanceof Cat) ) return false;  
        // { h is a Cat }  
        if ( ! super.equals(ob) ) return false;  
        Cat c= (Cat) ob ; // downward cast  
        return weight == c.getWeight();  
    }  
}
```

a0

age 5 Animal

isOlder(Animal)

weight \_\_\_\_ Cat  
getNoise() toString()  
getWeight()

h a0

Animal

<object> instanceof <class-name>

true iff <object> has a partition for <class-name>

# Opinions about casting

26

- Use of instanceof and downcasts can indicate bad design

DON'T:

```
if (x instanceof C1)
    do thing with (C1) x
else if (x instanceof C2)
    do thing with (C2) x
else if (x instanceof C3)
    do thing with (C3) x
```

DO:

`x.do()`

(do thing overridden in C1, C2, C3)

- But how do I implement equals() ?

That requires casting