

# Errors

## **mod** errors

### **class** EmptyChannelError

Bases: `Exception`

Raised when attempting to get the value of a channel that hasn't been updated for the first time yet.

### **class** GraphRecursionError

Bases: `RecursionError`

Raised when the graph has exhausted the maximum number of steps.

This prevents infinite loops. To increase the maximum number of steps, run your graph with a config specifying a higher `recursion_limit`.

Troubleshooting guides:

- `GRAPH_RECURSION_LIMIT`

Examples:

```
graph = builder.compile()
graph.invoke(
    {"messages": [("user", "Hello, world!)]},
    # The config is the second positional argument
    {"recursion_limit": 1000},
)
```

### **class** InvalidUpdateError

Bases: `Exception`

Raised when attempting to update a channel with an invalid set of updates.

Troubleshooting guides:

- `INVALID_CONCURRENT_GRAPH_UPDATE`
- `INVALID_GRAPH_NODE_RETURN_VALUE`

### `class` `GraphInterrupt`

Bases: `GraphBubbleUp`

Raised when a subgraph is interrupted, suppressed by the root graph. Never raised directly, or surfaced to the user.

### `class` `NodeInterrupt` `deprecated`

Bases: `GraphInterrupt`



#### Deprecated



`NodeInterrupt` is deprecated. Please use `interrupt` instead.

Raised by a node to interrupt execution.

### `class` `EmptyInputError`

Bases: `Exception`

Raised when graph receives an empty input.

### `class` `TaskNotFound`

Bases: `Exception`

Raised when the executor is unable to find a task (for distributed mode).