

paragon.contextMenu

Use the paragon.contextMenu API to add items to Paragon's context menu. You can choose what types of objects your context menu additions apply to, such as images, hyperlinks, and pages.

Summary

Methods
create
update
remove
removeAll
Events
onclick

Methods

create

Gets the current application.

```
paragon.contextMenu.create(object createProperties, function callback)
```

Parameters			
object	createProperties	boolean	checked
		boolean	enabled
		integer	groupId
		integer	id
		integer	parentId
		string	title
		enum of "normal", "checkbox", "radio", or "separator"	type
		Defaults to 'normal' if not specified.	
function	callback	Return the ID of the item created. The <i>callback</i> parameter should be a function that looks like this: <div>function(integer id) {...};</div>	

update

Gets the current application version.

```
paragon.contextMenu.update(integer id, object updateProperties, function callback)
```

Parameters

integer	id	The ID of the context menu item to update.									
object	updateProperties	The properties to update. Accepts the same values as the create function. <table> <tr> <td>boolean</td><td>checked</td><td></td></tr> <tr> <td>boolean</td><td>enabled</td><td></td></tr> <tr> <td>string</td><td>title</td><td></td></tr> </table>	boolean	checked		boolean	enabled		string	title	
boolean	checked										
boolean	enabled										
string	title										
function	callback	The <i>callback</i> parameter should be a function that looks like this: <pre>function() {...};</pre>									

remove

Removes a context menu item.

```
paragon.contextMenu.remove(integer id, function callback)
```

Parameters

integer	id	The ID of the context menu item to remove.
function	callback	The <i>callback</i> parameter should be a function that looks like this: <pre>function() {...};</pre>

removeAll

Removes all items from the context menu.

```
paragon.contextMenu.removeAll(function callback)
```

Parameters

function	callback	The <i>callback</i> parameter should be a function that looks like this: <pre>function() {...};</pre>
----------	----------	---

Events

onclick

Fired when an app is launched.

addListener

```
paragon.contextMenu.onclick.addListener(function callback)
```

Parameters

function

callback

The *callback* parameter should be a function that looks like this:

```
function() {...};
```