

Neovim Daily Keybind Reference

leader = localleader = `Space` · generated from `~/ .config/nvim`

General & Navigation

<code>Esc</code>	Clear search highlight
<code>Esc Esc</code>	Leave terminal mode (Claude, Antigravity, any :terminal)
<code>C-h/j/k/l</code>	Move focus between window splits
<code>C-o</code> / <code>C-i</code>	Jump back / forward (after <code>grd</code> , searches, etc.)
<code>leader q</code>	Diagnostics to quickfix list
<code>zR</code> / <code>zM</code>	Open / close all folds
<code>za</code> / <code>zo</code> / <code>zc</code>	Toggle / open / close fold under cursor
<code>saiw</code>	Surround Add Inner Word with)
<code>sd'</code>	Surround Delete '
<code>sr')</code>	Surround Replace) with '
<code>va)</code> / <code>ci'</code>	Select / change around-or-inside a text object

Search (Telescope) — `leader s...`

<code>sf</code>	Find files
<code>sg</code>	Live grep
<code>sw</code>	Grep word under cursor
<code>sd</code>	Search diagnostics
<code>sh</code>	Search help
<code>sk</code>	Search keymaps
<code>ss</code>	Search Telescope pickers
<code>sr</code>	Resume last search
<code>s.</code>	Recent files
<code>s/</code>	Grep in open files only
<code>sn</code>	Find files in nvim config
<code>leader leader</code>	Find open buffers
<code>leader /</code>	Fuzzy search current buffer

LSP

<code>K</code>	Hover docs
<code>grn</code>	Rename
<code>gra</code>	Code action
<code>grr</code>	References
<code>gri</code>	Go to implementation
<code>grd</code>	Go to definition
<code>grD</code>	Go to declaration
<code>grt</code>	Go to type definition
<code>g0</code> / <code>gw</code>	Document / workspace symbols
<code>leader th</code>	Toggle inlay hints

Completion (blink.cmp) — insert mode

<code>Tab</code> / <code>S-Tab</code>	Snippet jump forward / back
<code>C-y</code>	Accept completion
<code>C-n</code> / <code>C-p</code>	Next / previous item
<code>C-space</code>	Open menu / docs
<code>C-e</code>	Dismiss menu
<code>C-k</code>	Toggle signature help

Copilot — ghost text, insert mode

<code>M-l</code>	Accept suggestion
<code>M-]</code> / <code>M-[</code>	Next / previous suggestion
<code>C-]</code>	Dismiss suggestion

Formatting

<code>leader f</code>	Format buffer (conform.nvim; runs on save too)
-----------------------	--

Debugging (nvim-dap) — Python & C++

<code>F5</code>	Continue / start
<code>F1</code> / <code>F2</code> / <code>F3</code>	Step into / over / out
<code>leader b</code>	Toggle breakpoint
<code>leader B</code>	Conditional breakpoint
<code>F7</code>	Toggle debugger UI

First use in a session loads the plugin and may pause briefly while Mason finishes registering.

Julia REPL (iron.nvim) — `.jl` files

<code>localleader is</code>	Open REPL
<code>localleader ir</code>	Restart REPL
<code>localleader if</code>	Focus REPL
<code>localleader ih</code>	Hide REPL
<code>localleader sl</code>	Send line
<code>localleader sp</code>	Send paragraph
<code>localleader sc</code>	Send selection / motion
<code>localleader sf</code>	Send whole file
<code>localleader su</code>	Send until cursor
<code>localleader sq</code>	Exit REPL
<code>localleader scl</code>	Clear REPL

Real terminal REPL: Pkg mode], help ?, shell ;, and OhMyREPL all work natively.

Git Hunks (gitsigns)

<code>]c</code> / <code>[c</code>	Next / previous hunk
<code>leader hs</code>	Stage hunk (visual: stage selection)
<code>leader hr</code>	Reset hunk (visual: reset selection)
<code>leader hS</code>	Stage whole buffer
<code>leader hR</code>	Reset whole buffer
<code>leader hu</code>	Undo last stage
<code>leader hp</code>	Preview hunk diff
<code>leader hb</code>	Blame current line
<code>leader hd</code>	Diff file against index
<code>leader hD</code>	Diff file against last commit
<code>leader tb</code>	Toggle inline blame
<code>leader tD</code>	Toggle inline preview of deleted lines

AI Agents — `leader a`

<code>ac</code>	Toggle Claude Code
<code>af</code>	Focus Claude (smart toggle)
<code>ar</code>	Resume Claude session
<code>aC</code>	Continue Claude session
<code>am</code>	Select Claude model
<code>ab</code>	Add current buffer to context
<code>as</code>	Send selection (visual) / add file (tree)
<code>aa</code> / <code>ad</code>	Accept / deny Claude's diff
<code>ag</code>	Toggle Antigravity CLI (agy)

After a Claude/Antigravity window gains focus you're dropped into terminal mode — `Esc Esc` to leave it, `i` to resume typing to it.

Quarto / Molten — `.qmd` notebooks

<code>localleader rc</code>	Run cell
<code>localleader rl</code>	Run line
<code>localleader rA</code>	Run all cells
<code>localleader r</code>	(visual) Run range
<code>localleader mi</code> / <code>md</code>	Init / stop Molten kernel

localleader mp Image popup

localleader mb Open output in browser
localleader mh / ms Hide / show output