

Neovim Daily Keybind Reference

leader = `Space` · localleader = `,` · generated from `~/.config/nvim`

General & Navigation

`Esc` Clear search highlight
`Esc Esc` Leave terminal mode (Claude, Antigravity, any `:terminal`)
`C-h/j/k/l` Move focus between window splits
`C-o` / `C-i` Jump back / forward (after `grd`, searches, etc.)
`leader q` Diagnostics to quickfix list
`zR` / `zM` Open / close all folds
`za` / `zo` / `zc` Toggle / open / close fold under cursor
`saiw`) Surround Add Inner Word with)
`sd'` Surround Delete '
`sr)`' Surround Replace) with '
`va`) / `ci'` Select / change around-or-inside a text object
`\` Reveal current file in neo-tree

Built-in Essentials

`u` / `C-r` Undo / redo
`.` Repeat last change
`C-v` Visual block mode (column edits)
`qa ... q` Record macro to register a
`a` Play macro from register a
`ma` / ``a` Set mark a / jump to mark a
`J` Join line below with a space
`C-w s` / `C-w v` Split window horizontally / vertically
`C-w q` Close current window

Search (Telescope) — `leader s...`

`sf` Find files
`sg` Live grep
`sw` Grep word under cursor
`sd` Search diagnostics
`sh` Search help
`sk` Search keymaps
`ss` Search Telescope pickers

`sr` Resume last search
`s.` Recent files
`s/` Grep in open files only
`sn` Find files in nvim config
`leader leader` Find open buffers
`leader /` Fuzzy search current buffer

LSP

`K` Hover docs
`grn` Rename
`gra` Code action
`grr` References
`gri` Go to implementation
`grd` Go to definition
`grD` Go to declaration
`grt` Go to type definition
`g0` / `gW` Document / workspace symbols
`leader th` Toggle inlay hints

Completion (blink.cmp) — insert mode

`Tab` / `S-Tab` Snippet jump forward / back
`C-y` Accept completion
`C-n` / `C-p` Next / previous item
`C-space` Open menu / docs
`C-e` Dismiss menu
`C-k` Toggle signature help

Copilot — ghost text, insert mode

`M-l` Accept suggestion
`M-]` / `M-[` Next / previous suggestion
`C-]` Dismiss suggestion

Formatting

`leader f` Format buffer (conform.nvim; runs on save too)

Debugging (nvim-dap) — Python & C++

F5	Continue / start
F1 / F2 / F3	Step into / over / out
leader b	Toggle breakpoint
leader B	Conditional breakpoint
F7	Toggle debugger UI

First use in a session loads the plugin and may pause briefly while Mason finishes registering.

Julia REPL (iron.nvim) — .jl files

localleader is	Open REPL
localleader ir	Restart REPL
localleader if	Focus REPL (from code) / jump back (from REPL)
localleader ih	Hide REPL
localleader sl	Send line
localleader sp	Send paragraph
localleader sc	Send selection / motion
localleader sf	Send whole file
localleader su	Send until cursor
localleader sq	Exit REPL
localleader scl	Clear REPL

Real terminal REPL: Pkg mode], help ?, shell ;, and OhMyREPL all work natively.

Python REPL (iron.nvim) — .py files

localleader is	Open REPL (ipython)
localleader ir	Restart REPL
localleader if	Focus REPL (from code) / jump back (from REPL)
localleader ih	Hide REPL
localleader sl	Send line
localleader sp	Send paragraph
localleader sc	Send selection / motion
localleader sb	Send cell/block (between # %% markers)
localleader sf	Send whole file
localleader su	Send until cursor

localleader sq	Exit REPL
localleader scl	Clear REPL
localleader rr	Run file non-interactively (floating term)
]] / [[	Next / previous cell (# %% marker)

%% cells are the Jupyter/VS Code "percent format" — same convention .ipynb files already round-trip through. `localleader rr` is a one-shot run, separate from the REPL. Both auto-detect a project .venv (e.g. uv venv), walking up from the file, and fall back to the global interpreter if none is found.

Git Hunks (gitsigns)

]c / [c	Next / previous hunk
leader hs	Stage hunk (visual: stage selection)
leader hr	Reset hunk (visual: reset selection)
leader hS	Stage whole buffer
leader hR	Reset whole buffer
leader hu	Undo last stage
leader hp	Preview hunk diff
leader hb	Blame current line
leader hd	Diff file against index
leader hD	Diff file against last commit
leader tb	Toggle inline blame
leader tD	Toggle inline preview of deleted lines

AI Agents — `leader a`

ac	Toggle Claude Code
af	Focus Claude (smart toggle)
ar	Resume Claude session
aC	Continue Claude session
am	Select Claude model
ab	Add current buffer to context
as	Send selection (visual) / add file (tree)
aa / ad	Accept / deny Claude's diff
ag	Toggle Antigravity CLI (agy)

After a Claude/Antigravity window gains focus

you're dropped into terminal mode — `Esc Esc`
to leave it, `i` to resume typing to it.

Quarto / Molten — .qmd notebooks

<code>localleader rc</code>	Run cell
<code>localleader rl</code>	Run line
<code>localleader rA</code>	Run all cells
<code>localleader r</code>	(visual) Run range
<code>localleader mi</code> / <code>md</code>	Init / stop Molten

kernel

<code>localleader mp</code>	Image popup
<code>localleader mb</code>	Open output in browser
<code>localleader mh</code> / <code>ms</code>	Hide / show output

.ipynb opens via jupyter as `ft=python` (`# %%` cells), *not* quarto — `rc/rl/rA` don't bind there. Use `:MoltenEvaluateLine/Operator/Visual` for kernel output with plots, or the Python REPL section's `localleader sb/sc` etc. (iron.nvim) for plain-text ipython output.