Converting HTML to PDF

Created with a trial version of Syncfusion PDF library or registered the wrong key in your application. Click here to obtain the valid key.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg

(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package

Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

NOTE

The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

NOTE

This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

Created with a trial version of Syncfusion PDF library.

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Convert HTML to PDF

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested.

Created with a trial version of Syncfusion PDF library.

Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Created with the trial version of Syncfusion PDF library.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

ConvertHTMLtoPDF

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves

Created with a trial version of Syncfusion PDF library.

all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

ConvertHTMLtoPDF

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.
- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Image

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Partial webpage to PDF

Created with a trial version of Syncfusion PDF library.

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

Created with a trial version of Syncfusion PDF library.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE
>
> - The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
> - The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Created with a trial version of Syncfusion PDF library.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Created with a trial version of Syncfusion PDF library.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Rotate page

Created with a trial version of Syncfusion PDF library.

To set the page rotation when converting HTML to PDF, utilize the PageRotateAngle property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

HTML Header and Footer

When converting HTML to PDF, you can set an HTML file as header and footer. Use the **HtmlHeader** and **HtmlFooter** properties within the BlinkConverterSettings class to do this.

You can download a complete working sample from GitHub.

> NOTE
>
> Adjust the HTML margin top and bottom values according to the height of the HTML header and footer, as well as the margin settings.

Inject custom CSS

The Blink rendering engine supports the injection of custom CSS to be applied to HTML or a URL before rendering it into a PDF document using the 'Css' property of the BlinkConverterSettings class

You can download a complete working sample from GitHub.

Inject custom JavaScript

The Blink rendering engine offers support for injecting custom JavaScript to be applied to the HTML or a URL before rendering it into a PDF document using the 'JavaScript' property of the BlinkConverterSettings class.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Performance optimization

The Blink rendering engine provides support for reusing the browser process to optimize the HTML to a PDF performance for multiple operations using the 'ReuseBrowserProcess' property of the HtmlToPdfConverter class.

You can download a complete working sample from GitHub.

Temporary path

The Blink HTML converter launching Chrome browser to perform conversion. While launching Chrome browser, temporary files are created in a temporary folder.

By default, HTML converter takes system temporary path (C:\Users<<username»\AppData\Local\Temp or C:\Windows\Temp) to perform the conversion.

The temporary path can be changed by using the TempPath property of BlinkConverterSettings. If this property is set, the converter uses the provided path to perform the conversion. Refer to the following code example.

You can download a complete working sample from GitHub.

Blink path

When converting HTML to a PDF document, the default reference to the blink binaries path eliminates the need for manual addition. Nonetheless, if you prefer to manually add the blink binaries path or reference it from a custom location, simply set the path of the BlinkBinaries folder to the BlinkPath property of BlinkConverterSettings.

> NOTE

- The BlinkBinaries will be available in the HTMLConverter installed location ($SystemDrive\Program Files (x86)\Syncfusion\HTMLConverter\xx.x.x.xx\BlinkBinaries)
- The BlinkBinaries also available in NuGet package installed location if you are using Blink HTML converter from NuGet packages.

You can download a complete working sample from GitHub.

Scale

Resizing the HTML content within a PDF can be achieved through the utilization of the Scale property of Blink in HTML Converter.

> NOTE
>
> The scaling factor should be within the range of 0.1 to 2.0.

You can download a complete working sample from GitHub.

Timeout

HTML content being converted takes a long time to render or convert into a PDF can be achieved through the utilization of the Timeout property of Blink in HTML Converter.

You can download a complete working sample from GitHub.

Accessible PDF

The Blink HTML converter supports preserving tags from HTML to PDF using the EnableAccessibilityTags property in the BlinkConverterSettings class. Refer to the following code sample.

> NOTE
>
> This support fully depends on the Chromium headless browser. Our converter preserves the tags, same as the saved PDF from Chrome.

You can download a complete working sample from GitHub.

Image Background

The Blink HTML converter support adding the image background from HTML to Image using the ImageBackgroundColor property in BlinkConverterSettings class. Refer to the following code sample.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Converting HTML to PDF

Created with a trial version of Syncfusion PDF library.

The HTML to PDF converter is a .NET library for converting webpages, SVG, MHTML, and HTML files to PDF using C#. It uses popular rendering engines such as Blink (Google Chrome) and is reliable and accurate. The result preserves all graphics, images, text, fonts, and the layout of the original HTML document or webpage.

Syncfusion HTML-to-PDF converter will work seamlessly in various platforms like Azure Cloud or web apps, Azure Functions, Amazon Web Service (AWS), Docker, WinForms, WPF, ASP.NET MVC, ASP.NET Core with Windows, Linux, and macOS.

Key features for HTML Converter

- Converts any webpage to PDF.
- Converts any raw HTML string to PDF.
- Converts HTML form to fillable PDF form.
- Automatically creates Table of Contents.
- Automatically creates bookmark hierarchy.
- Converts only a part of the web page to PDF.
- Supports PDF header and PDF footer.
- Repeats HTML table header and footer in PDF.
- Supports HTML5, CSS3, SVG, and Web fonts.
- Converts any HTML to an image.

- Converts any SVG to image.
- Supports accessing HTML pages using both HTTP POST and GET methods.
- Supports HTTP cookies.
- Supports cookies-based form authentication.
- Thread safe.
- Supports internal and external hyperlinks.
- Sets document properties, page settings, security, viewer preferences, and more.
- Protects PDF document with password and permission.
- Compatible with .NET Framework 4.5 and above.
- Compatible with .NET Core 2.0 and above.

Created with a trial version of Syncfusion PDF library.

Install HTML to PDF .NET library to your project

Include the HTML to PDF converter in your project using two approaches.

- NuGet packages (Recommended)
- Assemblies.

NuGet Packages Required (Recommended)

Directly install the NuGet packages to your .NET application from nuget.org.

> NOTE
>
> The HTML to PDF converter library internally uses the Blink rendering engine for the conversion. The binaries will differ for Windows, Linux, Mac, and AWS. So, separate packages are provided based on OS. Include the packages based on your requirement.

Platform(s)	NuGet Package
(.NET Core, .NET 5, .NET 6) Windows	Syncfusion.HtmlToPdfConverter.Net.Windows.nupkg
(.NET Core, .NET 5, .NET 6) Linux	Syncfusion.HtmlToPdfConverter.Net.Linux.nupkg
(.NET Core, .NET 5, .NET 6) Mac	Syncfusion.HtmlToPdfConverter.Net.Mac.nupkg
(.NET Core, .NET 5, .NET 6) AWS	Syncfusion.HtmlToPdfConverter.Net.Aws.nupkg

Use the following packages for .NET Framework targeted applications. If you are using other Syncfusion libraries or components, use the HTML to PDF converter library with the same platform packages.

Platform(s)	NuGet Package
Windows Forms	Syncfusion.HtmlToPdfConverter.WinForms.nupkg
WPF	Syncfusion.HtmlToPdfConverter.Wpf.nupkg
ASP.NET	Syncfusion.HtmlToPdfConverter.AspNet.nupkg
ASP.NET MVC	Syncfusion.HtmlToPdfConverter.AspNet.Mvc5.nupkg

Assemblies Required

Get the following required assemblies by downloading the HTML converter installer. Download and install the HTML converter for Windows, Linux, and Mac, respectively. Please refer to the advanced installation steps for more details.

Platforms	Assemblies
WinForms WPF ASP.NET ASP.NET MVC	• Syncfusion.Compression.Base.dll • Syncfusion.Pdf.Base.dll • Syncfusion.HtmlConverter.Base.dll • Newtonsoft.Json package (v13.0.1 or above)
.NET/.NET Core Blazor	• Syncfusion.Compression.Portable.dll • Syncfusion.Pdf.Portable.dll • Syncfusion.HtmlConverter.Portable.dll • Newtonsoft.Json package (v13.0.1 or above)

Created with a trial version of Syncfusion PDF library.

Convert HTML to PDF in Linux

HTML to PDF converter .NET library supports conversion in Linux. Refer to this section for more information about HTML to PDF conversion in Linux.

Convert HTML to PDF in Docker

HTML to PDF converter .NET library supports conversion in Docker. Refer to this section for more information about HTML to PDF conversion in Docker.

Convert HTML to PDF in Mac

HTML to PDF converter .NET library supports conversion in Mac. Refer to this section for more information about HTML to PDF conversion in Mac.

Convert HTML to PDF in ASP.NET Core

HTML to PDF converter .NET library supports conversion in ASP.NET Core. Refer to this section for more information about HTML to PDF conversion in ASP.NET Core.

Convert HTML to PDF in ASP.NET MVC

HTML to PDF converter .NET library supports conversion in ASP.NET MVC. Refer to this section for more information about HTML to PDF conversion in ASP.NET MVC.

Convert HTML to PDF in Blazor

HTML to PDF converter .NET library supports conversion in Blazor. Refer to this section for more information about HTML to PDF conversion in Blazor.

Convert HTML to PDF in Azure

HTML to PDF converter .NET library supports conversion in Azure. Refer to this section for more information about HTML to PDF conversion in Azure.

Convert HTML to PDF in AWS

HTML to PDF converter .NET library supports conversion in AWS. Refer to this section for more information about HTML to PDF conversion in AWS.

Features

Refer to this section for more information about features in HTML to PDF converter, you can get the details, code examples and demo from this section.

Created with a trial version of Syncfusion PDF library.

HTML converter Features

URL to PDF

To convert website URL or local HTML file to PDF document using Convert method in HtmlToPdfConverter class. refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to PDF

The HTML to PDF converter provides support for converting HTML string to PDF. While converting HTML string to PDF, converter provides option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the above image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location, then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to PDF using Convert method, refer to the following code example.

You can download a complete working sample from GitHub.

URL to Image

To convert website URL or local HTML file to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

HTML String to Image

The Blink rendering engine supports converting HTML string to Image. While converting HTML string to Image, converter provides an option to specify the base URL.

baseURL: Path of the resources (images, style sheets, scripts.,) used in the input HTML string.

For the following HTML string, the baseURL will be the path of the *syncfusion_logo.gif* image.

For example, if the previous image is in *"C:/Temp/ HTMLFiles/syncfusion_logo.gif"* location then the baseURL will be as follows.

baseURL: C:/Temp/HTMLFiles/

To convert the HTML string to Image using ConvertToImage method, refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

JavaScript

The Blink HTML converter supports enabling or disabling the JavaScript using EnableJavaScript property in BlinkConverterSettings class. while converting HTML to PDF. Refer to the following code example.

You can download a complete working sample from GitHub.

Additional delay

The Blink HTML converter provides an option to set the AdditionalDelay property while converting HTML to PDF. Additional delay is the waiting time of the converter for loading the external resources (styles, scripts, images and more). Refer to the following code example.

You can download a complete working sample from GitHub.

Hyperlinks

The Blink HTML converter support preserving URL links from HTML to PDF using EnableHyperLink property in BlinkConverterSettings class. Refer to the following code snippet.

You can download a complete working sample from GitHub.

Bookmarks

The Blink HTML converter provides support for creating bookmarks automatically by enabling the EnableBookmarks property.

> NOTE
>
> The bookmarks are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents

The Blink HTML converter provides support for creating a table of contents automatically by using the EnableToc property.

> NOTE
>
> TOC are added from the `<h>` tag, it supports from `<h1>` to `<h6>`.

You can download a complete working sample from GitHub.

Table of contents with custom style

The Blink HTML converter provides support for customizing the table of contents style. Each header tag style can be customized by using HtmlToPdfTocStyle.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.

Media Type

The Blink HTML Converter allows selection of media type while converting HTML to PDF. Blink rendering engine supports **Screen** and **Print** media types. Refer to the following code snippet to select Print MediaType.

You can download a complete working sample from GitHub.

> NOTE
>
> Print MediaType MediaType enables the repeat html table header and footer support on every PDF page.

HTML Form to PDF Form

Blink rendering engine provides support for converting HTML forms to PDF fillable forms automatically by using the EnableForm property. To convert HTML form to PDF form, refer to the following code example.

You can download a complete working sample from GitHub.

Windows authentication

The webpage you want to convert may protected with windows authentication. Blink rendering engine provides support for converting the Windows Authenticated webpage to PDF document by providing the Username and Password property in BlinkConverterSettings class. Refer to the following code example.

Created with a trial version of Syncfusion PDF library.

You can download a complete working sample from GitHub.

Form authentication

The Blink HTML converter provides support for form authentication by using Cookies property in BlinkConverterSettings class. The cookies are send to web server for form authentication when the HTML page is requested. Each cookie is represented by a name and value. Refer to the following code example.

You can download a complete working sample from GitHub.

Token-based authentication

The Blink HTML converter supports token-based authentication by using the HttpRequestHeaders property in BlinkConverterSettings class.. The token values will be send to web server when the HTML page is requested. Refer to the following code example.

You can download a complete working sample from GitHub.

Offline conversion

The Blink HTML converter supports converting HTML to PDF in offline mode using EnableOfflineMode property in BlinkConverterSettings class. While converting HTML to PDF in offline mode, the converter does not access the resources from the internet. This may increase the performance in slow internet connection.

> NOTE
>
> If an online URL is converted in offline mode, the converter will generate empty PDF as it will not try to load any resource from online.

You can download a complete working sample from GitHub.

HTTP GET and POST

The Blink HTML converter supports transmitting the parameter to the webpage. There are two methods to access a webpage. By default, Blink uses GET method. By using HTTP GET method, the parameters can be passed in the query string. In POST method, the parameters can be passed by using the HttpPostFields property.
Refer to the following code snippet to access a webpage using HTTP POST.

You can download a complete working sample from GitHub.

You can download a complete working sample from GitHub.

System proxy

By default, the Blink rendering engine use system proxy settings for converting HTML to PDF. If proxy server is configured in the system, then the rendering engine automatically use the same settings for the conversion. Follow the below steps to set the system proxy settings:

1. Control Panel > Network and Internet > Internet Options.
2. From Internet properties window, open LAN settings under connections tab.
3. Then, set proxy server address and port in LAN settings window.

Manual proxy

You can specify the manual proxy settings for the conversion using the ProxySettings property. Refer to the following code snippet to configure the manual proxy settings for the conversion.

Viewport

Adjusting the HTML content size in PDF is possible by using the ViewPortSize property of Blink HTML converter. Refer to the following code snippet to adjust Blink viewport.

You can download a complete working sample from GitHub.

Partial webpage to PDF

The Blink rendering engine provides support for converting only the part of an HTML document like a table, div, or image elements from the URL/HTML string. You can convert the particular HTML element using ConvertPartialHtml method by specifying the HTML element ID, refer to the following code example.

You can download a complete working sample from GitHub.

HTML to single PDF page

By using this SinglePageLayout property, you can render the whole HTML content into a single PDF page. The PDF page size is limited to 14400 points. There are two options to enable this feature since this is disabled by

Created with a trial version of Syncfusion PDF library.

default.

```
1. FitWidth
2. FitHeight
```

Fit width option: Using this option, the HTML converter adjusts the PDF page height based on the HTML content height. PDF page width remains constant for this option.
Fit height option: Using this option, the HTML converter scale the HTML content and PDF page width to render the whole HTML content within the height. PDF page height remains constant for this option.

Layout Result

Getting height of the HTML content in PDF document is possible by using the PdfLayoutResult class. Using this result, you can add contents after converting HTML to PDF. Refer to the following code example.

Windows status

Windows status can be used instead of additional delay. In additional delay, the amount of time required for loading the resources is unpredictable. This behavior can be avoided by using WindowStatus property.

> NOTE
>
> This feature requires changes in the HTML file.
>
> NOTE
>
> If windows status does not match in code and HTML, then the converter will meet with deadlock.

You can download a complete working sample from GitHub.

Page size customization

To set the page size when converting HTML to PDF, utilize the PdfPageSize property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Margin customization

To set the margin when converting HTML to PDF, utilize the Margin property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Header and footer

To set the header and footer when converting HTML to PDF, utilize the PdfHeader and PdfFooter properties in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Page orientation customization

To set the Orientation when converting HTML to PDF, utilize the Orientation property in the BlinkConverterSettings class. Please refer to the following code example.

You can download a complete working sample from GitHub.

Created with a trial version of Syncfusion PDF library.
Created with a trial version of Syncfusion PDF library or registered the wrong key in your application. Click here to obtain the valid key.