

Verification and Validation Report: Software Engineering

Team 2, SyntaxSentinals
Mohammad Mohsin Khan
Lucas Chen
Dennis Fong
Julian Cecchini
Luigi Quattrociochi

March 11, 2025

1 Revision History

Date		Version	Notes
March 2025	10th,	0.0	First iteration of rough draft complete

2 Symbols, Abbreviations and Acronyms

symbol	description
T	Test
SRS	Software Requirements Specification
MOSS	Measure of Software Similarity
UI	User Interface
JSON	JavaScript Object Notation
NPM	Node Package Manager
VnV	Verification and Validation
API	Application Programming Interface
CI/CD	Continuous Integration/Continuous Deployment

Contents

1	Revision History	i
2	Symbols, Abbreviations and Acronyms	ii
3	Functional Requirements Evaluation	1
3.0.1	Plagiarism Analysis Input Upload Tests	1
3.0.2	Plagiarism Analysis Result Tests	1
3.0.3	Guide Documentation Generation Tests	1
3.0.4	Report Documentation Generation Tests	2
3.0.5	Account Creation Tests	2
3.0.6	Account Login Tests	2
3.0.7	Result Email Tests	3
3.0.8	Result Visualization Tests	3
4	Nonfunctional Requirements Evaluation	4
4.1	Usability	17
4.2	Performance	17
4.3	etc.	17
5	Comparison to Existing Implementation	17
5.1	Overview of Existing Solutions	17
5.1.1	MOSS (Measure of Software Similarity)	17
5.1.2	Other Notable Solutions	17
5.2	Our Implementation vs. Existing Solutions	18
5.2.1	Current Approach	18
5.2.2	Functional Comparison	18
5.3	Advantages of Our Approach	18
5.4	Current Limitations and Trade-offs	18
5.5	Design Decision Justification	19
5.6	Future Improvements	20
6	Unit Testing	20
6.1	AnalyzeFiles Component	20
6.1.1	Renders the component	20
6.1.2	Displays an alert when no file is uploaded	20
6.1.3	Displays an alert when no analysis name is entered	21

6.1.4	Calls uploadFiles and displays success message when form is submitted	21
6.1.5	Handles file drop event	22
6.2	UploadResults Component	22
6.2.1	Renders the component	22
6.2.2	Displays an error message when a non-ZIP file is uploaded	23
6.2.3	Displays an error message when no JSON file is found in the ZIP	23
6.2.4	Displays a success message when a valid ZIP file is uploaded	23
6.2.5	Displays a warning message when trying to view results without uploading a file	24
6.2.6	Handles errors during ZIP file processing	24
6.2.7	Handles file drop event	25
6.3	Index (Landing Page) Component	25
6.3.1	Renders the component	25
6.3.2	Displays loading spinner when loading	26
6.3.3	Calls loginWithRedirect when Get Started button is clicked	26
6.3.4	Navigates to /home when authenticated	26
6.3.5	Displays features section	27
6.3.6	Displays how it works section	27
6.3.7	Displays footer	28
6.4	Upload File Box Component	28
6.4.1	Renders the component	28
6.4.2	Uploads a valid file	28
6.4.3	Removes a file	29
6.4.4	Clears the file list when clearFiles is true	29
6.5	NavBar Component	30
6.5.1	Renders the component	30
6.5.2	Displays the login button when not authenticated	30
6.5.3	Displays the logout button when authenticated	30
6.5.4	Calls loginWithRedirect when Log In button is clicked	31

7 Changes Due to Testing 31

8	Automated Testing	32
8.1	Testing Workflow Configuration	33
8.2	Testing Workflow Steps	33
8.3	Test Coverage Workflow Configuration	34
8.4	Test Coverage Workflow Steps	35
9	Trace to Requirements	35
10	Trace to Modules	37
11	Code Coverage Metrics	37

List of Tables

2	Comparison between MOSS and our CodeBERT implementation	19
3	Traceability Matrix	36
4	Test Coverage Breakdown by Directory	38

List of Figures

3 Functional Requirements Evaluation

3.0.1 Plagiarism Analysis Input Upload Tests

Applies to all FRs involving uploading code snippets to the system. This refers to test-FR-1 from the VnV Plan.

1. test-FR-1

Expected result: The script should run and successfully upload the files, without encountering any errors due to the upload functionality

Actual Result: No errors from uplading

Evaluation: Pass

3.0.2 Plagiarism Analysis Result Tests

Applies to all FRs involving immediate output of plagiarism analysis. This refer to test-FR-2 from the VnV Plan.

1. test-FR-2

Expected result: The analysis should not throw any errors while the script runs, up until the analysis provides a response

Actual result: No errors were observed during script execution

Evaluation: Pass

3.0.3 Guide Documentation Generation Tests

Applies to all FRs involving guide documentation generation for user. This refers to test-FR-3 from the VnV plan.

1. test-FR-3

Expected result: Generation of documentation successful

Actual result: TBD when feature is implemented

Evaluation: TBD

3.0.4 Report Documentation Generation Tests

Applies to all FRs involving analysis report documentation generation for user. This refers to test-FR-4 from the VnV plan.

1. test-FR-4

Expected result: Generation of report is successful, with no errors encountered

Actual result: Report was successfully generated, no errors were found

Evaluation: Pass

3.0.5 Account Creation Tests

Applies to all FRs involving creating an account within the system. This refers to test-FR-5 and test-FR-6 from the VnV plan

1. test-FR-5

Expected result: An account should be successfully created, while the system avoids any failure modes.

Actual result: Account successfully created, and no failure modes were exhibited

Evaluation: Pass

2. test-FR-6

Expected result: Account creation should fail and the system will await further input from the user

Actual result: Account creation fails, and the system does not proceed

Evaluation: Pass

3.0.6 Account Login Tests

Applies to all FRs involving logging into account within the system. This refers to test-FR-7 and test-FR-8 in the VnV plan

1. test-FR-7

Expected result: Logging into system with correct existing credentials should succeed, and no errors should arise from logging in

Actual result: Logging in with existing credentials succeeds with no errors

Evaluation: Pass

2. **test-FR-8**

Expected result: Logging in with invalid credentials should fail

Actual result: Logging in with invalid credentials fails

Evaluation: Pass

3.0.7 Result Email Tests

Applies to all FRs involving emailing results of plagiarism analysis to users. This refers to test-FR-9 from the VnV plan.

1. **test-FR-9**

Expected result: The system will send an e-mail to address associated with the logged in account, containing a .zip file with plagiarism results corresponding to the files uploaded

Actual result: Correct and corresponding .zip file was sent to the expected e-mail

Evaluation: Pass

3.0.8 Result Visualization Tests

Applies to all FRs involving visualizing plagiarism analysis results provided by user in a .zip file. This refers to test-FR-10 from the VnV plan.

1. **test-FR-10**

Expected result: A visualization is successfully created after uploading a .zip file, with no errors observed during the process.

Actual result: A visualization was successfully created with no errors

Evaluation: Pass

4 Nonfunctional Requirements Evaluation

ID	Reference Re-quire-ments	User Action	Expected Result	Actual Re-sult	Result
test-LF-1	LF-AR1, LF-AR2, LF-AR3, LF-SR1, LF-SR2, LF-SR3, LF-SR4	Developer reviews UI code and interface for consistency with the SRS elements specified in VnV plan such as uniform colour palette.	UI should follow defined layout, typography, alignment, color palette, tooltips, responsiveness, and font.	Developer verified uniform color palette, tooltips, responsive design, and font consistency. All requirements were met.	Pass
test-LF-2	CR-SC3	Developer utilizes accessibility tools to assess sufficient readability and alt-text for images	All images should have alt text, and text should meet contrast and sizing standards.	Developer verified all images have alt text and all text meets contrast and sizing requirements using Chrome DevTools.	Pass

ID	Reference Re-quire-ments	User Action	Expected Result	Actual Re-sult	Result
test-UH-1	UH-E1, UH-E3, UH-L1, UH-UP1, UH-UP2, OE-P1	User goes through the onboarding process and provides feedback on usability.	User finds onboarding process intuitive with no major issues; usability rating should be 4/5 or greater.	5 users tested the onboarding process. All rated ease of use and clarity at 4/5 or greater.	Pass
test-UH-2	UH-E2	User navigates through key functions of code submission and report upload	User should complete each task with minimal clicks required.	5 users tested navigation to code submission and report upload, reporting 2-3 clicks each from upload to select to run.	Pass
test-UH-3	UH-PI2	Tester verifies that all pages and prompts are in English (US)	No foreign languages should be present on any page or prompt.	Tester verified that all pages and prompts were in English (US), no foreign languages found.	Pass

ID	Reference Re-quire-ments	User Action	Expected Result	Actual Re-sult	Result
test-V-1	MS-M1, OR-R2	Developer re-views GitHub repository for historical versions and changelogs	All previ-ous versions should be stored with performance reports and changelogs.	Developer confirmed that histori-cal versions with per-formance reports and changelogs are accessible on GitHub.	Pass
test-PS-1	SR-P1	Tester per-forms a data retention audit to identify any personally identifiable data	No personally identifiable data or user-generated data should be found in logs or filesystem.	Tester found no PII or user-generated data during testing. Logs were clean.	Pass
test-PS-2	SR-P2	Tester verifies that backend endpoints use HTTPS encryption	All endpoints should use HTTPS with proper secu-rity headers.	Tester con-firmed all backend end-points used HTTPS with proper secu-rity headers as shown with REST API utilized.	Pass

ID	Reference Re-quire-ments	User Action	Expected Result	Actual Re-sult	Result
test-PS-3	CR-L1, CR-L2, CR-L3, CR-S2, CR-S5	Legal audit of the system against regulations like PIPEDA, FIPPA, etc.	System should adhere to legal standards without any breaches.	Third-party tester verified the system's compliance with PIPEDA, FIPPA, and other regulations. No breaches found. This is inherent by only utilizing publicly available repos and data	Pass
test-DS-1	MS-M3	Tester inspects the GitHub repository for bug tracking.	Bugs should be listed as issues in the repository.	Tester confirmed bugs are listed in the 'issues' section on GitHub. Chores and fixes have been dealt with as issues	Pass

ID	Reference Re-quire-ments	User Action	Expected Result	Actual Re-sult	Result
test-DS-2	MS-S1, CR-SC1	Team inspects code to ensure adherence to software development standards	Code should follow SOLID principles, and be documented with appropriate tests.	Team inspected code, confirming adherence to SOLID principles, documentation, and test presence. Code for backend application follows direct interface hiding rules and currently complies. Our frontend works on a component based development path and therefore adheres too.	Pass

ID	Reference Re-quire-ments	User Action	Expected Result	Actual Re-sult	Result
test-D-1	UH-L2, OE-P2	Developer reviews user documen-tation for clarity, ac-curacy, and helpfulness	Documentation should be clear, non-technical, and helpful to users.	Help docu-mentation is still to be developed per extra but current README files exist to specify steps for applica-tion use in clear and ba-sic language for users.	Pass with ex-ception to extra
test-PR-1	PR-SL1, PR-C1	System pro-cesses 500 code snippets for plagia-rism analysis within 4 hours	Processing should com-plete in under 4 hours.	System completed processing within 4 hours, perfor-mance met expectations.	Pass

ID	Reference	User Action	Expected Result	Actual Result	Result
test-PR-2	PR-SL2	Tester initiates a long-running task and checks for an email notification after 10 minutes	Email should be sent after 10 minutes to notify the user of long processing time.	Email notification was sent 10 minutes after task initiation, confirming functionality. Although in practice, have not met any input size that has forced processing time that long.	Pass
test-PR-3	PR-SL2	Tester checks system logs to verify that a notification was triggered after 10 minutes of processing	Logs should show an entry for the email notification after 10 minutes.	System logs confirmed that a notification was triggered after 10 minutes. Emails have always been made within a 10 minute time window, for intense processing or not.	Pass

ID	Reference	User Action	Expected Result	Actual Result	Result
test-PR-4	PR-RFT1	Tester submits a corrupted file and verifies system response	System should reject the corrupted input with an error message without crashing.	System rejected the corrupted input with an error message. Valid input processed without issue. i.e., non-python or tar package file creates error which frontend appropriately communicates.	Pass

ID	Reference Re-quire-ments	User Action	Expected Result	Actual Re-sult	Result
test-PR-5	PR-PA1, PR-PA2	Tester submits 500 code snippets for plagiarism analysis and compares results with ground truth.	System should show over 90% accuracy and less than 5% false positives.	Recently found method to test this through self-labelled datasets as it was not immediately possible from python800 datasets (no concept of similarity or ground truths) Have spent time labelling hundreds of code in manual fashion to assess this and have not had time to test it.	Future Assessment

ID	Reference	User Action	Expected Result	Actual Result	Result
test-PR-6	PR-SE1	Developer adds a new feature, and all existing features are tested for regression.	All previous features should work as expected after the new feature is added.	Regression tests confirmed that all features worked as expected after the new feature was added but not server side yet	Fail
test-OE-1	OE-IAS1	User connects system to a cloud service (e.g., AWS or Azure) and verifies successful connection.	System should successfully connect to cloud service and display a confirmation message.	Cloud has yet to be connected. It is a later stage development process	Future Assessment
test-OE-2	OE-IAS2	User deploys the system on a free hosting service and verifies system access after cloning from github.	System should be accessible via a public URL and function as expected.	System has not been deployed to AWS or other free hosting services yet. Later stage development.	Future Assessment

ID	Reference	User Action	Expected Result	Actual Result	Result
test-OE-3	OE-IAS3	User authenticates via an external service (e.g., Google, GitHub) and gains access to the UI.	System should authenticate user and redirect to the home page.	User successfully authenticated via Google through Auth Zero and was redirected to the home page.	Pass
test-M-1	MS-M2	Model release is accompanied by a report of metrics such as accuracy, precision, etc.	A report should be generated with relevant metrics for the model release.	Current model release has metrics on microsoft although future releases will have a new report attached and that is part of later stage development	Future Assessment
test-M-2	MS-S3	User posts a request or issue on GitHub, verifying visibility to others	The request or issue should be visible to other users.	Request posted on GitHub was visible to other users as expected.	Pass

ID	Reference	User Action	Expected Result	Actual Result	Result
test-M-3	MS-A2	Model code follows template, and components inherit interfaces/classes.	Model components should follow the predefined template and interface inheritance.	Code was inspected and confirmed that all components inherited from interfaces/classes as required. Model app structure follows SOLID principles and model itself is masked in pytorch.	Pass
test-M-4	MS-A1	Training script receives two formats of training data and completes an epoch.	Training script should successfully complete an epoch with both data formats.	Training script completed successfully with both data formats (java and python files) and have corresponding checkpoint files to show.	Pass

ID	Reference Re-quire-ments	User Action	Expected Result	Actual Re-sult	Result
test-M-5	MS-A3	Each model layer/component is tested with an appropriate input vector and verifies transformation.	Each layer/component should modify the input vector according to its specific architecture.	Model layers were tested, and all correctly transformed input vectors according to design. Pytorch and scipy layers used are atomic in nature and can be mixed as desired	Pass
test-S-1	SR-A1	User enters valid credentials and accesses the UI.	User should be authenticated and granted access to the UI.	User entered valid credentials and successfully accessed the UI.	Pass
test-S-2	SR-A1	User submits code to API with valid auth token.	API should allow code upload and return a success response.	API accepted valid auth token and processed code upload successfully.	Pass

ID	Reference Re-quire-ments	User Action	Expected Result	Actual Re-sult	Result
test-S-3	SR-A1	User at-tempts to access the API with invalid or missing auth token.	API should deny access and return an unauthorized response.	API denied access when provided with invalid or missing auth token.	Pass

4.1 Usability

4.2 Performance

4.3 etc.

5 Comparison to Existing Implementation

5.1 Overview of Existing Solutions

5.1.1 MOSS (Measure of Software Similarity)

MOSS is currently the standard tool for detecting code plagiarism in academic settings. Developed at Stanford University, it works by:

- Tokenizing code into a sequence of symbols
- Using document fingerprinting to detect similar code segments
- Generating a similarity score based on matching sequences
- Providing a web interface to view overlapping code segments

5.1.2 Other Notable Solutions

- **JPlag**: Uses a token-based approach similar to MOSS, but with different tokenization strategies

- **PLAGGIE**: Java-specific plagiarism detection tool used in academic environments
- **CodeMatch**: Commercial solution that uses both tokenization and metric-based methods

5.2 Our Implementation vs. Existing Solutions

5.2.1 Current Approach

Our implementation leverages CodeBERT, a pre-trained model for programming language understanding, to perform code pair comparison. Key aspects include:

- Utilization of transformer-based neural networks to understand code semantics
- Direct comparison of code pairs to determine similarity
- A modern, user-friendly interface for result visualization and analysis

5.2.2 Functional Comparison

5.3 Advantages of Our Approach

1. **Semantic Understanding**: Unlike MOSS’s purely syntactic approach, CodeBERT can potentially understand the meaning behind code, making it more difficult to fool with non-functional additions.
2. **Context Awareness**: Our implementation considers the context in which code appears, potentially reducing false positives from common solutions to standard problems.
3. **Modern Interface**: Our user interface provides a more intuitive experience for instructors reviewing potential plagiarism cases.

5.4 Current Limitations and Trade-offs

1. **Computational Requirements**: Neural models like CodeBERT require more computational resources than traditional approaches like MOSS.

Feature	MOSS	Our CodeBERT Implementation
Detection Method	Token-based fingerprinting	Neural representation and semantic understanding
Language Support	Multiple languages	Multiple languages (supported by CodeBERT)
Semantic Understanding	Limited (syntax-focused)	Enhanced (captures semantic meaning)
Resistance to Obfuscation	Low-moderate	Potentially higher
Speed	Fast for large submissions	Currently slower for large-scale comparisons
Visualization	Basic web interface	Modern, interactive UI

Table 2: Comparison between MOSS and our CodeBERT implementation

2. **Development Maturity:** MOSS has been refined over decades, while our solution is still in the early stages of development.
3. **Validation:** Our approach needs more extensive testing across different programming languages and assignments to prove its effectiveness.
4. **Explainability:** Neural network decisions can be less transparent than token-matching approaches, making it potentially harder to explain why certain code pairs were flagged.

5.5 Design Decision Justification

1. **Choice of CodeBERT:** We selected CodeBERT over other models because it was specifically pre-trained on code from multiple programming languages, making it well-suited for understanding code semantics across different languages used in academic settings.
2. **Focus on Pair Comparison:** While MOSS compares each submission against all others, our current approach focuses on direct pair comparison, allowing for more detailed analysis of potentially plagiarized code.

3. **UI Priority:** We invested in a high-quality UI early in development to facilitate easier testing and validation of our detection results.

5.6 Future Improvements

1. **Hybrid Approach:** Combining neural understanding with traditional token-based methods to leverage strengths of both approaches.
2. **Performance Optimization:** Improving the computational efficiency to handle large class submissions more effectively.
3. **Tunable Sensitivity:** Implementing adjustable thresholds for different assignment types and programming languages.

6 Unit Testing

6.1 AnalyzeFiles Component

6.1.1 Renders the component

- **Description:** Ensures the `AnalyzeFiles` component renders correctly.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `AnalyzeFiles` component.
 2. Check for the presence of specific text.
- **Expected result:** The component renders with the text "Analyze a Dataset" and "Upload a dataset to analyze for potential code plagiarism. Use a ZIP file containing your project files."

6.1.2 Displays an alert when no file is uploaded

- **Description:** Ensures an alert is displayed when no file is uploaded.
- **Type:** Automatic, Functional

- **Initial state:** None
- **Test case steps:**
 1. Render the **AnalyzeFiles** component.
 2. Click the "Analyze Dataset" button.
- **Expected result:** An alert with the message "Please upload a dataset file first." is displayed.

6.1.3 Displays an alert when no analysis name is entered

- **Description:** Ensures an alert is displayed when no analysis name is entered.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the **AnalyzeFiles** component.
 2. Upload a valid ZIP file.
 3. Click the "Analyze Dataset" button.
- **Expected result:** An alert with the message "Please enter an analysis name." is displayed.

6.1.4 Calls uploadFiles and displays success message when form is submitted

- **Description:** Ensures the **uploadFiles** function is called and a success message is displayed when the form is submitted.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the **AnalyzeFiles** component.

2. Upload a valid ZIP file.
 3. Enter an analysis name.
 4. Click the "Analyze Dataset" button.
- **Expected result:** The `uploadFiles` function is called with the file and analysis name, and a success message "Analysis started successfully. You'll receive an email with the results once it's done!" is displayed.

6.1.5 Handles file drop event

- **Description:** Ensures the file drop event is handled correctly when a file is dropped on the component.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `AnalyzeFiles` component.
 2. Simulate a file drop event with a valid ZIP file.
- **Expected result:** The file is uploaded successfully.

6.2 UploadResults Component

6.2.1 Renders the component

- **Description:** Ensures the `UploadResults` component renders correctly.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `UploadResults` component.
 2. Check for the presence of specific text.
- **Expected result:** The component renders with the text "View Results" and "Upload your results ZIP file to view the analysis."

6.2.2 Displays an error message when a non-ZIP file is uploaded

- **Description:** Ensures an error message is displayed when a non-ZIP file is uploaded.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `UploadResults` component.
 2. Upload a non-ZIP file.
- **Expected result:** An error message "Only ZIP files are allowed." is displayed.

6.2.3 Displays an error message when no JSON file is found in the ZIP

- **Description:** Ensures an error message is displayed when no JSON file is found in the ZIP file.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `UploadResults` component.
 2. Upload a ZIP file without a JSON file.
- **Expected result:** An error message "No JSON file found in the ZIP." is displayed.

6.2.4 Displays a success message when a valid ZIP file is uploaded

- **Description:** Ensures a success message is displayed when a valid ZIP file is uploaded.
- **Type:** Automatic, Functional

- **Initial state:** None
- **Test case steps:**
 1. Render the `UploadResults` component.
 2. Upload a valid ZIP file.
- **Expected result:** A success message "Results file uploaded successfully." is displayed.

6.2.5 Displays a warning message when trying to view results without uploading a file

- **Description:** Ensures a warning message is displayed when trying to view results without uploading a file.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `UploadResults` component.
 2. Click the "View Results" button.
- **Expected result:** A warning message "Please upload a results file first." is displayed.

6.2.6 Handles errors during ZIP file processing

- **Description:** Ensures errors during ZIP file processing are handled correctly and an error message is displayed to the user.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `UploadResults` component.
 2. Upload a ZIP file that cannot be processed.

- **Expected result:** An error message "Invalid ZIP file or corrupt JSON." is logged into the console.

6.2.7 Handles file drop event

- **Description:** Ensures the file drop event is handled correctly when a file is dropped on the component.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `UploadResults` component.
 2. Simulate a file drop event with a valid ZIP file.
- **Expected result:** The file is uploaded successfully.

6.3 Index (Landing Page) Component

6.3.1 Renders the component

- **Description:** Ensures the `Index` component renders correctly.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `Index` component.
 2. Check for the presence of specific text.
- **Expected result:** The component renders with the text "Verify Academic and Contest Submissions" and "Empower educators and contest administrators with advanced AI-powered plagiarism detection. Ensure the integrity of student work and competition submissions."

6.3.2 Displays loading spinner when loading

- **Description:** Ensures the loading spinner is displayed when the component is in the loading state.
- **Type:** Automatic, Functional
- **Initial state:** `isLoading` is true
- **Test case steps:**
 1. Mock the `useAuth0` hook to return `isLoading` as true.
 2. Render the `Index` component.
- **Expected result:** The text "Preparing your experience..." is displayed.

6.3.3 Calls `loginWithRedirect` when Get Started button is clicked

- **Description:** Ensures the `loginWithRedirect` function is called when the "Get Started" button is clicked.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `Index` component.
 2. Click the "Get Started" button.
- **Expected result:** The `loginWithRedirect` function is called.

6.3.4 Navigates to `/home` when authenticated

- **Description:** Ensures the user is redirected to the Home page when authenticated.
- **Type:** Automatic, Functional
- **Initial state:** None

- **Test case steps:**
 1. Mock the `useAuth0` hook to return `isAuthenticated` as `true`.
 2. Render the `Index` component.
- **Expected result:** The user is redirected to the `Home` page.

6.3.5 Displays features section

- **Description:** Ensures the features section is displayed on the `Index` component.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `Index` component.
- **Expected result:** The features section is displayed with the text "Why Choose SyntaxSentinals?" along with the features.

6.3.6 Displays how it works section

- **Description:** Ensures the "How It Works" section is displayed on the `Index` component.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `Index` component.
- **Expected result:** The "How It Works" section is displayed along with the steps.

6.3.7 Displays footer

- **Description:** Ensures the footer is displayed on the `Index` component.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `Index` component.
- **Expected result:** The footer is displayed with the text "SyntaxSentials" and the links.

6.4 Upload File Box Component

6.4.1 Renders the component

- **Description:** Ensures the `UploadFileBox` component renders correctly.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the `UploadFileBox` component.
- **Expected result:** The component renders with the text "Upload a ZIP file" and the file input.

6.4.2 Uploads a valid file

- **Description:** Ensures a valid file is uploaded using the `UploadFileBox` component.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**

1. Render the `UploadFileBox` component.
 2. Upload a valid ZIP file.
- **Expected result:** The file is uploaded successfully.

6.4.3 Removes a file

- **Description:** Ensures a file is removed using the `UploadFileBox` component.
- **Type:** Automatic, Functional
- **Initial state:** A file is uploaded
- **Test case steps:**
 1. Render the `UploadFileBox` component.
 2. Click the "Remove" button.
- **Expected result:** The file is removed.

6.4.4 Clears the file list when `clearFiles` is true

- **Description:** Ensures the file list is cleared when the `clearFiles` prop is true.
- **Type:** Automatic, Functional
- **Initial state:** A file is uploaded
- **Test case steps:**
 1. Render the `UploadFileBox` component with the `clearFiles` prop set to true.
- **Expected result:** The file list is cleared.

6.5 NavBar Component

6.5.1 Renders the component

- **Description:** Ensures the NavBar component renders correctly.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Render the NavBar component.
- **Expected result:** The component renders with the logo and navigation links.

6.5.2 Displays the login button when not authenticated

- **Description:** Ensures the login button is displayed when the user is not authenticated.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Mock the `useAuth0` hook to return `isAuthenticated` as false.
 2. Render the NavBar component.
- **Expected result:** The login button is displayed.

6.5.3 Displays the logout button when authenticated

- **Description:** Ensures the logout button is displayed when the user is authenticated.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**

1. Mock the `useAuth0` hook to return `isAuthenticated` as `true`.
 2. Render the `NavBar` component.
- **Expected result:** The logout button is displayed.

6.5.4 Calls `loginWithRedirect` when Log In button is clicked

- **Description:** Ensures the `loginWithRedirect` function is called when the "Log In" button is clicked.
- **Type:** Automatic, Functional
- **Initial state:** None
- **Test case steps:**
 1. Mock the `useAuth0` hook to return `isAuthenticated` as `false`.
 2. Render the `NavBar` component.
 3. Click the "Log In" button.
- **Expected result:** The `loginWithRedirect` function is called.

7 Changes Due to Testing

During the testing process, several issues were identified and addressed, leading to improvements in both functionality and reliability:

- **Upload File Handling**
 - An issue was detected in `UploadBox.tsx`, where files were not properly validated before being uploaded. Additional validation logic was added to prevent incorrect file types from being processed.
 - A missing error message for unsupported file types was implemented to improve user feedback.
- **Error Handling in File Processing**

- In `UploadResults.tsx`, tests revealed that errors during ZIP file processing were not handled gracefully. Additional error handling was introduced to catch and display meaningful error messages when invalid or corrupted ZIP files were uploaded.
- **Form Validation Enhancements**
 - The `AnalyzeFiles.tsx` component initially allowed form submission without an analysis name, causing backend errors. A required field check was added to prevent submissions without a name.
- **Test Coverage Improvements**
 - Some uncovered lines in `button.tsx` and `UploadBox.tsx` were identified through test coverage reports. Additional unit tests were written to cover these missing scenarios, increasing overall test coverage.
 - Server side code was not tested with a testing framework. This will be implemented in the future.
- **Emailing Results**
 - We noticed we had not yet implemented the feature where users are emailed after 10 minutes that their request is still processing. This feature will be implemented and tested in the future.
- **Cloud**
 - Cloud deployment is a future feature that will be implemented once the model is certified per priorities

8 Automated Testing

The tests mentioned in the **Unit Testing** section are automated using the Jest testing framework. The tests are run using the command `npm test`.

To ensure continuous integration and automated testing, we have set up a GitHub Actions workflow. The workflow is triggered on every push and pull request to the repository. It runs the tests on an Ubuntu environment with Node.js version 18.x.

8.1 Testing Workflow Configuration

The following is the configuration of the GitHub Actions workflow used for automated testing:

```
name: Run Frontend Tests

on: [push, pull_request]

jobs:
  test:
    runs-on: ubuntu-20.04

    strategy:
      matrix:
        node-version: [18.x]

    steps:
      - name: Checkout repository
        uses: actions/checkout@v4

      - name: Set up Node.js
        uses: actions/setup-node@v4
        with:
          node-version: ${ matrix.node-version }

      - name: Install dependencies
        run: npm install
        working-directory: ./src/frontend

      - name: Run tests
        run: npm test
        working-directory: ./src/frontend
```

8.2 Testing Workflow Steps

- **Checkout repository:** This step uses the `actions/checkout@v4` action to check out the repository code.

- **Set up Node.js:** This step uses the `actions/setup-node@v4` action to set up Node.js with the specified version (18.x).
- **Install dependencies:** This step runs `npm install` to install the necessary dependencies for the frontend.
- **Run tests:** This step runs `npm test` to execute the Jest tests for the frontend.

By using this automated testing workflow, we ensure that our code is continuously tested and validated, providing immediate feedback on any issues that may arise from changes in the codebase.

8.3 Test Coverage Workflow Configuration

In addition to running unit tests, we have configured a separate GitHub Actions workflow to generate a test coverage report using Jest. This helps us monitor the extent to which our code is covered by automated tests.

The following is the configuration for the test coverage workflow:

```
name: Run Frontend Unit Tests

on: [push, pull_request]

jobs:
  coverage:
    runs-on: ubuntu-20.04

    steps:
      - name: Checkout repository
        uses: actions/checkout@v3

      - name: Run Jest Coverage Report
        uses: ArtiomTr/jest-coverage-report-action@v2
        with:
          working-directory: ./src/frontend
          github-token: ${ secrets.GITHUB_TOKEN }
```


8.4 Test Coverage Workflow Steps

- **Checkout repository:** This step uses the `actions/checkout@v3` action to check out the repository code.
- **Run Jest Coverage Report:** This step uses the `ArtiomTr/jest-coverage-report-action@v2` action to generate a coverage report for the Jest tests in the frontend directory.

By incorporating test coverage reporting into our workflow, we can ensure that our automated tests provide sufficient coverage of the codebase, identifying untested areas and improving software reliability.

9 Trace to Requirements

Test ID	Requirements
test-FR-1	FR-1
test-FR-2	FR-2, FR-4, FR-5
test-FR-3	FR-3
test-FR-4	FR-6
test-FR-5	FR-7
test-FR-6	FR-7
test-FR-7	FR-8
test-FR-8	FR-8
test-FR-9	FR-9
test-FR-10	FR-10
test-LF-1	LF-AR1, LF-AR2, LF-AR3, LF-SR1, LF-SR2, LF-SR3, LF-SR4
test-LF-2	CR-SC3
test-UH-1	UH-E1, UH-E3, UH-L1, UH-UP1, UH-UP2, OE-P1
test-UH-2	UH-E2
test-UH-3	UH-PI2
test-V-1	MS-M1, OR-R2

Test ID	Requirements
test-PS-1	SR-P1
test-PS-2	SR-P2
test-PS-3	CR-L1, CR-L2, CR-L3, CR-S2, CR-S5
test-DS-1	MS-M3
test-DS-2	MS-S1, CR-SC1
test-D-1	UH-L2, OE-P2
test-PR-1	PR-SL1, PR-C1
test-PR-2	PR-SL2
test-PR-3	PR-SL2
test-PR-4	PR-RFT1
test-PR-5	PR-PA1, PR-PA2
test-PR-6	PR-SE1
test-OE-1	OE-IAS1
test-OE-2	OE-IAS2
test-OE-3	OE-IAS3
test-M-1	MS-M2
test-M-2	MS-S3
test-M-3	MS-A2
test-M-4	MS-A1
test-M-5	MS-A3
test-S-1	SR-A1
test-S-2	SR-A1
test-S-3	SR-A1

Table 3: Traceability Matrix

10 Trace to Modules

11 Code Coverage Metrics

The below report is for the frontend codebase of SyntaxSentinals. The backend has not been tested with a testing framework yet. Instead we ensure the backend is working as expected by manually testing the API endpoints using Postman and ensuring the server is sent the expected request via the frontend testing suite.

The test coverage report provides the following key metrics:

- **Statements:** 94.35% (234/248)
- **Branches:** 81.03% (47/58)
- **Functions:** 86.79% (46/53)
- **Lines:** 96.18% (227/236)

Below is a breakdown of coverage by individual files:

Directory	Statements	Branches	Functions	Lines
Features.tsx	100%	100%	100%	100%
Navbar.tsx	100%	100%	100%	100%
UploadBox.tsx	96.42%	84.21%	93.33%	98.14%
GetStarted.tsx	100%	100%	100%	100%
Home.tsx	90.32%	69.56%	73.91%	93.16%
Button.tsx	100%	66.66%	100%	100%
utils.ts	100%	100%	100%	100%
AnalyzeFiles.tsx	91.52%	75%	75%	94.54%
UploadResults.tsx	89.23%	63.63%	72.72%	91.93%

Table 4: Test Coverage Breakdown by Directory

Some uncovered lines include:

- **UploadBox.tsx**: Line 26.
- **button.tsx**: Line 44.
- **AnalyzeFiles.tsx**: Lines 22, 25, 76.
- **UploadResults.tsx**: Lines 20, 23, 50-51, 89.

These uncovered areas indicate potential gaps in test cases that should be addressed to achieve full coverage.

References

Appendix — Reflection

The information in this section will be used to evaluate the team members on the graduate attribute of Reflection.

The purpose of reflection questions is to give you a chance to assess your own learning and that of your group as a whole, and to find ways to improve in the future. Reflection is an important part of the learning process. Reflection is also an essential component of a successful software development process.

Reflections are most interesting and useful when they're honest, even if the stories they tell are imperfect. You will be marked based on your depth of thought and analysis, and not based on the content of the reflections themselves. Thus, for full marks we encourage you to answer openly and honestly and to avoid simply writing "what you think the evaluator wants to hear."

Please answer the following questions. Some questions can be answered on the team level, but where appropriate, each team member should write their own response:

1. What went well while writing this deliverable?
2. What pain points did you experience during this deliverable, and how did you resolve them?
3. Which parts of this document stemmed from speaking to your client(s) or a proxy (e.g. your peers)? Which ones were not, and why?
4. In what ways was the Verification and Validation (VnV) Plan different from the activities that were actually conducted for VnV? If there were differences, what changes required the modification in the plan? Why did these changes occur? Would you be able to anticipate these changes in future projects? If there weren't any differences, how was your team able to clearly predict a feasible amount of effort and the right tasks needed to build the evidence that demonstrates the required quality? (It is expected that most teams will have had to deviate from their original VnV Plan.)