

In this example is shown a usage of the database containing list of books. The database name is "MYTEST" and has following tables:

AUTHOR:

```
IDAUTHOR INTEGER NOT NULL GENERATED BY DEFAULT AS IDENTITY,  
AUTHOR VARCHAR(100) NOT NULL, PRIMARY KEY(IDAUTHOR), UNIQUE (AUTHOR)
```

TITLE:

```
IDTITLE INTEGER NOT NULL GENERATED BY DEFAULT AS IDENTITY,  
TITLE VARCHAR(100) NOT NULL, ISSUED INTEGER, ISBN VARCHAR(10) NOT NULL,  
PRIMARY KEY(IDTITLE), UNIQUE (TITLE, ISBN)
```

TITLE_AUTHOR:

```
IDTITLE_AUTHOR INTEGER NOT NULL GENERATED BY DEFAULT AS IDENTITY,  
IDAUTHOR INTEGER NOT NULL, IDTITLE INTEGER NOT NULL,  
PRIMARY KEY(IDTITLE_AUTHOR),  
UNIQUE (IDAUTHOR, IDTITLE),  
FOREIGN KEY (IDAUTHOR) REFERENCES MYTEST.AUTHOR(IDAUTHOR),  
FOREIGN KEY (IDTITLE) REFERENCES MYTEST.TITLE(IDTITLE)
```

1. Read data from database.

X-Definition (file DBRead.xdef):

```
<xd:def xmlns:xd="http://www.syntea.cz/xdef/3.1" xd:name="inventory" >  
  <xd:declaration>  
    external Service service;  
    Statement statement = service.prepareStatement(  
      "SELECT TITLE,ISBN FROM MYTEST.TITLE ORDER BY TITLE ASC");  
  </xd:declaration>  
  
  <Inventory xd:script="">  
    <Book xd:script="occurs *; create statement.query()" isbn="int()">  
      <Title> string();</Title>  
    </Book>  
  </Inventory>  
</xd:def>
```

The Java program (file DBRead.java):

```
import cz.syntea.common.xml.KXmlUtils;  
import cz.syntea.xd.XDDocument;  
import cz.syntea.xd.XDFactory;  
import cz.syntea.xd.XDPool;  
import org.w3c.dom.Element;  
  
/** Read data from database.*/  
public class DBRead {  
  
    public static void main(String[] args) {  
        //Generate XDPool  
        XDPool xp = XDFactory.genXDPool(System.getProperties(),"DBread.xdef");  
  
        // Create XDDocument  
        XDDocument xd = xp.createXDDocument();  
  
        // Create database connection as Service  
        String url = "jdbc:derby://localhost:1527/sample";  
        String user = "app";  
        String password = "app";  
        XDService service = XDFactory.createSQLService(url, user, password);  
        // Set external variable XDDocument  
        xd.setVariable("service", service); //set external variable to the X-definition  
  
        // Construct element from database  
        Element el = xd.xcreate(null, "Inventory", null); //invoke construction mode  
  
        // Print created XML data  
        System.out.println(KXmlUtils.nodeToString(el, true));  
    }  
}
```


2. Insert data

Input XML data (file DBInsert.xml):

```
<Books>
  <Book issued='2008' isbn='12345678' title='The Last Theorem'>
    <Author>Arthur C. Clarke</Author>
  </Book>
  <Book issued='1968' isbn='234567819' title='2001: A Space Odyssey'>
    <Author>Arthur C. Clarke</Author>
  </Book>
  <Book title='Bible' isbn='9345678199' />
  <Book issued='2007' isbn='8345678191' title='The X-definition 3.1'>
    <Author>Václav Trojan</Author>
    <Author>Jindřich Kocman</Author>
    <Author>Jiří Kamenický</Author>
  </Book>
  <Book title='Koran' isbn='9345478191' />
</Books>
```

The X-definition designed to insert the XML data to database (file DBInsert.xdef):

```
<xd:def xmlns:xd="http://www.syntea.cz/xdef/3.1" xd:root="Books|Book">
  <xd:declaration>
    external Service service;
    int inserted = 0;
    boolean ignored = false;
    Statement isAuthor = service.prepareStatement(
      "SELECT AUTHOR FROM MYTEST.AUTHOR WHERE MYTEST.AUTHOR.AUTHOR = ?");
    Statement isTitle = service.prepareStatement(
      "SELECT TITLE FROM MYTEST.TITLE WHERE MYTEST.TITLE.TITLE = ?");
    Statement insertAuthor = service.prepareStatement(
      "INSERT INTO MYTEST.AUTHOR(AUTHOR) VALUES (?)");
    Statement insertTitle = service.prepareStatement(
      "INSERT INTO MYTEST.TITLE(TITLE,ISBN,ISSUED) VALUES (?, ?, ?)");
    Statement insertTitleAuthor = service.prepareStatement(
      "INSERT INTO MYTEST.TITLE_AUTHOR(IDAUTHOR, IDTITLE)
        VALUES ((SELECT IDAUTHOR FROM MYTEST.AUTHOR WHERE AUTHOR=?),
          (SELECT IDTITLE FROM MYTEST.TITLE WHERE TITLE=?))");
  </xd:declaration>
<Books>
  <Book xd:script="*";
    onStartElement {
      if (ignored = isTitle.hasItem(toString(@title))) {
        error('Book \'' + @title + '\'' already exists');
      } else {
        insertTitle.execute(toString(@title), toString(@isbn), toString(@issued));
        inserted++;
      }
    };
    title="string"
    isbn="regex('\\d{8,10}')"
    issued="optional gYear()"
    <Author xd:script="occurs *">
      optional string;
      finally if (!ignored) {
        String s = getText();
        if (!isAuthor.hasItem(s)) {
          insertAuthor.execute(s); /*new author*/
        }
        insertTitleAuthor.execute(s, xpath("../@title").toString());
      }
    </Author>
  </Book>
</Books>

</xd:def>
```

The Java program (file DBInsert.java):

```
import cz.syntea.common.sys.ArrayReporter;
import cz.syntea.xd.XDDocument;
import cz.syntea.xd.XDFactory;
import cz.syntea.xd.XDPool;
import cz.syntea.xd.XDService;

/** Insert books to database (explicite statements). */
public class DBInsert {

    public static void main(String[] args) {

        // Generate XDPool
        XDPool xp = XDFactory.genXDPool(System.getProperties(), "DBInsert.xdef");

        // Create XDDocument
        XDDocument xd = xp.createXDDocument();

        // Create database connection as Service
        String url = "jdbc:derby://localhost:1527/sample;";
        String user = "app";
        String password = "app";
        XDService service = XDFactory.createSQLService(url, user, password);

        // Set external variable with database connection to XDDocument
        xd.setVariable("service", service); //set external variable to the X-definition

        // Execute processing of XML data with XDefinition
        ArrayReporter reporter = new ArrayReporter(); //prepare reporter
        xd.xparse("ExampleDBInsert.xml", reporter); //process data
        //close database connection
        service.close();

        // Get number of inserted books from XDDocument
        int num = xd.getVariable("inserted").intValue();
        // Print number of inserted books
        System.out.println("Inserted " + num + " books");
        if (reporter.errors()) {
            reporter.printReports(System.err);
        }
    }
}
```