

VISHNU User Manual



Copyright © 2011 SysFera SAS

These manual pages are provided under the following conditions:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

This software is governed by the CECILL licence under French law and abiding by the rules of distribution of free software. You can use, modify and/ or redistribute the software under the terms of the CeCILL license as circulated by CEA, CNRS and INRIA at the following URL "<http://www.cecill.info>".

As a counterpart to the access to the source code and rights to copy, modify and redistribute granted by the license, users are provided only with a limited warranty and the software's author, the holder of the economic rights, and the successive licensors have only limited liability.

In this respect, the user's attention is drawn to the risks associated with loading, using, modifying and/or developing or reproducing the software by the user in light of its specific status of free software, that may mean that it is complicated to manipulate, and that also therefore means that it is reserved for developers and experienced professionals having in-depth computer knowledge. Users are therefore encouraged to load and test the software's suitability as regards their requirements in conditions enabling the security of their systems and/or data to be ensured and, more generally, to use and operate it in the same conditions as regards security.

COLLABORATORS

	<i>TITLE :</i> VISHNU User Manual		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY	Benjamin Isnard, Daouda Traoré, Eugène Pamba Capo-Chichi, Kevin Coulomb, and Ibrahima Cissé	March 8, 2011	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME
1	08/03/2011	First version of the VISHNU user manual which concerns only the UMS package.	SysFera
2	03/05/2011	Added details concerning the TMS package.	SysFera
3	15/06/2011	Added details concerning the IMS and FMS package.	SysFera
4	28/06/2011	Added TMS generic script example.	SysFera
5	18/07/2011	Add the CLI examples and fix some mistakes..	SysFera
6	11/08/2011	Added SLURM batch scheduler	SysFera

Contents

1	Document presentation	1
1.1	Document objectives	1
1.2	Document structure	1
1.3	References	1
2	Installation and usage	2
2.1	Installation procedure of the clients	2
2.1.1	From sources	3
2.1.2	From binaries package	3
2.2	Software usage description	3
2.2.1	UMS package	3
2.2.1.1	User account creation	3
2.2.1.2	Connection to VISHNU	4
2.2.1.3	Reconnection to VISHNU	4
2.2.1.4	Session management in VISHNU	4
2.2.1.4.1	Session close on timeout	4
2.2.1.4.2	Session close on disconnect	4
2.2.1.5	Local user configuration management	4
2.2.1.5.1	Local user configuration creation	4
2.2.1.5.2	Local user configuration update	4
2.2.1.5.3	Local user configuration remove	5
2.2.2	TMS package	5
2.2.2.1	Job submission	5
2.2.2.1.1	VISHNU generic script	5
2.2.2.2	Job Cancellation	6
2.2.2.3	Job output files	6
2.2.3	FMS package	6
2.2.3.1	Create and remove file or directories	6
2.2.3.2	Get file information	6
2.2.3.3	Modify files properties	6

2.2.3.4	Perform file transfer	6
2.2.4	IMS package	7
2.2.4.1	Export of commands	7
2.2.4.2	Get system information	7
2.2.4.3	Get the metric	7
2.2.5	Troubleshooting functions	7
3	UMS Command reference	8
3.1	vishnu_connect	8
3.2	vishnu_reconnect	9
3.3	vishnu_close	10
3.4	vishnu_change_password	10
3.5	vishnu_add_local_account	11
3.6	vishnu_update_local_account	12
3.7	vishnu_delete_local_account	13
3.8	vishnu_list_local_accounts	13
3.9	vishnu_list_machines	14
3.10	vishnu_list_history_cmd	15
3.11	vishnu_list_options	16
3.12	vishnu_list_sessions	17
3.13	vishnu_configure_option	18
4	TMS Command reference	19
4.1	vishnu_submit_job	19
4.2	vishnu_get_job_info	20
4.3	vishnu_get_job_progress	21
4.4	vishnu_list_queues	21
4.5	vishnu_list_jobs	22
4.6	vishnu_get_job_output	23
4.7	vishnu_get_completed_jobs_output	24
4.8	vishnu_cancel_job	24
5	FMS Command reference	26
5.1	vishnu_create_file	26
5.2	vishnu_create_dir	27
5.3	vishnu_remove_file	28
5.4	vishnu_remove_dir	28
5.5	vishnu_ch_grp	29
5.6	vishnu_ch_mod	30
5.7	vishnu_head_of_file	31

5.8	vishnu_tail_of_file	32
5.9	vishnu_content_of_file	33
5.10	vishnu_list_dir	34
5.11	vishnu_copy_file	35
5.12	vishnu_copy_async_file	36
5.13	vishnu_move_file	37
5.14	vishnu_move_async_file	38
5.15	vishnu_stop_file_transfer	39
5.16	vishnu_list_file_transfers	40
5.17	vishnu_get_file_info	41
6	IMS Command reference	43
6.1	vishnu_export_commands	43
6.2	vishnu_get_metric_current_value	44
6.3	vishnu_get_metric_history	44
6.4	vishnu_get_update_frequency	45
6.5	vishnu_get_system_info	46
7	UMS C++ API Reference	47
7.1	connect	47
7.2	reconnect	48
7.3	close	49
7.4	changePassword	49
7.5	addLocalAccount	50
7.6	updateLocalAccount	51
7.7	deleteLocalAccount	52
7.8	listLocalAccounts	53
7.9	listMachines	54
7.10	listHistoryCmd	55
7.11	listOptions	55
7.12	listSessions	56
7.13	configureOption	57
7.14	vishnuInitialize	58
7.15	vishnuFinalize	58
8	TMS C++ API Reference	60
8.1	submitJob	60
8.2	getJobInfo	61
8.3	getJobProgress	62
8.4	listQueues	62
8.5	listJobs	63
8.6	getJobOutput	64
8.7	getCompletedJobsOutput	65
8.8	cancelJob	66

9 FMS C++ API Reference	68
9.1 createFile	68
9.2 createDir	69
9.3 removeFile	70
9.4 removeDir	70
9.5 chGrp	71
9.6 chMod	72
9.7 headOfFile	73
9.8 tailOfFile	74
9.9 contentOfFile	75
9.10 listDir	76
9.11 copyFile	77
9.12 copyAsyncFile	78
9.13 moveFile	79
9.14 moveAsyncFile	80
9.15 stopFileTransfer	81
9.16 listFileTransfers	82
9.17 getFileInfo	83
10 IMS C++ API Reference	85
10.1 exportCommands	85
10.2 getMetricCurrentValue	86
10.3 getMetricHistory	86
10.4 getUpdateFrequency	87
10.5 getSystemInfo	88
11 UMS Python API Reference	89
11.1 VISHNU_UMS.connect	89
11.2 VISHNU_UMS.reconnect	90
11.3 VISHNU_UMS.close	91
11.4 VISHNU_UMS.changePassword	92
11.5 VISHNU_UMS.addLocalAccount	93
11.6 VISHNU_UMS.updateLocalAccount	94
11.7 VISHNU_UMS.deleteLocalAccount	95
11.8 VISHNU_UMS.listLocalAccounts	96
11.9 VISHNU_UMS.listMachines	97
11.10 VISHNU_UMS.listHistoryCmd	98
11.11 VISHNU_UMS.listOptions	99
11.12 VISHNU_UMS.listSessions	100
11.13 VISHNU_UMS.configureOption	101
11.14 VISHNU_UMS.vishnuInitialize	102
11.15 VISHNU_UMS.vishnuFinalize	103

12 TMS Python API Reference	104
12.1 VISHNU_UMS.submitJob	104
12.2 VISHNU_UMS.getJobInfo	105
12.3 VISHNU_UMS.getJobProgress	106
12.4 VISHNU_UMS.listQueues	107
12.5 VISHNU_UMS.listJobs	108
12.6 VISHNU_UMS.getJobOutput	109
12.7 VISHNU_UMS.getCompletedJobsOutput	110
12.8 VISHNU_UMS.cancelJob	111
13 FMS Python API Reference	113
13.1 VISHNU_UMS.createFile	113
13.2 VISHNU_UMS.createDir	114
13.3 VISHNU_UMS.removeFile	115
13.4 VISHNU_UMS.removeDir	116
13.5 VISHNU_UMS.chGrp	117
13.6 VISHNU_UMS.chMod	118
13.7 VISHNU_UMS.headOfFile	119
13.8 VISHNU_UMS.tailOfFile	120
13.9 VISHNU_UMS.contentOfFile	121
13.10 VISHNU_UMS.listDir	122
13.11 VISHNU_UMS.copyFile	123
13.12 VISHNU_UMS.copyAsyncFile	124
13.13 VISHNU_UMS.moveFile	125
13.14 VISHNU_UMS.moveAsyncFile	126
13.15 VISHNU_UMS.stopFileTransfer	128
13.16 VISHNU_UMS.listFilesTransfers	129
13.17 VISHNU_UMS.getFileInfo	130
14 IMS Python API Reference	131
14.1 VISHNU_UMS.exportCommands	131
14.2 VISHNU_UMS.getMetricCurrentValue	132
14.3 VISHNU_UMS.getMetricHistory	133
14.4 VISHNU_UMS.getUpdateFrequency	133
14.5 VISHNU_UMS.getSystemInfo	134

Chapter 1

Document presentation

1.1 Document objectives

This documents is a quick start guide of VISHNU software for users. The main objective of this document is to describe the VISHNU installation procedure and the way to use it.

1.2 Document structure

- Chapter 1 presents the document structure.
- Chapter 2 describes the VISHNU software (installation procedure, usage description and troubleshooting).
- Chapter 3, Chapter 4, Chapter 5 and Chapter 6 contain the VISHNU commands reference respectively for UMS, TMS, FMS and IMS package.
- Chapter 7, Chapter 8, Chapter 9 and Chapter 10 contain the C++ API reference respectively for UMS, TMS, FMS and IMS package.
- Chapter 11, Chapter 12, Chapter 13 and Chapter 14 contain the Python API reference respectively for UMS, TMS, FMS and IMS package.

1.3 References

- [D1.1b]: VISHNU "Spécifications techniques des besoins"
 - [DIETMAN]: DIET User's Manual v2.7 (available with the DIET distribution at <http://graal.ens-lyon.fr/~diet>)
-

Chapter 2

Installation and usage

The VISHNU software is based on SysFera-DS which is an open-source middleware developed by SysFera. VISHNU is primarily designed to facilitate the access to high-performance computing resources by providing the following services:

- User management services (UMS): authentication and session management.
- Information management services (IMS): monitoring and control services.
- Tasks management services (TMS): submission of tasks (jobs) on computing resources.
- File management services (FMS): display and transfer of files between storage resources.

2.1 Installation procedure of the clients

This section details the main steps of the installation process for the clients, including the installation requirements [D1.1b]. VISHNU is based on SysFera-DS software which must be installed before.

Installation requirements:

- GCC V4.4.3
- CMAKE V2.6
- OMNIORB 4.1.4
- SYSFERA-DS V2.7 (available at: <http://graal.ens-lyon.fr/DIET/>)
- BOOST V1.45
- PYTHON V2.5
- JAVA V1.6
- SWIG V1.3
- LIBCRYPT

Installation procedure:

2.1.1 From sources

- Download the VISHNU install sources
 - Decompress it and go to the vishnu directory
 - Create a build directory and run CMake as follows:
 - > mkdir build
 - > cd build
- If your install directory is for example: /opt/vishnu
- > cmake -DCLIENT_ONLY=ON -DCMAKE_INSTALL_PREFIX=/opt/vishnu ..
 - > make && make install
- The module for each client can be built using the '-DCOMPILER_*MS=ON' flag. These are some command line examples on how to build the clients
 - **To compile the UMS package :**
 - > cmake -DCOMPILER_UMS=ON -DCMAKE_INSTALL_PREFIX=/opt/vishnu ..
 - **To compile the TMS package :**
 - > cmake -DCOMPILER_UMS=ON -DCOMPILER_TMS=ON -DCMAKE_INSTALL_PREFIX=/opt/vishnu ..
 - **To compile the FMS package :**
 - > cmake -DCOMPILER_UMS=ON -DCOMPILER_FMS=ON -DCMAKE_INSTALL_PREFIX=/opt/vishnu ..
 - **To compile the IMS package :**
 - > cmake -DCOMPILER_UMS=ON -DCOMPILER_TMS=ON -DCOMPILER_FMS=ON -DCOMPILER_IMS=ON -DCMAKE_INSTALL_PREFIX=/opt/vishnu ..

2.1.2 From binaries package

Assuming the dependencies are installed (omniorb, diet, boost). Download the vishnu-client_*_i386.deb, where * stands for the VISHNU version and install it (dpkg -i vishnu-client_*_i386.deb). Then, if the DIET hierarchy is already running and accessible from the client, one can use VISHNU. All the services are available in the debian packages.

2.2 Software usage description

VISHNU is composed of 4 main packages, one that deals with the users and the machine (UMS), one that deals with the batch schedulers (TMS), one that deals with the files management (FMS) and one that handles the information of the system (IMS). These clients can be installed altogether or just one or two. Please contact your VISHNU admin to know the corresponding servers you can have before installing the client. It is important to note that the client can be installed without the server being on the platform, the call will end up with an exception and the message "Vishnu not available". Below each package will be described to show the services it offers to the user.

WARNING: The lists are INOUT parameters, the results are appended, they do not overwrite the existing list. Moreover, the get function on the lists does not check the bounds, it is like using the [] operator.

2.2.1 UMS package

2.2.1.1 User account creation

The first step to access VISHNU is to request a new account to a VISHNU administrator. The only information required to create a new account is your full name and email address. You will automatically receive an email containing your userId and password.

2.2.1.2 Connection to VISHNU

To connect, use the **vishnu_connect** command in the shell terminal (all bourne shell are supported). The password received by email is temporary and must be changed at the first connection by using the **vishnu_change_password** command.

2.2.1.3 Reconnection to VISHNU

Reconnection is done using the **vishnu_reconnect** command. This command allows using an existing session that was previously opened but not closed. It makes it possible to simultaneously use the same session in different shell terminals. A session is what authenticates a user once he has connected. The user does not need password or username when authenticated to use vishnu. Moreover, the session contains the commands made by a user, so he can retrieve the sequence of commands made in a previous work session.

2.2.1.4 Session management in VISHNU

After a successful call to the **vishnu_connect** command, a session is created. The session is required for calling any other commands. It avoids systematic authentication by userId and password. Only commands **vishnu_connect**, **vishnu_reconnect** and **vishnu_change_password** can be used outside a session by using userId and password. The **vishnu_list_history_cmd** command lists all the commands launched within a session.

To prevent unclosed sessions when the **vishnu_close** command is not used, the session is automatically closed on timeout or on disconnect (from the terminal).

2.2.1.4.1 Session close on timeout

In this mode, the session is automatically closed after an inactivity delay specified by the system or configured by the user using the **vishnu_configure_option** command.

2.2.1.4.2 Session close on disconnect

In this mode, the session is automatically closed when the shell terminal is closed. It is important to note that the system makes it impossible to close a session while commands are running. In this case, a session with automatic close on disconnect changes the close mode to automatic close on timeout.

2.2.1.5 Local user configuration management

2.2.1.5.1 Local user configuration creation

To access a UNIX account on a specific machine defined on VISHNU, the user must create a local user configuration by using the **vishnu_add_local_account** command. The **vishnu_list_machines** command gives information about the machines in which a local user configuration can be created or where a local user configuration has already been created. The information required to create a new local user configuration is: the userId, the machineId, the login of the UNIX account on the specified machine, the absolute path to the user's private SSH key (used for file transfers) and the home directory path.

The ssh public key of the machine named "*userId-machineId*" is returned and stored in the `$HOME/.vishnu/localAccountPublicKey/` directory and must be added by the user in the ssh authorized key directory of the UNIX account. Doing this allows VISHNU to be directly connected on this UNIX account, running tasks as if it was the owner of the UNIX account.

2.2.1.5.2 Local user configuration update

All previous parameters used to create a local user configuration can be updated by using the **vishnu_update_local_account** command except for userId and machineId.

2.2.1.5.3 Local user configuration remove

A local user configuration can be removed by using the **vishnu_delete_local_account** command.

It is possible to display the local user configurations with the **vishnu_list_local_account** command. Other commands which are not cited above can be used to display information, such as the **vishnu_list_options** command, which displays all the options configured by the user, or the **vishnu_list_sessions** command, which displays information about the sessions.

2.2.2 TMS package

2.2.2.1 Job submission

To submit a job, via VISHNU, to the batch scheduler of a specific machine, the user needs: an active VISHNU session, a local user configuration registered on VISHNU that corresponds to an existing UNIX account on the specified machine and a script that describes the job to submit. In the current implementation of VISHNU, it is possible to use the directives for two batch schedulers: TORQUE, LoadLeveler and SLURM. In order to use the same script on different batch schedulers, a generic script with generic VISHNU directives is used. The **vishnu_submit_job** command allows a user to submit a job in the shell terminal. To obtain information on a job, the user can use the **vishnu_get_job_info** or **vishnu_list_jobs**, and for a job's progression status, the **vishnu_get_job_progression** command is used. The job's progression status is calculated according to the wall-clock time specified by the user during the job's submission.

2.2.2.1.1 VISHNU generic script

The key words of a VISHNU generic script start with the special character **##**. For example, to specify a job's name, users have to use the following directive in their scripts: **## vishnu_job_name**. The possible generic directives are:

- **## vishnu_group**: specifies the group's name,
- **## vishnu_job_name**: specifies the job's name,
- **## vishnu_output**: specifies the path of the job's output file,
- **## vishnu_error**: specifies the path of the file containing the problems that occurred during the job's execution,
- **## vishnu_wallclocklimit**: specifies the estimated time for the job's execution,
- **## vishnu_notify_user**: specifies the mail address of the job's owner in order to receive a notification when the job is completed,
- **## vishnu_queue**: specifies the queue where the job will be submitted. It is possible to obtain a list of the batch scheduler's queues by using the **vishnu_list_queues** command.

It is important to note that the user can also add directives specific to a batch scheduler (TORQUE, LoadLeveler or SLURM). Such specific directives must be added directly after the generic directives. Here is an example:

```
#!/bin/sh
## vishnu_job_name=first_job
## vishnu_queue=first_queue
## vishnu_output=/path/to/jobOutput
## vishnu_error=/path/to/jobError
## vishnu_wallclocklimit=2:40:5
#This line is a comment
#The following lines are TORQUE specific section
#PBS -l ncpus=1
#PBS -l mem=50
#The following lines are LOADLEVELER specific section
#@ notify_user=user@mail
#@ cpu_limit=2
#The following lines are SLURM specific section
```

```
#SBATCH -J myFristJob
#SBATCH -o myJob-%j.out
#SBATCH -e myJob-%j.err
#SBATCH -t 01:02:20
#SBATCH -p myFavoritePartition
```

2.2.2.2 Job Cancellation

To cancel a job, the **vishnu_cancel_job** command is used with the VISHNU identifier of the job to cancel. When the identifier of the job is *all*, all of the user's jobs are cancelled. An admin can also cancel all the jobs of all the users of VISHNU.

2.2.2.3 Job output files

VISHNU offers two commands, to be used in a shell terminal, to get the result output files for a job:

- **vishnu_get_job_output** or,
- **vishnu_get_completed_jobs_output**

The former gives the output files for a specific job while the latter gives the output files for all the completed jobs. It is important to note that all submitted jobs have two output files: one with the job's results, one (possibly empty) with the errors that occurred during the job's execution. The path of the job's output files is specified during the job's submission.

2.2.3 FMS package

2.2.3.1 Create and remove file or directories

The user can create (or remove) a regular file located in a remote host by using the command **vishnu_create_file** (or **vishnu_remove_file**). He can also create (or remove) directory located in a remote host by using the command **vishnu_create_dir** (or **vishnu_remove_dir**).

2.2.3.2 Get file information

Several services are available to get file information. The user can get the first (or last lines) of a given remote file by using the command **vishnu_head_of_file** (or **vishnu_tail_of_file**). He can also get the entire content of a remote file (or remote directory) with the command **vishnu_content_of_file** (or **vishnu_list_dir**).

2.2.3.3 Modify files properties

The commands **vishnu_ch_grp** and **vishnu_ch_mod** allow the user to change respectively the group and the access permissions of remote file.

2.2.3.4 Perform file transfer

The user can submit a file transfer in many ways:

- copy (or move) file between two hosts by the commands **vishnu_copy_file** (or **vishnu_move_file**)
- copy (or move) file between two hosts in asynchronous way by the commands **vishnu_copy_async_file** (or **vishnu_move_async_file**)
- list or (cancel) file transfers by the commands **vishnu_list_file_transfers** (**vishnu_stop_file_transfers**)

2.2.4 IMS package

2.2.4.1 Export of commands

The user can export the commands made during a session in shell format. The file must have been created before the call, the file will contain a shell script that can be executed. For safety reasons, the connect and change password cannot be in the file. Thus, to execute the shell script, the connect command must be added after the first line of the file that declares the shell format.

2.2.4.2 Get system information

The get system information is to get information about a machine of the system. It can give information about the memory and/or disk space available on the machine.

2.2.4.3 Get the metric

The user can get the current metrics on a machine or the history of the metrics on a machine to know the evolution of the metric. The user can choose to get the metrics of a specific type (parameters are 1, 2, 3 respectively free CPUload, free disk space and free memory). Note, when getting the history of metrics, by default, only the first 1000 results are gotten. This is to avoid having too much results with a single command (the metric table may be filled very fast).

2.2.5 Troubleshooting functions

The *"There is no session in this terminal"* error can be solved by connecting to VISHNU using the **vishnu_connect** command.

Chapter 3

UMS Command reference

3.1 vishnu_connect

vishnu_connect — opens a session

Synopsis

```
vishnu_connect [-h] [-p closePolicy] [-d sessionInactivityDelay] [-s substituteUserId] userId
```

DESCRIPTION

Opening a VISHNU session is the first step before using any other VISHNU command. This command authenticates you. You must have been registered in the VISHNU system by an administrator. It also creates a session that remains open after the command is completed and until the session is either manually or automatically closed.

OPTIONS

-h *help* help about the command.

-p *closePolicy* is an option for closing session automatically. The value must be an integer. Predefined values are: 0 (UNDEFINED), 1 (CLOSE_ON_TIMEOUT), 2 (CLOSE_ON_DISCONNECT).

-d *sessionInactivityDelay* is the maximum delay in seconds between two user requests when the CLOSE_ON_TIMEOUT policy is set.

-s *substituteUserId* is an admin option which allows an admin to open a session as if she was another user identified by her *userId*.

ENVIRONMENT

VISHNU_CLOSE_POLICY The value of this environment variable represents the session close policy. Overridden by the **-p** option.

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"The user is unknown or the password is wrong" [20]

"The userId is unknown" [21]

"The user is locked" [23]

"The user is not an administrator" [25]

"The closure policy is unknown" [42]

"The value of the timeout is incorrect" [43]

3.2 vishnu_reconnect

`vishnu_reconnect` — reconnects to a session that is still active

Synopsis

```
vishnu_reconnect [-h] userId sessionId
```

DESCRIPTION

This command allows you to resume a session that has been opened previously and that has not yet been closed. You can disconnect from a session without closing it (for example if there are running commands in that session) by setting the session's close policy (at connection time) to `CLOSE_ON_TIMEOUT`. As sessions are linked to a specific client system, you cannot reconnect to a session that was opened on another client system.

OPTIONS

`-h help` help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"The user is unknown or the password is wrong" [20]

"The user is locked" [23]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The session Id is unknown" [30]

"The machine does not exist or it is locked" [36]

3.3 vishnu_close

vishnu_close — closes the session

Synopsis

```
vishnu_close [-h]
```

DESCRIPTION

This command closes the session that is currently active in the terminal. It will return an error if there are still some active requests that were been submitted by the user during the session (e.g., job submission or file transfers). After the session is closed, it cannot be re-opened.

OPTIONS

-h *help* help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"There is no open session in this terminal" [10]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"Commands are running" [31]

3.4 vishnu_change_password

vishnu_change_password — changes the password

Synopsis

```
vishnu_change_password [-h] userId
```

DESCRIPTION

This command is used to change the password. It can be done voluntarily or when the password is only temporary: for your first connection to VISHNU or after your password is reset by an administrator .

OPTIONS

-h *help* help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"The user is unknown or the password is wrong" [20]

"The user is locked" [23]

3.5 vishnu_add_local_account

`vishnu_add_local_account` — adds a new local user configuration

Synopsis

`vishnu_add_local_account [-h] userId machineId acLogin sshKeyPath homeDirectory`

DESCRIPTION

A local user configuration must be added to allow you (identified by `userId`) to connect to machine (identified by `machineId`). This configuration must match an existing system account on that machine with a login that matches `acLogin`. The parameters `sshKeyPath` parameter (the absolute path to your private SSH key, used for file transfers) must be provided as well as the `homeDirectory` path .

OPTIONS

-h *help* help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"There is no open session in this terminal" [10]

"The userId is unknown" [21]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The machine is locked" [34]

"The machine does not exist or it is locked" [36]

"The local account already exists" [37]

"The system account login is already used by another vishnu user" [46]

3.6 vishnu_update_local_account

vishnu_update_local_account — updates a local user configuration

Synopsis

```
vishnu_update_local_account [-h] [-l acLogin] [-s sshKeyPath] [-d homeDirectory] userId machineId
```

DESCRIPTION

The local user configuration can be updated. You can modify information of its local configuration such as *acLogin*, *sshKeyPath* or *homeDirectory*.

OPTIONS

-h *help* help about the command.

-l *acLogin* *acLogin* represents the login of the user on the associated machine.

-s *sshKeyPath* *sshKeyPath* is the path of the ssh key of the user on the associated machine.

-d *homeDirectory* *HomeDirectory* is the path of the home directory of the user on the associated machine.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"There is no open session in this terminal" [10]

"The userId is unknown" [21]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local is unknown" [38]

"The system account login is already used by another vishnu user" [46]

3.7 vishnu_delete_local_account

`vishnu_delete_local_account` — removes a local user configuration (for a given user on a given machine) from VISHNU

Synopsis

```
vishnu_delete_local_account [-h] userId machineId
```

DESCRIPTION

The local user configuration can be deleted from VISHNU. When a local user configuration is deleted, all the information about it is deleted from VISHNU.

OPTIONS

`-h help` help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"There is no open session in this terminal" [10]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The local is unknown" [38]

3.8 vishnu_list_local_accounts

`vishnu_list_local_accounts` — lists the local user configurations

Synopsis

```
vishnu_list_local_accounts [-h] [-a] [-u userId] [-i machineId]
```

DESCRIPTION

A local configuration is used to configure the access to a given system for a given user through VISHNU. It is related to an account on that system that is identified using its login. This command allows you to check all the local configurations related to your VISHNU account.

OPTIONS

- h** *help* help about the command.
- a** *adminListOption* is an admin option for listing all local configurations of all users .
- u** *userId* is an admin option for listing the local configurations of a specific user .
- i** *machineId* is an option for listing local user configurations on a specific machine.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

- "There is no open session in this terminal" [10]
- "The userId is unknown" [21]
- "The session key is unrecognized" [28]
- "The sessionKey is expired. The session is closed." [29]

3.9 vishnu_list_machines

vishnu_list_machines — lists the machines that are accessible through VISHNU

Synopsis

```
vishnu_list_machines [-h] [-u userId] [-a] [-m machineId]
```

DESCRIPTION

This command is used to display the machines that you can use for VISHNU services. The machines you can access through VISHNU are those that are configured in VISHNU by the VISHNU administrator, and that have been added to your personal VISHNU configuration using the **vishnu_add_local_account** command. The results contain, for each machine, a machine identifier that you can use as a parameter for other VISHNU commands.

OPTIONS

- h** *help* help about the command.
 - u** *userId* is an admin option for listing machines in which a specific user has a local configuration.
 - a** *listAllmachine* is an option for listing all VISHNU machines.
 - m** *machineId* is an option for listing information about a specific machine.
-

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"There is no open session in this terminal" [10]

"The userId is unknown" [21]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

3.10 vishnu_list_history_cmd

`vishnu_list_history_cmd` — lists the commands

Synopsis

```
vishnu_list_history_cmd [-h] [-a] [-u userId] [-i sessionId] [-s startDateOption] [-e endDateOption]
```

DESCRIPTION

This command displays a history of the commands you ran. Several options can be used to specify which commands to list.

OPTIONS

-h *help* help about the command.

-a *adminListOption* is an admin option for listing all commands of all users.

-u *userId* is an admin option for listing commands launched by a specific user identified by his/her *userId*.

-i *sessionId* lists all commands launched within a specific session.

-s *startDateOption* allows the user to organize the commands listed by providing the start date (the UNIX timestamp of the start date is used).

-e *endDateOption* allows the user to organize the commands listed by providing the end date (the timestamp of the end date is used). By default, the end date is the current day.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"There is no open session in this terminal" [10]

"The userId is unknown" [21]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

3.11 vishnu_list_options

vishnu_list_options — lists the options of the user

Synopsis

```
vishnu_list_options [-h] [-a] [-u userId] [-n optionName]
```

DESCRIPTION

This command displays the options you configured.

OPTIONS

-h *help* help about the command.

-a *listAllDefValue* is an option for listing all default option values defined by VISHNU administrator.

-u *userId* is an admin option for listing the options of a specific user.

-n *optionName* allows the user to get the value of a specific option identified by its name .

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"There is no open session in this terminal" [10]

"The userId is unknown" [21]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The name of the user option is unknown" [41]

3.12 vishnu_list_sessions

vishnu_list_sessions — lists all sessions of the user

Synopsis

```
vishnu_list_sessions [-h] [-t status] [-p sessionClosePolicy] [-d sessionInactivityDelay] [-m machineId] [-a] [-u userId] [-i sessionId] [-s startDateOption] [-e endDateOption]
```

DESCRIPTION

This command is used to display and filter the list of all your sessions. For each session, a session identifier is provided which you can use to reconnect to a given session using the vishnu_reconnect command. The session's status is either 0 (inactive) or 1 (active).

OPTIONS

- h help** help about the command.
- t status** specifies the status of the sessions which will be listed. The value must be an integer. Predefined values are: 0 (INACTIVE), 1 (ACTIVE).
- p sessionClosePolicy** specifies the closure mode of the sessions which will be listed (CLOSE_ON_TIMEOUT or CLOSE_ON_DISCONNECT). The value must be an integer. Predefined values are: 0 (UNDEFINED), 1 (CLOSE_ON_TIMEOUT), 2 (CLOSE_ON_DISCONNECT).
- d sessionInactivityDelay** specifies the inactivity delay in seconds of the sessions which will be listed.
- m machineId** allows the user to list sessions opened on a specific machine.
- a adminListOption** is an admin option for listing all sessions of all users.
- u userId** is an admin option for listing sessions opened by a specific user.
- i sessionId** allows the user to list all commands launched within a specific session.
- s startDateOption** allows the user to organize the commands listed by providing the start date (the UNIX timestamp of the start date is used).
- e endDateOption** allows the user to organize the commands listed by providing the end date (the timestamp of the end date is used). By default, the end date is the current day.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"There is no open session in this terminal" [10]

"The userId is unknown" [21]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The closure policy is unknown" [42]

3.13 vishnu_configure_option

vishnu_configure_option — configures an option of the user

Synopsis

```
vishnu_configure_option [-h] optionName value
```

DESCRIPTION

Options in VISHNU corresponds to the parameters of some VISHNU commands (e.g., the close policy for vishnu_connect) that can be preset in the user configuration stored by the VISHNU system. This command is used to set the value of an option for the current user (the user who opened the session).

OPTIONS

-h *help* help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"There is no open session in this terminal" [10]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The name of the user option is unknown" [41]

"The closure policy is unknown" [42]

"The value of the timeout is incorrect" [43]

"The value of the transfer command is incorrect" [44]

Chapter 4

TMS Command reference

4.1 vishnu_submit_job

`vishnu_submit_job` — submits a job on a machine through the use of a script (`scriptFilePath`)

Synopsis

```
vishnu_submit_job [-h] [-n name] [-q queue] [-t wallTime] [-m memory] [-P nbCpu] [-N nbNodesAndCpuPerNode] [-o outputPath] [-e errorPath] machineId scriptFilePath
```

DESCRIPTION

This command is used to submit a job to the specific batch scheduler associated to a machine. It allows describing a job in a script, using either the batch scheduler's directives or VISHNU's generic directives for all batch schedulers.

OPTIONS

- `-h help` help about the command.
- `-n name` Assigns a job name. The default is the path of job.
- `-q queue` Assigns the queue or class of the job.
- `-t wallTime` The maximum wall-clock time during which the job can run.
- `-m memory` Is the memory size that the job requires.
- `-P nbCpu` The number of cpu that the job requires.
- `-N nbNodesAndCpuPerNode` The number of nodes and processors per node.
- `-o outputPath` Assigns the path and file for job output.
- `-e errorPath` Assigns the path and file for job error.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (SSH error)" [9]

"Error invalid parameters" [10]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

4.2 vishnu_get_job_info

`vishnu_get_job_info` — gets information on a job from its id

Synopsis

```
vishnu_get_job_info [-h] machineId jobId
```

DESCRIPTION

This command allows getting information about a specific job. It can return the job's status, for example.

OPTIONS

-h *help* help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

4.3 vishnu_get_job_progress

vishnu_get_job_progress — gets the progression status of jobs

Synopsis

```
vishnu_get_job_progress [-h] [-i jobId] [-u jobOwner] machineId
```

DESCRIPTION

This command allows getting the progression status of a job based on the wall-clock time specified.

OPTIONS

- h** *help* help about the command.
- i** *jobId* Specifies the id of the job whose progression the user wants to see..
- u** *jobOwner* Specifies the owner of the job..

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

4.4 vishnu_list_queues

vishnu_list_queues — gets queues information

Synopsis

```
vishnu_list_queues [-h] [-q queueName] machineId
```

DESCRIPTION

This command displays the status of the queues of a specific machine's batch scheduler.

OPTIONS

- h** *help* help about the command.
 - q** *queueName* if it is given, listQueues gives information only of this queue.
-

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

4.5 vishnu_list_jobs

vishnu_list_jobs — gets a list of all submitted jobs

Synopsis

```
vishnu_list_jobs [-h] [-i jobId] [-P nbCpu] [-d fromSubmitDate] [-D toSubmitDate] [-u owner] [-s s-  
tatus] [-p priority] [-q queue] machineId
```

DESCRIPTION

This command allows displaying the jobs submitted on a specific machine's batch scheduler.

OPTIONS

-h help help about the command.

-i *jobId* lists the job with the specified id.

-P *nbCpu* lists the jobs with the specified number of CPUs.

-d *fromSubmitDate* lists the jobs submitted after the specified date (UNIX timestamp).

-D *toSubmitDate* lists jobs submitted before the specified date (UNIX timestamp).

-u *owner* lists the jobs submitted by the specified owner.

-s *status* lists the jobs with the specified status. The value must be an integer. Predefined values are: -1 (UNDEFINED), 1 (SUBMITTED), 2 (QUEUED), 3 (WAITING), 4 (RUNNING), 5 (TERMINATED), 6 (CANCELLED), 7 (ALREADY_DOWNLOADED).

-p *priority* lists the jobs with the specified priority. The value must be an integer. Predefined values are: -1 (UNDEFINED), 1 (VERY_LOW), 2 (LOW), 3 (NORMAL), 4 (HIGH), 5 (VERY_HIGH).

-q *queue* the jobs with the specified queue name.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

4.6 vishnu_get_job_output

`vishnu_get_job_output` — gets standard output and error output files of a job given its id

Synopsis

```
vishnu_get_job_output [-h] [-o outDir] machineId jobId
```

DESCRIPTION

This command allows getting a job's output files.

OPTIONS

-h *help* help about the command.

-o *outDir* The output directory where the files will be stored (default is current directory).

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (SSH error)" [9]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

"The job is not terminated" [107]

"The job is already downloaded" [108]

4.7 vishnu_get_completed_jobs_output

`vishnu_get_completed_jobs_output` — gets standard output and error output files of completed jobs (applies only once for each job)

Synopsis

```
vishnu_get_completed_jobs_output [-h] [-o outDir] machineId
```

DESCRIPTION

This command allows getting the output files of all the completed jobs.

OPTIONS

-h *help* help about the command.

-o *outDir* Specifies the output directory where the files will be stored (by default, the current directory)..

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (SSH error)" [9]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

4.8 vishnu_cancel_job

`vishnu_cancel_job` — cancels a job from its id

Synopsis

```
vishnu_cancel_job [-h] machineId jobId
```

DESCRIPTION

This command allows canceling a job submitted on a specific machine's batch scheduler.

OPTIONS

-h *help* help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (SSH error)" [9]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

"The job is already terminated" [105]

"The job is already canceled" [106]

Chapter 5

FMS Command reference

5.1 vishnu_create_file

`vishnu_create_file` — creates files on remote machines.

Synopsis

`vishnu_create_file [-h] path`

DESCRIPTION

Creates an empty file at the location given by the `path` parameter. The path must be provided in the form '`machine_id:path`' (the `machine_id` values can be obtained using the `vishnu_list_machine` command)

OPTIONS

`-h help` help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

5.2 vishnu_create_dir

vishnu_create_dir — creates directories on remote machines.

Synopsis

`vishnu_create_dir [-h] path`

DESCRIPTION

Creates an new directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

OPTIONS

`-h help` help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

5.3 vishnu_remove_file

vishnu_remove_file — removes files from remote hosts.

Synopsis

```
vishnu_remove_file [-h] [-r] path
```

DESCRIPTION

Deletes a file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

OPTIONS

-h *help* help about the command.

-r *isRecursive* It specifies when the remove command is recursive (case of directory) or not..

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

5.4 vishnu_remove_dir

vishnu_remove_dir — removes directories (and subdirectories) from remote machines.

Synopsis

```
vishnu_remove_dir [-h] path
```

DESCRIPTION

Deletes a directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

OPTIONS

-h *help* help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

5.5 vishnu_ch_grp

vishnu_ch_grp — changes group owner of remote files/directories.

Synopsis

```
vishnu_ch_grp [-h] group path
```

DESCRIPTION

Changes the group attribute of a file or directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

OPTIONS

-h *help* help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

5.6 vishnu_ch_mod

vishnu_ch_mod — changes access rights of remote files/directories.

Synopsis

vishnu_ch_mod [-h] *mode path*

DESCRIPTION

Changes the permissions of a file or directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command). The mode parameter is the same value as for the unix chmod command.

OPTIONS

-h *help* help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

5.7 vishnu_head_of_file

vishnu_head_of_file — displays a few first lines of files located on remote machines.

Synopsis

```
vishnu_head_of_file [-h] [-n nline] path
```

DESCRIPTION

Displays the first lines of a file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

OPTIONS

-h *help* help about the command.

-n *nline* the number of line to get.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

5.8 vishnu_tail_of_file

`vishnu_tail_of_file` — displays a few last lines of files located on remote machines

Synopsis

```
vishnu_tail_of_file [-h] [-n nline] path
```

DESCRIPTION

Displays the last lines of a file at the location given by the `path` parameter. The path must be provided in the form '`machine_id:path`' (the `machine_id` values can be obtained using the `vishnu_list_machine` command).

OPTIONS

-h *help* help about the command.

-n *nline* the number of line to get.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]
"an option or a parameter provided is invalid for this service." [10]
"Undefined configuration parameter" [12]
"The user is not an administrator" [25]
"The session key is unrecognized" [28]
"The session key has expired. The session is closed." [29]
"The machine id is unknown" [32]
"The local account is unknown" [38]
"The path provided is invalid." [201]
"Runtime error" [202]
"The transfer id ins unknown" [203]

5.9 vishnu_content_of_file

vishnu_content_of_file — displays content of files located on remote machines

Synopsis

`vishnu_content_of_file [-h] path`

DESCRIPTION

Displays the content of a file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

OPTIONS

`-h help` help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]
"an option or a parameter provided is invalid for this service." [10]
"Undefined configuration parameter" [12]
"The user is not an administrator" [25]
"The session key is unrecognized" [28]
"The session key has expired. The session is closed." [29]
"The machine id is unknown" [32]
"The local account is unknown" [38]
"The path provided is invalid." [201]
"Runtime error" [202]
"The transfer id ins unknown" [203]

5.10 vishnu_list_dir

vishnu_list_dir — displays the content of a remote directory.

Synopsis

```
vishnu_list_dir [-h] [-l] [-a] path
```

DESCRIPTION

Displays the content of a directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

OPTIONS

-h *help* help about the command.
-l *longFormat* It specifies the long display format (all available file informations).
-a *allFiles* Allows to display all files including hidden files.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]
"an option or a parameter provided is invalid for this service." [10]
"Undefined configuration parameter" [12]
"The user is not an administrator" [25]
"The session key is unrecognized" [28]
"The session key has expired. The session is closed." [29]
"The machine id is unknown" [32]
"The local account is unknown" [38]
"The path provided is invalid." [201]
"Runtime error" [202]
"The transfer id ins unknown" [203]

5.11 vishnu_copy_file

vishnu_copy_file — executes a synchronous copy of file.

Synopsis

```
vishnu_copy_file [-h] [-r] [-c trCommand] src dest
```

DESCRIPTION

Copy a file or directory from the location given by the *src* parameter to the location given by the *dest* parameter. The *src* parameter must be provided in the form '*machine_id:path*' (the *machine_id* values can be obtained using the *vishnu_list_machine* command) or '*path*' only if the file is on the local system. The *dest* parameter must be provided in a similar way. Note that one of the two locations at least must be a remote location, i.e. a local copy cannot be handled by this command.

OPTIONS

-h *help* help about the command.
-r *isRecursive* It specifies when the copy is recursive (case of directory) or not..
-c *trCommand* the command to use to perform file transfer.. The value must be an integer. Predefined values are: 0 (SCP), 1 (RSYNC), 2 (UNDEFINED).

ENVIRONMENT

VISHNU_TRANSFER_CMD It specifies the command to use for all file transfers by default. It takes its values in the set {SCP,RSYNC}.. Overriden by the -c option.

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]
"an option or a parameter provided is invalid for this service." [10]
"Undefined configuration parameter" [12]
"The user is not an administrator" [25]
"The session key is unrecognized" [28]
"The session key has expired. The session is closed." [29]
"The machine id is unknown" [32]
"The local account is unknown" [38]
"The path provided is invalid." [201]
"Runtime error" [202]
"The transfer id ins unknown" [203]

5.12 vishnu_copy_async_file

`vishnu_copy_async_file` — executes an asynchronous copy of file.

Synopsis

```
vishnu_copy_async_file [-h] [-r] [-c trCommand] src dest
```

DESCRIPTION

Initiates a copy of a file or directory from the location given by the `src` parameter to the location given by the `dest` parameter. The `src` parameter must be provided in the form '`machine_id:path`' (the `machine_id` values can be obtained using the `vishnu_list_machine` command) or '`path`' only if the file is on the local system. The `dest` parameter must be provided in a similar way. Note that one of the two locations at least must be a remote location, i.e. a local copy cannot be handled by this command. The command `listFileTransfers` can be used to check the status of the transfer after it is initiated, using the transfer id as the identifier.

OPTIONS

-h *help* help about the command.
-r *isRecursive* It specifies when the copy is recursive (case of directory) or not..
-c *trCommand* the command to use to perform file transfer.. The value must be an integer. Predefined values are: 0 (SCP), 1 (RSYNC), 2 (UNDEFINED).

ENVIRONMENT

VISHNU_TRANSFER_CMD It specifies the command to use for all file transfers by default. It takes its values in the set {SCP,RSYNC}.. Overridden by the -c option.

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

5.13 vishnu_move_file

vishnu_move_file — executes a synchronous move of file.

Synopsis

```
vishnu_move_file [-h] [-r] [-c trCommand] src dest
```

DESCRIPTION

Move a file or directory from the location given by the *src* parameter to the location given by the *dest* parameter. The *src* parameter must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command) or 'path' only if the file is on the local system. The *dest* parameter must be provided in a similar way. Note that one of the two locations at least must be a remote location, i.e. a local move cannot be handled by this command.

OPTIONS

-h *help* help about the command.

-r *isRecursive* It specifies when the copy is recursive (case of directory) or not..

-c *trCommand* the command to use to perform file transfer.. The value must be an integer. Predefined values are: 0 (SCP), 1 (RSYNC), 2 (UNDEFINED).

ENVIRONMENT

VISHNU_TRANSFER_CMD It specifies the command to use for all file transfers by default. It takes its values in the set {SCP,RSYNC}.. Overridden by the -c option.

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

5.14 vishnu_move_async_file

`vishnu_move_async_file` — executes an asynchronous move of file.

Synopsis

```
vishnu_move_async_file [-h] [-r] [-c trCommand] src dest
```

DESCRIPTION

Initiates a move of a file or directory from the location given by the `src` parameter to the location given by the `dest` parameter. The `src` parameter must be provided in the form '`machine_id:path`' (the `machine_id` values can be obtained using the `vishnu_list_machine` command) or '`path`' only if the file is on the local system. The `dest` parameter must be provided in a similar way. Note that one of the two locations at least must be a remote location, i.e. a local move cannot be handled by this command. The command `listFileTransfers` can be used to check the status of the transfer after it is initiated, using the transfer id as the identifier.

OPTIONS

-h *help* help about the command.

-r *isRecursive* It specifies when the copy is recursive (case of directory) or not..

-c *trCommand* the command to use to perform file transfer.. The value must be an integer. Predefined values are: 0 (SCP), 1 (RSYNC), 2 (UNDEFINED).

ENVIRONMENT

VISHNU_TRANSFER_CMD It specifies the command to use for all file transfers by default. It takes its values in the set {SCP,RSYNC}.. Overridden by the -c option.

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

5.15 vishnu_stop_file_transfer

`vishnu_stop_file_transfer` — stops an execution of a set of file transfers.

Synopsis

```
vishnu_stop_file_transfer [-h] [-i transferId] [-m fromMachineId] [-u userId]
```

DESCRIPTION

Cancels a file or directory transfer that has been initiated using a vishnu asynchronous copy or move file command. The command `listFileTransfers` can be used to check the status of the transfer after it has been cancelled, using the transfer id as the identifier.

OPTIONS

-h *help* help about the command.

-i *transferId* a given transfer id.

-m *fromMachineId* the machine that is the source or destination of the file transfer.

-u *userId* allows an admin to stop file transfers of a specific user.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

5.16 vishnu_list_file_transfers

`vishnu_list_file_transfers` — displays the history of all file transfers submitted by User.

Synopsis

```
vishnu_list_file_transfers [-h] [-t transferId] [-m fromMachineId] [-u userId] [-s status]
```

DESCRIPTION

Get the list of all file or directory transfers that have been initiated using a vishnu synchronous or asynchronous copy or move file command.

OPTIONS

-h *help* help about the command.

-t *transferId* a given transfer id.

-m *fromMachineId* the machine that is the source of the file transfer.

-u *userId* allows the admin to list file transfers initiated by a specific user.

-s *status* the file transfer status. The value must be an integer. Predefined values are: 0 (INPROGRESS), 1 (COMPLETED), 2 (CANCELLED), 3 (FAILED), 4 (UNDEFINED).

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

5.17 vishnu_get_file_info

`vishnu_get_file_info` — displays the information of files.

Synopsis

`vishnu_get_file_info [-h] path`

DESCRIPTION

Get the details of a remote file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the `vishnu_list_machine` command).

OPTIONS

`-h help` help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"Vishnu not available (Database error)" [2]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

Chapter 6

IMS Command reference

6.1 vishnu_export_commands

vishnu_export_commands — exports all the commands made by a user during a session

Synopsis

```
vishnu_export_commands [-h] [-t exportType] oldSessionId
```

DESCRIPTION

Exports all the VISHNU commands submitted during a completed session. This session must be in closed state. The output of this command is a file containing a shell script. For safety reasons, the commands having a password for parameter are not exported (for example the vishnu_connect and vishnu_change_password commands). This means the shell script must be run after opening a session manually or by adding the vishnu_connect command to the script. The access to other user's sessions is only permitted to administrators.

OPTIONS

-h *help* help about the command.

-t *exportType* The type to export. The value must be an integer. Predefined values are: 0 (UNDEFINED), 1 (SHELL).

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"The database generated an error" [2]

"Undefined error code" [9]

"If a parameter is invalid" [10]

"The session key is unrecognized." [28]

"The session key has expired. The session is closed." [29]

6.2 vishnu_get_metric_current_value

`vishnu_get_metric_current_value` — displays the current values of system metrics

Synopsis

```
vishnu_get_metric_current_value [-h] [-t metricType] machineId
```

DESCRIPTION

Displays the current values of the monitored metrics on the system identified by the `machineId` argument : `cpuload`, free disk space and free memory. The units of displayed values are percentages for `cpuload` and Megabytes (Mb) for `diskspace` and `memory`. The provided values are always standard integers (no float values). Please note that retrieving these values uses some valuable system resources and should not occur too frequently to avoid an impact on system performance.

OPTIONS

-h *help* help about the command.

-t *metricType* The type of the metric. The value must be an integer. Predefined values are: 0 (UNDEFINED), 1 (CPUUSE), 2 (FREEDISKSPACE), 3 (FREEMEMORY).

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on `stderr` and the command will return the code provided within brackets:

"The database generated an error" [2]

"Undefined error code" [9]

"If a parameter is invalid" [10]

"The session key is unrecognized." [28]

"The session key has expired. The session is closed." [29]

6.3 vishnu_get_metric_history

`vishnu_get_metric_history` — displays the history of values of a system metric

Synopsis

```
vishnu_get_metric_history [-h] [-s startTime] [-e endTime] [-t type] machineId
```

DESCRIPTION

Displays the chronological list of values of the metrics on the system identified by the `machineId` argument. Using the options it is possible to specify a type of metric and the starting and ending dates of the desired monitoring period. Note that some data will be available only if the required VISHNU agent (IMS server) has been running locally on the machine during the specified period.

OPTIONS

- h *help*** help about the command.
- s *startTime*** The start time to get the history.
- e *endTime*** The end time to get the history.
- t *type*** The type of metric searched. The value must be an integer. Predefined values are: 0 (UNDEFINED), 1 (CPUUSE), 2 (FREEDISKSPACE), 3 (FREEMEMORY).

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on `stderr` and the command will return the code provided within brackets:

"The database generated an error" [2]

"Undefined error code" [9]

"If a parameter is invalid" [10]

"The session key is unrecognized." [28]

"The session key has expired. The session is closed." [29]

6.4 vishnu_get_update_frequency

`vishnu_get_update_frequency` — gets the update frequency of the IMS database

Synopsis

```
vishnu_get_update_frequency [-h]
```

DESCRIPTION

This function allows a user to get the update frequency, to know how often the state of the machines is automatically polled to get historical data.

OPTIONS

- h *help*** help about the command.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"The database generated an error" [2]

"Undefined error code" [9]

"If a parameter is invalid" [10]

"The session key is unrecognized." [28]

"The session key has expired. The session is closed." [29]

6.5 vishnu_get_system_info

`vishnu_get_system_info` — To get the system info on a machine

Synopsis

```
vishnu_get_system_info [-h] [-m machineId]
```

DESCRIPTION

This function allows a user to get system information about a machine. A system information describes a machine. The option is the machine id (if no machine id, the information for all the machines are given)

OPTIONS

-h *help* help about the command.

-m *machineId* The machine id.

ENVIRONMENT

VISHNU_CONFIG_FILE Contains the path to the local configuration file for VISHNU.

DIAGNOSTICS

The following diagnostics may be issued on stderr and the command will return the code provided within brackets:

"The database generated an error" [2]

"Undefined error code" [9]

"If a parameter is invalid" [10]

"The session key is unrecognized." [28]

"The session key has expired. The session is closed." [29]

Chapter 7

UMS C++ API Reference

7.1 connect

connect — opens a session

Synopsis

```
int vishnu::connect(const string& userId, const string& password, Session& session, const ConnectOptions& options = ConnectOptions());
```

DESCRIPTION

Opening a VISHNU session is the first step before using any other VISHNU command. This command authenticates you. You must have been registered in the VISHNU system by an administrator. It also creates a session that remains open after the command is completed and until the session is either manually or automatically closed.

ARGUMENTS

userId Input argument. UserId represents the VISHNU user identifier.

password Input argument. Password represents the password of the user.

session Output argument. The session object that contains the created session details.

options Input argument. Options is an object which encapsulates the options available for the connect method. It allows the user to choose the way for closing the session automatically on TIMEOUT or on DISCONNECT and the possibility for an admin to open a session as he/she was a specific user.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The user is unknown or the password is wrong" [20]

"The userId is unknown" [21]

"The user is locked" [23]

"The user is not an administrator" [25]

"The closure policy is unknown" [42]

"The value of the timeout is incorrect" [43]

7.2 reconnect

`reconnect` — reconnects to a session that is still active

Synopsis

```
int vishnu::reconnect(const string& userId, const string& password, const string& sessionId, Session& session);
```

DESCRIPTION

This command allows you to resume a session that has been opened previously and that has not yet been closed. You can disconnect from a session without closing it (for example if there are running commands in that session) by setting the session's close policy (at connection time) to `CLOSE_ON_TIMEOUT`. As sessions are linked to a specific client system, you cannot reconnect to a session that was opened on another client system.

ARGUMENTS

userId Input argument. UserId represents the VISHNU user identifier.

password Input argument. Password represents the password of the user.

sessionId Input argument. SessionId is the identifier of the session defined in the database.

session Output argument. The session object containing session information.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The user is unknown or the password is wrong" [20]

"The user is locked" [23]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The session Id is unknown" [30]

"The machine does not exist or it is locked" [36]

7.3 close

close — closes the session

Synopsis

```
int vishnu::close(const string& sessionKey);
```

DESCRIPTION

This command closes the session that is currently active in the terminal. It will return an error if there are still some active requests that were been submitted by the user during the session (e.g., job submission or file transfers). After the session is closed, it cannot be re-opened.

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"Commands are running" [31]

7.4 changePassword

changePassword — changes the password

Synopsis

```
int vishnu::changePassword(const string& userId, const string& password, const string& passwordNew);
```

DESCRIPTION

This command is used to change the password. It can be done voluntarily or when the password is only temporary: for your first connection to VISHNU or after your password is reset by an administrator .

ARGUMENTS

userId Input argument. UserId represents the VISHNU user identifier.

password Input argument. Password represents the password of the user.

passwordNew Input argument. PasswordNew represents the new password of the user.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The user is unknown or the password is wrong" [20]

"The user is locked" [23]

7.5 addLocalAccount

addLocalAccount — adds a new local user configuration

Synopsis

```
int vishnu::addLocalAccount(const string& sessionKey, const LocalAccount& newAccount, string& sshPublicKey);
```

DESCRIPTION

A local user configuration must be added to allow you (identified by userId) to connect to machine (identified by machineId). This configuration must match an existing system account on that machine with a login that matches acLogin. The parameters sshKeyPath parameter (the absolute path to your private SSH key, used for file transfers) must be provided as well as the homeDirectory path .

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

newAccount Input argument. NewAccount is the object which encapsulates the new local user configuration.

sshPublicKey Output argument. The SSH public key generated by VISHNU for accessing a local account.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The userId is unknown" [21]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The machine is locked" [34]

"The machine does not exist or it is locked" [36]

"The local account already exists" [37]

"The system account login is already used by another vishnu user" [46]

7.6 updateLocalAccount

updateLocalAccount — updates a local user configuration

Synopsis

```
int vishnu::updateLocalAccount(const string& sessionKey, const LocalAccount& LocalAccUpd);
```

DESCRIPTION

The local user configuration can be updated. You can modify information of its local configuration such as acLogin, sshKeypath or homeDirectory.

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

LocalAccUpd Input argument. Is an object which encapsulates the local user configuration changes except the machineId and the userId.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The userId is unknown" [21]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local is unknown" [38]

"The system account login is already used by another vishnu user" [46]

7.7 deleteLocalAccount

`deleteLocalAccount` — removes a local user configuration (for a given user on a given machine) from VISHNU

Synopsis

```
int vishnu::deleteLocalAccount(const string& sessionKey, const string& userId, const string& machineId);
```

DESCRIPTION

The local user configuration can be deleted from VISHNU. When a local user configuration is deleted, all the information about it is deleted from VISHNU.

ARGUMENTS

sessionKey Input argument. The `sessionKey` is the encrypted identifier of the session generated by VISHNU.

userId Input argument. `UserId` represents the VISHNU user identifier of the user whose local configuration will be deleted for the given machine .

machineId Input argument. `MachineId` represents the identifier of the machine whose local configuration will be deleted for the given user .

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The local is unknown" [38]

7.8 listLocalAccounts

listLocalAccounts — lists the local user configurations

Synopsis

```
int vishnu::listLocalAccounts(const string& sessionKey, ListLocalAccounts& listLocalAcct, const ListLocalAccOptions& options = ListLocalAccOptions());
```

DESCRIPTION

A local configuration is used to configure the access to a given system for a given user through VISHNU. It is related to an account on that system that is identified using its login. This command allows you to check all the local configurations related to your VISHNU account.

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

listLocalAcct Output argument. ListLocalAccount is the list of the local user configurations .

options Input argument. Allows an admin to list all local configurations of all users or a simple user to list his/her local user configurations on a specific machine.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The userId is unknown" [21]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

7.9 listMachines

listMachines — lists the machines that are accessible through VISHNU

Synopsis

```
int vishnu::listMachines(const string& sessionKey, ListMachines& listMachine, const ListMachineOptions& options = ListMachineOptions());
```

DESCRIPTION

This command is used to display the machines that you can use for VISHNU services. The machines you can access through VISHNU are those that are configured in VISHNU by the VISHNU administrator, and that have been added to your personal VISHNU configuration using the `vishnu_add_local_account` command. The results contain, for each machine, a machine identifier that you can use as a parameter for other VISHNU commands.

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

listMachine Output argument. ListLocalAccount is the list of the local configs .

options Input argument. Allows a user to list all VISHNU machines or information about a specific machine and an admin to list machines used by a specific user.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The userId is unknown" [21]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

7.10 listHistoryCmd

listHistoryCmd — lists the commands

Synopsis

```
int vishnu::listHistoryCmd(const string& sessionKey, ListCommands& listCommands, const ListCmdOptions& options = ListCmdOptions());
```

DESCRIPTION

This command displays a history of the commands you ran. Several options can be used to specify which commands to list.

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

listCommands Output argument. ListCommands is the list of commands.

options Input argument. Allows the user to list commands by using several optional criteria: a period, specific session and for admin to list all commands of all VISHNU users or commands from a specific user.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The userId is unknown" [21]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

7.11 listOptions

listOptions — lists the options of the user

Synopsis

```
int vishnu::listOptions(const string& sessionKey, ListOptionsValues& listOptValues, const ListOptOptions& options = ListOptOptions());
```

DESCRIPTION

This command displays the options you configured.

ARGUMENTS

sessionKey Input argument. The sessionKey is the identifier of the session generated by VISHNU.

listOptValues Output argument. ListOptValues is an object which encapsulates the list of options.

options Input argument. Allows to list a specific option or all default options values or for an admin to list options of a specific user.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The userId is unknown" [21]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The name of the user option is unknown" [41]

7.12 listSessions

listSessions — lists all sessions of the user

Synopsis

```
int vishnu::listSessions(const string& sessionKey, ListSessions& listsession, const ListSessionOptions& options = ListSessionOptions());
```

DESCRIPTION

This command is used to display and filter the list of all your sessions. For each session, a session identifier is provided which you can use to reconnect to a given session using the vishnu_reconnect command. The session's status is either 0 (inactive) or 1 (active).

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

listsession Output argument. Listsession is the list of sessions .

options Input argument. Allows the user to list sessions using several optional criteria such as: the state of sessions (actives or inactives, by default, all sessions are listed), a period, a specific session or for admin to list all sessions of all users or sessions of a specific user..

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The userId is unknown" [21]

"The session key is unrecognized" [28]

"The sessionKey is expired. The session is closed." [29]

"The closure policy is unknown" [42]

7.13 configureOption

configureOption — configures an option of the user

Synopsis

```
int vishnu::configureOption(const string& sessionKey, const OptionValue& optionValue);
```

DESCRIPTION

Options in VISHNU corresponds to the parameters of some VISHNU commands (e.g., the close policy for vishnu_connect) that can be preset in the user configuration stored by the VISHNU system. This command is used to set the value of an option for the current user (the user who opened the session).

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

optionValue Input argument. The optionValue is an object which encapsulates the option information.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]
"Vishnu not available (Database error)" [2]
"Vishnu not available (Database connection)" [3]
"Vishnu not available (System)" [4]
"Internal Error: Undefined exception" [9]
"The session key is unrecognized" [28]
"The sessionKey is expired. The session is closed." [29]
"The name of the user option is unknown" [41]
"The closure policy is unknown" [42]
"The value of the timeout is incorrect" [43]
"The value of the transfer command is incorrect" [44]

7.14 vishnuInitialize

vishnuInitialize — initializes VISHNU

Synopsis

```
int vishnu::vishnuInitialize(const string& configPath);
```

DESCRIPTION

Calling this function is required before calling any function of the VISHNU API. It initializes the connection to the VISHNU infrastructure.

ARGUMENTS

configPath Input argument. ConfigPath is the path of VISHNU configuration file.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]
"Internal Error: Undefined exception" [9]

7.15 vishnuFinalize

vishnuFinalize — allows a user to go out properly from VISHNU

Synopsis

```
int vishnu::vishnuFinalize();
```

DESCRIPTION

Calling this function is necessary to free ressources consumed due to the VISHNU API

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Internal Error: Undefined exception" [9]

Chapter 8

TMS C++ API Reference

8.1 submitJob

`submitJob` — submits a job on a machine through the use of a script (`scriptFilePath`)

Synopsis

```
int vishnu::submitJob(const string& sessionKey, const string& machineId, const string& scriptFilePath, Job& jobInfo, const SubmitOptions& options = SubmitOptions());
```

DESCRIPTION

This command is used to submit a job to the specific batch scheduler associated to a machine. It allows describing a job in a script, using either the batch scheduler's directives or VISHNU's generic directives for all batch schedulers.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine on which the job must be submitted.

scriptFilePath Input argument. The path to the file containing the characteristics (job command, and batch scheduler directive required or optional) of the job to submit..

jobInfo Output argument. The Job object containing the output information (ex: `jobId` and `jobPath`) of the job to submit.

options Input argument. Is an instance of the class `SubmitOptions`. Each optionnal value is associated to a set operation (e.g: `setNbCpu(...)`) in the class `SubmitOptions`. If no set operation is not called on the instance object `options`, the job is submitted with the options defined in the `scriptFilePath`. Otherwise the job is submitted with the optionnal values set by the `options` object and optionnal values defined in the `scriptFilePath`, but optionnal values set by `SubmitOptions` object take precedence over those in `scriptFilePath`. With in the object `options` or within the `scriptFilePath`, the last occurrence of an optionnal value takes precedence over earlier occurrence..

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]
"Vishnu not available (Database connection)" [3]
"Vishnu not available (System)" [4]
"Vishnu not available (SSH error)" [9]
"Error invalid parameters" [10]
"The sessionKey is expired. The session is closed." [29]
"The machine id is unknown" [32]
"The batch scheduler type is unknown" [101]
"The batch scheduler indicates an error" [102]
"Permission denied" [104]

8.2 getJobInfo

getJobInfo — gets information on a job from its id

Synopsis

```
int vishnu::getJobInfo(const string& sessionKey, const string& machineId, const string& jobId, Job& jobInfos);
```

DESCRIPTION

This command allows getting information about a specific job. It can return the job's status, for example.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine on which the job is running.

jobId Input argument. The id of the job .

jobInfos Output argument. The resulting information on the job.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]
"Vishnu not available (Database error)" [2]
"Vishnu not available (Database connection)" [3]
"Vishnu not available (System)" [4]
"Internal Error: Undefined exception" [9]
"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

8.3 getJobProgress

getJobProgress — gets the progression status of jobs

Synopsis

```
int vishnu::getJobProgress(const string& sessionKey, const string& machineId, ListProgression& listProgress, const ProgressOptions& options = ProgressOptions());
```

DESCRIPTION

This command allows getting the progression status of a job based on the wall-clock time specified.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine to get the jobs progression.

listProgress Output argument. Is the object containing jobs progression information.

options Input argument. Is an object containing the available options jobs for progression ..

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

8.4 listQueues

listQueues — gets queues information

Synopsis

```
int vishnu::listQueues(const string& sessionKey, const string& machineId, ListQueues& listofQueues, const string& queue-
Name = string());
```

DESCRIPTION

This command displays the status of the queues of a specific machine's batch scheduler.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine that the user wants to list queues.

listofQueues Output argument. The list of queues.

queueName Input argument. If it is given, listQueues gives information only of this queue.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

8.5 listJobs

listJobs — gets a list of all submitted jobs

Synopsis

```
int vishnu::listJobs(const string& sessionKey, const string& machineId, ListJobs& listOfJobs, const ListJobsOptions& options
= ListJobsOptions());
```

DESCRIPTION

This command allows displaying the jobs submitted on a specific machine's batch scheduler.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine on which the jobs are running.

listOfJobs Output argument. The constructed object list of jobs.

options Input argument. Additional options for jobs listing.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Internal Error: Undefined exception" [9]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

8.6 getJobOutput

getJobOutput — gets standard output and error output files of a job given its id

Synopsis

```
int vishnu::getJobOutput(const string& sessionKey, const string& machineId, const string& jobId, JobResult& outputInfo,  
const string& outDir = string());
```

DESCRIPTION

This command allows getting a job's output files.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Gets outputPath and errorPath of a job from its id.

jobId Input argument. The Id of the job.

outputInfo Output argument. The Job object containing the job output information (ex: outputPath and errorPath) of the job to submit.

outDir Input argument. The output directory where the files will be stored (default is current directory).

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Vishnu not available (SSH error)" [9]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

"The job is not terminated" [107]

"The job is already downloaded" [108]

8.7 getCompletedJobsOutput

getCompletedJobsOutput — gets standard output and error output files of completed jobs (applies only once for each job)

Synopsis

```
int vishnu::getCompletedJobsOutput(const string& sessionKey, const string& machineId, ListJobResults& listOfResults, const string& outDir = string());
```

DESCRIPTION

This command allows getting the output files of all the completed jobs.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine on which the jobs are been submitted.

listOfResults Output argument. Is the list of jobs results.

outDir Input argument. Specifies the output directory where the files will be stored (by default, the current directory)..

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Vishnu not available (SSH error)" [9]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

8.8 cancelJob

cancelJob — cancels a job from its id

Synopsis

```
int vishnu::cancelJob(const string& sessionKey, const string& machineId, const string& jobId);
```

DESCRIPTION

This command allows canceling a job submitted on a specific machine's batch scheduler.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine on which the job is running.

jobId Input argument. The Id of the job.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Vishnu not available (Database connection)" [3]

"Vishnu not available (System)" [4]

"Vishnu not available (SSH error)" [9]

"The sessionKey is expired. The session is closed." [29]

"The machine id is unknown" [32]

"The batch scheduler type is unknown" [101]

"The batch scheduler indicates an error" [102]

"Permission denied" [104]

"The job is already terminated" [105]

"The job is already canceled" [106]

Chapter 9

FMS C++ API Reference

9.1 createFile

createFile — creates files on remote machines.

Synopsis

```
int vishnu::createFile(const string& sessionKey, const string& path);
```

DESCRIPTION

Creates an empty file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

ARGUMENTS

sessionKey Input argument. The session key..

path Input argument. The file to create following the pattern [host:]file path..

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.2 createDir

createDir — creates directories on remote machines.

Synopsis

```
int vishnu::createDir(const string& sessionKey, const string& path);
```

DESCRIPTION

Creates an new directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The directory to create following the pattern [host:]directory path..

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.3 removeFile

removeFile — removes files from remote hosts.

Synopsis

```
int vishnu::removeFile(const string& sessionKey, const string& path, const RmFileOptions& options = RmFileOptions());
```

DESCRIPTION

Deletes a file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The file to remove following the pattern [host:]file path.

options Input argument. The remove command options.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.4 removeDir

removeDir — removes directories (and subdirectories) from remote machines.

Synopsis

```
int vishnu::removeDir(const string& sessionKey, const string& path);
```

DESCRIPTION

Deletes a directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The directory to remove following the pattern [host:]directory path.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.5 chGrp

chGrp — changes group owner of remote files/directories.

Synopsis

```
int vishnu::chGrp(const string& sessionKey, const string& group, const string& path);
```

DESCRIPTION

Changes the group attribute of a file or directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

ARGUMENTS

sessionKey Input argument. The session key.

group Input argument. The new group owner of file/directory.

path Input argument. The file/directory following the pattern [host:]file path.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.6 chMod

chMod — changes access rights of remote files/directories.

Synopsis

```
int vishnu::chMod(const string& sessionKey, const mode_t& mode, const string& path);
```

DESCRIPTION

Changes the permissions of a file or directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command). The mode parameter is the same value as for the unix chmod command.

ARGUMENTS

sessionKey Input argument. The session key.

mode Input argument. the access rights of file/directory in octal system..

path Input argument. The file/directory following the pattern [host:]file path.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.7 headOfFile

headOfFile — displays a few first lines of files located on remote machines.

Synopsis

```
int vishnu::headOfFile(const string& sessionKey, const string& path, string& fileContent, const HeadOfFileOptions& options = HeadOfFileOptions());
```

DESCRIPTION

Displays the first lines of a file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The file following the pattern [host:]file path.

fileContent Output argument. The first "nLine" lines of the file.

options Input argument. The head commandoptions.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.8 tailOfFile

tailOfFile — displays a few last lines of files located on remote machines

Synopsis

```
int vishnu::tailOfFile(const string& sessionKey, const string& path, string& fileContent, const TailOfFileOptions& options = TailOfFileOptions());
```

DESCRIPTION

Displays the last lines of a file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The file following the pattern [host:]file path.

fileContent Output argument. The last "nLine" lines of the file.

options Input argument. The tail command options.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.9 contentOfFile

contentOfFile — displays content of files located on remote machines

Synopsis

```
int vishnu::contentOfFile(const string& sessionKey, const string& path, string& fileContent);
```

DESCRIPTION

Displays the content of a file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The file to display following the pattern [host:]file path.

fileContent Output argument. The content of the file.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.10 listDir

listDir — displays the content of a remote directory.

Synopsis

```
int vishnu::listDir(const string& sessionKey, const string& path, StringList& dirContent, const LsDirOptions& options);
```

DESCRIPTION

Displays the content of a directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The directory to list following the pattern [host:]directory path.

dirContent Output argument. The content of the directory (only files names with short format, all files informations with long format)..

options Input argument. List of options for the listDir command.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.11 copyFile

copyFile — executes a synchronous copy of file.

Synopsis

```
int vishnu::copyFile(const string& sessionKey, const string& src, const string& dest, const CpFileOptions& options = CpFileOptions());
```

DESCRIPTION

Copy a file or directory from the location given by the src parameter to the location given by the dest parameter. The src parameter must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command) or 'path' only if the file is on the local system. The dest parameter must be provided in a similar way. Note that one of the two locations at least must be a remote location, i.e. a local copy cannot be handled by this command.

ARGUMENTS

sessionKey Input argument. The session key.

src Input argument. The source file to copy following the pattern [host:]file path.

dest Input argument. The path of the destination file.

options Input argument. The copy options.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.12 copyAsyncFile

copyAsyncFile — executes an asynchronous copy of file.

Synopsis

```
int vishnu::copyAsyncFile(const string& sessionKey, const string& src, const string& dest, FileTransfer& transferInfo, const CpFileOptions& options);
```

DESCRIPTION

Initiates a copy of a file or directory from the location given by the *src* parameter to the location given by the *dest* parameter. The *src* parameter must be provided in the form 'machine_id:path' (the *machine_id* values can be obtained using the `vishnu_list_machine` command) or 'path' only if the file is on the local system. The *dest* parameter must be provided in a similar way. Note that one of the two locations at least must be a remote location, i.e. a local copy cannot be handled by this command. The command `listFileTransfers` can be used to check the status of the transfer after it is initiated, using the transfer id as the identifier.

ARGUMENTS

sessionKey Input argument. The session key.

src Input argument. The source file to copy following the pattern [host:]file path.

dest Input argument. The path of the destination file.

transferInfo Output argument. A file transfer identifier (allowing for instance to check the status of a file transfer, or to cancel it).

options Input argument. The copy options.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id is unknown" [203]

9.13 moveFile

moveFile — executes a synchronous move of file.

Synopsis

```
int vishnu::moveFile(const string& sessionKey, const string& src, const string& dest, const CpFileOptions& options);
```

DESCRIPTION

Move a file or directory from the location given by the *src* parameter to the location given by the *dest* parameter. The *src* parameter must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the `vishnu_list_machine` command) or 'path' only if the file is on the local system. The *dest* parameter must be provided in a similar way. Note that one of the two locations at least must be a remote location, i.e. a local move cannot be handled by this command.

ARGUMENTS

sessionKey Input argument. The session key.

src Input argument. The source file to move following the pattern [host:]file path.

dest Input argument. The path of the destination file.

options Input argument. The move command options.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.14 moveAsyncFile

moveAsyncFile — executes an asynchronous move of file.

Synopsis

```
int vishnu::moveAsyncFile(const string& sessionKey, const string& src, const string& dest, FileTransfer& transferInfo, const CpFileOptions& options = CpFileOptions());
```

DESCRIPTION

Initiates a move of a file or directory from the location given by the *src* parameter to the location given by the *dest* parameter. The *src* parameter must be provided in the form 'machine_id:path' (the *machine_id* values can be obtained using the `vishnu_list_machine` command) or 'path' only if the file is on the local system. The *dest* parameter must be provided in a similar way. Note that one of the two locations at least must be a remote location, i.e. a local move cannot be handled by this command. The command `listFileTransfers` can be used to check the status of the transfer after it is initiated, using the transfer id as the identifier.

ARGUMENTS

sessionKey Input argument. The session key.

src Input argument. The source file to move following the pattern [host:]file path.

dest Input argument. The path of the destination file.

transferInfo Output argument. A file tranfer identifier (allowing for instance to ckeck the status of a file transfer, or to cancel it).

options Input argument. The transfer command options.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.15 stopFileTransfer

stopFileTransfer — stops an execution of a set of file transfers.

Synopsis

```
int vishnu::stopFileTransfer(const string& sessionKey, const StopTransferOptions& options = StopTransferOptions());
```

DESCRIPTION

Cancels a file or directory transfer that has been initiated using a vishnu asynchronous copy or move file command. The command listFileTransfers can be used to check the status of the transfer after it has been cancelled, using the transfer id as the identifier.

ARGUMENTS

sessionKey Input argument. The session key.

options Input argument. The stop file transfer command options.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

9.16 listFileTransfers

listFileTransfers — displays the history of all file transfers submitted by User.

Synopsis

```
int vishnu::listFileTransfers(const string& sessionKey, FileTransferList& fileTransferList, const LsTransferOptions& options = LsTransferOptions());
```

DESCRIPTION

Get the list of all file or directory transfers that have been initiated using a vishnu synchronous or asynchronous copy or move file command.

ARGUMENTS

sessionKey Input argument. The session key.

fileTransferList Output argument. The file transfer list.

options Input argument. The filter options .

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]
"Vishnu not available (Database error)" [2]
"Internal Error: Undefined exception" [9]
"an option or a parameter provided is invalid for this service." [10]
"Undefined configuration parameter" [12]
"The user is not an administrator" [25]
"The session key is unrecognized" [28]
"The session key has expired. The session is closed." [29]
"The machine id is unknown" [32]
"The local account is unknown" [38]
"The path provided is invalid." [201]
"Runtime error" [202]
"The transfer id ins unknown" [203]

9.17 getFileInfo

getFileInfo — displays the information of files.

Synopsis

```
int vishnu::getFileInfo(const string& sessionKey, const string& path, FileStat& filesinfo);
```

DESCRIPTION

Get the details of a remote file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The file whose inode information will be displayed.

filesinfo Output argument. The inode information.

EXCEPTIONS

The following exceptions may be thrown:

"Vishnu not available (Service bus failure)" [1]

"Vishnu not available (Database error)" [2]

"Internal Error: Undefined exception" [9]

"an option or a parameter provided is invalid for this service." [10]

"Undefined configuration parameter" [12]

"The user is not an administrator" [25]

"The session key is unrecognized" [28]

"The session key has expired. The session is closed." [29]

"The machine id is unknown" [32]

"The local account is unknown" [38]

"The path provided is invalid." [201]

"Runtime error" [202]

"The transfer id ins unknown" [203]

Chapter 10

IMS C++ API Reference

10.1 exportCommands

exportCommands — exports all the commands made by a user during a session

Synopsis

```
int vishnu::exportCommands(const string& sessionKey, const string& oldSessionId, string& filename, const ExportOp& options = ExportOp());
```

DESCRIPTION

Exports all the VISHNU commands submitted during a completed session. This session must be in closed state. The output of this command is a file containing a shell script. For safety reasons, the commands having a password for parameter are not exported (for example the vishnu_connect and vishnu_change_password commands). This means the shell script must be run after opening a session manually or by adding the vishnu_connect command to the script. The access to other user's sessions is only permitted to administrators.

ARGUMENTS

sessionKey Input argument. The session key.

oldSessionId Input argument. The id of the session to export (session has ended).

filename Input/Output argument. The path of the output file containing the Vishnu shell commands.

options Input argument. Options which encapsulate the option for the export.

EXCEPTIONS

The following exceptions may be thrown:

"The database generated an error" [2]

"Undefined error code" [9]

"If a parameter is invalid" [10]

"The session key is unrecognized." [28]

"The session key has expired. The session is closed." [29]

10.2 getMetricCurrentValue

getMetricCurrentValue — displays the current values of system metrics

Synopsis

```
int vishnu::getMetricCurrentValue(const string& sessionKey, const string& machineId, ListMetric& metricValue, const Cur-  
MetricOp& options);
```

DESCRIPTION

Displays the current values of the monitored metrics on the system identified by the machineId argument : cpuload, free disk space and free memory. The units of displayed values are percentages for cpuload and Megabytes (Mb) for disk space and memory. The provided values are always standard integers (no float values). Please note that retrieving these values uses some valuable system resources and should not occur too frequently to avoid an impact on system performance.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. The id of the machine.

metricValue Output argument. Value of the metric.

options Input argument. The options for the current metric value.

EXCEPTIONS

The following exceptions may be thrown:

"The database generated an error" [2]

"Undefined error code" [9]

"If a parameter is invalid" [10]

"The session key is unrecognized." [28]

"The session key has expired. The session is closed." [29]

10.3 getMetricHistory

getMetricHistory — displays the history of values of a system metric

Synopsis

```
int vishnu::getMetricHistory(const string& sessionKey, const string& machineId, ListMetric& metricValues, const MetricHistOp&  
options = MetricHistOp());
```

DESCRIPTION

Displays the chronological list of values of the metrics on the system identified by the `machineId` argument. Using the options it is possible to specify a type of metric and the starting and ending dates of the desired monitoring period. Note that some data will be available only if the required VISHNU agent (IMS server) has been running locally on the machine during the specified period.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. The id of the machine.

metricValues Output argument. List of metric values.

options Input argument. The optional fields for the metric history.

EXCEPTIONS

The following exceptions may be thrown:

"The database generated an error" [2]

"Undefined error code" [9]

"If a parameter is invalid" [10]

"The session key is unrecognized." [28]

"The session key has expired. The session is closed." [29]

10.4 getUpdateFrequency

`getUpdateFrequency` — gets the update frequency of the IMS database

Synopsis

```
int vishnu::getUpdateFrequency(const string& sessionKey, int& freq);
```

DESCRIPTION

This function allows a user to get the update frequency, to know how often the state of the machines is automatically polled to get historical data.

ARGUMENTS

sessionKey Input argument. The session key.

freq Output argument. Frequency the data are updated, in second.

EXCEPTIONS

The following exceptions may be thrown:

"The database generated an error" [2]

"Undefined error code" [9]

"If a parameter is invalid" [10]

"The session key is unrecognized." [28]

"The session key has expired. The session is closed." [29]

10.5 getSystemInfo

getSystemInfo — To get the system info on a machine

Synopsis

```
int vishnu::getSystemInfo(const string& sessionKey, ListSysInfo& res, const SysInfoOp& options = SysInfoOp());
```

DESCRIPTION

This function allows a user to get system information about a machine. A system information describes a machine. The option is the machine id (if no machine id, the information for all the machines are given)

ARGUMENTS

sessionKey Input argument. The session key.

res Output argument. The list of the system information gotten.

options Input argument. Optional field for system information.

EXCEPTIONS

The following exceptions may be thrown:

"The database generated an error" [2]

"Undefined error code" [9]

"If a parameter is invalid" [10]

"The session key is unrecognized." [28]

"The session key has expired. The session is closed." [29]

Chapter 11

UMS Python API Reference

11.1 VISHNU_UMS.connect

VISHNU_UMS.connect — opens a session

Synopsis

VISHNU_UMS.connect(string userId, string password, Session session, ConnectOptions options = ConnectOptions());

DESCRIPTION

Opening a VISHNU session is the first step before using any other VISHNU command. This command authenticates you. You must have been registered in the VISHNU system by an administrator. It also creates a session that remains open after the command is completed and until the session is either manually or automatically closed.

ARGUMENTS

userId Input argument. UserId represents the VISHNU user identifier.

password Input argument. Password represents the password of the user.

session Output argument. The session object that contains the created session details.

options Input argument. Options is an object which encapsulates the options available for the connect method. It allows the user to choose the way for closing the session automatically on TIMEOUT or on DISCONNECT and the possibility for an admin to open a session as he/she was a specific user.

RETURNED OBJECTS

errorCode (*integer*) Output parameter. Contains 0 on success and the error code on failure.

sessionKey (*string*) Output parameter. Contains the session key.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The user is unknown or the password is wrong" [20])

UMSVishnuException("The userId is unknown" [21])

UMSVishnuException("The user is locked" [23])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The closure policy is unknown" [42])

UMSVishnuException("The value of the timeout is incorrect" [43])

11.2 VISHNU_UMS.reconnect

VISHNU_UMS.reconnect — reconnects to a session that is still active

Synopsis

VISHNU_UMS.reconnect(string userId, string password, string sessionId, Session session);

DESCRIPTION

This command allows you to resume a session that has been opened previously and that has not yet been closed. You can disconnect from a session without closing it (for example if there are running commands in that session) by setting the session's close policy (at connection time) to `CLOSE_ON_TIMEOUT`. As sessions are linked to a specific client system, you cannot reconnect to a session that was opened on another client system.

ARGUMENTS

userId Input argument. UserId represents the VISHNU user identifier.

password Input argument. Password represents the password of the user.

sessionId Input argument. SessionId is the identifier of the session defined in the database.

session Output argument. The session object containing session information.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

sessionKey (string) Output parameter. Contains the session key.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The user is unknown or the password is wrong" [20])

UMSVishnuException("The user is locked" [23])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The session Id is unknown" [30])

UMSVishnuException("The machine does not exist or it is locked" [36])

11.3 VISHNU_UMS.close

VISHNU_UMS.close — closes the session

Synopsis

VISHNU_UMS.close(string sessionKey);

DESCRIPTION

This command closes the session that is currently active in the terminal. It will return an error if there are still some active requests that were been submitted by the user during the session (e.g., job submission or file transfers). After the session is closed, it cannot be re-opened.

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("Commands are running" [31])

11.4 VISHNU_UMS.changePassword

VISHNU_UMS.changePassword — changes the password

Synopsis

VISHNU_UMS.changePassword(string userId, string password, string passwordNew);

DESCRIPTION

This command is used to change the password. It can be done voluntarily or when the password is only temporary: for your first connection to VISHNU or after your password is reset by an administrator .

ARGUMENTS

userId Input argument. UserId represents the VISHNU user identifier.

password Input argument. Password represents the password of the user.

passwordNew Input argument. PasswordNew represents the new password of the user.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The user is unknown or the password is wrong" [20])

UMSVishnuException("The user is locked" [23])

11.5 VISHNU_UMS.addLocalAccount

VISHNU_UMS.addLocalAccount — adds a new local user configuration

Synopsis

VISHNU_UMS.addLocalAccount(string sessionKey, LocalAccount newAccount, string sshPublicKey);

DESCRIPTION

A local user configuration must be added to allow you (identified by `userId`) to connect to machine (identified by `machineId`). This configuration must match an existing system account on that machine with a login that matches `acLogin`. The parameters `sshKeyPath` parameter (the absolute path to your private SSH key, used for file transfers) must be provided as well as the `homeDirectory` path .

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

newAccount Input argument. NewAccount is the object which encapsulates the new local user configuration.

sshPublicKey Output argument. The SSH public key generated by VISHNU for accessing a local account.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The userId is unknown" [21])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The machine is locked" [34])

UMSVishnuException("The machine does not exist or it is locked" [36])

UMSVishnuException("The local account already exists" [37])

UMSVishnuException("The system account login is already used by another vishnu user" [46])

11.6 VISHNU_UMS.updateLocalAccount

VISHNU_UMS.updateLocalAccount — updates a local user configuration

Synopsis

VISHNU_UMS.updateLocalAccount(string sessionKey, LocalAccount LocalAccUpd);

DESCRIPTION

The local user configuration can be updated. You can modify information of its local configuration such as acLogin, sshKeypath or homeDirectory.

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

LocalAccUpd Input argument. Is an object which encapsulates the local user configuration changes except the machineId and the userId.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The userId is unknown" [21])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local is unknown" [38])

UMSVishnuException("The system account login is already used by another vishnu user" [46])

11.7 VISHNU_UMS.deleteLocalAccount

VISHNU_UMS.deleteLocalAccount — removes a local user configuration (for a given user on a given machine) from VISHNU

Synopsis

VISHNU_UMS.deleteLocalAccount(string sessionKey, string userId, string machineId);

DESCRIPTION

The local user configuration can be deleted from VISHNU. When a local user configuration is deleted, all the information about it is deleted from VISHNU.

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

userId Input argument. UserId represents the VISHNU user identifier of the user whose local configuration will be deleted for the given machine .

machineId Input argument. MachineId represents the identifier of the machine whose local configuration will be deleted for the given user .

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The local is unknown" [38])

11.8 VISHNU_UMS.listLocalAccounts

VISHNU_UMS.listLocalAccounts — lists the local user configurations

Synopsis

VISHNU_UMS.listLocalAccounts(string sessionKey, ListLocalAccounts listLocalAcct, ListLocalAccOptions options = ListLocalAccOptions());

DESCRIPTION

A local configuration is used to configure the access to a given system for a given user through VISHNU. It is related to an account on that system that is identified using its login. This command allows you to check all the local configurations related to your VISHNU account.

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

listLocalAcct Output argument. ListLocalAccount is the list of the local user configurations .

options Input argument. Allows an admin to list all local configurations of all users or a simple user to list his/her local user configurations on a specific machine.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The userId is unknown" [21])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

11.9 VISHNU_UMS.listMachines

VISHNU_UMS.listMachines — lists the machines that are accessible through VISHNU

Synopsis

VISHNU_UMS.listMachines(string sessionKey, ListMachines listMachine, ListMachineOptions options = ListMachineOptions());

DESCRIPTION

This command is used to display the machines that you can use for VISHNU services. The machines you can access through VISHNU are those that are configured in VISHNU by the VISHNU administrator, and that have been added to your personal VISHNU configuration using the vishnu_add_local_account command. The results contain, for each machine, a machine identifier that you can use as a parameter for other VISHNU commands.

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

listMachine Output argument. ListLocalAccount is the list of the local configs .

options Input argument. Allows a user to list all VISHNU machines or information about a specific machine and an admin to list machines used by a specific user.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The userId is unknown" [21])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

11.10 VISHNU_UMS.listHistoryCmd

VISHNU_UMS.listHistoryCmd — lists the commands

Synopsis

VISHNU_UMS.listHistoryCmd(string sessionKey, ListCommands listCommands, ListCmdOptions options = ListCmdOptions());

DESCRIPTION

This command displays a history of the commands you ran. Several options can be used to specify which commands to list.

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

listCommands Output argument. ListCommands is the list of commands.

options Input argument. Allows the user to list commands by using several optional criteria: a period, specific session and for admin to list all commands of all VISHNU users or commands from a specific user.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The userId is unknown" [21])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

11.11 VISHNU_UMS.listOptions

VISHNU_UMS.listOptions — lists the options of the user

Synopsis

VISHNU_UMS.listOptions(string sessionKey, ListOptionsValues listOptValues, ListOptOptions options = ListOptOptions());

DESCRIPTION

This command displays the options you configured.

ARGUMENTS

sessionKey Input argument. The sessionKey is the identifier of the session generated by VISHNU.

listOptValues Output argument. ListOptValues is an object which encapsulates the list of options.

options Input argument. Allows to list a specific option or all default options values or for an admin to list options of a specific user.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The userId is unknown" [21])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The name of the user option is unknown" [41])

11.12 VISHNU_UMS.listSessions

VISHNU_UMS.listSessions — lists all sessions of the user

Synopsis

VISHNU_UMS.listSessions(string sessionKey, ListSessions listsession, ListSessionOptions options = ListSessionOptions());

DESCRIPTION

This command is used to display and filter the list of all your sessions. For each session, a session identifier is provided which you can use to reconnect to a given session using the `vishnu_reconnect` command. The session's status is either 0 (inactive) or 1 (active).

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

listsession Output argument. Listsession is the list of sessions .

options Input argument. Allows the user to list sessions using several optional criteria such as: the state of sessions (actives or inactives, by default, all sessions are listed), a period, a specific session or for admin to list all sessions of all users or sessions of a specific user..

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The userId is unknown" [21])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The closure policy is unknown" [42])

11.13 VISHNU_UMS.configureOption

VISHNU_UMS.configureOption — configures an option of the user

Synopsis

VISHNU_UMS.configureOption(string sessionKey, OptionValue optionValue);

DESCRIPTION

Options in VISHNU corresponds to the parameters of some VISHNU commands (e.g., the close policy for vishnu_connect) that can be preset in the user configuration stored by the VISHNU system. This command is used to set the value of an option for the current user (the user who opened the session).

ARGUMENTS

sessionKey Input argument. The sessionKey is the encrypted identifier of the session generated by VISHNU.

optionValue Input argument. The optionValue is an object which encapsulates the option information.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The name of the user option is unknown" [41])

UMSVishnuException("The closure policy is unknown" [42])

UMSVishnuException("The value of the timeout is incorrect" [43])

UMSVishnuException("The value of the transfer command is incorrect" [44])

11.14 VISHNU_UMS.vishnuInitialize

VISHNU_UMS.vishnuInitialize — initializes VISHNU

Synopsis

VISHNU_UMS.vishnuInitialize(string configPath);

DESCRIPTION

Calling this function is required before calling any function of the VISHNU API. It initializes the connection to the VISHNU infrastructure.

ARGUMENTS

configPath Input argument. ConfigPath is the path of VISHNU configuration file.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Internal Error: Undefined exception" [9])

11.15 VISHNU_UMS.vishnuFinalize

VISHNU_UMS.vishnuFinalize — allows a user to go out properly from VISHNU

Synopsis

VISHNU_UMS.vishnuFinalize();

DESCRIPTION

Calling this function is necessary to free ressources consumed due to the VISHNU API

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Internal Error: Undefined exception" [9])

Chapter 12

TMS Python API Reference

12.1 VISHNU_UMS.submitJob

VISHNU_UMS.submitJob — submits a job on a machine through the use of a script (scriptFilePath)

Synopsis

VISHNU_UMS.submitJob(string sessionKey, string machineId, string scriptFilePath, Job jobInfo, SubmitOptions options = SubmitOptions());

DESCRIPTION

This command is used to submit a job to the specific batch scheduler associated to a machine. It allows describing a job in a script, using either the batch scheduler's directives or VISHNU's generic directives for all batch schedulers.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine on which the job must be submitted.

scriptFilePath Input argument. The path to the file containing the characteristics (job command, and batch scheduler directive required or optional) of the job to submit..

jobInfo Output argument. The Job object containing the output information (ex: jobId and jobPath) of the job to submit.

options Input argument. Is an instance of the class SubmitOptions. Each optionnal value is associated to a set operation (e.g: setNbCpu(...)) in the class SubmitOptions. If no set operation is not called on the instance object options, the job is submitted with the options defined in the scriptFilePath. Otherwise the job is submitted with the optionnal values set by the options object and optionnal values defined in the scriptFilePath, but optionnal values set by SubmitOptions object take precedence over those in scriptFilePath. With in the object options or within the scriptFilePath, the last occurrence of an optionnal value takes precedence over earlier occurrence..

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Vishnu not available (SSH error)" [9])

UserException("Error invalid parameters" [10])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The batch scheduler type is unknown" [101])

UMSVishnuException("The batch scheduler indicates an error" [102])

UMSVishnuException("Permission denied" [104])

12.2 VISHNU_UMS.getJobInfo

VISHNU_UMS.getJobInfo — gets information on a job from its id

Synopsis

VISHNU_UMS.getJobInfo(string sessionKey, string machineId, string jobId, Job jobInfos);

DESCRIPTION

This command allows getting information about a specific job. It can return the job's status, for example.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine on which the job is running.

jobId Input argument. The id of the job .

jobInfos Output argument. The resulting information on the job.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The batch scheduler type is unknown" [101])

UMSVishnuException("The batch scheduler indicates an error" [102])

UMSVishnuException("Permission denied" [104])

12.3 VISHNU_UMS.getJobProgress

VISHNU_UMS.getJobProgress — gets the progression status of jobs

Synopsis

VISHNU_UMS.getJobProgress(string sessionKey, string machineId, ListProgression listProgress, ProgressOptions options = ProgressOptions());

DESCRIPTION

This command allows getting the progression status of a job based on the wall-clock time specified.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine to get the jobs progression.

listProgress Output argument. Is the object containing jobs progression information.

options Input argument. Is an object containing the available options jobs for progression ..

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

12.4 VISHNU_UMS.listQueues

VISHNU_UMS.listQueues — gets queues information

Synopsis

VISHNU_UMS.listQueues(string sessionKey, string machineId, ListQueues listofQueues, string queueName = string());

DESCRIPTION

This command displays the status of the queues of a specific machine's batch scheduler.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine that the user wants to list queues.

listofQueues Output argument. The list of queues.

queueName Input argument. If it is given, listQueues gives information only of this queue.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The batch scheduler type is unknown" [101])

UMSVishnuException("The batch scheduler indicates an error" [102])

UMSVishnuException("Permission denied" [104])

12.5 VISHNU_UMS.listJobs

VISHNU_UMS.listJobs — gets a list of all submitted jobs

Synopsis

VISHNU_UMS.listJobs(string sessionKey, string machineId, ListJobs listOfJobs, ListJobsOptions options = ListJobsOptions());

DESCRIPTION

This command allows displaying the jobs submitted on a specific machine's batch scheduler.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine on which the jobs are running.

listOfJobs Output argument. The constructed object list of jobs.

options Input argument. Additional options for jobs listing.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Internal Error: Undefined exception" [9])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The batch scheduler type is unknown" [101])

UMSVishnuException("The batch scheduler indicates an error" [102])

UMSVishnuException("Permission denied" [104])

12.6 VISHNU_UMS.getJobOutput

VISHNU_UMS.getJobOutput — gets standard output and error output files of a job given its id

Synopsis

VISHNU_UMS.getJobOutput(string sessionKey, string machineId, string jobId, JobResult outputInfo, string outDir = string());

DESCRIPTION

This command allows getting a job's output files.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Gets outputPath and errorPath of a job from its id.

jobId Input argument. The Id of the job.

outputInfo Output argument. The Job object containing the job output information (ex: outputPath and errorPath) of the job to submit.

outDir Input argument. The output directory where the files will be stored (default is current directory).

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Vishnu not available (SSH error)" [9])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The batch scheduler type is unknown" [101])

UMSVishnuException("The batch scheduler indicates an error" [102])

UMSVishnuException("Permission denied" [104])

UMSVishnuException("The job is not terminated" [107])

UMSVishnuException("The job is already downloaded" [108])

12.7 VISHNU_UMS.getCompletedJobsOutput

VISHNU_UMS.getCompletedJobsOutput — gets standard output and error output files of completed jobs (applies only once for each job)

Synopsis

VISHNU_UMS.getCompletedJobsOutput(string sessionKey, string machineId, ListJobResults listOfResults, string outDir = string());

DESCRIPTION

This command allows getting the output files of all the completed jobs.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine on which the jobs are been submitted.

listOfResults Output argument. Is the list of jobs results.

outDir Input argument. Specifies the output directory where the files will be stored (by default, the current directory)..

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Vishnu not available (SSH error)" [9])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The batch scheduler type is unknown" [101])

UMSVishnuException("The batch scheduler indicates an error" [102])

UMSVishnuException("Permission denied" [104])

12.8 VISHNU_UMS.cancelJob

VISHNU_UMS.cancelJob — cancels a job from its id

Synopsis

VISHNU_UMS.cancelJob(string sessionKey, string machineId, string jobId);

DESCRIPTION

This command allows canceling a job submitted on a specific machine's batch scheduler.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. Is the id of the machine on which the job is running.

jobId Input argument. The Id of the job.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Vishnu not available (Database connection)" [3])

SystemException("Vishnu not available (System)" [4])

SystemException("Vishnu not available (SSH error)" [9])

UMSVishnuException("The sessionKey is expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The batch scheduler type is unknown" [101])

UMSVishnuException("The batch scheduler indicates an error" [102])

UMSVishnuException("Permission denied" [104])

UMSVishnuException("The job is already terminated" [105])

UMSVishnuException("The job is already canceled" [106])

Chapter 13

FMS Python API Reference

13.1 VISHNU_UMS.createFile

VISHNU_UMS.createFile — creates files on remote machines.

Synopsis

VISHNU_UMS.createFile(string sessionKey, string path);

DESCRIPTION

Creates an empty file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

ARGUMENTS

sessionKey Input argument. The session key..

path Input argument. The file to create following the pattern [host:]file path..

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.2 VISHNU_UMS.createDir

VISHNU_UMS.createDir — creates directories on remote machines.

Synopsis

VISHNU_UMS.createDir(string sessionKey, string path);

DESCRIPTION

Creates an new directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The directory to create following the pattern [host:]directory path..

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.3 VISHNU_UMS.removeFile

VISHNU_UMS.removeFile — removes files from remote hosts.

Synopsis

VISHNU_UMS.removeFile(string sessionKey, string path, RmFileOptions options = RmFileOptions());

DESCRIPTION

Deletes a file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The file to remove following the pattern [host:]file path.

options Input argument. The remove command options.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.4 VISHNU_UMS.removeDir

VISHNU_UMS.removeDir — removes directories (and subdirectories) from remote machines.

Synopsis

VISHNU_UMS.removeDir(string sessionKey, string path);

DESCRIPTION

Deletes a directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The directory to remove following the pattern [host:]directory path.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.5 VISHNU_UMS.chGrp

VISHNU_UMS.chGrp — changes group owner of remote files/directories.

Synopsis

VISHNU_UMS.chGrp(string sessionKey, string group, string path);

DESCRIPTION

Changes the group attribute of a file or directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command)

ARGUMENTS

sessionKey Input argument. The session key.

group Input argument. The new group owner of file/directory.

path Input argument. The file/directory following the pattern [host:]file path.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.6 VISHNU_UMS.chMod

VISHNU_UMS.chMod — changes access rights of remote files/directories.

Synopsis

VISHNU_UMS.chMod(string sessionKey, mode_t mode, string path);

DESCRIPTION

Changes the permissions of a file or directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command). The mode parameter is the same value as for the unix chmod command.

ARGUMENTS

sessionKey Input argument. The session key.

mode Input argument. the access rigths of file/directory in octal system..

path Input argument. The file/directory following the pattern [host:]file path.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.7 VISHNU_UMS.headOfFile

VISHNU_UMS.headOfFile — displays a few first lines of files located on remote machines.

Synopsis

VISHNU_UMS.headOfFile(string sessionKey, string path, string fileContent, HeadOfFileOptions options = HeadOfFileOptions());

DESCRIPTION

Displays the first lines of a file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The file following the pattern [host:]file path.

fileContent Output argument. The first "nLine" lines of the file.

options Input argument. The head commandoptions.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])
UMSVishnuException("The user is not an administrator" [25])
UMSVishnuException("The session key is unrecognized" [28])
UMSVishnuException("The session key has expired. The session is closed." [29])
UMSVishnuException("The machine id is unknown" [32])
UMSVishnuException("The local account is unknown" [38])
UMSVishnuException("The path provided is invalid." [201])
UMSVishnuException("Runtime error" [202])
UMSVishnuException("The transfer id ins unknown" [203])

13.8 VISHNU_UMS.tailOfFile

VISHNU_UMS.tailOfFile — displays a few last lines of files located on remote machines

Synopsis

VISHNU_UMS.tailOfFile(string sessionKey, string path, string fileContent, TailOfFileOptions options = TailOfFileOptions());

DESCRIPTION

Displays the last lines of a file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The file following the pattern [host:]file path.

fileContent Output argument. The last "nLine" lines of the file.

options Input argument. The tail command options.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.9 VISHNU_UMS.contentOfFile

VISHNU_UMS.contentOfFile — displays content of files located on remote machines

Synopsis

VISHNU_UMS.contentOfFile(string sessionKey, string path, string fileContent);

DESCRIPTION

Displays the content of a file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The file to display following the pattern [host:]file path.

fileContent Output argument. The content of the file.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.10 VISHNU_UMS.listDir

VISHNU_UMS.listDir — displays the content of a remote directory.

Synopsis

VISHNU_UMS.listDir(string sessionKey, string path, StringList dirContent, LsDirOptions options);

DESCRIPTION

Displays the content of a directory at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The directory to list following the pattern [host:]directory path.

dirContent Output argument. The content of the directory (only files names with short format, all files informations with long format)..

options Input argument. List of options for the listDir command.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.11 VISHNU_UMS.copyFile

VISHNU_UMS.copyFile — executes a synchronous copy of file.

Synopsis

VISHNU_UMS.copyFile(string sessionKey, string src, string dest, CpFileOptions options = CpFileOptions());

DESCRIPTION

Copy a file or directory from the location given by the *src* parameter to the location given by the *dest* parameter. The *src* parameter must be provided in the form 'machine_id:path' (the *machine_id* values can be obtained using the *vishnu_list_machine* command) or 'path' only if the file is on the local system. The *dest* parameter must be provided in a similar way. Note that one of the two locations at least must be a remote location, i.e. a local copy cannot be handled by this command.

ARGUMENTS

sessionKey Input argument. The session key.

src Input argument. The source file to copy following the pattern [host:]file path.

dest Input argument. The path of the destination file.

options Input argument. The copy options.

RETURNED OBJECTS

errorCode (*integer*) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.12 VISHNU_UMS.copyAsyncFile

VISHNU_UMS.copyAsyncFile — executes an asynchronous copy of file.

Synopsis

VISHNU_UMS.copyAsyncFile(string sessionKey, string src, string dest, FileTransfer transferInfo, CpFileOptions options);

DESCRIPTION

Initiates a copy of a file or directory from the location given by the src parameter to the location given by the dest parameter. The src parameter must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command) or 'path' only if the file is on the local system. The dest parameter must be provided in a similar way. Note that one of the two locations at least must be a remote location, i.e. a local copy cannot be handled by this command. The command listFileTransfers can be used to check the status of the transfer after it is initiated, using the transfer id as the identifier.

ARGUMENTS

sessionKey Input argument. The session key.

src Input argument. The source file to copy following the pattern [host:]file path.

dest Input argument. The path of the destination file.

transferInfo Output argument. A file transfer identifier (allowing for instance to check the status of a file transfer, or to cancel it).

options Input argument. The copy options.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id is unknown" [203])

13.13 VISHNU_UMS.moveFile

VISHNU_UMS.moveFile — executes a synchronous move of file.

Synopsis

VISHNU_UMS.moveFile(string sessionKey, string src, string dest, CpFileOptions options);

DESCRIPTION

Move a file or directory from the location given by the `src` parameter to the location given by the `dest` parameter. The `src` parameter must be provided in the form `'machine_id:path'` (the `machine_id` values can be obtained using the `vishnu_list_machine` command) or `'path'` only if the file is on the local system. The `dest` parameter must be provided in a similar way. Note that one of the two locations at least must be a remote location, i.e. a local move cannot be handled by this command.

ARGUMENTS

sessionKey Input argument. The session key.

src Input argument. The source file to move following the pattern `[host:]file path`.

dest Input argument. The path of the destination file.

options Input argument. The move command options.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.14 VISHNU_UMS.moveAsyncFile

`VISHNU_UMS.moveAsyncFile` — executes an asynchronous move of file.

Synopsis

VISHNU_UMS.moveAsyncFile(string sessionKey, string src, string dest, FileTransfer transferInfo, CpFileOptions options = CpFileOptions());

DESCRIPTION

Initiates a move of a file or directory from the location given by the `src` parameter to the location given by the `dest` parameter. The `src` parameter must be provided in the form `'machine_id:path'` (the `machine_id` values can be obtained using the `vishnu_list_machine` command) or `'path'` only if the file is on the local system. The `dest` parameter must be provided in a similar way. Note that one of the two locations at least must be a remote location, i.e. a local move cannot be handled by this command. The command `listFileTransfers` can be used to check the status of the transfer after it is initiated, using the transfer id as the identifier.

ARGUMENTS

sessionKey Input argument. The session key.

src Input argument. The source file to move following the pattern `[host:]file path`.

dest Input argument. The path of the destination file.

transferInfo Output argument. A file transfer identifier (allowing for instance to check the status of a file transfer, or to cancel it).

options Input argument. The transfer command options.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id is unknown" [203])

13.15 VISHNU_UMS.stopFileTransfer

VISHNU_UMS.stopFileTransfer — stops an execution of a set of file transfers.

Synopsis

VISHNU_UMS.stopFileTransfer(string sessionKey, StopTransferOptions options = StopTransferOptions());

DESCRIPTION

Cancels a file or directory transfer that has been initiated using a vishnu asynchronous copy or move file command. The command `listFileTransfers` can be used to check the status of the transfer after it has been cancelled, using the transfer id as the identifier.

ARGUMENTS

sessionKey Input argument. The session key.

options Input argument. The stop file transfer command options.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.16 VISHNU_UMS.listFilesTransfers

VISHNU_UMS.listFilesTransfers — displays the history of all file transfers submitted by User.

Synopsis

VISHNU_UMS.listFilesTransfers(string sessionKey, FileTransferList fileTransferList, LsTransferOptions options = LsTransferOptions());

DESCRIPTION

Get the list of all file or directory transfers that have been initiated using a vishnu synchronous or asynchronous copy or move file command.

ARGUMENTS

sessionKey Input argument. The session key.

fileTransferList Output argument. The file transfer list.

options Input argument. The filter options .

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

13.17 VISHNU_UMS.getFileInfo

VISHNU_UMS.getFileInfo — displays the information of files.

Synopsis

VISHNU_UMS.getFileInfo(string sessionKey, string path, FileStat filesinfo);

DESCRIPTION

Get the details of a remote file at the location given by the path parameter. The path must be provided in the form 'machine_id:path' (the machine_id values can be obtained using the vishnu_list_machine command).

ARGUMENTS

sessionKey Input argument. The session key.

path Input argument. The file whose inode information will be displayed.

filesinfo Output argument. The inode information.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("Vishnu not available (Service bus failure)" [1])

SystemException("Vishnu not available (Database error)" [2])

SystemException("Internal Error: Undefined exception" [9])

UserException("an option or a parameter provided is invalid for this service." [10])

UserException("Undefined configuration parameter" [12])

UMSVishnuException("The user is not an administrator" [25])

UMSVishnuException("The session key is unrecognized" [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

UMSVishnuException("The machine id is unknown" [32])

UMSVishnuException("The local account is unknown" [38])

UMSVishnuException("The path provided is invalid." [201])

UMSVishnuException("Runtime error" [202])

UMSVishnuException("The transfer id ins unknown" [203])

Chapter 14

IMS Python API Reference

14.1 VISHNU_UMS.exportCommands

VISHNU_UMS.exportCommands — exports all the commands made by a user during a session

Synopsis

VISHNU_UMS.exportCommands(string sessionKey, string oldSessionId, string filename, ExportOp options = ExportOp());

DESCRIPTION

Exports all the VISHNU commands submitted during a completed session. This session must be in closed state. The output of this command is a file containing a shell script. For safety reasons, the commands having a password for parameter are not exported (for example the vishnu_connect and vishnu_change_password commands). This means the shell script must be run after opening a session manually or by adding the vishnu_connect command to the script. The access to other user's sessions is only permitted to administrators.

ARGUMENTS

sessionKey Input argument. The session key.

oldSessionId Input argument. The id of the session to export (session has ended).

filename Input/Output argument. The path of the output file containing the Vishnu shell commands.

options Input argument. Options which encapsulate the option for the export.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("The database generated an error" [2])

SystemException("Undefined error code" [9])

UserException("If a parameter is invalid" [10])

UMSVishnuException("The session key is unrecognized." [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

14.2 VISHNU_UMS.getMetricCurrentValue

VISHNU_UMS.getMetricCurrentValue — displays the current values of system metrics

Synopsis

VISHNU_UMS.getMetricCurrentValue(string sessionKey, string machineId, ListMetric metricValue, CurMetricOp options);

DESCRIPTION

Displays the current values of the monitored metrics on the system identified by the machineId argument : cpuload, free disk space and free memory. The units of displayed values are percentages for cpuload and Megabytes (Mb) for disk space and memory. The provided values are always standard integers (no float values). Please note that retrieving these values uses some valuable system resources and should not occur too frequently to avoid an impact on system performance.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. The id of the machine.

metricValue Output argument. Value of the metric.

options Input argument. The options for the current metric value.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("The database generated an error" [2])

SystemException("Undefined error code" [9])

UserException("If a parameter is invalid" [10])

UMSVishnuException("The session key is unrecognized." [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

14.3 VISHNU_UMS.getMetricHistory

VISHNU_UMS.getMetricHistory — displays the history of values of a system metric

Synopsis

VISHNU_UMS.getMetricHistory(string sessionKey, string machineId, ListMetric metricValues, MetricHistOp options = MetricHistOp());

DESCRIPTION

Displays the chronological list of values of the metrics on the system identified by the machineId argument. Using the options it is possible to specify a type of metric and the starting and ending dates of the desired monitoring period. Note that some data will be available only if the required VISHNU agent (IMS server) has been running locally on the machine during the specified period.

ARGUMENTS

sessionKey Input argument. The session key.

machineId Input argument. The id of the machine.

metricValues Output argument. List of metric values.

options Input argument. The optional fields for the metric history.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("The database generated an error" [2])

SystemException("Undefined error code" [9])

UserException("If a parameter is invalid" [10])

UMSVishnuException("The session key is unrecognized." [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

14.4 VISHNU_UMS.getUpdateFrequency

VISHNU_UMS.getUpdateFrequency — gets the update frequency of the IMS database

Synopsis

VISHNU_UMS.getUpdateFrequency(string sessionKey, int freq);

DESCRIPTION

This function allows a user to get the update frequency, to know how often the state of the machines is automatically polled to get historical data.

ARGUMENTS

sessionKey Input argument. The session key.

freq Output argument. Frequency the data are updated, in second.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("The database generated an error" [2])

SystemException("Undefined error code" [9])

UserException("If a parameter is invalid" [10])

UMSVishnuException("The session key is unrecognized." [28])

UMSVishnuException("The session key has expired. The session is closed." [29])

14.5 VISHNU_UMS.getSystemInfo

VISHNU_UMS.getSystemInfo — To get the system info on a machine

Synopsis

```
VISHNU_UMS.getSystemInfo(string sessionKey, ListSysInfo res, SysInfoOp options = SysInfoOp());
```

DESCRIPTION

This function allows a user to get system information about a machine. A system information describes a machine. The option is the machine id (if no machine id, the information for all the machines are given)

ARGUMENTS

sessionKey Input argument. The session key.

res Output argument. The list of the system information gotten.

options Input argument. Optional field for system information.

RETURNED OBJECTS

errorCode (integer) Output parameter. Contains 0 on success and the error code on failure.

EXCEPTIONS

The following exceptions may be thrown:

SystemException("The database generated an error" [2])

SystemException("Undefined error code" [9])

UserException("If a parameter is invalid" [10])

UMSVishnuException("The session key is unrecognized." [28])

UMSVishnuException("The session key has expired. The session is closed." [29])
