DSC PowerG Wireless Repeater

PG4920 · extends PowerG range · 48 h backup

STOCK CODE

22PG4920

Extends wireless range in big or thick-walled buildings — mains powered with a 48-hour backup battery.



48 h	AC	Tamper	LED
battery backup	mains powered	wall + case	link quality

WHY CUSTOMERS CHOOSE IT

- **Extends range** between devices and the panel
- **Rechargeable backup** — 48 hours
- LEDs for power failure, activity, diagnostics
- Wall and case tamper

BEST FOR

- ✔ Large homes, outbuildings, double-storeys
- ✔ Concrete or steel structures blocking signal
- ✔ Detectors at the edge of range

NOT FOR

- ✖ Small sites where devices already reach the panel
- ✖ Non-PowerG systems

KEY SPECS

Size / weight	**161 × 161 × 50 mm · 470 g**
Backup battery	**4.8 V 1300 mAh Ni-MH**
Backup time	**48 hours**
Operating temp	**−10 to +55 °C**
Compatibility	**PowerSeries Neo, iotega**

FAMILY — PICK THE RIGHT ONE

PG4920	433 MHz — **this unit**
PG8920	868 MHz version

COUNTER QUICK ANSWERS

How many per system? Up to 8 repeaters on a Neo with HSM2HOST.

Needs power? Yes — mains adapter, with 48 h battery backup.

Where to mount? Halfway between the panel and far devices.