C-TEC CAST Manual Call Point (Red)

Addressable resettable break-glass call point · CAST

STOCK CODE

29CA470

Resettable addressable call point for exits and stairways on C-TEC CAST systems.



EN54-11 LPCB | **Resettable** no glass | **IP42** standard | **Isolator** built in

WHY CUSTOMERS CHOOSE IT

- **Resettable element** feels like breaking glass
- **Red LED alarm ring** lights on activation
- Glow-in-the-dark window (visible ~5 min)
- Built-in short-circuit isolator
- Surface back box + flush plate + reset key included

BEST FOR

- ✔ Exits, stairwells and escape routes
- ✔ C-TEC XFP / ZFP CAST systems
- ✔ Surface or flush mounting

NOT FOR

- ✖ Outdoor/wet areas — order the IP67 CA47067
- ✖ Conventional or other-brand panels

KEY SPECS

Supply	**27 – 40 VDC**
Current	**370 µA quiet · 5 mA alarm**
Size	**87 × 88 × 62 mm (with back box)**
Weight	**180 g**
Rating	**IP42**

FAMILY — PICK THE RIGHT ONE

CA470	**Red, IP42 — this unit**
CA47067	**IP67 version**
Other colours	**Yellow, green, blue, white**

COUNTER QUICK ANSWERS

Need glass? No — resettable element, reset with the key.

Outdoor? Order the IP67 CA47067.

Back box? Included.