Dahua ITC413 Access ANPR Camera

DHI-ITC413-PW4D-IZ1 · 4MP ANPR · 2.7–12 mm · relays · IP67/IK10

STOCK CODE

51ITC413-PW4D-IZ1

All-in-one ANPR camera for gates — reads plates, opens the boom from its allow list.



≥96%	3–8 m	2 relays	IK10
plate recognition*	capture distance	barrier control	IP67

BEST FOR

- ✔ Estate and factory gates
- ✔ Boom-gate automation
- ✔ Car park entrances

NOT FOR

- ✖ Wide lanes over 4 m
- ✖ Highway speed capture

WHY CUSTOMERS CHOOSE IT

- **Plate, vehicle type, brand & colour** recognition
- **Allow/block lists** (110,000 entries)
- 2 relay outputs, Wiegand & RS-485
- Built-in speaker + red/blue warning light
- Junction box and bracket built in

KEY SPECS

Lens	**2.7–12 mm motorised**
Lane width	**3–4 m**
Power	**12 VDC 2 A or PoE 802.3at · max 20 W**
Size	**395 × 121 × 128 mm**

FAMILY — PICK THE RIGHT ONE

ITC413-PW4D-IZ1	2.7–12 mm, IR — **this unit**
ITC413-PW4D-IZ3	8–32 mm, 8–30 m capture

COUNTER QUICK ANSWERS

Opens the boom itself? Yes — relay output from the allow list.

Distance? 3–8 m capture.

***Recognition rate?** ≥96% in recommended conditions.

Source: Dahua DHI-ITC413-PW4D Series datasheet.