Impro Distributed Controller (PoE++ Metal)

HCD903 · 2-door controller · PoE++ PSU · steel enclosure

STOCK CODE

72HCD903-0-0-GB-00

Impro 2-door controller in a metal box powered by PoE++ — no mains needed.

No product photo in the datasheet

2 doors	PoE++	10,000	OSDP
4 inputs, 2+1 relays	802.3bt	credentials offline	1000 m

WHY CUSTOMERS CHOOSE IT

- Door, Lite or full system controller (up to 64 devices)
- OSDP or Wiegand readers
- Offline anti-passback · duress
- 3 × 12 V outputs with resettable fuses · battery monitoring

BEST FOR

- ✔ Impro Primo / Access Portal sites
- ✔ Doors without nearby mains
- ✔ Aperio wireless lock hubs

NOT FOR

- ✖ Non-Impro software

KEY SPECS

Power	**PoE++ (802.3bt)**
Size / weight	**82 × 383 × 313 mm · 3.5 kg**
Reader cable	**Wiegand 150 m · OSDP 1000 m**

FAMILY — PICK THE RIGHT ONE

HCD900	**Module only**
HCD901/2	**Metal box, mains PSU**
HCD903	**Metal box, PoE++ — this unit**
HCD905	**Plastic box**

COUNTER QUICK ANSWERS

Mains needed? No — PoE++.

Readers? OSDP or Wiegand.

Offline? Yes — 10,000 credentials stored.