C-TEC CAST Heat Detector

Programmable addressable heat detector · CAST

STOCK CODE

29CA402

Heat detector for kitchens, garages and dusty areas where smoke detectors false-alarm.



A1R / A2 / B	60 °C	EN54-5	Isolator
programmable	default (A2)	LPCB	built in

WHY CUSTOMERS CHOOSE IT

- **3 modes** — rate-of-rise (A1R), 60 °C (A2), 80 °C (B)
- Different sensitivity by day/night
- Built-in short-circuit isolator
- 360° red LED strips

BEST FOR

- ✔ Kitchens, canteens, laundries
- ✔ Garages, plant rooms, dusty areas
- ✔ C-TEC XFP / ZFP CAST systems

NOT FOR

- ✖ Bedrooms and escape routes (use smoke/multi-sensor)
- ✖ Conventional or other-brand panels

KEY SPECS

Supply	**27 – 40 VDC, 2-wire**
Current	**370 µA quiet · 5 mA alarm**
Size	**102.2 Ø × 57.5 mm in base**
Weight	**154 g in base**
Rating	**IP42**

FAMILY — PICK THE RIGHT ONE

CA402	Heat — **this unit**
CA414	Multi-sensor
CA416	Optical smoke
CA408	CAST base — required

COUNTER QUICK ANSWERS

Base included? No — order the CA408.

Default setting? Class A2 (60 °C fixed).

Kitchen? Yes — this is the right detector.

Source: C-TEC CAST CA402 datasheet.

Internal counter reference