Optex AX-130TN Outdoor Beam (40 m)

Wired photoelectric beam pair · 40 m outdoor · IP65

STOCK CODE

07AX130TN

Compact wired beam for walls, gates and perimeters — 40 m outdoors.



40 m	IP65	41 mA	99%
outdoor range	weatherproof	Tx + Rx	beam loss tolerance

BEST FOR

- ✔ Walls, fences and gate lines
- ✔ Driveways and side passages
- ✔ Wired alarm systems

NOT FOR

- ✖ Runs over 40 m (use AX-200TN)
- ✖ Sites without cabling (use a wireless beam)

WHY CUSTOMERS CHOOSE IT

- **IP65** sealed with rubber packing
- Works with up to 99% beam loss (rain, fog)
- AGC adjusts to changing weather
- Lightning protection over 14 kV
- Adjustable interruption time

KEY SPECS

Power	**10.5–28 VDC · 41 mA (Tx + Rx)**
Alarm output	**N.C. 28 VDC 0.2 A**
Response	**50 / 100 / 250 / 500 ms**
Operating temp	**−35 to +60 °C**
Weight	**650 g (pair)**

FAMILY — PICK THE RIGHT ONE

AX-70TN	20 m
AX-130TN	40 m — **this unit**
AX-200TN	60 m

COUNTER QUICK ANSWERS

Range? 40 m outdoors.

Pole mount? Yes — wall or pole. BC-3 / PSC-3 covers optional.

Cold or frost? Add the HU-3 heater kit.