Uniross LFP12-50 Lithium Battery

12.8 V 50 Ah LiFePO4 lithium battery with built-in BMS

STOCK CODE

10LFP12-50

Big lithium battery for gate motors, solar and backup — 2000+ cycles at a third of the lead-acid weight.



50 Ah	2000+	6 kg	640 Wh
capacity	cycles	weight	energy

WHY CUSTOMERS CHOOSE IT

- **Built-in BMS** — over-charge, over-discharge, short-circuit, temperature
- Cell balancing
- IP56 ABS case
- M6 terminals

BEST FOR

- ✔ Solar and inverter backup
- ✔ Long-runtime security backup
- ✔ Replacing heavy lead-acid banks

NOT FOR

- ✖ Charging below 0 °C
- ✖ Chargers without a lithium/14.4 V profile

KEY SPECS

Charge	**14.4 V ±0.2 · 10 A standard, 50 A max**
Discharge	**50 A continuous / pulse**
Size	**229 × 138 × 215 mm**
Temp	**Charge 0–45 °C · discharge −20–60 °C**

FAMILY — PICK THE RIGHT ONE

LFP12-20	20 Ah
LFP12-50	50 Ah — **this unit**
LFP12-100	100 Ah

COUNTER QUICK ANSWERS

Charger? Use a lithium (LiFePO4) profile, 14.4 V.

Max load? 50 A continuous.

Outdoor box? IP56 case, but keep it out of direct weather.

Source: Uniross LFP12-50 datasheet.