DSC TL280LE LTE + IP Dual-Path Communicator

PowerSeries Neo cellular (LTE/HSPA) + Internet alarm communicator

STOCK CODE

22TL280LE

Dual-path communicator for Neo panels — reports over LTE and the Internet, no phone line needed.

⚠ This datasheet is the North American version (AT&T / Bell / Rogers SIM). Confirm local network and SIM support before selling.



LTE + IP	AES	90 mA	Neo
dual path	128-bit	current	HS2016–HS2128

WHY CUSTOMERS CHOOSE IT

- **Cellular + Internet** fully redundant paths
- Remote upload/download via DLS
- Visual verification support
- SMS command and control
- Antenna extension kits available

BEST FOR

- ✔ Monitored Neo systems
- ✔ Sites with no phone line
- ✔ Upgrading a phone-line panel to dual path

NOT FOR

- ✖ Non-Neo panels
- ✖ Areas with poor cellular signal (use antenna kit or remote mounting)

KEY SPECS

Compatible panels	**HS2016 / HS2032 / HS2064 / HS2128**
Receivers	**Sur-Gard System I-IP to 5**
Current draw	**90 mA**
Size / weight	**150 × 115 mm · 310 g**
Operating temp	**5 to 40 °C**

FAMILY — PICK THE RIGHT ONE

TL280E	Internet only
LE2080E	Cellular only
TL280LE	Cellular + Internet — **this unit**

COUNTER QUICK ANSWERS

Phone line needed? No.

Connects how? PC-Link header on the Neo panel.

Weak signal? Use LT-15/25/50ANT antenna kits or remote mount.