Forbatt FB7.2-12 Battery 12 V 7.2 Ah

Sealed lead-acid (AGM-VRLA) standby battery

STOCK CODE

06AS12-7

The standard alarm-panel battery — 12 V 7.2 Ah, maintenance-free, fits most panels and power supplies.



12 V	7.2 Ah	2.05 kg	AGM
nominal	capacity	weight	sealed VRLA

BEST FOR

- ✔ Alarm panel backup (most panels take 7 Ah)
- ✔ Electric fence energisers
- ✔ Small gate motors & access control PSUs
- ✔ CCTV power supply backup
- ✔ UPS / standby use

NOT FOR

- ✖ Heavy daily deep cycling (consider lithium)
- ✖ Hot spots above 40 °C
- ✖ Applications needing more than 7 Ah runtime

WHY CUSTOMERS CHOOSE IT

- **Maintenance-free** sealed AGM construction
- Standard 151 × 65 × 94 mm size — fits most enclosures
- Low self-discharge — 90% after 3 months
- UL recognised, CE marked
- Recyclable lead-acid

KEY SPECS

Capacity (20 h)	**7.2 Ah**
Standby charge	**13.5 – 13.8 V**
Cycle charge	**14.4 – 15.0 V**
Max initial current	**2.16 A**
Size	**151 × 65 × 94 mm (100 mm with terminal)**
Internal resistance	**30 mΩ**

COUNTER QUICK ANSWERS

Fits my alarm panel? Yes, if it takes a standard 12 V 7 Ah — same size.

How long does it last? Check it under load at every service and replace when it fails.

Cold weather? Capacity drops to ~85% at 0 °C.

Source: Forbatt FB7.2-12 datasheet.

Internal counter reference