C-TEC CAST Optical Smoke Detector

Addressable optical smoke detector — CAST protocol

STOCK CODE

29CA416

Addressable smoke detector for C-TEC XFP/ZFP CAST fire panels, with smart false-alarm filtering.



EN54-7 LPCB certified

CAST addressable

5 mA alarm current

Built-in loop isolator

WHY CUSTOMERS CHOOSE IT

- **Smart algorithms** reduce false alarms
- **Built-in short-circuit isolator** on every device
- Drift compensation for dust build-up
- Two ultra-bright red LED strips + programmable status LED

BEST FOR

- ✔ Offices, corridors, bedrooms, stairwells
- ✔ C-TEC XFP / ZFP CAST addressable systems
- ✔ Sites needing EN54-certified detection

NOT FOR

- ✖ Kitchens / dusty or steamy areas (use heat or multi-sensor)
- ✖ Conventional or other-brand panels
- ✖ Outdoor use

KEY SPECS

Protocol	**C-TEC CAST (XFP / ZFP panels)**
Supply	**22 – 40 VDC**
Current	**370 µA quiet · 5 mA alarm**
Sensitivity	**0.16 dB/m**
Approvals	**LPCB EN54-7/17, DBI EN54-13**

FAMILY — PICK THE RIGHT ONE

CA416	**Optical smoke — this unit**
CA414	**Multi-sensor (smoke + heat)**
CA408	**CAST base — required, sold separately**

COUNTER QUICK ANSWERS

Base included? No — order the CA408 CAST base.

Works with my panel? Only C-TEC XFP/ZFP CAST-protocol panels.

Kitchen? No — sell a heat or multi-sensor detector.