C-TEC CAST Compact Wall Sounder

Addressable 96 dB(A) sounder · CAST · red

STOCK CODE

29CA450A-SR

Loop-powered addressable sounder for C-TEC CAST fire systems — no separate sounder wiring.



96 dB(A)	15	7	EN54-3
@ 1 m	tone pairs	volume levels	LPCB

WHY CUSTOMERS CHOOSE IT

- **96 dB(A)** at 1 m
- **Loop powered** — on the CAST loop
- Group addressing — sound areas together
- Built-in short-circuit isolator

BEST FOR

- ✔ Corridors, rooms and stairwells on CAST systems
- ✔ Loop-powered sounders (saves cabling)
- ✔ Wall or ceiling mounting

NOT FOR

- ✖ Conventional or other-brand panels
- ✖ Wet or outdoor areas (IP21C)
- ✖ Deaf/hard-of-hearing areas — add a VAD/beacon

KEY SPECS

Supply	**27 – 40 VDC (loop)**
Current	**550 µA quiet · 5.5 mA alarm**
Size	**102 Ø × 63 mm**
Weight	**160 g**
Rating	**IP21C**

COUNTER QUICK ANSWERS

Separate wiring? No — it runs on the detector loop.

Panels? C-TEC CAST (XFP / ZFP).

Volume? 7 levels, 15 tone options.