
Kantech KT-400 Four-Door Controller

Ethernet 4-door / 8-reader controller · standalone or EntraPass

STOCK CODE

39KT-400-EU

Four doors in one cabinet — web-based standalone setup, or full EntraPass for larger systems.



4	8	100k	5 yr
doors	readers	cards offline	warranty

WHY CUSTOMERS CHOOSE IT

- **Standalone mode** — browser setup, 2,000 cardholders
- **EntraPass mode** — 8 readers, advanced features
- 4 supervised lock outputs (12 V internal)
- Expand to 256 inputs / 256 outputs
- Double/triple-swipe to arm alarm

BEST FOR

- ✔ Offices with 2–4 controlled doors
- ✔ Growing to larger EntraPass systems
- ✔ Integration with DSC alarm panels

NOT FOR

- ✖ Single door only (KT-1 is cheaper)
- ✖ Outdoor mounting

KEY SPECS

Power	**16.5 or 24 VAC, 75 VA transformer**
Battery	**12 V 7 or 12 Ah · up to 12 h**
Lock power	**12 VDC, 2 A max total**
Relays	**4 × Form C, 30 VDC 3 A**
Cabinet	**376 × 305 × 126 mm · 4 kg**
Operating temp	**2 to 49 °C, indoor**

FAMILY — PICK THE RIGHT ONE

KT-1	**1 door, PoE**
KT-400	**4 doors / 8 readers — this unit**

COUNTER QUICK ANSWERS

Readers? Kantech ioProx XSF or ioSmart readers.

Software needed? Not for standalone — up to 2,000 cardholders in a browser.

Battery? 12 V 7 or 12 Ah.

Source: Kantech KT-400 datasheet.