Kantech ioProx P225XSF Mullion Reader

125 kHz proximity reader · mullion · XSF / 26-bit

STOCK CODE

39P225XSF

Slim proximity reader for door frames — reads Kantech ioProx cards and tags.

D29010398R002

16.5 cm	125 kHz	300 m	−35–65 °C
read range	proximity	from controller	operating

BEST FOR

- ✔ Door frames and narrow mullions
- ✔ Kantech KT-1 / KT-400 systems
- ✔ Indoor or outdoor doors

NOT FOR

- ✖ Smart-card (13.56 MHz) systems — use ioSmart
- ✖ Non-Kantech systems needing XSF format

WHY CUSTOMERS CHOOSE IT

- **Mullion size** — fits door frames
- Bicolour LED + buzzer
- Reads XSF and 26-bit Wiegand
- Optional tamper (P-TAMP)

KEY SPECS

Read range	**Up to 16.5 cm**
Voltage	**4.5 – 14 VDC, 45 mA max**
Size / weight	**114 × 44.5 × 21 mm · 90 g**
Cable	**3 twisted pairs #22 AWG, up to 300 m**
Colour	**Black**

FAMILY — PICK THE RIGHT ONE

P225XSF	**Mullion — this unit**
P225KPXSF	**Mullion with keypad**
P325XSF	**Single-gang, 20.5 cm range**
P325KPXSF	**Single-gang with keypad**

COUNTER QUICK ANSWERS

Which cards? Kantech ioProx (e.g. P30DMG, P40KEY).

Keypad? Sell the P225KPXSF.

Outdoor? Rated −35 to 65 °C.