Texecom Premier Compact PIR

Compact Grade 2 residential PIR range (IR / XT / QD / PW)

STOCK CODE

41ACH-0001

Small, reliable home detectors — choose IR, digital XT, quad QD or pet-immune PW to suit the room.

⚠ Datasheet covers the whole Premier Compact range (IR, XT, QD, PW). Confirm which model this stock code is.



12–15 m range

35 kg pet immune (PW)

Grade 2 EN50131

12 V 9–15 VDC

WHY CUSTOMERS CHOOSE IT

- **Sealed optics** — no dust or insects
- **Mounting-height alignment** 1.5–3.1 m
- Selectable pulse count
- Interchangeable curtain/long-range lenses
- EOL resistors built in

BEST FOR

- ✔ Homes and small offices
- ✔ Texecom Premier systems
- ✔ Pet owners (PW model)
- ✔ Hot rooms (XT/QD temperature compensation)

NOT FOR

- ✖ Outdoor use
- ✖ Commercial Grade 3 sites

KEY SPECS

Range	**IR & PW 12 m · XT & QD 15 m**
Power	**9 – 15 VDC, max 10.6 mA**
Start-up	**60 seconds**
Mount height	**1.5 – 3.1 m (PW: 1.5 – 2.3 m)**
Approvals	**EN 50131-2-2 Grade 2**

FAMILY — PICK THE RIGHT ONE

Compact IR	**Dual element, 12 m**
Compact XT	**Digital, 15 m**
Compact QD	**Digital quad, 15 m**
Compact PW	**Pet immune to 35 kg, 12 m**

COUNTER QUICK ANSWERS

Pets? Sell the Compact PW — immune to 35 kg.

Hot rooms? XT or QD have digital temperature compensation.

Brackets? Wall/ceiling brackets sold separately (packs of 10).