
Kantech KT-MOD-INP16 16-Input Module

16-zone input expansion for KT-400

STOCK CODE

39KT-MOD-INP16

Adds 16 inputs to a KT-400 — door contacts, sensors or lift feedback.



No product photo in the datasheet

16	15	256	40 mA
inputs	modules / KT-400	inputs max	per module

WHY CUSTOMERS CHOOSE IT

- **Dry, single-EOL or double-EOL** inputs (5.6 kΩ)
- NO or NC contacts
- Daisy-chain up to 15 modules
- SPI cable + 16 resistors included

KEY SPECS

Current	**Up to 40 mA per module**
Size	**140 × 80 mm**
Mounting	**Kantech cabinet, within 1 m of KT-400**
Operating temp	**−10 to +55 °C**

BEST FOR

- ✔ Extra door contacts and sensors on a KT-400
- ✔ Elevator input monitoring
- ✔ Large KT-400 installs

NOT FOR

- ✖ KT-1 (KT-400 only)
- ✖ More than 8 inputs in double-EOL mode (Z1–Z8 only)

FAMILY — PICK THE RIGHT ONE

KT-MOD-INP16	16 inputs — **this unit**
KT-MOD-REL8	8 relays
KT-MOD-OUT16	16 outputs

COUNTER QUICK ANSWERS

External power? Yes, 12 V 2 A if SPI load exceeds 500 mA.

Mix with output modules? Yes — via its SPI EXP port; input module goes first.

Double-EOL? Yes, but only 8 inputs work in that mode.