ZKTeco KR310 Dual-Frequency Reader

125 kHz + 13.56 MHz Wiegand reader · IP65

STOCK CODE

42KR101E

Waterproof card reader that reads both EM and MIFARE cards — for outdoor gates and doors.

⚠ The datasheet on file is for the KR310. Confirm this stock code (KR101E) is the same reader.



IP65	Dual	10 cm	W34
waterproof	125k / 13.56M	read range	Wiegand

WHY CUSTOMERS CHOOSE IT

- **Dual frequency** — EM ID + MIFARE Classic/DESFire
- **IP65** waterproof
- LED access indication
- Wiegand 34-bit

BEST FOR

- ✔ Outdoor gates and doors
- ✔ Reading the exit side of a ZKTeco controller
- ✔ Sites with mixed EM and MIFARE cards

NOT FOR

- ✖ Fingerprint or face verification
- ✖ OSDP systems

KEY SPECS

Power	**6 – 14 VDC, max 70 mA**
Read time	**< 300 ms**
Size	**77.5 × 42.8 × 16.5 mm**
Operating temp	**−10 to +70 °C**

COUNTER QUICK ANSWERS

Outdoor? Yes, IP65.

Which cards? EM ID, MIFARE Classic, DESFire.

Controller? Any ZKTeco panel with Wiegand input.