Impro Seos Multi-Discipline Reader

MDR-SE mullion reader · 125 kHz + 13.56 MHz + BLE · IP54

STOCK CODE

72HRN980

Secure multi-technology reader — reads HID Seos, iClass, MIFARE, DESFire, prox and mobile.

⚠ Datasheet lists part numbers HRW910 (Wiegand) and HRW911 (OSDP). Confirm which variant this stock code is.



Seos	BLE	OSDP	IP54
+ iClass	10 m mobile	1000 m	indoor/outdoor

WHY CUSTOMERS CHOOSE IT

- **Reads** Seos, iClass, MIFARE, DESFire, NFC, 125 kHz
- **OSDP** (2-wire, 1000 m) or Wiegand (150 m)
- AES-128 reader-to-controller encryption
- Tri-colour LED + buzzer · optical tamper

BEST FOR

- ✔ Impro Access Portal / Primo systems
- ✔ Sites using HID Seos/iClass or mobile credentials
- ✔ Mullion door frames

NOT FOR

- ✖ Keypad entry (no keypad)
- ✖ Fully exposed outdoor spots (IP54)

KEY SPECS

Voltage	**8 – 14 VDC, 200 mA @ 12 V**
RFID range	**15 – 50 mm**
Size / weight	**97 × 45 × 21 mm · 61.5 g**
Operating temp	**−25 to +60 °C**

FAMILY — PICK THE RIGHT ONE

HRW910	**MDR-SE Wiegand**
HRW911	**MDR-SE OSDP**

COUNTER QUICK ANSWERS

Phone as a card? Yes — BLE/NFC mobile credentials.

Software? Access Portal 4.4+ (and Primo).

Long cable? OSDP variant runs up to 1000 m.