Suprema FaceStation 2

Face recognition terminal · 4" touch · live-face anti-spoof

STOCK CODE

74FS2-D

Fast, accurate face recognition in any lighting — from complete darkness to 25,000 lux.



3,000	0–25k lx	4"	SIP
face users (1:N)	lighting	touch LCD	video phone

WHY CUSTOMERS CHOOSE IT

- **Live face detection** — IR, blocks photos/screens
- **3,000 matches/second**
- Reads EM, MIFARE, DESFire, FeliCa, NFC
- Tilt bracket for wheelchair users
- SIP video intercom

BEST FOR

- ✔ Touchless entry for offices and labs
- ✔ Time attendance at busy entrances
- ✔ Bright or dark lobbies

NOT FOR

- ✖ Outdoor exposed mounting
- ✖ HID iClass / BLE needs (choose FS2-AWB)

KEY SPECS

Users	**30,000 (1:1) · 3,000 (1:N)**
Logs	**5 M text · 50,000 images**
Network	**Gigabit Ethernet, RS-485, Wiegand**
Power	**12 VDC 2.5 A**
Size / weight	**141 × 164 × 125 mm · 548 g**
Operating temp	**−20 to +50 °C**

FAMILY — PICK THE RIGHT ONE

FS2-D	**Standard RF — this unit**
FS2-AWB	**Adds HID Prox/iClass, BLE, WiFi**

COUNTER QUICK ANSWERS

Works in the dark? Yes — 0 to 25,000 lux.

Photo spoofing? Live-face detection blocks it.

WiFi? Only on FS2-AWB.

Source: Suprema FaceStation 2 datasheet.