Kantech KT-1 One-Door Controller (single-gang)

Ethernet-ready 1-door controller · PoE or 12 V · standalone, EntraPass or Cloudvue

STOCK CODE

39KT-1

One-door IP controller that runs standalone from a web browser — or grows into EntraPass.



1 door
2 readers

2,000
cardholders (standalone)

PoE
or 12 V

AES
128-bit

WHY CUSTOMERS CHOOSE IT

- **3 modes** — standalone web, EntraPass, Cloudvue
- One-touch enrolment into EntraPass v6.02+
- Head controller for up to 31 more in EntraPass
- Encrypted with ioSmart readers & cards

BEST FOR

- ✔ Single doors in offices and shops
- ✔ Starting small and growing into EntraPass
- ✔ Sites with PoE switches

NOT FOR

- ✖ DSC alarm integration (needs KT-1-PCB)
- ✖ Many doors on one controller

KEY SPECS

Standalone users	**2,000 · 60,000 events**
I/O	**4 inputs · 4 aux outputs**
Power	**PoE, PoE+ or 12 VDC**
Mounting	**Single-gang (KT-1) or cabinet (KT-1-PCB)**

FAMILY — PICK THE RIGHT ONE

KT-1	**Single-gang mount — this unit**
KT-1-PCB	**Cabinet board, DSC integration**
KT-1-EU-MET-POE	**Metal housing, PoE**

COUNTER QUICK ANSWERS

Software needed? No — standalone via web browser.

Power? PoE or 12 V.

Readers? 2 (in and out); ioSmart for end-to-end encryption.

Source: Kantech KT-1 data sheet.