DSC TL2803G IP + 3G Dual-Path Communicator

PowerSeries Neo Internet + HSPA (3G) alarm communicator

STOCK CODE

22TL2803G

Dual-path communicator for Neo panels — reports over Internet and 3G cellular.

⚠ This is an HSPA (3G) cellular communicator. Confirm local 3G network availability before selling — the TL280LE (LTE) may be the better choice.



IP + 3G dual path

AES 128-bit

SIM included

Neo HS2016–2128

WHY CUSTOMERS CHOOSE IT

- **Fully redundant** Internet + cellular
- Remote programming via DLS
- Visual verification support
- PC-Link connection to panel

BEST FOR

- ✔ Monitored Neo systems
- ✔ Sites with no phone line

NOT FOR

- ✖ Areas where 3G is switched off (use TL280LE)

KEY SPECS

Panels	**HS2016 / HS2032 / HS2064 / HS2128**
Antenna	**GS-50ANTQ extension available**

FAMILY — PICK THE RIGHT ONE

TL280E	**Internet only**
TL2803G	**Internet + 3G — this unit**
TL280LE	**Internet + LTE**

COUNTER QUICK ANSWERS

3G still OK? Check local network — LTE model may be safer.

SIM? Included (needs active account).

Phone line? Not needed.