
Kantech KT-MOD-OUT16 16-Output Module

16 low-current outputs for KT-400 · elevator control

STOCK CODE

39KT-MOD-OUT16

Adds 16 low-current outputs to a KT-400 — for lifts or driving external relays.



No product photo in the datasheet

16	16	256	750 mA
outputs	modules / KT-400	outputs max	per module

WHY CUSTOMERS CHOOSE IT

- 16 open-collector outputs, 5–24 VDC, 4–750 mA
- Daisy-chain up to 16 modules
- Mix with KT-MOD-REL8 in one SPI group
- SPI cable included

BEST FOR

- ✔ Elevator floor control
- ✔ Driving external relays
- ✔ Large KT-400 installs

NOT FOR

- ✖ Switching loads directly (low-current outputs)
- ✖ KT-1

KEY SPECS

Current	**Up to 750 mA per module**
Mounting	**Kantech cabinet, within 1 m of KT-400**
Connection	**6-pin SPI**

FAMILY — PICK THE RIGHT ONE

KT-MOD-REL8	**8 relays**
KT-MOD-OUT16	**16 outputs — this unit**
KT-MOD-INP16	**16 inputs**

COUNTER QUICK ANSWERS

External power? Yes, 12 V 2 A if SPI load exceeds 500 mA.

Relays? No — low-current outputs; use REL8 for relays.

Lifts? Yes, elevator control.