# Optex HX-80N High-Mount PIR

24 m long & narrow outdoor PIR · mounts 2.5–3 m high

STOCK CODE

**07HX80N**

**High-mount outdoor curtain PIR that's out of reach of tampering — 24 m long, with adjustable range.**



| 24 × 2 m | 2.5–3 m | IP55 | 12 V |
|---|---|---|---|
| narrow coverage | mount height | weatherproof | 9.5–18 VDC |

## WHY CUSTOMERS CHOOSE IT

- **Range limit** — 6.5, 10, 13 or 18 m to stop short of roads
- **Bracket** ±20° vertical, ±95° horizontal
- Double conductive shielding · temperature compensation
- Masking plates & flaps to fine-tune coverage
- Aux input for a second device

## BEST FOR

- ✔ Long walls, fence lines and driveways
- ✔ High mounting out of reach of vandals
- ✔ Commercial sites, storage yards, homes
- ✔ Sloping ground (adjustable bracket)

## NOT FOR

- ✖ Wide open areas — coverage is only 2 m wide
- ✖ Battery installs — sell the HX-80NRAM
- ✖ Areas where it can't see along the full 24 m

## COVERAGE

| | |
|---|---|
| Area | **24 m × 2 m · 20 zones** |
| Range limit | **6.5 / 10 / 13 / 18 m** |
| Mount height | **2.5 – 3.0 m** |
| Walk speed | **0.3 – 1.5 m/s** |

## KEY SPECS

| | |
|---|---|
| Power | **9.5 – 18 VDC · 35 mA max** |
| Alarm output | **Form C, 28 VDC 0.2 A** |
| Tamper | **N.C., 28 VDC 0.1 A** |
| Operating temp | **−20 to +60 °C · 95% RH** |
| Weight | **720 g with bracket** |

## FAMILY — PICK THE RIGHT ONE

| | |
|---|---|
| **HX-80N** | **Standard 2-PIR model — this unit** |
| **HX-80NAM** | **Adds anti-masking + trouble output** |
| **HX-80NRAM** | **Battery operated, anti-masking** |

## COUNTER QUICK ANSWERS

**Why high mount?** Harder to reach or tamper with, and sees over low obstacles.

**Can I stop it at the boundary?** Yes — set the range limit (6.5–18 m).

**Anti-masking?** Not this model — sell the HX-80NAM.