C-TEC CAST Multi-Sensor Detector

Programmable smoke + heat addressable detector — CAST

STOCK CODE

29CA414

Smoke and heat in one detector — fewer false alarms, and the mode can be changed from the panel.



Smoke+Heat multi-sensor

5 sensitivity modes

EN54-5/7 LPCB

Built-in loop isolator

WHY CUSTOMERS CHOOSE IT

- **Smoke + heat combined** for faster, more reliable response
- **Programmable** — 5 modes, different by day/night
- Smart algorithms & drift compensation
- Built-in short-circuit isolator · 360° LEDs

BEST FOR

- ✔ Areas where smoke-only causes false alarms
- ✔ Mixed-use areas, day/night sensitivity changes
- ✔ C-TEC XFP / ZFP CAST systems
- ✔ Hotels, offices, schools

NOT FOR

- ✖ Very steamy/dusty areas — consider a heat-only CA402
- ✖ Conventional or other-brand panels
- ✖ Outdoor use (IP42)

KEY SPECS

Supply	**27 – 40 VDC, 2-wire**
Current	**370 µA quiet · 5 mA alarm**
Approvals	**LPCB EN54-5, 7 & 17, CEA 4021**
Size	**102.2 Ø × 57.5 mm in base**
Operating temp	**−20 to +85 °C · IP42**

FAMILY — PICK THE RIGHT ONE

CA414	**Multi-sensor — this unit**
CA416	**Optical smoke only**
CA402	**Heat only**
CA408	**CAST base — required**

COUNTER QUICK ANSWERS

Base included? No — order the CA408 base.

Kitchen? Steamy kitchens are better served by a heat-only CA402.

Which panels? C-TEC XFP / ZFP CAST panels.

Source: C-TEC CAST CA414 datasheet.

Internal counter reference